



Automatic Power Control

This chapter describes the Automatic Power Control optical application for Cisco NCS 1010.

Table 1: Feature History

Feature Name	Release Information	Feature Description
APC enhancements	Cisco IOS XR Release 7.9.1	APC (Automatic Power Control) on NCS 1010 now supports C+L band networks in addition to C band only networks. Also, APC is enhanced to perform power correction even when it doesn't have end-to-end network visibility. This ensures that the operational section of the network always has power at the target PSD profile, and when the network comes up, the traffic restoration is faster.

- [Overview of Automatic Power Control, on page 1](#)

Overview of Automatic Power Control

On a fiber, the power level may vary between channels. Over long distances and multiple amplifications, these differences in power levels can result in deterioration of the quality of some channels. Automatic Power Control (APC) corrects the power level differences and ensures that power for different channels is according to the target power profile for the spectrum. APC compensates for the degradation of the network over time. APC is enabled if automatic link bring up is enabled.

APC is a network-level feature that is distributed among different nodes. An APC domain is a set of nodes that is controlled by the same instance of APC at the network level. An APC domain identifies a portion of the network that can be independently regulated. The source OLT node acts as the APC Manager or Domain Manager for all the nodes in the path. The subsequent nodes in the path act as APC agent nodes. The manager node enables APC on agent nodes, monitors DISCREPANCY and initiates regulation if correction is required. To avoid large power fluctuations, APC adjusts power levels incrementally. APC performs power correction in steps of +/-0.8dB. This is applied to each iteration until the optimal power level is reached.

APC is direction-specific. You can enable APC for each direction at the transmitting OLT node. The source node enables and controls different parameters in all ILA nodes on the path and the far-end OLT ingress EDFA.

The following table lists the parameters that APC configures and controls in different nodes.

Node	Parameters
Transmitting OLT	EDFA Gain EDFA Tilt VOA Attenuation WSS Attenuation
ILA	EDFA Gain EDFA Tilt VOA Attenuation DGE Attenuation
Receiving OLT	EDFA Gain EDFA Tilt WSS Attenuation

When you enable APC, APC controls these parameters. APC overrides any manual configuration. When you disable APC, user configuration is applied.

APC divides the C band spectrum into 32 equal parts. APC uses 33 frequencies across the C band to divide the band. We call these 33 frequencies, **setpoints**. Each setpoint is 150 GHz apart from the adjacent setpoints. You can configure a power profile across the spectrum using these setpoints. You can configure the target PSD for each OLT and ILA node on a link.

APC applies amplification and attenuation as required at channel level and composite signal level to ensure that the channels are at the target power level. You can configure the target power spectral densities for 33 points across the band. If you enable link tuner, link tuner sets the target PSDs for APC on all nodes in the path.

APC performs the following functions:

- APC monitors the current PSD against the target PSD for each channel (ASE and user channel) and changes the amplifier parameters including VOA, WSS, and DGE to achieve the target PSD.
- APC detects optical network changes on the path and alters the amplifier parameters on the nearest nodes to compensate for the changes. APC performs these alterations in multiple steps.
- APC collects measurements from other link nodes at the transmitting OLT to precisely locate optical network changes.



Note

- If the input slice power of a channel is below psd-min and APC is unable to bring the channel above psd-min even after setting the WSS attenuation to 0dB, APC declares the channel as failed.
- After APC regulation, all channel powers must be above psd-min (-24-dBm default) and at least one channel should be within 0.5 dB of psd-min.

View APC Status and Information

Use the **show olc apc** command to view APC status.

The following sample is an output of **show olc apc**.

```
RP/0/RP0/CPU0:OLT1#show olc apc

Controller      : Ots0/0/0/0
APC Status      : WORKING

Node RID        : 10.1.1.1
Internal State  : IDLE

Node RID        : 10.99.1.2
Internal State  : IDLE

Node RID        : 10.99.2.2
Internal State  : IDLE

Node RID        : 10.99.4.1
Internal State  : IDLE

Node RID        : 10.1.1.5
Internal State  : DISCREPANCY
```

APC Status is the status of APC in the complete path. The following table lists and describes the APC Statuses.

APC Status	Description
BLOCKED	APC moves to BLOCKED state if: <ul style="list-style-type: none"> there is an event in the network which resulted in topology failure an amplifier safety event like APR or OSRI has been triggered in the network APC is locally disabled on agent node
PAUSED	APC is paused using the apc-pause command.
IDLE	APC regulation has been completed successfully. All the channels in the network have achieved the target PSD provided by Link-tuner or configured by user
WORKING	APC detected a DISCREPANCY between current and target PSD. APC regulation is in progress to converge the power to target PSD.
DISABLED	APC is disabled.

Internal State is the state of APC on each individual node. The following table lists and describes the internal states.

APC Internal State	Description
--------------------	-------------

DISCREPANCY	The APC manager flags an agent node which needs correction when there is a discrepancy between target PSD and current PSD. This state is temporary and lasts until APC starts power correction and goes into CORRECTING state.
CORRECTING	APC correction is in progress on the node
OOR	APC-OUT-OF-RANGE condition is raised on an agent node when APC fails to regulate and achieve the target PSD power level because the requested gain or attenuation setpoint cannot be set due to one of the following conditions: <ul style="list-style-type: none"> • Amplifier gain is exhausted in the current gain range. • WSS range (0-25dB) is exhausted for a single or multiple channels. • DGE range (0-3dB) is exhausted for a single or multiple channels. • Spanloss increased and amplifier gain is insufficient to achieve target PSD
IDLE	APC regulation has been completed successfully. All the channels in the network have achieved the target PSD provided by Link-tuner or configured by user
BLOCKED	APC is unable to perform for the following reasons: <ul style="list-style-type: none"> • OSRI has shut down the amplifier: AMPLI-SHUT • APC is disabled locally on the node: USER-DISABLED • Gain Estimation is in progress: GAIN-ESTIMATION-IN-PROGRESS • Amplifier auto power reduction is enabled: AMPLI-APR-ENABLED • Amplifier is shut because of loss of input power: AMPLI-SHUT • An event in the network resulted in topology failure.

The following sample is an output of **show olc apc** command when OSRI has shut down an amplifier in the link.

```
RP/0/RP0/CPU0:ios#sh olc apc
Thu Jul  7 13:21:05.807 UTC

Controller      : Ots0/0/0/0
```

```

APC Status      : BLOCKED

Node RID       : 10.1.1.1
Internal State : IDLE

Node RID       : 10.1.1.2
Internal State : BLOCKED
Blocked Reason : [ AMPLI-SHUT ]

Node RID       : 10.1.1.3
Internal State : DISCREPANCY

Node RID       : 10.1.1.4
Internal State : DISCREPANCY

Node RID       : 10.1.1.5
Internal State : DISCREPANCY

```

The following sample is an output of **show olc apc** command when APC is disabled locally on a node.

```

RP/0/RP0/CPU0:ios#sh olc apc
Thu Jul  7 13:22:44.145 UTC

Controller      : Ots0/0/0/0
APC Status      : BLOCKED

Node RID       : 10.1.1.1
Internal State : IDLE

Node RID       : 10.1.1.2
Internal State : BLOCKED
Blocked Reason : [ USER-DISABLED ]

Node RID       : 10.1.1.3
Internal State : DISCREPANCY

Node RID       : 10.1.1.4
Internal State : DISCREPANCY

Node RID       : 10.1.1.5
Internal State : DISCREPANCY

```

The following sample is an output of **show olc apc** command when Gain Estimation is in progress on a node.

```

RP/0/RP0/CPU0:ios#sh olc apc
Tue Jun 7 11:43:10.801 UTC

Controller : Ots0/0/0/0
APC Status : BLOCKED

Node RID : 10.1.1.1
Internal State : DISCREPANCY

Node RID : 10.1.1.2
Internal State : DISCREPANCY

Node RID : 10.1.1.3
Internal State : BLOCKED
Blocked Reason : [ GAIN-ESTIMATION-IN-PROGRESS ]

```

The following sample is an output of **show olc apc** command when amplifier auto power reduction is enabled on a node.

```

RP/0/RP0/CPU0:ios#sh olc apc
Thu Jul  7 13:21:49.530 UTC

```

Overview of Automatic Power Control

```

Controller      : Ots0/0/0/0
APC Status     : BLOCKED

Node RID       : 10.1.1.1
Internal State : IDLE

Node RID       : 10.1.1.2
Internal State : BLOCKED
Blocked Reason : [ AMPLI-APR-ENABLED ]

Node RID       : 10.1.1.3
Internal State : DISCREPANCY

Node RID       : 10.1.1.4
Internal State : DISCREPANCY

Node RID       : 10.1.1.5
Internal State : DISCREPANCY

```

You can view the local status of APC on each node using the **show olc apc-local** command. This command shows if APC is enabled or disabled on the node.

The following sample is an output of **show olc apc-local** command.

```

RP/0/RP0/CPU0:ios#show olc apc-local
Mon Apr 11 06:59:14.679 UTC

Controller : Ots0/0/0/0

TX Status : ENABLED
RX Status : ENABLED

```

You can view the target PSDs configured for all setpoints using the **show olc apc-local target-psd-profile** command. The output shows the source of the PSD configuration also. The target PSD source can be Link Tuner or Configuration.

The following sample is an output of **show olc apc-local target-psd-profile** command on a C band node..

```

RP/0/RP0/CPU0:ios#show olc apc-local target-psd-profile
Tue Apr 26 10:19:24.910 UTC
Controller      : Ots0/0/0/0
Target PSD source : Configuration
-----
Setpoint          Frequency           Target PSD
                           (THz)                (dBm/12.5 GHz)
-----
01               191.337494        15.0
02               191.488678        15.0
03               191.639847       -4.1
04               191.791016       -4.1
05               191.942184       -4.1
06               192.093353       -4.1
07               192.244537       -4.1
08               192.395706       -4.1
09               192.546875       -4.1
10               192.698044       -4.1
11               192.849213       -4.1
12               193.000397       -4.1
13               193.151566       -4.1
14               193.302734       -4.1
15               193.453903       -4.1
16               193.605072       -4.1
17               193.756256       -4.1
18               193.907425       -4.1

```

19	194.058594	-4.1
20	194.209763	-4.1
21	194.360931	-4.1
22	194.512115	-4.1
23	194.663284	-4.1
24	194.814453	-4.1
25	194.965622	-4.1
26	195.116791	-4.1
27	195.267975	-4.1
28	195.419144	-4.1
29	195.570312	-4.1
30	195.721481	-4.1
31	195.872650	-4.1
32	196.023834	-4.1
33	196.175003	-4.1

The following sample is an output of **show olc apc-local target-psd-profile** command on an L band node.

```
RP/0/RP0/CPU0:ios#sh olc apc-local target-psd-profile
Wed Jan 18 12:12:02.236 UTC
Controller      : Ots0/0/0/0
Target PSD source : Configuration
-----
Setpoint          Frequency           Target PSD
                  (THz)                (dBm/12.5 GHz)
-----
01               186.050000        -6.4
02               186.201000        -6.3
03               186.352000        -6.2
04               186.503000        -6.2
05               186.654000        -6.1
06               186.805000        -6.1
07               186.956000        -6.0
08               187.107000        -6.0
09               187.258000        -5.9
10               187.409000        -5.9
11               187.560000        -5.9
12               187.711000        -5.8
13               187.862000        -5.7
14               188.013000        -5.7
15               188.164000        -5.6
16               188.315000        -5.5
17               188.466000        -5.5
18               188.617000        -5.4
19               188.768000        -5.4
20               188.919000        -5.3
21               189.070000        -5.2
22               189.221000        -5.2
23               189.372000        -5.1
24               189.523000        -5.1
25               189.674000        -5.0
26               189.825000        -5.0
27               189.976000        -4.9
28               190.127000        -4.9
29               190.278000        -4.8
30               190.429000        -4.7
31               190.580000        -4.7
32               190.731000        -4.6
33               190.882000        -4.6
```

You can view the detailed information about APC on each node using the **show olc apc-local regulation-info** command. This command provides the following information:

- Controller

Overview of Automatic Power Control

- APC Domain Manager
- Internal Status
- Minimum PSD
- Last correction timestamp
- Gain range
- Amplifier and attenuation parameters: Configured and current values and available ranges
- Detailed information on the channels

The following details are available:

- Center frequency of each channel
- Channel width
- Channel ID
- Channel Source (ASE or user channel)
- Slice number of the center frequency of the channel in the WSS
- PSD of the channel at the input of the amplifier
- Target PSD for the channel
- Current PSD of the channel
- Discrepancy between current and target PSD
- The configured attenuation on the WSS (OLT) or DGE (ILA) for the channel

You can view the APC information for only the Tx or Rx direction using the **tx|rx** keyword with the **show olc apc-local regulation-info controller ots R/S/I/P** command.

The following sample is an output of **show olc apc-local regulation-info** command.

```
RP/0/RP0/CPU0:ios#show olc apc-local regulation-info controller ots 0/0/0/0 tx
Wed Jul  6 05:01:45.177 UTC
Controller          : Ots0/0/0/0
Domain Manager     : 10.1.1.1
Internal Status    : OOR
Direction          : TX
PSD Minimum       : -24.0 (dBm/12.5 GHz)
Gain Range         : Normal
Last Correction    : 2022-07-06 05:01:28

Device Parameters           Min   Max Configuration Operational
=====
Egress Ampli Gain (dB)      :15.4  29.4 19.5          19.5
Egress Ampli Tilt (dB)       :-5.0  3.1  -2.2        -2.2
TX Ampli Power (dBm)        : -    22.4  -          21.4
TX VOA Attenuation (dB)      :0.0   20.0  0.0          0.0
Egress WSS/DGE Attenuation (dB):0.0   25.0  -          -

Channel Center Channel Channel Spectrum Ampli-Input      Target      Current
Discrepancy Channel Slice
Frequency   Width    ID     Source  Slice Num      PSD        PSD

```

(THz) (dB)	(GHz) (dB)	Attn Config			(dBm/12.5 GHz) (dBm/12.5 GHz) (dBm/12.5 GHz)		
191.375000 0.2	75.00 7.1	1	OCh	13	-23.2	-4.6	-4.9
191.449997 0.1	75.00 9.2	-	ASE	37	-23.0	-4.6	-4.7
191.524994 0.1	75.00 9.3	-	ASE	61	-23.1	-4.6	-4.7
191.600006 0.1	75.00 8.0	4	OCh	85	-23.1	-4.5	-4.7
191.675003 0.0	75.00 9.1	-	ASE	109	-23.0	-4.5	-4.5
191.750000 0.1	75.00 8.0	6	OCh	133	-23.0	-4.4	-4.6
191.824997 0.1	75.00 9.3	-	ASE	157	-23.1	-4.4	-4.6
191.899994 0.0	75.00 8.0	8	OCh	181	-23.0	-4.4	-4.4
191.975006 0.1	75.00 9.1	-	ASE	205	-23.0	-4.3	-4.5
192.050003 0.1	75.00 8.2	10	OCh	229	-23.0	-4.3	-4.5
192.125000 0.0	75.00 9.0	-	ASE	253	-22.9	-4.3	-4.3
192.199997 0.0	75.00 8.3	12	OCh	277	-22.8	-4.2	-4.3
192.274994 0.1	75.00 9.0	-	ASE	301	-22.9	-4.2	-4.4
192.350006 0.0	75.00 8.3	14	OCh	325	-22.6	-4.2	-4.2
192.425003 0.1	75.00 8.7	-	ASE	349	-22.8	-4.2	-4.3
192.500000 -0.2	75.00 8.1	16	OCh	373	-22.4	-4.1	-3.9
192.574997 0.1	75.00 8.6	-	ASE	397	-22.7	-4.1	-4.2
192.649994 0.1	75.00 8.1	18	OCh	421	-22.6	-4.1	-4.2
192.725006 0.1	75.00 8.6	-	ASE	445	-22.7	-4.0	-4.2
192.800003 0.1	75.00 7.9	20	OCh	469	-22.7	-4.0	-4.1
192.875000 0.0	75.00 8.4	-	ASE	493	-22.6	-4.0	-4.0
192.949997 0.1	75.00 7.6	22	OCh	517	-22.6	-3.9	-4.1
193.024994 0.1	75.00 8.2	-	ASE	541	-22.5	-3.9	-4.0
193.100006 0.1	75.00 7.5	24	OCh	565	-22.7	-3.8	-4.0
193.175003 0.1	75.00 8.2	-	ASE	589	-22.7	-3.8	-4.0
193.250000 0.1	75.00 7.2	26	OCh	613	-22.5	-3.8	-3.9
193.324997 0.2	75.00 8.1	-	ASE	637	-22.6	-3.8	-4.0
193.399994 0.1	75.00 7.2	28	OCh	661	-22.7	-3.7	-3.9
193.475006 0.1	75.00 8.0	-	ASE	685	-22.5	-3.7	-3.8
193.550003	75.00	30	OCh	709	-22.7	-3.7	-3.8

Overview of Automatic Power Control

0.1	7.0							
193.625000	75.00	-	ASE	733	-22.7	-3.6	-3.8	
0.1	8.1							
193.699997	75.00	32	OCh	757	-22.7	-3.6	-3.7	
0.1	6.7							
193.774994	75.00	-	ASE	781	-22.7	-3.5	-3.7	
0.1	8.2							
193.850006	75.00	34	OCh	805	-22.7	-3.5	-3.7	
0.1	6.6							
193.925003	75.00	-	ASE	829	-22.7	-3.5	-3.6	
0.1	8.1							
194.000000	75.00	36	OCh	853	-22.8	-3.5	-3.7	
0.2	6.6							
194.074997	75.00	-	ASE	877	-22.8	-3.4	-3.6	
0.1	8.3							
194.149994	75.00	38	OCh	901	-22.7	-3.4	-3.5	
0.1	10.9							
194.225006	75.00	-	ASE	925	-22.8	-3.3	-3.5	
0.1	8.2							
194.300003	75.00	40	OCh	949	-22.9	-3.3	-3.5	
0.1	7.1							
194.375000	75.00	-	ASE	973	-22.8	-3.3	-3.4	
0.1	8.4							
194.449997	75.00	42	OCh	997	-22.9	-3.2	-3.5	
0.2	7.3							
194.524994	75.00	-	ASE	1021	-22.9	-3.2	-3.4	
0.1	8.4							
194.600006	75.00	44	OCh	1045	-22.8	-3.2	-3.3	
0.1	7.2							
194.675003	75.00	-	ASE	1069	-22.8	-3.2	-3.3	
0.1	8.4							
194.750000	75.00	46	OCh	1093	-22.9	-3.1	-3.4	
0.2	7.3							
194.824997	75.00	-	ASE	1117	-22.8	-3.1	-3.2	
0.1	8.2							
194.899994	75.00	48	OCh	1141	-22.8	-3.0	-3.3	
0.2	6.9							
194.975006	75.00	-	ASE	1165	-22.9	-3.0	-3.2	
0.1	8.3							
195.050003	75.00	50	OCh	1189	-22.8	-3.0	-3.1	
0.1	6.6							
195.125000	75.00	-	ASE	1213	-22.9	-3.0	-3.1	
0.1	8.3							
195.199997	75.00	52	OCh	1237	-22.9	-2.9	-3.1	
0.1	6.3							
195.274994	75.00	-	ASE	1261	-23.0	-2.9	-3.0	
0.1	8.1							
195.350006	75.00	54	OCh	1285	-23.1	-2.8	-3.0	
0.1	6.4							
195.425003	75.00	-	ASE	1309	-23.2	-2.8	-3.0	
0.1	8.3							
195.500000	75.00	56	OCh	1333	-23.1	-2.8	-2.9	
0.1	6.2							
195.574997	75.00	-	ASE	1357	-23.4	-2.8	-3.0	
0.2	8.2							
195.649994	75.00	58	OCh	1381	-23.4	-2.7	-2.9	
0.1	6.4							
195.725006	75.00	-	ASE	1405	-23.4	-2.7	-2.8	
0.1	8.5							
195.800003	75.00	60	OCh	1429	-23.6	-2.7	-2.8	
0.1	6.6							
195.875000	75.00	-	ASE	1453	-23.7	-2.6	-2.9	
0.2	8.7							
195.949997	75.00	62	OCh	1477	-23.7	-2.6	-2.8	

0.2	6.9							
196.024994	75.00	-	ASE	1501	-23.6	-2.5	-2.7	
0.1	9.0							
196.100006	75.00	64	OCh	1525	-23.7	-2.5	-2.7	
0.1	7.1							

ASE - Noise Loaded Channel
OCh - Optical Channel



Note

- In the previous sample output, the channel source is ASE for channels that are empty and for channels that failed due to power level dropping below psd-min. For dropped channels, channel ID is present and the channel source is ASE. ASE or Noise loader fills noise across the spectrum with a spacing of 75 GHz for wherever optical cross connects are not present.

Configure APC

If you enable link tuner, the link tuner sets the target PSDs for APC on all nodes in the path.

You can configure the target power spectral densities for 33 points across the band. The 33 PSD values divide the entire spectrum into 150-GHz steps. APC uses the corresponding PSD value if the channel frequency corresponds to a configured point. If the central frequency is not on a configured position, APC computes the target PSD for a channel by extrapolating from the two adjacent steps.

Use the following commands to set the target PSDs for single-band for each node on a C-band network.

configure

optical-line-control

controller ots *Rack/Slot/Instance/Port*

psd <1-33> *value*

commit

end

The following is a sample configuration that sets the psd to 15 dBm/12.5 GHz for the setpoints 1 and 2.

```
RP/0/RP0/CPU0:ios#configure
RP/0/RP0/CPU0:ios(config)#optical-line-control
RP/0/RP0/CPU0:ios(config-olc)#controller ots 0/0/0/0
RP/0/RP0/CPU0:ios(config-olc-ots)#psd 1 150
RP/0/RP0/CPU0:ios(config-olc-ots)#psd 2 150
RP/0/RP0/CPU0:ios(config-olc-ots)#commit
RP/0/RP0/CPU0:ios(config-olc-ots)#end
```

Disable APC

To disable APC for a link, execute the following commands on the transmitting OLT node.

configure

optical-line-control

Configure APC

controller ots *Rack/Slot/Instance/Port*

apc disable

commit

end

The following is a sample configuration that disables APC.

```
RP/0/RP0/CPU0:ios#configure
RP/0/RP0/CPU0:ios(config)#optical-line-control
RP/0/RP0/CPU0:ios(config-olc)#controller ots 0/0/0/0
RP/0/RP0/CPU0:ios(config-olc-ots)#apc disable
RP/0/RP0/CPU0:ios(config-olc-ots)#commit
RP/0/RP0/CPU0:ios(config-olc-ots)#end
```

**Important**

- When you disable APC, NCS 1010 sets all setpoints to values in the configuration. If there is no configuration, NCS 1010 sets all setpoints to default values. Disabling APC is traffic impacting.
- For BFR to work, APC must be enabled on both C and L-band devices. We recommended to pause BFR before running the **apc-pause** or **apc disable** commands.

Enable APC

To enable APC for a link, execute the following commands on the transmitting OLT node.

configure

optical-line-control

controller ots *Rack/Slot/Instance/Port*

apc enable

commit

end

The following is a sample configuration that enables APC.

```
RP/0/RP0/CPU0:ios#configure
RP/0/RP0/CPU0:ios(config)#optical-line-control
RP/0/RP0/CPU0:ios(config-olc)#controller ots 0/0/0/0
RP/0/RP0/CPU0:ios(config-olc-ots)#apc enable
RP/0/RP0/CPU0:ios(config-olc-ots)#commit
RP/0/RP0/CPU0:ios(config-olc-ots)#end
```

Pause APC

If you want to modify the network without APC compensating for the changes, you can pause APC. Use the following commands to pause APC.

configure

optical-line-control

controller ots *Rack/Slot/Instance/Port*

apc-pause

commit

end

The following is a sample configuration that pauses APC.

```
RP/0/RP0/CPU0:ios#configure
RP/0/RP0/CPU0:ios(config)#optical-line-control
RP/0/RP0/CPU0:ios(config-olc)#controller ots 0/0/0/0
RP/0/RP0/CPU0:ios(config-olc-ots)#apc pause
RP/0/RP0/CPU0:ios(config-olc-ots)#commit
RP/0/RP0/CPU0:ios(config-olc-ots)#end
```



Note

- If you run the **apc-pause** command when APC is in idle state, APC remains in the idle state until APC detects changes in the network that requires power correction. APC changes the status to paused after it detects changes, but does not perform power correction.
- Running the **apc-pause** command, does not pause channel startup.

Disable APC on an ILA Node

If you want to manually disable APC on a particular node. For example, consider a scenario where the headend OLT encounters a headless event. For any power correction required at agent nodes, APC manager is unavailable to initiate regulation. Also, you cannot perform any adjustments as APC is enabled and user-configuration of target-psd does not take effect. This command gives you an option to disable APC locally on an agent node to perform the parameter adjustments manually. Use the **apc-local disable** command to disable APC on an agent node.

Use the following commands to disable APC on an ILA node.

configure

optical-line-control

controller ots Rack/Slot/Instance/Port

apc-local [RX | TX] disable

commit

end

The following is a sample configuration that disables APC locally.

```
RP/0/RP0/CPU0:ios#configure
RP/0/RP0/CPU0:ios(config)#optical-line-control
RP/0/RP0/CPU0:ios(config-olc)#controller ots 0/0/0/0
RP/0/RP0/CPU0:ios(config-olc-ots)#apc-local RX disable
RP/0/RP0/CPU0:ios(config-olc-ots)#commit
RP/0/RP0/CPU0:ios(config-olc-ots)#end
```

Configure Target Drop PSD

Link Tuner does not set the target PSD for drop ports. The default target PSD for drop ports is -8.0 dBm/12.5 GHz. The NCS 1010 applies drop PSD configuration for channels with cross connect configurations. Use the **drop-psd** command to set the desired drop-psd.

Use the following commands to set the desired drop-psd.

```
configure
optical-line-control
controller ots Rack/Slot/Instance/Port
drop-psd value
commit
end
```

The following is a sample configuration that sets the target PSD at drop ports to -25 dBm/12.5 GHz.

```
RP/0/RP0/CPU0:ios#configure
RP/0/RP0/CPU0:ios(config)#optical-line-control
RP/0/RP0/CPU0:ios(config-olc)#controller ots 0/0/0/0
RP/0/RP0/CPU0:ios(config-olc-ots)#drop-psd -250
RP/0/RP0/CPU0:ios(config-olc-ots)#commit
Tue Apr 26 09:50:12.055 UTC
RP/0/RP0/CPU0:ios(config-olc-ots)#end
```

Configure Minimum PSD

If the PSD of a channel with minimum attenuation at the amplifier input on an OLT is less than the minimum PSD, APC marks the channel as failed and replaces the channel using ASE source. The default minimum PSD is -24 dBm/12.5 GHz. Use the **psd-min** command to set the desired minimum PSD.

Use the following commands to set the desired minimum PSD.

```
configure
optical-line-control
controller ots Rack/Slot/Instance/Port
psd-min value
commit
end
```

The following is a sample configuration that sets the minimum PSD to -25 dBm/12.5 GHz.

```
RP/0/RP0/CPU0:ios#configure
RP/0/RP0/CPU0:ios(config)#optical-line-control
RP/0/RP0/CPU0:ios(config-olc)#controller ots 0/0/0/0
RP/0/RP0/CPU0:ios(config-olc-ots)#psd-min -250
RP/0/RP0/CPU0:ios(config-olc-ots)#commit
Tue Apr 26 09:50:12.055 UTC
RP/0/RP0/CPU0:ios(config-olc-ots)#end
```