



Sample End-to-end Configuration

This appendix describes an end-to-end provisioning example for a Routed Optical Networking topology.

- [Sample Configuration, on page 1](#)

Sample Configuration

This section details the step-by-step approach to build a new Routed Optical Networking based, 75 km fiber span to replace an existing legacy span in a two-node DCI topology.

- [Network Sizing Requirements, on page 1](#)
- [Planning and Design Phase, on page 4](#)
- [Implement Phase, on page 5](#)
- [Operate Phase, on page 70](#)
- [Optimization Phase, on page 82](#)

Network Sizing Requirements

This section details the sizing requirements for a network. For a small lab installation, three servers with 256 GB of RAM is enough to run the Crosswork, Crosswork Network Controller, Cisco Optical Network Controller, NSO, Crosswork Hierarchical Controller, and EPNM in a non-HA deployment. For a production setup, calculate the total resources required using information in the following tables.

Network Profiles

Network profiles are defined based on network size, services, and application features.

Network Entity/Feature	Lab (20%)	Production (100%)
Devices	2000	10000
Total number of interfaces	100000	650000
IGP interfaces	20000	100000

Network Entity/Feature	Lab (20%)	Production (100%)
VPN Services (L2, L3)	40000	200000
Endpoints per VPN service	2 to 10	50
Total LSPs (SR policies and RSVP tunnels)	12000	60000
Number of PCEP sessions	2000	10000



Note Each SR-PCE pair can only support 2000 PCEP sessions which means only 2000 headends for lab networks and 10000 headends for production networks. While counting headends, LCM nodes must be included.

Deployment Size per Network Profile

The following table is the recommended deployment sizing requirement for solution using Cisco Crosswork Network Controller.

Package	Contents	Crosswork Data Gateway Deployment	Recommended number of cluster VMs
Cisco Crosswork Network Controller Essentials	Cisco Crosswork Optimization Engine	On-Premise Standard (default): Collectors only.	When Essentials package is installed WITHOUT Element Management Functions: • 3 Hybrid nodes When Essentials package is installed WITH Element Management Functions: • 3 Hybrid nodes + 1 Worker node
	Cisco Crosswork Active Topology	On-Premise Standard (default): Collectors only.	
	Element Management Functions	On-Premise Standard (default): Collectors only.	
Cisco Crosswork Network Controller Advantage	Cisco Crosswork Service Health	On-Premise Extended: Collectors and offload services.	3 Hybrid nodes + 2 Worker nodes

Package	Contents	Crosswork Data Gateway Deployment	Recommended number of cluster VMs
Add-on Package	Cisco Crosswork Change Automation	On-Premise Extended: Collectors and offload services.	3 Hybrid nodes + 2 Worker nodes
	Cisco Crosswork Health Insights	On-Premise Extended: Collectors and offload services.	
	Cisco Crosswork Zero Touch Provisioning	On-Premise Standard (default): Collectors only.	



Note For non-production lab installations without HA, you can use 1 Hybrid node.

VM Resources

The following table provide the details on CPU, memory, and disk requirements needed for each Crosswork VM and the other VMs in the deployment.

Crosswork VM	Crosswork Data Gateway	NSO	SR-PCE	Crosswork Hierarchical Controller	EPNM
<ul style="list-style-type: none"> • CPU: 12 vCPU • RAM: 96 GB • DISK: 1 TB (SSD) 	<ul style="list-style-type: none"> • CPU: 20 vCPU • RAM: 112 GB • DISK: 0.5 TB 	<ul style="list-style-type: none"> • Small Network Profile <ul style="list-style-type: none"> • CPU: 8 vCPU • RAM: 64 GB • DISK: 250 GB • Large Network Profile <ul style="list-style-type: none"> • CPU: 24 vCPU • RAM: 132 GB • DISK: 1TB 	<ul style="list-style-type: none"> • CPU: 8 vCPU • RAM: 24 GB • DISK: 45 GB 	<ul style="list-style-type: none"> • CPU: 10 cores • RAM: 96 GB • DISK: 400G SSD (lab) , 3TB SSD (production) 	<ul style="list-style-type: none"> • Professional (Small) <ul style="list-style-type: none"> • CPU: 16 vCPU • RAM: 64 GB • DISK: 2.8 TB • Extended (Medium/Large) <ul style="list-style-type: none"> • CPU: 24 vCPU • RAM: 128 GB • DISK: 4 TB



Note In Routed Optical Networking 2.1, Cisco Optical Network Controller and Crosswork Network Controller require different Crosswork Infrastructure versions. The Crosswork Infrastructure Cluster for Cisco Optical Network Controller must have:

- 3 VM
- CPU: 12 vCPU
- RAM: 96 GB
- DISK: 1TB SSD

Cisco Optical Network Controller Scale Support

Cisco Optical Network Controller supports a maximum of 500 nodes and 600 services. Cisco Optical Network Controller can run on the same cluster. Cisco Optical Network Controller adds more resources incrementally at the maximum supported scale. It is captured in Crosswork VM resources in the table above.

Planning and Design Phase

The planning and design phase involves:

1. Network Planning and Design

Inputs needed: Packet layer traffic demands, optical fiber topology, resiliency criteria, and other network constraints.

- a. WAE can be used to determine a new network build or augmentations to an existing network.
- b. After the IP network circuits have been determined, Cisco ONP is used to determine the optical layer feasibility and components that are used to support the network.

Output for a sample configuration:

This topology uses two Cisco 8201 routers, two NCS 2006 terminal nodes with NCS1K-MD-64 add/drop multiplexers, and EDFA-35 bi-directional amplifiers. The span length is 75 kms. Longer spans may require additional ILA nodes for amplification.

2. Automation Software Resource Planning

Server requirements for the Routed Optical Networking software elements

Determine the servers required for the full solution. See [Network Sizing Requirements, on page 1](#) and [Installation Requirements for Routed Optical Networking Components, on page 4](#).

- a. For a lab or EFT setup, it is recommended to use three servers each with 384 G of RAM, 32 cores, and two TB SSD.
- b. The solution requires the use of VMware ESX 6.7 or higher.

Installation Requirements for Routed Optical Networking Components

The following list points to the installation requirements for different Routed Optical Networking components.

- [Cisco Optical Network Planner 5.2](#)

- [Cisco WAN Automation Engine 7.6.x](#)
- [Cisco Crosswork Cluster, Crosswork Data Gateway, and Crosswork Applications](#)
- [Cisco Optical Network Controller 3.1](#)
- [Cisco Evolved Programmable Network Manager 7.1.2](#)
- [Cisco Network Services Orchestrator 6.1.9](#)
 - [Cisco NSO Routed Optical Networking Core Function Pack 3.0.0](#)
 - [Cisco NSO Transport-SDN Function Pack Bundle 6.0](#)
 - [Cisco Network Services Orchestrator DLM Service Pack 6.0](#)
- [Cisco Crosswork Hierarchical Controller 8.0](#)
- [Cisco Crosswork Network Controller 6.0](#)

Implement Phase

The implement phase involves:

1. Installation of hardware components

- a. Hardware staging or installation and initial base configuration required for management connectivity.
- b. All onboard software updates must be completed to the required revision.
- c. All associated base wiring must be completed to support the network. This includes connections between the optical elements and connections between routers and optical add/drop end-points to support Routed Optical Networking circuits using ZR/ZR+ optics. See [Deployment Topologies](#).
- d. Install Cisco Optical Site Manager to support NCS 1010 nodes. See [Install Cisco Optical Site Manager](#)

2. Installation of the Automation Software Components

- a. Complete all server hardware installation and base configuration to support the solution, including VMWare ESX if not already installed.
- b. Install the following software components to support the Routed Optical Networking solution.
 - [Cisco Optical Network Planner 5.2](#) (for optical planning)
 - [Cisco WAN Automation Engine 7.6.x](#) (for IP planning)
 - [Cisco Crosswork Cluster, Crosswork Data Gateway, and Crosswork Applications](#) (for supporting Crosswork Network Controller)
 - [Cisco Optical Network Controller 3.1](#) (for supporting optical network)
 - [Cisco Evolved Programmable Network Manager 7.1.4](#) (for managing the physical router and the optical network nodes)
 - [Cisco Network Services Orchestrator 6.1.9](#) (base installation to support RON FP)
 - [Cisco NSO Routed Optical Networking Core Function Pack 3.0](#) (for RON ML provisioning)

- [Cisco NSO Transport-SDN Function Pack Bundle 6.0](#) (for Crosswork Network Controller SR and xVPN provisioning)
- [Cisco Network Services Orchestrator DLM Service Pack 6.0](#) (for device synchronization between Crosswork Network Controller and NSO)
- [Cisco Crosswork Hierarchical Controller 8.0](#) (for provisioning the Routed Optical Networking ML service using the Crosswork Hierarchical Controller)



Note This is required only if the Routed Optical Networking ML service is provisioned via the Crosswork Hierarchical Controller GUI.

3. Onboarding of Devices

- Add devices to Cisco Optical Network Controller. See [Onboard Devices to Cisco Optical Network Controller](#).
- Add NSO, SR-PCE, and devices to Crosswork Network Controller. See [Add SR-PCE, NSO, and Routers to Crosswork Network Controller, on page 7](#).
- Add routers to NSO using the IOS-XR CLI NED. See Step 3 in [Provision ML Service Using NSO Routed Optical Networking CFP , on page 30](#).
- Add and configure the following Crosswork Hierarchical Controller adapters. See [Configure Adapters for Crosswork Hierarchical Controller, on page 13](#).



Note This step is required only if the Routed Optical Networking ML service is provisioned via the Crosswork Hierarchical Controller GUI.

- Add and configure the Crosswork Network Controller adapter.
- Create or import sites in Crosswork Hierarchical Controller. See the sections, "Add Sites" and "Export and Import Sites" in the [Cisco Crosswork Hierarchical Controller Administration Guide 8.0](#).
- Add and configure the IOS-XR adapter. Create router devices in Crosswork Hierarchical Controller using the IOS-XR adapter type. After the routers are created, add the Crosswork Network Controller adapter to the router device.
- Add and configure the Cisco Optical Network Controller adapter.

4. Provisioning of Services

- Ensure all device interconnections are complete.
- To provision the Routed Optical Networking ML service, use either one of the procedures:
 - Using the NSO GUI:**
 - Utilize the Routed Optical Networking FP ML services to provision and end-to-end service. See [Provision ML Service Using NSO Routed Optical Networking CFP , on page 30](#).

Edit Profile nso ×

Profile Name * nso

Add Credential Protocols

Connectivity Type	User Name *	Password *	Confirm Password *	
NETCONF	nso	
HTTPS	nso	

[+ Add Another](#)

[Save](#) [Cancel](#)

521905

- b. The SR-PCE credential profile requires HTTP credentials to communicate with the SR-PCE Northbound API.

Edit Profile SR-PCE ×

Profile Name * SR-PCE

Add Credential Protocols

Connectivity Type	User Name *	Password *	Confirm Password *	
HTTP	admin	

[+ Add Another](#)

[Save](#) [Cancel](#)

521906

- c. The router credential profile requires at a minimum, the SNMPv2 or SNMPv3 and SSH connectivity types. NETCONF is optional. GNMi is used when utilizing GNMi to configure streaming telemetry sensors on the node.

Edit Profile routers

Profile Name * routers

Add Credential Protocols

Connectivity Type	Read Community *	Write Community
SNMPv2	*****	*****

Connectivity Type	User Name *	Password *	Confirm Password *
SSH	admin	*****	*****
Enable Password			

Connectivity Type	User Name *	Password *	Confirm Password *
NETCONF	admin	*****	*****

Connectivity Type	User Name *	Password *	Confirm Password *
GNMI	admin	*****	*****

+ Add Another

Save Cancel

521907

3. Add the providers. See [About Adding Providers](#).
 - a. To add the SR-PCE or NSO provider, choose **Administration > Manage Provider Access** from the main menu. See [Manage Providers](#).
 - b. Add the NSO provider. See [Add Cisco NSO Providers](#).

Select the credential profile created for NSO. Select the family as NSO. The Device Key may be set to either the HOST_NAME or INVENTORY_ID depending on the specific deployment.

The following image demonstrates the connectivity to NSO's RESTCONF API over SSL using port 8888 and NETCONF using the default port of 2022. Since the Routed Optical Networking NSO CFP utilizes the XR CLI NED, the Cisco-IOS-XR model is not applicable and may be set to any version.

Edit Provider
✕

Provider Name *

Credential Profile *

Family *

Device Key *

Connection Type(s)

Protocol *	IP Address / Subnet Mask *	Port *	Timeout	
HTTPS	172.29.11.58 / 25	8888	60	🗑️
NETCONF	172.29.11.58 / 25	2022	60	🗑️

[+ Add Another](#)

Provider Properties

Property Key	Property Value	
forward	true	🗑️

[+ Add Another](#)

Model Prefix Info

Model *	Version *	
Cisco-IOS-XR	7.3.1	🗑️

521908

- c. Add the SR-PCE provider. See [Add Cisco SR-PCE Providers](#).

Select the credential profile created for SR-PCE. Select the family type as SR_PCE. The connectivity type for SR-PCE must be the HTTP. In the following image, the default API port of 8080 is specified. When the Property Key, "auto-onboard" is set to a Property value, "off", Crosswork Network Controller does not automatically add nodes that are discovered via the SR-PCE IGP topology to the device inventory. Devices must be added through the Crosswork Network Controller UI or inventory API.

Edit Provider
✕

Provider Name *

Credential Profile *

Family *

Connection Type(s)

Protocol *	IP Address / Subnet Mask *	Port *	Timeout
HTTP	172.29.11.54 / 25	8080	60

[+ Add Another](#)

Provider Properties

Property Key ?	Property Value ?
auto-onboard	off

[+ Add Another](#)

521909

4. Validate communications with one or more providers. Check on the provider's reachability using the steps in [Get Provider Details](#).
5. Onboard devices. See [Add Devices Through the UI](#).
 - a. The Administration State, Reachability Check, and Credential Profile are mandatory elements. The Host Name must be used if the NSO provider device key is set to the Host Name value. If the NSO provider device key is set to Inventory ID that field must be populated. The Software Type, Software Version, UUID, Serial Number, MAC address, and Product Type are filled by device discovery. Optionally, tags can be applied to the device. The GNMI encoding type can be set to JSON or PROTO.

Add New Device
✕

▼ General

<p>Administration State* <input type="text" value="UP"/></p> <p>Reachability Check* <input type="text" value="ENABLE"/></p> <p>Credential Profile* <input type="text" value="routers"/></p> <p>Host Name <input type="text" value="ron-8201-1"/></p> <p>Inventory ID <input type="text"/></p> <p>Software Type <input type="text"/></p> <p>Software Version <input type="text"/></p>	<p>UUID <input type="text"/></p> <p>Serial Number <input type="text"/></p> <p>Mac Address <input type="text"/></p> <p>Capability* <input type="text" value="YANG_MDT, SNMP, GNMI"/></p> <p>Tags <input type="text"/></p> <p>Product Type <input type="text"/></p> <p>Syslog Format <input type="text"/></p>
--	---

▼ Connectivity Details

Protocol *	IP Address / Subnet Mask *	Port *	Timeout	Encoding Type	
<input type="text" value="SSH"/>	<input type="text" value="172.29.11.20 / 25"/>	<input type="text" value="22"/>	<input type="text" value="60"/>	<input type="text"/>	<input type="text"/>
<input type="text" value="SNMP"/>	<input type="text" value="172.29.11.20 / 25"/>	<input type="text" value="161"/>	<input type="text" value="60"/>	<input type="text"/>	<input type="text"/>
<input type="text" value="GNMI"/>	<input type="text" value="172.29.11.20 / 25"/>	<input type="text" value="57333"/>	<input type="text" value="60"/>	<input type="text" value="PROTO"/>	<input type="text"/>
<input type="text" value="NETCONF"/>	<input type="text" value="172.29.11.20 / 25"/>	<input type="text" value="830"/>	<input type="text" value="60"/>	<input type="text"/>	<input type="text"/>

[+ Add Another](#)

➤ Routing Info

521910

Optionally, location information can be entered. Latitude and Longitude information place the node at a specific location on a geographic map.

Add the previously configured NSO provider as a provider for the device.

Add New Device
✕

SNMP	172.29.11.20	/ 25	161	60		
GNMI	172.29.11.20	/ 25	57333	60	PROTO	
NETCONF	172.29.11.20	/ 25	830	60		

[+ Add Another](#)

> Routing Info

> Streaming Telemetry config

∨ Location

Building

Street

City

State

Country

Region

Zip

Latitude

Longitude

Altitude

∨ Providers and Access

Provider Family	Provider Name	Credential	Device Key
NSO	nso-58	nso	ron-8201-1

[+ Add Another](#)

Save
Cancel

- b. Attach the devices to an active Cisco Crosswork Data Gateway pool to manage them (device discovery). Review the Data Gateways pane (see [Overview of Cisco Crosswork Data Gateway](#)). The operational state of the Cisco Crosswork Data Gateway pool to which you want to attach devices must be **Up**. Follow the steps in [Attach Devices to Cisco Crosswork Data Gateway](#).

Administration / Data Gateway Management
SHOW ALL

Data Gateways
Pools
Virtual Machines

∨ Data Gateway Metrics Summary

Operational State

- Up (1)
- Down (0)
- Degraded (0)
- Unknown (0)

Administration State

- Up (1)
- Maintenance (0)

High Availability Status

- Protected (0)
- Not Protected (0)
- Limited Protection (0)
- None Planned (1)

Devices

- Attached (13)
- Available (0)

Data Gateways Total 1

Name	Operational State	Administration State	High Availability Status	Pool Name	Outage History	Average Availability	VM ID	Attached Device Count	Actions
cdg-pool-1-1	Up	Up	None Planned	cdg-pool-1			cdg-socket	13	<ul style="list-style-type: none"> Attach Devices Detach Devices Move Devices

Configure Adapters for Crosswork Hierarchical Controller

Prerequisite

When you work with Crosswork Hierarchical Controller adapters you are required to use credentials. These credentials are used for authentication when a device is assigned to an adapter. The same credentials may be shared by multiple adapters. The credentials are added under the **Services > Device Manager > Credentials**

tab in the Crosswork Hierarchical Controller GUI. The adapters needed for the Routed Optical Networking solution are:

Table 1: Routed Optical Networking Adapters

Adapter	Credential Type
Crosswork Network Controller	HTTP (username/password)
Crosswork Network Controller Crosswork Data Gateway	HTTP (username/password)
Cisco Optical Network Controller	HTTP (username/password)
IOS-XR	SSH - User and password



Note If Cisco Optical Network Controller and Crosswork Network Controller are on the same Crosswork cluster, they can use the same credential profile.

To add the adapters, perform the following steps:

1. In the applications bar in Crosswork Hierarchical Controller, select **Services > Device Manager > Adapters**.
2. Click **Add new adapter**.
3. Enter the adapter details:
 - **Adapter Type:** Select an adapter type from the list of available adapter types currently installed in Crosswork Hierarchical Controller.
 - **Adapter Name:** Unique user defined name of this adapter type instance (there can be several instances of the same adapter type).
4. To configure the adapter, select the adapter in the Adapters pane. Configure the parameters as displayed in the following images.
 - **Crosswork Network Controller Adapter:**



Note API version for Crosswork Network Controller must be V2.

Figure 1: Crosswork Network Controller Adapter Configuration - General Tab



Note The Full Data Fetch Interval must be set to 300s or higher in a production network.


The following parameters must be configured for Crosswork Network Controller notifications and collection.

Figure 2: Crosswork Network Controller Notifications

Figure 3: Crosswork Network Controller Collection and Provisioning

• **IOS-XR Adapter**


Figure 4: IOS-XR Adapter - General Tab




Note The Polling Cycle should not be less than 300s in a production network. Concurrency can be increased. The Logging Level must be set to Info if everything is working correctly.


The following collection parameters must be configured. These parameters collect optical power values for the link assurance application.

Figure 5: IOS-XR Adapter - General Tab




Note Check the **Enable collection of optics and coherent DSP Statistics** parameter only when using Automation Starter Solution.

Figure 6: IOS-XR Adapter - General Tab



The status of the devices must be **ok** in the Devices tab after the addition and completion of a successful collection cycle.

Figure 7: IOS-XR Adapter - Devices Tab

Name	Status	Status Changes (Last 24 hrs)	Site	Adapter(s)	Host	Port
16 ITEMS						
172.29.11.26	✓ Ok	0	Monterey	cisco-xr, cnc30	172.29.11.26	22
172.29.11.41	✓ Ok	0	Tucson	cisco-xr, cnc30	172.29.11.41	22
172.29.11.23	✓ Ok	2	Las Vegas	cisco-xr, cnc30	172.29.11.23	22
172.29.11.40	✓ Ok	0	Monterey	cisco-xr, cnc30	172.29.11.40	22
172.29.11.29	✓ Ok	0	ST. George	cisco-xr, cnc30	172.29.11.29	22
172.27.227.11	✓ Ok	0	Cedar City	cisco-xr, cnc30	172.27.227.11	22
172.29.11.120	✓ Ok	0	Tucson	cisco-xr, cnc30	172.29.11.120	22
172.29.11.22	✓ Ok	0	Mortero Palms	cisco-xr, cnc30	172.29.11.22	22
172.29.11.28	✓ Ok	0	Albuquerque	cisco-xr, cnc30	172.29.11.28	22
172.29.11.24	✓ Ok	0	San Diego	cisco-xr, cnc30	172.29.11.24	22
172.27.227.10	✓ Ok	0	Santa Fe	cisco-xr, cnc30	172.27.227.10	22
172.29.11.30	✓ Ok	0	ST. George	cisco-xr, cnc30	172.29.11.30	22
172.29.11.21	✓ Ok	0	Las Vegas	cisco-xr, cnc30	172.29.11.21	22
172.29.11.27	✓ Ok	2	San Luis Obispo	cisco-xr, cnc30	172.29.11.27	22
172.29.11.20	✓ Ok	0	Los Angeles	cisco-xr, cnc30	172.29.11.20	22
172.29.11.25	✓ Ok	0	Flagstaff	cisco-xr, cnc30	172.29.11.25	22

To add routers to Crosswork Hierarchical Controller, click the **Managed Devices** tab and then **+ Add Device**.

Figure 8: IOS-XR Adapter -Add New Device - General Tab

172.29.11.40

General Adapters Events

Name* 172.29.11.40 Network Element Site Monterey

It is recommended to use the hostname+hco (ron-8201-1-hco) or the device IP address. The device must be assigned a site for it to be displayed in the Explorer UI.

Assign both the IOS-XR and Crosswork Network Controller adapter type to the device. Do not enable discovery for the Crosswork Network Controller adapter.

Figure 9: IOS-XR Adapter -Add New Device - Adapters Tab

172.29.11.40

General Adapters Events

cisco-xr Unassign device from this adapter

Host* 172.29.11.40 Port* 22

Direct Connect (avoid tunnel if configured) Authentication cisco-XR

Enabled*

cnc30 Unassign device from this adapter

SSH CONFIGURATION

Device should be discovered

• Cisco Optical Network Controller Adapter

Figure 10: Cisco Optical Network Controller Adapter - General Tab

The Polling cycle must be set to 300s or higher in a production network. Polling retrieves TAPI SIPs, topology, and connectivity services.

The URL in the following figure is for the Cisco Optical Network Controller 3.1.

The screenshot displays the 'General' configuration tab for the Cisco Optical Network Controller Adapter. The configuration is organized into several sections:

- Adapter Properties:** Includes 'Enabled' (checked), 'Logging Level' (Info), 'Polling Cycle [sec]' (240), 'Provisioning' (checked), 'Connection Timeout [sec]' (600), and 'Minimal interval time between data updates [sec]' (0).
- Connection Properties:** Includes 'Host [including protocol, port and URI prefix]' (https://172.29.11.81:8443/onc-nbi-service/), 'Credentials' (onc31), and 'URI prefix [crosswork/onc-tapi] or [nbi/service] or [onc-nbi-service]'.
- File-Bringers Configuration:** Includes 'Enabled' (unchecked), 'Remote address with file pattern', and 'Credentials'.
- Notifications Configuration:** Includes 'Enabled' (checked), 'URL, Sub-port' (CONC_NETCONF), and 'NETCONF or CONC_NETCONF'.
- Stats Collection Configuration:** Includes 'Enabled' (checked) and 'Stats Interval Polling [sec]' (600).
- Hyperlinker Rules Configuration:** Includes 'Enabled' (checked) and 'Hyperlinker Rules Interval Checking [sec]' (600).

The optical nodes are discovered automatically from Cisco Optical Network Controller. Nodes must be assigned a site for it to be displayed in the Explorer UI.

Figure 11: Cisco Optical Network Controller Adapter - Devices Tab

Adapters	Name	Status	Status Changes (Last 24 hr)	Site	Adapter(s)
cisco-xr					
cnc30					
onc-76	SITEMS				
onc-poc50-1	ron-ols-5-readm	✓ Ok	0	Monterey	onc-76
	ron-ols-4-readm	✓ Ok	0	San Luis Obispo	onc-76
sw0	ron-ols-2-readm	✓ Ok	0	Las Vegas	onc-76
	ron-ols-1-readm	✓ Ok	0	Los Angeles	onc-76
	ron-ols-3	✓ Ok	0	Barstow	onc-76

• Crosswork Network Controller Crosswork Data Gateway Adapter

Crosswork Network Controller Crosswork Data Gateway adapter is used to collect telemetry data via gNMI to the router. In Crosswork Network Controller, the routers must be configured with the gNMI protocol with the encoding type set to "PROTO" and the GNMI capability enabled. In IOS XR, the routers must be configured for gRPC so that Crosswork Data Gateway can create gNMI telemetry subscriptions.

Figure 12: Crosswork Network Controller Crosswork Data Gateway Adapter

Protocol *	IP Address / Subnet Mask *	Port *	Timeout(sec)	Encoding Type
SSH	172.29.11.40 / 25	22	60	
SNMP	172.29.11.40 / 25	161	60	
Encryption <input type="text"/>				
NETCONF	172.29.11.40 / 25	830	60	
GNMI	172.29.11.40 / 25	57333	60	PROTO

[+ Add Another](#)

Capability*

YANG MDT
 TL1
 YANG CLI
 YANG EPNM
 SNMP
 GNMI

> Providers and Access
 > Routing Info
 > Streaming Telemetry config
 > Location

The Crosswork Data Gateway adapter is configured to connect to Crosswork Network Controller controlling Crosswork Data Gateway instance. It can be the same as the Crosswork Network Controller used for the topology or a different Crosswork Network Controller. The collection parameters describe the supported telemetry collection jobs. The statistics show up in the physical interface statistics and in the Link Assurance application.

Figure 13: Crosswork Network Controller Crosswork Data Gateway Adapter - General Tab

Devices Events **General**

Enabled
 Logging Level: Info

Collector Cadence [sec]: 300
 Status Update Interval [sec]: 300

Collector sample cadence in seconds
NOTE: You can see missed stats errors if the interval is less than the collector cadence

CNC CONFIGURATION

Host: 172.29.11.75
 Port: 30603
Timeout [sec]:

Credentials: cnc-6-75

GRPC LISTENER CONFIGURATION

Public IP Address for GRPC listen port 65001: 172.27.227.32
 Destination Name: netfusion_cdg_32
 GRPC Messages Debug Logging

NOTE: Make sure that the address is forwarded (or belonged) to the docker host
NOTE: The name should be unique in the crosswork context

COLLECTION PARAMETERS

Missed ports stats error threshold (percentage): 10

Threshold in percentages per device ports with no stats to report error

Enable Optics Counters: 30 Seconds
 Enable Interface Counters
 Enable Optics Counters: Instant

Enable OTU Counters: Instant
 Enable Optics Counters: 15 Minutes
 Enable Optics Counters: 24 Hours

Enable OTU Counters: 24 Hours
 Enable OTU Counters: 30 Seconds
 Enable OTU Counters: 15 Minutes

- The device name in Cisco Crosswork Hierarchical Controller must match the device name in Crosswork Network Controller for successful deployment. If successful, you will see Cisco Crosswork Hierarchical Controller as a new destination in Crosswork Network Controller. This is setup by Cisco Crosswork Hierarchical Controller and user interaction is not required. As Crosswork Data Gateway is enabled on devices, new collection jobs are populated. A single collection job is available for each router collecting multiple KPIs.

Figure 14: Crosswork Network Controller Crosswork Data Gateway Adapter - Data Destinations

Destination Name	Server Type	Compression Type	Encoding	UUID
Crosswork_Kafka	Kafka	snappy	gpbkv	c2a8fba8-8363-3d22-b0c2-a9e449693fae
cdg-astack-pipeline	gRPC	gzip	gpbkv	e9b4c2ec-b2e6-4db0-a942-0402dd347a1d
netfusion_cdg	gRPC	gzip	gpbkv	0a088f8b-3fea-4694-a744-54c02fbdda5e

Figure 15: Crosswork Network Controller Crosswork Data Gateway Adapter - Collection Jobs

Status	App ID	Context ID	Action
Successful	netfusion_cdg	ron-poc-8201-2	
Successful	cw.dminvmgr0	dim/ci-collector/group...	
Successful	cw.dminvmgr0	dim/ci-collector/group...	
Successful	cw.optimatrafic	cw.optimatraficmtd-ctx	
Successful	cw.dminvmgr0	dim/vmp-collector/grp...	
Successful	cw.dminvmgr0	dim/ci-collector/group...	
Successful	cw.topo_svc	cw.topo_svc.snmp	
Successful	netfusion_cdg	ron-poc-8201-1	
Successful	cw.optimatrafic	cw.optimatraficmtd-ctx	
Successful	cw.topo-visualization	topo-visualization.colle...	
Degraded	cw.topo_svc	cw.topo_svc.snmptraps	

• NSO Adapter In Hierarchical Controller

In Hierarchical Controller 8.0 there is an embedded NSO installed when Hierarchical Controller 8.0 is installed. The NSO adapter can use the internal NSO or point to an external NSO instance. Provisioning using the NSO adapter requires adding the NSO adapter to the devices you want to provision.

Use the NSO adapter when you use the [Automation Starter Solution](#).



Note

- If using the internal NSO, the Routed Optical Networking 3.0 Core Function Pack must be installed on the NSO instance.
- If using the internal NSO, devices must be added to that NSO, adding them to Hierarchical Controller does not automatically onboard them into the internal NSO.

Figure 16: NSO Adapter - General Tab

device-manager-srv Adapters Managed Devices Credentials

Adapters Devices Events General

cnc
cdg
cisco-xr
onc
onc-50
nso

Enabled Loading Level: Debug

Use internal nso
Connect to an already-existing local nso instance (you may leave Server Configuration parameters empty)

SERVER CONFIGURATION

Host: Port: Credentials: nso

PROVISIONING PARAMETERS

IP-Link create timeout: 600

Start configuration with NSO and XR adapters.

cloud-ncs540-1

General Adapters Events

cisco-xr Unassign device from this adapter

Host: 172.29.11.120 Port: 22

Direct Connect (avoid tunnel if configured) Authentication: cisco-xr

Enabled*

nso Unassign device from this adapter

DEVICE CONFIGURATION

+ Assign device to a new adapter

Delete device Cancel Save

Configure SSO in Crosswork Hierarchical Controller

This section describes how to configure SSO in Crosswork Hierarchical Controller with Crosswork Network Controller as Identity Provider. You can use the same SSO configuration to set up SSO for Cisco Optical Network Controller Release 3.1.

1. Configure Crosswork Hierarchical Controller

a. Click **Settings > Security > SAML Configuration**

Enter the necessary information:

- **Login URL:** `https://<CNC_IP>:<port>/crosswork/sso/idp/profile/SAML2/Redirect/SSO`
- **Entity ID:** `https://<CNC_IP>/idp`
- **Certificate:** Copy from Crosswork Network Controller metadata from `https://<CNC_IP>:<port>/crosswork/sso/idp/metadata`
- Use **Groups Attribute Name** `authenticationMethod`

Figure 17: Crosswork Hierarchical Controller Provider Configuration Sample

SAML SSO

Enabled

Login URL

Entity ID

Base URL
 Use Current


Signing Certificate

Groups Attribute Name

Reload Save


b. Click **Settings > Security > Permission Mapping**

Figure 18: Crosswork Hierarchical Controller Permission Mapping Sample



- c. Add a **Match** condition for **SAML Group** of **QueryDatabaseAuthenticationHandler** with a permission of `permission/admin`

Figure 19: Crosswork Hierarchical Controller Permission Mapping Sample



2. Copy Crosswork Hierarchical Controller SAML metadata to a file, metadata is located at `https://<HCO_IP>:<port>/sso/metadata`. The following is a sample.

```
<EntityDescriptor entityID="https://172.29.11.83:8443"
xmlns="urn:oasis:names:tc:SAML:2.0:metadata"
xmlns:assertion="urn:oasis:names:tc:SAML:2.0:assertion"
xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
  <SPSSODescriptor AuthnRequestsSigned="false" WantAssertionsSigned="false"
protocolSupportEnumeration="urn:oasis:names:tc:SAML:2.0:protocol">
    <NameIDFormat>urn:oasis:names:tc:SAML:1.1:nameid-format:emailAddress</NameIDFormat>

    <SingleLogoutService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-Redirect"
Location="https://172.29.11.83:8443/sso/logout">
</SingleLogoutService>
<AssertionConsumerService index="0"
```

```


Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST"
Location="https://172.29.11.83:8443/sso/acs">
  </AssertionConsumerService>
</SPSSODescriptor>
</EntityDescriptor>

```

3. Configure Crosswork Network Controller

- a. Login to Crosswork Network Controller, click **Administration** > **AAA** > **SSO**


Figure 20: Crosswork Network Controller AAA



- b. Click +

- Add a name
- Add a unique evaluation order number
- Upload HCO's Metadata file in XML format

Figure 21: Crosswork Network Controller Add new Service Provider



- c. Click **Save**

Figure 22: Crosswork Network Controller AAA

Identity Provider ?

Entity ID *

+ ✎ 🗑

Service Name

Evaluation Order

Service Provider


Name *

Evaluation Order *

Metadata

4. Login to

Figure 23: Crosswork Network Controller AAA



Troubleshooting Cisco Crosswork Hierarchical Controller SSO

- Use the **sedo logs security audit** in the Crosswork Hierarchical Controller to get the logs.
- Ensure time is synchronised between Cisco Crosswork Hierarchical Controller and Cisco Crosswork Network Controller
- If there is an error related to `QueryDatabaseAuthenticationHandler` add the SAML group mapping in Crosswork Hierarchical Controller configuration, map to group Admin

Examples of Cross Launch

SSO is supported across Hierarchical Controller 8.0, Crosswork Network Controller 6.0, and Cisco Optical Network Controller/Cisco Optical Site Manager.

- Cross Launch from IGP Link SRC/DST Router in Hierarchical Controller to Crosswork Network Controller

1. Click on **Links > IGP**
2. Hover over either Source Device or Destination Device, click the ellipsis and click **IGP device at Crosswork Network Controller**

Figure 24: Network Inventory

The screenshot shows the 'Network Inventory' page with a table of links. A 'More Information' popup is open over a link, showing the option 'IGP device at CNC'.

Name	Source Port	Source Device
ron-8201-1 100.1.1.14 to ron-asr9903-1 100.1.1.15	100.1.1.20/31	ron-8201-1
ron-8201-1 100.1.1.20 to ron-ncs55a2-1 100.1.1.21	100.1.4.1/31	ron-ncs55a2-1
ron-ncs540-1 100.1.4.1 to ron-poc-8201-1 100.1.4.0	100.1.2.2/31	ron-8201-1
ron-8201-2 100.1.2.2 to ron-8201-4 100.1.2.3	67.67.67.0/31	ron-8201-1
ron-8201-1 67.67.67.0 to ron-ncs5504-1 67.67.67.1	139.1.1.2/30	ron-ncs5504-1
ron-ncs57b1-1 139.1.1.2 to ron-ncs57c3-1 139.1.1.1	100.1.1.16/31	ron-8201-1
ron-8201-1 100.1.1.16 to ron-ncs540-1 100.1.1.17		

This operation launches the router traffic engineering information in Crosswork Network Controller.

Figure 25: Traffic Engineering

The screenshot shows the 'Traffic Engineering' dashboard in the Crosswork Network Controller. It features a network map of the United States with various routers connected. A 'Device Details' popup is open for the router 'ron-8201-1'.

Summary	
Host Name	ron-8201-1
Reachability	Reachable
IP Address	172.29.11.20
Geo Location	Latitude 35.335000, Longitude -90.043000
Device Type	Router
Device Group	Location > All Locations > Unassigned Devices
Product Type	Cisco 8201 Router
Connect To Device	SSH IPv4
Last Update	08-Jan-2024 09:39:57 AM CST

Routing	
TE Router ID	100.0.0.1
ISIS System ID	1000.0100.0001 Level-2
ASN	100

- Hierarchical Controller SR Policy to Crosswork Network Controller

1. Click on **Connections > SR Policy**
2. Hover over policy and click on ellipses to open cross launch.

Figure 26: Network Inventory

Network Inventory

Filter inventory by: Regions/Sites/Devices

Devices Sites Links Connections Services Cards Ports Transceivers Power Supplies Fans Shelves

NMC OCH ETHERNET SR POLICY MC

Apply Inventory Filter On Connections Export Table

Name	Source Device	Destination Device	Operation State	Protectex	IGP Hops Count	Tags	Color	Preference
100.0.0.20 to 100.0.0.3, color 1000	ron-ncs57b1-1	ron-8201-32FH-3	UP	SINGLE...	3		1000	200
100.0.0.50 to 100.0.0.52, color 101			UP	SINGLE...	3		101	100
100.0.0.50 to 100.0.0.52, color 1000			UP	SINGLE...	3		1000	200
100.0.0.50 to 100.0.0.52, color 705			UP	SINGLE...	3		705	200
100.0.0.50 to 100.0.0.52, color 103			UP	SINGLE...	3		103	200
100.0.0.50 to 100.0.0.27, color 705			UP	SINGLE...	3		705	200
100.0.0.52, color 10000			UP	SINGLE...	3		10000	200
100.0.0.50 to 100.0.0.52, color 102			UP	SINGLE...	3		102	100
100.0.1.1 to 100.0.1.3, color 9010			UP	SINGLE...	1		9010	100
100.0.1.1 to 100.0.0.27, color 9009			UP	SINGLE...	3		9009	100
100.0.0.52 to 100.0.1.3, color 1000			UP	SINGLE...	3		1000	100
100.0.0.52 to 100.0.0.27, color 5227			UP	SINGLE...	3		5227	100
100.0.0.52 to 100.0.0.50, color 4000	ron-ncs540-1	cloud-ncs540-1	UP	SINGLE...	3		4000	200

More Information:
[SR Policy at CNC](#)

This operation launches detailed policy information in Crosswork Network Controller.

Figure 27: Traffic Engineering

Crosswork Network Controller

Traffic Engineering

Dashboard

Show: Traffic Engineering Device Groups: Locati...

Location

Show: Participating Only IGP Path

Show Groups

SR Policy Details

Current History

Headend cloud-ncs540-1 Source IP: 100.0.0.50
TE RID: 100.0.0.50
PCC IP: 100.0.0.50

Endpoint ron-ncs540-1 Dest IP: 100.0.0.52
TE RID: 100.0.0.52

Color 10000

Summary

Admin State Up
Oper State Up
Binding SID 24010
Policy Type Regular
Profile ID
Description
Traffic Rate 0 Mbps
Unused True


Candidate Path

Expand All

Path Name	Preference	Path Type	State
cfg_srte_c_10000_ep_100...	200	Unknown	Up

- Hierarchical Controller Optical Node to Cisco Optical Site Manager
1. Click on **Devices** > **ONS**
 2. Hover over a device, click ellipsis and click Optical Node at COSM.


Figure 28: Network Inventory



• Hierarchical Controller Optical Port to Cisco Optical Site Manager

1. Click on **Ports** > **OTS**
2. Hover over a port, click ellipsis and click Optical Port at COSM.

Figure 29: Network Inventory



• Hierarchical Controller Link Assurance Node to Cisco Optical Site Manager or SVO

1. Click **Link Assurance** > **Inspect links**
2. Hover over a node, click ellipsis and click Optical Node at COSM.

Figure 30: Link Assurance

The screenshot shows the Cisco Link Assurance interface. On the left, there are navigation icons and a sidebar with 'Link Assurance', 'Inspect Links', and 'Settings'. The main area displays a network diagram titled '10.28.29.20 to 10.28.29.21 L3 Logical Link' with nodes for FRA and MUN. A table below the diagram lists 17 items, including various L3 logical links. A 'More Information' dialog box is open over the 'ron-poc-ols-1' link, showing a link to 'Optical Node at COSM'.

This operation launches the node functional view in Cisco Optical Site Manager (for NCS 1000 series devices) or SVO (for NCS 2000 series devices).

The screenshot shows the Cisco Optical Site Manager interface. On the left, there is a rack view showing a physical device. On the right, there is an 'Alarm Summary' section with a table of alarms. The table has columns for Rack, UID, Device Name, Severity, Service Affe..., Condition, and Timestamp. The table contains three rows of alarm data.

Rack	UID	Device Name	Severity	Service Affe...	Condition	Timestamp
1/1	1	ron-poc-ols-1	Warning	NSA	SSM-ST3	08/12/2001, 05:11:32
1/1	1	ron-poc-ols-1	Warning	NSA	FRNGSYNC	08/12/2001, 05:11:37
1/1	1	ron-poc-ols-1	Minor	NSA	EQPT-MISS	08/12/2001, 05:12:04

- Hierarchical Controller Link Assurance Port to Cisco Optical Site Manager

1. Click **Link Assurance** > **Inspect links**
2. Hover over a port, click ellipsis and click Optical Port at COSM.


Figure 31: Link Assurance

The screenshot displays the Link Assurance configuration page. On the left, there are navigation icons and a sidebar with 'Link Assurance', 'Inspect Links', and 'Settings'. The main area is titled '45.54.23.0 to 45.54.23.1 L3 Logical Link'. It features a network diagram with three domains: VAL, BAR, and Geneva. VAL contains a router 'ron-8201-32F...' and an OLT 'OLT5-R_Cro...'. BAR contains a router 'ron-mcs1010_olt5-r-c/1/0/LINE' and an ILA2 component. Geneva contains a router 'ron-ecs57b1-1' and an OLT 'OLT6-roadm'. A table lists 17 L3 Logical Links, with the selected link '45.54.23.0 to 45.54.23.1' showing 'UP' status. A 'More Information' panel shows 'Admin Status: UP' and 'Operational Status: UP'.


Provision ML Service Using NSO Routed Optical Networking CFP

Perform the following steps to provision the Routed Optical Networking ML service using the NSO Web UI.


1. To add a new device, perform these steps:
 - a. In the Device manager, click the + to add a new device. Specify a name for the new device. Click **Confirm**.




- b. After creating the new device, click the device name to fill required and optional parameters. In this screen, the required parameters are the authgroup and IP address of the device.




- c. Scroll down in the device configuration screen. Click the “device-type” to bring up the device type selection screen. The device-type that is supported in the Routed Optical Networking ML FP is IOS-XR CLI NED.



- d. Click the blue NETCONF text to select the proper NED. The Routed Optical Networking ML FP requires the use of the **cisco-iosxr-nc-7.3** NED.




- e. Click the Commit manager to view the NSO CLI configuration being applied. Click **Commit** to save the device configuration to NSO.





Note Next we add the multilayer end-to-end service to configure and provision both the optical line system and routers. We recommend you to click **check-sync** in the Device manager to ensure that the device configuration is properly in sync with NSO before provisioning. If the device is out of sync, initial provisioning fails.



2. To create Routed Optical Networking ML service, perform these steps:
 - a. In the Service manager, select the Routed Optical Networking ML service point from the drop-down list. When we create the new Routed Optical Networking ML service, the required components are the service name, mode of the service (transponder or muxponder), and the bandwidth. The bandwidth corresponds to the line rate of the ZR/ZR+ optics. Click **Confirm**.

Create service

name

mode

bandwidth

- b. In the Configuration editor, click the newly created service name for editing the additional parameters that are required for the service. In this example, we set the circuit-id name in the global parameters. The frequency is set by the optical controller based on the specified optical add/drop port. The dac-rate

is set to the default value.

The screenshot shows the Cisco Configuration Editor interface for a circuit named 'poc_circuit_195200'. The configuration fields are as follows:

- name:** poc_circuit_195200
- circuit-id:** This is a demo circuit
- dac-rate:** (empty)
- mode*:** transponder
- grid-type:** (100mhz-grid)
- clear-rollback:** (empty)
- bandwidth*:** 400
- frequency:** (empty)


Below the configuration fields, there are sections for 'end-point' and 'custom-template', both of which are currently empty. The 'end-point' section has an 'Add list item' button. The 'custom-template' section also has an 'Add list item' button. The bottom navigation bar shows the following tabs: C* Control Manager, E Configuration editor (active), A Alarm Manager, B Dashboard, D Device Manager, and S Service Manager. The version number 521926 is visible in the bottom right corner.



Note


- User configuration global options are frequency and dac-rate
- Dac-rate controls the TX shaping parameters: 1x1.25 = enabled, 1x1 = disabled. Leaving it blank uses system default of enabled, and can be used in most circumstances
- Modulation of 16 QAM is available for 2x100G muxponder mode.

- c. After the ols-domain is added, you must add end-points to the circuit. Two end-points are always required. The end-points are the routers with ZR/ZR+ optics.



521927

d. Add the end-point-device to the service. Click **Confirm**.



521928

After the end-point is created, click the end-point to edit the end-point parameters. The line-port is a required parameter and refers to the optics port on the router. In this example, this is the same as the line-port specified in the inter-layer-link service for the end-point router.

The screenshot shows a dialog box titled "Add new list item". It contains a text input field with the value "end-point-device". Below this is a dropdown menu with the selected item "ron-poc-8201-2". At the bottom of the dialog are two buttons: "cancel" and "confirm".

The transmit-power is an optional parameter for end-to-end provisioning. If it is omitted the optical controller (Cisco Optical Network Controller) will provide the transmit power. Transmit power sets the transmit power, the value is in 100*value in 0.1dBm increments. For example, -100 is -10dBm. If no value is specified the default of -10dBm is used for QDD-400G-ZR-S or QDD-400G-ZRP-S, or 0dBm for DP04QSDD-HE0 (Bright ZR+). The transceiver-capability field specifies the optic type and is only required if no packet layer configuration is being performed. In this example, you are performing packet layer provisioning so specifying the transceiver capability is not required.

Add the line-port of 0/0/0/20 to the Routed Optical Networking ML service.

The screenshot shows the Cisco Configuration Editor interface. The breadcrumb path is `/cisco-ron-clp/ron/ml[poc_circuit_195200]/end-point[ron-poc-8201-1]`. The configuration tree on the left includes sections for `terminal-device-optical/`, `ols-domain/`, and `terminal-device-packet/`. The `terminal-device-packet/` section is expanded, showing three empty lists: `bundle`, `interface`, and `custom-template`. Each list has an 'Add list item' button with a plus sign. The bottom navigation bar shows tabs for `Configuration editor`, `Alarm manager`, `Dashboard`, `Device manager`, and `Service manager`.

- e. Click end-point to go back to the top-level endpoint configuration, click **terminal-device-packet** to configure Ethernet/IP parameters

The screenshot shows the Cisco Configuration Editor interface. The breadcrumb path is `/cisco-ron-clp/ron/ml[poc_8201_1_to_poc_8201_2_20]/end-point[ron-poc-8201-1]/terminal-device-packet/`. The configuration tree on the left shows three empty lists: `bundle`, `interface`, and `custom-template`. Each list has an 'Add list item' button with a plus sign. The bottom navigation bar shows tabs for `Configuration editor`, `Alarm manager`, `Dashboard`, `Device manager`, and `Service manager`.



Note


- Ethernet/IP configuration is optional.
- Bundle configuration adds an interface to an existing bundle or creates a new bundle and adds the newly created IP interface to it.

Interface configuration is used for configuring IP address parameters on newly created Ethernet interfaces.


In this example we add a new Bundle and assign an IP address to the Bundle.

- f. Click the plus sign next to bundle to add a bundle, in this case with an identifier of 500. This creates a bundle interface Bundle-Ether 500 on the endpoint router


The interface index for a bundle use case is always 0. In case of a non-bundle configuration in muxponder mode, the index can be 0–3 representing the number of interfaces created as part of the muxponder configuration.



- g. Click the bundle number and *ip-address* to configure an IP address on the bundle.



- h. Return to the top-level endpoint configuration, select the index 0 previously created and click **membership** to add the interface to the bundle



Configuration editor
NSO VERSION: 5.7.6.2

↑ /cisco-ron-cfp:ron/ron-ml{poc_8201_1_to_poc_8201_2_20}/end-point{ron-poc-8201-1}/terminal-device-packet/interface{0}/membership/

See 'poc_8201_1_to_poc_8201_2_20' in Service manager

bundle-id*

500


mode

active

**Note**

- Bundle-id selects the previously created bundle.
- Mode sets the bundle LAG signaling mode. Active=LACP, passive=LACP listener only, on=No active signaling, inherit=Inherit signaling from Bundle interface configuration. Default is active.

- Return to the top level of the service configuration and similarly configure the second endpoint.



Configuration editor
NSO VERSION: 5.7.6.2

↑ /cisco-ron-cfp:ron/ron-ml{poc_8201_1_to_poc_8201_2_20}/

See 'poc_8201_1_to_poc_8201_2_20' in Service manager

name
poc_8201_1_to_poc_8201_2_20

circuit-id
poc_circuit

disc-rate

mode*
transponder

grid-type
(100mhz-grid)

clear-rollback

bandwidth*
400

frequency
1952000

end-point

end-point-device


ron-poc-8201-1

ron-poc-8201-2

ots-domain/


srlg/

- Click **SRLG** to perform SRLG configuration

**Note**

- Configuration options are to specify a preconfigured group, a list of numeric SRLG values, or a list of SRLG names associated with preconfigured name:value pairs.
- Each type can be populated in the same configuration.
- In this example we specify a list of explicit numeric values. An index is used along with the numeric value.

3. In the Commit manager, click the config tab. The NSO CLI configuration for the end-to-end service is displayed. If the ols-domain component is not specified in the global configuration, no optical line system provisioning is performed, only router provisioning. You can preview and then commit the configuration.



521934

4. Verify status in NSO UI.

You can verify the status by inspecting the plan associated with the service. You can find the plan under the main ron-ml configuration which you can access by clicking the top portion of the service configuration. An example is highlighted in the following image.

The screenshot shows the Cisco NSO Configuration editor interface. The breadcrumb path is `/cisco-ron-cfp:ron/ron-ml[poc_8201_1_to_poc_8201_2_20]`. A notification bar says "See 'poc_8201_1_to_poc_8201_2_20' in Service manager". The configuration is displayed in a table-like view:

name poc_8201_1_to_poc_8201_2_20	bandwidth* 400	frequency 1952000
plan-location /cisco-ron-cfp:ron/cisco-ron-cfp:ron-ml-plan[cisco-ron-cfp:name='poc_8201_1_to_poc_8201_2_20']	circuit-id poc_circuit	dac-rate
mode* transponder	grid-type (100mhz-grid)	clear-rollback

a. Inspect the plan by clicking on the newly created service

The screenshot shows the 'ron-ml-plan' configuration page in the NSO UI. The configuration is as follows:

```

ron-ml-plan
name
682b3df2_30b2_4af2_9438_6dfb7738d0ef
6e2b4907_b08b_4338_8304_a4f2903b3311
f7a00076_d3db_4bd9_9d94_673d4cc462cb
poc_8201_1_to_poc_8201_2_20
  
```

If all steps are green and complete, the service has been properly deployed to the network



b. Inspect router configuration.

The **show configuration commit changes last 1** command shows the CLI config applied to the device during the NSO provisioning.

The **show optics controller 0/0/0/20** command verifies the operational status.

```

RP/0/RP0/CPU0:ron-poc-8201-1#show configuration commit changes last 1
Mon Oct 17 09:51:11.625 PDT
Building configuration...
!! IOS XR Configuration 7.7.1
sr1g
interface Bundle-Ether500
  10 value 1000
  20 value 2000
  !
!
interface Bundle-Ether500
  ipv4 address 102.20.20.20 255.255.255.254
  !
controller Optics0/0/0/20
  description poc_circuit
  transmit-power -100
  fec OFEC
  dwdm-carrier 100MHz-grid frequency 1952000
  DAC-Rate 1x1.25
  !
interface FourHundredGigE0/0/0/20
  bundle id 500 mode active
  !
!
End

```

```

RP/0/RP0/CPU0:ron-poc-8201-1#show controllers optics 0/0/0/20
Mon Oct 17 09:57:25.475 PDT

Controller State: Up
Transport Admin State: In Service

Laser State: On
LED State: Green
FEC State: FEC ENABLED

Optics Status

  Optics Type: QSFPDD 400G ZRP
  DWDM carrier Info: C BAND, MSA ITU Channel=19, Frequency=195.20THz,
  Wavelength=1535.822nm

Alarm Status:
-----
Detected Alarms: None

```


Provision Routed Optical Networking ML Service Using Crosswork Hierarchical Controller

1. If you are performing both router and optical line system provisioning, you must create NMC Cross Links between router optics port and optical line system add/drop port.


Crosswork Hierarchical Controller 8.0 in Routed Optical Networking 3.0 also supports “router only” provisioning which provisions optical parameters on router optics port and IP layer parameters but does not provision OLS.

- a. Select **Link Manager** application.

Figure 32: Crosswork Hierarchical Controller




You get the following initial view that shows the list of Cross Links.




b. Click **Add Cross Link**.


Figure 33:




c. Select the NMC cross link type. Cross Link Manager supports ETH and NMC cross links.




- d. The Link Manager application allows you to select either router DCO port or optical add/drop first. In the following image we filter the ports by the router device that we use for our NMC cross link.




- e. The following image shows the filtered list. Our router, ron-poc-8201-1 has a single ZR+ optics port, select the port and click OK



- f. Like in the previous step, select the second port which is the optical add/drop port. Filter by device as *ron-poc-ols-1* and the Name as *194.000* to filter to the add/drop port




- g. Select the two ports (Ethernet and OCH) in your NMC Cross Link. Click **Add Cross Link**.
(Optional) Add a description



- h. Click the added cross link to see its attributes.

Link Name	Description	Type	Created By	Device A / Port A	Device B / Port B	Status	Method
ron-poc-ols-1/1/CHAN 46 (192.725) / Optics0/0/0/10	Bright ZR+ poc-82... Frequency: 192.725	NMC	Manual	ron-poc-ols-1-roadm / ron-poc-ols-1/1/CHAN 46 (192.725)	ron-poc-8201-1 / Optics0/0/0/10	Unknown	N/A

- i. View the added crosslink in the explorer app by clicking on the link.



- j. Similar to the previous steps, create the second NMC cross link.


Link Manager Cross Links

+ Add Cross Link Validate All Manual

Link Name	Description	Type	Provider	Device A / Port A	Device B / Port B	Status	Method	Last Change
Manual Cross Link ron-poc-8201-1 Optics0/0/...	ron-poc-8201-1 ...	NMC	Manual	ron-poc-8201-1 / Optics0/0/0/22	ron-poc-ols-1-roadm / 1/CHAN 29 (194.000)	Unknown	N/A	2023-04-24 10:23:34 EDT
Manual Cross Link ron-poc-57b1-1 Optics0/0/...	NCS-57B1 0/0/0/...	NMC	Manual	ron-poc-57b1-1 / Optics0/0/0/24	ron-poc-ols-2-roadm / 1/CHAN 29 (194.000)	Unknown	N/A	2023-04-24 10:29:55 EDT

Link Name	Summary	Evidence	History
LINK NAME Manual Cross Link ron-poc-57b1-1 Optics0/0/0/24 to ron-poc-ols-2-roadm 1/CHAN 29 (194.000)	DEVICE A / PORT A ron-poc-57b1-1 / Optics0/0/0/24		DEVICE B / PORT B ron-poc-ols-2-roadm 1/CHAN 29 (194.000)
TIME ADDED N/A	SOURCE Manual		STATUS Unknown
METHOD N/A	LAST CHANGE N/A		DESCRIPTION NCS-57B1 0/0/0/24 to NCS 2000 MD-64 channel 29

k. View the end-to-end network with both crosslinks in the Explorer app.



2. (Optional) Cross-Link Connectivity Verification

- Cross-Link Connectivity Verification is supported on all router platforms and NCS 1010 with MD-32 and BRK-24 modules.
- Connectivity Verification uses NSO CLI NED to modify router port state and TX power, is service affecting.


- When validation starts, Hierarchical Controller continuously checks the RX power on the optical add/drop port. Connectivity Verification is performed in the background.
- a. Configure NMC Validation Settings. Settings are used to control validation, **Wait period to receive samples while on** must be set to 180 seconds, **Wait period to receive samples while off** must be set to 50.

The screenshot shows a 'Settings' dialog box with two tabs: 'ETH validation' and 'NMC Validation'. The 'NMC Validation' tab is active. The settings are as follows:


Setting	Value
Power on [dbm]:	-11
Power off [dbm]:	-50
Timestamp precision [sec]:	2
Number of cycles:	3
Wait period to receive samples while on [sec]:	200
Wait period to receive samples while off [sec]:	50
Sample interval [sec]:	2
Buffer for power off/on [dbm]:	10

A blue 'Confirm' button is located at the bottom of the dialog box, with a mouse cursor hovering over it.


- b. Select a link and click **Validate Link**. Alternatively, you can click **Validate All Manual Links** to perform connectivity verification for all links.




- c. After validation completes, inspect the evidence of either successful or unsuccessful verification. The following image shows a successful verification. Status changes from **Unknown** to **Validated By Shut No Shut**. The time it takes for the ZR/ZR+ to start transmitting after no shut is set is typically 60–80 seconds.




The following image shows a failed verification. There is no change in the optical device port power levels after the **no shut** operation




3. To provision the Routed Optical Networking IP link, perform these steps:
 - a. In the applications bar in the Crosswork Hierarchical Controller, click the **Services Manager** icon.



The Service Manager Application shows you a list of services.



- b. Select the **Point to Point** tab and click **IP Link** from the **Create New P2P** drop-down list to create end to end service between router DCO ports.



The **IP Link Creation** wizard appears.

- c. Enter the Cisco Crosswork Hierarchical Controller service name, description of the router optical controller, and the Link Rate Mode in the **General** tab.
 - Here, we are creating a 1x400G link. In 2x100G, 3x100G, and 4x100G modes, you can choose to create separate IP links or create a Bundle with each channel link added as a member.

Services Manager Tunnels **Point to Point** IP Services

Create New P2P ▶

Name P2P Type Configuration State Creation Date Endpoint A Endpoint B

0 OUT OF 2 ITEMS MATCHING FILTERS

IP Link Creation

1 GENERAL 2 ENDPOINTS 3 ADVANCED 4 SUMMARY

Name*
ron-poc-8201-1_ron-poc-57b1-1_1940000

Description
ron-poc-8201-1 0/0/0/20 to ron-poc-57b1-1 over NCS2K

Link Rate Mode*
400G - 1x400G

Router Configuration Only

X Cancel < Back > Next

Alternatively

- To create a 200G 16-QAM link, Select the 200G – 2x100G link rate mode.

200G 16-QAM allows the use of 200G signals on 50Ghz optical line systems. Default for 200G is QPSK at 60.1Ghz.

IP Link Creation

1 GENERAL 2 ENDPOINTS 3 ADVANCED 4 SUMMARY

Name*
200G legacy mode support

Description
Configure link as 200G 16QAM @ 30.1Ghz

Link Rate Mode*
200G - 2x100G

Router Configuration Only

Alternatively

- To create a Bundle interface, Select a bundle option from the link rate mode drop down list.

You can create a 400G bundle interface (400G Member). Alternatively, 300G-bundle (3X100G Members) and 200G-Bundle (2x100G Members) can be created

IP Link Creation

1
GENERAL

2
ENDPOINTS

3
ADVANCED

4
SUMMARY

Name*
400G-Bundle-Cisco8000-ASR9903

Description

Link Rate Mode*
400G - Bundle

Router Configuration Only

✕ Cancel < Back > Next

(Optional) Check the **Router Configuration Only** check box to configure only the router optical controller and IP information and not the optical line system. This configuration is used when the OCHNC is created outside Cisco Crosswork Hierarchical Controller.

- d. Select the two router ports in the service. This is done by selecting the Site and Port. The transmit power for each endpoint is an optional parameter. The default TX power is used if no value is provided.

- e. Click the magnifying glass icon to select the first router port.

The ports are displayed based on the following criteria:

- Is a ZR/ZR+ interface
- Has no existing optics configuration
- Has a proper NMC cross-connect configured

This page lists all available ZR/ZR+ ports currently unused on all devices. Select the *ron-poc-8201-1 Optics0/0/0/22* port.

Name	Device	Type	Capacity	Description	Admin Status
17 ITEMS					
Optics0/0/0/24	ron-poc-57b1-1	OCH		OCH port of Cisco QSFDD 400G ZRP Plug...	UP
Optics0/0/0/24	ron-ncs57b1-1	OCH		OCH port of Cisco QSFDD 400G ZRP Plug...	UP
Optics0/0/0/14	ron-8201-3ZFH-3	OCH		OCH port of Cisco QDD 400G BRT ZRP Plug...	UP
Optics0/0/0/16	ron-8201-3ZFH-3	OCH		OCH port of Cisco QSFDD 400G ZRP Plug...	UP
Optics0/0/0/0	ron-ncs540-2dd-1	OCH		OCH port of Cisco QSFDD 400G ZRP Plug...	UP
Optics0/0/0/18	ron-8201-1	OCH		OCH port of Cisco QSFDD 400G ZRP Plug...	UP
Optics0/0/0/8	ron-8201-1	OCH		OCH port of Cisco QSFDD 400G ZRP Plug...	DOWN
Optics0/0/0/20	ron-8201-1	OCH		OCH port of Cisco QSFDD 400G ZR Plug...	UP
Optics0/0/0/22	ron-8201-1	OCH		OCH port of Cisco QSFDD 400G ZRP Plug...	UP
Optics0/0/1/4	ron-asr9903-1	OCH		OCH port of 400G ZRP-S QSFDD Module	UP
Optics0/0/1/8	ron-asr9903-1	OCH		OCH port of 400G ZR-S QSFDD Module	UP
Optics0/0/0/10	ron-8201-2	OCH		OCH port of Cisco QSFDD 400G ZRP Plug...	UP
Optics0/0/0/20	ron-8201-2	OCH		OCH port of Cisco QSFDD 400G ZR Plug...	UP
Optics0/0/0/22	ron-poc-8201-1	OCH		OCH port of Cisco QSFDD 400G ZRP Pla...	UP
Optics0/0/0/20	ron-8201-4	OCH		OCH port of Cisco QSFDD 400G ZR Plug...	UP
Optics0/0/3/0	ron-ncs57c3-1	OCH		OCH port of Cisco QDD 400G BRT ZRP Plug...	UP
Optics0/0/2/2	ron-ncs57c3-1	OCH		OCH port of Cisco QSFDD 400G ZRP Plug...	UP

- f. Similar to the previous step, choose *ron-poc-57b1-1 Optics 0/0/0/24* as the second router port.
- g. (Optional) Set the transmit power in dBm on each port. If OLS provisioning is being performed, the OLS controller returns the optical power. If the OLS controller does not return the optical power or **router only** provisioning is being used, the router default power is used.
- h. (Optional) Enter the IP address information for interfaces. If IP addresses are not entered, ZR/ZR+ router optical configuration happens; however, IP addresses are not configured.
- i. Click **Next** to move to **Advanced** configuration.

IP Link Creation

1
GENERAL

2
ENDPOINTS

3
ADVANCED

4
SUMMARY

Transmit Power [dBm]

ENDPOINT B

Site B

Port B*

Transmit Power [dBm]

LINK #1 IP ADDRESSES

IP Address A (CIDR)

IP Address B (CIDR)

✕ Cancel

- j. (Optional) Set the Frequency. If optical provisioning is being performed, the OLS controller can return the frequency to be used, and it may be omitted. If **router only** provisioning is being performed, the Frequency must be specified.
- k. (Optional) Set the DAC rate. A DAC rate setting can be used to enable OpenZR+ compatibility mode, disabling TX shaping and enhanced modem mode. See [OpenZR+ Compatibility Mode](#) for more information on mode support.

IP Link Creation

1 GENERAL 2 ENDPOINTS 3 ADVANCED 4 SUMMARY

Add to existing LAG

FREQUENCY

L Band

C Band

Frequency THz

Digital-to-Analog Converter (DAC) rate

1 X 1

1 X 1.25

Set Path Preferences

Min Path Criteria

▼ **Include Nodes or Links**

✕ Cancel

- I. (Optional) Set links or nodes to include/exclude in the optical path. This setting is not available in **router only** provisioning.

- m. (Optional) To add the new link or set of links to an existing Bundle LAG interface configured on the routers, choose the bundle from the **Add to existing LAG** drop-down.

IP Link Creation

1 GENERAL 2 ENDPOINTS **3 ADVANCED** 4 SUMMARY

✓ Add to existing LAG

Bundle-Ether1 to Bundle-Ether1

L Band

C Band

Frequency THz*
195.200

Digital-to-Analog Converter (DAC) rate

Modulation

Set Path Preferences

Min Path Criteria
Latency

▼ Include Nodes or Links

Select Node or Link

× Cancel < Back > Next

- n. (Optional) If you are configuring a 200G 16-QAM link, set the DAC rate to 1x1.25.
200G link rate mode enables the **Modulation** selection drop-down. Modulation selection is not available in any other mode. Select the 16 QAM (30GHz) modulation.

IP Link Creation

1
GENERAL

2
ENDPOINTS

3
ADVANCED

4
SUMMARY

Add to existing LAG ▼

FREQUENCY

L Band

C Band

Frequency THz

Digital-to-Analog Converter (DAC) rate

Modulation

✓ 8 QAM

16 QAM

QPSK

▼ Include Nodes or Links

🔍

✕ Cancel< Back> Next

- o. Click **Next** to review the final configuration. Verify the router endpoint and optical line system parameters. Click **Finish** to start provisioning, or click **Save** to save for later provisioning.

IP Link Creation

1
GENERAL

2
ENDPOINTS

3
ADVANCED

4
SUMMARY

Name: ron-poc-8201-1_ron-poc-57b1-1_1940000

Description: ron-poc-8201-1 0/0/0/20 to ron-poc-57b1-1 over NCS2K

▼ **Endpoint A**

Port: ron-poc-8201-1 - Optics0/0/0/22

Transmit Power: -10.0 dBm

▼ **Endpoint B**

Port: ron-poc-57b1-1 - Optics0/0/0/24

Transmit Power: -10.0 dBm

Link Rate Mode: 400G - 1x400G

Frequency: 194.0 THz

DAC rate: -

Modulation: -

Path Criteria: Latency

Optical Excluded List: -

Included List: -

Disjoint From Links: -

✕ Cancel

< Back
> Finish
Save

The following image shows a sample summary for a 200G 16-QAM link.

IP Link Creation

1
GENERAL

2
ENDPOINTS

3
ADVANCED

4
SUMMARY

Name: 200G legacy mode support
Description: Configure link as 200G 16QAM @ 30.1Ghz

▼ **Endpoint A**
Port: ron-ncs540-2dd-1 - Optics0/0/0/0
Transmit Power: -

▼ **Endpoint B**
Port: ron-ncs57b1-1 - Optics0/0/0/24
Transmit Power: -

Link Rate Mode: 200G - 2x100G
Frequency: 195.2 THz
DAC rate: 1 X 1.25
Modulation: MT_16QAM

Path Criteria: Latency
Optical Excluded List: -
Included List: -
Disjoint From Links: -

✕ Cancel< Back> FinishSave

- p. Go to Services Manager to view provisioning progress.

Click the **Operations** > **Logs** tab to view the provisioning API calls used and responses. The logs show API calls and responses for both optical line system provisioning via Cisco Optical Network Controller and router provisioning via Crosswork Network Controller.

The screenshot shows the 'Services Manager' interface with the 'Point to Point' tab selected. A table lists service links, with one link in 'IN PROGRESS' state. Below the table, the 'Operations' tab is active, showing a log for the selected link. The log indicates a 'Normal Flow' with the following steps:

- Adapter #1: onc-poc-90 ✓
- create service
- create service response


If the provisioning is successful, the **Configuration State** field changes to INSTALLED state and the **Operational State** field changes to UP state.

The screenshot shows the 'Services Manager' interface with the 'Point to Point' tab selected. The table now shows the service link in 'INSTALLED' state. Below the table, the 'Summary' tab is active, displaying the following details for the service link:

- GUID:** S:/7d4cd2016cd64eb7ad44a1269d2d45b
- Name:** ron-poc-8201-1_ron-poc-57b1-1_1940000
- Creation Time:** 24-04-2023 14:44:21 UTC
- Last Changed:** 24-04-2023 14:44:21 UTC
- Template Name:** default-template
- Service Links:** 100.28.30.23 to 100.28.30.22
- IP Address Assignment Policy:** User Allocated
- Is Bundle:** No
- Channel Config:** 1 X 400G
- Path Criteria:** Latency

The **Summary** tab displays the new service link.

- q. Verify the end to end link across both IP and optical layers in the Explorer view.



4. Use the Link Assurance application to verify the end to end path and relevant PM data. Select a link or port to see data on the ZRM, OCH, and OTS layers.

The screenshot displays the Link Assurance interface for inspecting a logical link. The main panel shows a network diagram with two sites: Charleston and Jacksonville. Charleston has a router 'ron-poc-5701-1' and two optical devices 'ron-poc-ols-2...' and 'ron-poc-ols-1...'. Jacksonville has a router 'ron-poc-8201-1'. The diagram shows connections between the routers and the optical devices. The interface also includes a sidebar with navigation icons, a search bar, and a table of items.

Name	Type	Status
100.28.30.23 to 100.28.30.22 L3 Log...	L3 Log...	UP
Optics0/0/0/24 to Optics0/0/0/22	OCH	UP

Summary		Performance		Events	
Name	Layer	Admin Status	Operational Status	Endpoint A	
Fiber-1	OTS	UP	UP	ron-poc-ols-1-roadm	
Endpoint Z		Port A Tx Power (dbm)	Port Z Tx Power (dbm)	Port A Rx Power (dbm)	Port Z Rx Power (dbm)
ron-poc-ols-2-roadm		Min: -0.50	Min: 2.60	Min: -4.00	Min: -7.30
		Average: -0.50	Average: 2.60	Average: -4.00	Average: -7.30
		Max: -0.40	Max: 2.60	Max: -4.00	Max: -7.20

Operate Phase

To monitor the ZR/Z+ optics:

1. Use either CLI commands or EPNM to monitor router ZR/Z+ optics for proper operation. See [Monitor ZR or ZR+ Optics Using EPNM, on page 70](#).
2. (Optional) Setup router ZR/ZR+ optics data collection in CW Health Insights. See [Monitor Performance of ZR/ZR+ Optics Using KPIs, on page 79](#).


To monitor NCS 1010, use Cisco Optical Network Controller and Cisco Optical Site Manager:

- [Monitoring using Cisco Optical Network Controller](#)
- [Network and Circuit Monitoring using Workspaces in Cisco Optical Network Controller](#)
- [Monitoring Alarms in Cisco Optical Network Controller](#)
- [Fault Monitoring using Cisco Optical Site Manager](#)

Monitor ZR or ZR+ Optics Using EPNM


This section adds the 8201 router to EPNM for monitoring the PM parameters on the ZR or ZR+ optics.

1. To add a new device to EPNM choose **Inventory > Device Management > Network Devices**. Click **Routers** or a subgroup if it is already defined in the left panel.



521942

- Click the **+** icon above the Network Devices table, then choose **Add Device**.



521943

- Configure the General, SNMP, and SSH parameters as seen in that following figures. Click **Verify Credentials** to validate that Cisco EPN Manager can reach the device. Click **Add** to add the device to EPNM.

Add Device

- General ✔
- SNMP
(Optional if TL1 is configured)
- Telnet/SSH
- HTTP/HTTPS
- TL1
- Civic Location

General Parameters

- IP Address
- DNS Name
- License Level
- Device Role
- Add to Group
- Credential Profile

Add
Verify Credentials
Cancel

521945

Add Device

* General ✔
 * SNMP ✔
 (Optional if TL1 is configured)
 Telnet/SSH ✔
 HTTP/HTTPS
 TL1
 Civic Location

Telnet/SSH Parameters

Protocol

* Port

* Timeout (secs)

Username

Password

Confirm Password

Enable Password ?

Confirm Enable Password

* Note: Not providing Telnet/SSH credentials may result in partial collection of inventory data.

521946

Add Device

* General ✔
 *** SNMP** ✔
 (Optional if TL1 is configured)
 Telnet/SSH ✔
 HTTP/HTTPS
 TL1
 Civic Location

* SNMP Parameters

Version

* SNMP Retries

* SNMP Timeout (secs)

* SNMP Port

* Read Community ?


* Confirm Read Community

Write Community ?

Confirm Write Community


521947

- To open the chassis view from the Network devices table, click the device name link. The following figure displays the chassis view of the 8201 router.



521948

5. Click the QSFP-DD ZR+ port to see specific data about that port.



521949

Here you can view the port and specific optical channel and CoherentDSP entities.

Front8: FourHundredGigE8-IDPRM
ron-8201-1 / Rack_0 / Front1: GRRPU-CPU0 / Front8: FourHundredGigE8-IDPRM

Alarms Configuration Inventory Interfaces Circuits

Type: All Interfaces Property All Properties Selected 0 / Total 2

Alarm	Name	Type	Admin Status	Operational Status	Transport Admi
<input type="radio"/>	Cleared CoherentDSP0/0/8	OTNOTU	Up	Up	IS
<input type="radio"/>	Cleared Optics0/0/8	OPTICALCHANNEL	Up	Up	IS

521950

- Clicking the additional information icon for the optical channel and then the **Optical Physical** measurement tab displays the relevant optical PM values such as **RX/TX signal power** and **OSNR** values.

Interface 360°
Auto-Refresh Off

Optics0/0/8

Interface Type: OPTICALCHANNEL
Transport Admin State: IS
Device Name: ron-8201-1
Adjacent Interface(s): N/A


Alarms Optical Physical FEC Interface Circuits/VCs

Total 2

Timestamp	OSNR	RX-POWER	TX-POWER	LBC	DGD	PCR
16:02:55, 24-Jun-2021 EST	31.50	-13.36 dBm	-10.53 dBm	0	2.00	0
16:02:36, 24-Jun-2021 EST	31.70	-13.28 dBm	-10.55 dBm	0	2.00	0

521951


- Clicking the additional information icon for the coherent DSP and then the **FEC** measurement tab displays the relevant coherent DSP FEC statistics such as **PreFEC Bit Error Rate**, **Bit Error Rate Count (BIEC)**, and **Uncorrected Words (UCW)**. The UCW value must remain 0.



521952


The following figures display the current and historical performance monitoring data in EPNM that is specific to the ZR or ZR+ optics.

Figure 34: Optical Physical Parameters




521883

Figure 35: Historical Optical Physical Parameters




521884

Figure 36: Historical Optical Physical Parameters




521885

Figure 37: Historical Optical Physical Parameters



521888

Figure 38: FEC Parameters




521881

Figure 39: Historical FEC Parameters



521889

Figure 40: Historical FEC Parameters



521890

Figure 41: Historical OTN Parameters





Figure 42: Historical OTN Parameters



Monitor Performance of ZR/ZR+ Optics Using KPIs

Perform the following steps to create KPI Profiles in Health Insights and enable them on the devices to monitor network health.



Note Plan which Cisco-supplied KPIs you want to begin using, based on each device's function and the device performance characteristics you want to monitor. Review the Cisco-supplied KPIs documented in [List of Health Insights KPIs](#). In the following image, you see the available default L1 optics KPIs.

KPI Name	Category	Description	Linked Playbook
<input type="checkbox"/> Layer 1 optical alarms	Layer1-Optics	Monitors per-port optical alarms	
<input type="checkbox"/> Layer 1 optical errors	Layer1-Optics	Monitors per-port Layer 1 errors; generates ale...	
<input type="checkbox"/> Layer 1 optical FEC errors	Layer1-Optics	Monitors per-port optical FEC errors; generate...	
<input type="checkbox"/> Layer 1 optical power	Layer1-Optics	Monitors per-port optical power; generates ale...	
<input type="checkbox"/> Layer 1 optical temperature	Layer1-Optics	Monitors per-port optical temperature; generat...	
<input type="checkbox"/> Layer 1 optical voltage	Layer1-Optics	Monitors per-port optical voltage; generates al...	

521913

1. Group the relevant KPIs to form a KPI Profile. A KPI profile can have many different KPIs assigned. In this case, the focus is only on some specific optics KPIs to add to the **optics_profile** KPI profile.


Category	KPI	Summary
optics		
<input type="checkbox"/> Layer1-Optics	Layer 1 optical alarms	Monitors per-port optical alarms
<input type="checkbox"/> Layer1-Optics	Layer 1 optical errors	Monitors per-port Layer 1 errors; generates alert when error rates exceeds the configured threshold
<input type="checkbox"/> Layer1-Optics	Layer 1 optical FEC errors	Monitors per-port optical FEC errors; generates an alert when FEC errors exceeds the configured th...
<input checked="" type="checkbox"/> Layer1-Optics	Layer 1 optical power	Monitors per-port optical power; generates alert when power levels exceeds the configured threshold
<input checked="" type="checkbox"/> Layer1-Optics	Layer 1 optical temperature	Monitors per-port optical temperature; generates alert when temperature exceeds the configured th...
<input checked="" type="checkbox"/> Layer1-Optics	Layer 1 optical voltage	Monitors per-port optical voltage; generates alert when voltages exceeds the configured threshold

521914

See [Create a New KPI Profile](#).


2. Enable the appropriate KPI Profiles on the devices you want to monitor. From the main menu, choose **Performance Alerts > Enable/Disable KPI Profiles**. Check the checkboxes of all the nodes to which the profile must be applied to, and click **Enable KPI Profiles**.

Multiple nodes may be selected. In the following figure, we are applying the KPI profile to a single node.



521915

3. Select the optics_profile KPI profile that was created in the previous step and click next to finalize enabling the KPI for the selected device.



521916


4. The following image displays the final page before enabling the KPI profile for the router. After you click **Enable**, the appropriate configuration is applied to the router to begin streaming the telemetry sensors data for the selected optical KPIs.

521917

See [Enable KPI Profiles on Devices](#).

- To view alerts from network devices, see [View Alerts for Network Devices](#).

The following figure displays the RX and TX power of the QDD-400G-ZR-S transceiver.



521918

Optimization Phase

The optimization phase involves:

- Return to planning stage.
- Continue to add or change circuits on the network to match packet demands.