



Release-specific Caveats and Workarounds

This section lists the caveats and workarounds when setting up or upgrading the software for each Cisco IOS XR release.

- [Caveats and Workarounds, on page 1](#)

Caveats and Workarounds

Release 7.4.1

There are no caveats for system upgrade to Cisco IOS XR Release 7.4.1.

Release 7.4.2

CSCvp19524: When downgrading from Cisco IOS XR Release 7.4.2 to any release lower than Cisco IOS XR Release 7.0.1, it is necessary to remove AAA user configurations from SYSADMIN/XR VMs before proceeding with the downgrade.

Release 7.5.1

CSCvp19524: When downgrading from Cisco IOS XR Release 7.5.1 to any release lower than Cisco IOS XR Release 7.0.1, it is necessary to remove AAA user configurations from SYSADMIN/XR VMs before proceeding with the downgrade.

Release 7.5.2

CSCvp19524: When downgrading from Cisco IOS XR Release 7.5.2 to any release lower than Cisco IOS XR Release 7.0.1, it is necessary to remove AAA user configurations from SYSADMIN/XR VMs before proceeding with the downgrade.

Release 7.6.2

CSCvp19524: When downgrading from Cisco IOS XR Release 7.6.2 to any release lower than Cisco IOS XR Release 7.0.1, it is necessary to remove AAA user configurations from SYSADMIN/XR VMs before proceeding with the downgrade.

Release 7.7.2

CSCvp19524: When downgrading from Cisco IOS XR Release 7.7.2 to any release lower than Cisco IOS XR Release 7.0.1, it is necessary to remove AAA user configurations from SYSADMIN/XR VMs before proceeding with the downgrade.

Release 7.8.1

CSCvp19524: When downgrading from Cisco IOS XR Release 7.8.1 to any release lower than Cisco IOS XR Release 7.0.1, it is necessary to remove AAA user configurations from SYSADMIN/XR VMs before proceeding with the downgrade.

Release 7.8.2

CSCvp19524: When downgrading from Cisco IOS XR Release 7.8.2 to any release lower than Cisco IOS XR Release 7.0.1, it is necessary to remove AAA user configurations from SYSADMIN/XR VMs before proceeding with the downgrade.

Release 7.9.1

CSCvp19524: When downgrading from Cisco IOS XR Release 7.9.1 to any release lower than Cisco IOS XR Release 7.0.1, it's necessary to remove AAA user configurations from SYSADMIN/XR VMs before proceeding with the downgrade.

1. **CSCwd30936:** When downgrading from Cisco IOS XR Release 7.9.1 to an older release, the "ema_server_sdr" process may crash.

Release 7.9.2

1. **CSCvp19524:** When downgrading from Cisco IOS XR Release 7.9.2 to any release lower than Cisco IOS XR Release 7.0.1, it is necessary to remove AAA user configurations from SYSADMIN/XR VMs before proceeding with the downgrade.
2. **CSCwd30936:** When downgrading from Cisco IOS XR Release 7.9.2 to an older release, the "ema_server_sdr" process may crash.

Release 7.10.1

1. **CSCvp19524:** When downgrading from Cisco IOS XR release 7.10.1 to any release lower than Cisco IOS XR Release 7.0.1, it is necessary to remove AAA user configurations from SYSADMIN/XR VMs before proceeding with the downgrade.
2. **CSCwd30936:** When downgrading from Cisco IOS XR Release 7.10.1 to an older release, the "ema_server_sdr" process may crash.
3. **SR695094155:** When upgrading the software version of an ASR 9000 router with an mLACP/ICCP Redundancy Model setup, ensure that both the active and standby nodes are upgraded to the same IOS XR version.