



# New and Changed Information for Segment Routing Features

This table summarizes the new and changed feature information for the *Segment Routing Configuration Guide for Cisco ASR 9000 Aggregation Services Routers*, and lists where they are documented.

- [New and Changed Segment Routing Features](#), on page 1

## New and Changed Segment Routing Features

### Segment Routing Features Added or Modified in IOS XR Release 6.3.x

Feature	Description	Introduced/Changed in Release	Where Documented
Layer 2 Adjacency SIDs	This feature was introduced.	Release 6.3.2	<i>Configure Segment Routing for IS-IS Protocol</i>
Explicit Binding SID	This feature was introduced.	Release 6.3.2	<i>Configure SR-TE Policies</i>
Segment Routing Local Block	This feature was introduced.	Release 6.3.1	<i>Configure Segment Routing Global Block and Segment Routing Local Block</i>
Segment Routing Global Block	The maximum size of the Segment Routing Global Block (SRGB) was increased from 65536 to 262,143.	Release 6.3.1	<i>Configure Segment Routing Global Block and Segment Routing Local Block</i>
Bandwidth-Based Local UCMP	This feature was introduced.	Release 6.3.1	<i>Configure Segment Routing for IS-IS Protocol</i>
Manually Allocated Adjacency SIDs	This feature was introduced.	Release 6.3.1	<i>Configure Segment Routing for IS-IS Protocol</i>

<b>Feature</b>	<b>Description</b>	<b>Introduced/Changed in Release</b>	<b>Where Documented</b>
OAM for BGP-SR	This feature was introduced.	Release 6.3.1	<i>Using Segment Routing OAM</i>