



What's New for Cisco IOS XE Dublin 17.12.x

- [What's New in Hardware for IOS XE Dublin 17.12.3, on page 1](#)
- [What's New in Software for IOS XE Dublin 17.12.3, on page 1](#)
- [What's New in Hardware for IOS XE Dublin 17.12.2a, on page 1](#)
- [What's New in Software for IOS XE Dublin 17.12.2a, on page 1](#)
- [What's New in Hardware for Cisco IOS XE Dublin 17.12.1, on page 2](#)
- [What's New in Software for Cisco IOS XE Dublin 17.12.1, on page 2](#)

What's New in Hardware for IOS XE Dublin 17.12.3

There are no new hardware features introduced for this release.

What's New in Software for IOS XE Dublin 17.12.3

There are no new software features introduced for this release.

What's New in Hardware for IOS XE Dublin 17.12.2a

There are no new hardware features introduced for this release.

What's New in Software for IOS XE Dublin 17.12.2a

There are no new software features introduced for this release.

What's New in Hardware for Cisco IOS XE Dublin 17.12.1

Optics	Description
Optics	<p>This release launches the following new optics on selective hardware within the product portfolio. For details refer to the Transceiver Module Group (TMG) Compatibility Matrix.</p> <p>Cisco 10GBASE Dense Wavelength-Division Multiplexing Small Form-Factor Pluggable (SFP+):</p> <ul style="list-style-type: none"> • DWDM-SFP10G-C-S

What's New in Software for Cisco IOS XE Dublin 17.12.1

Feature	Description
Carrier Ethernet	
Service Instance as Track Client	Track can be configured to check for reachability to IBR(Upstream router). If IBR is not reachable, the service instance is kept in admin down state. This avoids traffic drop until the route is installed which optimizes the convergence. Currently, IOS XE platforms do not have options to shutdown EFP based on track reachability.
CEM	
BGP PIC with CEM	BGP PIC extends support to TDM CEM pseudowire to facilitate faster, sub-second BGP convergence and to improve fast failover.
CEM Description Command	You can add description for a cem group up to 200 characters using the description command.
DCC CLNP Interworking	This feature enables you to exchange Network Management System (NMS) management traffic between OSI Data Communication Channel (DCC) and Ethernet ports over Connectionless Network Protocol (CLNP) interworking. With this, you can maintain in-band communication between old Add/Drop Multiplexer (ADM) equipments to be managed from NMS.
Layer 2	
MACsec support with PTP for 1GE A900-IMA8CS1Z-M Interface Module	You can now configure MACsec support with Precision Time Protocol (PTP) packets for mitigating security vulnerabilities on a router.