

## **About this Guide**



**Note** The documentation set for this product strives to use bias-free language. For purposes of this documentation set, bias-free is defined as language that does not imply discrimination based on age, disability, gender, racial identity, ethnic identity, sexual orientation, socioeconomic status, and intersectionality. While any existing biased terms are being substituted, exceptions may be present in the documentation due to language that is hardcoded in the user interfaces of the product software, language used based on RFP documentation, or language that is used by a referenced third-party product.

This guide provides details about the CLI commands available for the Cloud Native Broadband Network Gateway (cnBNG) Control Plane (CP).

• Conventions Used, on page i

## **Conventions Used**

The following tables describe the conventions used throughout this documentation.

Notice Type	Description		
Information Note	Provides information about important features or instructions.		
Caution	Alerts you of potential damage to a program, device, or system.		
Warning	Alerts you of potential personal injury or fatality. May also alert you of potential electrical h		
Typeface Conventions		Description	
Text represented as a screen		This typeface represents displays that appear on your terminal screen, for exam	

display	Login:
Text represented as commands	This typeface represents commands that you enter, for example:
	show ip access-list
	This document always gives the full form of a command in lowercase letters. Co are not case sensitive.

I

Typeface Conventions	Description
Text represented as a <b>command</b> <i>variable</i>	This typeface represents a variable that is part of a command, for example: <b>show card</b> <i>slot_number</i> <i>slot_number</i> is a variable representing the desired chassis slot number.
Text represented as menu or sub-menu names	This typeface represents menus and sub-menus that you access within a software application, for example: Click the <b>File</b> menu, then click <b>New</b>