infra

- OpenAPI, on page 1
- Info, on page 1
- Servers, on page 1
- tags, on page 1
- Paths, on page 2
- Components, on page 3768

OpenAPI

OpenAPI Version: 3.0.1

Info

```
Title: tailf-mobile-infra
Description: ''
Version: '2021-02-19'
```

Servers

```
  URL: /restconf
```

tags

```
- Name: root
  Description: root resources
- Name: operations
  Description: operations resources
- Name: data
  Description: data resources
```

```
- Name: get
  Description: get resources
- Name: head
  Description: head resources
- Name: post
  Description: post resources
- Name: patch
  Description: patch resources
- Name: put
  Description: put resources
- Name: options
  Description: options resources
- Name: delete
  Description: delete resources
```

Paths

/

```
get:

  Tags:
  - root
  - get
  Operation ID: root_get

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/root'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - root
  - head
  Operation ID: root_head

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/operations

```
get:

  Tags:
  - operations
  - get
  Operation ID: operations_get

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/operations'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
```

/yang-library-version

```
get:

  Tags:
  - yang-library-version
  - get
  Operation ID: yang_library_version_get

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/yang-library-version'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - yang-library-version
  - head
  Operation ID: yang_library_version_head

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data


```
get:

  Tags:
  - data
  - get
  Operation ID: data_get

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data-put-patch'
    Required/Optional: true

  Responses:
    '201':
      Description: Created
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: data
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data-post'
    Required/Optional: true

  Responses:
    '201':
      Description: Created
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: data
head:

  Tags:
  - data
  - head
  Operation ID: data_head

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data-put-patch'
    Required/Optional: true

  Responses:
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: data
```

/data/tailf-mobile-infra:sessions

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_sessions_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_sessions'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_sessions_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_sessions'
```

```
    Required/Optional: true

  Responses:
    '201':
      Description: container sessions created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sessions
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_sessions_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_sessions-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container sessions created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sessions
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_sessions_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_sessions_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_sessions_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_sessions_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_sessions'
    Required/Optional: true

  Responses:
    '204':
      Description: container sessions updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sessions
```

/data/tailf-mobile-infra:sessions/commit-pending

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_sessions_commit_pending_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_sessions_commit-pending'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_sessions_commit_pending_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:sessions/commit-pending={commit-pending-p odInstance},{commit-pending-grInstance}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_get


    Parameters:
    - Name: commit-pending-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: commit-pending-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_head


    Parameters:
    - Name: commit-pending-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: commit-pending-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:sessions/commit-pending={commit-pending-p odInstance},{commit-pending-grInstance}/podInstance

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_podInstance_get


  Parameters:
  - Name: commit-pending-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: commit-pending-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_podInstance'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_podInstance_head


  Parameters:
  - Name: commit-pending-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: commit-pending-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:sessions/commit-pending={commit-pending-p odInstance},{commit-pending-grInstance}/grInstance

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_grInstance_get


  Parameters:
  - Name: commit-pending-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: commit-pending-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_grInstance'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_grInstance_head


    Parameters:
    - Name: commit-pending-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: commit-pending-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:sessions/commit-pending={commit-pending-p odInstance},{commit-pending-grInstance}/count

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_count_get


  Parameters:
  - Name: commit-pending-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: commit-pending-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_count'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_count_head


    Parameters:
    - Name: commit-pending-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: commit-pending-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:sessions/commit-pending={commit-pending-p odInstance},{commit-pending-grInstance}/pendingCommit

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_pendingCommit_get


  Parameters:
  - Name: commit-pending-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: commit-pending-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_pendingCommit'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_pendingCommit_head


    Parameters:
    - Name: commit-pending-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: commit-pending-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:sessions/commit-pending={commit-pending-p odInstance},{commit-pending-grInstance}/dbBinarySize

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_dbBinarySize_get


  Parameters:
  - Name: commit-pending-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: commit-pending-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_dbBinarySize'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_dbBinarySize_head


  Parameters:
  - Name: commit-pending-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: commit-pending-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:sessions/commit-pending={commit-pending-p odInstance},{commit-pending-grInstance}/lastDbSyncTime

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_lastDbSyncTime_get


  Parameters:
  - Name: commit-pending-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: commit-pending-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_lastDbSyncTime'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_sessions_commit_pending_commit_pending_podInstance_commit_pending_grInstance_lastDbSyncTime_head


    Parameters:
    - Name: commit-pending-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: commit-pending-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:sessions/affinity

```
get:
```

```
Tags:
- data
- get
Operation ID: data_tailf_mobile_infra_sessions_affinity_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
           Reference: '#/components/schemas/data_tailf-mobile-infra_sessions_affinity'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_sessions_affinity_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:sessions/affinity={affinity-podInstance}:

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_sessions_affinity_affinity_podInstance_get

  Parameters:
  - Name: affinity-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_sessions_affinity_affinity-podInstance'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_sessions_affinity_affinity_podInstance_head

  Parameters:
  - Name: affinity-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:sessions/affinity={affinity-podInstance}/ podInstance

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_sessions_affinity_affinity_podInstance_podInstance_get

    Parameters:
    - Name: affinity-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_sessions_affinity_affinity-podInstance_podInstance'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_sessions_affinity_affinity_podInstance_podInstance_head

  Parameters:
  - Name: affinity-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:sessions/affinity={affinity-podInstance}/ count

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_sessions_affinity_affinity_podInstance_count_get


  Parameters:
  - Name: affinity-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_sessions_affinity_affinity-podInstance_count'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_tailf_mobile_infra_sessions_affinity_affinity_podInstance_count_head


  Parameters:
  - Name: affinity-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_peers_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_peers'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_peers_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_peers'
      Required/Optional: true

    Responses:
      '201':
        Description: container peers created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
```

```
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: peers
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_peers_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_peers-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container peers created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: peers
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_peers_delete
```

```
  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_peers_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_peers_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_peers_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_peers'
    Required/Optional: true

  Responses:
    '204':
      Description: container peers updated
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: peers
```

/data/tailf-mobile-infra:peers/all

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_peers_all_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_peers_all'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_peers_all_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint} ,{all-localAddress},{all-peerAddress}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_get


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_head


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-localAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-peerAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint} ,{all-localAddress},{all-peerAddress}/grInstance

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_grInstance_get


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_grInstance'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_grInstance_head


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint} ,{all-localAddress},{all-peerAddress}/endpoint

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_endpoint_get


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_endpoint'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_endpoint_head


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
    - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint} ,{all-localAddress},{all-peerAddress}/localAddress

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_localAddress_get


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_localAddress'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_localAddress_head


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint},{all-localAddress},{all-peerAddress}/peerAddress

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_peerAddress_get


  Parameters:
  - Name: all-grInstance
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_peerAddress'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_peerAddress_head


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint} ,{all-localAddress},{all-peerAddress}/direction

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_direction_get


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_direction'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_direction_head


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
```

```
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint} ,{all-localAddress},{all-peerAddress}/podInstance

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_podInstance_get
```

```
Parameters:
- Name: all-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_podInstance'

    '204':
      Description: No Content
      Content: {}
    '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_podInstance_head


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint} ,{all-localAddress},{all-peerAddress}/type

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_type_get


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-localAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_type'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_type_head
```

```
Parameters:
- Name: all-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint} ,{all-localAddress},{all-peerAddress}/connectedTime

```
get:
```

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_connectedTime_get

Parameters:
- **Name**: all-grInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: all-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_connectedTime'
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_connectedTime_head


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-localAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint} ,{all-localAddress},{all-peerAddress}/rpc

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_rpc_get


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-localAddress
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_rpc'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
```

```
    - head
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_rpc_head


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-localAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-peerAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
```

```
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint} ,{all-localAddress},{all-peerAddress}/additionalDetails

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_additionalDetails_get


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
```

```
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_additionalDetails'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_additionalDetails_head


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
- Name: all-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint} ,{all-localAddress},{all-peerAddress}/interfaceName

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_interfaceName_get


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_interfaceName'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_interfaceName_head


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-localAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-peerAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
```

```
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:peers/all={all-grInstance},{all-endpoint} ,{all-localAddress},{all-peerAddress}/vrf

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_vrf_get


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-localAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-peerAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_vrf'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_peers_all_all_grInstance_all_endpoint_all_localAddress_all_peerAddress_vrf_head


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-localAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-peerAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:rpc

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_rpc_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
```

```
          Reference: '#/components/schemas/data_tailf-mobile-infra_rpc'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_rpc_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_rpc'
    Required/Optional: true

  Responses:
    '201':
      Description: container rpc created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: rpc
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_rpc_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_rpc-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container rpc created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: rpc
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_rpc_delete

  Responses:
```

```
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_rpc_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_rpc_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_rpc_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_rpc'
    Required/Optional: true

  Responses:
    '204':
      Description: container rpc updated
      Content: {}
    '400':
```

```
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: rpc
```

/data/tailf-mobile-infra:rpc/all

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_rpc_all_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_rpc_all'
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_rpc_all_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all -remoteAddress}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_get

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        '200':
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
'#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress'

        '204':
          Description: No Content
          Content: {}
        '400':
          Description: Bad Request
          Content: {}
        '401':
          Description: Unauthorized
          Content: {}
        '404':
          Description: Not Found
          Content: {}
        '405':
          Description: Method Not Allowed
          Content: {}
        '409':
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    head:

      Tags:
      - data
      - head
      Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_head
```

```
Parameters:
- Name: all-podInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all -remoteAddress}/podInstance

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_podInstance_get

    Parameters:
    - Name: all-podInstance
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_podInstance'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_podInstance_head


    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
```

```
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all -remoteAddress}/name

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_name_get

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_name'

    '204':
      Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_name_head

  Parameters:
  - Name: all-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all -remoteAddress}/remoteAddress

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_remoteAddress_get


    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_remoteAddress'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_remoteAddress_head


    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: all-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all -remoteAddress}/remoteHost

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_remoteHost_get

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: all-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_remoteHost'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_remoteHost_head

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all -remoteAddress}/type

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_type_get

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: all-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_type'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:
```

```
    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_type_head

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all -remoteAddress}/setName

```
get:

  Tags:
  - data
  - get
```

```
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_setName_get

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_setName'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_setName_head

  Parameters:
  - Name: all-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all -remoteAddress}/status

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_status_get

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_status'

    '204':
      Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_status_head

  Parameters:
  - Name: all-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all -remoteAddress}/connectedTime

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_connectedTime_get


  Parameters:
  - Name: all-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_connectedTime'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_connectedTime_head


    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
    Schema:
      Type: string
      Format: string
  - Name: all-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all -remoteAddress}/disconnectedTime

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_disconnectedTime_get


    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: all-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_disconnectedTime'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_disconnectedTime_head


    Parameters:
    - Name: all-podInstance
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all -remoteAddress}/monitorRPCHost

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_monitorRPCHost_get


    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_monitorRPCHost'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
```

```
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_monitorRPCHost_head


    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all -remoteAddress}/processingInstanceInfo

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_processingInstanceInfo_get


  Parameters:
  - Name: all-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_processingInstanceInfo'

    '204':
```

```
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_processingInstanceInfo_head


  Parameters:
  - Name: all-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-remoteAddress
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
      - report-all
      - trim
      - explicit
      - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all -remoteAddress}/version

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_version_get

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-remoteAddress
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_version'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_version_head

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: all-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:rpc/all={all-podInstance},{all-name},{all -remoteAddress}/vrf

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_vrf_get

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-remoteAddress
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_vrf'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_rpc_all_all_podInstance_all_name_all_remoteAddress_vrf_head

    Parameters:
    - Name: all-podInstance
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-remoteAddress
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:resources

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resources_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
```

```
            Reference: '#/components/schemas/data_tailf-mobile-infra_resources'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_resources_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_resources'
      Required/Optional: true

    Responses:
      '201':
        Description: container resources created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: resources
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_resources_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_resources-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container resources created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: resources
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_resources_delete

  Responses:
```

```
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resources_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resources_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_resources_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_resources'
      Required/Optional: true

    Responses:
      '204':
        Description: container resources updated
        Content: {}
      '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: resources
```

/data/tailf-mobile-infra:resources/info

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resources_info_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_resources_info'
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resources_info_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:resources/info={info-podInstance}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resources_info_info_podInstance_get

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_resources_info_info-podInstance'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_resources_info_info_podInstance_head

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:resources/info={info-podInstance}/podInst ance

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_resources_info_info_podInstance_podInstance_get


  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_resources_info_info-podInstance_podInstance'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:
```

```
Tags:
- data
- head
Operation ID: data_tailf_mobile_infra_resources_info_info_podInstance_podInstance_head

Parameters:
- Name: info-podInstance
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:resources/info={info-podInstance}/cpuUsag e

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resources_info_info_podInstance_cpuUsage_get

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_resources_info_info-podInstance_cpuUsage'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_resources_info_info_podInstance_cpuUsage_head

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:resources/info={info-podInstance}/totalNo deMemoryInMB

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_resources_info_info_podInstance_totalNodeMemoryInMB_get

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resources_info_info-podInstance_totalNodeMemoryInMB'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
```

```
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_resources_info_info_podInstance_totalNodeMemoryInMB_head

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:resources/info={info-podInstance}/usedPod MemoryInMB

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_resources_info_info_podInstance_usedPodMemoryInMB_get

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_resources_info_info-podInstance_usedPodMemoryInMB'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_resources_info_info_podInstance_usedPodMemoryInMB_head

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:resources/info={info-podInstance}/diskUsa geInKbps

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_resources_info_info_podInstance_diskUsageInKbps_get

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resources_info_info-podInstance_diskUsageInKbps'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_resources_info_info_podInstance_diskUsageInKbps_head

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:resources/info={info-podInstance}/goRouti nesCount

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_resources_info_info_podInstance_goRoutinesCount_get

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_resources_info_info-podInstance_goRoutinesCount'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_resources_info_info_podInstance_goRoutinesCount_head

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
    - trim
    - explicit
    - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:resources/info={info-podInstance}/gcCount

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resources_info_info_podInstance_gcCount_get

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_resources_info_info-podInstance_gcCount'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resources_info_info_podInstance_gcCount_head

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:resources/info={info-podInstance}/gcPause InNS

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_resources_info_info_podInstance_gcPauseInNS_get


  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_resources_info_info-podInstance_gcPauseInNS'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_tailf_mobile_infra_resources_info_info_podInstance_gcPauseInNS_head


    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
    - trim
    - explicit
    - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:running-status

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_running_status_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_running-status'
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
```

```
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_running_status_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_running-status'
    Required/Optional: true

  Responses:
    '201':
      Description: container running-status created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: running-status
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_running_status_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_running-status-post'

    Required/Optional: true
```

```
  Responses:
    '201':
      Description: container running-status created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: running-status
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_running_status_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_running_status_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:
```

```
Tags:
- data
- head
Operation ID: data_tailf_mobile_infra_running_status_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_running_status_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_running-status'
      Required/Optional: true

    Responses:
      '204':
        Description: container running-status updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: running-status
```

/data/tailf-mobile-infra:running-status/info

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_running_status_info_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_running-status_info'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_running_status_info_head

  Parameters:
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
    - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:running-status/info={info-podInstance}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_running_status_info_info_podInstance_get

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_running-status_info_info-podInstance'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_running_status_info_info_podInstance_head

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:running-status/info={info-podInstance}/po dInstance

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_running_status_info_info_podInstance_podInstance_get

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_running-status_info_info-podInstance_podInstance'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_running_status_info_info_podInstance_podInstance_head

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:running-status/info={info-podInstance}/runningStatus

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_running_status_info_info_podInstance_runningStatus_get

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_running-status_info_info-podInstance_runningStatus'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_running_status_info_info_podInstance_runningStatus_head

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:running-status/info={info-podInstance}/systemHealth

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_running_status_info_info_podInstance_systemHealth_get

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_running-status_info_info-podInstance_systemHealth'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_running_status_info_info_podInstance_systemHealth_head

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:running-status/info={info-podInstance}/st artTime

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_running_status_info_info_podInstance_startTime_get

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_running-status_info_info-podInstance_startTime'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_running_status_info_info_podInstance_startTime_head

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:diagnostics

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_diagnostics_get

  Parameters:
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_diagnostics'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_diagnostics_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_diagnostics'
    Required/Optional: true

  Responses:
    '201':
      Description: container diagnostics created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: diagnostics
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_diagnostics_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_diagnostics-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container diagnostics created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: diagnostics
```

```
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_diagnostics_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_diagnostics_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_diagnostics_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_diagnostics_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
        Reference: '#/components/schemas/data_tailf-mobile-infra_diagnostics'
    Required/Optional: true

  Responses:
    '204':
      Description: container diagnostics updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: diagnostics
```

/data/tailf-mobile-infra:diagnostics/info

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_diagnostics_info_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_diagnostics_info'

  '204':
    Description: No Content
    Content: {}
  '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_diagnostics_info_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:diagnostics/info={info-podInstance},{info-diagnostic}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_get

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: info-diagnostic
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_head

    Parameters:
    - Name: info-podInstance
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-diagnostic
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:diagnostics/info={info-podInstance},{info -diagnostic}/podInstance

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_podInstance_get

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-diagnostic
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_podInstance'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_podInstance_head

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: info-diagnostic
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:diagnostics/info={info-podInstance},{info -diagnostic}/diagnostic

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_diagnostic_get

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-diagnostic
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_diagnostic'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_diagnostic_head

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-diagnostic
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:diagnostics/info={info-podInstance},{info -diagnostic}/component

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_component_get

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-diagnostic
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
```

```
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_component'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_component_head

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-diagnostic
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:diagnostics/info={info-podInstance},{info -diagnostic}/startTime

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_startTime_get

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-diagnostic
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_startTime'

    '204':
      Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_startTime_head

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-diagnostic
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
```

```
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:diagnostics/info={info-podInstance},{info -diagnostic}/status

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_status_get

  Parameters:
  - Name: info-podInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-diagnostic
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_status'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
```

```
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_status_head

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-diagnostic
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
```

```
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:diagnostics/info={info-podInstance},{info -diagnostic}/retries

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_retries_get

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-diagnostic
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_retries'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
```

```
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_diagnostics_info_info_podInstance_info_diagnostic_retries_head

    Parameters:
    - Name: info-podInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-diagnostic
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:infra

```
get:

  Tags:
```

```
- data
- get
Operation ID: data_tailf_mobile_infra_infra_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_infra'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_infra_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_infra'
    Required/Optional: true

  Responses:
    '201':
      Description: container infra created or replaced
      Content: {}
```

```
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: infra
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_infra_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_infra-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container infra created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: infra
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_infra_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
```

```
- data
- patch
Operation ID: data_tailf_mobile_infra_infra_patch
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_infra'
  Required/Optional: true

Responses:
  '204':
    Description: container infra updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: infra
```

/data/tailf-mobile-infra:infra/metrics

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_infra_metrics_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_infra_metrics'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_infra_metrics_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_infra_metrics'
      Required/Optional: true

    Responses:
      '201':
        Description: container metrics created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
```

```
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: metrics
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_infra_metrics_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_infra_metrics-post'

    Required/Optional: true

  Responses:
    '201':
      Description: container metrics created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: metrics
delete:

  Tags:
  - data
  - delete
```

```
  Operation ID: data_tailf_mobile_infra_infra_metrics_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_metrics_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_metrics_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_infra_metrics_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_infra_metrics'
    Required/Optional: true

  Responses:
    '204':
```

```
    Description: container metrics updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: metrics
```

/data/tailf-mobile-infra:infra/metrics/experimental

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_experimental'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_experimental'
    Required/Optional: true

  Responses:
    '201':
      Description: container experimental created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: experimental
Method: Post
```

```
    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_experimental-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container experimental created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: experimental
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
```

```
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_experimental'
      Required/Optional: true

    Responses:
      '204':
        Description: container experimental updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
```

```
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: experimental
```

/data/tailf-mobile-infra:infra/metrics/experimental/version

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_version_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_experimental_version'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_version_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_experimental_version'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf version created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: version
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_version_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
```

```
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_version_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_version_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_infra_metrics_experimental_version_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_experimental_version'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf version updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
```

```
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: version
```

/data/tailf-mobile-infra:infra/metrics/verbose

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_infra_metrics_verbose_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_infra_metrics_verbose_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose'

    Required/Optional: true

  Responses:
    '201':
      Description: container verbose created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: verbose
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_infra_metrics_verbose_post
  Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container verbose created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: verbose
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_infra_metrics_verbose_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_infra_metrics_verbose_options

    Responses:
```

```
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_metrics_verbose_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_infra_metrics_verbose_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose'

    Required/Optional: true

  Responses:
    '204':
      Description: container verbose updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: verbose
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podType}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_get

  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_put

    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
```

```
        - service
        - application
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType'

    Required/Optional: true

  Responses:
    '201':
      Description: list verboseLevels created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: verboseLevels
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_delete

  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_options

  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
```

```
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_head

    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_patch

    Parameters:
```

```
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType'

      Required/Optional: true

    Responses:
      '204':
        Description: list verboseLevels updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: verboseLevels
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verb oseLevels-podType}/podType

```
  get:
```

```
    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_podType_get


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_podType'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_podType_put


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_podType'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf podType created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: podType
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_podType_delete


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_podType_options


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
```

```
        enum:
        - protocol
        - load-balancer
        - service
        - application

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_podType_head


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_podType_patch


    Parameters:
```

```
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_podType'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf podType updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: podType
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verb oseLevels-podType}/pods

```
  get:
```

```
    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_get

    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_put

    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods'

      Required/Optional: true

    Responses:
      '201':
        Description: container pods created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
```

```
    security:
    - basicAuth: []
    x-codegen-request-body-name: pods
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_post


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container pods created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pods
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_delete


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_options


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_head


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_patch
```

```
    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods'

      Required/Optional: true

    Responses:
      '204':
        Description: container pods updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pods
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verb oseLevels-podType}/pods/pod-names

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_options


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verb oseLevels-podType}/pods/pod-names={pod-names-pod-name}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_get


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: pod-names-pod-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

Tags:
- data
- put

Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_put

Parameters:
- **Name**: verboseLevels-podType
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: protocol
    enum:
    - protocol
    - load-balancer
    - service
    - application
- **Name**: pod-names-pod-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: insert
  In: query
  Description: controlling the order when adding new list elements
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: first
    enum:
    - first
    - last
    - before
    - after
- **Name**: point
  In: query
  Description: used to specify the insertion point
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string

```
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name'

    Required/Optional: true

  Responses:
    '201':
      Description: list pod-names created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pod-names
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_delete


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
```

```
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
    - Name: pod-names-pod-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_options


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: pod-names-pod-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
```

```
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_head


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: pod-names-pod-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_patch
```

```
    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: pod-names-pod-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name'

      Required/Optional: true

    Responses:
      '204':
        Description: list pod-names updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
```

```
    security:
    - basicAuth: []
    x-codegen-request-body-name: pod-names
?
/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podType}/pods/pod-names={pod-names-pod-name}/pod-name
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_pod_name_get


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: pod-names-pod-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_pod-name'

    '204':
      Description: No Content
      Content: {}
    '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_pod_name_put


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: pod-names-pod-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_pod-name'
```

```
    Required/Optional: true

  Responses:
    '201':
      Description: leaf pod-name created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pod-name
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_pod_name_delete


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: pod-names-pod-name
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_pod_name_options


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: pod-names-pod-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:
```

```
    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_pod_name_head

    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: pod-names-pod-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_pod_name_patch


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: pod-names-pod-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_pod-name'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf pod-name updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pod-name
?
/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podType}/pods/pod-names={pod-names-pod-name}/level
: get:

    Tags:
```

- data
- get

Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_level_get

Parameters:
- **Name**: verboseLevels-podType
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: protocol
    enum:
    - protocol
    - load-balancer
    - service
    - application
- **Name**: pod-names-pod-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_level'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
```

```
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_level_put


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: pod-names-pod-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_level'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf level created or replaced
        Content: {}
      '204':
```

```
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: level
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_level_delete


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: pod-names-pod-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
```

```
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_level_options


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: pod-names-pod-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_level_head


    Parameters:
    - Name: verboseLevels-podType
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: protocol
    enum:
    - protocol
    - load-balancer
    - service
    - application
- Name: pod-names-pod-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_pods_pod_names_pod_names_pod_name_level_patch


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
```

```
      - application
    - Name: pod-names-pod-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_level'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf level updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: level
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verb oseLevels-podType}/level

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_level_get
```

```
Parameters:
- Name: verboseLevels-podType
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: protocol
    enum:
    - protocol
    - load-balancer
    - service
    - application
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_level'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
```

```
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_level_put


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_level'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf level created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
    x-codegen-request-body-name: level
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_level_delete


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_level_options


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_level_head


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_level_patch


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_level'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf level updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: level
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verb oseLevels-podType}/metrics

```
  get:

    Tags:
    - data
    - get
    Operation ID:
```

```
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_get

  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_put


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics'

      Required/Optional: true

    Responses:
      '201':
        Description: container metrics created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: metrics
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_post


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container metrics created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
```

```
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: metrics
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_delete


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_options


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
```

```
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_head


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_patch
```

```
    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics'

      Required/Optional: true

    Responses:
      '204':
        Description: container metrics updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: metrics
```

/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verb oseLevels-podType}/metrics/metricsList

```
  options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_options


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
?
/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podType}/metrics/metricsList={metricsList-name}
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_get


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
```

```
- Name: metricsList-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_put


    Parameters:
    - Name: verboseLevels-podType
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: metricsList-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name'

    Required/Optional: true

  Responses:
```

```
      '201':
        Description: list metricsList created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: metricsList
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_delete


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: metricsList-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_options


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: metricsList-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_head

Parameters:
- **Name**: verboseLevels-podType
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: protocol
    enum:
    - protocol
    - load-balancer
    - service
    - application
- **Name**: metricsList-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_patch


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: metricsList-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name'

      Required/Optional: true

    Responses:
      '204':
        Description: list metricsList updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: metricsList
?
/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podType}/metrics/metricsList={metricsList-name}/name
: get:

    Tags:
    - data
    - get
```

Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_name_get

Parameters:
- **Name**: verboseLevels-podType
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: protocol
    enum:
    - protocol
    - load-balancer
    - service
    - application
- **Name**: metricsList-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_name'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_name_put


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: metricsList-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_name'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf name created or replaced
      Content: {}
    '204':
      Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_name_delete


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: metricsList-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_name_options


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: metricsList-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_name_head


  Parameters:
  - Name: verboseLevels-podType
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: protocol
    enum:
    - protocol
    - load-balancer
    - service
    - application
- Name: metricsList-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_name_patch


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
```

```
    - Name: metricsList-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_name'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf name updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
?
/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podType}/metrics/metricsList={metricsList-name}/level
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_level_get


    Parameters:
    - Name: verboseLevels-podType
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: metricsList-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_level'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_level_put


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: metricsList-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_level'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf level created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: level
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_level_delete


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: metricsList-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
```

```
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_level_options


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: metricsList-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_level_head


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
```

```
    enum:
    - protocol
    - load-balancer
    - service
    - application
- Name: metricsList-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_level_patch


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: metricsList-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_level'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf level updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: level
?
/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podType}/metrics/metricsList={metricsList-name}/granular-labels
: options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_granular_labels_options


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
```

```
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: metricsList-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
?
/data/tailf-mobile-infra:infra/metrics/verbose/verboseLevels={verboseLevels-podType}/metrics/metricsList={metricsList-name}/granular-labels={granular-labels-id}
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_granular_labels_granular_labels_id_get


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: metricsList-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: granular-labels-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_granular-labels_granular-labels-id'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_granular_labels_granular_labels_id_put


    Parameters:
    - Name: verboseLevels-podType
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: protocol
    enum:
    - protocol
    - load-balancer
    - service
    - application
- Name: metricsList-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: granular-labels-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: insert
  In: query
  Description: controlling the order when adding new list elements
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: first
    enum:
    - first
    - last
    - before
    - after
- Name: point
  In: query
  Description: used to specify the insertion point
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_granular-labels_granular-labels-id'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf-list granular-labels created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: granular-labels
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_granular_labels_granular_labels_id_delete


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
```

```
      - protocol
      - load-balancer
      - service
      - application
  - Name: metricsList-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: granular-labels-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_granular_labels_granular_labels_id_options


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: metricsList-name
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: granular-labels-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_granular_labels_granular_labels_id_head


    Parameters:
    - Name: verboseLevels-podType
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
    - Name: metricsList-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: granular-labels-id
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_infra_metrics_verbose_verboseLevels_verboseLevels_podType_metrics_metricsList_metricsList_name_granular_labels_granular_labels_id_patch


  Parameters:
  - Name: verboseLevels-podType
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol
      enum:
      - protocol
      - load-balancer
      - service
      - application
  - Name: metricsList-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: granular-labels-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_granular-labels_granular-labels-id'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf-list granular-labels updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: granular-labels
```

/data/tailf-mobile-infra:infra/transaction

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_infra_transaction_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
```

```
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
           Reference: '#/components/schemas/data_tailf-mobile-infra_infra_transaction'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_infra_transaction_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_infra_transaction'
    Required/Optional: true

  Responses:
    '201':
      Description: container transaction created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: transaction
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_infra_transaction_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_infra_transaction-post'

    Required/Optional: true

  Responses:
    '201':
      Description: container transaction created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: transaction
delete:
```

```
  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_infra_transaction_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_transaction_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_transaction_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_infra_transaction_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_infra_transaction'
      Required/Optional: true
```

```
Responses:
  '204':
    Description: container transaction updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: transaction
```

/data/tailf-mobile-infra:infra/transaction/limit

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_infra_transaction_limit_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
```

```
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit'
      Required/Optional: true

    Responses:
      '201':
        Description: container limit created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
    x-codegen-request-body-name: limit
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container limit created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: limit
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
```

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_transaction_limit_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_transaction_limit_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit'
      Required/Optional: true

    Responses:
      '204':
        Description: container limit updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
```

```
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: limit
```

/data/tailf-mobile-infra:infra/transaction/limit/stage

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_infra_transaction_limit_stage_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_stage'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
```

```
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_stage_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_stage'
       Required/Optional: true

    Responses:
      '201':
        Description: leaf stage created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: stage
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_stage_delete

    Responses:
      '204':
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_transaction_limit_stage_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_transaction_limit_stage_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_stage_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_stage'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf stage updated
        Content: {}
      '400':
```

```
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: stage
```

/data/tailf-mobile-infra:infra/transaction/limit/consecutive

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive'
    Required/Optional: true

  Responses:
    '201':
      Description: container consecutive created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: consecutive
Method: Post

  Tags:
  - data
  - post
```

```
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive-post'
       Required/Optional: true

    Responses:
      '201':
        Description: container consecutive created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: consecutive
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_options
```

```
  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive'
      Required/Optional: true

    Responses:
      '204':
        Description: container consecutive updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: consecutive
```

/data/tailf-mobile-infra:infra/transaction/limit/consecutive/same:

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive_same'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive_same'
      Required/Optional: true

    Responses:
      '201':
        Description: container same created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: same
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive_same-post'

      Required/Optional: true
```

```
  Responses:
    '201':
      Description: container same created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: same
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_delete


  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_options


  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

```
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive_same'
      Required/Optional: true

    Responses:
      '204':
        Description: container same updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: same
```

/data/tailf-mobile-infra:infra/transaction/limit/consecutive/same/ stage

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_stage_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive_same_stage'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID:
data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_stage_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive_same_stage'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf stage created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: stage
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_stage_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
```

```
    - options
    Operation ID:
data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_stage_options

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_stage_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_transaction_limit_consecutive_same_stage_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive_same_stage'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf stage updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: stage
```

/data/tailf-mobile-infra:infra/transaction/loop

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_infra_transaction_loop_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_infra_transaction_loop_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop'

    Required/Optional: true

  Responses:
    '201':
      Description: container loop created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: loop
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_infra_transaction_loop_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
```

```
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop-post'
     Required/Optional: true

  Responses:
    '201':
      Description: container loop created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: loop
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_infra_transaction_loop_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_transaction_loop_options

  Responses:
    '200':
      Description: OK
      Content: {}
```

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_transaction_loop_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
```

```
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_infra_transaction_loop_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop'

    Required/Optional: true

  Responses:
    '204':
      Description: container loop updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: loop
```

/data/tailf-mobile-infra:infra/transaction/loop/detection

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_infra_transaction_loop_detection_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_detection'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
```

```
    Operation ID: data_tailf_mobile_infra_infra_transaction_loop_detection_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_detection'
       Required/Optional: true

    Responses:
      '201':
        Description: leaf detection created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: detection
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_infra_transaction_loop_detection_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_infra_transaction_loop_detection_options
```

```
  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_infra_transaction_loop_detection_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_infra_transaction_loop_detection_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_detection'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf detection updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
```

```
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: detection
```

/data/tailf-mobile-infra:infra/transaction/loop/category

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_infra_transaction_loop_category_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:infra/transaction/loop/category={category -name}

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_infra_transaction_loop_category_category_name_get


  Parameters:
  - Name: category-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_tailf_mobile_infra_infra_transaction_loop_category_category_name_put


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name'

      Required/Optional: true

    Responses:
      '201':
        Description: list category created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: category
  delete:

    Tags:
    - data
```

```
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_delete

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_options

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_head

    Parameters:
    - Name: category-name
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_patch

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name'

      Required/Optional: true

    Responses:
      '204':
        Description: list category updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: category
```

/data/tailf-mobile-infra:infra/transaction/loop/category={category-name}/name

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_name_get

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_name'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_name_put

  Parameters:
  - Name: category-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_name'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf name created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
```

```
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_name_delete

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_name_options

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
```

```
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_name_head

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_name_patch

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_name'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf name updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
```

/data/tailf-mobile-infra:infra/transaction/loop/category={category -name}/threshold

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_get

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_put

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold'
```

```
      Required/Optional: true

    Responses:
      '201':
        Description: container threshold created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: threshold
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_post

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold-post'

      Required/Optional: true
```

```
    Responses:
      '201':
        Description: container threshold created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: threshold
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_delete

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
```

```
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_options

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_head

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
```

```
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_patch

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold'

      Required/Optional: true

    Responses:
      '204':
        Description: container threshold updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: threshold
```

/data/tailf-mobile-infra:infra/transaction/loop/category={category -name}/threshold/interval

```
  get:

    Tags:
    - data
    - get
```

Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_interval_get

Parameters:
- **Name**: category-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_interval'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_interval_put
```

```
    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_interval'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf interval created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interval
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_interval_delete
```

```
    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_interval_options


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_interval_head


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_interval_patch


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_interval'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf interval updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
```

```
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: interval
```

/data/tailf-mobile-infra:infra/transaction/loop/category={category -name}/threshold/thresholds

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_options


  Parameters:
  - Name: category-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:infra/transaction/loop/category={category -name}/threshold/thresholds={thresholds-name}

```
get:

  Tags:
  - data
  - get
```

Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_get

Parameters:
- **Name**: category-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: thresholds-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: low
    enum:
    - low
    - high
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_put


  Parameters:
  - Name: category-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: thresholds-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: low
      enum:
      - low
      - high
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name'

      Required/Optional: true

    Responses:
      '201':
        Description: list thresholds created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: thresholds
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_delete


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_options


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_head


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_patch
```

```
  Parameters:
  - Name: category-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: thresholds-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: low
      enum:
      - low
      - high
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name'

    Required/Optional: true

  Responses:
    '204':
      Description: list thresholds updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: thresholds
```

/data/tailf-mobile-infra:infra/transaction/loop/category={category -name}/threshold/thresholds={thresholds-name}/name

get:

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_name_get

Parameters:
- **Name**: category-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: thresholds-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: low
    enum:
    - low
    - high
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_name'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
```

```
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_name_put


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_name'

      Required/Optional: true

    Responses:
```

```
      '201':
        Description: leaf name created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_name_delete


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
```

```
        - high

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_name_options


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_name_head


    Parameters:
```

```
- Name: category-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: thresholds-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: low
    enum:
    - low
    - high
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_name_patch


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_name'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf name updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
```

/data/tailf-mobile-infra:infra/transaction/loop/category={category -name}/threshold/thresholds={thresholds-name}/count

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_count_get
```

```
Parameters:
- Name: category-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: thresholds-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: low
    enum:
    - low
    - high
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_count'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
```

```
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_count_put


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_count'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf count created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: count
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_count_delete


  Parameters:
  - Name: category-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: thresholds-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: low
      enum:
      - low
      - high

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
```

```
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_count_options

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_count_head

    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: low
    enum:
    - low
    - high
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_count_patch


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_count'

Required/Optional: true

Responses:
'204':
Description: leaf count updated
Content: {}
'400':
Description: Bad Request
Content: {}
'401':
Description: Unauthorized
Content: {}
'404':
Description: Not Found
Content: {}
'405':
Description: Method Not Allowed
Content: {}
'409':
Description: Conflict
Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: count

/data/tailf-mobile-infra:infra/transaction/loop/category={category -name}/threshold/thresholds={thresholds-name}/action

get:

Tags:
- data
- get
Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_action_get

Parameters:
- Name: category-name
In: path
Required/Optional: true
Style: simple
Explode: false
Schema:
Type: string
Format: identityref
- Name: thresholds-name
In: path
Required/Optional: true

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: low
      enum:
      - low
      - high
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_action'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_action_put


    Parameters:
    - Name: category-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: thresholds-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: low
      enum:
      - low
      - high
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_action'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf action created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
    x-codegen-request-body-name: action
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_action_delete


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_action_options


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref
  - Name: thresholds-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: low
      enum:
      - low
      - high

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_action_head


  Parameters:
  - Name: category-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: thresholds-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: low
      enum:
      - low
      - high
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_infra_transaction_loop_category_category_name_threshold_thresholds_thresholds_name_action_patch


    Parameters:
    - Name: category-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: thresholds-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: low
        enum:
        - low
        - high
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_action'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf action updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: action
```

/data/tailf-mobile-infra:client

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_client'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_client_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client'
    Required/Optional: true

  Responses:
    '201':
      Description: container client created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: client
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_client_post
  Request Body:
    Content:
      application/yang-data+json:
```

```
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container client created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: client
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_client_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_client_options

    Responses:
      '200':
        Description: OK
        Content: {}
```

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
```

```
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_client_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client'
    Required/Optional: true

  Responses:
    '204':
      Description: container client updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: client
```

/data/tailf-mobile-infra:client/http

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_http_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference: '#/components/schemas/data_tailf-mobile-infra_client_http'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_http_put
    Request Body:
```

```
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_http'
    Required/Optional: true

  Responses:
    '201':
      Description: container http created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: http
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_client_http_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_http-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container http created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: http
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_http_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_http_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_http_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_client_http_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_http'
    Required/Optional: true

  Responses:
    '204':
      Description: container http updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: http
```

/data/tailf-mobile-infra:client/http/header

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_http_header_get
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_http_header'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_client_http_header_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_http_header'

    Required/Optional: true

  Responses:
    '201':
      Description: container header created or replaced
      Content: {}
    '204':
      Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: header
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_client_http_header_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_http_header-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container header created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: header
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_http_header_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_http_header_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_http_header_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
```

```
- patch
Operation ID: data_tailf_mobile_infra_client_http_header_patch
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_client_http_header'

  Required/Optional: true

Responses:
  '204':
    Description: container header updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: header
```

/data/tailf-mobile-infra:client/http/header/user-agent

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_http_header_user_agent_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_http_header_user-agent'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_http_header_user_agent_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_http_header_user-agent'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf user-agent created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: user-agent
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_http_header_user_agent_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_http_header_user_agent_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_http_header_user_agent_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_http_header_user_agent_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_http_header_user-agent'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf user-agent updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: user-agent
```

/data/tailf-mobile-infra:client/http/ping

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_client_http_ping_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_client_http_ping'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_client_http_ping_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_http_ping'
    Required/Optional: true

  Responses:
    '201':
      Description: container ping created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ping
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_client_http_ping_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_client_http_ping-post'

    Required/Optional: true

  Responses:
    '201':
      Description: container ping created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ping
```

```
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_http_ping_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_http_ping_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_http_ping_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_http_ping_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
        Reference: '#/components/schemas/data_tailf-mobile-infra_client_http_ping'
    Required/Optional: true

  Responses:
    '204':
      Description: container ping updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ping
```

/data/tailf-mobile-infra:client/http/ping/timeout

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_http_ping_timeout_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_http_ping_timeout'
      '204':
        Description: No Content
        Content: {}
      '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_client_http_ping_timeout_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_http_ping_timeout'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf timeout created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: timeout
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_http_ping_timeout_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_http_ping_timeout_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_http_ping_timeout_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_client_http_ping_timeout_patch
  Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_http_ping_timeout'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf timeout updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: timeout
```

/data/tailf-mobile-infra:client/http/ping/interval

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_client_http_ping_interval_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

```
'#/components/schemas/data_tailf-mobile-infra_client_http_ping_interval'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_http_ping_interval_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_http_ping_interval'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf interval created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interval
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_http_ping_interval_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_http_ping_interval_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_http_ping_interval_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
```

```
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_http_ping_interval_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_http_ping_interval'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf interval updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interval
```

/data/tailf-mobile-infra:client/outbound

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_client_outbound_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_client_outbound'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_outbound_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_client_outbound'
      Required/Optional: true

    Responses:
      '201':
        Description: container outbound created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
```

```
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: outbound
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_client_outbound_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_outbound-post'

    Required/Optional: true

  Responses:
    '201':
      Description: container outbound created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: outbound
delete:

  Tags:
  - data
  - delete
```

```
  Operation ID: data_tailf_mobile_infra_client_outbound_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_outbound_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_outbound_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_client_outbound_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_outbound'
    Required/Optional: true

  Responses:
    '204':
```

```
    Description: container outbound updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: outbound
```

/data/tailf-mobile-infra:client/outbound/interface

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_outbound_interface_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:client/outbound/interface={interface-inte rface}

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_client_outbound_interface_interface_interface_get


  Parameters:
  - Name: interface-interface
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_tailf_mobile_infra_client_outbound_interface_interface_interface_put


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface'

      Required/Optional: true

    Responses:
      '201':
        Description: list interface created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_delete

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_options

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
```

```
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_head

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_patch

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface'

      Required/Optional: true
```

```
Responses:
  '204':
    Description: list interface updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: interface
```

/data/tailf-mobile-infra:client/outbound/interface={interface-inte rface}/interface

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_interface_get

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_interface'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_interface_put

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_interface'

      Required/Optional: true
```

```
    Responses:
      '201':
        Description: leaf interface created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_interface_delete

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
```

```
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_interface_options

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_interface_head

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_interface_patch
```

```
    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_interface'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf interface updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface
```

/data/tailf-mobile-infra:client/outbound/interface={interface-inte rface}/limit

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_get
```

```
Parameters:
- Name: interface-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_put

    Parameters:
    - Name: interface-interface
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit'

      Required/Optional: true

    Responses:
      '201':
        Description: container limit created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: limit
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_post

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container limit created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: limit
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_delete

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_options

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_head

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_patch

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit'

      Required/Optional: true

    Responses:
      '204':
        Description: container limit updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: limit
```

/data/tailf-mobile-infra:client/outbound/interface={interface-inte rface}/limit/pending

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_get

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_put

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending'

      Required/Optional: true

    Responses:
      '201':
        Description: container pending created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
```

```
    security:
    - basicAuth: []
    x-codegen-request-body-name: pending
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_post

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container pending created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
    x-codegen-request-body-name: pending
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_delete

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_options


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

```
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_head

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_patch

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending'

      Required/Optional: true

    Responses:
      '204':
        Description: container pending updated
        Content: {}
      '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pending
```

/data/tailf-mobile-infra:client/outbound/interface={interface-inte rface}/limit/pending/response

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_response_get


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending_response'
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_response_put


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending_response'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf response created or replaced
        Content: {}
      '204':
```

```
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: response
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_response_delete


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_response_options
```

```
    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_response_head


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_pending_response_patch


    Parameters:
```

```
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending_response'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf response updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: response
```

/data/tailf-mobile-infra:client/outbound/interface={interface-inte rface}/limit/consecutive

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_get
```

```
Parameters:
- Name: interface-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_put


    Parameters:
```

```
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive'

      Required/Optional: true

    Responses:
      '201':
        Description: container consecutive created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: consecutive
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_post


    Parameters:
    - Name: interface-interface
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container consecutive created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: consecutive
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_delete


    Parameters:
    - Name: interface-interface
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_options


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_head


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_patch


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive'

    Required/Optional: true

  Responses:
    '204':
      Description: container consecutive updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: consecutive
```

/data/tailf-mobile-infra:client/outbound/interface={interface-inte rface}/limit/consecutive/failure

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_get


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_put


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure'

    Required/Optional: true

  Responses:
    '201':
      Description: container failure created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: failure
Method: Post

  Tags:
  - data
  - post
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_post


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure-post'

    Required/Optional: true

  Responses:
    '201':
      Description: container failure created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: failure
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_delete


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_options


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_head


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
```

```
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure'

    Required/Optional: true

  Responses:
    '204':
      Description: container failure updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: failure
```

/data/tailf-mobile-infra:client/outbound/interface={interface-inte rface}/limit/consecutive/failure/count

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_count_get


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_count'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_count_put


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_count'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf count created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: count
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_count_delete


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_count_options


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_count_head


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_count_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_count'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf count updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: count
```

/data/tailf-mobile-infra:client/outbound/interface={interface-inte rface}/limit/consecutive/failure/codes

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_codes_options


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:client/outbound/interface={interface-inte rface}/limit/consecutive/failure/codes={codes-id}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_codes_codes_id_get


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
- Name: codes-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_codes_codes-id'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_codes_codes_id_put


    Parameters:
    - Name: interface-interface
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: codes-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_codes_codes-id'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf-list codes created or replaced
      Content: {}
    '204':
      Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: codes
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_codes_codes_id_delete


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: codes-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_codes_codes_id_options

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: codes-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_codes_codes_id_head

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: codes-id
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_limit_consecutive_failure_codes_codes_id_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: codes-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_codes_codes-id'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf-list codes updated
        Content: {}
```

```
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: codes
```

/data/tailf-mobile-infra:client/outbound/interface={interface-inte rface}/host

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_get

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host'

      '204':
```

```
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_put

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host'

    Required/Optional: true

  Responses:
    '201':
      Description: container host created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: host
Method: Post

  Tags:
  - data
  - post
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_post

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host-post'

    Required/Optional: true

  Responses:
    '201':
      Description: container host created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
```

```
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: host
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_delete

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_options

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_head

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_patch

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host'

      Required/Optional: true

    Responses:
      '204':
        Description: container host updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: host
```

/data/tailf-mobile-infra:client/outbound/interface={interface-inte rface}/host/ping

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_get

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_put

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping'

      Required/Optional: true

    Responses:
      '201':
        Description: container ping created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ping
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_post

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container ping created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ping
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_delete

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_options

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_head

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_patch

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping'

      Required/Optional: true

    Responses:
      '204':
        Description: container ping updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ping
```

/data/tailf-mobile-infra:client/outbound/interface={interface-inte rface}/host/ping/timeout

```
  get:
```

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_timeout_get

Parameters:
- **Name**: interface-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_timeout'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
```

```
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_timeout_put


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_timeout'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf timeout created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: timeout
  delete:

    Tags:
    - data
    - delete
```

```
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_timeout_delete


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_timeout_options


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_timeout_head


    Parameters:
```

```
- Name: interface-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_timeout_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_timeout'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf timeout updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: timeout
```

/data/tailf-mobile-infra:client/outbound/interface={interface-inte rface}/host/ping/interval

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_interval_get


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_interval'

    '204':
      Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_interval_put


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_interval'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf interval created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interval
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_interval_delete


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_interval_options


  Parameters:
  - Name: interface-interface
    In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_interval_head


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_interval_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_interval'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf interval updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interval
```

/data/tailf-mobile-infra:client/outbound/interface={interface-inte rface}/host/ping/backoff

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_backoff_get


    Parameters:
    - Name: interface-interface
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_backoff'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_backoff_put


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_backoff'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf backoff created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: backoff
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_backoff_delete


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_backoff_options


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_backoff_head


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_backoff_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_backoff'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf backoff updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
```

```
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: backoff
```

/data/tailf-mobile-infra:client/outbound/interface={interface-inte rface}/host/ping/retry

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_retry_get

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_retry'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_retry_put

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_retry'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf retry created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: retry
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_retry_delete


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_retry_options


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_retry_head

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_retry_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_retry'
```

```
    Required/Optional: true

  Responses:
    '204':
      Description: leaf retry updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: retry
```

/data/tailf-mobile-infra:client/outbound/interface={interface-inte rface}/host/ping/fast-interval

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_fast_interval_get


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_fast-interval'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_fast_interval_put


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_fast-interval'
```

```
      Required/Optional: true

    Responses:
      '201':
        Description: leaf fast-interval created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: fast-interval
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_fast_interval_delete


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
```

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_fast_interval_options


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_fast_interval_head


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_fast_interval_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_fast-interval'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf fast-interval updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: fast-interval
```

/data/tailf-mobile-infra:client/outbound/interface={interface-inte rface}/host/ping/all-host-down-interval

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_all_host_down_interval_get


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_all-host-down-interval'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_all_host_down_interval_put


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_all-host-down-interval'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf all-host-down-interval created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: all-host-down-interval
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_all_host_down_interval_delete


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_all_host_down_interval_options


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:
```

Tags:
- data
- head

Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_all_host_down_interval_head

Parameters:
- **Name**: interface-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_interface_interface_interface_host_ping_all_host_down_interval_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_all-host-down-interval'

      Required/Optional: true

    Responses:
```

```
    '204':
      Description: leaf all-host-down-interval updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: all-host-down-interval
```

/data/tailf-mobile-infra:client/outbound/limit

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_client_outbound_limit'

    Required/Optional: true

  Responses:
    '201':
      Description: container limit created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: limit
```

```
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_client_outbound_limit_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit-post'
       Required/Optional: true

    Responses:
      '201':
        Description: container limit created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: limit
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_client_outbound_limit_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:
```

```
  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_outbound_limit'

    Required/Optional: true

  Responses:
    '204':
      Description: container limit updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: limit
```

/data/tailf-mobile-infra:client/outbound/limit/pending

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

   Responses:
     '200':
       Description: OK
       Content:
         application/yang-data+json:
           Schema:
             Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_pending'
     '204':
       Description: No Content
       Content: {}
     '400':
       Description: Bad Request
       Content: {}
     '401':
       Description: Unauthorized
       Content: {}
     '404':
       Description: Not Found
       Content: {}
     '405':
       Description: Method Not Allowed
       Content: {}
     '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_pending'
    Required/Optional: true

  Responses:
    '201':
      Description: container pending created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pending
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
```

```
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_pending-post'
     Required/Optional: true

  Responses:
    '201':
      Description: container pending created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pending
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_options

  Responses:
    '200':
      Description: OK
      Content: {}
```

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_pending'
      Required/Optional: true

    Responses:
      '204':
        Description: container pending updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: pending
```

/data/tailf-mobile-infra:client/outbound/limit/pending/response

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_response_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_pending_response'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_response_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_pending_response'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf response created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: response
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_response_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
   Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_response_options
```

```
  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_response_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_outbound_limit_pending_response_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_pending_response'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf response updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
```

```
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: response
```

/data/tailf-mobile-infra:client/outbound/limit/consecutive

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive'
      Required/Optional: true

    Responses:
      '201':
        Description: container consecutive created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: consecutive
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive-post'
      Required/Optional: true
```

```
  Responses:
    '201':
      Description: container consecutive created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: consecutive
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:
```

```
Tags:
- data
- head
Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive'
      Required/Optional: true

    Responses:
      '204':
        Description: container consecutive updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: consecutive
```

/data/tailf-mobile-infra:client/outbound/limit/consecutive/failure

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure'
     Required/Optional: true

   Responses:
     '201':
       Description: container failure created or replaced
       Content: {}
     '204':
       Description: No Content
       Content: {}
     '400':
       Description: Bad Request
       Content: {}
     '401':
       Description: Unauthorized
       Content: {}
     '404':
       Description: Not Found
       Content: {}
     '405':
       Description: Method Not Allowed
       Content: {}
     '409':
       Description: Conflict
       Content: {}
   security:
   - basicAuth: []
   x-codegen-request-body-name: failure
  Method: Post

   Tags:
   - data
   - post
  Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_post

   Request Body:
     Content:
       application/yang-data+json:
         Schema:
           Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure-post'

     Required/Optional: true

   Responses:
     '201':
       Description: container failure created
       Content: {}
     '204':
       Description: No Content
       Content: {}
     '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: failure
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_delete


  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_options


  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_head


  Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
      - report-all
      - trim
      - explicit
      - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
   Operation ID: data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure'
      Required/Optional: true

    Responses:
      '204':
        Description: container failure updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: failure
```

/data/tailf-mobile-infra:client/outbound/limit/consecutive/failure /count

```
  get:
```

```
    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_count_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_count'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_count_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_count'
```

```
      Required/Optional: true

    Responses:
      '201':
        Description: leaf count created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: count
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_count_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_count_options

    Responses:
      '200':
        Description: OK
        Content: {}
```

```
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_count_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_count_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_count'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf count updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: count
```

/data/tailf-mobile-infra:client/outbound/limit/consecutive/failure /codes

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_codes_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:client/outbound/limit/consecutive/failure /codes={codes-id}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_codes_codes_id_get

  Parameters:
  - Name: codes-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_codes_codes-id'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_codes_codes_id_put

    Parameters:
    - Name: codes-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
```

```
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_codes_codes-id'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf-list codes created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: codes
  delete:

    Tags:
    - data
    - delete
```

```
    Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_codes_codes_id_delete

    Parameters:
    - Name: codes-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_codes_codes_id_options

    Parameters:
    - Name: codes-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_codes_codes_id_head

    Parameters:
    - Name: codes-id
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_limit_consecutive_failure_codes_codes_id_patch

    Parameters:
    - Name: codes-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_codes_codes-id'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf-list codes updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
```

```
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: codes
```

/data/tailf-mobile-infra:client/outbound/host

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_outbound_host_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_outbound_host'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_client_outbound_host_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_client_outbound_host'

    Required/Optional: true

  Responses:
    '201':
      Description: container host created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: host
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_client_outbound_host_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

```
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container host created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: host
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_client_outbound_host_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_client_outbound_host_options

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
```

```
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_outbound_host_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_client_outbound_host_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_client_outbound_host'

    Required/Optional: true

  Responses:
    '204':
      Description: container host updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: host
```

/data/tailf-mobile-infra:client/outbound/host/ping

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_put
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping'
       Required/Optional: true

    Responses:
      '201':
        Description: container ping created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ping
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping-post'
       Required/Optional: true

    Responses:
      '201':
        Description: container ping created
        Content: {}
      '204':
        Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ping
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_head

  Parameters:
  - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping'
      Required/Optional: true

    Responses:
      '204':
        Description: container ping updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ping
```

/data/tailf-mobile-infra:client/outbound/host/ping/timeout

```
  get:

    Tags:
```

```
- data
- get
Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_timeout_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_timeout'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_timeout_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_timeout'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf timeout created or replaced
```

```
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: timeout
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_timeout_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_timeout_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_timeout_head
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_timeout_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_timeout'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf timeout updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: timeout
```

/data/tailf-mobile-infra:client/outbound/host/ping/interval

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_interval_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_interval'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_interval_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_interval'
     Required/Optional: true

  Responses:
    '201':
      Description: leaf interval created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interval
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_interval_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_interval_options

  Responses:
    '200':
      Description: OK
      Content: {}
```

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_interval_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_interval_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_interval'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf interval updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: interval
```

/data/tailf-mobile-infra:client/outbound/host/ping/backoff

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_backoff_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_backoff'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_backoff_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_backoff'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf backoff created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: backoff
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_backoff_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_backoff_options
```

```
  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_backoff_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_backoff_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_backoff'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf backoff updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: backoff
```

/data/tailf-mobile-infra:client/outbound/host/ping/retry

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_retry_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_retry'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_retry_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_retry'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf retry created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: retry
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_retry_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:
```

```
  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_retry_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_retry_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_retry_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_retry'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf retry updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: retry
```

/data/tailf-mobile-infra:client/outbound/host/ping/fast-interval

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_fast_interval_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_fast-interval'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_fast_interval_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_fast-interval'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf fast-interval created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: fast-interval
 delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_fast_interval_delete


  Responses:
    '204':
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_fast_interval_options


  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_fast_interval_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_outbound_host_ping_fast_interval_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_fast-interval'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf fast-interval updated
        Content: {}
```

```
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: fast-interval
```

/data/tailf-mobile-infra:client/outbound/host/ping/all-host-down-i nterval

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_client_outbound_host_ping_all_host_down_interval_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_all-host-down-interval'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_outbound_host_ping_all_host_down_interval_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_all-host-down-interval'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf all-host-down-interval created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: all-host-down-interval
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_outbound_host_ping_all_host_down_interval_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_outbound_host_ping_all_host_down_interval_options

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_outbound_host_ping_all_host_down_interval_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_outbound_host_ping_all_host_down_interval_patch
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_all-host-down-interval'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf all-host-down-interval updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: all-host-down-interval
```

/data/tailf-mobile-infra:client/inbound

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_client_inbound_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_inbound'
  '204':
```

```
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_client_inbound_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_inbound'
    Required/Optional: true

  Responses:
    '201':
      Description: container inbound created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: inbound
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_client_inbound_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_client_inbound-post'

    Required/Optional: true

  Responses:
    '201':
      Description: container inbound created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: inbound
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_inbound_delete

  Responses:
    '204':
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_inbound_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_inbound_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_inbound_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_client_inbound'
      Required/Optional: true

    Responses:
      '204':
        Description: container inbound updated
        Content: {}
      '400':
        Description: Bad Request
```

```
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: inbound
```

/data/tailf-mobile-infra:client/inbound/interface

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_inbound_interface_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:client/inbound/interface={interface-inter face}

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_client_inbound_interface_interface_interface_get


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_inbound_interface_interface_interface_put


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: insert
```

```
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface'

      Required/Optional: true

    Responses:
      '201':
        Description: list interface created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_delete

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_options

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:
```

```
Tags:
- data
- head
Operation ID: data_tailf_mobile_infra_client_inbound_interface_interface_interface_head


Parameters:
- Name: interface-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_patch

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface'

      Required/Optional: true

    Responses:
      '204':
        Description: list interface updated
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface
```

/data/tailf-mobile-infra:client/inbound/interface={interface-interface}/interface

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_interface_get

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_interface'
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_interface_put

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_interface'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf interface created or replaced
        Content: {}
      '204':
        Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_interface_delete

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_interface_options

  Parameters:
  - Name: interface-interface
    In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_interface_head

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_interface_patch

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_interface'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf interface updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface
```

/data/tailf-mobile-infra:client/inbound/interface={interface-inter face}/limit

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_get

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_put

  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit'

      Required/Optional: true

    Responses:
      '201':
        Description: container limit created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: limit
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_post

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container limit created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: limit
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_delete

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
```

```
      Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_options

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_head

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_patch

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit'

      Required/Optional: true

    Responses:
      '204':
        Description: container limit updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: limit
```

/data/tailf-mobile-infra:client/inbound/interface={interface-inter face}/limit/pending

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_get

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
```

```
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_put

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending'

      Required/Optional: true

    Responses:
      '201':
        Description: container pending created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pending
```

```
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_post

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container pending created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pending
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_delete

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_options

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_head

    Parameters:
```

```
- Name: interface-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_patch

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending'

      Required/Optional: true

    Responses:
      '204':
        Description: container pending updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pending
```

/data/tailf-mobile-infra:client/inbound/interface={interface-inter face}/limit/pending/request

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_request_get


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending_request'

    '204':
      Description: No Content
      Content: {}
```

```
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_request_put


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending_request'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf request created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
```

```
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: request
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_request_delete


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_request_options


  Parameters:
  - Name: interface-interface
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_request_head


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_pending_request_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending_request'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf request updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: request
```

/data/tailf-mobile-infra:client/inbound/interface={interface-inter face}/limit/overload

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_get

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_put

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload'

      Required/Optional: true

    Responses:
      '201':
        Description: container overload created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: overload
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_post

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container overload created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: overload
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_delete

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
```

```
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_options


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_head

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_patch

    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload'

      Required/Optional: true

    Responses:
      '204':
        Description: container overload updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: overload
```

/data/tailf-mobile-infra:client/inbound/interface={interface-inter face}/limit/overload/reject-code

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_reject_code_get


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload_reject-code'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_reject_code_put


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload_reject-code'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf reject-code created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: reject-code
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_reject_code_delete


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_reject_code_options


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:
```

Tags:
- data
- head

Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_reject_code_head

Parameters:
- **Name**: interface-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_client_inbound_interface_interface_interface_limit_overload_reject_code_patch


    Parameters:
    - Name: interface-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload_reject-code'

      Required/Optional: true

    Responses:
```

```
    '204':
      Description: leaf reject-code updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: reject-code
```

/data/tailf-mobile-infra:client/inbound/limit

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_inbound_limit'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_client_inbound_limit'

    Required/Optional: true

  Responses:
    '201':
      Description: container limit created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: limit
```

```
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_client_inbound_limit_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_limit-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container limit created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: limit
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_client_inbound_limit_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:
```

```
  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_inbound_limit'

    Required/Optional: true

  Responses:
    '204':
      Description: container limit updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: limit
```

/data/tailf-mobile-infra:client/inbound/limit/pending

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_pending'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_pending'
    Required/Optional: true

  Responses:
    '201':
      Description: container pending created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pending
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
```

```
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_pending-post'
     Required/Optional: true

  Responses:
    '201':
      Description: container pending created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pending
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_options

  Responses:
    '200':
      Description: OK
      Content: {}
```

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_pending'
      Required/Optional: true

    Responses:
      '204':
        Description: container pending updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: pending
```

/data/tailf-mobile-infra:client/inbound/limit/pending/request

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_request_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_pending_request'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_request_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_pending_request'
       Required/Optional: true

    Responses:
      '201':
        Description: leaf request created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: request
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_request_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_request_options
```

```
  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_request_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_inbound_limit_pending_request_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_pending_request'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf request updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: request
```

/data/tailf-mobile-infra:client/inbound/limit/overload

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_overload'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_overload'
      Required/Optional: true

    Responses:
      '201':
        Description: container overload created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: overload
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_overload-post'
      Required/Optional: true
```

```
  Responses:
    '201':
      Description: container overload created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: overload
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:
```

```
Tags:
- data
- head
Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_overload'
      Required/Optional: true

    Responses:
      '204':
        Description: container overload updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: overload
```

/data/tailf-mobile-infra:client/inbound/limit/overload/reject-code

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_reject_code_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_overload_reject-code'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_reject_code_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_overload_reject-code'
     Required/Optional: true

  Responses:
    '201':
      Description: leaf reject-code created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: reject-code
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_reject_code_delete


  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_reject_code_options


  Responses:
    '200':
      Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_reject_code_head


  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
   Operation ID: data_tailf_mobile_infra_client_inbound_limit_overload_reject_code_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_overload_reject-code'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf reject-code updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
```

```
    Description: Conflict
    Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: reject-code
```

/data/tailf-mobile-infra:edr

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_edr_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_edr'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
```

```
  - put
  Operation ID: data_tailf_mobile_infra_edr_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_edr'
    Required/Optional: true

  Responses:
    '201':
      Description: container edr created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: edr
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_edr_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_edr-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container edr created
      Content: {}
    '204':
      Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: edr
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_edr_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_edr_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_edr_head

  Parameters:
  - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_edr_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_edr'
    Required/Optional: true

  Responses:
    '204':
      Description: container edr updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: edr
```

/data/tailf-mobile-infra:edr/reporting

```
get:

  Tags:
  - data
```

```
- get
Operation ID: data_tailf_mobile_infra_edr_reporting_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_edr_reporting'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_edr_reporting_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_edr_reporting'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf reporting created or replaced
      Content: {}
```

```
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: reporting
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_edr_reporting_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_edr_reporting_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_edr_reporting_head
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_edr_reporting_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_edr_reporting'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf reporting updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: reporting
```

/data/tailf-mobile-infra:edr/edrsubscribers

```
get:
```

```
Tags:
- data
- get
Operation ID: data_tailf_mobile_infra_edr_edrsubscribers_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_edr_edrsubscribers'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_edr_edrsubscribers_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_edr_edrsubscribers'

      Required/Optional: true

    Responses:
      '201':
```

```
      Description: container edrsubscribers created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: edrsubscribers
 Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_edr_edrsubscribers_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_edrsubscribers-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container edrsubscribers created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: edrsubscribers
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_edr_edrsubscribers_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_edr_edrsubscribers_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_edr_edrsubscribers_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_edr_edrsubscribers_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_edr_edrsubscribers'

    Required/Optional: true

  Responses:
    '204':
      Description: container edrsubscribers updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: edrsubscribers
```

/data/tailf-mobile-infra:edr/edrsubscribers/subscribers

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_edr_edrsubscribers_subscribers_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:edr/edrsubscribers/subscribers={subscribe rs-id}

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_edr_edrsubscribers_subscribers_subscribers_id_get


  Parameters:
  - Name: subscribers-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_edrsubscribers_subscribers_subscribers-id'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
put:

  Tags:
  - data
  - put
 Operation ID: data_tailf_mobile_infra_edr_edrsubscribers_subscribers_subscribers_id_put


  Parameters:
  - Name: subscribers-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_edrsubscribers_subscribers_subscribers-id'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf-list subscribers created or replaced
      Content: {}
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: subscribers
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_edr_edrsubscribers_subscribers_subscribers_id_delete

    Parameters:
    - Name: subscribers-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_edr_edrsubscribers_subscribers_subscribers_id_options

    Parameters:
```

```
    - Name: subscribers-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_edr_edrsubscribers_subscribers_subscribers_id_head

    Parameters:
    - Name: subscribers-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: integer
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        '200':
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_tailf_mobile_infra_edr_edrsubscribers_subscribers_subscribers_id_patch

      Parameters:
      - Name: subscribers-id
        In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_edrsubscribers_subscribers_subscribers-id'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf-list subscribers updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: subscribers
```

/data/tailf-mobile-infra:edr/all

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_edr_all_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_edr_all'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_edr_all_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_edr_all'
    Required/Optional: true

  Responses:
    '201':
      Description: container all created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: all
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_edr_all_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_edr_all-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container all created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: all
```

```
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_edr_all_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_edr_all_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_edr_all_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_edr_all_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
        Reference: '#/components/schemas/data_tailf-mobile-infra_edr_all'
    Required/Optional: true

  Responses:
    '204':
      Description: container all updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: all
```

/data/tailf-mobile-infra:edr/all/subscribers

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_edr_all_subscribers_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_edr_all_subscribers'

  '204':
    Description: No Content
    Content: {}
  '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_edr_all_subscribers_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_edr_all_subscribers'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf subscribers created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: subscribers
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_edr_all_subscribers_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_edr_all_subscribers_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_edr_all_subscribers_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_edr_all_subscribers_patch
    Request Body:
```

```
    Content:
      application/yang-data+json:
        Schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_edr_all_subscribers'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf subscribers updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: subscribers
```

/data/tailf-mobile-infra:edr/file

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_edr_file_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_edr_file'
```

```
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_edr_file_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_edr_file'
    Required/Optional: true

  Responses:
    '201':
      Description: container file created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: file
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_edr_file_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_edr_file-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container file created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: file
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_edr_file_delete

  Responses:
    '204':
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_edr_file_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_edr_file_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_edr_file_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_edr_file'
      Required/Optional: true

    Responses:
      '204':
        Description: container file updated
        Content: {}
      '400':
        Description: Bad Request
```

```
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: file
```

/data/tailf-mobile-infra:edr/file/files

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_edr_file_files_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:edr/file/files={files-name}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_get

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_put

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name'
      Required/Optional: true

    Responses:
      '201':
        Description: list files created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
  x-codegen-request-body-name: files
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_delete

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_options

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_head
```

```
Parameters:
- Name: files-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_patch

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name'
      Required/Optional: true

    Responses:
      '204':
        Description: list files updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: files
```

/data/tailf-mobile-infra:edr/file/files={files-name}/name

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_name_get

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_name'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_name_put

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_name'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf name created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_name_delete

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_name_options

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
```

```
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_name_head

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_name_patch

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_name'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf name updated
```

```
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: name
```

/data/tailf-mobile-infra:edr/file/files={files-name}/reporting

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_reporting_get

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_reporting'
    '204':
```

```
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_reporting_put

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_reporting'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf reporting created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
```

```
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: reporting
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_reporting_delete

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_reporting_options

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_reporting_head

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_reporting_patch

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_reporting'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf reporting updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: reporting
```

/data/tailf-mobile-infra:edr/file/files={files-name}/verbose

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_verbose_get

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_verbose'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_verbose_put

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_verbose'
      Required/Optional: true

    Responses:
      '201':
```

```
      Description: leaf verbose created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: verbose
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_verbose_delete

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_verbose_options
```

```
  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_verbose_head

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_verbose_patch

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_verbose'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf verbose updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: verbose
```

/data/tailf-mobile-infra:edr/file/files={files-name}/limit

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_get

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_limit'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_put

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_limit'
      Required/Optional: true

    Responses:
      '201':
        Description: container limit created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: limit
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_post

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

```
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_limit-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container limit created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: limit
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_delete

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:
```

```
  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_options

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_head

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_patch
```

```
    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_limit'
      Required/Optional: true

    Responses:
      '204':
        Description: container limit updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: limit
```

/data/tailf-mobile-infra:edr/file/files={files-name}/limit/size

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_size_get

    Parameters:
    - Name: files-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_limit_size'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_size_put

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_limit_size'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf size created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: size
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_size_delete

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_size_options

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_size_head

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_size_patch

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_limit_size'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf size updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: size
```

/data/tailf-mobile-infra:edr/file/files={files-name}/limit/count

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_count_get

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_limit_count'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_count_put

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_limit_count'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf count created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: count
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_count_delete
```

```
  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_count_options

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_count_head

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_count_patch

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_limit_count'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf count updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: count
```

/data/tailf-mobile-infra:edr/file/files={files-name}/limit/storage

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_storage_get

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_limit_storage'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_storage_put

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_limit_storage'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf storage created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  x-codegen-request-body-name: storage
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_storage_delete


  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_storage_options


  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
```

Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_storage_head

Parameters:
- **Name**: files-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_limit_storage_patch

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_limit_storage'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf storage updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: storage
```

/data/tailf-mobile-infra:edr/file/files={files-name}/rate

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_rate_get

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_rate'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
```

```
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_rate_put

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_rate'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf rate created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: rate
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_rate_delete

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_rate_options

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_rate_head

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_rate_patch

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_rate'
      Required/Optional: true

    Responses:
```

```
    '204':
      Description: leaf rate updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: rate
```

/data/tailf-mobile-infra:edr/file/files={files-name}/threshold

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_threshold_get

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

```
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_threshold'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_threshold_put

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_threshold'
      Required/Optional: true

    Responses:
      '201':
        Description: container threshold created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: threshold
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_threshold_post

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_threshold-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container threshold created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: threshold
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_threshold_delete

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_threshold_options

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_threshold_head

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_threshold_patch

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

```
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_threshold'
     Required/Optional: true

   Responses:
     '204':
       Description: container threshold updated
       Content: {}
     '400':
       Description: Bad Request
       Content: {}
     '401':
       Description: Unauthorized
       Content: {}
     '404':
       Description: Not Found
       Content: {}
     '405':
       Description: Method Not Allowed
       Content: {}
     '409':
       Description: Conflict
       Content: {}
   security:
   - basicAuth: []
   x-codegen-request-body-name: threshold
```

/data/tailf-mobile-infra:edr/file/files={files-name}/threshold/cpu

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_threshold_cpu_get

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_threshold_cpu'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_threshold_cpu_put

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_threshold_cpu'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf cpu created or replaced
        Content: {}
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu
  delete:

    Tags:
    - data
    - delete
   Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_threshold_cpu_delete


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
   Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_threshold_cpu_options


    Parameters:
```

```
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_threshold_cpu_head

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_threshold_cpu_patch

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_threshold_cpu'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf cpu updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu
```

/data/tailf-mobile-infra:edr/file/files={files-name}/threshold/ses sion

```
  get:

    Tags:
    - data
    - get
   Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_threshold_session_get


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_threshold_session'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_threshold_session_put


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_threshold_session'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf session created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: session
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_threshold_session_delete

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
```

```
      Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_threshold_session_options

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_threshold_session_head


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
   Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_threshold_session_patch


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_threshold_session'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf session updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: session
```

/data/tailf-mobile-infra:edr/file/files={files-name}/flush

```
  get:
```

```
Tags:
- data
- get
Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_flush_get

Parameters:
- Name: files-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        '200':
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_flush'
        '204':
          Description: No Content
          Content: {}
        '400':
          Description: Bad Request
          Content: {}
        '401':
          Description: Unauthorized
          Content: {}
        '404':
          Description: Not Found
          Content: {}
        '405':
          Description: Method Not Allowed
          Content: {}
        '409':
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    put:

      Tags:
      - data
      - put
      Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_flush_put
```

```
    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_flush'
      Required/Optional: true

    Responses:
      '201':
        Description: container flush created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: flush
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_flush_post

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_flush-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container flush created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: flush
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_flush_delete

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_flush_options

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_flush_head

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
 patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_flush_patch

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_flush'
    Required/Optional: true

  Responses:
    '204':
      Description: container flush updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: flush
```

/data/tailf-mobile-infra:edr/file/files={files-name}/flush/interva l

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_flush_interval_get

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_flush_interval'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_flush_interval_put

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_flush_interval'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf interval created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interval
  delete:

    Tags:
    - data
    - delete
   Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_flush_interval_delete
```

```
  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_flush_interval_options


  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_flush_interval_head

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
   Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_flush_interval_patch


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_flush_interval'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf interval updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
```

```
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: interval
```

/data/tailf-mobile-infra:edr/file/files={files-name}/procedure

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_procedure_get

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
```

```
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_procedure_put

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure'
      Required/Optional: true

    Responses:
      '201':
        Description: container procedure created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: procedure
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_procedure_post

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container procedure created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: procedure
```

```
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_procedure_delete

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_procedure_options

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_procedure_head

  Parameters:
```

```
- Name: files-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_edr_file_files_files_name_procedure_patch

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure'
      Required/Optional: true

    Responses:
      '204':
        Description: container procedure updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: procedure
```

/data/tailf-mobile-infra:edr/file/files={files-name}/procedure/enable-event-id

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_options

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:edr/file/files={files-name}/procedure/ena ble-event-id={enable-event-id-procedure}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_get
```

```
Parameters:
- Name: files-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: enable-event-id-procedure
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_put


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure'

Required/Optional: true

Responses:
'201':
Description: list enable-event-id created or replaced
Content: {}
'204':
Description: No Content
Content: {}
'400':
Description: Bad Request
Content: {}
'401':
Description: Unauthorized
Content: {}
'404':
Description: Not Found
Content: {}
'405':
Description: Method Not Allowed
Content: {}
'409':
Description: Conflict
Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: enable-event-id
delete:

Tags:
- data
- delete
Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_delete

Parameters:
- Name: files-name
In: path
Required/Optional: true
Style: simple
Explode: false
Schema:
Type: string
Format: identityref
- Name: enable-event-id-procedure
In: path
Required/Optional: true
Style: simple
Explode: false

```
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_options


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_head


    Parameters:
    - Name: files-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: enable-event-id-procedure
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_patch


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure'

      Required/Optional: true

    Responses:
      '204':
        Description: list enable-event-id updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable-event-id
```

/data/tailf-mobile-infra:edr/file/files={files-name}/procedure/ena ble-event-id={enable-event-id-procedure}/procedure

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_procedure_get


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
- Name: enable-event-id-procedure
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_procedure'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_procedure_put


    Parameters:
    - Name: files-name
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_procedure'

      Required/Optional: true

  Responses:
    '201':
      Description: leaf procedure created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: procedure
delete:

  Tags:
  - data
  - delete
```

```
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_procedure_delete

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_procedure_options

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_procedure_head


  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: enable-event-id-procedure
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_procedure_patch


    Parameters:
```

```
- Name: files-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: enable-event-id-procedure
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_procedure'

  Required/Optional: true

Responses:
  '204':
    Description: leaf procedure updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: procedure
```

/data/tailf-mobile-infra:edr/file/files={files-name}/procedure/ena ble-event-id={enable-event-id-procedure}/enable-inner

get:

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_get

Parameters:
- **Name**: files-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: enable-event-id-procedure
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_put


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner'

      Required/Optional: true

    Responses:
      '201':
        Description: container enable-inner created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
```

```
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable-inner
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_post


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner-post'

      Required/Optional: true
```

```
    Responses:
      '201':
        Description: container enable-inner created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable-inner
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_delete


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
```

```
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_options


  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: enable-event-id-procedure
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_head


  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: identityref
- Name: enable-event-id-procedure
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_patch


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner'
```

```
      Required/Optional: true

    Responses:
      '204':
        Description: container enable-inner updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable-inner
?
/data/tailf-mobile-infra:edr/file/files={files-name}/procedure/enable-event-id={enable-event-id-procedure}/enable-inner/event
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_get


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_put


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event'

      Required/Optional: true

    Responses:
      '201':
        Description: container event created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: event
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_post


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container event created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: event
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_delete
```

```
  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: enable-event-id-procedure
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_options


  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: enable-event-id-procedure
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_head


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_patch

    Parameters:
    - Name: files-name
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event'

      Required/Optional: true

    Responses:
      '204':
        Description: container event updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: event
?
/data/tailf-mobile-infra:edr/file/files={files-name}/procedure/enable-event-id={enable-event-id-procedure}/enable-inner/event/enable-field-id
: options:

    Tags:
    - data
    - options
    Operation ID:
```

data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_options

```
    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
?
/data/tailf-mobile-infra:edr/file/files={files-name}/procedure/enable-event-id={enable-event-id-procedure}/enable-inner/event/enable-field-id={enable-field-id-event}
: get:

    Tags:
    - data
    - get
    Operation ID:
```

data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_get

```
    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: enable-field-id-event
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_put


    Parameters:
```

```
- Name: files-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: enable-event-id-procedure
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: enable-field-id-event
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: insert
  In: query
  Description: controlling the order when adding new list elements
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: first
    enum:
    - first
    - last
    - before
    - after
- Name: point
  In: query
  Description: used to specify the insertion point
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
```

```
          Reference:
"#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event"

      Required/Optional: true

    Responses:
      '201':
        Description: list enable-field-id created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable-field-id
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_delete


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    - Name: enable-field-id-event
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_options


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: enable-field-id-event
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_head


  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: enable-event-id-procedure
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: enable-field-id-event
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
```

```
    - data
    - patch
  Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_patch

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: enable-event-id-procedure
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: enable-field-id-event
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id_procedure_enable-inner_event_enable-field-id_enable-field-id-event'

    Required/Optional: true

  Responses:
    '204':
      Description: list enable-field-id updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
```

```
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable-field-id
?
/data/tailf-mobile-infra:edr/file/files={files-name}/procedure/enable-event-id={enable-event-id-procedure}/enable-inner/event/enable-field-id={enable-field-id-event}/event
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_event_get


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: enable-field-id-event
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event_event'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_event_put


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: enable-field-id-event
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id_event_event'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf event created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: event
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_event_delete

    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: enable-field-id-event
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_event_options


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: string
  - Name: enable-field-id-event
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_event_head


  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: enable-event-id-procedure
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: enable-field-id-event
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_event_patch


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: enable-field-id-event
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event_event'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf event updated
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: event
?
/data/tailf-mobile-infra:edr/file/files={files-name}/procedure/enable-event-id={enable-event-id-procedure}/enable-inner/event/enable-field-id={enable-field-id-event}/enable
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_enable_get


  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: enable-event-id-procedure
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: enable-field-id-event
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra-edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event_enable'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf-mobile-infra-edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event_enable-put


  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: enable-field-id-event
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event_enable'

    Required/Optional: true

  Responses:
    '201':
      Description: container enable created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
Method: Post
```

```
  Tags:
  - data
  - post
  Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_enable_post

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: enable-event-id-procedure
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: enable-field-id-event
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event_enable-post'

    Required/Optional: true

  Responses:
    '201':
      Description: container enable created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_enable_delete


  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: enable-event-id-procedure
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: enable-field-id-event
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_enable_options


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: enable-field-id-event
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_enable_head


    Parameters:
    - Name: files-name
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: enable-event-id-procedure
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: enable-field-id-event
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_enable_patch


  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: enable-event-id-procedure
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: enable-field-id-event
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event_enable'

      Required/Optional: true

    Responses:
      '204':
        Description: container enable updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable
?
/data/tailf-mobile-infra:edr/file/files={files-name}/procedure/enable-event-id={enable-event-id-procedure}/enable-inner/event/enable-field-id={enable-field-id-event}/enable/field
: options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_enable_field_options
```

```
    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: enable-field-id-event
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
?
/data/tailf-mobile-infra:edr/file/files={files-name}/procedure/enable-event-id={enable-event-idprocedure}/enable-inner/event/enable-field-id={enable-field-idevent}/enable/field={field-id}
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_enable_field_field_id_get


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: identityref
- Name: enable-event-id-procedure
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: enable-field-id-event
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: field-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field_id_enable-field_id_event_enable-field_field-id'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_enable_field_field_id_put

  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: enable-event-id-procedure
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: enable-field-id-event
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: field-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event_enable-field-id-id'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf-list field created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: field
```

```
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_enable_field_field_id_delete


  Parameters:
  - Name: files-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: enable-event-id-procedure
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: enable-field-id-event
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: field-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
```

```
    - options
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_enable_field_field_id_options


    Parameters:
    - Name: files-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: enable-event-id-procedure
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: enable-field-id-event
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: field-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_enable_field_field_id_head
```

```
Parameters:
- Name: files-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: enable-event-id-procedure
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: enable-field-id-event
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: field-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_edr_file_files_files_name_procedure_enable_event_id_enable_event_id_procedure_enable_inner_event_enable_field_id_enable_field_id_event_enable_field_field_id_patch


    Parameters:
```

```
- Name: files-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: enable-event-id-procedure
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: enable-field-id-event
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: field-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/tailf-mobile-infa_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id_event_enable-field-id'

  Required/Optional: true

Responses:
  '204':
    Description: leaf-list field updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: field
```

/data/tailf-mobile-infra:instance

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_instance_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_instance'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_instance_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_instance'
      Required/Optional: true

    Responses:
      '201':
        Description: container instance created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instance
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_instance_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_instance-post'
      Required/Optional: true
```

```
  Responses:
    '201':
      Description: container instance created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instance
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_instance_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_instance_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:
```

```
Tags:
- data
- head
Operation ID: data_tailf_mobile_infra_instance_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_instance_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_instance'
    Required/Optional: true

  Responses:
    '204':
      Description: container instance updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instance
```

/data/tailf-mobile-infra:instance/instance-id

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_instance_instance_id_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
```

```
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id'
      Required/Optional: true

    Responses:
      '201':
        Description: list instance-id created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instance-id
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref

    Responses:
```

```
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_options

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_head

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_patch

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id'
      Required/Optional: true

    Responses:
      '204':
        Description: list instance-id updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instance-id
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/id:

```
  get:
```

```
Tags:
- data
- get
Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_id_get

Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_id'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_id_put
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_id'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf id created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: id
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_id_delete

    Parameters:
    - Name: instance-id-id
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_id_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_id_head

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_id_patch

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_id'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf id updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: id
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
 Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint'

    Required/Optional: true

  Responses:
    '201':
      Description: container endpoint created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: endpoint
  Method: Post

    Tags:
    - data
    - post
   Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_post


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container endpoint created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: endpoint
```

```
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_head
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_patch

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint'

      Required/Optional: true

    Responses:
      '204':
        Description: container endpoint updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
```

```
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: endpoint
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_options

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}

```
get:

  Tags:
```

```
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_get

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
```

```
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_put

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype'

      Required/Optional: true

    Responses:
      '201':
        Description: list ep created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ep
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_head

    Parameters:
    - Name: instance-id-id
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_patch

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype'

      Required/Optional: true

    Responses:
      '204':
        Description: list ep updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ep
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/eptype

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_eptype_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_eptype'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_eptype_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_eptype'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf eptype created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: eptype
  delete:

    Tags:
    - data
    - delete
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_eptype_delete

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_eptype_options

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_eptype_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_eptype_patch


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_eptype'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf eptype updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: eptype
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/replicas

```
  get:
```

```
    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_replicas_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_replicas'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_replicas_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_replicas'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf replicas created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: replicas
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_replicas_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_replicas_options
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_replicas_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_replicas_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_replicas'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf replicas updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replicas
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/nodes

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_nodes_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_nodes'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_nodes_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_nodes'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf nodes created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: nodes
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_nodes_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_nodes_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_nodes_head


    Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_nodes_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_nodes'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf nodes updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: nodes
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/loopbackEth

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackEth_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackEth'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackEth_put


    Parameters:
    - Name: instance-id-id
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackEth'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf loopbackEth created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: loopbackEth
  delete:

    Tags:
```

```
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackEth_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackEth_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackEth_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackEth_patch
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackEth'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf loopbackEth updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: loopbackEth
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/loopbackPort

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackPort_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackPort'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackPort_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackPort'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf loopbackPort created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
```

```
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: loopbackPort
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackPort_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackPort_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackPort_head

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_loopbackPort_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackPort'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf loopbackPort updated
        Content: {}
      '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: loopbackPort
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/instancetype

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_instancetype_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_instancetype'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_instancetype_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_instancetype'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf instancetype created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instancetype
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_instancetype_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_instancetype_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
```

```
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_instancetype_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_instancetype_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_instancetype'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf instancetype updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instancetype
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/vip

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_options


    Parameters:
    - Name: instance-id-id
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/vip={vip-vip-ip}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_put


    Parameters:
    - Name: instance-id-id
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip'

Required/Optional: true

Responses:
'201':
Description: list vip created or replaced
Content: {}
'204':
Description: No Content
Content: {}
'400':
Description: Bad Request
Content: {}
'401':
Description: Unauthorized
Content: {}
'404':
Description: Not Found
Content: {}
'405':
Description: Method Not Allowed
Content: {}
'409':
Description: Conflict
Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: vip
delete:

Tags:
- data
- delete
Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_delete

Parameters:
- Name: instance-id-id
In: path
Required/Optional: true
Style: simple
Explode: false
Schema:
Type: string
Format: leafref
- Name: ep-eptype
In: path
Required/Optional: true
Style: simple
Explode: false
Schema:

```
      Type: string
      Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
```

```
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
```

```
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_patch

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip'

      Required/Optional: true

    Responses:
      '204':
        Description: list vip updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/vip={vip-vip-ip}/vip-ip

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_ip_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-ip'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_ip_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-ip'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf vip-ip created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-ip
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_ip_delete
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_ip_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_ip_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_ip_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-ip'

      Required/Optional: true
```

```
Responses:
  '204':
    Description: leaf vip-ip updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: vip-ip
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/vip={vip-vip-ip}/vip-port

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_port_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-port'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_port_put


    Parameters:
```

```
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-port'

      Required/Optional: true

  Responses:
    '201':
      Description: leaf vip-port created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_port_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_port_options
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_port_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_port_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-port'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vip-port updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-port
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/vip={vip-vip-ip}/vip-interface

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_interface_get


    Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-interface'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_interface_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-interface'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf vip-interface created or replaced
        Content: {}
      '204':
```

```
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-interface
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_interface_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_interface_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
```

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_interface_head

Parameters:
- **Name**: instance-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vip_interface_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-interface'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vip-interface updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-interface
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/vip={vip-vip-ip}/offline

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_offline_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_offline'

  '204':
```

```
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_offline_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_offline'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf offline created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_offline_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_offline_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_offline_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_offline_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_offline'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf offline updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: offline
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/vip={vip-vip-ip}/vrf

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vrf_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vrf'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vrf_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vrf'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf vrf created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
  delete:

    Tags:
```

```
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vrf_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vrf_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vrf_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip_vip_vip_ip_vrf_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vrf'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vrf updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/vip6

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/vip6={vip6-vip-ipv6}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6'

    Required/Optional: true

  Responses:
    '201':
      Description: list vip6 created or replaced
      Content: {}
    '204':
```

```
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip6
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_head

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6'

      Required/Optional: true

    Responses:
      '204':
        Description: list vip6 updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip6
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/vip6={vip6-vip-ipv6}/vip-ipv6

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6'

    '204':
```

```
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf vip-ipv6 created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-ipv6
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vip-ipv6 updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
```

```
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: vip-ipv6
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/vip6={vip6-vip-ipv6}/vip-ipv6-port

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_port_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6-port'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_port_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6-port'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf vip-ipv6-port created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-ipv6-port
  delete:

    Tags:
```

```
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_port_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_port_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_port_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_ipv6_port_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6-port'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vip-ipv6-port updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-ipv6-port
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/vip6={vip6-vip-ipv6}/vip-interface

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_interface_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-interface'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
```

- put

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_interface_put

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string

Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-interface'

  Required/Optional: true

Responses:
  '201':
    Description: leaf vip-interface created or replaced
    Content: {}
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-interface
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_interface_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_interface_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_interface_head

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vip_interface_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-interface'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vip-interface updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-interface
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/vip6={vip6-vip-ipv6}/offline

```
  get:

    Tags:
    - data
```

```
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_offline_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
```

```
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_offline'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_offline_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_offline'

    Required/Optional: true
```

```
    Responses:
      '201':
        Description: leaf offline created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_offline_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_offline_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
```

```
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_offline_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_offline_patch
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_offline'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf offline updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: offline
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/vip6={vip6-vip-ipv6}/vrf

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vrf_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vrf'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vrf_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vrf'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf vrf created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vrf_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vrf_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vrf_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_vip6_vip6_vip_ipv6_vrf_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vrf'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vrf updated
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/system-health-level

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level'

      Required/Optional: true

    Responses:
      '201':
        Description: container system-health-level created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: system-health-level
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_post


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container system-health-level created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: system-health-level
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_delete
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: integer
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        '200':
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_patch

      Parameters:
      - Name: instance-id-id
        In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level'

      Required/Optional: true

    Responses:
      '204':
        Description: container system-health-level updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: system-health-level
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/system-health-level/warn

```
  get:
```

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn'

      Required/Optional: true

    Responses:
      '201':
        Description: container warn created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: warn
Method: Post

  Tags:
  - data
  - post
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_post


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn-post'

    Required/Optional: true

  Responses:
    '201':
      Description: container warn created
      Content: {}
    '204':
      Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: warn
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn'

    Required/Optional: true

  Responses:
    '204':
      Description: container warn updated
      Content: {}
```

```
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: warn
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/system-health-level/warn/cpu-percent
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_cpu_percent_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_cpu-percent'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_cpu_percent_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_cpu-percent'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf cpu-percent created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu-percent
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_cpu_percent_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_cpu_percent_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_cpu_percent_head
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_cpu_percent_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_cpu-percent'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf cpu-percent updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu-percent
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/system-health-level/warn/memory-in-mbs
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_memory_in_mbs_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_memory-in-mbs'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_memory_in_mbs_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_memory-in-mbs'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf memory-in-mbs created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: memory-in-mbs
  delete:

    Tags:
    - data
    - delete
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_memory_in_mbs_delete

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_memory_in_mbs_options

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_memory_in_mbs_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_memory_in_mbs_patch


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_memory-in-mbs'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf memory-in-mbs updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: memory-in-mbs
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/system-health-level/warn/num-of-goroutine
: get:

    Tags:
    - data
    - get
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_num_of_goroutine_get

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_num-of-goroutine'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_num_of_goroutine_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_num-of-goroutine'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf num-of-goroutine created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: num-of-goroutine
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_num_of_goroutine_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_num_of_goroutine_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_num_of_goroutine_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_warn_num_of_goroutine_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_num-of-goroutine'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf num-of-goroutine updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
```

```
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: num-of-goroutine
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/system-health-level/critical

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical'

    '204':
      Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical'

    Required/Optional: true
```

```
  Responses:
    '201':
      Description: container critical created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: critical
Method: Post

  Tags:
  - data
  - post
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_post


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container critical created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: critical
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_head
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical'

      Required/Optional: true

    Responses:
      '204':
        Description: container critical updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: critical
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/system-health-level/critical/cpu-percent
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_cpu_percent_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_cpu-percent'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_cpu_percent_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_cpu-percent'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf cpu-percent created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu-percent
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_cpu_percent_delete
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_cpu_percent_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_cpu_percent_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_cpu_percent_patch


  Parameters:
  - Name: instance-id-id
    In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_cpu-percent'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf cpu-percent updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu-percent
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/system-health-level/critical/memory-in-mbs
: get:

    Tags:
    - data
    - get
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_memory_in_mbs_get

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_memory-in-mbs'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_memory_in_mbs_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_memory-in-mbs'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf memory-in-mbs created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory-in-mbs
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_memory_in_mbs_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_memory_in_mbs_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_memory_in_mbs_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_memory_in_mbs_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_memory-in-mbs'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf memory-in-mbs updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
```

```
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: memory-in-mbs
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/system-health-level/critical/num-of-goroutine
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_num_of_goroutine_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
```

```
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_num-of-goroutine'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
```

```
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_num_of_goroutine_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_num-of-goroutine'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf num-of-goroutine created or replaced
        Content: {}
```

```
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: num-of-goroutine
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_num_of_goroutine_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_num_of_goroutine_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_num_of_goroutine_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_critical_num_of_goroutine_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_num-of-goroutine'

      Required/Optional: true

    Responses:
      '204':
```

```
      Description: leaf num-of-goroutine updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: num-of-goroutine
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/system-health-level/crash

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash'

      Required/Optional: true

    Responses:
      '201':
        Description: container crash created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: crash
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_post


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container crash created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: crash
  delete:

    Tags:
    - data
    - delete
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_delete

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_options

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_patch


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
   Request Body:
     Content:
       application/yang-data+json:
         Schema:
           Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash'

      Required/Optional: true

   Responses:
     '204':
       Description: container crash updated
       Content: {}
     '400':
       Description: Bad Request
       Content: {}
     '401':
       Description: Unauthorized
       Content: {}
     '404':
       Description: Not Found
       Content: {}
     '405':
       Description: Method Not Allowed
       Content: {}
     '409':
       Description: Conflict
       Content: {}
   security:
   - basicAuth: []
   x-codegen-request-body-name: crash
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/system-health-level/crash/cpu-percent
: get:

   Tags:
   - data
   - get
   Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_cpu_percent_get

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_cpu-percent'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_cpu_percent_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_cpu-percent'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf cpu-percent created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cpu-percent
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_cpu_percent_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_cpu_percent_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_cpu_percent_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_cpu_percent_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_cpu-percent'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf cpu-percent updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
```

```
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu-percent
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/system-health-level/crash/memory-in-mbs
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_memory_in_mbs_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
```

```
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_memory-in-mbs'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
```

```
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_memory_in_mbs_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_memory-in-mbs'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf memory-in-mbs created or replaced
        Content: {}
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: memory-in-mbs
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_memory_in_mbs_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_memory_in_mbs_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_memory_in_mbs_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_memory_in_mbs_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_memory-in-mbs'

      Required/Optional: true

    Responses:
      '204':
```

```
      Description: leaf memory-in-mbs updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory-in-mbs
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/system-health-level/crash/num-of-goroutine
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_num_of_goroutine_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_num-of-goroutine'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_num_of_goroutine_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_num-of-goroutine'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf num-of-goroutine created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: num-of-goroutine
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_num_of_goroutine_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
```

```
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_num_of_goroutine_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_num_of_goroutine_head

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_system_health_level_crash_num_of_goroutine_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_num-of-goroutine'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf num-of-goroutine updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: num-of-goroutine
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/monitor

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_put
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor'

  Required/Optional: true

Responses:
  '201':
    Description: container monitor created or replaced
    Content: {}
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: monitor
```

```
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_post


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container monitor created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor'

      Required/Optional: true

    Responses:
      '204':
        Description: container monitor updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
```

```
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/monitor/protocol

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_protocol_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor_protocol'

    '204':
      Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_protocol_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor_protocol'

    Required/Optional: true
```

```
  Responses:
    '201':
      Description: leaf protocol created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: protocol
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_protocol_delete


  Parameters:
  - Name: instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
```

```
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_protocol_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_protocol_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_monitor_protocol_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor_protocol'
```

```
    Required/Optional: true

  Responses:
    '204':
      Description: leaf protocol updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: protocol
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/uri-scheme

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_uri_scheme_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_uri-scheme'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_uri_scheme_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_uri-scheme'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf uri-scheme created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: uri-scheme
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_uri_scheme_delete


    Parameters:
```

```
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_uri_scheme_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_uri_scheme_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_uri_scheme_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_uri-scheme'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf uri-scheme updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: uri-scheme
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/mtls-enable

```
  get:

    Tags:
    - data
```

```
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_mtls_enable_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_mtls-enable'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
```

```
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_mtls_enable_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_mtls-enable'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf mtls-enable created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
```

```
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: mtls-enable
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_mtls_enable_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_mtls_enable_options


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_mtls_enable_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_mtls_enable_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_mtls-enable'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf mtls-enable updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: mtls-enable
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/certificate-name

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_certificate_name_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_certificate-name'
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_certificate_name_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_certificate-name'
```

```
    Required/Optional: true

  Responses:
    '201':
      Description: leaf certificate-name created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: certificate-name
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_certificate_name_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_certificate_name_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_certificate_name_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_certificate_name_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

```
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_certificate-name'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf certificate-name updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: certificate-name
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/service

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/service={service-service-name}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name'

    Required/Optional: true

  Responses:
    '201':
      Description: list service created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
```

```
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: service
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_head
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
        Type: string
        Format: leafref
      - Name: ep-eptype
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: identityref
      - Name: service-service-name
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name'

        Required/Optional: true

      Responses:
        '204':
          Description: list service updated
          Content: {}
        '400':
          Description: Bad Request
          Content: {}
        '401':
          Description: Unauthorized
          Content: {}
        '404':
          Description: Not Found
          Content: {}
        '405':
          Description: Method Not Allowed
          Content: {}
        '409':
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
      x-codegen-request-body-name: service
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/service-name
: get:
```

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_service_name_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_service-name'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_service_name_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_service-name'
```

```
    Required/Optional: true

  Responses:
    '201':
      Description: leaf service-name created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: service-name
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_service_name_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_service_name_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
```

```
      Description: OK
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_service_name_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
```

```
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
```

```
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_service_name_patch

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_service-name'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf service-name updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: service-name
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface
: options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}
: get:
```

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type'
```

```
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type'

    Required/Optional: true

  Responses:
    '201':
      Description: list interface created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
```

```
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type'

```
      Required/Optional: true

    Responses:
      '204':
        Description: list interface updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/interface-type
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_interface_type_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_interface-type'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
Tags:
- data
- put
Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_interface_type_put

Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_interface-type'

  Required/Optional: true

Responses:
  '201':
    Description: leaf interface-type created or replaced
    Content: {}
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface-type
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_interface_type_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_interface_type_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_interface_type_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_interface_type_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_interface-type'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf interface-type updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface-type
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/loopback#ch
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_loopback#ch_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_loopback'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_loopback$th_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_loopback$th'
```

```
    Required/Optional: true

  Responses:
    '201':
      Description: leaf loopbackEth created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: loopbackEth
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_loopbackEth_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_loopback_Eth_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_loopback_Eth_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_loopback1_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_loopbackEth'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf loopbackEth updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: loopbackEth
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/loopbackPort
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_loopbackPort_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
```

```
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_loopback-Port'

  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_loopback0ort_put

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_loopbackPort'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf loopbackPort created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: loopbackPort
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_loopbackPort_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_loopback0ort_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_loopbackPort_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface_interface-type_loopback-Port_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_loopbackPort'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf loopbackPort updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: loopbackPort
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/uri-scheme
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_uri-scheme_get
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_uri-scheme'

    '204':
      Description: No Content
      Content: {}
    '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_uri_scheme_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_uri-scheme'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf uri-scheme created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: uri-scheme
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_uri-scheme_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_uri_scheme_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
```

```
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_uri_scheme_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_uri_scheme_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_uri-scheme'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf uri-scheme updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: uri-scheme
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/instancetype
```

```
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_instancetype_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_instancetype'

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_instancetype_put

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_instancetype'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf instancetype created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instancetype
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_instancetype_delete
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_instancetype_options


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_instancetype_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_instancetype_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_instancetype'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf instancetype updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instancetype
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/tls-enable
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_tls_enable_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_tls-enable'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_tls_enable_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_tls-enable'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf tls-enable created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: tls-enable
  delete:
```

```
  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_tls_enable_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
```

```
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_tls_enable_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_tls_enable_head
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_tls_enable_patch


    Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_tls-enable'

  Required/Optional: true

Responses:
  '204':
    Description: leaf tls-enable updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
```

```
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: tls-enable
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/tls-enable
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_tls_enable_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_rtls-enable'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_rtls-enable_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
```

```
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_mtls-enable'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf mtls-enable created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: mtls-enable
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_mtls_enable_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
```

```
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_mtls-enable_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:
```

```
Tags:
- data
- head
Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_mtls_enable_head

Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
```

```
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
```

```
    - data
    - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_mtls_enable_patch

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_mtls-enable'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf mtls-enable updated
      Content: {}
    '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: mtls-enable
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/certificate-name
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_certificate_name_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_certificate-name'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_certificate-name_put


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_certificate-name'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf certificate-name created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: certificate-name
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_certificate_name_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
```
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_certificate_name_options

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_certificate_name_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_certificate_name_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_certificate-name'

      Required/Optional: true
```

```
    Responses:
      '204':
        Description: leaf certificate-name updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: certificate-name
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/sla
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_put

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref

Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla'

  Required/Optional: true

Responses:
  '201':
    Description: container sla created or replaced
    Content: {}
  '204':
    Description: No Content
    Content: {}

```
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sla
Method: Post

  Tags:
  - data
  - post
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_post


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container sla created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: sla
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla_delete


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla'

    Required/Optional: true

  Responses:
    '204':
      Description: container sla updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sla
```

?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/sla/response
: get:

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_response_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla_response'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_response_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla_response'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf response created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: response
  delete:

    Tags:
    - data
    - delete
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_response_delete

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_response_options

```
  Parameters:
```

```
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_response_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_response_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla_response'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf response updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: response
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/sla/procedure
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_procedure_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla_procedure'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_procedure_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla_procedure'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf procedure created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  x-codegen-request-body-name: procedure
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_procedure_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
```

```
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_procedure_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_procedure_head
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sla_procedure_patch

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla_procedure'

  Required/Optional: true

Responses:
  '204':
    Description: leaf procedure updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: procedure
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/vip
: options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/vip={vip-vip-ip}
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_put


    Parameters:
    - Name: instance-id-id
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: insert
  In: query
  Description: controlling the order when adding new list elements
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: first
    enum:
    - first
    - last
```

```
      - before
      - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip'

      Required/Optional: true

    Responses:
      '201':
        Description: list vip created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_delete
```

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
```

```
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
```

```
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_head

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip'

      Required/Optional: true

    Responses:
      '204':
        Description: list vip updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/vip={vip-vip-ip}/vip-ip
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-ip_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-ip'

    '204':
      Description: No Content
      Content: {}
    '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_ip_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-ip'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf vip-ip created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-ip
  delete:

    Tags:
    - data
    - delete
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_ip_delete

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

Tags:
- data
- options

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_ip_options

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string

Responses:
  '200':
    Description: OK

```
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_ip_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_ip_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-ip'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vip-ip updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-ip
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/vip={vip-vip-ip}/vip-port
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-port_get

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-port'

    '204':
      Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_port_put

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-port'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf vip-port created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-port
  delete:

    Tags:
```

```
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_port_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
```

```
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_port_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
```

```
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_port_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_port_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-port'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vip-port updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-port
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/vip={vip-vip-ip}/vip-interface
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-interface-get

    Parameters:
    - Name: instance-id-id
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
```

```
    - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-interface'
```

```
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_interface_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-interface'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf vip-interface created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-interface
  delete:
```

Tags:
- data
- delete

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_interface_delete

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string

Responses:
  '204':
    Description: No Content

```
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip_interface_options

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_interface_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vip_interface_patch

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-interface'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vip-interface updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-interface
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/vip={vip-vip-ip}/offline
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_offline_get
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
```

```
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_offline'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_offline_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_offline'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf offline created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: offline
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_offline_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_offline_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
```
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_offline_head

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_offline_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_offline'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf offline updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/vip={vip-vip-ip}/vrf
: get:

    Tags:
    - data
    - get
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vrf_get

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vrf'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vrf_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vrf'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf vrf created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vrf_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vrf_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vrf_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip_vip_vip_ip_vrf_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vrf'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vrf updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/sec-vip
: options:

    Tags:
```

```
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/sec-vip={sec-vip-sec-vip-ip}
: get:

    Tags:
    - data
    - get
```

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip_sec-vip-ip_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: insert
  In: query
  Description: controlling the order when adding new list elements
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: first
    enum:
    - first
    - last
    - before
    - after
- Name: point
  In: query
  Description: used to specify the insertion point
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
```

'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip'

```
    Required/Optional: true

  Responses:
    '201':
      Description: list sec-vip created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip
delete:

  Tags:
  - data
  - delete
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_delete

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_patch
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip'

  Required/Optional: true

Responses:
  '204':
```

```
      Description: list sec-vip updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/sec-vip={sec-vip-sec-vip-ip}/sec-vip-ip
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_sec_vip_ip_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_service-ip_service-ip_service-ip_service-ip'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_ip_sec_vip_ip_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-ip_sec-vip-ip"

      Required/Optional: true

    Responses:
      '201':
        Description: leaf sec-vip-ip created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: sec-vip-ip
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-ip_sec-vip-ip_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_sec_vip_ip_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
```

```
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_end-point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_sec-vip_ip_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_sec_vip_ip_patch

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string

Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:

'#/components/schemas/data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_sec_vip_ip'

  Required/Optional: true

```
    Responses:
      '204':
        Description: leaf sec-vip-ip updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: sec-vip-ip
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/sec-vip={sec-vip-sec-vip-ip}/vipport
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vipport_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_service-ip_service-ip-ip-ip-port'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-ip_vip-port_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-ip_vip_port'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf vip-port created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_ip_vip_port_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_port_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_port_head


    Parameters:
    - Name: instance-id-id
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
```

```
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
```

```
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_ip_vip_port_patch

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_ip_vip_port'
```

```
      Required/Optional: true

    Responses:
      '204':
        Description: leaf vip-port updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-port
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/sec-vip={sec-vip-sec-vip-ip}/vip-interface
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_interface_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_service-ip_service-ip-ip_ip-interface'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_interface_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sc-vip_sc-vip_sc-vip-ip_vip-interface'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf vip-interface created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-interface
 delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sc-vip_sc-vip_sc-vip-ip_vip-interface_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
```

```
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_interface_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_interface_head


    Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

Tags:
- data
- patch

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_interface_patch

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string

Request Body:
  Content:
    application/yang-data+json:
      Schema:

```
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip_sec-vip_ip_vip-interface'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vip-interface updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-interface
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/sec-vip={sec-vip-sec-vip-ip}/offline
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip_sec-vip_ip_offline_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_service_service-ip_service-ip_ip_offline'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_offline_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_offline"

      Required/Optional: true

    Responses:
      '201':
        Description: leaf offline created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id_id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_offline_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_offline_options


    Parameters:
    - Name: instance-id-id
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_offline_head

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
```

```
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_offline_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_offline'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf offline updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/sec-vip={sec-vip-sec-vip-ip}/vrf
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip_sec-vip-ip_vrf_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
```

```
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sc-vip_sc-vip-sc-vip-ip_vrf'

  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vrf_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vrf'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf vrf created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vrf_delete


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vrf_options
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
```

```
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vrf_head

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vrf_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_ip_vrf'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf vrf updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/vip6
: options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
```

```
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/vip6={vip6-vip-ipv6}
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
```

```
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6'

  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_put

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: insert
  In: query
  Description: controlling the order when adding new list elements
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: first
    enum:
    - first
    - last
    - before
    - after
- Name: point
  In: query
  Description: used to specify the insertion point
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6'

  Required/Optional: true

Responses:
  '201':
    Description: list vip6 created or replaced
    Content: {}
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip6
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6'

    Required/Optional: true

  Responses:
    '204':
      Description: list vip6 updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip6
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/vip6={vip6-vip-ipv6}/vip-ipv6
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf vip-ipv6 created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
```

```
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ipv6
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf vip-ipv6 updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-ipv6
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/vip6={vip6-vip-ipv6}/vip-ipv6-port
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_port_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6-port'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6-port_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6-port'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf vip-ipv6-port created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ipv6-port
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_port_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_port_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_port_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_port_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6-port'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf vip-ipv6-port updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ipv6-port
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/vip6={vip6-vip-ipv6}/vip-interface
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_interface_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ip6_vip-interface'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ip6_vip-interface_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf vip-interface created or replaced
      Content: {}
    '204':
      Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-interface
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_interface_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_interface_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_interface_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_interface_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface'

      Required/Optional: true

  Responses:
    '204':
      Description: leaf vip-interface updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-interface
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/vip6={vip6-vip-ipv6}/offline
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_offline_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline_put


    Parameters:
    - Name: instance-id-id
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf offline created or replaced
      Content: {}
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_offline_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_offline_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_offline_head

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_offline_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf offline updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/vip6={vip6-vip-ipv6}/vrf
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_put
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf'

  Required/Optional: true

Responses:
  '201':
```

```
      Description: leaf vrf created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf'

      Required/Optional: true

  Responses:
    '204':
      Description: leaf vrf updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/sec-vip6
: options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/sec-vip6={sec-vip6-sec-vip-ipv6}
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_put
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: insert
  In: query
  Description: controlling the order when adding new list elements
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: first
```

```
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-ip6'

    Required/Optional: true

  Responses:
    '201':
      Description: list sec-vip6 created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip6
delete:

  Tags:
  - data
  - delete
```

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_delete

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string

Responses:
  '204':
    Description: No Content
    Content: {}
security:
- **basicAuth**: []

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_patch

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6'

      Required/Optional: true

    Responses:
      '204':
        Description: list sec-vip6 updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: sec-vip6
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/sec-vip6={sec-vip6-sec-vip-ipv6}/sec-vip-ipv6
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_sec-vip-ipv6-get


    Parameters:
    - Name: instance-id-id
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
```

```
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_ip6_ip6-ip6-ip6-ip6"

  '204':
```

```
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_sec_vip_ipv6_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_tailfmobile-infa_instance_instance-id_instance-id-id_endpoint_ep_eptype_service_service-name_interface_interface-interface-type_sec-vip6_sec-vip6_sec-vip-ipv6_sec-vip-ipv6"

    Required/Optional: true

  Responses:
    '201':
      Description: leaf sec-vip-ipv6 created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip-ipv6
delete:
```

Tags:
- data
- delete

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_sec_vip_ipv6_delete

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string

Responses:
  '204':
    Description: No Content
    Content: {}

```
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_sec_vip_ipv6_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_sec_vip_ipv6_head

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_sec_vip_ipv6_patch

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_sec-vip-ipv6'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf sec-vip-ipv6 updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: sec-vip-ipv6
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/sec-vip6={sec-vip6-sec-vip-ipv6}/ip-ipv6-port
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_ip-ipv6-port_get


    Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
```

```
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_ipv6_ipv6-ipv6-ip_ipv6-ipv6-port'
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_ipv6_port_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-ipv6-port'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf vip-ipv6-port created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ipv6-port
```

delete:

Tags:
- data
- delete

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_ipv6_port_delete

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string

Responses:
  '204':

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_ipv6_port_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_ipv6_port_head

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sc_vip6_sc_vip6_sc_vip_ipv6_vip_ipv6_port_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6_sec-vip-ipv6_vip-ipv6-port"

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vip-ipv6-port updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-ipv6-port
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/sec-vip6={sec-vip6-sec-vip-ipv6}/vip-interface
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6_sec-vip-ipv6_vip-interface_get
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
```

```
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sc-vip6_sc-vip6_sc-vip-ipv6_vip-interface'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sc-vip6_sc-vip6_sc-vip-ipv6_vip-interface_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-interface'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf vip-interface created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: vip-interface
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_end-point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6_sec-vip-ipv6_vip-interface_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_interface_options

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_interface_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sc_vip6_sc_vip6_sc_vip_ipv6_vip_interface_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-interface'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vip-interface updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-interface
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/sec-vip6={sec-vip6-sec-vip-ipv6}/offline
: get:

    Tags:
    - data
    - get
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_offline_get

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6_sec-vip-ip6_offline'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6_sec-vip-ip6_offline_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_offline'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf offline created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_offline_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_offline_options

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_offline_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_offline_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_offline'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf offline updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: offline
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/sec-vip6={sec-vip6-sec-vip-ipv6}/of
: get:

  Tags:
```

- data
- get

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vrf_get

Parameters:

- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6_sec-vip-ipv6_vrf"

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id_id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6_sec-vip-ipv6_vrf_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6-vrf'

  Required/Optional: true

Responses:
  '201':
    Description: leaf vrf created or replaced
    Content: {}
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vrf_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vrf_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vrf_head

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ip6_vrf_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vrf'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vrf updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/vrf
```

```
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vrf_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vrf'

```
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
```

data_tailf-mobile-infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vrf_put

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vrf'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf vrf created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vrf_delete
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vrf_options


    Parameters:
    - Name: instance-id-id
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vrf_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_vrf_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vrf'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf vrf updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/dispatcher
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher'

      Required/Optional: true

    Responses:
      '201':
        Description: container dispatcher created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: dispatcher
  Method: Post
```

```
  Tags:
  - data
  - post
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_post

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher-post'

    Required/Optional: true

  Responses:
    '201':
      Description: container dispatcher created
```

```
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dispatcher
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_patch

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher'

    Required/Optional: true

  Responses:
    '204':
      Description: container dispatcher updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dispatcher
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/dispatcher/count
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_count_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
```

```
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_out'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_count_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_count'
```

```
    Required/Optional: true

  Responses:
    '201':
      Description: leaf count created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: count
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_count_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_count_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_count_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_count_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_count'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf count updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: count
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/dispatcher/capacity
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_capacity_get


    Parameters:
    - Name: instance-id-id
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
```

```
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_capacity'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_capacity_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_capacity'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf capacity created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: capacity
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_capacity_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_capacity_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_capacity_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_capacity_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_capacity'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf capacity updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: capacity
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/dispatcher/outbound
: get:

    Tags:
    - data
    - get
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_outbound_get

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_outbound'

    '204':
      Description: No Content
      Content: {}
    '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_outbound_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_outbound'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf outbound created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: outbound
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_outbound_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_outbound_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
```

```
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_outbound_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_outbound_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_outbound'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf outbound updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: outbound
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/dispatcher/rate-limit
```

```
: get:

   Tags:
   - data
   - get
   Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_rate_limit_get

   Parameters:
   - Name: instance-id-id
     In: path
     Required/Optional: true
     Style: simple
     Explode: false
     Schema:
       Type: string
       Format: leafref
   - Name: ep-eptype
     In: path
     Required/Optional: true
     Style: simple
     Explode: false
     Schema:
       Type: string
       Format: identityref
   - Name: service-service-name
     In: path
     Required/Optional: true
     Style: simple
     Explode: false
     Schema:
       Type: string
       Format: string
   - Name: interface-interface-type
     In: path
     Required/Optional: true
     Style: simple
     Explode: false
     Schema:
       Type: string
       Format: identityref
   - Name: content
     In: query
     Description: controlling descendant nodes in response
     Required/Optional: false
     Style: form
     Explode: true
     Schema:
       Type: string
       Format: enumeration
       Default: config
       enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_rate-limit'

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_rate_limit_put

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_rate-limit"

      Required/Optional: true

    Responses:
      '201':
        Description: leaf rate-limit created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: rate-limit
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_rate-limit_delete
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_rate_limit_options


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_rate_limit_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_rate_limit_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_rate-limit'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf rate-limit updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: rate-limit
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/dispatcher/cache
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_cache_get

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_cache'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_cache_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_cache'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf cache created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cache
delete:
```

```
  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_cache_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
 options:

  Tags:
  - data
  - options
```

```
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_cache_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_cache_head
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_cache_patch


  Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_cache'

  Required/Optional: true

Responses:
  '204':
    Description: leaf cache updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cache
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/dispatcher/threshold
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_threshold_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_threshold'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_threshold_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
```

```
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_threshold'

  Required/Optional: true

Responses:
  '201':
    Description: leaf threshold created or replaced
    Content: {}
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
```

```
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: threshold
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_threshold_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
```

```
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_threshold_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:
```

Tags:
- data
- head

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_threshold_head

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
```

```
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_threshold_patch

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_threshold'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf threshold updated
        Content: {}
      '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: threshold
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/dispatcher/expiry
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_expiry_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_expiry'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_expiry_put


    Parameters:
    - Name: instance-id-id
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
 Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_expiry'

    Required/Optional: true

 Responses:
    '201':
      Description: leaf expiry created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: expiry
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_expiry_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_expiry_options

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_expiry_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_expiry_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_expiry'

      Required/Optional: true
```

```
    Responses:
      '204':
        Description: leaf expiry updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: expiry
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/dispatcher/nonresponsive
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_nonresponsive_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_responsive'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_nonresponsive_put

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref

Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_nonresponsive'

  Required/Optional: true

Responses:
  '201':
    Description: leaf nonresponsive created or replaced
    Content: {}
  '204':
    Description: No Content
    Content: {}

```
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: nonresponsive
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_nonresponsive_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_noresponsive_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_nonresponsive_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_nonresponsive_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_nonresponsive'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf nonresponsive updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: nonresponsive
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/dispatcher/flowctrl-group
: options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/dispatcher/flowctrl-grop={flowctrl-grop-name}
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-grop_flowctrl-grop-name_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_fwd-group_fwd-group-name'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
```

```
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name'

      Required/Optional: true

  Responses:
    '201':
      Description: list flowctrl-group created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: flowctrl-group
delete:

  Tags:
  - data
  - delete
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_end_point_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_delete

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_end-point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctl_group_flowctl_group_name_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_interface-type-ref_flowctrl-group_flowctrl-group-name'

    Required/Optional: true

  Responses:
    '204':
      Description: list flowctrl-group updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
    x-codegen-request-body-name: flowctrl-group
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/dispatcher/flowctrl-group={flowctrl-group-name}/ne
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_ne_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flow-ctrl-grp_flow-ctrl-grp-name_get'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flow-ctrl-grp_flow-ctrl-grp-name_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
 Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_flowctrl-group_flowctrl-group-name'

    Required/Optional: true

 Responses:
    '201':
      Description: leaf name created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctl_grp_flowctl_grp_name_name_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_name_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_end_point_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_name_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flow_ctrl_group_flow_ctrl_group_name_name_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name'

  Required/Optional: true

Responses:
  '204':
    Description: leaf name updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
```

```
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/dispatcher/flowctrl-group={flowctrl-group-name}/capacity
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_capacity_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctl_group_flowctl_group_name_capacity'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctl_group_flowctl_group_name_capacity_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
```

```
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/tailf-mobile-infra:instance_instance-id_end point_ep_ep-eptype_service_service-service_interface_interface-interface-type_ipsec_flowctrl-group_flowctrl-group-name_capacity'

  Required/Optional: true

Responses:
  '201':
    Description: leaf capacity created or replaced
    Content: {}
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: capacity
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flow_ctrl_group_flow_ctrl_group_name_capacity_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_end_point_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_capacity_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_end-point_ep_ep-eptype_service_service-service-name_interface_interface-id_interface-type_dispatcher_flowctrl-group_flowctrl-group-name_capacity_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_end_point_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctl_group_flowctl_group_name_capacity_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_flowctrl-group_flowctrl-group-name_capacity'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf capacity updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: capacity
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/dispatcher/flowctrl-group={flowctrl-group-name}/rate-limit
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface_interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate-limit_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infa_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctl-group_flowctl-group-rate-limit'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf-mobile-infa_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctl-group_flowctl-group-rate-limit_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/tailf-mobile-infra:instance/instance-id/end point/ep/service/service-name/interface/interface-interface-type/data/flowctrl-group/flowctrl-group-name/rate-limit'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf rate-limit created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
```

```
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: rate-limit
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_end_point_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flow_ctrl_group_flow_ctrl_group_name_rate_limit_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface_interface-type-dispatcher_flowctrl-group_flowctrl-group-name_rate-limit-options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_rate_limited


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_rate_limit_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/tailf-mobile-infra:instance-instance-id-endpoint-ep-eptype-service-service-name-interface-interface-type-flowctrl-group-flowctrl-group-name-rate-limit'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf rate-limit updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: rate-limit
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/dispatcher/flowctrl-group={flowctrl-group-name}/token-capacity
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_end-point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_token-capacity_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher-flow-control-group_flow-control-group-name_downlink-policy'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher-flow-control-group_flow-control-group-name_downlink-policy_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/tailf-mobile-infra_instance_instance-id_end point_ep_eptype_service_service-name_interface_interface-type_flowctrl-group_flowctrl-group-name_outbound-capacity'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf outbound-capacity created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
```

```
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: outbound-capacity
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_end_point_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dscp_for_ctrl_grp_for_ctrl_grp_name_outbound_capacity_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_end-point_ep_ep-eptype_service_service-service-name_interface_interface-type_dispatcher_flowctrl-group_flowctrl-group-name_operation_options

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_end_point_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_flowctrl_group_flowctrl_group_name_action_activate_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_end_point_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flow_control_group_flow_control_group_name_downlink_policy_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_end point_ep_service_service-name_interface_interface-type_data_flowctrl-group_flowctrl-group-name_outbound-capacity'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf outbound-capacity updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
```

```
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: outbound-capacity
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/dispatcher-flow-control-group={flow-control-group-name}/outbound-limit
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_end_point_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flow_control_group_flow_control_group_name_outbound_limit_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flow-control-group_flow-control-group-name_token-rate-limit'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flow-control-group_flow-control-group-name_token-rate-limit_put


    Parameters:
    - Name: instance-id-id
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_end point_ep_eptype_service_service-service_interface_interface-type_flowctrl-group_flowctrl-group-name_outbound-rate-limit'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf outbound-rate-limit created or replaced
      Content: {}
    '204':
```

```
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: outbound-rate-limit
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_end_point_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dscp_for_ctrl_grp_for_ctrl_grp_name_outbound_rate_limit_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_end-point_ep_service_service-name_interface_interface-type_flowctrl-group_flowctrl-group-name_options

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_end_point_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_action_undelimited


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_end_point_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_dispatcher_flow_control_group_flow_control_group_name_token_bucket_rate_limit_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
```

```
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"/operations/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/service={service-service-name}/interface/interface={interface-interface-type}/qos/flowctrl-group={flowctrl-group-name}/outbound-rate-limit"

  Required/Optional: true

Responses:
  '204':
    Description: leaf outbound-rate-limit updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: outbound-rate-limit
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/monitor
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
```

```
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor'

    Required/Optional: true

  Responses:
    '201':
      Description: container monitor created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor
Method: Post

  Tags:
  - data
  - post
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_post


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor-post'

```
    Required/Optional: true

  Responses:
    '201':
      Description: container monitor created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor
delete:

  Tags:
  - data
  - delete
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_delete

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor'

      Required/Optional: true

    Responses:
      '204':
        Description: container monitor updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: monitor
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/monitor/protocol
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor_protocol_get

    Parameters:
    - Name: instance-id-id
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor_protocol'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_protocol_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor_protocol'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf protocol created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: protocol
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_protocol_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
```

```
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_protocol_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_protocol_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_monitor_protocol_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor_protocol'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf protocol updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: protocol
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/internal
: get:

    Tags:
    - data
    - get
```

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_interal'

    '204':
      Description: No Content
      Content: {}
```

```
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal'

      Required/Optional: true

    Responses:
      '201':
        Description: container internal created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: internal
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_post

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal-post'

    Required/Optional: true

  Responses:
    '201':
      Description: container internal created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: internal
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_delete

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal'

      Required/Optional: true
```

```
    Responses:
      '204':
        Description: container internal updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: internal
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/internal/base-port
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_base_port_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_base_port_put
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_interal_base-port'

  Required/Optional: true

Responses:
  '201':
    Description: container base-port created or replaced
    Content: {}
  '204':
    Description: No Content
    Content: {}
  '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: base-port
Method: Post

  Tags:
  - data
  - post
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_base_port_post


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container base-port created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: base-port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_interral_base_port_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_base_port_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_base_port_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port'

      Required/Optional: true

    Responses:
      '204':
        Description: container base-port updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: base-port
?
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/service={service-service-name}/interface={interface-interface-type}/internal/base-port/start
: get:

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_base_port_start_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
```

```
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_interal_base-port_start'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_interal_base-port_start_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: service-service-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port_start'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf start created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: start
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port_start_delete
```

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_base_port_start_options


  Parameters:
  - Name: instance-id-id
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_base_port_start_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: service-service-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_service_service_service_name_interface_interface_interface_type_internal_base_port_start_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: service-service-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_interal_base-port_start'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf start updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: start
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/interface

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_get
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
```

```
        - last
        - before
        - after
      - Name: point
        In: query
        Description: used to specify the insertion point
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type'

        Required/Optional: true

      Responses:
        '201':
          Description: list interface created or replaced
          Content: {}
        '204':
          Description: No Content
          Content: {}
        '400':
          Description: Bad Request
          Content: {}
        '401':
          Description: Unauthorized
          Content: {}
        '404':
          Description: Not Found
          Content: {}
        '405':
          Description: Method Not Allowed
          Content: {}
        '409':
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
      x-codegen-request-body-name: interface
    delete:

      Tags:
      - data
      - delete
      Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_delete
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type'
```

```
      Required/Optional: true

    Responses:
      '204':
        Description: list interface updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/interface-type
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_interface_type_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_interface-type'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_interface-type_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_interface-type'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf interface-type created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface-type
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_interface_type_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_interface_type_options


  Parameters:
```

```
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_interface_type_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_interface_type_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_interface-type'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf interface-type updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface-type
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/loopbackEth
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackEth_get


    Parameters:
    - Name: instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopback5th'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
Tags:
- data
- put
Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackEth_put

Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopbackEth'

  Required/Optional: true

Responses:
  '201':
    Description: leaf loopbackEth created or replaced
    Content: {}
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: loopbackEth
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackEth_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackEth_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackEth_head


    Parameters:
    - Name: instance-id-id
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackEth_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopbackEth'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf loopbackEth updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: loopbackEth
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/loopbackPort
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackPort_get
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopbackPort'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
```

```
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackPort_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopbackPort'

      Required/Optional: true

    Responses:
      '201':
```

```
      Description: leaf loopbackPort created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: loopbackPort
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackPort_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackPort_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:
```

Tags:
- data
- head

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackPort_head

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_loopbackPort_patch


    Parameters:
    - Name: instance-id-id
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopbackPort'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf loopbackPort updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: loopbackPort
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/uri-scheme
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_uri_scheme_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_uri-scheme'

    '204':
      Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_uri_scheme_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_uri-scheme'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf uri-scheme created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: uri-scheme
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_uri_scheme_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_uri_scheme_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_uri_scheme_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_uri_scheme_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_uri-scheme'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf uri-scheme updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: uri-scheme
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/instancetype
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_instancetype_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_instancetype'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_instancetype_put


    Parameters:
    - Name: instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
        Format: identityref
      - Name: interface-interface-type
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_instancetype'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf instancetype created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instancetype
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_instancetype_delete


    Parameters:
```

```
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_instancetype_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_instancetype_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_instancetype_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_instancetype'

      Required/Optional: true
```

```
    Responses:
      '204':
        Description: leaf instancetype updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instancetype
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/tls-enable
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_tls_enable_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_tls-enable'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_tls_enable_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_tls-enable'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf tls-enable created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
    x-codegen-request-body-name: tls-enable
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_tls_enable_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_tls_enable_options


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_tls_enable_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_tls_enable_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_tls-enable'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf tls-enable updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tls-enable
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/mtls-enable
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_mtls_enable_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_rtls-enable'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
```

```
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_mtls_enable_put

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_mtls-enable'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf mtls-enable created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: mtls-enable
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_mtls_enable_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_mtls_enable_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_mtls_enable_head

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_mtls_enable_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_mtls-enable'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf mtls-enable updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: mtls-enable
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/certificate-name
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_certificate_name_get
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_certificate-name'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_certificate_name_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_certificate-name'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf certificate-name created or replaced
      Content: {}
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: certificate-name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_certificate_name_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_certificate_name_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
```

```
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_certificate_name_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_certificate_name_patch

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_certificate-name'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf certificate-name updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: certificate-name
```

?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/sla
: get:

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla'

    '204':
      Description: No Content
      Content: {}
    '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla'

      Required/Optional: true

    Responses:
      '201':
        Description: container sla created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: sla
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_post


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container sla created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: sla
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_delete
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla'
```

```
      Required/Optional: true

    Responses:
      '204':
        Description: container sla updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: sla
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/sla/response
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_response_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_response'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_response_put


    Parameters:
    - Name: instance-id
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_response'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf response created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: response
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_response_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_response_options
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_response_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_response_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_response'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf response updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: response
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/sla/procedure
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface_interface-type_sla_procedure_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_procedure'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_procedure_put

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_procedure'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf procedure created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: procedure
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_procedure_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
```

```
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_procedure_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_procedure_head


    Parameters:
    - Name: instance-id-id
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sla_procedure_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_procedure'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf procedure updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: procedure
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/vip
: options:

    Tags:
    - data
    - options
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_options

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/vip={vip-vip-ip}
: get:

    Tags:
    - data
    - get
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_get

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip'

    Required/Optional: true

  Responses:
    '201':
      Description: list vip created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
    x-codegen-request-body-name: vip
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
```

```
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_head
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_patch
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip'

  Required/Optional: true

Responses:
  '204':
    Description: list vip updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/vip={vip-vip-ip}/vip-ip
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_ip_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-ip'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_ip_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-ip'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf vip-ip created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ip
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_ip_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
```

```
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_ip_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:
```

Tags:
- data
- head

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_ip_head

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_ip_patch

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-ip'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vip-ip updated
        Content: {}
```

```
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-ip
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/vip={vip-vip-ip}/vip-port
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_port_get

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-port'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_port_put


    Parameters:
    - Name: instance-id-id
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-port'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf vip-port created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-port
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_port_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_port_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
```

```
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_port_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_port_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-port'
```

```
      Required/Optional: true

    Responses:
      '204':
        Description: leaf vip-port updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-port
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/vip={vip-vip-ip}/vip-interface
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_interface_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-interface'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
```

```
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_interface_put

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-interface'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf vip-interface created or replaced
        Content: {}
      '204':
        Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-interface
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_interface_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_interface_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_interface_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vip_interface_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-interface'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vip-interface updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-interface
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/vip={vip-vip-ip}/offline
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_offline_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_offline'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
```

```
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_offline_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_offline'

      Required/Optional: true
```

```
  Responses:
    '201':
      Description: leaf offline created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: offline
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_offline_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_offline_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_offline_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_offline_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_offline'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf offline updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/vip={vip-vip-ip}/vrf
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vrf_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vrf'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
```

```
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vrf_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vrf'

        Required/Optional: true

      Responses:
        '201':
          Description: leaf vrf created or replaced
          Content: {}
        '204':
          Description: No Content
          Content: {}
        '400':
          Description: Bad Request
          Content: {}
        '401':
          Description: Unauthorized
          Content: {}
        '404':
          Description: Not Found
          Content: {}
        '405':
          Description: Method Not Allowed
          Content: {}
        '409':
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
      x-codegen-request-body-name: vrf
    delete:

      Tags:
      - data
      - delete
      Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vrf_delete


      Parameters:
      - Name: instance-id-id
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: leafref
      - Name: ep-eptype
        In: path
        Required/Optional: true
        Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vrf_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vrf_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip_vip_vip_ip_vrf_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: identityref
    - Name: vip-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vrf'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vrf updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/sec-vip
: options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_options
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/sec-vip={sec-vip-sec-vip-ip}
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip'

    Required/Optional: true

  Responses:
    '201':
      Description: list sec-vip created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip
delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_options

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_head

```
  Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_patch


    Parameters:
    - Name: instance-id-id
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip'

    Required/Optional: true

  Responses:
    '204':
      Description: list sec-vip updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/sec-vip={sec-vip-sec-vip-ip}/sec-vip-ip
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_sec_vip_ip_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_sec-vip-ip'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip_sec-vip-ip_sec-vip-ip_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_sec-vip-ip'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf sec-vip-ip created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip-ip
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_sec_vip_ip_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_sec_vip_ip_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
```

```
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_sec_vip_ip_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
```

```
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
```

```
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_sec_vip_ip_patch

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_sec-vip-ip'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf sec-vip-ip updated
        Content: {}
      '400':
        Description: Bad Request
```

```
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip-ip
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/sec-vip={sec-vip-sec-vip-ip}/vip-port
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_port_get

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-port'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip_sec-vip-ip_vip-port_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-port'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf vip-port created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-port
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_port_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_port_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_port_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_port_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-port'

      Required/Optional: true
```

```
    Responses:
      '204':
        Description: leaf vip-port updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-port
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/sec-vip={sec-vip-sec-vip-ip}/vip-interface
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_interface_get

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-interface'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_interface_put
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-interface'

  Required/Optional: true

Responses:
  '201':
    Description: leaf vip-interface created or replaced
    Content: {}
  '204':
    Description: No Content
    Content: {}
  '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-interface
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_interface_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
```
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_interface_options

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_interface_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vip_interface_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
```

```
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-interface'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vip-interface updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-interface
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/sec-vip={sec-vip-sec-vip-ip}/offline
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_offline_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_offline'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_offline_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_offline'

    Required/Optional: true

  Responses:
    '201':
```

```
      Description: leaf offline created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: offline
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_offline_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_offline_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_offline_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_offline_patch

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_offline'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf offline updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/sec-vip={sec-vip-sec-vip-ip}/vrf
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip_sec-vip_ip_vrf_get

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vrf'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vrf_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vrf'

```
      Required/Optional: true

    Responses:
      '201':
        Description: leaf vrf created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
  delete:

    Tags:
    - data
    - delete
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vrf_delete

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vrf_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip-sec-vip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vrf_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: identityref
- Name: sec-vip-sec-vip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip_sec_vip_sec_vip_ip_vrf_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
    - Name: sec-vip-sec-vip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vrf'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vrf updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/vip6
: options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_options


    Parameters:
    - Name: instance-id-id
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/vip6={vip6-vip-ipv6}
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
      Default: first
      enum:
      - first
      - last
      - before
      - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6'

      Required/Optional: true

    Responses:
      '201':
        Description: list vip6 created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip6
  delete:

    Tags:
    - data
```

```
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_options
```

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_head

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6'

    Required/Optional: true

  Responses:
    '204':
      Description: list vip6 updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip6
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/vip6={vip6-vip-ipv6}/vip-ipv6
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf vip-ipv6 created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: vip-ipv6
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_head

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_patch
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6'

  Required/Optional: true

Responses:
  '204':
    Description: leaf vip-ipv6 updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ipv6
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/vip6={vip6-vip-ipv6}/vip-ipv6-port
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_port_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6-port'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_port_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6-port'

      Required/Optional: true

  Responses:
    '201':
      Description: leaf vip-ipv6-port created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
```

```
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ipv6-port
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_port_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
```

```
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_port_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
```

```
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_port_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_ipv6_port_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6-port'

      Required/Optional: true

    Responses:
      '204':
```

```
      Description: leaf vip-ipv6-port updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ipv6-port
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/vip6={vip6-vip-ipv6}/vip-interface
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_interface_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_interface_put
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface'

  Required/Optional: true

Responses:
  '201':
    Description: leaf vip-interface created or replaced
    Content: {}
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
```

```
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-interface
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_interface_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
```
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_interface_options

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_interface_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vip_interface_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface'

```
      Required/Optional: true

    Responses:
      '204':
        Description: leaf vip-interface updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-interface
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/vip6={vip6-vip-ipv6}/offline
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_offline_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_offline_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf offline created or replaced
      Content: {}
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_rmobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_offline_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_offline_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
```
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_offline_head
```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: vip6-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_offline_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf offline updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/vip6={vip6-vip-ipv6}/vrf
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf'
```

```
    Required/Optional: true

  Responses:
    '201':
      Description: leaf vrf created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
- Name: vip6-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vip6_vip6_vip_ipv6_vrf_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: vip6-vip-ipv6
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vrf updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/sec-vip6
: options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/sec-vip6={sec-vip6-sec-vip-ipv6}
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
```

```
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6'

    Required/Optional: true

  Responses:
    '201':
      Description: list sec-vip6 created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip6
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_delete
```

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_options


  Parameters:
  - Name: instance-id-id
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6'

    Required/Optional: true

  Responses:
    '204':
      Description: list sec-vip6 updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: sec-vip6
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/sec-vip6={sec-vip6-sec-vip-ipv6}/sec-vip-ipv6
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_sec_vip_ipv6_get

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_sec-vip-ipv6'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_sec-vip-ipv6-put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_sec-vip-ipv6'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf sec-vip-ipv6 created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip-ipv6
```

```
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_sec_vip_ipv6_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
```

```
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_sec_vip_ipv6_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_sec_vip_ipv6_head
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_sec_vip_ipv6_patch


  Parameters:
```

```
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_sec-vip-ipv6'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf sec-vip-ipv6 updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sec-vip-ipv6
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/sec-vip6={sec-vip6-sec-vip-ipv6}/vip-ipv6-port
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_ipv6_port_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-ipv6-port'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_ipv6_port_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
```

```
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-ipv6-port'

  Required/Optional: true

Responses:
  '201':
    Description: leaf vip-ipv6-port created or replaced
    Content: {}
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
```

```
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-ipv6-port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_ipv6_port_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
```

```
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_ipv6_port_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:
```

Tags:
- data
- head

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_ipv6_port_head

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig

```
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
```

```
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_ipv6_port_patch

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-ipv6-port'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vip-ipv6-port updated
        Content: {}
      '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-ipv6-port
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/sec-vip6={sec-vip6-sec-vip-ipv6}/vip-interface
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_interface_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-interface'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-interface_put


    Parameters:
    - Name: instance-id-id
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-interface'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf vip-interface created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vip-interface
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_interface_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_interface_options

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_interface_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vip_interface_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-interface'

      Required/Optional: true
```

```
    Responses:
      '204':
        Description: leaf vip-interface updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vip-interface
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/sec-vip6={sec-vip6-sec-vip-ipv6}/offline
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_offline_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_offline'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_offline_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_offline'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf offline created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
```

```
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_offline_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_offline_options

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_offline_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_offline_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_offline'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf offline updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: offline
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/sec-vip6={sec-vip6-sec-vip-ipv6}/vrf
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vrf_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: sec-vip6-sec-vip-ipv6
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vrf'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
```

```
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vrf_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vrf'

      Required/Optional: true
```

```
  Responses:
    '201':
      Description: leaf vrf created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vrf_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vrf_options

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vrf_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: sec-vip6-sec-vip-ipv6
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_sec_vip6_sec_vip6_sec_vip_ipv6_vrf_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: sec-vip6-sec-vip-ipv6
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vrf'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vrf updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/vrf
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vrf_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vrf'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vrf_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vrf'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf vrf created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
```

```
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vrf_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
```

```
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vrf_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vrf_head


  Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_vrf_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vrf'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vrf updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/dispatcher
: get:

    Tags:
    - data
    - get
```

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher'

    Required/Optional: true

  Responses:
```

```
    '201':
      Description: container dispatcher created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dispatcher
Method: Post

  Tags:
  - data
  - post
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_post


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container dispatcher created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: dispatcher
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher'

      Required/Optional: true

    Responses:
      '204':
        Description: container dispatcher updated
        Content: {}
```

```
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: dispatcher
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/dispatcher/count
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_count_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_count'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_count_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_count'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf count created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: count
 delete:

  Tags:
```

```
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_count_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_count_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_count_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_count_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_count'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf count updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: count
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/dispatcher/capacity
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_capacity_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_capacity'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_capacity_put
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_capacity'

  Required/Optional: true

Responses:
  '201':
    Description: leaf capacity created or replaced
    Content: {}
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: capacity
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_capacity_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
```

```
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_capacity_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_capacity_head

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_capacity_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_capacity'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf capacity updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: capacity
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/dispatcher/outbound
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_outbound_get


    Parameters:
    - Name: instance-id-id
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_outbound'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_outbound_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_outbound'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf outbound created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
```

```
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: outbound
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_outbound_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_outbound_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_outbound_head
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_outbound_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: leafref
      - Name: ep-eptype
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: identityref
      - Name: interface-interface-type
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: identityref
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_outbound'

        Required/Optional: true

      Responses:
        '204':
          Description: leaf outbound updated
          Content: {}
        '400':
          Description: Bad Request
          Content: {}
        '401':
          Description: Unauthorized
          Content: {}
        '404':
          Description: Not Found
          Content: {}
        '405':
          Description: Method Not Allowed
          Content: {}
        '409':
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
      x-codegen-request-body-name: outbound
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/dispatcher/rate-limit
: get:
```

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_rate_limit_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_rate-limit'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_rate_limit_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_rate-limit'
```

```
    Required/Optional: true

  Responses:
    '201':
      Description: leaf rate-limit created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: rate-limit
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_rate_limit_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_rate_limit_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_rate_limit_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
```

```
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_rate_limit_patch

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_rate-limit'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf rate-limit updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: rate-limit
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/dispatcher/cache
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_cache_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
```

```
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_cache'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_cache_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_cache'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf cache created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cache
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_cache_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_cache_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_cache_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_cache_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_cache'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf cache updated
      Content: {}
    '400':
```

```
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cache
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/dispatcher/threshold
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_threshold_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_threshold'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface_interface-type_dispatcher_threshold_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_threshold'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf threshold created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: threshold
delete:

  Tags:
  - data
  - delete
```

```
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_threshold_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_threshold_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_threshold_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_threshold_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_threshold'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf threshold updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: threshold
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/dispatcher/expiry
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_expiry_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_expiry'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_expiry_put


    Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_expiry'

  Required/Optional: true

Responses:
  '201':
    Description: leaf expiry created or replaced
    Content: {}
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
```

```
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: expiry
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_expiry_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_expiry_options
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_expiry_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_expiry_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_expiry'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf expiry updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: expiry
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/dispatcher/nonresponsive
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_nonresponsive_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_nonresponsive'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_nonresponsive_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_nonresponsive'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf nonresponsive created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
```

```
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: nonresponsive
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_nonresponsive_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_nonresponsive_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_nonresponsive_head
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_nonresponsive_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
```

```
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_nonresponsive'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf nonresponsive updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: nonresponsive
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/dispatcher/flowctrl-group
: options:

  Tags:
```

```
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/dispatcher/flowctrl-group={flowctrl-group-name}
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
```

```
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
```

```
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name'

    Required/Optional: true

  Responses:
    '201':
      Description: list flowctrl-group created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: flowctrl-group
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_head

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
```

data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_patch

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name'
    Required/Optional: true

Responses:
  '204':
    Description: list flowctrl-group updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: flowctrl-group
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/dispatcher/flowctrl-group={flowctrl-group-name}/rate
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_rate_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_name"

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_name_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name-name'

      Required/Optional: true

  Responses:
    '201':
      Description: leaf name created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
```

```
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_name_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
```

```
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_name_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
```

```
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_name_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_name_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_name'

    Required/Optional: true

  Responses:
    '204':
```

```
      Description: leaf name updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/dispatcher/flowctrl-group={flowctrl-group-name}/capacity
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_capacity_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_capacity'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_capacity_put
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_capacity'

  Required/Optional: true

Responses:
  '201':
    Description: leaf capacity created or replaced
    Content: {}
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
```

```
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: capacity
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_capacity_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_capacity_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_capacity_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_capacity_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-grp_flowctrl-grp-name_capacity'

```
      Required/Optional: true

    Responses:
      '204':
        Description: leaf capacity updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: capacity
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/dispatcher/flowctrl-grp={flowctrl-grp-name}/rate-limit
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-grp_flowctrl-grp-name_rate-limit_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctl-grp_flowctl-grp_rate-limit'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
Tags:
- data
- put
Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_rate_limit_put

Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate-limit'

  Required/Optional: true

Responses:
  '201':
    Description: leaf rate-limit created or replaced
    Content: {}
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: rate-limit
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_rate_limit_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_rate_limit_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_rate_limit_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_rate_limit_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate-limit'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf rate-limit updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: rate-limit
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/dispatcher/flowctrl-group={flowctrl-group-name}/outbound-capacity
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-capacity_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_end point_ep_ep-eptype_interface_interface-interface-type_dispatcher_flow-control-group_flow-control-group-name_throughput-capacity'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_capacity_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_capacity'
```

```
    Required/Optional: true

  Responses:
    '201':
      Description: leaf outbound-capacity created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: outbound-capacity
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_capacity_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_capacity_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_capacity_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_capacity_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-capacity'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf outbound-capacity updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: outbound-capacity
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/dispatcher/flowctrl-group={flowctrl-group-name}/outbound-rate-limit
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-rate-limit_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
```

```
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_fwctrl-gop_fwctrl-gop-name_outbound-init'

  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_rate_limit_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: flowctrl-group-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-grp_flowctrl-grp-name_outbound-rate-limit'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf outbound-rate-limit created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: outbound-rate-limit
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-grp_flowctrl-grp-name_outbound-rate-limit_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_rate_limit_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_rate_limit_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: flowctrl-group-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_dispatcher_flowctrl_group_flowctrl_group_name_outbound_rate_limit_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: flowctrl-group-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface_interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-rate-limit'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf outbound-rate-limit updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: outbound-rate-limit
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/monitor
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_get
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
```

```
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor'

      Required/Optional: true

    Responses:
      '201':
```

```
      Description: container monitor created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor
Method: Post

  Tags:
  - data
  - post
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_post


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container monitor created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: monitor
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor'

    Required/Optional: true

  Responses:
    '204':
      Description: container monitor updated
      Content: {}
    '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/monitor/protocol
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_protocol_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor_protocol'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_protocol_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor_protocol'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf protocol created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: protocol
  delete:

    Tags:
    - data
    - delete
```

```
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_protocol_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_protocol_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_protocol_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_monitor_protocol_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor_protocol'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf protocol updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: protocol
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/internal
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_put


    Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal'

    Required/Optional: true

Responses:
  '201':
    Description: container internal created or replaced
    Content: {}
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
```

```
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: internal
Method: Post

  Tags:
  - data
  - post
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_post


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal-post'

    Required/Optional: true

  Responses:
    '201':
      Description: container internal created
      Content: {}
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: internal
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
```

```
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
```

```
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        '200':
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_patch


      Parameters:
      - Name: instance-id-id
        In: path
        Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal'

    Required/Optional: true

  Responses:
    '204':
      Description: container internal updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: internal
```

?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/internal/base-port
: get:

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port'

    '204':
      Description: No Content
      Content: {}
    '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
```

```
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port'

      Required/Optional: true

    Responses:
      '201':
        Description: container base-port created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: base-port
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_post


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container base-port created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: base-port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf-mobile-infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_delete
```

```
  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port'
```

```
      Required/Optional: true

    Responses:
      '204':
        Description: container base-port updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: base-port
?
/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/endpoint/ep={ep-eptype}/interface={interface-interface-type}/internal/base-port/start
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_start_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
```

```
- Name: interface-interface-type
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port_start'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface_interface-type_internal_base-port_start_put


    Parameters:
    - Name: instance-id-id
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port_start'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf start created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: start
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_start_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_start_options
```

```
    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: interface-interface-type
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_start_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_interface_interface_interface_type_internal_base_port_start_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: interface-interface-type
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port_start'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf start updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: start
```


/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/internal


```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_get


  Parameters:
  - Name: instance-id-id
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal'

      Required/Optional: true

    Responses:
      '201':
        Description: container internal created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: internal
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_post


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container internal created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
```

```
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: internal
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_options


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal'

    Required/Optional: true

  Responses:
    '204':
      Description: container internal updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: internal
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/internal/base-port

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port'
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port'
```

```
    Required/Optional: true

  Responses:
    '201':
      Description: container base-port created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: base-port
Method: Post

  Tags:
  - data
  - post
  Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_post


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: ep-eptype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container base-port created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: base-port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_head
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port'

      Required/Optional: true

    Responses:
      '204':
        Description: container base-port updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: base-port
```

/data/tailf-mobile-infra:instance/instance-id={instance-id-id}/end point/ep={ep-eptype}/internal/base-port/start

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_start_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port_start'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_start_put
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: ep-eptype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port_start'

  Required/Optional: true

Responses:
  '201':
    Description: leaf start created or replaced
    Content: {}
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: start
```

```
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_start_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_start_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_start_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
```

```
    Operation ID:
data_tailf_mobile_infra_instance_instance_id_instance_id_id_endpoint_ep_ep_eptype_internal_base_port_start_patch

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: ep-eptype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port_start'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf start updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: start
```

/data/tailf-mobile-infra:endpoint

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_endpoint_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference: '#/components/schemas/data_tailf-mobile-infra_endpoint'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_endpoint_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_endpoint'
```

```
    Required/Optional: true

  Responses:
    '201':
      Description: container endpoint created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: endpoint
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_endpoint_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_endpoint-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container endpoint created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: endpoint
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_endpoint_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_endpoint_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_endpoint_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_endpoint_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_endpoint'
    Required/Optional: true

  Responses:
    '204':
      Description: container endpoint updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: endpoint
```

/data/tailf-mobile-infra:endpoint/info

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_endpoint_info_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_endpoint_info'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_endpoint_info_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info={info-grInstance},{info-end point},{info-address}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_get

    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address'

    '204':
      Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_head

  Parameters:
  - Name: info-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
      - trim
      - explicit
      - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info={info-grInstance},{info-end point},{info-address}/grInstance

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_grInstance_get


    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_grInstance'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_grInstance_head


    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: info-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info={info-grInstance},{info-end point},{info-address}/endpoint

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_endpoint_get


  Parameters:
  - Name: info-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: info-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_endpoint'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_endpoint_head


    Parameters:
    - Name: info-grInstance
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: info-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: info-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info={info-grInstance},{info-end point},{info-address}/address

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_address_get


    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: info-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: info-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_address'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
```

```
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_address_head


    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info={info-grInstance},{info-end point},{info-address}/type

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_type_get

    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_type'

    '204':
      Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_type_head

  Parameters:
  - Name: info-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info={info-grInstance},{info-end point},{info-address}/status

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_status_get


  Parameters:
  - Name: info-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_status'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_status_head


    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: info-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info={info-grInstance},{info-end point},{info-address}/Interface

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_Interface_get


    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: info-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_Interface'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_Interface_head


    Parameters:
    - Name: info-grInstance
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info={info-grInstance},{info-end point},{info-address}/internal

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_internal_get


    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_internal'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
```

```
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_internal_head


    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info={info-grInstance},{info-end point},{info-address}/startTime

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_startTime_get


  Parameters:
  - Name: info-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_startTime'

    '204':
```

```
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_startTime_head


  Parameters:
  - Name: info-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: info-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
      - report-all
      - trim
      - explicit
      - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info={info-grInstance},{info-end point},{info-address}/stoppedTime

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_stoppedTime_get


    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_stoppedTime'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_stoppedTime_head


    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: info-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/info={info-grInstance},{info-end point},{info-address}/vrf

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_vrf_get

    Parameters:
    - Name: info-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: info-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: info-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_vrf'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_info_info_grInstance_info_endpoint_info_address_vrf_head

    Parameters:
    - Name: info-grInstance
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: info-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: info-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_endpoint_all_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_endpoint_all'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_endpoint_all_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
```

```
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all={all-grInstance},{all-endpoi nt},{all-address}

```
get:

  Tags:
  - data
  - get
  Operation ID:
```

```
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_get

  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
```

```
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_head

    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all={all-grInstance},{all-endpoi nt},{all-address}/grInstance

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_grInstance_get


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_grInstance'

    '204':
```

```
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_grInstance_head


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
      - report-all
      - trim
      - explicit
      - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all={all-grInstance},{all-endpoi nt},{all-address}/endpoint

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_endpoint_get

    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_endpoint'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_endpoint_head

    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: all-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all={all-grInstance},{all-endpoi nt},{all-address}/address

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_address_get

    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-address
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_address'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_address_head

    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all={all-grInstance},{all-endpoi nt},{all-address}/type

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_type_get

    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_type'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 head:
```

```
    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_type_head

    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
```

```
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all={all-grInstance},{all-endpoi nt},{all-address}/status

```
get:

  Tags:
  - data
  - get
  Operation ID:
```

```
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_status_get

  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_status'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
```

```
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_status_head

    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all={all-grInstance},{all-endpoi nt},{all-address}/Interface

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_Interface_get

    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_Interface'

      '204':
        Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_Interface_head


  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all={all-grInstance},{all-endpoi nt},{all-address}/internal

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_internal_get

  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_internal'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_internal_head

    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: all-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all={all-grInstance},{all-endpoi nt},{all-address}/startTime

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_startTime_get

  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-address
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_startTime'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_startTime_head


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all={all-grInstance},{all-endpoi nt},{all-address}/stoppedTime

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_stoppedTime_get


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: all-endpoint
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: all-address
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_stoppedTime'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:
```

```
    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_stoppedTime_head


    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:endpoint/all={all-grInstance},{all-endpoi nt},{all-address}/vrf

```
get:

  Tags:
  - data
```

```
    - get
    Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_vrf_get

    Parameters:
    - Name: all-grInstance
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-endpoint
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: all-address
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_vrf'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_endpoint_all_all_grInstance_all_endpoint_all_address_vrf_head

  Parameters:
  - Name: all-grInstance
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-endpoint
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: all-address
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:vrf

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_vrf'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_vrf_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_vrf'
```

```
    Required/Optional: true

  Responses:
    '201':
      Description: container vrf created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_vrf_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_vrf-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container vrf created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_vrf_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_vrf_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_vrf_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_vrf'
    Required/Optional: true

  Responses:
    '204':
      Description: container vrf updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
```

/data/tailf-mobile-infra:vrf/vrflist

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_options

  Responses:
    '200':
      Description: OK
      Content: {}
```

```
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf/vrflist={vrflist-name}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_get

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
```

```
  security:
  - basicAuth: []
 put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_put

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name'
    Required/Optional: true

  Responses:
    '201':
      Description: list vrflist created or replaced
```

```
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrflist
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_delete

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_options

  Parameters:
```

```
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_head

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_patch

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name'
      Required/Optional: true

    Responses:
      '204':
        Description: list vrflist updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrflist
```

/data/tailf-mobile-infra:vrf/vrflist={vrflist-name}/name

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_name_get

    Parameters:
    - Name: vrflist-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_name'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_name_put

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_name'
       Required/Optional: true

    Responses:
      '201':
        Description: leaf name created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_name_delete

    Parameters:
    - Name: vrflist-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
```

```
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_name_options

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_name_head

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
```

```
    - patch
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_name_patch

    Parameters:
    - Name: vrflist-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_name'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf name updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
```

/data/tailf-mobile-infra:vrf/vrflist={vrflist-name}/gateway

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gateway_get
```

```
Parameters:
- Name: vrflist-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gateway'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gateway_put

    Parameters:
    - Name: vrflist-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gateway'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf gateway created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: gateway
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gateway_delete

    Parameters:
    - Name: vrflist-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gateway_options

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gateway_head

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
 patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gateway_patch

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gateway'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf gateway updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: gateway
```

/data/tailf-mobile-infra:vrf/vrflist={vrflist-name}/gatewayIpv6

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gatewayIpv6_get

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gatewayIpv6'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gatewayIpv6_put

    Parameters:
    - Name: vrflist-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gatewayIpv6'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf gatewayIpv6 created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: gatewayIpv6
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gatewayIpv6_delete
```

```
  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gatewayIpv6_options

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gatewayIpv6_head

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_gatewayIpv6_patch

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gatewayIpv6'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf gatewayIpv6 updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: gatewayIpv6
```

/data/tailf-mobile-infra:vrf/vrflist={vrflist-name}/device

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_device_get

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_device'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_device_put

    Parameters:
    - Name: vrflist-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_device'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf device created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
  x-codegen-request-body-name: device
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_device_delete

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_device_options

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_device_head
```

```
Parameters:
- Name: vrflist-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_device_patch

    Parameters:
    - Name: vrflist-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_device'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf device updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: device
```

/data/tailf-mobile-infra:vrf/vrflist={vrflist-name}/linkDevice

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_linkDevice_get

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_linkDevice'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_linkDevice_put

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_linkDevice'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf linkDevice created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: linkDevice
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_linkDevice_delete

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_linkDevice_options

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
```

```
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_linkDevice_head

  Parameters:
  - Name: vrflist-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_vrf_vrflist_vrflist_name_linkDevice_patch

    Parameters:
    - Name: vrflist-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_linkDevice'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf linkDevice updated
```

```
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: linkDevice
```

/data/tailf-mobile-infra:vrf-info

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_vrf-info'
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_vrf_info_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_vrf-info'
    Required/Optional: true

  Responses:
    '201':
      Description: container vrf-info created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf-info
Method: Post

  Tags:
  - data
```

```
    - post
    Operation ID: data_tailf_mobile_infra_vrf_info_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_vrf-info-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container vrf-info created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf-info
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_vrf_info_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_vrf_info_options
```

```
  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_vrf_info_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_vrf-info'
      Required/Optional: true

    Responses:
      '204':
        Description: container vrf-info updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
```

```
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: vrf-info
```

/data/tailf-mobile-infra:vrf-info/all

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_all_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_vrf-info_all'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:
```

Tags:
- data
- head

Operation ID: data_tailf_mobile_infra_vrf_info_all_head

Parameters:
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/all={all-name}

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_get

    Parameters:
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf-info_all_all-name'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
```

```
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_head

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/all={all-name}/name

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_name_get

  Parameters:
```

```
- Name: all-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf-info_all_all-name_name'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_name_head

    Parameters:
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/all={all-name}/gateway

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_gateway_get

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf-info_all_all-name_gateway'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
```

```
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_gateway_head

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/all={all-name}/gatewayIpv6

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_gatewayIpv6_get

  Parameters:
  - Name: all-name
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf-info_all_all-name_gatewayIpv6'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_gatewayIpv6_head

    Parameters:
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/all={all-name}/device

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_device_get

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf-info_all_all-name_device'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_device_head

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/all={all-name}/linkDevice

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_linkDevice_get

  Parameters:
  - Name: all-name
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf-info_all_all-name_linkDevice'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_linkDevice_head

    Parameters:
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/all={all-name}/tableId

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_tableId_get

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf-info_all_all-name_tableId'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_tableId_head

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/all={all-name}/state

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_state_get

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf-info_all_all-name_state'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_state_head

    Parameters:
    - Name: all-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:vrf-info/all={all-name}/podName

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_podName_get

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf-info_all_all-name_podName'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_vrf_info_all_all_name_podName_head

  Parameters:
  - Name: all-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:logging

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_logging'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_logging'
    Required/Optional: true

  Responses:
    '201':
      Description: container logging created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: logging
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_logging_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_logging-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container logging created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: logging
delete:
```

```
  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_logging'
```

```
    Required/Optional: true

  Responses:
    '204':
      Description: container logging updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: logging
```

/data/tailf-mobile-infra:logging/transaction

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_transaction_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_logging_transaction'

  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
```

```
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_transaction_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_logging_transaction'

    Required/Optional: true

  Responses:
    '201':
      Description: container transaction created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: transaction
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_logging_transaction_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_transaction-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container transaction created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: transaction
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_logging_transaction_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
```

```
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_transaction_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_transaction_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_logging_transaction_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_logging_transaction'

    Required/Optional: true

  Responses:
    '204':
      Description: container transaction updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
```

```
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: transaction
```

/data/tailf-mobile-infra:logging/transaction/persist

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_transaction_persist_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_transaction_persist'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_transaction_persist_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_transaction_persist'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf persist created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: persist
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_transaction_persist_delete

  Responses:
```

```
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_transaction_persist_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_transaction_persist_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_transaction_persist_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_transaction_persist'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf persist updated
        Content: {}
```

```
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: persist
```

/data/tailf-mobile-infra:logging/transaction/max-file-size

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_transaction_max_file_size_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_transaction_max-file-size'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_transaction_max_file_size_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_transaction_max-file-size'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf max-file-size created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: max-file-size
delete:

  Tags:
  - data
```

```
  - delete
  Operation ID: data_tailf_mobile_infra_logging_transaction_max_file_size_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_transaction_max_file_size_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_transaction_max_file_size_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_transaction_max_file_size_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_transaction_max-file-size'
      Required/Optional: true
```

```
  Responses:
    '204':
      Description: leaf max-file-size updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: max-file-size
```

/data/tailf-mobile-infra:logging/transaction/max-rotation

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_transaction_max_rotation_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_transaction_max-rotation'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
```

```
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_transaction_max_rotation_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_transaction_max-rotation'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf max-rotation created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
  x-codegen-request-body-name: max-rotation
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_transaction_max_rotation_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_transaction_max_rotation_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_transaction_max_rotation_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_transaction_max_rotation_patch
    Request Body:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_transaction_max-rotation'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf max-rotation updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: max-rotation
```

/data/tailf-mobile-infra:logging/transaction/message

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_transaction_message_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_transaction_message'
    '204':
      Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_transaction_message_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_transaction_message'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf message created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: message
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_transaction_message_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_transaction_message_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_transaction_message_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
```

```
    Operation ID: data_tailf_mobile_infra_logging_transaction_message_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_transaction_message'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf message updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: message
```

/data/tailf-mobile-infra:logging/transaction/duplicate

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_logging_transaction_duplicate_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_transaction_duplicate'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_transaction_duplicate_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_transaction_duplicate'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf duplicate created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
```

```
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: duplicate
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_transaction_duplicate_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_transaction_duplicate_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_transaction_duplicate_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_transaction_duplicate_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_transaction_duplicate'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf duplicate updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: duplicate
```

/data/tailf-mobile-infra:logging/level

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_logging_level_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
```

```
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_logging_level'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_level_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_logging_level'
    Required/Optional: true

  Responses:
    '201':
      Description: container level created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: level
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_logging_level_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_logging_level-post'

    Required/Optional: true

  Responses:
    '201':
      Description: container level created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: level
delete:

  Tags:
```

```
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_level_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_level_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_level_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_logging_level_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_logging_level'
    Required/Optional: true
```

```
  Responses:
    '204':
      Description: container level updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: level
```

/data/tailf-mobile-infra:logging/level/application

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_level_application_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_level_application'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
```

```
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_level_application_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_level_application'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf application created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
  x-codegen-request-body-name: application
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_level_application_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_level_application_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_level_application_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_level_application_patch
    Request Body:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_level_application'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf application updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: application
```

/data/tailf-mobile-infra:logging/level/transaction

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_logging_level_transaction_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_level_transaction'
      '204':
        Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_level_transaction_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_level_transaction'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf transaction created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: transaction
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_level_transaction_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_level_transaction_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_level_transaction_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
```

```
    Operation ID: data_tailf_mobile_infra_logging_level_transaction_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_level_transaction'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf transaction updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: transaction
```

/data/tailf-mobile-infra:logging/level/tracing

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_logging_level_tracing_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_level_tracing'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_level_tracing_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
           Reference: '#/components/schemas/data_tailf-mobile-infra_logging_level_tracing'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf tracing created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
```

```
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tracing
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_level_tracing_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_level_tracing_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_level_tracing_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_level_tracing_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_logging_level_tracing'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf tracing updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: tracing
```

/data/tailf-mobile-infra:logging/level/monitor-subscriber

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_logging_level_monitor_subscriber_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_level_monitor-subscriber'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_level_monitor_subscriber_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_level_monitor-subscriber'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf monitor-subscriber created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor-subscriber
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_level_monitor_subscriber_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_level_monitor_subscriber_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_level_monitor_subscriber_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_level_monitor_subscriber_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_level_monitor-subscriber'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf monitor-subscriber updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: monitor-subscriber
```

/data/tailf-mobile-infra:logging/logger

```
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_logging_logger_options

    Responses:
      '200':
        Description: OK
        Content: {}
```

```
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:logging/logger={logger-name}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_get

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
 put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_put

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name'
    Required/Optional: true

  Responses:
    '201':
      Description: list logger created or replaced
```

```
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: logger
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_delete

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_options

  Parameters:
```

```
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_head

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_patch

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name'
      Required/Optional: true

    Responses:
      '204':
        Description: list logger updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: logger
```

/data/tailf-mobile-infra:logging/logger={logger-name}/name

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_name_get

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_name'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_name_put

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_name'
       Required/Optional: true

    Responses:
      '201':
        Description: leaf name created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_name_delete

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
```

```
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_name_options

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_name_head

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
```

```
    - patch
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_name_patch

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_name'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf name updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
```

/data/tailf-mobile-infra:logging/logger={logger-name}/level

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_get
```

```
Parameters:
- Name: logger-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_put

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level'
      Required/Optional: true

    Responses:
      '201':
        Description: container level created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: level
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_post

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container level created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: level
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_delete

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_options

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_head

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_patch

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level'
      Required/Optional: true

    Responses:
      '204':
        Description: container level updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: level
```

/data/tailf-mobile-infra:logging/logger={logger-name}/level/applic ation

```
  get:
```

```
Tags:
- data
- get
Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_application_get


Parameters:
- Name: logger-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_application'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_application_put

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_application'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf application created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: application
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_application_delete
```

```
    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_application_options

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_application_head


    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_application_patch

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_application'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf application updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
```

```
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: application
```

/data/tailf-mobile-infra:logging/logger={logger-name}/level/transa ction

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_transaction_get


  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_transaction'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
 Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_transaction_put


  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_transaction'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf transaction created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: transaction
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_transaction_delete

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_transaction_options

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
```

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_transaction_head


  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_transaction_patch

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_transaction'

      Required/Optional: true
```

```
  Responses:
    '204':
      Description: leaf transaction updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: transaction
```

/data/tailf-mobile-infra:logging/logger={logger-name}/level/tracin g

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_tracing_get

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_tracing'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_tracing_put

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_tracing'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf tracing created or replaced
        Content: {}
      '204':
        Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tracing
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_tracing_delete


  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_tracing_options


  Parameters:
  - Name: logger-name
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_tracing_head

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
   Operation ID: data_tailf_mobile_infra_logging_logger_logger_name_level_tracing_patch


    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_tracing'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf tracing updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: tracing
```

/data/tailf-mobile-infra:logging/logger={logger-name}/level/monitor-subscriber

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_monitor_subscriber_get

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_monitor-subscriber'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_monitor_subscriber_put

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_monitor-subscriber'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf monitor-subscriber created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: monitor-subscriber
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_monitor_subscriber_delete

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
 options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_monitor_subscriber_options

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_monitor_subscriber_head

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_logging_logger_logger_name_level_monitor_subscriber_patch

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_monitor-subscriber'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf monitor-subscriber updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: monitor-subscriber
```

/data/tailf-mobile-infra:logging/async

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_logging_async'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_async_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_logging_async'
```

```
    Required/Optional: true

  Responses:
    '201':
      Description: container async created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: async
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_logging_async_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_logging_async-post'

    Required/Optional: true

  Responses:
    '201':
      Description: container async created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: async
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_async_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_async_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_logging_async_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_logging_async'
    Required/Optional: true

  Responses:
    '204':
      Description: container async updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: async
```

/data/tailf-mobile-infra:logging/async/application

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_application_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_application'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_async_application_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_application'
      Required/Optional: true

    Responses:
      '201':
        Description: container application created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
```

```
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: application
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_logging_async_application_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_application-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container application created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: application
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_async_application_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_async_application_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_application_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_application_patch
    Request Body:
      Content:
```

```
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_application'
    Required/Optional: true

  Responses:
    '204':
      Description: container application updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: application
```

/data/tailf-mobile-infra:logging/async/application/enable

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_application_enable_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_application_enable'
      '204':
```

```
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_async_application_enable_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_application_enable'
    Required/Optional: true

  Responses:
    '201':
      Description: container enable created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_logging_async_application_enable_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_application_enable-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container enable created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_logging_async_application_enable_delete

    Responses:
```

```
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_async_application_enable_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_application_enable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_application_enable_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_application_enable'
      Required/Optional: true

    Responses:
      '204':
        Description: container enable updated
        Content: {}
```

```
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
```

/data/tailf-mobile-infra:logging/async/application/enable/buffer-s ize

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_logging_async_application_enable_buffer_size_get


  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        '200':
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_application_enable_buffer-size'

        '204':
          Description: No Content
          Content: {}
        '400':
          Description: Bad Request
          Content: {}
        '401':
          Description: Unauthorized
          Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_tailf_mobile_infra_logging_async_application_enable_buffer_size_put

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_application_enable_buffer-size'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf buffer-size created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: buffer-size
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_logging_async_application_enable_buffer_size_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_logging_async_application_enable_buffer_size_options

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_tailf_mobile_infra_logging_async_application_enable_buffer_size_head


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_logging_async_application_enable_buffer_size_patch
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_application_enable_buffer-size'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf buffer-size updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: buffer-size
```

/data/tailf-mobile-infra:logging/async/application/disable

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_logging_async_application_disable_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_application_disable'
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_async_application_disable_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_application_disable'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf disable created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: disable
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_async_application_disable_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_async_application_disable_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_application_disable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
```

```
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_application_disable_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_application_disable'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf disable updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: disable
```

/data/tailf-mobile-infra:logging/async/transaction

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_logging_async_transaction_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_transaction'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_async_transaction_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_transaction'
      Required/Optional: true

    Responses:
      '201':
        Description: container transaction created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: transaction
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_transaction-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container transaction created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: transaction
delete:

  Tags:
  - data
```

```
  - delete
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_transaction_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_transaction'
      Required/Optional: true
```

```
Responses:
  '204':
    Description: container transaction updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: transaction
```

/data/tailf-mobile-infra:logging/async/transaction/enable

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_enable_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_enable'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
```

```
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_async_transaction_enable_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_enable'
      Required/Optional: true

    Responses:
      '201':
        Description: container enable created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
    x-codegen-request-body-name: enable
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_logging_async_transaction_enable_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_enable-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container enable created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_logging_async_transaction_enable_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
```

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_enable_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_enable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_transaction_enable_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_enable'
      Required/Optional: true

    Responses:
      '204':
        Description: container enable updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
```

```
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: enable
```

/data/tailf-mobile-infra:logging/async/transaction/enable/buffer-s ize

```
get:

 Tags:
 - data
 - get
Operation ID: data_tailf_mobile_infra_logging_async_transaction_enable_buffer_size_get


 Parameters:
 - Name: content
   In: query
   Description: controlling descendant nodes in response
   Required/Optional: false
   Style: form
   Explode: true
   Schema:
     Type: string
     Format: enumeration
     Default: config
     enum:
     - config
     - nonconfig
     - all
 - Name: depth
   In: query
   Description: limit the depth of nodes in response
   Required/Optional: false
   Style: form
   Explode: true
   Schema:
     Type: integer
     Format: uint16
 - Name: fields
   In: query
   Description: optionally identify specific data nodes in response
   Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_enable_buffer-size'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
 Operation ID: data_tailf_mobile_infra_logging_async_transaction_enable_buffer_size_put

  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_enable_buffer-size'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf buffer-size created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: buffer-size
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_logging_async_transaction_enable_buffer_size_delete
```

```
    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_logging_async_transaction_enable_buffer_size_options

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_tailf_mobile_infra_logging_async_transaction_enable_buffer_size_head


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_logging_async_transaction_enable_buffer_size_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_enable_buffer-size'

      Required/Optional: true
```

```
  Responses:
    '204':
      Description: leaf buffer-size updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: buffer-size
```

/data/tailf-mobile-infra:logging/async/transaction/disable

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_disable_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_disable'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
```

```
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_async_transaction_disable_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_disable'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf disable created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
  x-codegen-request-body-name: disable
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_disable_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_disable_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_disable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_logging_async_transaction_disable_patch
  Request Body:
    Content:
      application/yang-data+json:
```

```
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_disable'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf disable updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: disable
```

/data/tailf-mobile-infra:logging/async/tracing

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_tracing'
      '204':
        Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_logging_async_tracing'

    Required/Optional: true

  Responses:
    '201':
      Description: container tracing created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tracing
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_tracing-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container tracing created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tracing
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_delete

  Responses:
    '204':
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_tracing_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
           Reference: '#/components/schemas/data_tailf-mobile-infra_logging_async_tracing'

      Required/Optional: true

    Responses:
      '204':
        Description: container tracing updated
        Content: {}
      '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tracing
```

/data/tailf-mobile-infra:logging/async/tracing/enable

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_enable'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_enable'
    Required/Optional: true

  Responses:
    '201':
      Description: container enable created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
Method: Post

  Tags:
  - data
  - post
```

```
    Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_enable-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container enable created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_options
```

```
  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_enable'
      Required/Optional: true

    Responses:
      '204':
        Description: container enable updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
```

```
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: enable
```

/data/tailf-mobile-infra:logging/async/tracing/enable/buffer-size:

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_buffer_size_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_enable_buffer-size'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_buffer_size_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_enable_buffer-size'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf buffer-size created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: buffer-size
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_buffer_size_delete


    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
```

```
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_buffer_size_options


  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_buffer_size_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_tracing_enable_buffer_size_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_enable_buffer-size'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf buffer-size updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: buffer-size
```

/data/tailf-mobile-infra:logging/async/tracing/disable

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_disable_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_disable'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_disable_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_disable'
     Required/Optional: true

  Responses:
    '201':
      Description: leaf disable created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: disable
 delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_disable_delete

  Responses:
```

```
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_disable_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_tracing_disable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_tracing_disable_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_disable'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf disable updated
        Content: {}
```

```
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: disable
```

/data/tailf-mobile-infra:logging/async/monitor-subscriber

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber'
    Required/Optional: true

  Responses:
    '201':
      Description: container monitor-subscriber created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor-subscriber
Method: Post

  Tags:
  - data
```

```
    - post
    Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container monitor-subscriber created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: monitor-subscriber
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
```

```
  Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber'
      Required/Optional: true

    Responses:
      '204':
        Description: container monitor-subscriber updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
```

```
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor-subscriber
```

/data/tailf-mobile-infra:logging/async/monitor-subscriber/enable

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_enable'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_enable'
      Required/Optional: true

    Responses:
      '201':
        Description: container enable created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_enable-post'
```

```
    Required/Optional: true

  Responses:
    '201':
      Description: container enable created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_delete


  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_options


  Responses:
    '200':
      Description: OK
      Content: {}
  security:
```

```
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_enable'
      Required/Optional: true

    Responses:
      '204':
        Description: container enable updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: enable
```

/data/tailf-mobile-infra:logging/async/monitor-subscriber/enable/buffer-size

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_buffer_size_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_enable_buffer-size'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID:
data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_buffer_size_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_enable_buffer-size'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf buffer-size created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: buffer-size
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_buffer_size_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
```

```
    - options
    Operation ID:
data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_buffer_size_options

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_buffer_size_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_logging_async_monitor_subscriber_enable_buffer_size_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_enable_buffer-size'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf buffer-size updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: buffer-size
```

/data/tailf-mobile-infra:logging/async/monitor-subscriber/disable:

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_disable_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

   Responses:
     '200':
       Description: OK
       Content:
         application/yang-data+json:
           Schema:
             Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_disable'
     '204':
       Description: No Content
       Content: {}
     '400':
       Description: Bad Request
       Content: {}
     '401':
       Description: Unauthorized
       Content: {}
     '404':
       Description: Not Found
       Content: {}
     '405':
       Description: Method Not Allowed
       Content: {}
     '409':
```

```
      Description: Conflict
      Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_disable_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_disable'
       Required/Optional: true

    Responses:
      '201':
        Description: leaf disable created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: disable
  delete:

    Tags:
    - data
    - delete
   Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_disable_delete


    Responses:
      '204':
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_disable_options


  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_disable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
   Operation ID: data_tailf_mobile_infra_logging_async_monitor_subscriber_disable_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_disable'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf disable updated
        Content: {}
```

```
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: disable
```

/data/tailf-mobile-infra:logging/error

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_error_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_logging_error'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_error_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_logging_error'
    Required/Optional: true

  Responses:
    '201':
      Description: container error created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: error
Method: Post

  Tags:
  - data
  - post
```

```
  Operation ID: data_tailf_mobile_infra_logging_error_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_logging_error-post'

    Required/Optional: true

  Responses:
    '201':
      Description: container error created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: error
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_error_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_error_options
```

```
  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_error_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_logging_error_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_logging_error'
      Required/Optional: true

    Responses:
      '204':
        Description: container error updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
```

```
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: error
```

/data/tailf-mobile-infra:logging/error/stack

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_logging_error_stack_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_logging_error_stack'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_logging_error_stack_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_logging_error_stack'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf stack created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: stack
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_logging_error_stack_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_logging_error_stack_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_logging_error_stack_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_logging_error_stack_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_logging_error_stack'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf stack updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: stack
```

/data/tailf-mobile-infra:nodemonitor

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_nodemonitor_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_nodemonitor'
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_nodemonitor_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_nodemonitor'
    Required/Optional: true

  Responses:
    '201':
      Description: container nodemonitor created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: nodemonitor
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_nodemonitor_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_nodemonitor-post'
```

```
    Required/Optional: true

  Responses:
    '201':
      Description: container nodemonitor created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: nodemonitor
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_nodemonitor_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_nodemonitor_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

```
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_nodemonitor_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_nodemonitor_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_nodemonitor'
    Required/Optional: true

  Responses:
    '204':
      Description: container nodemonitor updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: nodemonitor
```

/data/tailf-mobile-infra:nodemonitor/mode

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_nodemonitor_mode_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_nodemonitor_mode'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_nodemonitor_mode_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
```

```
          Reference: '#/components/schemas/data_tailf-mobile-infra_nodemonitor_mode'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf mode created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: mode
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_nodemonitor_mode_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_nodemonitor_mode_options

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
```

```
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_nodemonitor_mode_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_nodemonitor_mode_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_nodemonitor_mode'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf mode updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: mode
```

/data/tailf-mobile-infra:nodemonitor/interval

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_nodemonitor_interval_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_nodemonitor_interval'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_nodemonitor_interval_put
```

```
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_nodemonitor_interval'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf interval created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interval
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_nodemonitor_interval_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_nodemonitor_interval_options
```

```
  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_nodemonitor_interval_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_nodemonitor_interval_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_nodemonitor_interval'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf interval updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: interval
```

/data/tailf-mobile-infra:monitor

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_monitor_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_monitor'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_monitor_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_monitor'
    Required/Optional: true

  Responses:
    '201':
      Description: container monitor created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_monitor_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_monitor-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container monitor created
      Content: {}
```

```
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_monitor_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_monitor_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_monitor_head
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_monitor_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_monitor'
    Required/Optional: true

  Responses:
    '204':
      Description: container monitor updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor
```

/data/tailf-mobile-infra:monitor/bfd

```
get:
```

```
Tags:
- data
- get
Operation ID: data_tailf_mobile_infra_monitor_bfd_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_monitor_bfd'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_monitor_bfd_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_monitor_bfd'
    Required/Optional: true

  Responses:
    '201':
      Description: container bfd created or replaced
```

```
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: bfd
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_monitor_bfd_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_monitor_bfd-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container bfd created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: bfd
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_monitor_bfd_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_monitor_bfd_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_monitor_bfd_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_monitor_bfd_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_monitor_bfd'
    Required/Optional: true

  Responses:
    '204':
      Description: container bfd updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: bfd
```

/data/tailf-mobile-infra:monitor/bfd/node-status

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_monitor_bfd_node_status_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_monitor_bfd_node-status'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_monitor_bfd_node_status_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_monitor_bfd_node-status'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf node-status created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: node-status
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_monitor_bfd_node_status_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_monitor_bfd_node_status_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_monitor_bfd_node_status_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
```

```
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_monitor_bfd_node_status_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_monitor_bfd_node-status'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf node-status updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: node-status
```

/data/tailf-mobile-infra:monitor/protocol

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_monitor_protocol_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_monitor_protocol'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_monitor_protocol_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_monitor_protocol'
    Required/Optional: true

  Responses:
    '201':
      Description: container protocol created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: protocol
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_monitor_protocol_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_monitor_protocol-post'

    Required/Optional: true

  Responses:
    '201':
      Description: container protocol created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  x-codegen-request-body-name: protocol
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_monitor_protocol_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_monitor_protocol_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_monitor_protocol_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_monitor_protocol_patch
  Request Body:
    Content:
      application/yang-data+json:
```

```
      Schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_monitor_protocol'
    Required/Optional: true

  Responses:
    '204':
      Description: container protocol updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: protocol
```

/data/tailf-mobile-infra:monitor/protocol/cpu-limit

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_monitor_protocol_cpu_limit_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_monitor_protocol_cpu-limit'
    '204':
      Description: No Content
      Content: {}
```

```
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_monitor_protocol_cpu_limit_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_monitor_protocol_cpu-limit'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf cpu-limit created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cpu-limit
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_monitor_protocol_cpu_limit_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_monitor_protocol_cpu_limit_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_monitor_protocol_cpu_limit_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_monitor_protocol_cpu_limit_patch
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_monitor_protocol_cpu-limit'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf cpu-limit updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu-limit
```

/data/tailf-mobile-infra:router

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_router_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
```

```
            Reference: '#/components/schemas/data_tailf-mobile-infra_router'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_router_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_router'
      Required/Optional: true

    Responses:
      '201':
        Description: container router created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: router
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_router_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_router-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container router created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: router
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_router_delete

  Responses:
```

```
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_router_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_router_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_router_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_router'
      Required/Optional: true

    Responses:
      '204':
        Description: container router updated
        Content: {}
      '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: router
```

/data/tailf-mobile-infra:router/bgplist

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_router_bgplist_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_get

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: integer
    Format: uint32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_put

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: insert
      In: query
```

```
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp'
    Required/Optional: true

  Responses:
    '201':
      Description: list bgplist created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: bgplist
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_delete

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_options

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_head
```

```
Parameters:
- Name: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_patch

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp'
      Required/Optional: true

    Responses:
      '204':
        Description: list bgplist updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
```

```
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: bgplist
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/bgp

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bgp_get

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bgp'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bgp_put

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bgp'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf bgp created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
```

```
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: bgp
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bgp_delete

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bgp_options

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    '200':
      Description: OK
      Content: {}
```

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bgp_head

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bgp_patch

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bgp'
      Required/Optional: true

    Responses:
      '204':
```

```
    Description: leaf bgp updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: bgp
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/loopbackPort

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackPort_get

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackPort'
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackPort_put

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackPort'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf loopbackPort created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
```

```
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: loopbackPort
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackPort_delete


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackPort_options


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: integer
        Format: uint32

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackPort_head

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackPort_patch

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackPort'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf loopbackPort updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: loopbackPort
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/loopbackBFDP ort

```
  get:

    Tags:
    - data
    - get
   Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackBFDPort_get


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackBFDPort'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackBFDPort_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackBFDPort'
```

```
    Required/Optional: true

  Responses:
    '201':
      Description: leaf loopbackBFDPort created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: loopbackBFDPort
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackBFDPort_delete


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackBFDPort_options

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackBFDPort_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
```

```
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_loopbackBFDPort_patch

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackBFDPort'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf loopbackBFDPort updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: loopbackBFDPort
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/learnDefault Route

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_learnDefaultRoute_get
```

```
Parameters:
- Name: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_learnDefaultRoute'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_learnDefaultRoute_put


    Parameters:
    - Name: bgplist-bgp
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_learnDefaultRoute'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf learnDefaultRoute created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: learnDefaultRoute
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_learnDefaultRoute_delete

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_learnDefaultRoute_options

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_learnDefaultRoute_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_learnDefaultRoute_patch

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_learnDefaultRoute'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf learnDefaultRoute updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
```

```
    Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: learnDefaultRoute
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/prepend

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_get

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_put

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend'
      Required/Optional: true

    Responses:
      '201':
        Description: container prepend created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: prepend
```

```
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_post

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container prepend created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: prepend
  delete:

    Tags:
    - data
```

```
  - delete
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_delete

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_options

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_head

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_patch

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend'
      Required/Optional: true

    Responses:
      '204':
        Description: container prepend updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
```

```
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: prepend
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/prepend/as-p ath

```
get:

 Tags:
 - data
 - get
 Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_as_path_get


 Parameters:
 - Name: bgplist-bgp
   In: path
   Required/Optional: true
   Style: simple
   Explode: false
   Schema:
     Type: integer
     Format: uint32
 - Name: content
   In: query
   Description: controlling descendant nodes in response
   Required/Optional: false
   Style: form
   Explode: true
   Schema:
     Type: string
     Format: enumeration
     Default: config
     enum:
     - config
     - nonconfig
     - all
 - Name: depth
   In: query
   Description: limit the depth of nodes in response
   Required/Optional: false
   Style: form
   Explode: true
   Schema:
     Type: integer
     Format: uint16
 - Name: fields
   In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend_as-path'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
 Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_as_path_put


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend_as-path'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf as-path created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: as-path
  delete:

    Tags:
    - data
    - delete
   Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_as_path_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_as_path_options

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:
```

Tags:
- data
- head

Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_as_path_head

Parameters:
- **Name**: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_prepend_as_path_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend_as-path'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf as-path updated
        Content: {}
```

```
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: as-path
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceLis t

```
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_options


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceLis t={interfaceList-interface}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_get


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
```

```
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface'

      Required/Optional: true

    Responses:
      '201':
        Description: list interfaceList created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interfaceList
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_delete


    Parameters:
    - Name: bgplist-bgp
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
```

```
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: integer
        Format: uint32
      - Name: interfaceList-interface
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface'

        Required/Optional: true

      Responses:
        '204':
          Description: list interfaceList updated
          Content: {}
        '400':
          Description: Bad Request
          Content: {}
        '401':
          Description: Unauthorized
          Content: {}
        '404':
          Description: Not Found
          Content: {}
        '405':
          Description: Method Not Allowed
          Content: {}
        '409':
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
      x-codegen-request-body-name: interfaceList
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceLis t={interfaceList-interface}/interface

```
    get:

      Tags:
      - data
      - get
```

Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_interface_get

Parameters:
- **Name**: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- **Name**: interfaceList-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_interface'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_interface_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_interface'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf interface created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_interface_delete


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_interface_options


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_interface_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_interface_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_interface'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf interface updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceLis t={interfaceList-interface}/bondingInterfaces

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_options


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
?
/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceList={interfaceList-interface}/bondingInterfaces={bondingInterfaces-bondingInterface}
: get:

  Tags:
  - data
  - get
```

Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_get

Parameters:
- **Name**: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- **Name**: interfaceList-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: bondingInterfaces-bondingInterface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields

```
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_put


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: bondingInterfaces-bondingInterface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
```

```
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface'

    Required/Optional: true

  Responses:
    '201':
      Description: list bondingInterfaces created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: bondingInterfaces
delete:

  Tags:
  - data
  - delete
```

```
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_delete

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: bondingInterfaces-bondingInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_options

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
```

```
      Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: bondingInterfaces-bondingInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: bondingInterfaces-bondingInterface
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: bondingInterfaces-bondingInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface'

      Required/Optional: true

    Responses:
      '204':
        Description: list bondingInterfaces updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: bondingInterfaces
?
/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceList={interfaceList-interface}/bondingInterfaces={bondingInterfaces-bondingInterface}/bondingInterface
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_bondingInterface_get


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: bondingInterfaces-bondingInterface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface_bondingInterface'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_bondingInterface_put


    Parameters:
```

```
- Name: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: interfaceList-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: bondingInterfaces-bondingInterface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface_bondingInterface'

  Required/Optional: true

Responses:
  '201':
    Description: leaf bondingInterface created or replaced
    Content: {}
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
```

```
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: bondingInterface
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_bondingInterface_delete


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: bondingInterfaces-bondingInterface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_bondingInterface_options
```

```
    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: bondingInterfaces-bondingInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_bondingInterface_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: bondingInterfaces-bondingInterface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_bondingInterfaces_bondingInterfaces_bondingInterface_bondingInterface_patch


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: bondingInterfaces-bondingInterface
    In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface_bondingInterface'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf bondingInterface updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: bondingInterface
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceLis t={interfaceList-interface}/vrf

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_vrf_get


    Parameters:
```

```
- Name: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: interfaceList-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_vrf'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
```

```
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_vrf_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_vrf'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf vrf created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_vrf_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_vrf_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
```

```
      Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_vrf_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_vrf_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_vrf'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vrf updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
```

```
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceLis t={interfaceList-interface}/neighbors

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
?
/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceList={interfaceList-interface}/neighbors={neighbors-neighbor}
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_get


    Parameters:
```

```
- Name: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: interfaceList-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: neighbors-neighbor
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
```

```
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor'

      Required/Optional: true

    Responses:
      '201':
        Description: list neighbors created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: neighbors
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_delete
```

```
    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: union
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor'

      Required/Optional: true
```

```
    Responses:
      '204':
        Description: list neighbors updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: neighbors
?
/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceList={interfaceList-interface}/neighbors={neighbors-neighbor}/neighbor
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_neighbor_get


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_neighbor'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_neighbor_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: neighbors-neighbor
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_neighbor'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf neighbor created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: neighbor
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_neighbor_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_neighbor_options


    Parameters:
    - Name: bgplist-bgp
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_neighbor_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: neighbors-neighbor
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_neighbor_patch

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: neighbors-neighbor
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
        Type: string
        Format: union
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_neighbor'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf neighbor updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: neighbor
?
/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceList={interfaceList-interface}/neighbors={neighbors-neighbor}/remote-as
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_remote_as_get


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
```

```
- Name: interfaceList-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: neighbors-neighbor
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_remote-as'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
```

```
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_remote_as_put

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_remote-as'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf remote-as created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remote-as
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_remote_as_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
```

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_remote_as_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_remote_as_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: neighbors-neighbor
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_remote_as_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_remote-as'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf remote-as updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remote-as
?
/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/interfaceList={interfaceList-interface}/neighbors={neighbors-neighbor}/fail-over
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_fail_over_get
```

```
Parameters:
- Name: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: interfaceList-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: neighbors-neighbor
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_fail-over'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_fail_over_put


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: neighbors-neighbor
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_fail-over'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf fail-over created or replaced
```

```
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: fail-over
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_fail_over_delete


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: neighbors-neighbor
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: union

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_fail_over_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: interfaceList-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:
```

Tags:
- data
- head

Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_fail_over_head

Parameters:
- **Name**: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- **Name**: interfaceList-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: neighbors-neighbor
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:

```
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_interfaceList_interfaceList_interface_neighbors_neighbors_neighbor_fail_over_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: interfaceList-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: neighbors-neighbor
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_fail-over'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf fail-over updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: fail-over
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/policies

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_options

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/policies={policies-policy-name}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_get

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_put

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name'

      Required/Optional: true

    Responses:
      '201':
        Description: list policies created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: policies
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_delete

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
```

```
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_options

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_head

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_patch

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name'

      Required/Optional: true

    Responses:
      '204':
        Description: list policies updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: policies
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/policies={po licies-policy-name}/policy-name

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_policy_name_get


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_policy-name'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_policy_name_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_policy-name'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf policy-name created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: policy-name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_policy_name_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_policy_name_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_policy_name_head
```

```
Parameters:
- Name: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: policies-policy-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_policy_name_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_policy-name'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf policy-name updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: policy-name
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/policies={po licies-policy-name}/as-path-set

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_as_path_set_get


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: integer
    Format: uint32
- Name: policies-policy-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_as-path-set'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_as_path_set_put
```

```
    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_as-path-set'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf as-path-set created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: as-path-set
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_as_path_set_delete

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_as_path_set_options

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_as_path_set_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
```

data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_as_path_set_patch

```
Parameters:
- Name: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: policies-policy-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_as-path-set'

  Required/Optional: true

Responses:
  '204':
    Description: leaf as-path-set updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: as-path-set
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/policies={po licies-policy-name}/ip-prefix

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_ip_prefix_get


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_ip-prefix'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_ip_prefix_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_ip-prefix'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf ip-prefix created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
```

```
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ip-prefix
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_ip_prefix_delete


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_ip_prefix_options

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_ip_prefix_head

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_ip_prefix_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_ip-prefix'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf ip-prefix updated
        Content: {}
      '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ip-prefix
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/policies={po licies-policy-name}/source-prefix

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_source_prefix_get


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_source-prefix'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_source_prefix_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_source-prefix'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf source-prefix created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: source-prefix
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_source_prefix_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_source_prefix_options


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
```

```
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_source_prefix_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_source_prefix_patch


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_source-prefix'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf source-prefix updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: source-prefix
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/policies={po licies-policy-name}/mask-range

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_mask_range_get


    Parameters:
    - Name: bgplist-bgp
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: policies-policy-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_mask-range'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
```

```
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_mask_range_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_mask-range'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf mask-range created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
```

```
    security:
    - basicAuth: []
    x-codegen-request-body-name: mask-range
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_mask_range_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_mask_range_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
```

```
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_mask_range_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_mask_range_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_mask-range'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf mask-range updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: mask-range
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/policies={po licies-policy-name}/interface

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_interface_get


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_interface'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
```

```
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_interface_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_interface'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf interface created or replaced
        Content: {}
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_interface_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_interface_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_interface_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_interface_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_interface'

      Required/Optional: true

    Responses:
      '204':
```

```
      Description: leaf interface updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/policies={po licies-policy-name}/modifySourceIp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_modifySourceIp_get


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_modifySourceIp'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_modifySourceIp_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_modifySourceIp'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf modifySourceIp created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: modifySourceIp
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_modifySourceIp_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_modifySourceIp_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

```
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_modifySourceIp_head


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_modifySourceIp_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
```

```
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_modifySourceIp'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf modifySourceIp updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: modifySourceIp
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/policies={po licies-policy-name}/isStaticRoute

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_isStaticRoute_get
```

```
Parameters:
- Name: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: policies-policy-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_isStaticRoute'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_isStaticRoute_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_isStaticRoute'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf isStaticRoute created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
```

```
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: isStaticRoute
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_isStaticRoute_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_isStaticRoute_options


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_isStaticRoute_head


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_isStaticRoute_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_isStaticRoute'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf isStaticRoute updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: isStaticRoute
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/policies={po licies-policy-name}/gateWay

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_gateWay_get


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_gateWay'

    '204':
      Description: No Content
      Content: {}
```

```
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_gateWay_put


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_gateWay'

      Required/Optional: true

    Responses:
```

```
      '201':
        Description: leaf gateWay created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: gateWay
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_gateWay_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_gateWay_options


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: policies-policy-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_gateWay_head


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
```

```
    Format: uint32
- Name: policies-policy-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_policies_policies_policy_name_gateWay_patch


    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: policies-policy-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_gateWay'

      Required/Optional: true
```

```
  Responses:
    '204':
      Description: leaf gateWay updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: gateWay
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/bfd

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_get

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_put

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd'
      Required/Optional: true

    Responses:
      '201':
        Description: container bfd created or replaced
        Content: {}
      '204':
        Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: bfd
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_post

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container bfd created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
```

```
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: bfd
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_delete

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_options

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
```

```
      Format: uint32

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_head

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_patch

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd'
    Required/Optional: true

  Responses:
    '204':
      Description: container bfd updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: bfd
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/bfd/interval

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_interval_get

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_interval'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_interval_put

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_interval'
      Required/Optional: true

    Responses:
      '201':
```

```
      Description: leaf interval created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interval
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_interval_delete


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_interval_options
```

```
  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_interval_head

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_interval_patch

    Parameters:
    - Name: bgplist-bgp
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_interval'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf interval updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interval
```


/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/bfd/min_rx


```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_min_rx_get

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_min_rx'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_min_rx_put

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
```

```
      Format: uint32
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_min_rx'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf min_rx created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: min_rx
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_min_rx_delete

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    '204':
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_min_rx_options

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_min_rx_head

  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_min_rx_patch

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_min_rx'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf min_rx updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: min_rx
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/bfd/multipli er

```
  get:
```

```
Tags:
- data
- get
Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_multiplier_get

Parameters:
- Name: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        '200':
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_multiplier'
        '204':
          Description: No Content
          Content: {}
        '400':
          Description: Bad Request
          Content: {}
        '401':
          Description: Unauthorized
          Content: {}
        '404':
          Description: Not Found
          Content: {}
        '405':
          Description: Method Not Allowed
          Content: {}
        '409':
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    put:

      Tags:
      - data
      - put
      Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_multiplier_put
```

```
    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_multiplier'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf multiplier created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: multiplier
  delete:

    Tags:
    - data
    - delete
   Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_multiplier_delete


    Parameters:
    - Name: bgplist-bgp
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_multiplier_options


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_multiplier_head


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_multiplier_patch


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_multiplier'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf multiplier updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
    Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: multiplier
```

/data/tailf-mobile-infra:router/bgplist={bgplist-bgp}/bfd/dscp-mar king

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_dscp_marking_get


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_dscp-marking'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_dscp_marking_put


  Parameters:
  - Name: bgplist-bgp
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_dscp-marking'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf dscp-marking created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
    x-codegen-request-body-name: dscp-marking
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_dscp_marking_delete

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_dscp_marking_options

    Parameters:
    - Name: bgplist-bgp
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

```
Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_dscp_marking_head

Parameters:
- Name: bgplist-bgp
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        '200':
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
     Operation ID: data_tailf_mobile_infra_router_bgplist_bgplist_bgp_bfd_dscp_marking_patch


      Parameters:
      - Name: bgplist-bgp
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: integer
          Format: uint32
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
    '#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_dscp-marking'
        Required/Optional: true

      Responses:
        '204':
          Description: leaf dscp-marking updated
          Content: {}
        '400':
          Description: Bad Request
```

```
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: dscp-marking
```

/data/tailf-mobile-infra:router/bfd

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_router_bfd_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_router_bfd'
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
```

```
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_router_bfd_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_router_bfd'
    Required/Optional: true

  Responses:
    '201':
      Description: container bfd created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: bfd
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_router_bfd_post
  Request Body:
```

```
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_router_bfd-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container bfd created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: bfd
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_router_bfd_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_router_bfd_options

    Responses:
      '200':
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_router_bfd_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_router_bfd_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_router_bfd'
    Required/Optional: true

  Responses:
    '204':
      Description: container bfd updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
    Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: bfd
```

/data/tailf-mobile-infra:router/bfd/instance

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_router_bfd_instance_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_router_bfd_instance'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
```

```
    - put
    Operation ID: data_tailf_mobile_infra_router_bfd_instance_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
           Reference: '#/components/schemas/data_tailf-mobile-infra_router_bfd_instance'

      Required/Optional: true

    Responses:
      '201':
        Description: container instance created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instance
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_router_bfd_instance_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container instance created
        Content: {}
```

```
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instance
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_router_bfd_instance_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_router_bfd_instance_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_router_bfd_instance_head
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_router_bfd_instance_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_router_bfd_instance'

    Required/Optional: true

  Responses:
    '204':
      Description: container instance updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instance
```

/data/tailf-mobile-infra:router/bfd/instance/instance-id

```
options:
```

```
    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_router_bfd_instance_instance_id_options

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:router/bfd/instance/instance-id={instance -id-id}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_get

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
        Format: string
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id'

        Required/Optional: true

      Responses:
        '201':
          Description: list instance-id created or replaced
          Content: {}
        '204':
          Description: No Content
          Content: {}
        '400':
          Description: Bad Request
          Content: {}
        '401':
          Description: Unauthorized
          Content: {}
        '404':
          Description: Not Found
          Content: {}
        '405':
          Description: Method Not Allowed
          Content: {}
        '409':
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
      x-codegen-request-body-name: instance-id
    delete:

      Tags:
      - data
      - delete
      Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_delete

      Parameters:
      - Name: instance-id-id
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: leafref
```

```
    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_head

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_patch

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id'

      Required/Optional: true

    Responses:
      '204':
        Description: list instance-id updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instance-id
```

/data/tailf-mobile-infra:router/bfd/instance/instance-id={instance -id-id}/id

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_id_get

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_id'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_id_put

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_id'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf id created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: id
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_id_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_id_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_id_head

    Parameters:
```

```
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_id_patch

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_id'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf id updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: id
```

/data/tailf-mobile-infra:router/bfd/instance/instance-id={instance -id-id}/interface-list

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:router/bfd/instance/instance-id={instance -id-id}/interface-list={interface-list-interface}

```
  get:

    Tags:
```

```
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_get


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface'

      Required/Optional: true

    Responses:
      '201':
        Description: list interface-list created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface-list
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_head
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: interface-list-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface'

    Required/Optional: true

  Responses:
    '204':
      Description: list interface-list updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface-list
?
/data/tailf-mobile-infra:router/bfd/instance/instance-id={instance-id-id}/interface-list={interface-list-interface}/interface
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_interface_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
```

```
- Name: interface-list-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_interface'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_interface_put


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_interface'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf interface created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface
  delete:

    Tags:
    - data
    - delete
```

```
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_interface_delete

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_interface_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_interface_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_interface_patch


    Parameters:
```

```
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_interface'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf interface updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface
```

/data/tailf-mobile-infra:router/bfd/instance/instance-id={instance -id-id}/interface-list={interface-list-interface}/vrf

get:

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_vrf_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: interface-list-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_vrf'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_vrf_put


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_vrf'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf vrf created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
```

```
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vrf
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_vrf_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_vrf_options

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_vrf_head

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_vrf_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_vrf'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf vrf updated
      Content: {}
    '400':
```

```
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vrf
?
/data/tailf-mobile-infra:router/bfd/instance/instance-id={instance-id-id}/interface-list={interface-list-interface}/neighbors
: options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
?
```

/data/tailf-mobile-infra:router/bfd/instance/instance-id={instance-id-id}/interface-list={interface-list-interface}/neighbors={neighbors-neighbor}
: get:

Tags:
- data
- get

Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_neighbors_neighbor_get

Parameters:
- **Name**: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- **Name**: interface-list-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: neighbors-neighbor
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false

```
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
```

```
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_neighbors_neighbor_put


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: neighbors-neighbor
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor'

      Required/Optional: true

    Responses:
      '201':
        Description: list neighbors created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
    x-codegen-request-body-name: neighbors
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_neighbors_neighbor_delete


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_neighbors_neighbor_options


    Parameters:
    - Name: instance-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_neighbors_neighbor_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: neighbors-neighbor
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_neighbors_neighbor_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: neighbors-neighbor
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: union
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor'

    Required/Optional: true

  Responses:
    '204':
      Description: list neighbors updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: neighbors
?
/data/tailf-mobile-infra:router/bfd/instance/instance-id={instance-id-id}/interface-list={interface-list-interface}/neighbors={neighbors-neighbor}/neighbor
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors_neighbor_neighbor_get


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: neighbors-neighbor
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbor_neighbor'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
```

```
    - put
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_neighbors_neighbor_neighbor_put

    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor_neighbor'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf neighbor created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: neighbor
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_neighbors_neighbor_neighbor_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: neighbors-neighbor
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_neighbors_neighbor_neighbor_options


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_neighbors_neighbor_neighbor_head


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: interface-list-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: neighbors-neighbor
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_neighbors_neighbors_neighbor_neighbor_patch


    Parameters:
    - Name: instance-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    - Name: neighbors-neighbor
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor_neighbor'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf neighbor updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: neighbor
?
/data/tailf-mobile-infra:router/bfd/instance/instance-id={instance-id-id}/interface-list={interface-list-interface}/gateway-ip
: get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_gateway_ip_get
```

```
Parameters:
- Name: instance-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: interface-list-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_gateway-ip'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_gateway_ip_put

  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_gateway-ip'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf gateway-ip created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: gateway-ip
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_gateway_ip_delete


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_gateway_ip_options


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_gateway_ip_head


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_router_bfd_instance_instance_id_instance_id_id_interface_list_interface_list_interface_gateway_ip_patch


  Parameters:
  - Name: instance-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_gateway-ip'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf gateway-ip updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
    Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: gateway-ip
```

/data/tailf-mobile-infra:router/monitor-interface

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_router_monitor_interface_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_monitor-interface'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
```

```
    - put
    Operation ID: data_tailf_mobile_infra_router_monitor_interface_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_monitor-interface'
      Required/Optional: true

    Responses:
      '201':
        Description: container monitor-interface created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: monitor-interface
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_router_monitor_interface_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_monitor-interface-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container monitor-interface created
        Content: {}
```

```
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitor-interface
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_router_monitor_interface_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_router_monitor_interface_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_router_monitor_interface_head
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_router_monitor_interface_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_monitor-interface'
      Required/Optional: true

    Responses:
      '204':
        Description: container monitor-interface updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: monitor-interface
```

/data/tailf-mobile-infra:router/monitor-interface/interface-list

```
  options:
```

```
    Tags:
    - data
    - options
   Operation ID: data_tailf_mobile_infra_router_monitor_interface_interface_list_options

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:router/monitor-interface/interface-list={ interface-list-interface}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_get

    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface'

    '204':
      Description: No Content
      Content: {}
    '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_put


  Parameters:
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface'

      Required/Optional: true

    Responses:
      '201':
        Description: list interface-list created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface-list
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_delete


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_options


  Parameters:
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_head


  Parameters:
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_patch


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface'

      Required/Optional: true

    Responses:
      '204':
        Description: list interface-list updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
```

```
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface-list
```

/data/tailf-mobile-infra:router/monitor-interface/interface-list={ interface-list-interface}/interface

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_get


  Parameters:
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_put


  Parameters:
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf interface created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
```

```
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_delete


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_options


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
```

```
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_head


  Parameters:
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_patch


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf interface updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: interface
```

/data/tailf-mobile-infra:router/monitor-interface/interface-list={ interface-list-interface}/linked-interface

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_linked_interface_get

    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_linked-interface'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_linked_interface_put


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_linked-interface'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf linked-interface created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: linked-interface
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_linked_interface_delete


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
```

```
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_linked_interface_options


  Parameters:
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_linked_interface_head


  Parameters:
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_linked_interface_patch


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_linked-interface'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf linked-interface updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: linked-interface
```

/data/tailf-mobile-infra:router/monitor-interface/interface-list={ interface-list-interface}/interface-type

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_type_get


  Parameters:
  - Name: interface-list-interface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface-type'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_type_put


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface-type'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf interface-type created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: interface-type
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_type_delete


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_type_options


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:
```

Tags:
- data
- head

Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_type_head

Parameters:
- **Name**: interface-list-interface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_router_monitor_interface_interface_list_interface_list_interface_interface_type_patch


    Parameters:
    - Name: interface-list-interface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface-type'

      Required/Optional: true

    Responses:
```

```
    '204':
      Description: leaf interface-type updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: interface-type
```

/data/tailf-mobile-infra:deployment

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_deployment_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_deployment'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_deployment_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_deployment'
    Required/Optional: true

  Responses:
    '201':
      Description: container deployment created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: deployment
Method: Post
```

```
  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_deployment_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_deployment-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container deployment created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: deployment
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_deployment_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
```

```
  - data
  - options
  Operation ID: data_tailf_mobile_infra_deployment_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_deployment_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_deployment_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_deployment'
    Required/Optional: true

  Responses:
    '204':
      Description: container deployment updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
```

```
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: deployment
```

/data/tailf-mobile-infra:deployment/app-name

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_deployment_app_name_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_deployment_app-name'

  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
```

```
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_deployment_app_name_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_deployment_app-name'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf app-name created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: app-name
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_deployment_app_name_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
```

```
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_deployment_app_name_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_deployment_app_name_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_deployment_app_name_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
           Reference: '#/components/schemas/data_tailf-mobile-infra_deployment_app-name'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf app-name updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
```

```
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: app-name
```

/data/tailf-mobile-infra:deployment/cluster-name

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_deployment_cluster_name_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_deployment_cluster-name'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_deployment_cluster_name_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_deployment_cluster-name'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf cluster-name created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cluster-name
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_deployment_cluster_name_delete

  Responses:
```

```
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_deployment_cluster_name_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_deployment_cluster_name_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_deployment_cluster_name_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_deployment_cluster-name'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf cluster-name updated
        Content: {}
```

```
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cluster-name
```

/data/tailf-mobile-infra:deployment/dc-name

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_deployment_dc_name_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_deployment_dc-name'

  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_deployment_dc_name_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_deployment_dc-name'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf dc-name created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dc-name
delete:

  Tags:
  - data
```

```
  - delete
  Operation ID: data_tailf_mobile_infra_deployment_dc_name_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_deployment_dc_name_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_deployment_dc_name_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_deployment_dc_name_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_deployment_dc-name'

      Required/Optional: true
```

```
Responses:
  '204':
    Description: leaf dc-name updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: dc-name
```

/data/tailf-mobile-infra:deployment/model

```
get:

  Tags:
  - data
  - get
  Summary: Deployment Model default large
  Description: Deployment Model default large
  Operation ID: data_tailf_mobile_infra_deployment_model_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
    Description: Deployment Model default large
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_deployment_model'

  '204':
    Description: No Content
    Content: {}
  '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Summary: Deployment Model default large
  Description: Deployment Model default large
  Operation ID: data_tailf_mobile_infra_deployment_model_put
  Request Body:
    Description: Deployment Model default large
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_deployment_model'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf model created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: model
delete:

  Tags:
  - data
  - delete
  Summary: Deployment Model default large
  Description: Deployment Model default large
  Operation ID: data_tailf_mobile_infra_deployment_model_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Summary: Deployment Model default large
  Description: Deployment Model default large
  Operation ID: data_tailf_mobile_infra_deployment_model_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Summary: Deployment Model default large
  Description: Deployment Model default large
  Operation ID: data_tailf_mobile_infra_deployment_model_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
```

```
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Summary: Deployment Model default large
  Description: Deployment Model default large
  Operation ID: data_tailf_mobile_infra_deployment_model_patch
  Request Body:
    Description: Deployment Model default large
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_deployment_model'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf model updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: model
```

/data/tailf-mobile-infra:deployment/resource

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_deployment_resource_get

  Parameters:
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_deployment_resource'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_deployment_resource_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_deployment_resource'

    Required/Optional: true

  Responses:
    '201':
      Description: container resource created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
```

```
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: resource
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_deployment_resource_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_deployment_resource-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container resource created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: resource
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_deployment_resource_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_deployment_resource_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_deployment_resource_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_deployment_resource_patch
    Request Body:
```

```
    Content:
      application/yang-data+json:
        Schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_deployment_resource'

    Required/Optional: true

  Responses:
    '204':
      Description: container resource updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: resource
```

/data/tailf-mobile-infra:deployment/resource/cpu

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_deployment_resource_cpu_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

```
'#/components/schemas/data_tailf-mobile-infra_deployment_resource_cpu'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_deployment_resource_cpu_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_deployment_resource_cpu'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf cpu created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cpu
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_deployment_resource_cpu_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_deployment_resource_cpu_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_deployment_resource_cpu_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
```

```
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_deployment_resource_cpu_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_deployment_resource_cpu'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf cpu updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu
```

/data/tailf-mobile-infra:deployment/logical-nf-instance-id

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_deployment_logical_nf_instance_id_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_deployment_logical-nf-instance-id'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_deployment_logical_nf_instance_id_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_deployment_logical-nf-instance-id'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf logical-nf-instance-id created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: logical-nf-instance-id
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_deployment_logical_nf_instance_id_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_deployment_logical_nf_instance_id_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_deployment_logical_nf_instance_id_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_deployment_logical_nf_instance_id_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_deployment_logical-nf-instance-id'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf logical-nf-instance-id updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: logical-nf-instance-id
```

/data/tailf-mobile-infra:k8

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_k8_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_k8'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_k8_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_k8'
    Required/Optional: true

  Responses:
    '201':
      Description: container k8 created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: k8
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_k8_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_k8-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container k8 created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: k8
delete:
```

```
  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_k8_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_k8_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_k8_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_k8_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_k8'
    Required/Optional: true
```

```
  Responses:
    '204':
      Description: container k8 updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: k8
```

/data/tailf-mobile-infra:k8/label

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_k8_label_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_k8_label'
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
```

```
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_k8_label_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_k8_label'
    Required/Optional: true

  Responses:
    '201':
      Description: container label created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: label
```

```
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_k8_label_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_k8_label-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container label created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: label
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_k8_label_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_k8_label_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_k8_label_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_k8_label_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_k8_label'
    Required/Optional: true

  Responses:
    '204':
      Description: container label updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: label
```

/data/tailf-mobile-infra:k8/label/pod-group-config

```
 options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_k8_label_pod_group_config_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
?
/data/tailf-mobile-infra:k8/label/pod-group-config={pod-group-config-pod-group},{pod-group-config-key},{pod-group-config-value}
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_get


  Parameters:
  - Name: pod-group-config-pod-group
    In: path
    Description: Group for the VMs
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
```

```
    - oam-layer
- Name: pod-group-config-key
  In: path
  Description: Key for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: pod-group-config-value
  In: path
  Description: Value for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

put:

Tags:
- data
- put

Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_put

Parameters:
- **Name**: pod-group-config-pod-group
  In: path
  Description: Group for the VMs
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: protocol-layer
    enum:
    - protocol-layer
    - service-layer
    - cdl-layer
    - oam-layer
- **Name**: pod-group-config-key
  In: path
  Description: Key for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: pod-group-config-value
  In: path
  Description: Value for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: insert
  In: query
  Description: controlling the order when adding new list elements
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: first

```
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value'

    Required/Optional: true

  Responses:
    '201':
      Description: list pod-group-config created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pod-group-config
delete:

  Tags:
  - data
  - delete
```

```
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_delete

    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol-layer
        enum:
        - protocol-layer
        - service-layer
        - cdl-layer
        - oam-layer
    - Name: pod-group-config-key
      In: path
      Description: Key for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: pod-group-config-value
      In: path
      Description: Value for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_options
```

```
    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol-layer
        enum:
        - protocol-layer
        - service-layer
        - cdl-layer
        - oam-layer
    - Name: pod-group-config-key
      In: path
      Description: Key for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: pod-group-config-value
      In: path
      Description: Value for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_head


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: protocol-layer
    enum:
    - protocol-layer
    - service-layer
    - cdl-layer
    - oam-layer
- Name: pod-group-config-key
  In: path
  Description: Key for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: pod-group-config-value
  In: path
  Description: Value for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_patch


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol-layer
        enum:
        - protocol-layer
        - service-layer
        - cdl-layer
        - oam-layer
    - Name: pod-group-config-key
      In: path
      Description: Key for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: pod-group-config-value
      In: path
      Description: Value for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value'

      Required/Optional: true

  Responses:
    '204':
      Description: list pod-group-config updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pod-group-config
?
/data/tailf-mobile-infra:k8/label/pod-group-config={pod-group-config-pod-group},{pod-group-config-key},{pod-group-config-value}/pod-group
: get:

  Tags:
  - data
  - get
  Summary: Group for the VMs
  Description: Group for the VMs
  Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_pod_group_get


  Parameters:
  - Name: pod-group-config-pod-group
    In: path
    Description: Group for the VMs
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
  - Name: pod-group-config-key
    In: path
    Description: Key for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: pod-group-config-value
    In: path
    Description: Value for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: Group for the VMs
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_pod-group'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Summary: Group for the VMs
    Description: Group for the VMs
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_pod_group_put


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: enumeration
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
  - Name: pod-group-config-key
    In: path
    Description: Key for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: pod-group-config-value
    In: path
    Description: Value for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Description: Group for the VMs
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_pod-group'

      Required/Optional: true

  Responses:
    '201':
      Description: leaf pod-group created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pod-group
delete:

  Tags:
  - data
  - delete
  Summary: Group for the VMs
  Description: Group for the VMs
  Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_pod_group_delete


  Parameters:
  - Name: pod-group-config-pod-group
    In: path
    Description: Group for the VMs
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
  - Name: pod-group-config-key
    In: path
    Description: Key for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: pod-group-config-value
    In: path
    Description: Value for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Summary: Group for the VMs
    Description: Group for the VMs
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_pod_group_options


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol-layer
        enum:
        - protocol-layer
        - service-layer
        - cdl-layer
        - oam-layer
    - Name: pod-group-config-key
      In: path
      Description: Key for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: pod-group-config-value
      In: path
      Description: Value for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Summary: Group for the VMs
  Description: Group for the VMs
  Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_pod_group_head


  Parameters:
  - Name: pod-group-config-pod-group
    In: path
    Description: Group for the VMs
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
  - Name: pod-group-config-key
    In: path
    Description: Key for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: pod-group-config-value
    In: path
    Description: Value for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Summary: Group for the VMs
    Description: Group for the VMs
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_pod_group_patch


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol-layer
        enum:
        - protocol-layer
        - service-layer
        - cdl-layer
        - oam-layer
    - Name: pod-group-config-key
      In: path
      Description: Key for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: pod-group-config-value
      In: path
      Description: Value for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Description: Group for the VMs
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_pod-group'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf pod-group updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pod-group
?
/data/tailf-mobile-infra:k8/label/pod-group-config={pod-group-config-pod-group},{pod-group-config-key},{pod-group-config-value}/key
: get:

    Tags:
    - data
    - get
    Summary: Key for the label
    Description: Key for the label
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_key_get


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: protocol-layer
    enum:
    - protocol-layer
    - service-layer
    - cdl-layer
    - oam-layer
- Name: pod-group-config-key
  In: path
  Description: Key for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: pod-group-config-value
  In: path
  Description: Value for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: Key for the label
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_key'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Summary: Key for the label
  Description: Key for the label
  Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_key_put


  Parameters:
  - Name: pod-group-config-pod-group
    In: path
    Description: Group for the VMs
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: enumeration
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
  - Name: pod-group-config-key
    In: path
    Description: Key for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: pod-group-config-value
    In: path
    Description: Value for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Description: Key for the label
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_key'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf key created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key
  delete:

    Tags:
    - data
    - delete
    Summary: Key for the label
    Description: Key for the label
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_key_delete


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol-layer
```

```
        enum:
        - protocol-layer
        - service-layer
        - cdl-layer
        - oam-layer
      - Name: pod-group-config-key
        In: path
        Description: Key for the label
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
      - Name: pod-group-config-value
        In: path
        Description: Value for the label
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Summary: Key for the label
    Description: Key for the label
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_key_options


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol-layer
        enum:
        - protocol-layer
```

```
        - service-layer
        - cdl-layer
        - oam-layer
    - Name: pod-group-config-key
      In: path
      Description: Key for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: pod-group-config-value
      In: path
      Description: Value for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Summary: Key for the label
    Description: Key for the label
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_key_head


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol-layer
        enum:
        - protocol-layer
        - service-layer
        - cdl-layer
```

```
    - oam-layer
- Name: pod-group-config-key
  In: path
  Description: Key for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: pod-group-config-value
  In: path
  Description: Value for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Summary: Key for the label
    Description: Key for the label
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_key_patch


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol-layer
        enum:
        - protocol-layer
```

```
      - service-layer
      - cdl-layer
      - oam-layer
  - Name: pod-group-config-key
    In: path
    Description: Key for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: pod-group-config-value
    In: path
    Description: Value for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Description: Key for the label
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_key'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf key updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: key
```

?
/data/tailf-mobile-infra:k8/label/pod-group-config={pod-group-config-pod-group},{pod-group-config-key},{pod-group-config-value}/value
: get:

Tags:
- data
- get

Summary: Value for the label
Description: Value for the label
Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_value_get

Parameters:
- **Name**: pod-group-config-pod-group
  In: path
  Description: Group for the VMs
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: enumeration
    Default: protocol-layer
    enum:
    - protocol-layer
    - service-layer
    - cdl-layer
    - oam-layer
- **Name**: pod-group-config-key
  In: path
  Description: Key for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: pod-group-config-value
  In: path
  Description: Value for the label
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
```

```
        Description: Value for the label
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_value'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Summary: Value for the label
    Description: Value for the label
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_value_put


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol-layer
        enum:
        - protocol-layer
        - service-layer
        - cdl-layer
        - oam-layer
```

```
  - Name: pod-group-config-key
    In: path
    Description: Key for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: pod-group-config-value
    In: path
    Description: Value for the label
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Description: Value for the label
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_value'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf value created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
    x-codegen-request-body-name: value
  delete:

    Tags:
    - data
    - delete
    Summary: Value for the label
    Description: Value for the label
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_value_delete


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol-layer
        enum:
        - protocol-layer
        - service-layer
        - cdl-layer
        - oam-layer
    - Name: pod-group-config-key
      In: path
      Description: Key for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: pod-group-config-value
      In: path
      Description: Value for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:
```

```
    Tags:
    - data
    - options
    Summary: Value for the label
    Description: Value for the label
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_value_options

    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol-layer
        enum:
        - protocol-layer
        - service-layer
        - cdl-layer
        - oam-layer
    - Name: pod-group-config-key
      In: path
      Description: Key for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: pod-group-config-value
      In: path
      Description: Value for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
```

```
    - data
    - head
    Summary: Value for the label
    Description: Value for the label
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_value_head


    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol-layer
        enum:
        - protocol-layer
        - service-layer
        - cdl-layer
        - oam-layer
    - Name: pod-group-config-key
      In: path
      Description: Key for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: pod-group-config-value
      In: path
      Description: Value for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Summary: Value for the label
    Description: Value for the label
    Operation ID:
data_tailf_mobile_infra_k8_label_pod_group_config_pod_group_config_pod_group_pod_group_config_key_pod_group_config_value_value_patch

    Parameters:
    - Name: pod-group-config-pod-group
      In: path
      Description: Group for the VMs
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: enumeration
        Default: protocol-layer
        enum:
        - protocol-layer
        - service-layer
        - cdl-layer
        - oam-layer
    - Name: pod-group-config-key
      In: path
      Description: Key for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: pod-group-config-value
      In: path
      Description: Value for the label
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Description: Value for the label
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_value'

      Required/Optional: true
```

```
Responses:
  '204':
    Description: leaf value updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: value
```

/data/tailf-mobile-infra:geo

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_geo_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_geo'
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
```

```
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_geo_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:show

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_show_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_show'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_show_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:clear

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_clear_get

  Parameters:
  - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_clear'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_clear_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/tailf-mobile-infra:dump

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_dump_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_dump'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_dump_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_dump'
```

```
    Required/Optional: true

  Responses:
    '201':
      Description: container dump created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dump
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_dump_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_dump-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container dump created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dump
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_dump_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_dump_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_dump_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_dump_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_dump'
    Required/Optional: true

  Responses:
    '204':
      Description: container dump updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dump
```

/data/tailf-mobile-infra:config-error

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_config_error_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_config-error'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_config_error_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_config-error'
    Required/Optional: true

  Responses:
    '201':
      Description: container config-error created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: config-error
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_config_error_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_config-error-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container config-error created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: config-error
```

```
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_config_error_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_config_error_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_config_error_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_config_error_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
        Reference: '#/components/schemas/data_tailf-mobile-infra_config-error'
    Required/Optional: true

  Responses:
    '204':
      Description: container config-error updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: config-error
```

/data/tailf-mobile-infra:config-error/info

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_config_error_info_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_config-error_info'

  '204':
    Description: No Content
    Content: {}
  '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_config_error_info_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:config-error/info={info-errorComponent}

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_config_error_info_info_errorComponent_get

    Parameters:
    - Name: info-errorComponent
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_config-error_info_info-errorComponent'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_tailf_mobile_infra_config_error_info_info_errorComponent_head

    Parameters:
    - Name: info-errorComponent
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:config-error/info={info-errorComponent}/e rrorComponent

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_config_error_info_info_errorComponent_errorComponent_get

  Parameters:
  - Name: info-errorComponent
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_config-error_info_info-errorComponent_errorComponent'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
```

```
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_config_error_info_info_errorComponent_errorComponent_head

    Parameters:
    - Name: info-errorComponent
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:config-error/info={info-errorComponent}/e rrorDescription

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_config_error_info_info_errorComponent_errorDescription_get

    Parameters:
    - Name: info-errorComponent
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_config-error_info_info-errorComponent_errorDescription'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_config_error_info_info_errorComponent_errorDescription_head

    Parameters:
    - Name: info-errorComponent
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:resource

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resource_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_resource'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_resource_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_resource'
    Required/Optional: true

  Responses:
    '201':
      Description: container resource created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: resource
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_resource_post
  Request Body:
    Content:
      application/yang-data+json:
```

```
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_resource-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container resource created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: resource
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_resource_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_resource_options

    Responses:
      '200':
        Description: OK
        Content: {}
```

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resource_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
```

```
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_resource_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_resource'
    Required/Optional: true

  Responses:
    '204':
      Description: container resource updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: resource
```

/data/tailf-mobile-infra:resource/pod

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resource_pod_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_get

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype'
      '204':
        Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_put

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype'
      Required/Optional: true

    Responses:
      '201':
        Description: list pod created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pod
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_delete

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_options

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
 patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_patch

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype'
    Required/Optional: true

  Responses:
    '204':
      Description: list pod updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pod
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}/podtype

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_podtype_get

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_podtype'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_podtype_put

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_podtype'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf podtype created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: podtype
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_podtype_delete
```

```
  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_podtype_options

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_podtype_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_podtype_patch

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_podtype'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf podtype updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: podtype
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}/cpu

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_get

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_put

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu'
      Required/Optional: true

    Responses:
      '201':
        Description: container cpu created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
    x-codegen-request-body-name: cpu
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_post

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container cpu created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu
  delete:

    Tags:
```

```
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_delete

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_options

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_patch

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu'
      Required/Optional: true

    Responses:
      '204':
        Description: container cpu updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cpu
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}/cpu/request

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_request_get

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_request'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
```

```
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_request_put

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_request'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf request created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: request
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_request_delete

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_request_options

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
```

```
- head
Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_request_head

Parameters:
- Name: pod-podtype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_request_patch

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_request'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf request updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
```

```
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: request
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}/cpu/limit

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_limit_get

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_limit'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
```

```
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_limit_put

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_limit'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf limit created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: limit
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_limit_delete

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_limit_options

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_limit_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_cpu_limit_patch

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_limit'
      Required/Optional: true
```

```
Responses:
  '204':
    Description: leaf limit updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: limit
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}/memory

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_get

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
```

```
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_put

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory'
      Required/Optional: true

    Responses:
      '201':
        Description: container memory created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
```

```
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: memory
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_post

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container memory created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_delete

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_options

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
```

```
  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_patch

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
```

```
          Reference: '#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory'
      Required/Optional: true

    Responses:
      '204':
        Description: container memory updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: memory
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}/memory/request

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_request_get

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
```

```
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_request'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_request_put

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_request'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf request created or replaced
```

```
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: request
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_request_delete


  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_request_options
```

```
  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_request_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_request_patch

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_request'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf request updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: request
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}/memory/limit

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_limit_get

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_limit'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_limit_put

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_limit'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf limit created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: limit
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_limit_delete

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref

    Responses:
      '204':
        Description: No Content
        Content: {}
```

```
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_limit_options

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_limit_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
```

```
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_memory_limit_patch

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_limit'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf limit updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: limit
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}/gomaxproc

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_gomaxproc_get
```

```
Parameters:
- Name: pod-podtype
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: identityref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_gomaxproc'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_gomaxproc_put

    Parameters:
    - Name: pod-podtype
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_gomaxproc'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf gomaxproc created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: gomaxproc
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_gomaxproc_delete

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_gomaxproc_options

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_gomaxproc_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_gomaxproc_patch

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_gomaxproc'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf gomaxproc updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: gomaxproc
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}/labels

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_get

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_put

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels'
      Required/Optional: true

    Responses:
      '201':
        Description: container labels created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: labels
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_post
```

```
    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container labels created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: labels
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_delete

    Parameters:
    - Name: pod-podtype
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_options

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_patch

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels'
      Required/Optional: true

    Responses:
      '204':
        Description: container labels updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: labels
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}/labels/key

```
get:

  Tags:
  - data
  - get
  Summary: Key for the label
  Description: Key for the label
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_key_get

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: Key for the label
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels_key'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Summary: Key for the label
  Description: Key for the label
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_key_put

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Description: Key for the label
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels_key'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf key created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: key
delete:

  Tags:
  - data
  - delete
  Summary: Key for the label
  Description: Key for the label
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_key_delete

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Summary: Key for the label
  Description: Key for the label
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_key_options

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
```

```
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Summary: Key for the label
  Description: Key for the label
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_key_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Summary: Key for the label
  Description: Key for the label
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_key_patch

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  Request Body:
    Description: Key for the label
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

```
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels_key'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf key updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key
```

/data/tailf-mobile-infra:resource/pod={pod-podtype}/labels/value

```
  get:

    Tags:
    - data
    - get
    Summary: Value for the label
    Description: Value for the label
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_value_get

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      '200':
        Description: Value for the label
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels_value'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Summary: Value for the label
    Description: Value for the label
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_value_put

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Description: Value for the label
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels_value'
      Required/Optional: true
```

```
  Responses:
    '201':
      Description: leaf value created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: value
delete:

  Tags:
  - data
  - delete
  Summary: Value for the label
  Description: Value for the label
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_value_delete

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
  Tags:
  - data
  - options
  Summary: Value for the label
  Description: Value for the label
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_value_options

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Summary: Value for the label
  Description: Value for the label
  Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_value_head

  Parameters:
  - Name: pod-podtype
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: identityref
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:
```

```
    Tags:
    - data
    - patch
    Summary: Value for the label
    Description: Value for the label
    Operation ID: data_tailf_mobile_infra_resource_pod_pod_podtype_labels_value_patch

    Parameters:
    - Name: pod-podtype
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: identityref
    Request Body:
      Description: Value for the label
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels_value'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf value updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: value
```

/data/tailf-mobile-infra:geomonitor

```
  get:
```

```
Tags:
- data
- get
Operation ID: data_tailf_mobile_infra_geomonitor_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference: '#/components/schemas/data_tailf-mobile-infra_geomonitor'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_geomonitor_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_geomonitor'
      Required/Optional: true

    Responses:
      '201':
```

```
      Description: container geomonitor created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: geomonitor
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_geomonitor_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_geomonitor-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container geomonitor created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
```

```
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: geomonitor
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_geomonitor_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_geomonitor_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_geomonitor_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_geomonitor_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_geomonitor'
    Required/Optional: true

  Responses:
    '204':
      Description: container geomonitor updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: geomonitor
```

/data/tailf-mobile-infra:geomonitor/podmonitor

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor'

      Required/Optional: true

    Responses:
      '201':
        Description: container podmonitor created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: podmonitor
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container podmonitor created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: podmonitor
delete:

  Tags:
```

```
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor'

    Required/Optional: true
```

```
  Responses:
    '204':
      Description: container podmonitor updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: podmonitor
```

/data/tailf-mobile-infra:geomonitor/podmonitor/pods

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:geomonitor/podmonitor/pods={pods-name}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_get

  Parameters:
```

```
- Name: pods-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_put

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name'
    Required/Optional: true

  Responses:
    '201':
      Description: list pods created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pods
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_delete

  Parameters:
  - Name: pods-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_options

  Parameters:
  - Name: pods-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
```

```
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_head

  Parameters:
  - Name: pods-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_patch

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name'
      Required/Optional: true

    Responses:
      '204':
        Description: list pods updated
```

```
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: pods
```

/data/tailf-mobile-infra:geomonitor/podmonitor/pods={pods-name}/na me

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_name_get

  Parameters:
  - Name: pods-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_name'
      '204':
```

```
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_name_put

  Parameters:
  - Name: pods-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_name'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf name created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
```

```
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_name_delete


  Parameters:
  - Name: pods-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_name_options


  Parameters:
  - Name: pods-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_name_head


  Parameters:
  - Name: pods-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_name_patch


    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_name'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf name updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
```

/data/tailf-mobile-infra:geomonitor/podmonitor/pods={pods-name}/retryCount

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryCount_get

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryCount'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryCount_put

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryCount'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf retryCount created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: retryCount
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryCount_delete

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryCount_options

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryCount_head

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryCount_patch

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryCount'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf retryCount updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: retryCount
```

/data/tailf-mobile-infra:geomonitor/podmonitor/pods={pods-name}/re tryInterval

```
  get:

    Tags:
```

```
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryInterval_get

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        '200':
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryInterval'

        '204':
          Description: No Content
          Content: {}
        '400':
          Description: Bad Request
          Content: {}
        '401':
          Description: Unauthorized
          Content: {}
        '404':
          Description: Not Found
          Content: {}
        '405':
          Description: Method Not Allowed
          Content: {}
        '409':
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    put:

      Tags:
      - data
      - put
      Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryInterval_put
```

```
    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryInterval'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf retryInterval created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: retryInterval
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryInterval_delete

    Parameters:
```

```
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryInterval_options

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryInterval_head

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryInterval_patch

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryInterval'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf retryInterval updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: retryInterval
```

/data/tailf-mobile-infra:geomonitor/podmonitor/pods={pods-name}/re tryFailOverInterval

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryFailOverInterval_get

  Parameters:
  - Name: pods-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryFailOverInterval'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryFailOverInterval_put

  Parameters:
  - Name: pods-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryFailOverInterval'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf retryFailOverInterval created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: retryFailOverInterval
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryFailOverInterval_delete

  Parameters:
  - Name: pods-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryFailOverInterval_options

  Parameters:
  - Name: pods-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
```

```
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryFailOverInterval_head

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_retryFailOverInterval_patch

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryFailOverInterval'

      Required/Optional: true
```

```
    Responses:
      '204':
        Description: leaf retryFailOverInterval updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: retryFailOverInterval
```

/data/tailf-mobile-infra:geomonitor/podmonitor/pods={pods-name}/fa iledReplicaPercent

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_failedReplicaPercent_get

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_failedReplicaPercent'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_failedReplicaPercent_put

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_failedReplicaPercent'

      Required/Optional: true
```

```
    Responses:
      '201':
        Description: leaf failedReplicaPercent created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: failedReplicaPercent
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_failedReplicaPercent_delete

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
```

```
    - options
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_failedReplicaPercent_options

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_failedReplicaPercent_head

    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_geomonitor_podmonitor_pods_pods_name_failedReplicaPercent_patch
```

```
    Parameters:
    - Name: pods-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_failedReplicaPercent'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf failedReplicaPercent updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: failedReplicaPercent
```

/data/tailf-mobile-infra:geomonitor/remoteclustermonitor

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_get

    Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor'
      Required/Optional: true

    Responses:
      '201':
        Description: container remoteclustermonitor created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
```

```
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remoteclustermonitor
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container remoteclustermonitor created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: remoteclustermonitor
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
```

```
    Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor'
      Required/Optional: true

    Responses:
      '204':
        Description: container remoteclustermonitor updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remoteclustermonitor
```

/data/tailf-mobile-infra:geomonitor/remoteclustermonitor/retryCoun t

```
  get:

    Tags:
    - data
    - get
   Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryCount_get


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryCount'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryCount_put

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryCount'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf retryCount created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: retryCount
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryCount_delete


  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryCount_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryCount_head


  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryCount_patch

  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryCount'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf retryCount updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: retryCount
```

/data/tailf-mobile-infra:geomonitor/remoteclustermonitor/retryInte rval

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryInterval_get
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryInterval'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryInterval_put

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryInterval'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf retryInterval created or replaced
```

```
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: retryInterval
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryInterval_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryInterval_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
```

```
    - head
    Operation ID:
data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryInterval_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_geomonitor_remoteclustermonitor_retryInterval_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryInterval'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf retryInterval updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: retryInterval
```

/data/tailf-mobile-infra:geomonitor/vipmonitor

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_geomonitor_vipmonitor_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_geomonitor_vipmonitor_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference: '#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor'

      Required/Optional: true

    Responses:
      '201':
        Description: container vipmonitor created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vipmonitor
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_geomonitor_vipmonitor_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container vipmonitor created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
```

```
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vipmonitor
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_geomonitor_vipmonitor_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_geomonitor_vipmonitor_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_geomonitor_vipmonitor_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_geomonitor_vipmonitor_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor'

    Required/Optional: true

  Responses:
    '204':
      Description: container vipmonitor updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vipmonitor
```

/data/tailf-mobile-infra:geomonitor/vipmonitor/instance

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_geomonitor_vipmonitor_instance_options

  Responses:
```

```
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:geomonitor/vipmonitor/instance={instance-instance-id}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_get

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_put

  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id'
```

```
      Required/Optional: true

    Responses:
      '201':
        Description: list instance created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instance
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_delete

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_options

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_head

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
```

```
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
```

```
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_patch

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id'

      Required/Optional: true

    Responses:
      '204':
        Description: list instance updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instance
```

/data/tailf-mobile-infra:geomonitor/vipmonitor/instance={instance-instance-id}/instance-id

```
  get:

    Tags:
    - data
```

```
    - get
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_instance_id_get


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        '200':
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_instance-id'

        '204':
          Description: No Content
          Content: {}
        '400':
          Description: Bad Request
          Content: {}
        '401':
          Description: Unauthorized
          Content: {}
        '404':
          Description: Not Found
          Content: {}
        '405':
          Description: Method Not Allowed
          Content: {}
        '409':
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    put:

      Tags:
      - data
      - put
      Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_instance_id_put
```

```
    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_instance-id'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf instance-id created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instance-id
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_instance_id_delete
```

```
    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_instance_id_options


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_instance_id_head


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_instance_id_patch


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_instance-id'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf instance-id updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instance-id
```

/data/tailf-mobile-infra:geomonitor/vipmonitor/instance={instance-instance-id}/vips

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_options

  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:geomonitor/vipmonitor/instance={instance-instance-id}/vips={vips-vipInterface}

```
get:

  Tags:
  - data
  - get
  Operation ID:
```

data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_get

```
Parameters:
- Name: instance-instance-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: int32
- Name: vips-vipInterface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_put


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: vips-vipInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface'

      Required/Optional: true

    Responses:
      '201':
        Description: list vips created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vips
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_delete


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: vips-vipInterface
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_options


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: vips-vipInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_head


    Parameters:
```

```
- Name: instance-instance-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: int32
- Name: vips-vipInterface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_patch


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: vips-vipInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface'

      Required/Optional: true

    Responses:
      '204':
        Description: list vips updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vips
```

/data/tailf-mobile-infra:geomonitor/vipmonitor/instance={instance-instance-id}/vips={vips-vipInterface}/vipInterface

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_vipInterface_get


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
```

```
    Format: int32
- Name: vips-vipInterface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_vipInterface'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_vipInterface_put


    Parameters:
    - Name: instance-instance-id
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: vips-vipInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_vipInterface'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf vipInterface created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vipInterface
  delete:

    Tags:
```

```
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_vipInterface_delete


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: vips-vipInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_vipInterface_options


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: vips-vipInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_vipInterface_head


  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32
  - Name: vips-vipInterface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_vipInterface_patch
```

```
Parameters:
- Name: instance-instance-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: int32
- Name: vips-vipInterface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_vipInterface'

  Required/Optional: true

Responses:
  '204':
    Description: leaf vipInterface updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: vipInterface
```

/data/tailf-mobile-infra:geomonitor/vipmonitor/instance={instance-instance-id}/vips={vips-vipInterface}/viplp

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_vipIp_get


  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32
  - Name: vips-vipInterface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_vipIp'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_vipIp_put


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: vips-vipInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_vipIp'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf vipIp created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
```

```
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: vipIp
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_vipIp_delete


  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32
  - Name: vips-vipInterface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_vipIp_options

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: vips-vipInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_vipIp_head

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: vips-vipInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_vipIp_patch


  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32
  - Name: vips-vipInterface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_vipIp'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf vipIp updated
      Content: {}
    '400':
```

```
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: vipIp
```

/data/tailf-mobile-infra:geomonitor/vipmonitor/instance={instance-instance-id}/vips={vips-vipInterface}/vipPort

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_vipPort_get


  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32
  - Name: vips-vipInterface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_vipPort'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_vipPort_put


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: vips-vipInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_vipPort'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf vipPort created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vipPort
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_vipPort_delete


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: integer
      Format: int32
  - Name: vips-vipInterface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_vipPort_options


  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32
  - Name: vips-vipInterface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
```

```
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_vipPort_head


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: vips-vipInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_vipPort_patch


  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32
  - Name: vips-vipInterface
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_vipPort'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf vipPort updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: vipPort
```

/data/tailf-mobile-infra:geomonitor/vipmonitor/instance={instance-instance-id}/vips={vips-vipInterface}/retryCount

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_retryCount_get


    Parameters:
    - Name: instance-instance-id
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: int32
- Name: vips-vipInterface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_retryCount'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
```

```
    - put
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_retryCount_put

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: vips-vipInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_retryCount'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf retryCount created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
```

```
    security:
    - basicAuth: []
    x-codegen-request-body-name: retryCount
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_retryCount_delete


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: vips-vipInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_retryCount_options


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
```

```
  - Name: vips-vipInterface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_retryCount_head


  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32
  - Name: vips-vipInterface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
      - nonconfig
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:
```

```
  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_retryCount_patch

  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32
  - Name: vips-vipInterface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_retryCount'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf retryCount updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: retryCount
```

/data/tailf-mobile-infra:geomonitor/vipmonitor/instance={instance-instance-id}/vips={vips-vipInterface}/retryInterval

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_retryInterval_get


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: vips-vipInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_retryInterval'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
```

```
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_retryInterval_put


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: vips-vipInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_retryInterval'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf retryInterval created or replaced
        Content: {}
```

```
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: retryInterval
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_retryInterval_delete


  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32
  - Name: vips-vipInterface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_retryInterval_options


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: vips-vipInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_retryInterval_head


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: vips-vipInterface
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_retryInterval_patch


  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32
  - Name: vips-vipInterface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_retryInterval'

    Required/Optional: true

  Responses:
    '204':
```

```
      Description: leaf retryInterval updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: retryInterval
?
/data/tailf-mobile-infra:geomonitor/vipmonitor/instance={instance-instance-id}/vips={vips-vipInterface}/retryFailOverInterval
: get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_retryFailOverInterval_get


  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32
  - Name: vips-vipInterface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
```

```
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_retryFailOverInterval'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_retryFailOverInterval_put


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: vips-vipInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_retryFailOverInterval'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf retryFailOverInterval created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: retryFailOverInterval
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_retryFailOverInterval_delete


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
```

```
  - Name: vips-vipInterface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_retryFailOverInterval_options


  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32
  - Name: vips-vipInterface
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
```

data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_retryFailOverInterval_head

```
Parameters:
- Name: instance-instance-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: int32
- Name: vips-vipInterface
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_geomonitor_vipmonitor_instance_instance_instance_id_vips_vips_vipInterface_retryFailOverInterval_patch


    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: vips-vipInterface
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_retryFailOverInterval'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf retryFailOverInterval updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: retryFailOverInterval
```

/data/tailf-mobile-infra:geomonitor/trafficMonitor

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor'
    Required/Optional: true

  Responses:
    '201':
      Description: container trafficMonitor created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: trafficMonitor
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container trafficMonitor created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: trafficMonitor
delete:

  Tags:
```

```
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor'
      Required/Optional: true
```

```
Responses:
  '204':
    Description: container trafficMonitor updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: trafficMonitor
```

/data/tailf-mobile-infra:geomonitor/trafficMonitor/thresholdCount:

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdCount_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdCount'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
```

```
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdCount_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdCount'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf thresholdCount created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
  x-codegen-request-body-name: thresholdCount
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdCount_delete


  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdCount_options


  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdCount_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdCount_patch

    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdCount'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf thresholdCount updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: thresholdCount
```

/data/tailf-mobile-infra:geomonitor/trafficMonitor/thresholdInterv al

```
  get:

    Tags:
    - data
    - get
   Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdInterval_get


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
```

```
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdInterval'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdInterval_put

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdInterval'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf thresholdInterval created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
```

```
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: thresholdInterval
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdInterval_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdInterval_options

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdInterval_head


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
   Operation ID: data_tailf_mobile_infra_geomonitor_trafficMonitor_thresholdInterval_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdInterval'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf thresholdInterval updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: thresholdInterval
```

/data/tailf-mobile-infra:instances

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_tailf_mobile_infra_instances_get

    Parameters:
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference: '#/components/schemas/data_tailf-mobile-infra_instances'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_instances_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_instances'
      Required/Optional: true

    Responses:
      '201':
        Description: container instances created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instances
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_instances_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_instances-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container instances created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instances
```

```
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_instances_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_instances_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_instances_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_instances_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
        Reference: '#/components/schemas/data_tailf-mobile-infra_instances'
    Required/Optional: true

  Responses:
    '204':
      Description: container instances updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instances
```

/data/tailf-mobile-infra:instances/instance

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_instances_instance_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:instances/instance={instance-instance-id}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_instances_instance_instance_instance_id_get
```

```
Parameters:
- Name: instance-instance-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: int32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_instances_instance_instance_instance_id_put

    Parameters:
    - Name: instance-instance-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id'
    Required/Optional: true

  Responses:
    '201':
      Description: list instance created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instance
delete:

  Tags:
  - data
  - delete
 Operation ID: data_tailf_mobile_infra_instances_instance_instance_instance_id_delete


  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_tailf_mobile_infra_instances_instance_instance_instance_id_options


  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32

  Responses:
    '200':
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_instances_instance_instance_instance_id_head

  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_instances_instance_instance_instance_id_patch

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id'
      Required/Optional: true
```

```
  Responses:
    '204':
      Description: list instance updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instance
```

/data/tailf-mobile-infra:instances/instance={instance-instance-id}/instance-id

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_instance_id_get

  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_instance-id'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_instance_id_put

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_instance-id'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf instance-id created or replaced
```

```
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instance-id
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_instance_id_delete

  Parameters:
  - Name: instance-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: int32

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_instance_id_options
```

```
    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_instance_id_head

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_instance_id_patch

    Parameters:
    - Name: instance-instance-id
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_instance-id'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf instance-id updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instance-id
```

/data/tailf-mobile-infra:instances/instance={instance-instance-id}/system-id

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_system_id_get

    Parameters:
    - Name: instance-instance-id
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: int32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_system-id'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_system_id_put

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: integer
        Format: int32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_system-id'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf system-id created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: system-id
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_system_id_delete

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
```

```
        Format: int32

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_system_id_options

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_system_id_head

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_system_id_patch

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_system-id'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf system-id updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: system-id
```

/data/tailf-mobile-infra:instances/instance={instance-instance-id}/cluster-id

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_cluster_id_get

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_cluster-id'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_cluster_id_put

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_cluster-id'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf cluster-id created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cluster-id
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_cluster_id_delete

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_cluster_id_options

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_cluster_id_head

    Parameters:
```

```
- Name: instance-instance-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: int32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_cluster_id_patch

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_cluster-id'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf cluster-id updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cluster-id
```

/data/tailf-mobile-infra:instances/instance={instance-instance-id}/slice-name

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_slice_name_get

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_slice-name'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
```

```
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_slice_name_put

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_slice-name'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf slice-name created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: slice-name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_slice_name_delete

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_slice_name_options

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_slice_name_head

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_instances_instance_instance_instance_id_slice_name_patch

    Parameters:
    - Name: instance-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: int32
    Request Body:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_slice-name'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf slice-name updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: slice-name
```

/data/tailf-mobile-infra:local-instance

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_local_instance_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_local-instance'
  '204':
    Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_local_instance_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_local-instance'
    Required/Optional: true

  Responses:
    '201':
      Description: container local-instance created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: local-instance
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_tailf_mobile_infra_local_instance_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_local-instance-post'

    Required/Optional: true

  Responses:
    '201':
      Description: container local-instance created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: local-instance
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_local_instance_delete

  Responses:
    '204':
      Description: No Content
```

```
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_local_instance_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_local_instance_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_local_instance_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_local-instance'
    Required/Optional: true

  Responses:
    '204':
      Description: container local-instance updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
```

```
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: local-instance
```

/data/tailf-mobile-infra:local-instance/instance

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_local_instance_instance_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_local-instance_instance'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_local_instance_instance_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_local-instance_instance'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf instance created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instance
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_local_instance_instance_delete
```

```
  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_local_instance_instance_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_local_instance_instance_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_local_instance_instance_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_local-instance_instance'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf instance updated
```

```
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: instance
```

/data/tailf-mobile-infra:datastore

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_datastore_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_datastore'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_datastore_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_datastore'
    Required/Optional: true

  Responses:
    '201':
      Description: container datastore created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: datastore
Method: Post

  Tags:
  - data
```

```
  - post
  Operation ID: data_tailf_mobile_infra_datastore_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_datastore-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container datastore created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: datastore
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_datastore_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_datastore_options
```

```
  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_datastore_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_datastore_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_datastore'
      Required/Optional: true

    Responses:
      '204':
        Description: container datastore updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
```

```
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: datastore
```

/data/tailf-mobile-infra:datastore/session-db

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_datastore_session_db_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_datastore_session-db'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_datastore_session_db_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
           Reference: '#/components/schemas/data_tailf-mobile-infra_datastore_session-db'

      Required/Optional: true

    Responses:
      '201':
        Description: container session-db created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: session-db
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_datastore_session_db_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_session-db-post'
      Required/Optional: true

    Responses:
```

```
    '201':
      Description: container session-db created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: session-db
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_datastore_session_db_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_datastore_session_db_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
```

```
- data
- head
Operation ID: data_tailf_mobile_infra_datastore_session_db_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_datastore_session_db_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_datastore_session-db'

    Required/Optional: true

  Responses:
    '204':
      Description: container session-db updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: session-db
```

/data/tailf-mobile-infra:datastore/session-db/endpoints

```
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_datastore_session_db_endpoints_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:datastore/session-db/endpoints={endpoints -host}

```
get:

  Tags:
  - data
  - get
 Operation ID: data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_get


  Parameters:
  - Name: endpoints-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host'

    '204':
      Description: No Content
      Content: {}
```

```
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
 Operation ID: data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_put


  Parameters:
  - Name: endpoints-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host'

      Required/Optional: true

    Responses:
      '201':
        Description: list endpoints created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: endpoints
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_delete

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_options

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_head

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_patch

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host'

      Required/Optional: true

    Responses:
      '204':
        Description: list endpoints updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: endpoints
```

/data/tailf-mobile-infra:datastore/session-db/endpoints={endpoints-host}/host

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_host_get

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_host'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_host_put

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_host'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf host created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
    x-codegen-request-body-name: host
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_host_delete

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_host_options

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_host_head

Parameters:
- **Name**: endpoints-host
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_host_patch

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_host'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf host updated
        Content: {}
      '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: host
```

/data/tailf-mobile-infra:datastore/session-db/endpoints={endpointshost}/port

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_port_get

  Parameters:
  - Name: endpoints-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_port'

    '204':
      Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_port_put

  Parameters:
  - Name: endpoints-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_port'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf port created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
```

```
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: port
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_port_delete

  Parameters:
  - Name: endpoints-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_port_options

  Parameters:
  - Name: endpoints-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_port_head

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_datastore_session_db_endpoints_endpoints_host_port_patch

    Parameters:
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_port'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf port updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: port
```

/data/tailf-mobile-infra:datastore/dbs

```
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_datastore_dbs_options

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/tailf-mobile-infra:datastore/dbs={dbs-name}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_get

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
Tags:
- data
- put
Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_put

Parameters:
- Name: dbs-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: insert
  In: query
  Description: controlling the order when adding new list elements
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: first
    enum:
    - first
    - last
    - before
    - after
- Name: point
  In: query
  Description: used to specify the insertion point
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
      Reference: '#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name'

  Required/Optional: true

Responses:
  '201':
    Description: list dbs created or replaced
    Content: {}
  '204':
    Description: No Content
    Content: {}
```

```
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dbs
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_delete

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_options

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_head

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_patch

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name'

    Required/Optional: true

  Responses:
    '204':
      Description: list dbs updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dbs
```

/data/tailf-mobile-infra:datastore/dbs={dbs-name}/name

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_name_get

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_name'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_name_put

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_name'
    Required/Optional: true
```

```
  Responses:
    '201':
      Description: leaf name created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_name_delete

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
```

```
  - options
  Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_name_options

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_name_head

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_name_patch

    Parameters:
```

```
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_name'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf name updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
```

/data/tailf-mobile-infra:datastore/dbs={dbs-name}/endpoints

```
  options:

    Tags:
    - data
    - options
    Operation ID: data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_options

    Parameters:
    - Name: dbs-name
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/tailf-mobile-infra:datastore/dbs={dbs-name}/endpoints={endpoints-host}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_get

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: endpoints-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
```

```
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_put

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host'

      Required/Optional: true

    Responses:
      '201':
        Description: list endpoints created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: endpoints
```

```
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_delete

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_options

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_head

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_patch
```

```
    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host'

      Required/Optional: true

    Responses:
      '204':
        Description: list endpoints updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: endpoints
```

/data/tailf-mobile-infra:datastore/dbs={dbs-name}/endpoints={endpo ints-host}/host

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_host_get

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_host'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_host_put

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: endpoints-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_host'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf host created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
```

```
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: host
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_host_delete

  Parameters:
  - Name: dbs-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: endpoints-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
```

```
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_host_options

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_host_head

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_host_patch

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_host'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf host updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: host
```

/data/tailf-mobile-infra:datastore/dbs={dbs-name}/endpoints={endpo ints-host}/port

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_port_get

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_port'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_port_put

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_port'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf port created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_port_delete

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_port_options

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_port_head

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: endpoints-host
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_tailf_mobile_infra_datastore_dbs_dbs_name_endpoints_endpoints_host_port_patch

    Parameters:
    - Name: dbs-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_port'
```

```
  Required/Optional: true

Responses:
  '204':
    Description: leaf port updated
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: port
```

/data/tailf-mobile-infra:datastore/notification-ep

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep'
    '204':
      Description: No Content
      Content: {}
    '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep'
    Required/Optional: true

  Responses:
    '201':
      Description: container notification-ep created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
```

```
    security:
    - basicAuth: []
    x-codegen-request-body-name: notification-ep
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_tailf_mobile_infra_datastore_notification_ep_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container notification-ep created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: notification-ep
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_tailf_mobile_infra_datastore_notification_ep_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
```

```
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_datastore_notification_ep_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep'
      Required/Optional: true

    Responses:
      '204':
        Description: container notification-ep updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
```

```
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: notification-ep
```

/data/tailf-mobile-infra:datastore/notification-ep/host

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_host_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep_host'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_host_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep_host'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf host created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: host
delete:

  Tags:
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_host_delete
```

```
  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_host_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_host_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_datastore_notification_ep_host_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep_host'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf host updated
```

```
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: host
```

/data/tailf-mobile-infra:datastore/notification-ep/port

```
get:

  Tags:
  - data
  - get
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_port_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep_port'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
```

```
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_tailf_mobile_infra_datastore_notification_ep_port_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep_port'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf port created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: port
  delete:

    Tags:
```

```
  - data
  - delete
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_port_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_port_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_tailf_mobile_infra_datastore_notification_ep_port_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_tailf_mobile_infra_datastore_notification_ep_port_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep_port'
      Required/Optional: true
```

```
  Responses:
    '204':
      Description: leaf port updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: port
```

Components

```
schemas:
  data:
    Type: object
    Properties:
      ietf-restconf:data:
        Type: object
        Properties: {}
        Description: This resource represents the combined configuration and state
          data resources that can be accessed by a client and cannot be created
          or deleted by the client. See RESTCONF RFC 8040 for further information.
        x-yang:
          Type: datastore
  data-post:
    Type: object
    Properties:
      tailf-mobile-infra:sessions:
        Reference: '#/components/schemas/datapost_tailfmobileinfrasessions'
      tailf-mobile-infra:peers:
        Reference: '#/components/schemas/datapost_tailfmobileinfrapeers'
      tailf-mobile-infra:rpc:
        Reference: '#/components/schemas/datapost_tailfmobileinfrarpc'
      tailf-mobile-infra:resources:
        Reference: '#/components/schemas/datapost_tailfmobileinfraresources'
```

```
tailf-mobile-infra:running-status:
  Reference: '#/components/schemas/datapost_tailfmobileinfrarunningstatus'
tailf-mobile-infra:diagnostics:
  Reference: '#/components/schemas/datapost_tailfmobileinfradiagnostics'
tailf-mobile-infra:infra:
  Reference: '#/components/schemas/datapost_tailfmobileinfrainfra'
tailf-mobile-infra:client:
  Reference: '#/components/schemas/datapost_tailfmobileinfraclient'
tailf-mobile-infra:edr:
  Reference: '#/components/schemas/datapost_tailfmobileinfraedr'
tailf-mobile-infra:instance:
  Reference: '#/components/schemas/datapost_tailfmobileinfrainstance'
tailf-mobile-infra:endpoint:
  Reference: '#/components/schemas/datapost_tailfmobileinfraendpoint'
tailf-mobile-infra:vrf:
  Reference: '#/components/schemas/datapost_tailfmobileinfravrf'
tailf-mobile-infra:vrf-info:
  Reference: '#/components/schemas/datapost_tailfmobileinfravrfinfo'
tailf-mobile-infra:logging:
  Reference: '#/components/schemas/datapost_tailfmobileinfralogging'
tailf-mobile-infra:nodemonitor:
  Reference: '#/components/schemas/datapost_tailfmobileinfranodemonitor'
tailf-mobile-infra:monitor:
  Reference: '#/components/schemas/datapost_tailfmobileinframonitor'
tailf-mobile-infra:router:
  Reference: '#/components/schemas/datapost_tailfmobileinfrarouter'
tailf-mobile-infra:deployment:
  Reference: '#/components/schemas/datapost_tailfmobileinfradeployment'
tailf-mobile-infra:k8:
  Reference: '#/components/schemas/datapost_tailfmobileinfrak8'
tailf-mobile-infra:geo:
  Type: object
  Properties: {}
  Description: (non-presence)
  x-yang:
    Type: container
    is_presence: 'false'
tailf-mobile-infra:show:
  Type: object
  Properties: {}
  Description: (non-presence)
  x-yang:
    Type: container
    is_presence: 'false'
tailf-mobile-infra:clear:
  Type: object
  Properties: {}
  Description: (non-presence)
  x-yang:
    Type: container
    is_presence: 'false'
```

```
    tailf-mobile-infra:dump:
      Type: object
      Properties: {}
      Description: (non-presence)
      x-yang:
        Type: container
        is_presence: 'false'
    tailf-mobile-infra:config-error:
      Reference: '#/components/schemas/datapost_tailfmobileinfraconfigerror'
    tailf-mobile-infra:resource:
      Reference: '#/components/schemas/datapost_tailfmobileinfraresource'
    tailf-mobile-infra:geomonitor:
      Reference: '#/components/schemas/datapost_tailfmobileinfrageomonitor'
    tailf-mobile-infra:instances:
      Reference: '#/components/schemas/datapost_tailfmobileinfrainstances'
    tailf-mobile-infra:local-instance:
      Reference: '#/components/schemas/datapost_tailfmobileinfralocalinstance'
    tailf-mobile-infra:datastore:
      Reference: '#/components/schemas/datapost_tailfmobileinfradatastore'
data-put-patch:
  Type: object
  Properties:
    ietf-restconf:data:
      Reference: '#/components/schemas/dataputpatch_ietfrestconfdata'
data_tailf-mobile-infra_clear:
  Type: object
  Properties:
    tailf-mobile-infra:clear:
      Type: object
      Properties: {}
      Description: (non-presence)
      x-yang:
        Type: container
        is_presence: 'false'
data_tailf-mobile-infra_client:
  Type: object
  Properties:
    tailf-mobile-infra:client:
      Reference: '#/components/schemas/datapost_tailfmobileinfraclient'
data_tailf-mobile-infra_client-post:
  Type: object
  Properties:
    tailf-mobile-infra:http:
      Reference: '#/components/schemas/datapost_tailfmobileinfraclient_http'
    tailf-mobile-infra:outbound:
      Reference: '#/components/schemas/datapost_tailfmobileinfraclient_outbound'
    tailf-mobile-infra:inbound:
      Reference: '#/components/schemas/datapost_tailfmobileinfraclient_inbound'
data_tailf-mobile-infra_client_http:
  Type: object
  Properties:
```

```
    tailf-mobile-infra:http:
      Reference: '#/components/schemas/datapost_tailfmobileinfraclient_http'
data_tailf-mobile-infra_client_http-post:
  Type: object
  Properties:
    tailf-mobile-infra:header:
      Reference: '#/components/schemas/datapost_tailfmobileinfraclient_http_header'
    tailf-mobile-infra:ping:
      Reference: '#/components/schemas/datapost_tailfmobileinfraclient_http_ping'
data_tailf-mobile-infra_client_http_header:
  Type: object
  Properties:
    tailf-mobile-infra:header:
      Reference: '#/components/schemas/datapost_tailfmobileinfraclient_http_header'
data_tailf-mobile-infra_client_http_header-post:
  Type: object
  Properties:
    tailf-mobile-infra:user-agent:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: cluster-name
      enum:
      - cluster-name
      - app-name
      - disable
      x-yang:
        Type: leaf
data_tailf-mobile-infra_client_http_header_user-agent:
  Type: object
  Properties:
    tailf-mobile-infra:user-agent:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: cluster-name
      enum:
      - cluster-name
      - app-name
      - disable
      x-yang:
        Type: leaf
data_tailf-mobile-infra_client_http_ping:
  Type: object
  Properties:
    tailf-mobile-infra:ping:
      Reference: '#/components/schemas/datapost_tailfmobileinfraclient_http_ping'
data_tailf-mobile-infra_client_http_ping-post:
  Type: object
  Properties:
    tailf-mobile-infra:timeout:
      Type: integer
      Description: (leaf)
```

```
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:interval:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_client_http_ping_interval:
    Type: object
    Properties:
      tailf-mobile-infra:interval:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_client_http_ping_timeout:
    Type: object
    Properties:
      tailf-mobile-infra:timeout:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_client_inbound:
    Type: object
    Properties:
      tailf-mobile-infra:inbound:
        Reference: '#/components/schemas/datapost_tailfmobileinfraclient_inbound'
  data_tailf-mobile-infra_client_inbound-post:
    Type: object
    Properties:
      tailf-mobile-infra:interface:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_inbound_interface'
        x-yang:
          Type: list
      tailf-mobile-infra:limit:
        Reference: '#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit'
  data_tailf-mobile-infra_client_inbound_interface_interface-interface:
    Type: object
    Properties:
      tailf-mobile-infra:interface:
        Type: array
        Description: (list)
        Items:
```

```
        Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_inbound_interface'
      x-yang:
        Type: list

data_tailf-mobile-infra_client_inbound_interface_interface-interface_interface:

  Type: object
  Properties:
    tailf-mobile-infra:interface:
      Type: string
      Description: (leaf)
      format: identityref
      x-yang:
        Type: leaf

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit:

  Type: object
  Properties:
    tailf-mobile-infra:limit:
      Reference: '#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit'

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit-post:

  Type: object
  Properties:
    tailf-mobile-infra:pending:
      Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit_pending'
    tailf-mobile-infra:overload:
      Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit_overload'

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload:

  Type: object
  Properties:
    tailf-mobile-infra:overload:
      Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit_overload'

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload-post:

  Type: object
  Properties:
    tailf-mobile-infra:reject-code:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload_reject-code:
```

```
    Type: object
    Properties:
      tailf-mobile-infra:reject-code:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending:

    Type: object
    Properties:
      tailf-mobile-infra:pending:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit_pending'

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending-post:

    Type: object
    Properties:
      tailf-mobile-infra:request:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending_request:

    Type: object
    Properties:
      tailf-mobile-infra:request:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_client_inbound_limit:
    Type: object
    Properties:
      tailf-mobile-infra:limit:
        Reference: '#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit'
  data_tailf-mobile-infra_client_inbound_limit-post:
    Type: object
    Properties:
      tailf-mobile-infra:pending:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit_pending'
      tailf-mobile-infra:overload:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit_overload'
  data_tailf-mobile-infra_client_inbound_limit_overload:
```

```
    Type: object
    Properties:
      tailf-mobile-infra:overload:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit_overload'
  data_tailf-mobile-infra_client_inbound_limit_overload-post:
    Type: object
    Properties:
      tailf-mobile-infra:reject-code:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_client_inbound_limit_overload_reject-code:
    Type: object
    Properties:
      tailf-mobile-infra:reject-code:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_client_inbound_limit_pending:
    Type: object
    Properties:
      tailf-mobile-infra:pending:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit_pending'
  data_tailf-mobile-infra_client_inbound_limit_pending-post:
    Type: object
    Properties:
      tailf-mobile-infra:request:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_client_inbound_limit_pending_request:
    Type: object
    Properties:
      tailf-mobile-infra:request:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_client_outbound:
    Type: object
    Properties:
      tailf-mobile-infra:outbound:
        Reference: '#/components/schemas/datapost_tailfmobileinfraclient_outbound'
```

```
  data_tailf-mobile-infra_client_outbound-post:
    Type: object
    Properties:
      tailf-mobile-infra:interface:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_outbound_interface'
        x-yang:
          Type: list
      tailf-mobile-infra:limit:
       Reference: '#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit'

      tailf-mobile-infra:host:
        Reference: '#/components/schemas/datapost_tailfmobileinfraclient_outbound_host'
  data_tailf-mobile-infra_client_outbound_host:
    Type: object
    Properties:
      tailf-mobile-infra:host:
        Reference: '#/components/schemas/datapost_tailfmobileinfraclient_outbound_host'
  data_tailf-mobile-infra_client_outbound_host-post:
    Type: object
    Properties:
      tailf-mobile-infra:ping:
       Reference: '#/components/schemas/datapost_tailfmobileinfraclient_outbound_host_ping'

  data_tailf-mobile-infra_client_outbound_host_ping:
    Type: object
    Properties:
      tailf-mobile-infra:ping:
       Reference: '#/components/schemas/datapost_tailfmobileinfraclient_outbound_host_ping'

  data_tailf-mobile-infra_client_outbound_host_ping-post:
    Type: object
    Properties:
      tailf-mobile-infra:timeout:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:interval:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:backoff:
        Type: integer
        Description: (leaf)
        format: int32
```

```
      x-yang:
        Type: leaf
    tailf-mobile-infra:retry:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    tailf-mobile-infra:fast-interval:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    tailf-mobile-infra:all-host-down-interval:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_client_outbound_host_ping_all-host-down-interval:
  Type: object
  Properties:
    tailf-mobile-infra:all-host-down-interval:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_client_outbound_host_ping_backoff:
  Type: object
  Properties:
    tailf-mobile-infra:backoff:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_client_outbound_host_ping_fast-interval:
  Type: object
  Properties:
    tailf-mobile-infra:fast-interval:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_client_outbound_host_ping_interval:
  Type: object
  Properties:
    tailf-mobile-infra:interval:
```

```
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
    data_tailf-mobile-infra_client_outbound_host_ping_retry:
      Type: object
      Properties:
        tailf-mobile-infra:retry:
          Type: integer
          Description: (leaf)
          format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_client_outbound_host_ping_timeout:
      Type: object
      Properties:
        tailf-mobile-infra:timeout:
          Type: integer
          Description: (leaf)
          format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_client_outbound_interface_interface-interface:
      Type: object
      Properties:
        tailf-mobile-infra:interface:
          Type: array
          Description: (list)
          Items:
            Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_outbound_interface'
          x-yang:
            Type: list

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host:

      Type: object
      Properties:
        tailf-mobile-infra:host:
          Reference: '#/components/schemas/datapost_tailfmobileinfraclient_outbound_host'

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host-post:

      Type: object
      Properties:
        tailf-mobile-infra:ping:
         Reference: '#/components/schemas/datapost_tailfmobileinfraclient_outbound_host_ping'


data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping:

      Type: object
```

```
    Properties:
      tailf-mobile-infra:ping:
       Reference: '#/components/schemas/datapost_tailfmobileinfraclient_outbound_host_ping'
```

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping-post:

```
    Type: object
    Properties:
      tailf-mobile-infra:timeout:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:interval:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:backoff:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:retry:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:fast-interval:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:all-host-down-interval:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_all-host-down-interval:

```
    Type: object
    Properties:
      tailf-mobile-infra:all-host-down-interval:
        Type: integer
```

```
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_backoff:

    Type: object
    Properties:
      tailf-mobile-infra:backoff:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_fast-interval:

    Type: object
    Properties:
      tailf-mobile-infra:fast-interval:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_interval:

    Type: object
    Properties:
      tailf-mobile-infra:interval:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_retry:

    Type: object
    Properties:
      tailf-mobile-infra:retry:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_timeout:

    Type: object
    Properties:
```

```
      tailf-mobile-infra:timeout:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_client_outbound_interface_interface-interface_interface:

    Type: object
    Properties:
      tailf-mobile-infra:interface:
        Type: string
        Description: (leaf)
        format: identityref
        x-yang:
          Type: leaf

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit:

    Type: object
    Properties:
      tailf-mobile-infra:limit:
        Reference: '#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit'


data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit-post:

    Type: object
    Properties:
      tailf-mobile-infra:pending:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_pending'
      tailf-mobile-infra:consecutive:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_consecutive'

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive:

    Type: object
    Properties:
      tailf-mobile-infra:consecutive:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_consecutive'

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive-post:

    Type: object
    Properties:
      tailf-mobile-infra:failure:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_consecutive_failure'

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure:
```

```
    Type: object
    Properties:
      tailf-mobile-infra:failure:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_consecutive_failure'
```

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure-post:

```
    Type: object
    Properties:
      tailf-mobile-infra:count:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:codes:
        Type: array
        Items:
          Type: string
          Description: (leaf-list)
          format: string
        x-yang:
          Type: leaf-list
```

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_codes_codes-id:

```
    Type: object
    Properties:
      tailf-mobile-infra:codes:
        Type: array
        Items:
          Type: string
          Description: (leaf-list)
          format: string
        x-yang:
          Type: leaf-list
```

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_count:

```
    Type: object
    Properties:
      tailf-mobile-infra:count:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending:

```
    Type: object
    Properties:
```

```
      tailf-mobile-infra:pending:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_pending'

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending-post:

    Type: object
    Properties:
      tailf-mobile-infra:response:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending_response:

    Type: object
    Properties:
      tailf-mobile-infra:response:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_client_outbound_limit:
    Type: object
    Properties:
      tailf-mobile-infra:limit:
        Reference: '#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit'

  data_tailf-mobile-infra_client_outbound_limit-post:
    Type: object
    Properties:
      tailf-mobile-infra:pending:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_pending'
      tailf-mobile-infra:consecutive:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_consecutive'
  data_tailf-mobile-infra_client_outbound_limit_consecutive:
    Type: object
    Properties:
      tailf-mobile-infra:consecutive:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_consecutive'
  data_tailf-mobile-infra_client_outbound_limit_consecutive-post:
    Type: object
    Properties:
      tailf-mobile-infra:failure:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_consecutive_failure'
  data_tailf-mobile-infra_client_outbound_limit_consecutive_failure:
```

```
    Type: object
    Properties:
      tailf-mobile-infra:failure:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_consecutive_failure'
  data_tailf-mobile-infra_client_outbound_limit_consecutive_failure-post:

    Type: object
    Properties:
      tailf-mobile-infra:count:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:codes:
        Type: array
        Items:
          Type: string
          Description: (leaf-list)
          format: string
        x-yang:
          Type: leaf-list

data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_codes_codes-id:

    Type: object
    Properties:
      tailf-mobile-infra:codes:
        Type: array
        Items:
          Type: string
          Description: (leaf-list)
          format: string
        x-yang:
          Type: leaf-list
  data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_count:

    Type: object
    Properties:
      tailf-mobile-infra:count:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_client_outbound_limit_pending:
    Type: object
    Properties:
      tailf-mobile-infra:pending:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_pending'
  data_tailf-mobile-infra_client_outbound_limit_pending-post:
```

```
  Type: object
  Properties:
    tailf-mobile-infra:response:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_client_outbound_limit_pending_response:
  Type: object
  Properties:
    tailf-mobile-infra:response:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_config-error:
  Type: object
  Properties:
    tailf-mobile-infra:config-error:
      Reference: '#/components/schemas/datapost_tailfmobileinfraconfigerror'
data_tailf-mobile-infra_config-error-post:
  Type: object
  Properties:
    tailf-mobile-infra:info:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfraconfigerror_info'
      x-yang:
        Type: list
data_tailf-mobile-infra_config-error_info:
  Type: object
  Properties:
    tailf-mobile-infra:info:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfraconfigerror_info'
      x-yang:
        Type: list
data_tailf-mobile-infra_config-error_info_info-errorComponent:
  Type: object
  Properties:
    tailf-mobile-infra:info:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfraconfigerror_info'
      x-yang:
```

```
        Type: list

data_tailf-mobile-infra_config-error_info_info-errorComponent_errorComponent:

    Type: object
    Properties:
      tailf-mobile-infra:errorComponent:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_config-error_info_info-errorComponent_errorDescription:

    Type: object
    Properties:
      tailf-mobile-infra:errorDescription:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_datastore:
    Type: object
    Properties:
      tailf-mobile-infra:datastore:
        Reference: '#/components/schemas/datapost_tailfmobileinfradatastore'
  data_tailf-mobile-infra_datastore-post:
    Type: object
    Properties:
      tailf-mobile-infra:session-db:
        Reference: '#/components/schemas/datapost_tailfmobileinfradatastore_sessiondb'
      tailf-mobile-infra:dbs:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfradatastore_dbs'
        x-yang:
          Type: list
      tailf-mobile-infra:notification-ep:
       Reference: '#/components/schemas/datapost_tailfmobileinfradatastore_notificationep'

  data_tailf-mobile-infra_datastore_dbs_dbs-name:
    Type: object
    Properties:
      tailf-mobile-infra:dbs:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfradatastore_dbs'
        x-yang:
```

```
        Type: list
  data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host:
    Type: object
    Properties:
      tailf-mobile-infra:endpoints:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfradatastore_sessiondb_endpoints'
        x-yang:
          Type: list

data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_host:
    Type: object
    Properties:
      tailf-mobile-infra:host:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_port:
    Type: object
    Properties:
      tailf-mobile-infra:port:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_datastore_dbs_dbs-name_name:
    Type: object
    Properties:
      tailf-mobile-infra:name:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_datastore_notification-ep:
    Type: object
    Properties:
      tailf-mobile-infra:notification-ep:
       Reference: '#/components/schemas/datapost_tailfmobileinfradatastore_notificationep'

  data_tailf-mobile-infra_datastore_notification-ep-post:
    Type: object
    Properties:
```

```
      tailf-mobile-infra:host:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
      tailf-mobile-infra:port:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_datastore_notification-ep_host:
    Type: object
    Properties:
      tailf-mobile-infra:host:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_datastore_notification-ep_port:
    Type: object
    Properties:
      tailf-mobile-infra:port:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_datastore_session-db:
    Type: object
    Properties:
      tailf-mobile-infra:session-db:
        Reference: '#/components/schemas/datapost_tailfmobileinfradatastore_sessiondb'
  data_tailf-mobile-infra_datastore_session-db-post:
    Type: object
    Properties:
      tailf-mobile-infra:endpoints:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfradatastore_sessiondb_endpoints'
        x-yang:
          Type: list
  data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host:
    Type: object
    Properties:
      tailf-mobile-infra:endpoints:
        Type: array
        Description: (list)
```

```
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfradatastore_sessiondb_endpoints'
        x-yang:
          Type: list

data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_host:

    Type: object
    Properties:
      tailf-mobile-infra:host:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_port:

    Type: object
    Properties:
      tailf-mobile-infra:port:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_deployment:
    Type: object
    Properties:
      tailf-mobile-infra:deployment:
        Reference: '#/components/schemas/datapost_tailfmobileinfradeployment'
  data_tailf-mobile-infra_deployment-post:
    Type: object
    Properties:
      tailf-mobile-infra:app-name:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
      tailf-mobile-infra:cluster-name:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
      tailf-mobile-infra:dc-name:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
```

```
        Type: leaf
      tailf-mobile-infra:model:
        Type: string
        Description: Deployment Model default large (leaf)
        format: enumeration
        Default: small
        enum:
        - small
        x-yang:
          Type: leaf
      tailf-mobile-infra:resource:
        Reference: '#/components/schemas/datapost_tailfmobileinfradeployment_resource'
      tailf-mobile-infra:logical-nf-instance-id:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_deployment_app-name:
    Type: object
    Properties:
      tailf-mobile-infra:app-name:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_deployment_cluster-name:
    Type: object
    Properties:
      tailf-mobile-infra:cluster-name:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_deployment_dc-name:
    Type: object
    Properties:
      tailf-mobile-infra:dc-name:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_deployment_logical-nf-instance-id:
    Type: object
    Properties:
      tailf-mobile-infra:logical-nf-instance-id:
        Type: integer
        Description: (leaf)
        format: int32
```

```
      x-yang:
        Type: leaf
data_tailf-mobile-infra_deployment_model:
  Type: object
  Properties:
    tailf-mobile-infra:model:
      Type: string
      Description: Deployment Model default large (leaf)
      format: enumeration
      Default: small
      enum:
      - small
      x-yang:
        Type: leaf
data_tailf-mobile-infra_deployment_resource:
  Type: object
  Properties:
    tailf-mobile-infra:resource:
      Reference: '#/components/schemas/datapost_tailfmobileinfradeployment_resource'
data_tailf-mobile-infra_deployment_resource-post:
  Type: object
  Properties:
    tailf-mobile-infra:cpu:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_deployment_resource_cpu:
  Type: object
  Properties:
    tailf-mobile-infra:cpu:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_diagnostics:
  Type: object
  Properties:
    tailf-mobile-infra:diagnostics:
      Reference: '#/components/schemas/datapost_tailfmobileinfradiagnostics'
data_tailf-mobile-infra_diagnostics-post:
  Type: object
  Properties:
    tailf-mobile-infra:info:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfradiagnostics_info'
      x-yang:
        Type: list
```

```
 data_tailf-mobile-infra_diagnostics_info:
   Type: object
   Properties:
     tailf-mobile-infra:info:
       Type: array
       Description: (list)
       Items:
         Reference: '#/components/schemas/datapost_tailfmobileinfradiagnostics_info'
       x-yang:
         Type: list
 data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic:

   Type: object
   Properties:
     tailf-mobile-infra:info:
       Type: array
       Description: (list)
       Items:
         Reference: '#/components/schemas/datapost_tailfmobileinfradiagnostics_info'
       x-yang:
         Type: list

data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_component:

   Type: object
   Properties:
     tailf-mobile-infra:component:
       Type: string
       Description: (leaf)
       format: string
       x-yang:
         Type: leaf

data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_diagnostic:

   Type: object
   Properties:
     tailf-mobile-infra:diagnostic:
       Type: string
       Description: (leaf)
       format: string
       x-yang:
         Type: leaf

data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_podInstance:

   Type: object
   Properties:
     tailf-mobile-infra:podInstance:
       Type: string
       Description: (leaf)
       format: string
       x-yang:
```

```
        Type: leaf
data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_retries:
  Type: object
  Properties:
    tailf-mobile-infra:retries:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_startTime:
  Type: object
  Properties:
    tailf-mobile-infra:startTime:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_diagnostics_info_info-podInstance_info-diagnostic_status:
  Type: object
  Properties:
    tailf-mobile-infra:status:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_dump:
  Type: object
  Properties:
    tailf-mobile-infra:dump:
      Type: object
      Properties: {}
      Description: (non-presence)
      x-yang:
        Type: container
        is_presence: 'false'
data_tailf-mobile-infra_dump-post:
  Type: object
data_tailf-mobile-infra_edr:
  Type: object
  Properties:
    tailf-mobile-infra:edr:
      Reference: '#/components/schemas/datapost_tailfmobileinfraedr'
data_tailf-mobile-infra_edr-post:
  Type: object
```

```
  Properties:
    tailf-mobile-infra:reporting:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
    tailf-mobile-infra:edrsubscribers:
      Reference: '#/components/schemas/datapost_tailfmobileinfraedr_edrsubscribers'
    tailf-mobile-infra:all:
      Reference: '#/components/schemas/datapost_tailfmobileinfraedr_all'
    tailf-mobile-infra:file:
      Reference: '#/components/schemas/datapost_tailfmobileinfraedr_file'
data_tailf-mobile-infra_edr_all:
  Type: object
  Properties:
    tailf-mobile-infra:all:
      Reference: '#/components/schemas/datapost_tailfmobileinfraedr_all'
data_tailf-mobile-infra_edr_all-post:
  Type: object
  Properties:
    tailf-mobile-infra:subscribers:
      Type: string
      Description: (leaf)
      format: '[null]'
      x-yang:
        Type: leaf
data_tailf-mobile-infra_edr_all_subscribers:
  Type: object
  Properties:
    tailf-mobile-infra:subscribers:
      Type: string
      Description: (leaf)
      format: '[null]'
      x-yang:
        Type: leaf
data_tailf-mobile-infra_edr_edrsubscribers:
  Type: object
  Properties:
    tailf-mobile-infra:edrsubscribers:
      Reference: '#/components/schemas/datapost_tailfmobileinfraedr_edrsubscribers'
data_tailf-mobile-infra_edr_edrsubscribers-post:
  Type: object
  Properties:
    tailf-mobile-infra:subscribers:
      Type: array
      Items:
        Type: string
```

```
      Description: (leaf-list)
      format: string
    x-yang:
      Type: leaf-list
data_tailf-mobile-infra_edr_edrsubscribers_subscribers_subscribers-id:
  Type: object
  Properties:
    tailf-mobile-infra:subscribers:
      Type: array
      Items:
        Type: string
        Description: (leaf-list)
        format: string
      x-yang:
        Type: leaf-list
data_tailf-mobile-infra_edr_file:
  Type: object
  Properties:
    tailf-mobile-infra:file:
      Reference: '#/components/schemas/datapost_tailfmobileinfraedr_file'
data_tailf-mobile-infra_edr_file-post:
  Type: object
  Properties:
    tailf-mobile-infra:files:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfraedr_file_files'
      x-yang:
        Type: list
data_tailf-mobile-infra_edr_file_files_files-name:
  Type: object
  Properties:
    tailf-mobile-infra:files:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfraedr_file_files'
      x-yang:
        Type: list
data_tailf-mobile-infra_edr_file_files_files-name_flush:
  Type: object
  Properties:
    tailf-mobile-infra:flush:
      Reference: '#/components/schemas/datapost_tailfmobileinfraedr_file_flush'
data_tailf-mobile-infra_edr_file_files_files-name_flush-post:
  Type: object
  Properties:
    tailf-mobile-infra:interval:
      Type: integer
      Description: (leaf)
```

```
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_edr_file_files_files-name_flush_interval:
  Type: object
  Properties:
    tailf-mobile-infra:interval:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_edr_file_files_files-name_limit:
  Type: object
  Properties:
    tailf-mobile-infra:limit:
      Reference: '#/components/schemas/datapost_tailfmobileinfraedr_file_limit'
data_tailf-mobile-infra_edr_file_files_files-name_limit-post:
  Type: object
  Properties:
    tailf-mobile-infra:size:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    tailf-mobile-infra:count:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    tailf-mobile-infra:storage:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_edr_file_files_files-name_limit_count:
  Type: object
  Properties:
    tailf-mobile-infra:count:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_edr_file_files_files-name_limit_size:
  Type: object
  Properties:
    tailf-mobile-infra:size:
```

```
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
  data_tailf-mobile-infra_edr_file_files_files-name_limit_storage:
    Type: object
    Properties:
      tailf-mobile-infra:storage:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_edr_file_files_files-name_name:
    Type: object
    Properties:
      tailf-mobile-infra:name:
        Type: string
        Description: (leaf)
        format: identityref
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_edr_file_files_files-name_procedure:
    Type: object
    Properties:
      tailf-mobile-infra:procedure:
        Reference: '#/components/schemas/datapost_tailfmobileinfraedr_file_procedure'
  data_tailf-mobile-infra_edr_file_files_files-name_procedure-post:
    Type: object
    Properties:
      tailf-mobile-infra:enable-event-id:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfraedr_file_procedure_enableeventid'
        x-yang:
          Type: list

data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure:

    Type: object
    Properties:
      tailf-mobile-infra:enable-event-id:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfraedr_file_procedure_enableeventid'
        x-yang:
          Type: list
```

data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner:

```
    Type: object
    Properties:
      tailf-mobile-infra:enable-inner:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraedr_file_procedure_enableinner'
```

data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner-post:

```
    Type: object
    Properties:
      tailf-mobile-infra:event:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraedr_file_procedure_enableinner_event'
```

data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event:

```
    Type: object
    Properties:
      tailf-mobile-infra:event:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraedr_file_procedure_enableinner_event'
  ?
data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event-post

  : type: object
    Properties:
      tailf-mobile-infra:enable-field-id:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfraedr_file_procedure_enableinner_event_enablefieldid'

        x-yang:
          Type: list
  ?
data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event

  : type: object
    Properties:
      tailf-mobile-infra:enable-field-id:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfraedr_file_procedure_enableinner_event_enablefieldid'

        x-yang:
          Type: list
  ?
data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event_enable

  : type: object
```

```
    Properties:
      tailf-mobile-infra:enable:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraedr_file_procedure_enableinner_event_enable'

  ?
data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event_enable-post

  : type: object
    Properties:
      tailf-mobile-infra:field:
        Type: array
        Items:
          Type: string
          Description: (leaf-list)
          format: string
        x-yang:
          Type: leaf-list
  ?
data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event_enable_field_field-id

  : type: object
    Properties:
      tailf-mobile-infra:field:
        Type: array
        Items:
          Type: string
          Description: (leaf-list)
          format: string
        x-yang:
          Type: leaf-list
  ?
data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event_event

  : type: object
    Properties:
      tailf-mobile-infra:event:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_procedure:

```
    Type: object
    Properties:
      tailf-mobile-infra:procedure:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_edr_file_files_files-name_rate:

```
    Type: object
    Properties:
      tailf-mobile-infra:rate:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_edr_file_files_files-name_reporting:
    Type: object
    Properties:
      tailf-mobile-infra:reporting:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: enable
        enum:
        - enable
        - disable
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_edr_file_files_files-name_threshold:
    Type: object
    Properties:
      tailf-mobile-infra:threshold:
        Reference: '#/components/schemas/datapost_tailfmobileinfraedr_file_threshold'
  data_tailf-mobile-infra_edr_file_files_files-name_threshold-post:
    Type: object
    Properties:
      tailf-mobile-infra:cpu:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:session:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_edr_file_files_files-name_threshold_cpu:
    Type: object
    Properties:
      tailf-mobile-infra:cpu:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_edr_file_files_files-name_threshold_session:
    Type: object
```

```
  Properties:
    tailf-mobile-infra:session:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_edr_file_files_files-name_verbose:
  Type: object
  Properties:
    tailf-mobile-infra:verbose:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
data_tailf-mobile-infra_edr_reporting:
  Type: object
  Properties:
    tailf-mobile-infra:reporting:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
data_tailf-mobile-infra_endpoint:
  Type: object
  Properties:
    tailf-mobile-infra:endpoint:
      Reference: '#/components/schemas/datapost_tailfmobileinfraendpoint'
data_tailf-mobile-infra_endpoint-post:
  Type: object
  Properties:
    tailf-mobile-infra:info:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfraendpoint_info'
      x-yang:
        Type: list
    tailf-mobile-infra:all:
      Type: array
      Description: (list)
      Items:
```

```
        Reference: '#/components/schemas/datapost_tailfmobileinfraendpoint_info'
      x-yang:
        Type: list
  data_tailf-mobile-infra_endpoint_all:
    Type: object
    Properties:
      tailf-mobile-infra:all:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfraendpoint_info'
        x-yang:
          Type: list

data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address:

    Type: object
    Properties:
      tailf-mobile-infra:all:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfraendpoint_info'
        x-yang:
          Type: list

data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_Interface:

    Type: object
    Properties:
      tailf-mobile-infra:Interface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_address:

    Type: object
    Properties:
      tailf-mobile-infra:address:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_endpoint:

    Type: object
    Properties:
      tailf-mobile-infra:endpoint:
```

```
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_grInstance:

    Type: object
    Properties:
      tailf-mobile-infra:grInstance:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_internal:

    Type: object
    Properties:
      tailf-mobile-infra:internal:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_startTime:

    Type: object
    Properties:
      tailf-mobile-infra:startTime:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_status:

    Type: object
    Properties:
      tailf-mobile-infra:status:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_stoppedTime:

    Type: object
```

```
    Properties:
      tailf-mobile-infra:stoppedTime:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_type:

    Type: object
    Properties:
      tailf-mobile-infra:type:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_endpoint_all_all-grInstance_all-endpoint_all-address_vrf:

    Type: object
    Properties:
      tailf-mobile-infra:vrf:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_endpoint_info:
    Type: object
    Properties:
      tailf-mobile-infra:info:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfraendpoint_info'
        x-yang:
          Type: list

data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address:

    Type: object
    Properties:
      tailf-mobile-infra:info:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfraendpoint_info'
        x-yang:
          Type: list

data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_Interface:
```

```
    Type: object
    Properties:
      tailf-mobile-infra:Interface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_address:

    Type: object
    Properties:
      tailf-mobile-infra:address:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_endpoint:

    Type: object
    Properties:
      tailf-mobile-infra:endpoint:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_grInstance:

    Type: object
    Properties:
      tailf-mobile-infra:grInstance:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_internal:

    Type: object
    Properties:
      tailf-mobile-infra:internal:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_startTime:

```
Type: object
Properties:
  tailf-mobile-infra:startTime:
    Type: string
    Description: (leaf)
    format: string
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_status:

```
Type: object
Properties:
  tailf-mobile-infra:status:
    Type: string
    Description: (leaf)
    format: string
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_stoppedTime:

```
Type: object
Properties:
  tailf-mobile-infra:stoppedTime:
    Type: string
    Description: (leaf)
    format: string
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_type:

```
Type: object
Properties:
  tailf-mobile-infra:type:
    Type: string
    Description: (leaf)
    format: string
    x-yang:
      Type: leaf
```

data_tailf-mobile-infra_endpoint_info_info-grInstance_info-endpoint_info-address_vrf:

```
Type: object
Properties:
  tailf-mobile-infra:vrf:
    Type: string
    Description: (leaf)
    format: string
```

```
      x-yang:
        Type: leaf
  data_tailf-mobile-infra_geo:
    Type: object
    Properties:
      tailf-mobile-infra:geo:
        Type: object
        Properties: {}
        Description: (non-presence)
        x-yang:
          Type: container
          is_presence: 'false'
  data_tailf-mobile-infra_geomonitor:
    Type: object
    Properties:
      tailf-mobile-infra:geomonitor:
        Reference: '#/components/schemas/datapost_tailfmobileinfrageomonitor'
  data_tailf-mobile-infra_geomonitor-post:
    Type: object
    Properties:
      tailf-mobile-infra:podmonitor:
        Reference: '#/components/schemas/datapost_tailfmobileinfrageomonitor_podmonitor'

      tailf-mobile-infra:remoteclustermonitor:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrageomonitor_remoteclustermonitor'
      tailf-mobile-infra:vipmonitor:
        Reference: '#/components/schemas/datapost_tailfmobileinfrageomonitor_vipmonitor'

      tailf-mobile-infra:trafficMonitor:
       Reference: '#/components/schemas/datapost_tailfmobileinfrageomonitor_trafficMonitor'

  data_tailf-mobile-infra_geomonitor_podmonitor:
    Type: object
    Properties:
      tailf-mobile-infra:podmonitor:
        Reference: '#/components/schemas/datapost_tailfmobileinfrageomonitor_podmonitor'

  data_tailf-mobile-infra_geomonitor_podmonitor-post:
    Type: object
    Properties:
      tailf-mobile-infra:pods:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrageomonitor_podmonitor_pods'
        x-yang:
          Type: list
  data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name:
    Type: object
    Properties:
      tailf-mobile-infra:pods:
```

```
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrageomonitor_podmonitor_pods'
        x-yang:
          Type: list

data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_failedReplicaPercent:

    Type: object
    Properties:
      tailf-mobile-infra:failedReplicaPercent:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_name:
    Type: object
    Properties:
      tailf-mobile-infra:name:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryCount:

    Type: object
    Properties:
      tailf-mobile-infra:retryCount:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryFailOverInterval:

    Type: object
    Properties:
      tailf-mobile-infra:retryFailOverInterval:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryInterval:

    Type: object
    Properties:
```

```
      tailf-mobile-infra:retryInterval:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_geomonitor_remoteclustermonitor:
    Type: object
    Properties:
      tailf-mobile-infra:remoteclustermonitor:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrageomonitor_remoteclustermonitor'
  data_tailf-mobile-infra_geomonitor_remoteclustermonitor-post:
    Type: object
    Properties:
      tailf-mobile-infra:retryCount:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:retryInterval:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryCount:
    Type: object
    Properties:
      tailf-mobile-infra:retryCount:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryInterval:
    Type: object
    Properties:
      tailf-mobile-infra:retryInterval:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_geomonitor_trafficMonitor:
    Type: object
    Properties:
      tailf-mobile-infra:trafficMonitor:
       Reference: '#/components/schemas/datapost_tailfmobileinfrageomonitor_trafficMonitor'

  data_tailf-mobile-infra_geomonitor_trafficMonitor-post:
```

```
      Type: object
      Properties:
        tailf-mobile-infra:thresholdCount:
          Type: integer
          Description: (leaf)
          format: int32
          x-yang:
            Type: leaf
        tailf-mobile-infra:thresholdInterval:
          Type: integer
          Description: (leaf)
          format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdCount:
      Type: object
      Properties:
        tailf-mobile-infra:thresholdCount:
          Type: integer
          Description: (leaf)
          format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdInterval:
      Type: object
      Properties:
        tailf-mobile-infra:thresholdInterval:
          Type: integer
          Description: (leaf)
          format: int32
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_geomonitor_vipmonitor:
      Type: object
      Properties:
        tailf-mobile-infra:vipmonitor:
          Reference: '#/components/schemas/datapost_tailfmobileinfrageomonitor_vipmonitor'

    data_tailf-mobile-infra_geomonitor_vipmonitor-post:
      Type: object
      Properties:
        tailf-mobile-infra:instance:
          Type: array
          Description: (list)
          Items:
            Reference:
  '#/components/schemas/datapost_tailfmobileinfrageomonitor_vipmonitor_instance'
          x-yang:
            Type: list

  data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id:
```

```
    Type: object
    Properties:
      tailf-mobile-infra:instance:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrageomonitor_vipmonitor_instance'
        x-yang:
          Type: list
```

data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_instance-id:

```
    Type: object
    Properties:
      tailf-mobile-infra:instance-id:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface:

```
    Type: object
    Properties:
      tailf-mobile-infra:vips:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrageomonitor_vipmonitor_vips'
        x-yang:
          Type: list
```

data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_retryCount:

```
    Type: object
    Properties:
      tailf-mobile-infra:retryCount:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_retryFailOverInterval:

```
    Type: object
    Properties:
      tailf-mobile-infra:retryFailOverInterval:
        Type: integer
        Description: (leaf)
```

```
        format: int32
        x-yang:
          Type: leaf
data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_retryInterval:
    Type: object
    Properties:
      tailf-mobile-infra:retryInterval:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_vipInterface:
    Type: object
    Properties:
      tailf-mobile-infra:vipInterface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_vipIp:
    Type: object
    Properties:
      tailf-mobile-infra:vipIp:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_vipPort:
    Type: object
    Properties:
      tailf-mobile-infra:vipPort:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_infra:
    Type: object
    Properties:
      tailf-mobile-infra:infra:
        Reference: '#/components/schemas/datapost_tailfmobileinfrainfra'
  data_tailf-mobile-infra_infra-post:
```

```
    Type: object
    Properties:
      tailf-mobile-infra:metrics:
        Reference: '#/components/schemas/datapost_tailfmobileinfrainfra_metrics'
      tailf-mobile-infra:transaction:
        Reference: '#/components/schemas/datapost_tailfmobileinfrainfra_transaction'
  data_tailf-mobile-infra_infra_metrics:
    Type: object
    Properties:
      tailf-mobile-infra:metrics:
        Reference: '#/components/schemas/datapost_tailfmobileinfrainfra_metrics'
  data_tailf-mobile-infra_infra_metrics-post:
    Type: object
    Properties:
      tailf-mobile-infra:experimental:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_metrics_experimental'
      tailf-mobile-infra:verbose:
        Reference: '#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose'

  data_tailf-mobile-infra_infra_metrics_experimental:
    Type: object
    Properties:
      tailf-mobile-infra:experimental:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_metrics_experimental'
  data_tailf-mobile-infra_infra_metrics_experimental-post:
    Type: object
    Properties:
      tailf-mobile-infra:version:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_infra_metrics_experimental_version:
    Type: object
    Properties:
      tailf-mobile-infra:version:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_infra_metrics_verbose:
    Type: object
    Properties:
      tailf-mobile-infra:verbose:
        Reference: '#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose'

  data_tailf-mobile-infra_infra_metrics_verbose-post:
    Type: object
```

```
    Properties:
      tailf-mobile-infra:verboseLevels:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_verboseLevels'
        x-yang:
          Type: list

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType:

    Type: object
    Properties:
      tailf-mobile-infra:verboseLevels:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_verboseLevels'
        x-yang:
          Type: list

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_level:

    Type: object
    Properties:
      tailf-mobile-infra:level:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: production
        enum:
        - production
        - debug
        - trace
        - 'off'
        x-yang:
          Type: leaf

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics:

    Type: object
    Properties:
      tailf-mobile-infra:metrics:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_metrics'

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics-post:

    Type: object
    Properties:
      tailf-mobile-infra:metricsList:
        Type: array
```

```
      Description: (list)
      Items:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_metrics_metricsList'
      x-yang:
        Type: list
```

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name:

```
  Type: object
  Properties:
    tailf-mobile-infra:metricsList:
      Type: array
      Description: (list)
      Items:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_metrics_metricsList'
      x-yang:
        Type: list
?
data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_granular-labels_granular-labels-id

: type: object
  Properties:
    tailf-mobile-infra:granular-labels:
      Type: array
      Items:
        Type: string
        Description: (leaf-list)
        format: string
      x-yang:
        Type: leaf-list
?
data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_level

: type: object
  Properties:
    tailf-mobile-infra:level:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: production
      enum:
      - production
      - debug
      - trace
      - 'off'
      x-yang:
        Type: leaf
?
data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_name

: type: object
  Properties:
    tailf-mobile-infra:name:
```

```
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_podType:

    Type: object
    Properties:
      tailf-mobile-infra:podType:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: protocol
        enum:
        - protocol
        - load-balancer
        - service
        - application
        x-yang:
          Type: leaf

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods:

    Type: object
    Properties:
      tailf-mobile-infra:pods:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_pods'

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods-post:

    Type: object
    Properties:
      tailf-mobile-infra:pod-names:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_pods_podnames'
        x-yang:
          Type: list

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name:

    Type: object
    Properties:
      tailf-mobile-infra:pod-names:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_pods_podnames'
```

```
      x-yang:
        Type: list

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_level:
    Type: object
    Properties:
      tailf-mobile-infra:level:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: production
        enum:
        - production
        - debug
        - trace
        - 'off'
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_pod-name

  : type: object
    Properties:
      tailf-mobile-infra:pod-name:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_infra_transaction:
    Type: object
    Properties:
      tailf-mobile-infra:transaction:
        Reference: '#/components/schemas/datapost_tailfmobileinfrainfra_transaction'
  data_tailf-mobile-infra_infra_transaction-post:
    Type: object
    Properties:
      tailf-mobile-infra:limit:
       Reference: '#/components/schemas/datapost_tailfmobileinfrainfra_transaction_limit'

      tailf-mobile-infra:loop:
       Reference: '#/components/schemas/datapost_tailfmobileinfrainfra_transaction_loop'

  data_tailf-mobile-infra_infra_transaction_limit:
    Type: object
    Properties:
      tailf-mobile-infra:limit:
       Reference: '#/components/schemas/datapost_tailfmobileinfrainfra_transaction_limit'

  data_tailf-mobile-infra_infra_transaction_limit-post:
    Type: object
    Properties:
      tailf-mobile-infra:stage:
```

```
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
      tailf-mobile-infra:consecutive:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_transaction_limit_consecutive'
  data_tailf-mobile-infra_infra_transaction_limit_consecutive:
    Type: object
    Properties:
      tailf-mobile-infra:consecutive:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_transaction_limit_consecutive'
  data_tailf-mobile-infra_infra_transaction_limit_consecutive-post:
    Type: object
    Properties:
      tailf-mobile-infra:same:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_transaction_limit_consecutive_same'
  data_tailf-mobile-infra_infra_transaction_limit_consecutive_same:
    Type: object
    Properties:
      tailf-mobile-infra:same:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_transaction_limit_consecutive_same'
  data_tailf-mobile-infra_infra_transaction_limit_consecutive_same-post:
    Type: object
    Properties:
      tailf-mobile-infra:stage:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_infra_transaction_limit_consecutive_same_stage:

    Type: object
    Properties:
      tailf-mobile-infra:stage:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_infra_transaction_limit_stage:
    Type: object
    Properties:
      tailf-mobile-infra:stage:
        Type: integer
        Description: (leaf)
        format: uint32
```

```
      x-yang:
        Type: leaf
  data_tailf-mobile-infra_infra_transaction_loop:
    Type: object
    Properties:
      tailf-mobile-infra:loop:
       Reference: '#/components/schemas/datapost_tailfmobileinfrainfra_transaction_loop'

  data_tailf-mobile-infra_infra_transaction_loop-post:
    Type: object
    Properties:
      tailf-mobile-infra:detection:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: enable
        enum:
        - enable
        - disable
        x-yang:
          Type: leaf
      tailf-mobile-infra:category:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_transaction_loop_category'
        x-yang:
          Type: list
  data_tailf-mobile-infra_infra_transaction_loop_category_category-name:
    Type: object
    Properties:
      tailf-mobile-infra:category:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_transaction_loop_category'
        x-yang:
          Type: list

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_name:

    Type: object
    Properties:
      tailf-mobile-infra:name:
        Type: string
        Description: (leaf)
        format: identityref
        x-yang:
          Type: leaf

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold:
```

```
    Type: object
    Properties:
      tailf-mobile-infra:threshold:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_transaction_loop_threshold'
```

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold-post:

```
    Type: object
    Properties:
      tailf-mobile-infra:interval:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
      tailf-mobile-infra:thresholds:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_transaction_loop_threshold_thresholds'

        x-yang:
          Type: list
```

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_interval:

```
    Type: object
    Properties:
      tailf-mobile-infra:interval:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name:

```
    Type: object
    Properties:
      tailf-mobile-infra:thresholds:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_transaction_loop_threshold_thresholds'

        x-yang:
          Type: list
```

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_action:

```
    Type: object
    Properties:
      tailf-mobile-infra:action:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: noop
        enum:
        - noop
        - log-event
        - kill-session
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_count:

```
    Type: object
    Properties:
      tailf-mobile-infra:count:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_name:

```
    Type: object
    Properties:
      tailf-mobile-infra:name:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: low
        enum:
        - low
        - high
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_infra_transaction_loop_detection:
    Type: object
    Properties:
      tailf-mobile-infra:detection:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: enable
        enum:
        - enable
        - disable
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_instance:
    Type: object
```

```
    Properties:
      tailf-mobile-infra:instance:
        Reference: '#/components/schemas/datapost_tailfmobileinfrainstance'
  data_tailf-mobile-infra_instance-post:
    Type: object
    Properties:
      tailf-mobile-infra:instance-id:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_instanceid'

        x-yang:
          Type: list
  data_tailf-mobile-infra_instance_instance-id_instance-id-id:
    Type: object
    Properties:
      tailf-mobile-infra:instance-id:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_instanceid'

        x-yang:
          Type: list
  data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint:
    Type: object
    Properties:
      tailf-mobile-infra:endpoint:
        Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint'
  data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint-post:

    Type: object
    Properties:
      tailf-mobile-infra:ep:
        Type: array
        Description: (list)
        Items:
         Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_ep'

        x-yang:
          Type: list

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype:

    Type: object
    Properties:
      tailf-mobile-infra:ep:
        Type: array
        Description: (list)
        Items:
         Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_ep'
```

```
        x-yang:
          Type: list

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_certificate-name:

    Type: object
    Properties:
      tailf-mobile-infra:certificate-name:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_eptype:

    Type: object
    Properties:
      tailf-mobile-infra:eptype:
        Type: string
        Description: (leaf)
        format: identityref
        x-yang:
          Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_instancetype:

    Type: object
    Properties:
      tailf-mobile-infra:instancetype:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: IPv4
        enum:
        - IPv4
        - IPv6
        - Dual
        x-yang:
          Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type:

    Type: object
    Properties:
      tailf-mobile-infra:interface:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_interface'
        x-yang:
          Type: list
  ?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_certificate-name

```
  : type: object
    Properties:
      tailf-mobile-infra:certificate-name:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher

  : type: object
    Properties:
      tailf-mobile-infra:dispatcher:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_dispatcher'
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher-post

  : type: object
    Properties:
      tailf-mobile-infra:count:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:capacity:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:outbound:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
      tailf-mobile-infra:rate-limit:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:cache:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
      tailf-mobile-infra:threshold:
        Type: integer
```

```
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:expiry:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:nonresponsive:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:flowctrl-group:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_dispatcher_flowctrlgroup'
        x-yang:
          Type: list
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_cache

  : type: object
    Properties:
      tailf-mobile-infra:cache:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_capacity

  : type: object
    Properties:
      tailf-mobile-infra:capacity:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_count

  : type: object
    Properties:
      tailf-mobile-infra:count:
        Type: integer
        Description: (leaf)
```

```
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_expiry

  : type: object
    Properties:
      tailf-mobile-infra:expiry:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name

  : type: object
    Properties:
      tailf-mobile-infra:flowctrl-group:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_dispatcher_flowctrlgroup'
        x-yang:
          Type: list
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_capacity

  : type: object
    Properties:
      tailf-mobile-infra:capacity:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_name

  : type: object
    Properties:
      tailf-mobile-infra:name:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-capacity

  : type: object
    Properties:
      tailf-mobile-infra:outbound-capacity:
```

```
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-rate-limit

  : type: object
    Properties:
      tailf-mobile-infra:outbound-rate-limit:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate-limit

  : type: object
    Properties:
      tailf-mobile-infra:rate-limit:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_nonresponsive

  : type: object
    Properties:
      tailf-mobile-infra:nonresponsive:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_outbound

  : type: object
    Properties:
      tailf-mobile-infra:outbound:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_rate-limit

  : type: object
    Properties:
      tailf-mobile-infra:rate-limit:
```

```
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_threshold

  : type: object
    Properties:
      tailf-mobile-infra:threshold:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_instancetype

  : type: object
    Properties:
      tailf-mobile-infra:instancetype:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: IPv4
        enum:
        - IPv4
        - IPv6
        - Dual
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_interface-type

  : type: object
    Properties:
      tailf-mobile-infra:interface-type:
        Type: string
        Description: (leaf)
        format: identityref
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal

  : type: object
    Properties:
      tailf-mobile-infra:internal:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal'
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal-post

  : type: object
```

```
    Properties:
      tailf-mobile-infra:base-port:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal_baseport'
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port

  : type: object
    Properties:
      tailf-mobile-infra:base-port:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal_baseport'
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port-post

  : type: object
    Properties:
      tailf-mobile-infra:start:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port_start

  : type: object
    Properties:
      tailf-mobile-infra:start:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopbackEth

  : type: object
    Properties:
      tailf-mobile-infra:loopbackEth:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopbackPort

  : type: object
    Properties:
      tailf-mobile-infra:loopbackPort:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
```

```
        Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor

  : type: object
    Properties:
      tailf-mobile-infra:monitor:
       Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_monitor'

  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor-post

  : type: object
    Properties:
      tailf-mobile-infra:protocol:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: 'on'
        enum:
        - 'on'
        - 'off'
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor_protocol

  : type: object
    Properties:
      tailf-mobile-infra:protocol:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: 'on'
        enum:
        - 'on'
        - 'off'
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_mtls-enable

  : type: object
    Properties:
      tailf-mobile-infra:mtls-enable:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6

  : type: object
    Properties:
      tailf-mobile-infra:sec-vip6:
```

```
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_secvip6'
        x-yang:
          Type: list
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_offline

  : type: object
    Properties:
      tailf-mobile-infra:offline:
        Type: string
        Description: (leaf)
        format: '[null]'
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_sec-vip-ipv6

  : type: object
    Properties:
      tailf-mobile-infra:sec-vip-ipv6:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-interface

  : type: object
    Properties:
      tailf-mobile-infra:vip-interface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-ipv6-port

  : type: object
    Properties:
      tailf-mobile-infra:vip-ipv6-port:
        Type: integer
        Description: (leaf)
        format: uint16
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vrf

  : type: object
```

```
    Properties:
      tailf-mobile-infra:vrf:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip

  : type: object
    Properties:
      tailf-mobile-infra:sec-vip:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_secvip'
        x-yang:
          Type: list
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_offline

  : type: object
    Properties:
      tailf-mobile-infra:offline:
        Type: string
        Description: (leaf)
        format: '[null]'
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_sec-vip-ip

  : type: object
    Properties:
      tailf-mobile-infra:sec-vip-ip:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-interface

  : type: object
    Properties:
      tailf-mobile-infra:vip-interface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  ?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-port

```
: type: object
  Properties:
    tailf-mobile-infra:vip-port:
      Type: integer
      Description: (leaf)
      format: uint16
      x-yang:
        Type: leaf
?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vrf

```
: type: object
  Properties:
    tailf-mobile-infra:vrf:
      Type: string
      Description: (leaf)
      format: leafref
      x-yang:
        Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla:

```
  Type: object
  Properties:
    tailf-mobile-infra:sla:
      Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_sla'

?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla-post

```
: type: object
  Properties:
    tailf-mobile-infra:response:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    tailf-mobile-infra:procedure:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_procedure

```
: type: object
  Properties:
    tailf-mobile-infra:procedure:
      Type: integer
      Description: (leaf)
```

```
      format: int32
      x-yang:
        Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_response

  : type: object
    Properties:
      tailf-mobile-infra:response:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_tls-enable

  : type: object
    Properties:
      tailf-mobile-infra:tls-enable:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_uri-scheme

  : type: object
    Properties:
      tailf-mobile-infra:uri-scheme:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: http
        enum:
        - http
        - https
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6

  : type: object
    Properties:
      tailf-mobile-infra:vip6:
        Type: array
        Description: (list)
        Items:
         Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_vip6'

        x-yang:
          Type: list
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline
```

```
  : type: object
    Properties:
      tailf-mobile-infra:offline:
        Type: string
        Description: (leaf)
        format: '[null]'
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface

  : type: object
    Properties:
      tailf-mobile-infra:vip-interface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6

  : type: object
    Properties:
      tailf-mobile-infra:vip-ipv6:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6-port

  : type: object
    Properties:
      tailf-mobile-infra:vip-ipv6-port:
        Type: integer
        Description: (leaf)
        format: uint16
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf

  : type: object
    Properties:
      tailf-mobile-infra:vrf:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip
```

```
  : type: object
    Properties:
      tailf-mobile-infra:vip:
        Type: array
        Description: (list)
        Items:
         Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_vip'

        x-yang:
          Type: list
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_offline

  : type: object
    Properties:
      tailf-mobile-infra:offline:
        Type: string
        Description: (leaf)
        format: '[null]'
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-interface

  : type: object
    Properties:
      tailf-mobile-infra:vip-interface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-ip

  : type: object
    Properties:
      tailf-mobile-infra:vip-ip:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-port

  : type: object
    Properties:
      tailf-mobile-infra:vip-port:
        Type: integer
        Description: (leaf)
        format: uint16
        x-yang:
```

```
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vrf

  : type: object
    Properties:
      tailf-mobile-infra:vrf:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vrf:

```
    Type: object
    Properties:
      tailf-mobile-infra:vrf:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal:

```
    Type: object
    Properties:
      tailf-mobile-infra:internal:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal'
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal-post:

```
    Type: object
    Properties:
      tailf-mobile-infra:base-port:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal_baseport'
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port:

```
    Type: object
    Properties:
      tailf-mobile-infra:base-port:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal_baseport'
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port-post:

```
    Type: object
    Properties:
      tailf-mobile-infra:start:
        Type: integer
        Description: (leaf)
```

```
        format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port_start:

```
    Type: object
    Properties:
      tailf-mobile-infra:start:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackEth:

```
    Type: object
    Properties:
      tailf-mobile-infra:loopbackEth:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackPort:

```
    Type: object
    Properties:
      tailf-mobile-infra:loopbackPort:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor:

```
    Type: object
    Properties:
      tailf-mobile-infra:monitor:
       Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_monitor'
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor-post:

```
    Type: object
    Properties:
      tailf-mobile-infra:protocol:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: 'on'
```

```
        enum:
        - 'on'
        - 'off'
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor_protocol:

```
    Type: object
    Properties:
      tailf-mobile-infra:protocol:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: 'on'
        enum:
        - 'on'
        - 'off'
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_mtls-enable:

```
    Type: object
    Properties:
      tailf-mobile-infra:mtls-enable:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_nodes:

```
    Type: object
    Properties:
      tailf-mobile-infra:nodes:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_replicas:

```
    Type: object
    Properties:
      tailf-mobile-infra:replicas:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name:

```
    Type: object
    Properties:
      tailf-mobile-infra:service:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_service'
        x-yang:
          Type: list
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type

  : type: object
    Properties:
      tailf-mobile-infra:interface:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_interface'
        x-yang:
          Type: list
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_certificate-name

  : type: object
    Properties:
      tailf-mobile-infra:certificate-name:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher

  : type: object
    Properties:
      tailf-mobile-infra:dispatcher:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_dispatcher'
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher-post

  : type: object
    Properties:
      tailf-mobile-infra:count:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:capacity:
```

```
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:outbound:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
      tailf-mobile-infra:rate-limit:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:cache:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
      tailf-mobile-infra:threshold:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:expiry:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:nonresponsive:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:flowctrl-group:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_dispatcher_flowctrlgroup'
        x-yang:
          Type: list
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_cache

  : type: object
    Properties:
```

```
      tailf-mobile-infra:cache:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_capacity

  : type: object
    Properties:
      tailf-mobile-infra:capacity:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_count

  : type: object
    Properties:
      tailf-mobile-infra:count:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_expiry

  : type: object
    Properties:
      tailf-mobile-infra:expiry:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name

  : type: object
    Properties:
      tailf-mobile-infra:flowctrl-group:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_dispatcher_flowctrlgroup'
        x-yang:
          Type: list
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_capacity

  : type: object
```

```
    Properties:
      tailf-mobile-infra:capacity:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_name

  : type: object
    Properties:
      tailf-mobile-infra:name:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-capacity

  : type: object
    Properties:
      tailf-mobile-infra:outbound-capacity:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-rate-limit

  : type: object
    Properties:
      tailf-mobile-infra:outbound-rate-limit:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate-limit

  : type: object
    Properties:
      tailf-mobile-infra:rate-limit:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_type_service_service-service-name_interface_interface-interface-type_dispatcher_nonresponsive
```

```
  : type: object
    Properties:
      tailf-mobile-infra:nonresponsive:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_outbound

  : type: object
    Properties:
      tailf-mobile-infra:outbound:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_rate-limit

  : type: object
    Properties:
      tailf-mobile-infra:rate-limit:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_threshold

  : type: object
    Properties:
      tailf-mobile-infra:threshold:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_instancetype

  : type: object
    Properties:
      tailf-mobile-infra:instancetype:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: IPv4
        enum:
        - IPv4
        - IPv6
        - Dual
```

```
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_interface-type

  : type: object
    Properties:
      tailf-mobile-infra:interface-type:
        Type: string
        Description: (leaf)
        format: identityref
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal

  : type: object
    Properties:
      tailf-mobile-infra:internal:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal'
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal-post

  : type: object
    Properties:
      tailf-mobile-infra:base-port:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal_baseport'
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port

  : type: object
    Properties:
      tailf-mobile-infra:base-port:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal_baseport'
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port_post

  : type: object
    Properties:
      tailf-mobile-infra:start:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port_start

  : type: object
    Properties:
      tailf-mobile-infra:start:
        Type: integer
        Description: (leaf)
```

```
      format: int32
      x-yang:
        Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_loopbackEth

  : type: object
    Properties:
      tailf-mobile-infra:loopbackEth:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_loopbackPort

  : type: object
    Properties:
      tailf-mobile-infra:loopbackPort:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor

  : type: object
    Properties:
      tailf-mobile-infra:monitor:
       Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_monitor'

  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor-post

  : type: object
    Properties:
      tailf-mobile-infra:protocol:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: 'on'
        enum:
        - 'on'
        - 'off'
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor_protocol

  : type: object
    Properties:
      tailf-mobile-infra:protocol:
        Type: string
```

```
      Description: (leaf)
      format: enumeration
      Default: 'on'
      enum:
      - 'on'
      - 'off'
      x-yang:
        Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_mtls-enable

  : type: object
    Properties:
      tailf-mobile-infra:mtls-enable:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6

  : type: object
    Properties:
      tailf-mobile-infra:sec-vip6:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_secvip6'
        x-yang:
          Type: list
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_offline

  : type: object
    Properties:
      tailf-mobile-infra:offline:
        Type: string
        Description: (leaf)
        format: '[null]'
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_sec-vip-ipv6

  : type: object
    Properties:
      tailf-mobile-infra:sec-vip-ipv6:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-interface
```

```
  : type: object
    Properties:
      tailf-mobile-infra:vip-interface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-etype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-ipv6-port

  : type: object
    Properties:
      tailf-mobile-infra:vip-ipv6-port:
        Type: integer
        Description: (leaf)
        format: uint16
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-etype_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vrf

  : type: object
    Properties:
      tailf-mobile-infra:vrf:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-etype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip

  : type: object
    Properties:
      tailf-mobile-infra:sec-vip:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_secvip'
        x-yang:
          Type: list
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-etype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_offline

  : type: object
    Properties:
      tailf-mobile-infra:offline:
        Type: string
        Description: (leaf)
        format: '[null]'
        x-yang:
```

```
        Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_sec-vip-ip

  : type: object
    Properties:
      tailf-mobile-infra:sec-vip-ip:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-interface

  : type: object
    Properties:
      tailf-mobile-infra:vip-interface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-port

  : type: object
    Properties:
      tailf-mobile-infra:vip-port:
        Type: integer
        Description: (leaf)
        format: uint16
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vrf

  : type: object
    Properties:
      tailf-mobile-infra:vrf:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla

  : type: object
    Properties:
      tailf-mobile-infra:sla:
        Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_sla'

  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla-post
```

```
  : type: object
    Properties:
      tailf-mobile-infra:response:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:procedure:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla_procedure

  : type: object
    Properties:
      tailf-mobile-infra:procedure:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla_response

  : type: object
    Properties:
      tailf-mobile-infra:response:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_tls-enable

  : type: object
    Properties:
      tailf-mobile-infra:tls-enable:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_uri-scheme

  : type: object
    Properties:
      tailf-mobile-infra:uri-scheme:
        Type: string
```

```
      Description: (leaf)
      format: enumeration
      Default: http
      enum:
      - http
      - https
      x-yang:
        Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6

  : type: object
    Properties:
      tailf-mobile-infra:vip6:
        Type: array
        Description: (list)
        Items:
         Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_vip6'

        x-yang:
          Type: list
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline

  : type: object
    Properties:
      tailf-mobile-infra:offline:
        Type: string
        Description: (leaf)
        format: '[null]'
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface

  : type: object
    Properties:
      tailf-mobile-infra:vip-interface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6

  : type: object
    Properties:
      tailf-mobile-infra:vip-ipv6:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  ?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6-port

```
: type: object
  Properties:
    tailf-mobile-infra:vip-ipv6-port:
      Type: integer
      Description: (leaf)
      format: uint16
      x-yang:
        Type: leaf
?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf

```
: type: object
  Properties:
    tailf-mobile-infra:vrf:
      Type: string
      Description: (leaf)
      format: leafref
      x-yang:
        Type: leaf
?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip

```
: type: object
  Properties:
    tailf-mobile-infra:vip:
      Type: array
      Description: (list)
      Items:
       Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_vip'

      x-yang:
        Type: list
?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_offline

```
: type: object
  Properties:
    tailf-mobile-infra:offline:
      Type: string
      Description: (leaf)
      format: '[null]'
      x-yang:
        Type: leaf
?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-interface

```
: type: object
  Properties:
    tailf-mobile-infra:vip-interface:
      Type: string
      Description: (leaf)
      format: string
```

```
      x-yang:
        Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-ip

  : type: object
    Properties:
      tailf-mobile-infra:vip-ip:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-port

  : type: object
    Properties:
      tailf-mobile-infra:vip-port:
        Type: integer
        Description: (leaf)
        format: uint16
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vrf

  : type: object
    Properties:
      tailf-mobile-infra:vrf:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vrf

  : type: object
    Properties:
      tailf-mobile-infra:vrf:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_service-name

  : type: object
    Properties:
      tailf-mobile-infra:service-name:
        Type: string
        Description: (leaf)
```

```
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level:

```
    Type: object
    Properties:
      tailf-mobile-infra:system-health-level:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel'
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level-post:

```
    Type: object
    Properties:
      tailf-mobile-infra:warn:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel_warn'
      tailf-mobile-infra:critical:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel_warn'
      tailf-mobile-infra:crash:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel_warn'
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash:

```
    Type: object
    Properties:
      tailf-mobile-infra:crash:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel_warn'
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash-post:

```
    Type: object
    Properties:
      tailf-mobile-infra:cpu-percent:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:memory-in-mbs:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:num-of-goroutine:
        Type: integer
        Description: (leaf)
        format: int32
```

```
      x-yang:
        Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_cpu-percent:

```
    Type: object
    Properties:
      tailf-mobile-infra:cpu-percent:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_memory-in-mbs:

```
    Type: object
    Properties:
      tailf-mobile-infra:memory-in-mbs:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_num-of-goroutine

  : type: object
    Properties:
      tailf-mobile-infra:num-of-goroutine:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical:

```
    Type: object
    Properties:
      tailf-mobile-infra:critical:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel_warn'
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical-post:

```
    Type: object
    Properties:
      tailf-mobile-infra:cpu-percent:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
```

```
      tailf-mobile-infra:memory-in-mbs:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      tailf-mobile-infra:num-of-goroutine:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_cpu-percent:

```
    Type: object
    Properties:
      tailf-mobile-infra:cpu-percent:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_memory-in-mbs

  : type: object
    Properties:
      tailf-mobile-infra:memory-in-mbs:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_num-of-goroutine

  : type: object
    Properties:
      tailf-mobile-infra:num-of-goroutine:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn:

```
    Type: object
    Properties:
      tailf-mobile-infra:warn:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel_warn'
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn-post:

```
  Type: object
  Properties:
    tailf-mobile-infra:cpu-percent:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    tailf-mobile-infra:memory-in-mbs:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    tailf-mobile-infra:num-of-goroutine:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_cpu-percent:

```
  Type: object
  Properties:
    tailf-mobile-infra:cpu-percent:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_memory-in-mbs:

```
  Type: object
  Properties:
    tailf-mobile-infra:memory-in-mbs:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_num-of-goroutine

```
: type: object
  Properties:
    tailf-mobile-infra:num-of-goroutine:
      Type: integer
      Description: (leaf)
      format: int32
```

```
      x-yang:
        Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_uri-scheme:

```
    Type: object
    Properties:
      tailf-mobile-infra:uri-scheme:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: http
        enum:
        - http
        - https
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6:

```
    Type: object
    Properties:
      tailf-mobile-infra:vip6:
        Type: array
        Description: (list)
        Items:
         Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_vip6'

        x-yang:
          Type: list
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_offline:

```
    Type: object
    Properties:
      tailf-mobile-infra:offline:
        Type: string
        Description: (leaf)
        format: '[null]'
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-interface:

```
    Type: object
    Properties:
      tailf-mobile-infra:vip-interface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6:

```
    Type: object
    Properties:
      tailf-mobile-infra:vip-ipv6:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6-port:

```
    Type: object
    Properties:
      tailf-mobile-infra:vip-ipv6-port:
        Type: integer
        Description: (leaf)
        format: uint16
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vrf:

```
    Type: object
    Properties:
      tailf-mobile-infra:vrf:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip:

```
    Type: object
    Properties:
      tailf-mobile-infra:vip:
        Type: array
        Description: (list)
        Items:
         Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_vip'

        x-yang:
          Type: list
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_offline:

```
    Type: object
    Properties:
      tailf-mobile-infra:offline:
        Type: string
        Description: (leaf)
        format: '[null]'
```

```
      x-yang:
        Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-interface:

    Type: object
    Properties:
      tailf-mobile-infra:vip-interface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-ip:

    Type: object
    Properties:
      tailf-mobile-infra:vip-ip:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-port:

    Type: object
    Properties:
      tailf-mobile-infra:vip-port:
        Type: integer
        Description: (leaf)
        format: uint16
        x-yang:
          Type: leaf

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vrf:

    Type: object
    Properties:
      tailf-mobile-infra:vrf:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_instance_instance-id_instance-id-id_id:
    Type: object
    Properties:
      tailf-mobile-infra:id:
        Type: string
        Description: (leaf)
        format: leafref
```

```
      x-yang:
        Type: leaf
  data_tailf-mobile-infra_instances:
    Type: object
    Properties:
      tailf-mobile-infra:instances:
        Reference: '#/components/schemas/datapost_tailfmobileinfrainstances'
  data_tailf-mobile-infra_instances-post:
    Type: object
    Properties:
      tailf-mobile-infra:instance:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrainstances_instance'
        x-yang:
          Type: list
  data_tailf-mobile-infra_instances_instance_instance-instance-id:
    Type: object
    Properties:
      tailf-mobile-infra:instance:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrainstances_instance'
        x-yang:
          Type: list

data_tailf-mobile-infra_instances_instance_instance-instance-id_cluster-id:

    Type: object
    Properties:
      tailf-mobile-infra:cluster-id:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_instances_instance_instance-instance-id_instance-id:

    Type: object
    Properties:
      tailf-mobile-infra:instance-id:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_instances_instance_instance-instance-id_slice-name:

    Type: object
```

```
    Properties:
      tailf-mobile-infra:slice-name:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_instances_instance_instance-instance-id_system-id:
    Type: object
    Properties:
      tailf-mobile-infra:system-id:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_k8:
    Type: object
    Properties:
      tailf-mobile-infra:k8:
        Reference: '#/components/schemas/datapost_tailfmobileinfrak8'
  data_tailf-mobile-infra_k8-post:
    Type: object
    Properties:
      tailf-mobile-infra:label:
        Reference: '#/components/schemas/datapost_tailfmobileinfrak8_label'
  data_tailf-mobile-infra_k8_label:
    Type: object
    Properties:
      tailf-mobile-infra:label:
        Reference: '#/components/schemas/datapost_tailfmobileinfrak8_label'
  data_tailf-mobile-infra_k8_label-post:
    Type: object
    Properties:
      tailf-mobile-infra:pod-group-config:
        Type: array
        Description: (list)
        Items:
         Reference: '#/components/schemas/datapost_tailfmobileinfrak8_label_podgroupconfig'
        x-yang:
          Type: list
data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value:
    Type: object
    Properties:
      tailf-mobile-infra:pod-group-config:
        Type: array
        Description: (list)
        Items:
```

```
        Reference: '#/components/schemas/datapost_tailfmobileinfrak8_label_podgroupconfig'

        x-yang:
          Type: list
  ?
data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_key

  : type: object
    Properties:
      tailf-mobile-infra:key:
        Type: string
        Description: Key for the label (leaf)
        format: string
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_pod-group

  : type: object
    Properties:
      tailf-mobile-infra:pod-group:
        Type: string
        Description: Group for the VMs (leaf)
        format: enumeration
        Default: protocol-layer
        enum:
        - protocol-layer
        - service-layer
        - cdl-layer
        - oam-layer
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_value

  : type: object
    Properties:
      tailf-mobile-infra:value:
        Type: string
        Description: Value for the label (leaf)
        format: string
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_local-instance:
    Type: object
    Properties:
      tailf-mobile-infra:local-instance:
        Reference: '#/components/schemas/datapost_tailfmobileinfralocalinstance'
  data_tailf-mobile-infra_local-instance-post:
    Type: object
    Properties:
      tailf-mobile-infra:instance:
        Type: string
        Description: (leaf)
```

```
      format: leafref
      x-yang:
        Type: leaf
data_tailf-mobile-infra_local-instance_instance:
  Type: object
  Properties:
    tailf-mobile-infra:instance:
      Type: string
      Description: (leaf)
      format: leafref
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging:
  Type: object
  Properties:
    tailf-mobile-infra:logging:
      Reference: '#/components/schemas/datapost_tailfmobileinfralogging'
data_tailf-mobile-infra_logging-post:
  Type: object
  Properties:
    tailf-mobile-infra:transaction:
      Reference: '#/components/schemas/datapost_tailfmobileinfralogging_transaction'
    tailf-mobile-infra:level:
      Reference: '#/components/schemas/datapost_tailfmobileinfralogging_level'
    tailf-mobile-infra:logger:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfralogging_logger'
      x-yang:
        Type: list
    tailf-mobile-infra:async:
      Reference: '#/components/schemas/datapost_tailfmobileinfralogging_async'
    tailf-mobile-infra:error:
      Reference: '#/components/schemas/datapost_tailfmobileinfralogging_error'
data_tailf-mobile-infra_logging_async:
  Type: object
  Properties:
    tailf-mobile-infra:async:
      Reference: '#/components/schemas/datapost_tailfmobileinfralogging_async'
data_tailf-mobile-infra_logging_async-post:
  Type: object
  Properties:
    tailf-mobile-infra:application:
     Reference: '#/components/schemas/datapost_tailfmobileinfralogging_async_application'

    tailf-mobile-infra:transaction:
     Reference: '#/components/schemas/datapost_tailfmobileinfralogging_async_application'

    tailf-mobile-infra:tracing:
     Reference: '#/components/schemas/datapost_tailfmobileinfralogging_async_application'
```

```
      tailf-mobile-infra:monitor-subscriber:
       Reference: '#/components/schemas/datapost_tailfmobileinfralogging_async_application'

  data_tailf-mobile-infra_logging_async_application:
    Type: object
    Properties:
      tailf-mobile-infra:application:
       Reference: '#/components/schemas/datapost_tailfmobileinfralogging_async_application'

  data_tailf-mobile-infra_logging_async_application-post:
    Type: object
    Properties:
      tailf-mobile-infra:enable:
        Reference:
'#/components/schemas/datapost_tailfmobileinfralogging_async_application_enable'
      tailf-mobile-infra:disable:
        Type: string
        Description: (leaf)
        format: '[null]'
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_logging_async_application_disable:
    Type: object
    Properties:
      tailf-mobile-infra:disable:
        Type: string
        Description: (leaf)
        format: '[null]'
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_logging_async_application_enable:
    Type: object
    Properties:
      tailf-mobile-infra:enable:
        Reference:
'#/components/schemas/datapost_tailfmobileinfralogging_async_application_enable'
  data_tailf-mobile-infra_logging_async_application_enable-post:
    Type: object
    Properties:
      tailf-mobile-infra:buffer-size:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_logging_async_application_enable_buffer-size:
    Type: object
    Properties:
      tailf-mobile-infra:buffer-size:
        Type: integer
        Description: (leaf)
        format: int32
```

```
      x-yang:
        Type: leaf
  data_tailf-mobile-infra_logging_async_monitor-subscriber:
    Type: object
    Properties:
      tailf-mobile-infra:monitor-subscriber:
       Reference: '#/components/schemas/datapost_tailfmobileinfralogging_async_application'

  data_tailf-mobile-infra_logging_async_monitor-subscriber-post:
    Type: object
    Properties:
      tailf-mobile-infra:enable:
        Reference:
'#/components/schemas/datapost_tailfmobileinfralogging_async_application_enable'
      tailf-mobile-infra:disable:
        Type: string
        Description: (leaf)
        format: '[null]'
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_logging_async_monitor-subscriber_disable:
    Type: object
    Properties:
      tailf-mobile-infra:disable:
        Type: string
        Description: (leaf)
        format: '[null]'
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_logging_async_monitor-subscriber_enable:
    Type: object
    Properties:
      tailf-mobile-infra:enable:
        Reference:
'#/components/schemas/datapost_tailfmobileinfralogging_async_application_enable'
  data_tailf-mobile-infra_logging_async_monitor-subscriber_enable-post:
    Type: object
    Properties:
      tailf-mobile-infra:buffer-size:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_logging_async_monitor-subscriber_enable_buffer-size:

    Type: object
    Properties:
      tailf-mobile-infra:buffer-size:
        Type: integer
        Description: (leaf)
```

```
      format: int32
      x-yang:
        Type: leaf
  data_tailf-mobile-infra_logging_async_tracing:
    Type: object
    Properties:
      tailf-mobile-infra:tracing:
       Reference: '#/components/schemas/datapost_tailfmobileinfralogging_async_application'

  data_tailf-mobile-infra_logging_async_tracing-post:
    Type: object
    Properties:
      tailf-mobile-infra:enable:
        Reference:
'#/components/schemas/datapost_tailfmobileinfralogging_async_application_enable'
      tailf-mobile-infra:disable:
        Type: string
        Description: (leaf)
        format: '[null]'
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_logging_async_tracing_disable:
    Type: object
    Properties:
      tailf-mobile-infra:disable:
        Type: string
        Description: (leaf)
        format: '[null]'
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_logging_async_tracing_enable:
    Type: object
    Properties:
      tailf-mobile-infra:enable:
        Reference:
'#/components/schemas/datapost_tailfmobileinfralogging_async_application_enable'
  data_tailf-mobile-infra_logging_async_tracing_enable-post:
    Type: object
    Properties:
      tailf-mobile-infra:buffer-size:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_logging_async_tracing_enable_buffer-size:
    Type: object
    Properties:
      tailf-mobile-infra:buffer-size:
        Type: integer
        Description: (leaf)
        format: int32
```

```
      x-yang:
        Type: leaf
  data_tailf-mobile-infra_logging_async_transaction:
    Type: object
    Properties:
      tailf-mobile-infra:transaction:
       Reference: '#/components/schemas/datapost_tailfmobileinfralogging_async_application'

  data_tailf-mobile-infra_logging_async_transaction-post:
    Type: object
    Properties:
      tailf-mobile-infra:enable:
        Reference:
'#/components/schemas/datapost_tailfmobileinfralogging_async_application_enable'
      tailf-mobile-infra:disable:
        Type: string
        Description: (leaf)
        format: '[null]'
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_logging_async_transaction_disable:
    Type: object
    Properties:
      tailf-mobile-infra:disable:
        Type: string
        Description: (leaf)
        format: '[null]'
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_logging_async_transaction_enable:
    Type: object
    Properties:
      tailf-mobile-infra:enable:
        Reference:
'#/components/schemas/datapost_tailfmobileinfralogging_async_application_enable'
  data_tailf-mobile-infra_logging_async_transaction_enable-post:
    Type: object
    Properties:
      tailf-mobile-infra:buffer-size:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_logging_async_transaction_enable_buffer-size:
    Type: object
    Properties:
      tailf-mobile-infra:buffer-size:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
```

```
      Type: leaf
data_tailf-mobile-infra_logging_error:
  Type: object
  Properties:
    tailf-mobile-infra:error:
      Reference: '#/components/schemas/datapost_tailfmobileinfralogging_error'
data_tailf-mobile-infra_logging_error-post:
  Type: object
  Properties:
    tailf-mobile-infra:stack:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_error_stack:
  Type: object
  Properties:
    tailf-mobile-infra:stack:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_level:
  Type: object
  Properties:
    tailf-mobile-infra:level:
      Reference: '#/components/schemas/datapost_tailfmobileinfralogging_level'
data_tailf-mobile-infra_logging_level-post:
  Type: object
  Properties:
    tailf-mobile-infra:application:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - 'off'
      x-yang:
```

```
      Type: leaf
    tailf-mobile-infra:transaction:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - 'off'
      x-yang:
        Type: leaf
    tailf-mobile-infra:tracing:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - 'off'
      x-yang:
        Type: leaf
    tailf-mobile-infra:monitor-subscriber:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - 'off'
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_level_application:
  Type: object
  Properties:
    tailf-mobile-infra:application:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
```

```
      - error
      - 'off'
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_level_monitor-subscriber:
  Type: object
  Properties:
    tailf-mobile-infra:monitor-subscriber:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - 'off'
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_level_tracing:
  Type: object
  Properties:
    tailf-mobile-infra:tracing:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - 'off'
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_level_transaction:
  Type: object
  Properties:
    tailf-mobile-infra:transaction:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - 'off'
      x-yang:
        Type: leaf
```

```
data_tailf-mobile-infra_logging_logger_logger-name:
  Type: object
  Properties:
    tailf-mobile-infra:logger:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfralogging_logger'
      x-yang:
        Type: list
data_tailf-mobile-infra_logging_logger_logger-name_level:
  Type: object
  Properties:
    tailf-mobile-infra:level:
      Reference: '#/components/schemas/datapost_tailfmobileinfralogging_level'
data_tailf-mobile-infra_logging_logger_logger-name_level-post:
  Type: object
  Properties:
    tailf-mobile-infra:application:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - 'off'
      x-yang:
        Type: leaf
    tailf-mobile-infra:transaction:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - 'off'
      x-yang:
        Type: leaf
    tailf-mobile-infra:tracing:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: trace
      enum:
      - trace
      - debug
```

```
        - info
        - warn
        - error
        - 'off'
        x-yang:
          Type: leaf
      tailf-mobile-infra:monitor-subscriber:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: trace
        enum:
        - trace
        - debug
        - info
        - warn
        - error
        - 'off'
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_logging_logger_logger-name_level_application:
    Type: object
    Properties:
      tailf-mobile-infra:application:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: trace
        enum:
        - trace
        - debug
        - info
        - warn
        - error
        - 'off'
        x-yang:
          Type: leaf

data_tailf-mobile-infra_logging_logger_logger-name_level_monitor-subscriber:

    Type: object
    Properties:
      tailf-mobile-infra:monitor-subscriber:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: trace
        enum:
        - trace
        - debug
        - info
        - warn
        - error
        - 'off'
        x-yang:
          Type: leaf
```

```
data_tailf-mobile-infra_logging_logger_logger-name_level_tracing:
  Type: object
  Properties:
    tailf-mobile-infra:tracing:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - 'off'
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_logger_logger-name_level_transaction:
  Type: object
  Properties:
    tailf-mobile-infra:transaction:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: trace
      enum:
      - trace
      - debug
      - info
      - warn
      - error
      - 'off'
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_logger_logger-name_name:
  Type: object
  Properties:
    tailf-mobile-infra:name:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_transaction:
  Type: object
  Properties:
    tailf-mobile-infra:transaction:
      Reference: '#/components/schemas/datapost_tailfmobileinfralogging_transaction'
data_tailf-mobile-infra_logging_transaction-post:
  Type: object
  Properties:
    tailf-mobile-infra:persist:
      Type: string
      Description: (leaf)
```

```
      format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
    tailf-mobile-infra:max-file-size:
      Type: integer
      Description: (leaf)
      format: uint32
      x-yang:
        Type: leaf
    tailf-mobile-infra:max-rotation:
      Type: integer
      Description: (leaf)
      format: uint32
      x-yang:
        Type: leaf
    tailf-mobile-infra:message:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
    tailf-mobile-infra:duplicate:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_transaction_duplicate:
  Type: object
  Properties:
    tailf-mobile-infra:duplicate:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
data_tailf-mobile-infra_logging_transaction_max-file-size:
```

```
    Type: object
    Properties:
      tailf-mobile-infra:max-file-size:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_logging_transaction_max-rotation:
    Type: object
    Properties:
      tailf-mobile-infra:max-rotation:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_logging_transaction_message:
    Type: object
    Properties:
      tailf-mobile-infra:message:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: enable
        enum:
        - enable
        - disable
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_logging_transaction_persist:
    Type: object
    Properties:
      tailf-mobile-infra:persist:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: enable
        enum:
        - enable
        - disable
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_monitor:
    Type: object
    Properties:
      tailf-mobile-infra:monitor:
        Reference: '#/components/schemas/datapost_tailfmobileinframonitor'
  data_tailf-mobile-infra_monitor-post:
    Type: object
    Properties:
      tailf-mobile-infra:bfd:
```

```
      Reference: '#/components/schemas/datapost_tailfmobileinframonitor_bfd'
    tailf-mobile-infra:protocol:
      Reference: '#/components/schemas/datapost_tailfmobileinframonitor_protocol'
data_tailf-mobile-infra_monitor_bfd:
  Type: object
  Properties:
    tailf-mobile-infra:bfd:
      Reference: '#/components/schemas/datapost_tailfmobileinframonitor_bfd'
data_tailf-mobile-infra_monitor_bfd-post:
  Type: object
  Properties:
    tailf-mobile-infra:node-status:
      Type: string
      Description: (leaf)
      format: '[null]'
      x-yang:
        Type: leaf
data_tailf-mobile-infra_monitor_bfd_node-status:
  Type: object
  Properties:
    tailf-mobile-infra:node-status:
      Type: string
      Description: (leaf)
      format: '[null]'
      x-yang:
        Type: leaf
data_tailf-mobile-infra_monitor_protocol:
  Type: object
  Properties:
    tailf-mobile-infra:protocol:
      Reference: '#/components/schemas/datapost_tailfmobileinframonitor_protocol'
data_tailf-mobile-infra_monitor_protocol-post:
  Type: object
  Properties:
    tailf-mobile-infra:cpu-limit:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_monitor_protocol_cpu-limit:
  Type: object
  Properties:
    tailf-mobile-infra:cpu-limit:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_nodemonitor:
  Type: object
```

```
  Properties:
    tailf-mobile-infra:nodemonitor:
      Reference: '#/components/schemas/datapost_tailfmobileinfranodemonitor'
data_tailf-mobile-infra_nodemonitor-post:
  Type: object
  Properties:
    tailf-mobile-infra:mode:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: '0'
      enum:
      - '0'
      - '1'
      - '2'
      - '3'
      x-yang:
        Type: leaf
    tailf-mobile-infra:interval:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_nodemonitor_interval:
  Type: object
  Properties:
    tailf-mobile-infra:interval:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_nodemonitor_mode:
  Type: object
  Properties:
    tailf-mobile-infra:mode:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: '0'
      enum:
      - '0'
      - '1'
      - '2'
      - '3'
      x-yang:
        Type: leaf
data_tailf-mobile-infra_peers:
  Type: object
  Properties:
    tailf-mobile-infra:peers:
      Reference: '#/components/schemas/datapost_tailfmobileinfrapeers'
```

```
  data_tailf-mobile-infra_peers-post:
    Type: object
    Properties:
      tailf-mobile-infra:all:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrapeers_all'
        x-yang:
          Type: list
  data_tailf-mobile-infra_peers_all:
    Type: object
    Properties:
      tailf-mobile-infra:all:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrapeers_all'
        x-yang:
          Type: list
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress:

```
    Type: object
    Properties:
      tailf-mobile-infra:all:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrapeers_all'
        x-yang:
          Type: list
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_additionalDetails:

```
    Type: object
    Properties:
      tailf-mobile-infra:additionalDetails:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_connectedTime:

```
    Type: object
    Properties:
      tailf-mobile-infra:connectedTime:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
```

```
        Type: leaf
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_direction:

```
    Type: object
    Properties:
      tailf-mobile-infra:direction:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_endpoint:

```
    Type: object
    Properties:
      tailf-mobile-infra:endpoint:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_grInstance:

```
    Type: object
    Properties:
      tailf-mobile-infra:grInstance:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_interfaceName:

```
    Type: object
    Properties:
      tailf-mobile-infra:interfaceName:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_localAddress:

```
    Type: object
    Properties:
      tailf-mobile-infra:localAddress:
        Type: string
        Description: (leaf)
```

```
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_peerAddress:

```
    Type: object
    Properties:
      tailf-mobile-infra:peerAddress:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_podInstance:

```
    Type: object
    Properties:
      tailf-mobile-infra:podInstance:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_rpc:

```
    Type: object
    Properties:
      tailf-mobile-infra:rpc:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_type:

```
    Type: object
    Properties:
      tailf-mobile-infra:type:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_peers_all_all-grInstance_all-endpoint_all-localAddress_all-peerAddress_vrf:

```
    Type: object
    Properties:
      tailf-mobile-infra:vrf:
```

```
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resource:
  Type: object
  Properties:
    tailf-mobile-infra:resource:
      Reference: '#/components/schemas/datapost_tailfmobileinfraresource'
data_tailf-mobile-infra_resource-post:
  Type: object
  Properties:
    tailf-mobile-infra:pod:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfraresource_pod'
      x-yang:
        Type: list
data_tailf-mobile-infra_resource_pod_pod-podtype:
  Type: object
  Properties:
    tailf-mobile-infra:pod:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfraresource_pod'
      x-yang:
        Type: list
data_tailf-mobile-infra_resource_pod_pod-podtype_cpu:
  Type: object
  Properties:
    tailf-mobile-infra:cpu:
      Reference: '#/components/schemas/datapost_tailfmobileinfraresource_cpu'
data_tailf-mobile-infra_resource_pod_pod-podtype_cpu-post:
  Type: object
  Properties:
    tailf-mobile-infra:request:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    tailf-mobile-infra:limit:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_limit:
```

```
  Type: object
  Properties:
    tailf-mobile-infra:limit:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_request:
  Type: object
  Properties:
    tailf-mobile-infra:request:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resource_pod_pod-podtype_gomaxproc:
  Type: object
  Properties:
    tailf-mobile-infra:gomaxproc:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resource_pod_pod-podtype_labels:
  Type: object
  Properties:
    tailf-mobile-infra:labels:
      Reference: '#/components/schemas/datapost_tailfmobileinfraresource_labels'
data_tailf-mobile-infra_resource_pod_pod-podtype_labels-post:
  Type: object
  Properties:
    tailf-mobile-infra:key:
      Type: string
      Description: Key for the label (leaf)
      format: string
      x-yang:
        Type: leaf
    tailf-mobile-infra:value:
      Type: string
      Description: Value for the label (leaf)
      format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resource_pod_pod-podtype_labels_key:
  Type: object
  Properties:
    tailf-mobile-infra:key:
      Type: string
```

```
      Description: Key for the label (leaf)
      format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resource_pod_pod-podtype_labels_value:
  Type: object
  Properties:
    tailf-mobile-infra:value:
      Type: string
      Description: Value for the label (leaf)
      format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resource_pod_pod-podtype_memory:
  Type: object
  Properties:
    tailf-mobile-infra:memory:
      Reference: '#/components/schemas/datapost_tailfmobileinfraresource_cpu'
data_tailf-mobile-infra_resource_pod_pod-podtype_memory-post:
  Type: object
  Properties:
    tailf-mobile-infra:request:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    tailf-mobile-infra:limit:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resource_pod_pod-podtype_memory_limit:
  Type: object
  Properties:
    tailf-mobile-infra:limit:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resource_pod_pod-podtype_memory_request:
  Type: object
  Properties:
    tailf-mobile-infra:request:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
```

```
data_tailf-mobile-infra_resource_pod_pod-podtype_podtype:
  Type: object
  Properties:
    tailf-mobile-infra:podtype:
      Type: string
      Description: (leaf)
      format: identityref
      x-yang:
        Type: leaf
data_tailf-mobile-infra_resources:
  Type: object
  Properties:
    tailf-mobile-infra:resources:
      Reference: '#/components/schemas/datapost_tailfmobileinfraresources'
data_tailf-mobile-infra_resources-post:
  Type: object
  Properties:
    tailf-mobile-infra:info:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfraresources_info'
      x-yang:
        Type: list
data_tailf-mobile-infra_resources_info:
  Type: object
  Properties:
    tailf-mobile-infra:info:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfraresources_info'
      x-yang:
        Type: list
data_tailf-mobile-infra_resources_info_info-podInstance:
  Type: object
  Properties:
    tailf-mobile-infra:info:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfraresources_info'
      x-yang:
        Type: list
data_tailf-mobile-infra_resources_info_info-podInstance_cpuUsage:
  Type: object
  Properties:
    tailf-mobile-infra:cpuUsage:
      Type: integer
      Description: (leaf)
      format: int32
```

```
      x-yang:
        Type: leaf
  data_tailf-mobile-infra_resources_info_info-podInstance_diskUsageInKbps:
    Type: object
    Properties:
      tailf-mobile-infra:diskUsageInKbps:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_resources_info_info-podInstance_gcCount:
    Type: object
    Properties:
      tailf-mobile-infra:gcCount:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_resources_info_info-podInstance_gcPauseInNS:
    Type: object
    Properties:
      tailf-mobile-infra:gcPauseInNS:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_resources_info_info-podInstance_goRoutinesCount:
    Type: object
    Properties:
      tailf-mobile-infra:goRoutinesCount:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_resources_info_info-podInstance_podInstance:
    Type: object
    Properties:
      tailf-mobile-infra:podInstance:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_resources_info_info-podInstance_totalNodeMemoryInMB:
```

```
    Type: object
    Properties:
      tailf-mobile-infra:totalNodeMemoryInMB:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_resources_info_info-podInstance_usedPodMemoryInMB:
    Type: object
    Properties:
      tailf-mobile-infra:usedPodMemoryInMB:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_router:
    Type: object
    Properties:
      tailf-mobile-infra:router:
        Reference: '#/components/schemas/datapost_tailfmobileinfrarouter'
  data_tailf-mobile-infra_router-post:
    Type: object
    Properties:
      tailf-mobile-infra:bgplist:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrarouter_bgplist'
        x-yang:
          Type: list
      tailf-mobile-infra:bfd:
        Reference: '#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1'
      tailf-mobile-infra:monitor-interface:
       Reference: '#/components/schemas/datapost_tailfmobileinfrarouter_monitorinterface'
  data_tailf-mobile-infra_router_bfd:
    Type: object
    Properties:
      tailf-mobile-infra:bfd:
        Reference: '#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1'
  data_tailf-mobile-infra_router_bfd-post:
    Type: object
    Properties:
      tailf-mobile-infra:instance:
       Reference: '#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1_instance'
  data_tailf-mobile-infra_router_bfd_instance:
    Type: object
    Properties:
```

```
      tailf-mobile-infra:instance:
        Reference: '#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1_instance'

  data_tailf-mobile-infra_router_bfd_instance-post:
    Type: object
    Properties:
      tailf-mobile-infra:instance-id:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1_instance_instanceid'
        x-yang:
          Type: list
  data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id:

    Type: object
    Properties:
      tailf-mobile-infra:instance-id:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1_instance_instanceid'
        x-yang:
          Type: list
  data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_id:

    Type: object
    Properties:
      tailf-mobile-infra:id:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf

data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface:

    Type: object
    Properties:
      tailf-mobile-infra:interface-list:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1_instance_interfacelist'
        x-yang:
          Type: list

data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_gateway-ip:

    Type: object
```

```
    Properties:
      tailf-mobile-infra:gateway-ip:
        Type: string
        Description: (leaf)
        format: union
        x-yang:
          Type: leaf

data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_interface:

    Type: object
    Properties:
      tailf-mobile-infra:interface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor

  : type: object
    Properties:
      tailf-mobile-infra:neighbors:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1_instance_neighbors'
        x-yang:
          Type: list
  ?
data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor_neighbor

  : type: object
    Properties:
      tailf-mobile-infra:neighbor:
        Type: string
        Description: (leaf)
        format: union
        x-yang:
          Type: leaf

data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_vrf:

    Type: object
    Properties:
      tailf-mobile-infra:vrf:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp:
```

```
    Type: object
    Properties:
      tailf-mobile-infra:bgplist:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrarouter_bgplist'
        x-yang:
          Type: list
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd:
    Type: object
    Properties:
      tailf-mobile-infra:bfd:
        Reference: '#/components/schemas/datapost_tailfmobileinfrarouter_bfd'
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd-post:
    Type: object
    Properties:
      tailf-mobile-infra:interval:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
      tailf-mobile-infra:min_rx:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
      tailf-mobile-infra:multiplier:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
      tailf-mobile-infra:dscp-marking:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: none
        enum:
        - none
        - cs6
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_dscp-marking:
    Type: object
    Properties:
      tailf-mobile-infra:dscp-marking:
        Type: string
        Description: (leaf)
        format: enumeration
```

```
      Default: none
      enum:
      - none
      - cs6
      x-yang:
        Type: leaf
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_interval:
    Type: object
    Properties:
      tailf-mobile-infra:interval:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_min_rx:
    Type: object
    Properties:
      tailf-mobile-infra:min_rx:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_multiplier:
    Type: object
    Properties:
      tailf-mobile-infra:multiplier:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bgp:
    Type: object
    Properties:
      tailf-mobile-infra:bgp:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface:

    Type: object
    Properties:
      tailf-mobile-infra:interfaceList:
        Type: array
        Description: (list)
        Items:
         Reference: '#/components/schemas/datapost_tailfmobileinfrarouter_interfaceList'
```

```
        x-yang:
          Type: list
  ?
data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface

  : type: object
    Properties:
      tailf-mobile-infra:bondingInterfaces:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrarouter_bondingInterfaces'
        x-yang:
          Type: list
  ?
data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface_bondingInterface

  : type: object
    Properties:
      tailf-mobile-infra:bondingInterface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_interface:

```
    Type: object
    Properties:
      tailf-mobile-infra:interface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor:

```
    Type: object
    Properties:
      tailf-mobile-infra:neighbors:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrarouter_neighbors'
        x-yang:
          Type: list
  ?
data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_fail-over

  : type: object
```

```
    Properties:
      tailf-mobile-infra:fail-over:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: bfd
        enum:
        - bfd
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_neighbor

  : type: object
    Properties:
      tailf-mobile-infra:neighbor:
        Type: string
        Description: (leaf)
        format: union
        x-yang:
          Type: leaf
  ?
data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_remote-as

  : type: object
    Properties:
      tailf-mobile-infra:remote-as:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_vrf:

    Type: object
    Properties:
      tailf-mobile-infra:vrf:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_learnDefaultRoute:
    Type: object
    Properties:
      tailf-mobile-infra:learnDefaultRoute:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackBFDPort:
    Type: object
```

```
    Properties:
      tailf-mobile-infra:loopbackBFDPort:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackPort:
    Type: object
    Properties:
      tailf-mobile-infra:loopbackPort:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name:

    Type: object
    Properties:
      tailf-mobile-infra:policies:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrarouter_policies'
        x-yang:
          Type: list

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_as-path-set:

    Type: object
    Properties:
      tailf-mobile-infra:as-path-set:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_gateWay:

    Type: object
    Properties:
      tailf-mobile-infra:gateWay:
        Type: string
        Description: (leaf)
        format: union
        x-yang:
          Type: leaf

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_interface:
```

```
    Type: object
    Properties:
      tailf-mobile-infra:interface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_ip-prefix:

```
    Type: object
    Properties:
      tailf-mobile-infra:ip-prefix:
        Type: string
        Description: (leaf)
        format: union
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_isStaticRoute:

```
    Type: object
    Properties:
      tailf-mobile-infra:isStaticRoute:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_mask-range:

```
    Type: object
    Properties:
      tailf-mobile-infra:mask-range:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_modifySourceIp:

```
    Type: object
    Properties:
      tailf-mobile-infra:modifySourceIp:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_policy-name:

```
      Type: object
      Properties:
        tailf-mobile-infra:policy-name:
          Type: string
          Description: (leaf)
          format: string
          x-yang:
            Type: leaf

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_source-prefix:

      Type: object
      Properties:
        tailf-mobile-infra:source-prefix:
          Type: string
          Description: (leaf)
          format: union
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend:
      Type: object
      Properties:
        tailf-mobile-infra:prepend:
          Reference: '#/components/schemas/datapost_tailfmobileinfrarouter_prepend'
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend-post:
      Type: object
      Properties:
        tailf-mobile-infra:as-path:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend_as-path:
      Type: object
      Properties:
        tailf-mobile-infra:as-path:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
    data_tailf-mobile-infra_router_monitor-interface:
      Type: object
      Properties:
        tailf-mobile-infra:monitor-interface:
         Reference: '#/components/schemas/datapost_tailfmobileinfrarouter_monitorinterface'

    data_tailf-mobile-infra_router_monitor-interface-post:
      Type: object
      Properties:
        tailf-mobile-infra:interface-list:
          Type: array
          Description: (list)
```

```
      Items:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrarouter_monitorinterface_interfacelist'
      x-yang:
        Type: list

data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface:

  Type: object
  Properties:
    tailf-mobile-infra:interface-list:
      Type: array
      Description: (list)
      Items:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrarouter_monitorinterface_interfacelist'
      x-yang:
        Type: list

data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface:

  Type: object
  Properties:
    tailf-mobile-infra:interface:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf

data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface-type:

  Type: object
  Properties:
    tailf-mobile-infra:interface-type:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf

data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_linked-interface:

  Type: object
  Properties:
    tailf-mobile-infra:linked-interface:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
  data_tailf-mobile-infra_rpc:
    Type: object
```

```
    Properties:
      tailf-mobile-infra:rpc:
        Reference: '#/components/schemas/datapost_tailfmobileinfrarpc'
  data_tailf-mobile-infra_rpc-post:
    Type: object
    Properties:
      tailf-mobile-infra:all:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrarpc_all'
        x-yang:
          Type: list
  data_tailf-mobile-infra_rpc_all:
    Type: object
    Properties:
      tailf-mobile-infra:all:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrarpc_all'
        x-yang:
          Type: list

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress:

    Type: object
    Properties:
      tailf-mobile-infra:all:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrarpc_all'
        x-yang:
          Type: list

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_connectedTime:

    Type: object
    Properties:
      tailf-mobile-infra:connectedTime:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_disconnectedTime:

    Type: object
    Properties:
      tailf-mobile-infra:disconnectedTime:
        Type: string
```

```
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_monitorRPCHost:

  Type: object
  Properties:
    tailf-mobile-infra:monitorRPCHost:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_name:

  Type: object
  Properties:
    tailf-mobile-infra:name:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_podInstance:

  Type: object
  Properties:
    tailf-mobile-infra:podInstance:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_processingInstanceInfo:

  Type: object
  Properties:
    tailf-mobile-infra:processingInstanceInfo:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_remoteAddress:

  Type: object
  Properties:
```

```
      tailf-mobile-infra:remoteAddress:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_remoteHost:

    Type: object
    Properties:
      tailf-mobile-infra:remoteHost:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_setName:

    Type: object
    Properties:
      tailf-mobile-infra:setName:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_status:

    Type: object
    Properties:
      tailf-mobile-infra:status:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_type:

    Type: object
    Properties:
      tailf-mobile-infra:type:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_version:
```

```
    Type: object
    Properties:
      tailf-mobile-infra:version:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_tailf-mobile-infra_rpc_all_all-podInstance_all-name_all-remoteAddress_vrf:

    Type: object
    Properties:
      tailf-mobile-infra:vrf:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_running-status:
    Type: object
    Properties:
      tailf-mobile-infra:running-status:
        Reference: '#/components/schemas/datapost_tailfmobileinfrarunningstatus'
  data_tailf-mobile-infra_running-status-post:
    Type: object
    Properties:
      tailf-mobile-infra:info:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrarunningstatus_info'
        x-yang:
          Type: list
  data_tailf-mobile-infra_running-status_info:
    Type: object
    Properties:
      tailf-mobile-infra:info:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrarunningstatus_info'
        x-yang:
          Type: list
  data_tailf-mobile-infra_running-status_info_info-podInstance:
    Type: object
    Properties:
      tailf-mobile-infra:info:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrarunningstatus_info'
```

```
      x-yang:
        Type: list
  data_tailf-mobile-infra_running-status_info_info-podInstance_podInstance:
    Type: object
    Properties:
      tailf-mobile-infra:podInstance:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
data_tailf-mobile-infra_running-status_info_info-podInstance_runningStatus:
    Type: object
    Properties:
      tailf-mobile-infra:runningStatus:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_running-status_info_info-podInstance_startTime:
    Type: object
    Properties:
      tailf-mobile-infra:startTime:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_running-status_info_info-podInstance_systemHealth:
    Type: object
    Properties:
      tailf-mobile-infra:systemHealth:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_sessions:
    Type: object
    Properties:
      tailf-mobile-infra:sessions:
        Reference: '#/components/schemas/datapost_tailfmobileinfrasessions'
  data_tailf-mobile-infra_sessions-post:
    Type: object
    Properties:
      tailf-mobile-infra:commit-pending:
```

```
      Type: array
      Description: (list)
      Items:
       Reference: '#/components/schemas/datapost_tailfmobileinfrasessions_commitpending'

      x-yang:
        Type: list
    tailf-mobile-infra:affinity:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfrasessions_affinity'
      x-yang:
        Type: list
  data_tailf-mobile-infra_sessions_affinity:
    Type: object
    Properties:
      tailf-mobile-infra:affinity:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrasessions_affinity'
        x-yang:
          Type: list
  data_tailf-mobile-infra_sessions_affinity_affinity-podInstance:
    Type: object
    Properties:
      tailf-mobile-infra:affinity:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrasessions_affinity'
        x-yang:
          Type: list
  data_tailf-mobile-infra_sessions_affinity_affinity-podInstance_count:
    Type: object
    Properties:
      tailf-mobile-infra:count:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_sessions_affinity_affinity-podInstance_podInstance:

    Type: object
    Properties:
      tailf-mobile-infra:podInstance:
        Type: string
        Description: (leaf)
        format: string
```

```
      x-yang:
        Type: leaf
  data_tailf-mobile-infra_sessions_commit-pending:
    Type: object
    Properties:
      tailf-mobile-infra:commit-pending:
        Type: array
        Description: (list)
        Items:
         Reference: '#/components/schemas/datapost_tailfmobileinfrasessions_commitpending'

        x-yang:
          Type: list

data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance:

    Type: object
    Properties:
      tailf-mobile-infra:commit-pending:
        Type: array
        Description: (list)
        Items:
         Reference: '#/components/schemas/datapost_tailfmobileinfrasessions_commitpending'

        x-yang:
          Type: list

data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_count:

    Type: object
    Properties:
      tailf-mobile-infra:count:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_dbBinarySize:

    Type: object
    Properties:
      tailf-mobile-infra:dbBinarySize:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf

data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_grInstance:

    Type: object
    Properties:
```

```
      tailf-mobile-infra:grInstance:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_lastDbSyncTime:

```
    Type: object
    Properties:
      tailf-mobile-infra:lastDbSyncTime:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_pendingCommit:

```
    Type: object
    Properties:
      tailf-mobile-infra:pendingCommit:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
```

data_tailf-mobile-infra_sessions_commit-pending_commit-pending-podInstance_commit-pending-grInstance_podInstance:

```
    Type: object
    Properties:
      tailf-mobile-infra:podInstance:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_show:
    Type: object
    Properties:
      tailf-mobile-infra:show:
        Type: object
        Properties: {}
        Description: (non-presence)
        x-yang:
          Type: container
          is_presence: 'false'
  data_tailf-mobile-infra_vrf:
    Type: object
    Properties:
      tailf-mobile-infra:vrf:
```

```
      Reference: '#/components/schemas/datapost_tailfmobileinfravrf'
data_tailf-mobile-infra_vrf-info:
  Type: object
  Properties:
    tailf-mobile-infra:vrf-info:
      Reference: '#/components/schemas/datapost_tailfmobileinfravrfinfo'
data_tailf-mobile-infra_vrf-info-post:
  Type: object
  Properties:
    tailf-mobile-infra:all:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfravrfinfo_all'
      x-yang:
        Type: list
data_tailf-mobile-infra_vrf-info_all:
  Type: object
  Properties:
    tailf-mobile-infra:all:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfravrfinfo_all'
      x-yang:
        Type: list
data_tailf-mobile-infra_vrf-info_all_all-name:
  Type: object
  Properties:
    tailf-mobile-infra:all:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfravrfinfo_all'
      x-yang:
        Type: list
data_tailf-mobile-infra_vrf-info_all_all-name_device:
  Type: object
  Properties:
    tailf-mobile-infra:device:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_all_all-name_gateway:
  Type: object
  Properties:
    tailf-mobile-infra:gateway:
      Type: string
      Description: (leaf)
```

```
      format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_all_all-name_gatewayIpv6:
  Type: object
  Properties:
    tailf-mobile-infra:gatewayIpv6:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_all_all-name_linkDevice:
  Type: object
  Properties:
    tailf-mobile-infra:linkDevice:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_all_all-name_name:
  Type: object
  Properties:
    tailf-mobile-infra:name:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_all_all-name_podName:
  Type: object
  Properties:
    tailf-mobile-infra:podName:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_all_all-name_state:
  Type: object
  Properties:
    tailf-mobile-infra:state:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-info_all_all-name_tableId:
  Type: object
  Properties:
    tailf-mobile-infra:tableId:
```

```
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf-post:
  Type: object
  Properties:
    tailf-mobile-infra:vrflist:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfravrf_vrflist'
      x-yang:
        Type: list
data_tailf-mobile-infra_vrf_vrflist_vrflist-name:
  Type: object
  Properties:
    tailf-mobile-infra:vrflist:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfravrf_vrflist'
      x-yang:
        Type: list
data_tailf-mobile-infra_vrf_vrflist_vrflist-name_device:
  Type: object
  Properties:
    tailf-mobile-infra:device:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gateway:
  Type: object
  Properties:
    tailf-mobile-infra:gateway:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gatewayIpv6:
  Type: object
  Properties:
    tailf-mobile-infra:gatewayIpv6:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
```

```
        Type: leaf
  data_tailf-mobile-infra_vrf_vrflist_vrflist-name_linkDevice:
    Type: object
    Properties:
      tailf-mobile-infra:linkDevice:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  data_tailf-mobile-infra_vrf_vrflist_vrflist-name_name:
    Type: object
    Properties:
      tailf-mobile-infra:name:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  operations:
    Type: object
    Properties:
      ietf-restconf:operations:
        Type: object
        Properties: {}
        Description: This resource is a container that provides access to the
data-model-specific
          RPC operations supported by the server. See RESTCONF RFC 8040 for further
          information.
        x-yang:
          Type: operations
  root:
    Type: object
    Properties:
      ietf-restconf:restconf:
        Reference: '#/components/schemas/root_ietfrestconfrestconf'
  yang-library-version:
    Type: object
    Properties:
      ietf-restconf:yang-library-version:
        Type: object
        Properties: {}
        Description: This leaf identifies the revision date of the 'ietf-yang-library'
          YANG module that is implemented by this server. See RESTCONF RFC 8040
          for further information.
        x-yang:
          Type: leaf
  datapost_tailfmobileinfrasessions_commitpending:
    Type: object
    Properties:
      podInstance:
        Type: string
```

```
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    grInstance:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    count:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    pendingCommit:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    dbBinarySize:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    lastDbSyncTime:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
datapost_tailfmobileinfrasessions_affinity:
  Type: object
  Properties:
    podInstance:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    count:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
datapost_tailfmobileinfrasessions:
  Type: object
```

```
  Properties:
    commit-pending:
      Type: array
      Description: (list)
      Items:
       Reference: '#/components/schemas/datapost_tailfmobileinfrasessions_commitpending'

      x-yang:
        Type: list
    affinity:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfrasessions_affinity'
      x-yang:
        Type: list
  Description: (non-presence)
datapost_tailfmobileinfrapeers_all:
  Type: object
  Properties:
    grInstance:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    endpoint:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    localAddress:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    peerAddress:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    direction:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    podInstance:
      Type: string
```

```
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    Type:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    connectedTime:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    rpc:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    additionalDetails:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    interfaceName:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    vrf:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
datapost_tailfmobileinfrapeers:
  Type: object
  Properties:
    all:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfrapeers_all'
      x-yang:
        Type: list
  Description: (non-presence)
```

```
datapost_tailfmobileinfrarpc_all:
  Type: object
  Properties:
    podInstance:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    name:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    remoteAddress:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    remoteHost:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    Type:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    setName:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    status:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    connectedTime:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
```

```
    disconnectedTime:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    monitorRPCHost:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    processingInstanceInfo:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    version:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    vrf:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
datapost_tailfmobileinfrarpc:
  Type: object
  Properties:
    all:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfrarpc_all'
      x-yang:
        Type: list
  Description: (non-presence)
datapost_tailfmobileinfraresources_info:
  Type: object
  Properties:
    podInstance:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    cpuUsage:
```

```
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    totalNodeMemoryInMB:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    usedPodMemoryInMB:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    diskUsageInKbps:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    goRoutinesCount:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    gcCount:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    gcPauseInNS:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
datapost_tailfmobileinfraresources:
  Type: object
  Properties:
    info:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfraresources_info'
      x-yang:
        Type: list
```

```
  Description: (non-presence)
datapost_tailfmobileinfrarunningstatus_info:
  Type: object
  Properties:
    podInstance:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    runningStatus:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    systemHealth:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    startTime:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
datapost_tailfmobileinfrarunningstatus:
  Type: object
  Properties:
    info:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfrarunningstatus_info'
      x-yang:
        Type: list
  Description: (non-presence)
datapost_tailfmobileinfradiagnostics_info:
  Type: object
  Properties:
    podInstance:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    diagnostic:
      Type: string
      Description: (leaf)
```

```
      format: string
      x-yang:
        Type: leaf
    component:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    startTime:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    status:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    retries:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
datapost_tailfmobileinfradiagnostics:
  Type: object
  Properties:
    info:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfradiagnostics_info'
      x-yang:
        Type: list
  Description: (non-presence)
datapost_tailfmobileinfrainfra_metrics_experimental:
  Type: object
  Properties:
    version:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinfrainfra_metrics_verbose_pods_podnames:
  Type: object
  Properties:
```

```
      pod-name:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
      level:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: production
        enum:
        - production
        - debug
        - trace
        - 'off'
        x-yang:
          Type: leaf
  datapost_tailfmobileinfrainfra_metrics_verbose_pods:
    Type: object
    Properties:
      pod-names:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_pods_podnames'
        x-yang:
          Type: list
    Description: (non-presence)
  datapost_tailfmobileinfrainfra_metrics_verbose_metrics_metricsList:
    Type: object
    Properties:
      name:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
      level:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: production
        enum:
        - production
        - debug
        - trace
        - 'off'
        x-yang:
          Type: leaf
      granular-labels:
        Type: array
```

```
        Items:
          Type: string
          Description: (leaf-list)
          format: string
        x-yang:
          Type: leaf-list
    datapost_tailfmobileinfrainfra_metrics_verbose_metrics:
      Type: object
      Properties:
        metricsList:
          Type: array
          Description: (list)
          Items:
            Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_metrics_metricsList'
        x-yang:
          Type: list
      Description: (non-presence)
    datapost_tailfmobileinfrainfra_metrics_verbose_verboseLevels:
      Type: object
      Properties:
        podType:
          Type: string
          Description: (leaf)
          format: enumeration
          Default: protocol
          enum:
          - protocol
          - load-balancer
          - service
          - application
          x-yang:
            Type: leaf
        pods:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_pods'
        level:
          Type: string
          Description: (leaf)
          format: enumeration
          Default: production
          enum:
          - production
          - debug
          - trace
          - 'off'
          x-yang:
            Type: leaf
        metrics:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_metrics'
    datapost_tailfmobileinfrainfra_metrics_verbose:
      Type: object
      Properties:
```

```
      verboseLevels:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose_verboseLevels'
        x-yang:
          Type: list
    Description: (non-presence)
  datapost_tailfmobileinfrainfra_metrics:
    Type: object
    Properties:
      experimental:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_metrics_experimental'
      verbose:
        Reference: '#/components/schemas/datapost_tailfmobileinfrainfra_metrics_verbose'

    Description: (non-presence)
  datapost_tailfmobileinfrainfra_transaction_limit_consecutive_same:
    Type: object
    Properties:
      stage:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfrainfra_transaction_limit_consecutive:
    Type: object
    Properties:
      same:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_transaction_limit_consecutive_same'
    Description: (non-presence)
  datapost_tailfmobileinfrainfra_transaction_limit:
    Type: object
    Properties:
      stage:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
      consecutive:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_transaction_limit_consecutive'
    Description: (non-presence)
  datapost_tailfmobileinfrainfra_transaction_loop_threshold_thresholds:
    Type: object
    Properties:
```

```
      name:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: low
        enum:
        - low
        - high
        x-yang:
          Type: leaf
      count:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
      action:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: noop
        enum:
        - noop
        - log-event
        - kill-session
        x-yang:
          Type: leaf
  datapost_tailfmobileinfrainfra_transaction_loop_threshold:
    Type: object
    Properties:
      interval:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
      thresholds:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_transaction_loop_threshold_thresholds'

        x-yang:
          Type: list
    Description: (non-presence)
  datapost_tailfmobileinfrainfra_transaction_loop_category:
    Type: object
    Properties:
      name:
        Type: string
        Description: (leaf)
        format: identityref
```

```
      x-yang:
        Type: leaf
    threshold:
      Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_transaction_loop_threshold'
  datapost_tailfmobileinfrainfra_transaction_loop:
    Type: object
    Properties:
      detection:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: enable
        enum:
        - enable
        - disable
        x-yang:
          Type: leaf
      category:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainfra_transaction_loop_category'
        x-yang:
          Type: list
    Description: (non-presence)
  datapost_tailfmobileinfrainfra_transaction:
    Type: object
    Properties:
      limit:
       Reference: '#/components/schemas/datapost_tailfmobileinfrainfra_transaction_limit'

      loop:
       Reference: '#/components/schemas/datapost_tailfmobileinfrainfra_transaction_loop'

    Description: (non-presence)
  datapost_tailfmobileinfrainfra:
    Type: object
    Properties:
      metrics:
        Reference: '#/components/schemas/datapost_tailfmobileinfrainfra_metrics'
      transaction:
        Reference: '#/components/schemas/datapost_tailfmobileinfrainfra_transaction'
    Description: (non-presence)
  datapost_tailfmobileinfraclient_http_header:
    Type: object
    Properties:
      user-agent:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: cluster-name
```

```
      enum:
      - cluster-name
      - app-name
      - disable
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinfraclient_http_ping:
  Type: object
  Properties:
    timeout:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    interval:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinfraclient_http:
  Type: object
  Properties:
    header:
      Reference: '#/components/schemas/datapost_tailfmobileinfraclient_http_header'
    ping:
      Reference: '#/components/schemas/datapost_tailfmobileinfraclient_http_ping'
  Description: (non-presence)
datapost_tailfmobileinfraclient_outbound_limit_pending:
  Type: object
  Properties:
    response:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinfraclient_outbound_limit_consecutive_failure:
  Type: object
  Properties:
    count:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    codes:
      Type: array
```

```
        Items:
          Type: string
          Description: (leaf-list)
          format: string
        x-yang:
          Type: leaf-list
    Description: (non-presence)
  datapost_tailfmobileinfraclient_outbound_limit_consecutive:
    Type: object
    Properties:
      failure:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_consecutive_failure'
    Description: (non-presence)
  datapost_tailfmobileinfraclient_outbound_limit:
    Type: object
    Properties:
      pending:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_pending'
      consecutive:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit_consecutive'
    Description: (non-presence)
  datapost_tailfmobileinfraclient_outbound_host_ping:
    Type: object
    Properties:
      timeout:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      interval:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      backoff:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      retry:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      fast-interval:
```

```
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    all-host-down-interval:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
  Description: (non-presence)
 datapost_tailfmobileinfraclient_outbound_host:
  Type: object
  Properties:
    ping:
     Reference: '#/components/schemas/datapost_tailfmobileinfraclient_outbound_host_ping'

  Description: (non-presence)
 datapost_tailfmobileinfraclient_outbound_interface:
  Type: object
  Properties:
    interface:
      Type: string
      Description: (leaf)
      format: identityref
      x-yang:
        Type: leaf
    limit:
      Reference: '#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit'

    host:
      Reference: '#/components/schemas/datapost_tailfmobileinfraclient_outbound_host'
 datapost_tailfmobileinfraclient_outbound:
  Type: object
  Properties:
    interface:
      Type: array
      Description: (list)
      Items:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_outbound_interface'
      x-yang:
        Type: list
    limit:
      Reference: '#/components/schemas/datapost_tailfmobileinfraclient_outbound_limit'

    host:
      Reference: '#/components/schemas/datapost_tailfmobileinfraclient_outbound_host'
  Description: (non-presence)
 datapost_tailfmobileinfraclient_inbound_limit_pending:
  Type: object
```

```
    Properties:
      request:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      Description: (non-presence)
    datapost_tailfmobileinfraclient_inbound_limit_overload:
      Type: object
      Properties:
        reject-code:
          Type: integer
          Description: (leaf)
          format: int32
          x-yang:
            Type: leaf
      Description: (non-presence)
    datapost_tailfmobileinfraclient_inbound_limit:
      Type: object
      Properties:
        pending:
          Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit_pending'
        overload:
          Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit_overload'
      Description: (non-presence)
    datapost_tailfmobileinfraclient_inbound_interface:
      Type: object
      Properties:
        interface:
          Type: string
          Description: (leaf)
          format: identityref
          x-yang:
            Type: leaf
        limit:
          Reference: '#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit'
    datapost_tailfmobileinfraclient_inbound:
      Type: object
      Properties:
        interface:
          Type: array
          Description: (list)
          Items:
            Reference:
'#/components/schemas/datapost_tailfmobileinfraclient_inbound_interface'
          x-yang:
            Type: list
        limit:
          Reference: '#/components/schemas/datapost_tailfmobileinfraclient_inbound_limit'
```

```
  Description: (non-presence)
datapost_tailfmobileinfraclient:
  Type: object
  Properties:
    http:
      Reference: '#/components/schemas/datapost_tailfmobileinfraclient_http'
    outbound:
      Reference: '#/components/schemas/datapost_tailfmobileinfraclient_outbound'
    inbound:
      Reference: '#/components/schemas/datapost_tailfmobileinfraclient_inbound'
  Description: (non-presence)
datapost_tailfmobileinfraedr_edrsubscribers:
  Type: object
  Properties:
    subscribers:
      Type: array
      Items:
        Type: string
        Description: (leaf-list)
        format: string
      x-yang:
        Type: leaf-list
  Description: (non-presence)
datapost_tailfmobileinfraedr_all:
  Type: object
  Properties:
    subscribers:
      Type: string
      Description: (leaf)
      format: '[null]'
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinfraedr_file_limit:
  Type: object
  Properties:
    size:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    count:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    storage:
      Type: integer
      Description: (leaf)
```

```
        format: int32
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfraedr_file_threshold:
    Type: object
    Properties:
      cpu:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      session:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfraedr_file_flush:
    Type: object
    Properties:
      interval:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfraedr_file_procedure_enableinner_event_enable:
    Type: object
    Properties:
      field:
        Type: array
        Items:
          Type: string
          Description: (leaf-list)
          format: string
        x-yang:
          Type: leaf-list
    Description: (non-presence)

datapost_tailfmobileinfraedr_file_procedure_enableinner_event_enablefieldid:

    Type: object
    Properties:
      event:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
```

```
        Type: leaf
      enable:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraedr_file_procedure_enableinner_event_enable'

  datapost_tailfmobileinfraedr_file_procedure_enableinner_event:
    Type: object
    Properties:
      enable-field-id:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfraedr_file_procedure_enableinner_event_enablefieldid'

        x-yang:
          Type: list
    Description: (non-presence)
  datapost_tailfmobileinfraedr_file_procedure_enableinner:
    Type: object
    Properties:
      event:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraedr_file_procedure_enableinner_event'
    Description: (non-presence)
  datapost_tailfmobileinfraedr_file_procedure_enableeventid:
    Type: object
    Properties:
      procedure:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
      enable-inner:
        Reference:
'#/components/schemas/datapost_tailfmobileinfraedr_file_procedure_enableinner'
  datapost_tailfmobileinfraedr_file_procedure:
    Type: object
    Properties:
      enable-event-id:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfraedr_file_procedure_enableeventid'
        x-yang:
          Type: list
    Description: (non-presence)
  datapost_tailfmobileinfraedr_file_files:
    Type: object
    Properties:
      name:
```

```
      Type: string
      Description: (leaf)
      format: identityref
      x-yang:
        Type: leaf
    reporting:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
    verbose:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
    limit:
      Reference: '#/components/schemas/datapost_tailfmobileinfraedr_file_limit'
    rate:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    threshold:
      Reference: '#/components/schemas/datapost_tailfmobileinfraedr_file_threshold'
    flush:
      Reference: '#/components/schemas/datapost_tailfmobileinfraedr_file_flush'
    procedure:
      Reference: '#/components/schemas/datapost_tailfmobileinfraedr_file_procedure'
datapost_tailfmobileinfraedr_file:
  Type: object
  Properties:
    files:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfraedr_file_files'
      x-yang:
        Type: list
  Description: (non-presence)
datapost_tailfmobileinfraedr:
  Type: object
```

```
  Properties:
    reporting:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
    edrsubscribers:
      Reference: '#/components/schemas/datapost_tailfmobileinfraedr_edrsubscribers'
    all:
      Reference: '#/components/schemas/datapost_tailfmobileinfraedr_all'
    file:
      Reference: '#/components/schemas/datapost_tailfmobileinfraedr_file'
  Description: (non-presence)
datapost_tailfmobileinfrainstance_endpoint_vip:
  Type: object
  Properties:
    vip-ip:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    vip-port:
      Type: integer
      Description: (leaf)
      format: uint16
      x-yang:
        Type: leaf
    vip-interface:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    offline:
      Type: string
      Description: (leaf)
      format: '[null]'
      x-yang:
        Type: leaf
    vrf:
      Type: string
      Description: (leaf)
      format: leafref
      x-yang:
        Type: leaf
datapost_tailfmobileinfrainstance_endpoint_vip6:
```

```
    Type: object
    Properties:
      vip-ipv6:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
      vip-ipv6-port:
        Type: integer
        Description: (leaf)
        format: uint16
        x-yang:
          Type: leaf
      vip-interface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
      offline:
        Type: string
        Description: (leaf)
        format: '[null]'
        x-yang:
          Type: leaf
      vrf:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
  datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel_warn:
    Type: object
    Properties:
      cpu-percent:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      memory-in-mbs:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      num-of-goroutine:
        Type: integer
        Description: (leaf)
        format: int32
```

```
      x-yang:
        Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel:
    Type: object
    Properties:
      warn:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel_warn'
      critical:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel_warn'
      crash:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel_warn'
    Description: (non-presence)
  datapost_tailfmobileinfrainstance_endpoint_monitor:
    Type: object
    Properties:
      protocol:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: 'on'
        enum:
        - 'on'
        - 'off'
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfrainstance_endpoint_sla:
    Type: object
    Properties:
      response:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      procedure:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfrainstance_endpoint_secvip:
    Type: object
    Properties:
      sec-vip-ip:
        Type: string
        Description: (leaf)
```

```
      format: string
      x-yang:
        Type: leaf
    vip-port:
      Type: integer
      Description: (leaf)
      format: uint16
      x-yang:
        Type: leaf
    vip-interface:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    offline:
      Type: string
      Description: (leaf)
      format: '[null]'
      x-yang:
        Type: leaf
    vrf:
      Type: string
      Description: (leaf)
      format: leafref
      x-yang:
        Type: leaf
datapost_tailfmobileinfrainstance_endpoint_secvip6:
  Type: object
  Properties:
    sec-vip-ipv6:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    vip-ipv6-port:
      Type: integer
      Description: (leaf)
      format: uint16
      x-yang:
        Type: leaf
    vip-interface:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    offline:
      Type: string
      Description: (leaf)
```

```
      format: '[null]'
      x-yang:
        Type: leaf
    vrf:
      Type: string
      Description: (leaf)
      format: leafref
      x-yang:
        Type: leaf
datapost_tailfmobileinfrainstance_endpoint_dispatcher_flowctrlgroup:
  Type: object
  Properties:
    name:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    capacity:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    rate-limit:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    outbound-capacity:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    outbound-rate-limit:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
datapost_tailfmobileinfrainstance_endpoint_dispatcher:
  Type: object
  Properties:
    count:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
```

```
      capacity:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      outbound:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
      rate-limit:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      cache:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
      threshold:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      expiry:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      nonresponsive:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      flowctrl-group:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_dispatcher_flowctrlgroup'
        x-yang:
          Type: list
    Description: (non-presence)
  datapost_tailfmobileinfrainstance_endpoint_internal_baseport:
    Type: object
    Properties:
```

```
      start:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfrainstance_endpoint_internal:
    Type: object
    Properties:
      base-port:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal_baseport'
    Description: (non-presence)
  datapost_tailfmobileinfrainstance_endpoint_interface:
    Type: object
    Properties:
      interface-type:
        Type: string
        Description: (leaf)
        format: identityref
        x-yang:
          Type: leaf
      loopbackEth:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
      loopbackPort:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      uri-scheme:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: http
        enum:
        - http
        - https
        x-yang:
          Type: leaf
      instancetype:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: IPv4
        enum:
        - IPv4
```

```
        - IPv6
        - Dual
        x-yang:
          Type: leaf
      tls-enable:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
      mtls-enable:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
      certificate-name:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
      sla:
        Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_sla'

      vip:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_vip'

        x-yang:
          Type: list
      sec-vip:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_secvip'
        x-yang:
          Type: list
      vip6:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_vip6'

        x-yang:
          Type: list
      sec-vip6:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_secvip6'
```

```
      x-yang:
        Type: list
    vrf:
      Type: string
      Description: (leaf)
      format: leafref
      x-yang:
        Type: leaf
    dispatcher:
      Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_dispatcher'
    monitor:
     Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_monitor'

    internal:
      Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal'
 datapost_tailfmobileinfrainstance_endpoint_service:
   Type: object
   Properties:
    service-name:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    interface:
      Type: array
      Description: (list)
      Items:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_interface'
      x-yang:
        Type: list
 datapost_tailfmobileinfrainstance_endpoint_ep:
   Type: object
   Properties:
    eptype:
      Type: string
      Description: (leaf)
      format: identityref
      x-yang:
        Type: leaf
    replicas:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    nodes:
      Type: integer
      Description: (leaf)
```

```
        format: int32
        x-yang:
          Type: leaf
      loopbackEth:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
      loopbackPort:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      instancetype:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: IPv4
        enum:
        - IPv4
        - IPv6
        - Dual
        x-yang:
          Type: leaf
      vip:
        Type: array
        Description: (list)
        Items:
         Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_vip'

        x-yang:
          Type: list
      vip6:
        Type: array
        Description: (list)
        Items:
         Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_vip6'

        x-yang:
          Type: list
      system-health-level:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_systemhealthlevel'
      monitor:
       Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_monitor'

      uri-scheme:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: http
```

```
        enum:
        - http
        - https
        x-yang:
          Type: leaf
      mtls-enable:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
      certificate-name:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
      service:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_service'
        x-yang:
          Type: list
      interface:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_interface'
        x-yang:
          Type: list
      internal:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_internal'
  datapost_tailfmobileinfrainstance_endpoint:
    Type: object
    Properties:
      ep:
        Type: array
        Description: (list)
        Items:
         Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint_ep'

        x-yang:
          Type: list
    Description: (non-presence)
  datapost_tailfmobileinfrainstance_instanceid:
    Type: object
    Properties:
      id:
        Type: string
        Description: (leaf)
```

```
      format: leafref
      x-yang:
        Type: leaf
    endpoint:
      Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_endpoint'
datapost_tailfmobileinfrainstance:
  Type: object
  Properties:
    instance-id:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfrainstance_instanceid'

      x-yang:
        Type: list
  Description: (non-presence)
datapost_tailfmobileinfraendpoint_info:
  Type: object
  Properties:
    grInstance:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    endpoint:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    address:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    Type:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    status:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    Interface:
      Type: string
```

```
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    internal:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    startTime:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    stoppedTime:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    vrf:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
datapost_tailfmobileinfraendpoint:
  Type: object
  Properties:
    info:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfraendpoint_info'
      x-yang:
        Type: list
    all:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfraendpoint_info'
      x-yang:
        Type: list
  Description: (non-presence)
datapost_tailfmobileinfravrf_vrflist:
  Type: object
  Properties:
    name:
      Type: string
```

```
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    gateway:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    gatewayIpv6:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    device:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    linkDevice:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
datapost_tailfmobileinfravrf:
  Type: object
  Properties:
    vrflist:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfravrf_vrflist'
      x-yang:
        Type: list
  Description: (non-presence)
datapost_tailfmobileinfravrfinfo_all:
  Type: object
  Properties:
    name:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    gateway:
      Type: string
      Description: (leaf)
```

```
      format: string
      x-yang:
        Type: leaf
    gatewayIpv6:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    device:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    linkDevice:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    tableId:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    state:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    podName:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
datapost_tailfmobileinfravrfinfo:
  Type: object
  Properties:
    all:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfravrfinfo_all'
      x-yang:
        Type: list
  Description: (non-presence)
datapost_tailfmobileinfralogging_transaction:
  Type: object
```

```
  Properties:
    persist:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
    max-file-size:
      Type: integer
      Description: (leaf)
      format: uint32
      x-yang:
        Type: leaf
    max-rotation:
      Type: integer
      Description: (leaf)
      format: uint32
      x-yang:
        Type: leaf
    message:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
    duplicate:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfralogging_level:
    Type: object
    Properties:
      application:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: trace
        enum:
```

```
        - trace
        - debug
        - info
        - warn
        - error
        - 'off'
        x-yang:
          Type: leaf
      transaction:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: trace
        enum:
        - trace
        - debug
        - info
        - warn
        - error
        - 'off'
        x-yang:
          Type: leaf
      tracing:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: trace
        enum:
        - trace
        - debug
        - info
        - warn
        - error
        - 'off'
        x-yang:
          Type: leaf
      monitor-subscriber:
        Type: string
        Description: (leaf)
        format: enumeration
        Default: trace
        enum:
        - trace
        - debug
        - info
        - warn
        - error
        - 'off'
        x-yang:
          Type: leaf
    Description: (non-presence)
datapost_tailfmobileinfralogging_logger:
    Type: object
    Properties:
      name:
        Type: string
```

```
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    level:
      Reference: '#/components/schemas/datapost_tailfmobileinfralogging_level'
  datapost_tailfmobileinfralogging_async_application_enable:
    Type: object
    Properties:
      buffer-size:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfralogging_async_application:
    Type: object
    Properties:
      enable:
        Reference:
'#/components/schemas/datapost_tailfmobileinfralogging_async_application_enable'
      disable:
        Type: string
        Description: (leaf)
        format: '[null]'
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfralogging_async:
    Type: object
    Properties:
      application:
       Reference: '#/components/schemas/datapost_tailfmobileinfralogging_async_application'

      transaction:
       Reference: '#/components/schemas/datapost_tailfmobileinfralogging_async_application'

      tracing:
       Reference: '#/components/schemas/datapost_tailfmobileinfralogging_async_application'

      monitor-subscriber:
       Reference: '#/components/schemas/datapost_tailfmobileinfralogging_async_application'

    Description: (non-presence)
  datapost_tailfmobileinfralogging_error:
    Type: object
    Properties:
      stack:
        Type: string
        Description: (leaf)
        format: enumeration
```

```
      Default: enable
      enum:
      - enable
      - disable
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinfralogging:
  Type: object
  Properties:
    transaction:
      Reference: '#/components/schemas/datapost_tailfmobileinfralogging_transaction'
    level:
      Reference: '#/components/schemas/datapost_tailfmobileinfralogging_level'
    logger:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfralogging_logger'
      x-yang:
        Type: list
    async:
      Reference: '#/components/schemas/datapost_tailfmobileinfralogging_async'
    error:
      Reference: '#/components/schemas/datapost_tailfmobileinfralogging_error'
  Description: (non-presence)
datapost_tailfmobileinfranodemonitor:
  Type: object
  Properties:
    mode:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: '0'
      enum:
      - '0'
      - '1'
      - '2'
      - '3'
      x-yang:
        Type: leaf
    interval:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinframonitor_bfd:
  Type: object
  Properties:
    node-status:
      Type: string
```

```
      Description: (leaf)
      format: '[null]'
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinframonitor_protocol:
  Type: object
  Properties:
    cpu-limit:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinframonitor:
  Type: object
  Properties:
    bfd:
      Reference: '#/components/schemas/datapost_tailfmobileinframonitor_bfd'
    protocol:
      Reference: '#/components/schemas/datapost_tailfmobileinframonitor_protocol'
  Description: (non-presence)
datapost_tailfmobileinfrarouter_prepend:
  Type: object
  Properties:
    as-path:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinfrarouter_bondingInterfaces:
  Type: object
  Properties:
    bondingInterface:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
datapost_tailfmobileinfrarouter_neighbors:
  Type: object
  Properties:
    neighbor:
      Type: string
      Description: (leaf)
      format: union
      x-yang:
        Type: leaf
    remote-as:
```

```
      Type: integer
      Description: (leaf)
      format: uint32
      x-yang:
        Type: leaf
    fail-over:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: bfd
      enum:
      - bfd
      x-yang:
        Type: leaf
  datapost_tailfmobileinfrarouter_interfaceList:
    Type: object
    Properties:
      interface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
      bondingInterfaces:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrarouter_bondingInterfaces'
        x-yang:
          Type: list
      vrf:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
      neighbors:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrarouter_neighbors'
        x-yang:
          Type: list
  datapost_tailfmobileinfrarouter_policies:
    Type: object
    Properties:
      policy-name:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
```

```
        Type: leaf
      as-path-set:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
      ip-prefix:
        Type: string
        Description: (leaf)
        format: union
        x-yang:
          Type: leaf
      source-prefix:
        Type: string
        Description: (leaf)
        format: union
        x-yang:
          Type: leaf
      mask-range:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
      interface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
      modifySourceIp:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
      isStaticRoute:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
      gateWay:
        Type: string
        Description: (leaf)
        format: union
        x-yang:
          Type: leaf
  datapost_tailfmobileinfrarouter_bfd:
    Type: object
    Properties:
      interval:
```

```
      Type: integer
      Description: (leaf)
      format: uint32
      x-yang:
        Type: leaf
    min_rx:
      Type: integer
      Description: (leaf)
      format: uint32
      x-yang:
        Type: leaf
    multiplier:
      Type: integer
      Description: (leaf)
      format: uint32
      x-yang:
        Type: leaf
    dscp-marking:
      Type: string
      Description: (leaf)
      format: enumeration
      Default: none
      enum:
      - none
      - cs6
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinfrarouter_bgplist:
  Type: object
  Properties:
    bgp:
      Type: integer
      Description: (leaf)
      format: uint32
      x-yang:
        Type: leaf
    loopbackPort:
      Type: integer
      Description: (leaf)
      format: uint32
      x-yang:
        Type: leaf
    loopbackBFDPort:
      Type: integer
      Description: (leaf)
      format: uint32
      x-yang:
        Type: leaf
    learnDefaultRoute:
      Type: boolean
      Description: (leaf)
```

```
      x-yang:
        Type: leaf
    prepend:
      Reference: '#/components/schemas/datapost_tailfmobileinfrarouter_prepend'
    interfaceList:
      Type: array
      Description: (list)
      Items:
       Reference: '#/components/schemas/datapost_tailfmobileinfrarouter_interfaceList'

      x-yang:
        Type: list
    policies:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfrarouter_policies'
      x-yang:
        Type: list
    bfd:
      Reference: '#/components/schemas/datapost_tailfmobileinfrarouter_bfd'
  datapost_tailfmobileinfrarouter_bfd_1_instance_neighbors:
    Type: object
    Properties:
      neighbor:
        Type: string
        Description: (leaf)
        format: union
        x-yang:
          Type: leaf
  datapost_tailfmobileinfrarouter_bfd_1_instance_interfacelist:
    Type: object
    Properties:
      interface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
      vrf:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
      neighbors:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1_instance_neighbors'
        x-yang:
```

```
        Type: list
      gateway-ip:
        Type: string
        Description: (leaf)
        format: union
        x-yang:
          Type: leaf
  datapost_tailfmobileinfrarouter_bfd_1_instance_instanceid:
    Type: object
    Properties:
      id:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
      interface-list:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1_instance_interfacelist'
        x-yang:
          Type: list
  datapost_tailfmobileinfrarouter_bfd_1_instance:
    Type: object
    Properties:
      instance-id:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1_instance_instanceid'
        x-yang:
          Type: list
    Description: (non-presence)
  datapost_tailfmobileinfrarouter_bfd_1:
    Type: object
    Properties:
      instance:
        Reference: '#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1_instance'

    Description: (non-presence)
  datapost_tailfmobileinfrarouter_monitorinterface_interfacelist:
    Type: object
    Properties:
      interface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

```
      linked-interface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
      interface-type:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  datapost_tailfmobileinfrarouter_monitorinterface:
    Type: object
    Properties:
      interface-list:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrarouter_monitorinterface_interfacelist'
        x-yang:
          Type: list
    Description: (non-presence)
  datapost_tailfmobileinfrarouter:
    Type: object
    Properties:
      bgplist:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrarouter_bgplist'
        x-yang:
          Type: list
      bfd:
        Reference: '#/components/schemas/datapost_tailfmobileinfrarouter_bfd_1'
      monitor-interface:
       Reference: '#/components/schemas/datapost_tailfmobileinfrarouter_monitorinterface'

    Description: (non-presence)
  datapost_tailfmobileinfradeployment_resource:
    Type: object
    Properties:
      cpu:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfradeployment:
    Type: object
```

```
  Properties:
    app-name:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    cluster-name:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    dc-name:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    model:
      Type: string
      Description: Deployment Model default large (leaf)
      format: enumeration
      Default: small
      enum:
      - small
      x-yang:
        Type: leaf
    resource:
      Reference: '#/components/schemas/datapost_tailfmobileinfradeployment_resource'
    logical-nf-instance-id:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinfrak8_label_podgroupconfig:
  Type: object
  Properties:
    pod-group:
      Type: string
      Description: Group for the VMs (leaf)
      format: enumeration
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
      x-yang:
        Type: leaf
```

```
    key:
      Type: string
      Description: Key for the label (leaf)
      format: string
      x-yang:
        Type: leaf
    value:
      Type: string
      Description: Value for the label (leaf)
      format: string
      x-yang:
        Type: leaf
datapost_tailfmobileinfrak8_label:
  Type: object
  Properties:
    pod-group-config:
      Type: array
      Description: (list)
      Items:
       Reference: '#/components/schemas/datapost_tailfmobileinfrak8_label_podgroupconfig'

      x-yang:
        Type: list
  Description: (non-presence)
datapost_tailfmobileinfrak8:
  Type: object
  Properties:
    label:
      Reference: '#/components/schemas/datapost_tailfmobileinfrak8_label'
  Description: (non-presence)
datapost_tailfmobileinfraconfigerror_info:
  Type: object
  Properties:
    errorComponent:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    errorDescription:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
datapost_tailfmobileinfraconfigerror:
  Type: object
  Properties:
    info:
      Type: array
      Description: (list)
      Items:
```

```
        Reference: '#/components/schemas/datapost_tailfmobileinfraconfigerror_info'
      x-yang:
        Type: list
  Description: (non-presence)
datapost_tailfmobileinfraresource_cpu:
  Type: object
  Properties:
    request:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    limit:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinfraresource_labels:
  Type: object
  Properties:
    key:
      Type: string
      Description: Key for the label (leaf)
      format: string
      x-yang:
        Type: leaf
    value:
      Type: string
      Description: Value for the label (leaf)
      format: string
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_tailfmobileinfraresource_pod:
  Type: object
  Properties:
    podtype:
      Type: string
      Description: (leaf)
      format: identityref
      x-yang:
        Type: leaf
    cpu:
      Reference: '#/components/schemas/datapost_tailfmobileinfraresource_cpu'
    memory:
      Reference: '#/components/schemas/datapost_tailfmobileinfraresource_cpu'
    gomaxproc:
      Type: integer
```

```
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    labels:
      Reference: '#/components/schemas/datapost_tailfmobileinfraresource_labels'
datapost_tailfmobileinfraresource:
  Type: object
  Properties:
    pod:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_tailfmobileinfraresource_pod'
      x-yang:
        Type: list
  Description: (non-presence)
datapost_tailfmobileinfrageomonitor_podmonitor_pods:
  Type: object
  Properties:
    name:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    retryCount:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    retryInterval:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    retryFailOverInterval:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    failedReplicaPercent:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
datapost_tailfmobileinfrageomonitor_podmonitor:
```

```
    Type: object
    Properties:
      pods:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrageomonitor_podmonitor_pods'
        x-yang:
          Type: list
    Description: (non-presence)
  datapost_tailfmobileinfrageomonitor_remoteclustermonitor:
    Type: object
    Properties:
      retryCount:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      retryInterval:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfrageomonitor_vipmonitor_vips:
    Type: object
    Properties:
      vipInterface:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
      vipIp:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
      vipPort:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      retryCount:
        Type: integer
        Description: (leaf)
        format: int32
```

```
      x-yang:
        Type: leaf
    retryInterval:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
    retryFailOverInterval:
      Type: integer
      Description: (leaf)
      format: int32
      x-yang:
        Type: leaf
  datapost_tailfmobileinfrageomonitor_vipmonitor_instance:
    Type: object
    Properties:
      instance-id:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      vips:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrageomonitor_vipmonitor_vips'
        x-yang:
          Type: list
  datapost_tailfmobileinfrageomonitor_vipmonitor:
    Type: object
    Properties:
      instance:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfrageomonitor_vipmonitor_instance'
        x-yang:
          Type: list
    Description: (non-presence)
  datapost_tailfmobileinfrageomonitor_trafficMonitor:
    Type: object
    Properties:
      thresholdCount:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
```

```
      thresholdInterval:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfrageomonitor:
    Type: object
    Properties:
      podmonitor:
        Reference: '#/components/schemas/datapost_tailfmobileinfrageomonitor_podmonitor'

      remoteclustermonitor:
        Reference:
'#/components/schemas/datapost_tailfmobileinfrageomonitor_remoteclustermonitor'
      vipmonitor:
        Reference: '#/components/schemas/datapost_tailfmobileinfrageomonitor_vipmonitor'

      trafficMonitor:
       Reference: '#/components/schemas/datapost_tailfmobileinfrageomonitor_trafficMonitor'

    Description: (non-presence)
  datapost_tailfmobileinfrainstances_instance:
    Type: object
    Properties:
      instance-id:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
      system-id:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
      cluster-id:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
      slice-name:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  datapost_tailfmobileinfrainstances:
    Type: object
```

```
    Properties:
      instance:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfrainstances_instance'
        x-yang:
          Type: list
    Description: (non-presence)
  datapost_tailfmobileinfralocalinstance:
    Type: object
    Properties:
      instance:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfradatastore_sessiondb_endpoints:
    Type: object
    Properties:
      host:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
      port:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
  datapost_tailfmobileinfradatastore_sessiondb:
    Type: object
    Properties:
      endpoints:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfradatastore_sessiondb_endpoints'
        x-yang:
          Type: list
    Description: (non-presence)
  datapost_tailfmobileinfradatastore_dbs:
    Type: object
    Properties:
      name:
        Type: string
        Description: (leaf)
```

```
        format: string
        x-yang:
          Type: leaf
      endpoints:
        Type: array
        Description: (list)
        Items:
          Reference:
'#/components/schemas/datapost_tailfmobileinfradatastore_sessiondb_endpoints'
        x-yang:
          Type: list
  datapost_tailfmobileinfradatastore_notificationep:
    Type: object
    Properties:
      host:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
      port:
        Type: integer
        Description: (leaf)
        format: int32
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_tailfmobileinfradatastore:
    Type: object
    Properties:
      session-db:
        Reference: '#/components/schemas/datapost_tailfmobileinfradatastore_sessiondb'
      dbs:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_tailfmobileinfradatastore_dbs'
        x-yang:
          Type: list
      notification-ep:
       Reference: '#/components/schemas/datapost_tailfmobileinfradatastore_notificationep'

    Description: (non-presence)
  dataputpatch_ietfrestconfdata:
    Type: object
    Properties:
      tailf-mobile-infra:sessions:
        Reference: '#/components/schemas/datapost_tailfmobileinfrasessions'
      tailf-mobile-infra:peers:
        Reference: '#/components/schemas/datapost_tailfmobileinfrapeers'
      tailf-mobile-infra:rpc:
        Reference: '#/components/schemas/datapost_tailfmobileinfrarpc'
```

```
tailf-mobile-infra:resources:
  Reference: '#/components/schemas/datapost_tailfmobileinfraresources'
tailf-mobile-infra:running-status:
  Reference: '#/components/schemas/datapost_tailfmobileinfrarunningstatus'
tailf-mobile-infra:diagnostics:
  Reference: '#/components/schemas/datapost_tailfmobileinfradiagnostics'
tailf-mobile-infra:infra:
  Reference: '#/components/schemas/datapost_tailfmobileinfrainfra'
tailf-mobile-infra:client:
  Reference: '#/components/schemas/datapost_tailfmobileinfraclient'
tailf-mobile-infra:edr:
  Reference: '#/components/schemas/datapost_tailfmobileinfraedr'
tailf-mobile-infra:instance:
  Reference: '#/components/schemas/datapost_tailfmobileinfrainstance'
tailf-mobile-infra:endpoint:
  Reference: '#/components/schemas/datapost_tailfmobileinfraendpoint'
tailf-mobile-infra:vrf:
  Reference: '#/components/schemas/datapost_tailfmobileinfravrf'
tailf-mobile-infra:vrf-info:
  Reference: '#/components/schemas/datapost_tailfmobileinfravrfinfo'
tailf-mobile-infra:logging:
  Reference: '#/components/schemas/datapost_tailfmobileinfralogging'
tailf-mobile-infra:nodemonitor:
  Reference: '#/components/schemas/datapost_tailfmobileinfranodemonitor'
tailf-mobile-infra:monitor:
  Reference: '#/components/schemas/datapost_tailfmobileinframonitor'
tailf-mobile-infra:router:
  Reference: '#/components/schemas/datapost_tailfmobileinfrarouter'
tailf-mobile-infra:deployment:
  Reference: '#/components/schemas/datapost_tailfmobileinfradeployment'
tailf-mobile-infra:k8:
  Reference: '#/components/schemas/datapost_tailfmobileinfrak8'
tailf-mobile-infra:geo:
  Type: object
  Properties: {}
  Description: (non-presence)
  x-yang:
    Type: container
    is_presence: 'false'
tailf-mobile-infra:show:
  Type: object
  Properties: {}
  Description: (non-presence)
  x-yang:
    Type: container
    is_presence: 'false'
tailf-mobile-infra:clear:
  Type: object
  Properties: {}
  Description: (non-presence)
  x-yang:
```

```
          Type: container
          is_presence: 'false'
        tailf-mobile-infra:dump:
          Type: object
          Properties: {}
          Description: (non-presence)
          x-yang:
            Type: container
            is_presence: 'false'
        tailf-mobile-infra:config-error:
          Reference: '#/components/schemas/datapost_tailfmobileinfraconfigerror'
        tailf-mobile-infra:resource:
          Reference: '#/components/schemas/datapost_tailfmobileinfraresource'
        tailf-mobile-infra:geomonitor:
          Reference: '#/components/schemas/datapost_tailfmobileinfrageomonitor'
        tailf-mobile-infra:instances:
          Reference: '#/components/schemas/datapost_tailfmobileinfrainstances'
        tailf-mobile-infra:local-instance:
          Reference: '#/components/schemas/datapost_tailfmobileinfralocalinstance'
        tailf-mobile-infra:datastore:
          Reference: '#/components/schemas/datapost_tailfmobileinfradatastore'
      Description: ''
    root_ietfrestconfrestconf:
      Type: object
      Properties:
        data:
          Type: object
          Properties: {}
        operations:
          Type: object
          Properties: {}
        yang-library-version:
          Type: string
      Description: This is the RESTCONF root resource for the RESTCONF datastore and
        operation resources. See RESTCONF RFC 8040 for further information.
responses:
  '200':
    Description: OK
    content: {}
  '201':
    Description: Created
    content: {}
  '204':
    Description: No Content
    content: {}
  '400':
    Description: Bad Request
    content: {}
  '401':
    Description: Unauthorized
    content: {}
  '404':
```

```
      Description: Not Found
      content: {}
    '405':
      Description: Method Not Allowed
      content: {}
    '409':
      Description: Conflict
      content: {}
  parameters:
    content:
      name: content
      in: query
      Description: controlling descendant nodes in response
      Required: false
      style: form
      explode: true
      schema:
        Type: string
        format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    depth:
      name: depth
      in: query
      Description: limit the depth of nodes in response
      Required: false
      style: form
      explode: true
      schema:
        Type: integer
        format: uint16
    fields:
      name: fields
      in: query
      Description: optionally identify specific data nodes in response
      Required: false
      style: form
      explode: true
      schema:
        Type: string
        format: string
    filter:
      name: filter
      in: query
      Description: xpath expression to filter data nodes in response
      Required: false
      style: form
      explode: true
      schema:
```

```
    Type: string
    format: string
with-defaults:
  name: with-defaults
  in: query
  Description: controlling default values in response
  Required: false
  style: form
  explode: true
  schema:
    Type: string
    format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
insert:
  name: insert
  in: query
  Description: controlling the order when adding new list elements
  Required: false
  style: form
  explode: true
  schema:
    Type: string
    format: enumeration
    Default: first
    enum:
    - first
    - last
    - before
    - after
point:
  name: point
  in: query
  Description: used to specify the insertion point
  Required: false
  style: form
  explode: true
  schema:
    Type: string
    format: string
affinity-podInstance:
  name: affinity-podInstance
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
```

```
all-address:
  name: all-address
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
all-endpoint:
  name: all-endpoint
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
all-grInstance:
  name: all-grInstance
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
all-localAddress:
  name: all-localAddress
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
all-name:
  name: all-name
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
all-peerAddress:
  name: all-peerAddress
  in: path
  Required: true
  style: simple
  explode: false
```

```
    schema:
      Type: string
      format: string
  all-podInstance:
    name: all-podInstance
    in: path
    Required: true
    style: simple
    explode: false
    schema:
      Type: string
      format: string
  all-remoteAddress:
    name: all-remoteAddress
    in: path
    Required: true
    style: simple
    explode: false
    schema:
      Type: string
      format: string
  bgplist-bgp:
    name: bgplist-bgp
    in: path
    Required: true
    style: simple
    explode: false
    schema:
      Type: integer
      format: uint32
  bondingInterfaces-bondingInterface:
    name: bondingInterfaces-bondingInterface
    in: path
    Required: true
    style: simple
    explode: false
    schema:
      Type: string
      format: string
  category-name:
    name: category-name
    in: path
    Required: true
    style: simple
    explode: false
    schema:
      Type: string
      format: identityref
  codes-id:
    name: codes-id
    in: path
```

```
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
commit-pending-grInstance:
  name: commit-pending-grInstance
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
commit-pending-podInstance:
  name: commit-pending-podInstance
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
dbs-name:
  name: dbs-name
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
enable-event-id-procedure:
  name: enable-event-id-procedure
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
enable-field-id-event:
  name: enable-field-id-event
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
```

```
endpoints-host:
  name: endpoints-host
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
ep-eptype:
  name: ep-eptype
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: identityref
field-id:
  name: field-id
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
files-name:
  name: files-name
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: identityref
flowctrl-group-name:
  name: flowctrl-group-name
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
granular-labels-id:
  name: granular-labels-id
  in: path
  Required: true
  style: simple
  explode: false
```

```
  schema:
    Type: string
    format: string
info-address:
  name: info-address
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
info-diagnostic:
  name: info-diagnostic
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
info-endpoint:
  name: info-endpoint
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
info-errorComponent:
  name: info-errorComponent
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
info-grInstance:
  name: info-grInstance
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
info-podInstance:
  name: info-podInstance
  in: path
```

```
    Required: true
    style: simple
    explode: false
    schema:
      Type: string
      format: string
  instance-id-id:
    name: instance-id-id
    in: path
    Required: true
    style: simple
    explode: false
    schema:
      Type: string
      format: leafref
  instance-instance-id:
    name: instance-instance-id
    in: path
    Required: true
    style: simple
    explode: false
    schema:
      Type: integer
      format: int32
  interface-interface:
    name: interface-interface
    in: path
    Required: true
    style: simple
    explode: false
    schema:
      Type: string
      format: identityref
  interface-interface-type:
    name: interface-interface-type
    in: path
    Required: true
    style: simple
    explode: false
    schema:
      Type: string
      format: identityref
  interface-list-interface:
    name: interface-list-interface
    in: path
    Required: true
    style: simple
    explode: false
    schema:
      Type: string
      format: string
```

```
interfaceList-interface:
  name: interfaceList-interface
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
logger-name:
  name: logger-name
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
metricsList-name:
  name: metricsList-name
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
neighbors-neighbor:
  name: neighbors-neighbor
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: union
pod-group-config-key:
  name: pod-group-config-key
  in: path
  Description: Key for the label
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
pod-group-config-pod-group:
  name: pod-group-config-pod-group
  in: path
  Description: Group for the VMs
  Required: true
```

```
    style: simple
    explode: false
    schema:
      Type: string
      format: enumeration
      Default: protocol-layer
      enum:
      - protocol-layer
      - service-layer
      - cdl-layer
      - oam-layer
  pod-group-config-value:
    name: pod-group-config-value
    in: path
    Description: Value for the label
    Required: true
    style: simple
    explode: false
    schema:
      Type: string
      format: string
  pod-names-pod-name:
    name: pod-names-pod-name
    in: path
    Required: true
    style: simple
    explode: false
    schema:
      Type: string
      format: string
  pod-podtype:
    name: pod-podtype
    in: path
    Required: true
    style: simple
    explode: false
    schema:
      Type: string
      format: identityref
  pods-name:
    name: pods-name
    in: path
    Required: true
    style: simple
    explode: false
    schema:
      Type: string
      format: string
  policies-policy-name:
    name: policies-policy-name
    in: path
    Required: true
```

```
    style: simple
    explode: false
    schema:
      Type: string
      format: string
  sec-vip-sec-vip-ip:
    name: sec-vip-sec-vip-ip
    in: path
    Required: true
    style: simple
    explode: false
    schema:
      Type: string
      format: string
  sec-vip6-sec-vip-ipv6:
    name: sec-vip6-sec-vip-ipv6
    in: path
    Required: true
    style: simple
    explode: false
    schema:
      Type: string
      format: string
  service-service-name:
    name: service-service-name
    in: path
    Required: true
    style: simple
    explode: false
    schema:
      Type: string
      format: string
  subscribers-id:
    name: subscribers-id
    in: path
    Required: true
    style: simple
    explode: false
    schema:
      Type: string
      format: string
  thresholds-name:
    name: thresholds-name
    in: path
    Required: true
    style: simple
    explode: false
    schema:
      Type: string
      format: enumeration
      Default: low
```

```
    enum:
    - low
    - high
verboseLevels-podType:
  name: verboseLevels-podType
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: enumeration
    Default: protocol
    enum:
    - protocol
    - load-balancer
    - service
    - application
vip-vip-ip:
  name: vip-vip-ip
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
vip6-vip-ipv6:
  name: vip6-vip-ipv6
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
vips-vipInterface:
  name: vips-vipInterface
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
vrflist-name:
  name: vrflist-name
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
```

```
      format: string
requestBodies:
  data-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data-post'
    Required: true
  data-put-patch:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data-put-patch'
    Required: true
  data_tailf-mobile-infra_client:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client'
    Required: true
  data_tailf-mobile-infra_client-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client-post'
    Required: true
  data_tailf-mobile-infra_client_http:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_http'
    Required: true
  data_tailf-mobile-infra_client_http-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_http-post'
    Required: true
  data_tailf-mobile-infra_client_http_header:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_http_header'
    Required: true
  data_tailf-mobile-infra_client_http_header-post:
    content:
      application/yang-data+json:
        schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_client_http_header-post'

    Required: true
  data_tailf-mobile-infra_client_http_header_user-agent:
    content:
```

```
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_http_header_user-agent'
    Required: true
  data_tailf-mobile-infra_client_http_ping:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_http_ping'
    Required: true
  data_tailf-mobile-infra_client_http_ping-post:
    content:
      application/yang-data+json:
        schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_client_http_ping-post'

    Required: true
  data_tailf-mobile-infra_client_http_ping_interval:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_http_ping_interval'
    Required: true
  data_tailf-mobile-infra_client_http_ping_timeout:
    content:
      application/yang-data+json:
        schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_client_http_ping_timeout'

    Required: true
  data_tailf-mobile-infra_client_inbound:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_inbound'
    Required: true
  data_tailf-mobile-infra_client_inbound-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_inbound-post'
    Required: true
  data_tailf-mobile-infra_client_inbound_interface_interface-interface:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface'

    Required: true

data_tailf-mobile-infra_client_inbound_interface_interface-interface_interface:
```

```
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_interface'

    Required: true

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit'

    Required: true

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit-post:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit-post'

    Required: true

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload'

    Required: true

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload-post:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload-post'

    Required: true

data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload_reject-code:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_overload_reject-code'

    Required: true
```

```
data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending'
    Required: true
data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending-post'
    Required: true
data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending_request:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_interface_interface-interface_limit_pending_request'
    Required: true
  data_tailf-mobile-infra_client_inbound_limit:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_inbound_limit'
    Required: true
  data_tailf-mobile-infra_client_inbound_limit-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_limit-post'
    Required: true
  data_tailf-mobile-infra_client_inbound_limit_overload:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_overload'
    Required: true
  data_tailf-mobile-infra_client_inbound_limit_overload-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
```

```
'#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_overload-post'
    Required: true
  data_tailf-mobile-infra_client_inbound_limit_overload_reject-code:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_overload_reject-code'
    Required: true
  data_tailf-mobile-infra_client_inbound_limit_pending:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_pending'
    Required: true
  data_tailf-mobile-infra_client_inbound_limit_pending-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_pending-post'
    Required: true
  data_tailf-mobile-infra_client_inbound_limit_pending_request:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_inbound_limit_pending_request'
    Required: true
  data_tailf-mobile-infra_client_outbound:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_outbound'
    Required: true
  data_tailf-mobile-infra_client_outbound-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_outbound-post'

    Required: true
  data_tailf-mobile-infra_client_outbound_host:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_client_outbound_host'

    Required: true
  data_tailf-mobile-infra_client_outbound_host-post:
    content:
      application/yang-data+json:
        schema:
```

```
        Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host-post'
    Required: true
  data_tailf-mobile-infra_client_outbound_host_ping:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping'
    Required: true
  data_tailf-mobile-infra_client_outbound_host_ping-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping-post'
    Required: true
  data_tailf-mobile-infra_client_outbound_host_ping_all-host-down-interval:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_all-host-down-interval'

    Required: true
  data_tailf-mobile-infra_client_outbound_host_ping_backoff:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_backoff'
    Required: true
  data_tailf-mobile-infra_client_outbound_host_ping_fast-interval:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_fast-interval'
    Required: true
  data_tailf-mobile-infra_client_outbound_host_ping_interval:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_interval'
    Required: true
  data_tailf-mobile-infra_client_outbound_host_ping_retry:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_retry'
    Required: true
  data_tailf-mobile-infra_client_outbound_host_ping_timeout:
```

```
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_host_ping_timeout'
    Required: true
  data_tailf-mobile-infra_client_outbound_interface_interface-interface:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface'

    Required: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host'

    Required: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host-post:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host-post'

    Required: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping'

    Required: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping-post:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping-post'

    Required: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_all-host-down-interval:
```

```
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_all-host-down-interval'

    Required: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_backoff:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_backoff'

    Required: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_fast-interval:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_fast-interval'

    Required: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_interval:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_interval'

    Required: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_retry:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_retry'

    Required: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_timeout:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_host_ping_timeout'

    Required: true
```

data_tailf-mobile-infra_client_outbound_interface_interface-interface_interface:

  content:
    application/yang-data+json:
      schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_interface'

  Required: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit:

  content:
    application/yang-data+json:
      schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit'

  Required: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit-post:

  content:
    application/yang-data+json:
      schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit-post'

  Required: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive:

  content:
    application/yang-data+json:
      schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive'

  Required: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive-post:

  content:
    application/yang-data+json:
      schema:
        Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive-post'

  Required: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure:

  content:
    application/yang-data+json:
      schema:
        Reference:

'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure'

Required: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure-post:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure-post'

Required: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_codes_codes-id:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_codes_codes-id'

Required: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_count:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_consecutive_failure_count'

Required: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending'

Required: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending-post:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending-post'

Required: true

data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending_response:

content:

```
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_interface_interface-interface_limit_pending_response'

    Required: true
  data_tailf-mobile-infra_client_outbound_limit:
    content:
      application/yang-data+json:
        schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_client_outbound_limit'

    Required: true
  data_tailf-mobile-infra_client_outbound_limit-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit-post'
    Required: true
  data_tailf-mobile-infra_client_outbound_limit_consecutive:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive'
    Required: true
  data_tailf-mobile-infra_client_outbound_limit_consecutive-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive-post'
    Required: true
  data_tailf-mobile-infra_client_outbound_limit_consecutive_failure:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure'
    Required: true
  data_tailf-mobile-infra_client_outbound_limit_consecutive_failure-post:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure-post'

    Required: true

data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_codes_codes-id:

    content:
      application/yang-data+json:
```

```
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_codes_codes-id'

    Required: true
  data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_count:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_consecutive_failure_count'

    Required: true
  data_tailf-mobile-infra_client_outbound_limit_pending:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_pending'
    Required: true
  data_tailf-mobile-infra_client_outbound_limit_pending-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_pending-post'
    Required: true
  data_tailf-mobile-infra_client_outbound_limit_pending_response:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_client_outbound_limit_pending_response'
    Required: true
  data_tailf-mobile-infra_config-error:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_config-error'
    Required: true
  data_tailf-mobile-infra_config-error-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_config-error-post'
    Required: true
  data_tailf-mobile-infra_datastore:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_datastore'
    Required: true
  data_tailf-mobile-infra_datastore-post:
```

```
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_datastore-post'
    Required: true
  data_tailf-mobile-infra_datastore_dbs_dbs-name:
    content:
      application/yang-data+json:
        schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name'

    Required: true
  data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host'

    Required: true

data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_host:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_host'

    Required: true

data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_port:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_endpoints_endpoints-host_port'

    Required: true
  data_tailf-mobile-infra_datastore_dbs_dbs-name_name:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_dbs_dbs-name_name'
    Required: true
  data_tailf-mobile-infra_datastore_notification-ep:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep'
    Required: true
  data_tailf-mobile-infra_datastore_notification-ep-post:
```

```
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep-post'
    Required: true
  data_tailf-mobile-infra_datastore_notification-ep_host:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep_host'
    Required: true
  data_tailf-mobile-infra_datastore_notification-ep_port:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_notification-ep_port'
    Required: true
  data_tailf-mobile-infra_datastore_session-db:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_datastore_session-db'

    Required: true
  data_tailf-mobile-infra_datastore_session-db-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_session-db-post'
    Required: true
  data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host'

    Required: true

data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_host:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_host'

    Required: true

data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_port:
```

```
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_datastore_session-db_endpoints_endpoints-host_port'

    Required: true
  data_tailf-mobile-infra_deployment:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_deployment'
    Required: true
  data_tailf-mobile-infra_deployment-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_deployment-post'
    Required: true
  data_tailf-mobile-infra_deployment_app-name:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_deployment_app-name'
    Required: true
  data_tailf-mobile-infra_deployment_cluster-name:
    content:
      application/yang-data+json:
        schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_deployment_cluster-name'

    Required: true
  data_tailf-mobile-infra_deployment_dc-name:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_deployment_dc-name'
    Required: true
  data_tailf-mobile-infra_deployment_logical-nf-instance-id:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_deployment_logical-nf-instance-id'
    Required: true
  data_tailf-mobile-infra_deployment_model:
    Description: Deployment Model default large
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_deployment_model'
    Required: true
  data_tailf-mobile-infra_deployment_resource:
    content:
```

```
    application/yang-data+json:
      schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_deployment_resource'
  Required: true
data_tailf-mobile-infra_deployment_resource-post:
  content:
    application/yang-data+json:
      schema:
       Reference: '#/components/schemas/data_tailf-mobile-infra_deployment_resource-post'

  Required: true
data_tailf-mobile-infra_deployment_resource_cpu:
  content:
    application/yang-data+json:
      schema:
       Reference: '#/components/schemas/data_tailf-mobile-infra_deployment_resource_cpu'

  Required: true
data_tailf-mobile-infra_diagnostics:
  content:
    application/yang-data+json:
      schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_diagnostics'
  Required: true
data_tailf-mobile-infra_diagnostics-post:
  content:
    application/yang-data+json:
      schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_diagnostics-post'
  Required: true
data_tailf-mobile-infra_dump:
  content:
    application/yang-data+json:
      schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_dump'
  Required: true
data_tailf-mobile-infra_dump-post:
  content:
    application/yang-data+json:
      schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_dump-post'
  Required: true
data_tailf-mobile-infra_edr:
  content:
    application/yang-data+json:
      schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_edr'
  Required: true
data_tailf-mobile-infra_edr-post:
  content:
    application/yang-data+json:
      schema:
        Reference: '#/components/schemas/data_tailf-mobile-infra_edr-post'
  Required: true
```

```
    data_tailf-mobile-infra_edr_all:
      content:
        application/yang-data+json:
          schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_edr_all'
      Required: true
    data_tailf-mobile-infra_edr_all-post:
      content:
        application/yang-data+json:
          schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_edr_all-post'
      Required: true
    data_tailf-mobile-infra_edr_all_subscribers:
      content:
        application/yang-data+json:
          schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_edr_all_subscribers'
      Required: true
    data_tailf-mobile-infra_edr_edrsubscribers:
      content:
        application/yang-data+json:
          schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_edr_edrsubscribers'
      Required: true
    data_tailf-mobile-infra_edr_edrsubscribers-post:
      content:
        application/yang-data+json:
          schema:
           Reference: '#/components/schemas/data_tailf-mobile-infra_edr_edrsubscribers-post'

      Required: true
    data_tailf-mobile-infra_edr_edrsubscribers_subscribers_subscribers-id:
      content:
        application/yang-data+json:
          schema:
            Reference:
  '#/components/schemas/data_tailf-mobile-infra_edr_edrsubscribers_subscribers_subscribers-id'

      Required: true
    data_tailf-mobile-infra_edr_file:
      content:
        application/yang-data+json:
          schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_edr_file'
      Required: true
    data_tailf-mobile-infra_edr_file-post:
      content:
        application/yang-data+json:
          schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_edr_file-post'
      Required: true
    data_tailf-mobile-infra_edr_file_files_files-name:
      content:
        application/yang-data+json:
```

```
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name'
      Required: true
    data_tailf-mobile-infra_edr_file_files_files-name_flush:
      content:
        application/yang-data+json:
          schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_flush'
      Required: true
    data_tailf-mobile-infra_edr_file_files_files-name_flush-post:
      content:
        application/yang-data+json:
          schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_flush-post'
      Required: true
    data_tailf-mobile-infra_edr_file_files_files-name_flush_interval:
      content:
        application/yang-data+json:
          schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_flush_interval'
      Required: true
    data_tailf-mobile-infra_edr_file_files_files-name_limit:
      content:
        application/yang-data+json:
          schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_limit'
      Required: true
    data_tailf-mobile-infra_edr_file_files_files-name_limit-post:
      content:
        application/yang-data+json:
          schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_limit-post'
      Required: true
    data_tailf-mobile-infra_edr_file_files_files-name_limit_count:
      content:
        application/yang-data+json:
          schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_limit_count'
      Required: true
    data_tailf-mobile-infra_edr_file_files_files-name_limit_size:
      content:
        application/yang-data+json:
          schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_limit_size'
      Required: true
    data_tailf-mobile-infra_edr_file_files_files-name_limit_storage:
```

```
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_limit_storage'
    Required: true
  data_tailf-mobile-infra_edr_file_files_files-name_name:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_name'
    Required: true
  data_tailf-mobile-infra_edr_file_files_files-name_procedure:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure'
    Required: true
  data_tailf-mobile-infra_edr_file_files_files-name_procedure-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure-post'
    Required: true

data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure'

    Required: true

data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner'

    Required: true

data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner-post:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner-post'
```

```
    Required: true

data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event'

    Required: true
  ?
data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event-post

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event-post'

    Required: true
  ?
data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event'

    Required: true
  ?
data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event_enable

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event_enable'

    Required: true
  ?
data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event_enable-post

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event_enable-post'

    Required: true
  ?
data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event_enable_field_field-id

  : content:
      application/yang-data+json:
        schema:
          Reference:
```

'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event_enable-field-field-id'

Required: true

?
data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event_event

: content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_enable-inner_event_enable-field-id_enable-field-id-event_event'

Required: true

data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_procedure:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_procedure_enable-event-id_enable-event-id-procedure_procedure'

Required: true
data_tailf-mobile-infra_edr_file_files_files-name_rate:
content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_rate'
Required: true
data_tailf-mobile-infra_edr_file_files_files-name_reporting:
content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_reporting'
Required: true
data_tailf-mobile-infra_edr_file_files_files-name_threshold:
content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_threshold'
Required: true
data_tailf-mobile-infra_edr_file_files_files-name_threshold-post:
content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_threshold-post'
Required: true
data_tailf-mobile-infra_edr_file_files_files-name_threshold_cpu:
content:
application/yang-data+json:
schema:
Reference:

```
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_threshold_cpu'
    Required: true
  data_tailf-mobile-infra_edr_file_files_files-name_threshold_session:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_threshold_session'
    Required: true
  data_tailf-mobile-infra_edr_file_files_files-name_verbose:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_edr_file_files_files-name_verbose'
    Required: true
  data_tailf-mobile-infra_edr_reporting:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_edr_reporting'
    Required: true
  data_tailf-mobile-infra_endpoint:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_endpoint'
    Required: true
  data_tailf-mobile-infra_endpoint-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_endpoint-post'
    Required: true
  data_tailf-mobile-infra_geomonitor:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_geomonitor'
    Required: true
  data_tailf-mobile-infra_geomonitor-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_geomonitor-post'
    Required: true
  data_tailf-mobile-infra_geomonitor_podmonitor:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor'

    Required: true
  data_tailf-mobile-infra_geomonitor_podmonitor-post:
```

```
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor-post'
    Required: true
  data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name'
    Required: true

data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_failedReplicaPercent:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_failedReplicaPercent'

    Required: true
  data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_name:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_name'
    Required: true
  data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryCount:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryCount'

    Required: true

data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryFailOverInterval:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryFailOverInterval'

    Required: true

data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryInterval:

    content:
      application/yang-data+json:
        schema:
          Reference:
```

```
'#/components/schemas/data_tailf-mobile-infra_geomonitor_podmonitor_pods_pods-name_retryInterval'

    Required: true
  data_tailf-mobile-infra_geomonitor_remoteclustermonitor:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor'
    Required: true
  data_tailf-mobile-infra_geomonitor_remoteclustermonitor-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor-post'
    Required: true
  data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryCount:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryCount'
    Required: true
  data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryInterval:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_remoteclustermonitor_retryInterval'

    Required: true
  data_tailf-mobile-infra_geomonitor_trafficMonitor:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor'
    Required: true
  data_tailf-mobile-infra_geomonitor_trafficMonitor-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor-post'
    Required: true
  data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdCount:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdCount'
    Required: true
  data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdInterval:
    content:
```

```
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_trafficMonitor_thresholdInterval'
    Required: true
  data_tailf-mobile-infra_geomonitor_vipmonitor:
    content:
      application/yang-data+json:
        schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor'

    Required: true
  data_tailf-mobile-infra_geomonitor_vipmonitor-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor-post'
    Required: true

data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id'

    Required: true

data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_instance-id:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_instance-id'

    Required: true

data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface'

    Required: true

data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_retryCount:

    content:
      application/yang-data+json:
        schema:
          Reference:
```

'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_retryCount'

Required: true

data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_retryFailOverInterval:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_retryFailOverInterval'

Required: true

data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_retryInterval:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_retryInterval'

Required: true

data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_vipInterface:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_vipInterface'

Required: true

data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_vipIp:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_vipIp'

Required: true

data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_vipPort:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_geomonitor_vipmonitor_instance_instance-instance-id_vips_vips-vipInterface_vipPort'

Required: true
data_tailf-mobile-infra_infra:
content:
application/yang-data+json:
schema:

```
          Reference: '#/components/schemas/data_tailf-mobile-infra_infra'
      Required: true
    data_tailf-mobile-infra_infra-post:
      content:
        application/yang-data+json:
          schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_infra-post'
      Required: true
    data_tailf-mobile-infra_infra_metrics:
      content:
        application/yang-data+json:
          schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_infra_metrics'
      Required: true
    data_tailf-mobile-infra_infra_metrics-post:
      content:
        application/yang-data+json:
          schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_infra_metrics-post'
      Required: true
    data_tailf-mobile-infra_infra_metrics_experimental:
      content:
        application/yang-data+json:
          schema:
            Reference:
  '#/components/schemas/data_tailf-mobile-infra_infra_metrics_experimental'
      Required: true
    data_tailf-mobile-infra_infra_metrics_experimental-post:
      content:
        application/yang-data+json:
          schema:
            Reference:
  '#/components/schemas/data_tailf-mobile-infra_infra_metrics_experimental-post'
      Required: true
    data_tailf-mobile-infra_infra_metrics_experimental_version:
      content:
        application/yang-data+json:
          schema:
            Reference:
  '#/components/schemas/data_tailf-mobile-infra_infra_metrics_experimental_version'
      Required: true
    data_tailf-mobile-infra_infra_metrics_verbose:
      content:
        application/yang-data+json:
          schema:
           Reference: '#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose'

      Required: true
    data_tailf-mobile-infra_infra_metrics_verbose-post:
      content:
        application/yang-data+json:
          schema:
            Reference:
  '#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose-post'
```

```
    Required: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType'

    Required: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_level:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_level'

    Required: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics'

    Required: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics-post:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics-post'

    Required: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name'

    Required: true
  ?
data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_granular-labels_granular-labels-id

  : content:
      application/yang-data+json:
        schema:
```

```
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_granular-labels_granular-labels-id'

    Required: true
  ?
data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_level

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_level'

    Required: true
  ?
data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_name

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_metrics_metricsList_metricsList-name_name'

    Required: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_podType:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_podType'

    Required: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods'

    Required: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods-post:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods-post'

    Required: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name:

    content:
```

```
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name'

    Required: true

data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_level:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_level'

    Required: true
  ?
data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_pod-name

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_metrics_verbose_verboseLevels_verboseLevels-podType_pods_pod-names_pod-names-pod-name_pod-name'

    Required: true
  data_tailf-mobile-infra_infra_transaction:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_infra_transaction'
    Required: true
  data_tailf-mobile-infra_infra_transaction-post:
    content:
      application/yang-data+json:
        schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_infra_transaction-post'

    Required: true
  data_tailf-mobile-infra_infra_transaction_limit:
    content:
      application/yang-data+json:
        schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit'

    Required: true
  data_tailf-mobile-infra_infra_transaction_limit-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit-post'
    Required: true
  data_tailf-mobile-infra_infra_transaction_limit_consecutive:
    content:
      application/yang-data+json:
```

```
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive'
      Required: true
    data_tailf-mobile-infra_infra_transaction_limit_consecutive-post:
      content:
        application/yang-data+json:
          schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive-post'
      Required: true
    data_tailf-mobile-infra_infra_transaction_limit_consecutive_same:
      content:
        application/yang-data+json:
          schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive_same'
      Required: true
    data_tailf-mobile-infra_infra_transaction_limit_consecutive_same-post:
      content:
        application/yang-data+json:
          schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive_same-post'

      Required: true
    data_tailf-mobile-infra_infra_transaction_limit_consecutive_same_stage:

      content:
        application/yang-data+json:
          schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_consecutive_same_stage'

      Required: true
    data_tailf-mobile-infra_infra_transaction_limit_stage:
      content:
        application/yang-data+json:
          schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_limit_stage'
      Required: true
    data_tailf-mobile-infra_infra_transaction_loop:
      content:
        application/yang-data+json:
          schema:
           Reference: '#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop'

      Required: true
    data_tailf-mobile-infra_infra_transaction_loop-post:
      content:
        application/yang-data+json:
          schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop-post'
```

```
    Required: true
  data_tailf-mobile-infra_infra_transaction_loop_category_category-name:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name'

    Required: true

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_name:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_name'

    Required: true

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold'

    Required: true

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold-post:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold-post'

    Required: true

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_interval:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_interval'

    Required: true

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name'
```

```
    Required: true

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_action:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_action'

    Required: true

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_count:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_count'

    Required: true

data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_name:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_category_category-name_threshold_thresholds_thresholds-name_name'

    Required: true
  data_tailf-mobile-infra_infra_transaction_loop_detection:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_infra_transaction_loop_detection'
    Required: true
  data_tailf-mobile-infra_instance:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_instance'
    Required: true
  data_tailf-mobile-infra_instance-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_instance-post'
    Required: true
  data_tailf-mobile-infra_instance_instance-id_instance-id-id:
    content:
      application/yang-data+json:
        schema:
          Reference:
```

```
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id'
    Required: true
  data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint'

    Required: true
  data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint-post:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint-post'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_certificate-name:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_certificate-name'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_eptype:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_eptype'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_instancetype:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_instancetype'
```

```
    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_certificate-name

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_certificate-name'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher-post

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher-post'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_cache

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_cache'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_capacity

  : content:
      application/yang-data+json:
        schema:
```

```
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_capacity'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_count

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_count'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_expiry

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_expiry'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_capacity

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_capacity'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-capacity

  : content:
      application/yang-data+json:
```

```
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-capacity'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-rate-limit

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-rate-limit'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate-limit

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate-limit'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_nonresponsive

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_nonresponsive'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_outbound

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_outbound'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_rate-limit

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_rate-limit'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_threshold

  : content:
```

```
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_dispatcher_threshold'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_instancetype

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_instancetype'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_interface-type

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_interface-type'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal-post

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal-post'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port-post
```

```
  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port-post'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port_start

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_internal_base-port_start'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopbackEth

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopbackEth'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopbackPort

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_loopbackPort'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor-post

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor-post'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor_protocol
```

```
  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_monitor_protocol'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_mtls-enable

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_mtls-enable'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_offline

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_offline'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_sec-vip-ipv6

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_sec-vip-ipv6'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-interface

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-interface'

    Required: true
  ?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-ipv6-port

```
  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-ipv6-port'

    Required: true
  ?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vrf

```
  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vrf'

    Required: true
  ?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip

```
  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip'

    Required: true
  ?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_offline

```
  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_offline'

    Required: true
  ?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_sec-vip-ip

```
  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_sec-vip-ip'

    Required: true
  ?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-interface

```
  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-interface'

    Required: true
```

```
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-port

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-port'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vrf

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vrf'

    Required: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla:

```
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla-post

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla-post'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_procedure

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_procedure'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_response

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_sla_response'
```

```
    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_tls-enable

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_tls-enable'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_uri-scheme

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_uri-scheme'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6

  : content:
      application/yang-data+json:
        schema:
          Reference:
```

'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6-port

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6-port'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_offline

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_offline'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-interface

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-interface'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-ip

  : content:
      application/yang-data+json:
        schema:

```
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-ip'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-port

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vip-port'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vrf

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vip_vip-vip-ip_vrf'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vrf:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_interface_interface-interface-type_vrf'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal-post:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal-post'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port:

    content:
```

```
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port-post:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port-post'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port_start:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_internal_base-port_start'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackEth:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackEth'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackPort:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_loopbackPort'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor'

    Required: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor-post:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor-post'

Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor_protocol:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_monitor_protocol'

Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_mtls-enable:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_mtls-enable'

Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_nodes:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_nodes'

Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_replicas:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_replicas'

Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name'

```
    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_certificate-name

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_certificate-name'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher-post

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher-post'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_cache

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_cache'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_capacity

  : content:
      application/yang-data+json:
        schema:
          Reference:
```

'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_capacity'

Required: true

?

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_count

: content:

application/yang-data+json:

schema:

Reference:

'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_count'

Required: true

?

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_expiry

: content:

application/yang-data+json:

schema:

Reference:

'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_expiry'

Required: true

?

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-grop_flowctrl-grop-name

: content:

application/yang-data+json:

schema:

Reference:

'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-grop_flowctrl-grop-name'

Required: true

?

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-grop_flowctrl-grop-name_capacity

: content:

application/yang-data+json:

schema:

Reference:

'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-grop_flowctrl-grop-name_capacity'

Required: true

?

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-grop_flowctrl-grop-name_name

: content:

application/yang-data+json:

schema:

Reference:

'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-grop_flowctrl-grop-name_name'

Required: true

?

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-grop_flowctrl-grop-name_outbound-capacity

: content:

application/yang-data+json:

schema:

```
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-capacity'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-rate-limit

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_outbound-rate-limit'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate-limit

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_flowctrl-group_flowctrl-group-name_rate-limit'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_nonresponsive

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_nonresponsive'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_outbound

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_outbound'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_rate-limit

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_rate-limit'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-id_ep-type_service_service-service-name_interface_interface-interface-type_dispatcher_threshold

  : content:
      application/yang-data+json:
```

```
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_dispatcher_threshold'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_instancetype

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_instancetype'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_interface-type

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_interface-type'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal-post

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal-post'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port-post

  : content:
```

```
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port-post'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port_start

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_internal_base-port_start'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_loopbackEth

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_loopbackEth'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_loopbackPort

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_loopbackPort'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor-post

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor-post'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_monitor_protocol
```

```
  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_monitor_protocol'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_rtls-enable

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_rtls-enable'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_offline

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_offline'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_sec-vip-ipv6

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_sec-vip-ipv6'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-interface

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-interface'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ipv6_vip-ipv6-port
```

```
  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ip6_vip-ip6-port'

      Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ip6_vrf

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_sec-vip6_sec-vip6-sec-vip-ip6_vrf'

      Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip'

      Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_offline

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_offline'

      Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_sec-vip-ip

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_sec-vip-ip'

      Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-interface

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-ep-type_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-interface'

      Required: true
  ?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-port

```
  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vip-port'

    Required: true
  ?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vrf

```
  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sec-vip_sec-vip-sec-vip-ip_vrf'

    Required: true
  ?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla

```
  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla'

    Required: true
  ?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla-post

```
  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla-post'

    Required: true
  ?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla_procedure

```
  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla_procedure'

    Required: true
  ?
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla_response

```
  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_sla_response'

    Required: true
```

```
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_tls-enable

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_tls-enable'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_uri-scheme

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_uri-scheme'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_offline'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-interface'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6'
```

```
    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6-port

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vip-ipv6-port'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip6_vip6-vip-ipv6_vrf'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_offline

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_offline'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-interface

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-interface'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-ip

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-ip'
```

```
    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-port

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vip-port'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vrf

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vip_vip-vip-ip_vrf'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vrf

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_interface_interface-interface-type_vrf'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_service-name

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_service_service-service-name_service-name'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level-post:

    content:
      application/yang-data+json:
        schema:
```

```
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level-post'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash-post:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash-post'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_cpu-percent:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_cpu-percent'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_memory-in-mbs:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_memory-in-mbs'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_num-of-goroutine

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_crash_num-of-goroutine'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical:
```

```
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical'

    Required: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical-post:

```
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical-post'

    Required: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_cpu-percent:

```
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_cpu-percent'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_memory-in-mbs

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_memory-in-mbs'

    Required: true
  ?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_num-of-goroutine

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_critical_num-of-goroutine'

    Required: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn:

```
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn'

    Required: true
```

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn-post:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn-post'

Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_cpu-percent:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_cpu-percent'

Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_memory-in-mbs:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_memory-in-mbs'

Required: true
?
data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_num-of-goroutine

: content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_system-health-level_warn_num-of-goroutine'

Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_uri-scheme:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_uri-scheme'

Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6:

content:
application/yang-data+json:
schema:
Reference:

'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6'

Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_offline:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_offline'

Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-interface:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-interface'

Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6'

Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6-port:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vip-ipv6-port'

Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vrf:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip6_vip6-vip-ipv6_vrf'

Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip:

content:

```
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_offline:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_offline'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-interface:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-interface'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-ip:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-ip'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-port:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vip-port'

    Required: true

data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vrf:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_endpoint_ep_ep-eptype_vip_vip-vip-ip_vrf'

    Required: true
  data_tailf-mobile-infra_instance_instance-id_instance-id-id_id:
```

```
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instance_instance-id_instance-id-id_id'
    Required: true
  data_tailf-mobile-infra_instances:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_instances'
    Required: true
  data_tailf-mobile-infra_instances-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_instances-post'
    Required: true
  data_tailf-mobile-infra_instances_instance_instance-instance-id:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id'
    Required: true

data_tailf-mobile-infra_instances_instance_instance-instance-id_cluster-id:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_cluster-id'

    Required: true

data_tailf-mobile-infra_instances_instance_instance-instance-id_instance-id:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_instance-id'

    Required: true

data_tailf-mobile-infra_instances_instance_instance-instance-id_slice-name:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_slice-name'

    Required: true
  data_tailf-mobile-infra_instances_instance_instance-instance-id_system-id:
```

```
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_instances_instance_instance-instance-id_system-id'

    Required: true
  data_tailf-mobile-infra_k8:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_k8'
    Required: true
  data_tailf-mobile-infra_k8-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_k8-post'
    Required: true
  data_tailf-mobile-infra_k8_label:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_k8_label'
    Required: true
  data_tailf-mobile-infra_k8_label-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_k8_label-post'
    Required: true

data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value'

    Required: true
  ?
data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_key

  : description: Key for the label
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_key'

    Required: true
  ?
data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_pod-group
```

```
  : description: Group for the VMs
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_pod-group'

    Required: true
  ?
data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_value

  : description: Value for the label
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_k8_label_pod-group-config_pod-group-config-pod-group_pod-group-config-key_pod-group-config-value_value'

    Required: true
  data_tailf-mobile-infra_local-instance:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_local-instance'
    Required: true
  data_tailf-mobile-infra_local-instance-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_local-instance-post'
    Required: true
  data_tailf-mobile-infra_local-instance_instance:
    content:
      application/yang-data+json:
        schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_local-instance_instance'

    Required: true
  data_tailf-mobile-infra_logging:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_logging'
    Required: true
  data_tailf-mobile-infra_logging-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_logging-post'
    Required: true
  data_tailf-mobile-infra_logging_async:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_logging_async'
```

```
    Required: true
  data_tailf-mobile-infra_logging_async-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_logging_async-post'
    Required: true
  data_tailf-mobile-infra_logging_async_application:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_application'
    Required: true
  data_tailf-mobile-infra_logging_async_application-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_application-post'
    Required: true
  data_tailf-mobile-infra_logging_async_application_disable:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_application_disable'
    Required: true
  data_tailf-mobile-infra_logging_async_application_enable:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_application_enable'
    Required: true
  data_tailf-mobile-infra_logging_async_application_enable-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_application_enable-post'
    Required: true
  data_tailf-mobile-infra_logging_async_application_enable_buffer-size:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_application_enable_buffer-size'

    Required: true
  data_tailf-mobile-infra_logging_async_monitor-subscriber:
    content:
      application/yang-data+json:
        schema:
```

```
        Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber'
    Required: true
  data_tailf-mobile-infra_logging_async_monitor-subscriber-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber-post'
    Required: true
  data_tailf-mobile-infra_logging_async_monitor-subscriber_disable:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_disable'
    Required: true
  data_tailf-mobile-infra_logging_async_monitor-subscriber_enable:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_enable'
    Required: true
  data_tailf-mobile-infra_logging_async_monitor-subscriber_enable-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_enable-post'

    Required: true

data_tailf-mobile-infra_logging_async_monitor-subscriber_enable_buffer-size:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_monitor-subscriber_enable_buffer-size'

    Required: true
  data_tailf-mobile-infra_logging_async_tracing:
    content:
      application/yang-data+json:
        schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_logging_async_tracing'

    Required: true
  data_tailf-mobile-infra_logging_async_tracing-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_tracing-post'
```

```
    Required: true
  data_tailf-mobile-infra_logging_async_tracing_disable:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_disable'
    Required: true
  data_tailf-mobile-infra_logging_async_tracing_enable:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_enable'
    Required: true
  data_tailf-mobile-infra_logging_async_tracing_enable-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_enable-post'
    Required: true
  data_tailf-mobile-infra_logging_async_tracing_enable_buffer-size:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_tracing_enable_buffer-size'
    Required: true
  data_tailf-mobile-infra_logging_async_transaction:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_transaction'
    Required: true
  data_tailf-mobile-infra_logging_async_transaction-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_transaction-post'
    Required: true
  data_tailf-mobile-infra_logging_async_transaction_disable:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_disable'
    Required: true
  data_tailf-mobile-infra_logging_async_transaction_enable:
    content:
      application/yang-data+json:
        schema:
```

```
        Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_enable'
    Required: true
  data_tailf-mobile-infra_logging_async_transaction_enable-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_enable-post'
    Required: true
  data_tailf-mobile-infra_logging_async_transaction_enable_buffer-size:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_async_transaction_enable_buffer-size'

    Required: true
  data_tailf-mobile-infra_logging_error:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_logging_error'
    Required: true
  data_tailf-mobile-infra_logging_error-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_logging_error-post'
    Required: true
  data_tailf-mobile-infra_logging_error_stack:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_logging_error_stack'
    Required: true
  data_tailf-mobile-infra_logging_level:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_logging_level'
    Required: true
  data_tailf-mobile-infra_logging_level-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_logging_level-post'
    Required: true
  data_tailf-mobile-infra_logging_level_application:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_level_application'
```

```
    Required: true
  data_tailf-mobile-infra_logging_level_monitor-subscriber:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_level_monitor-subscriber'
    Required: true
  data_tailf-mobile-infra_logging_level_tracing:
    content:
      application/yang-data+json:
        schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_logging_level_tracing'

    Required: true
  data_tailf-mobile-infra_logging_level_transaction:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_level_transaction'
    Required: true
  data_tailf-mobile-infra_logging_logger_logger-name:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name'
    Required: true
  data_tailf-mobile-infra_logging_logger_logger-name_level:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level'
    Required: true
  data_tailf-mobile-infra_logging_logger_logger-name_level-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level-post'
    Required: true
  data_tailf-mobile-infra_logging_logger_logger-name_level_application:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_application'

    Required: true

data_tailf-mobile-infra_logging_logger_logger-name_level_monitor-subscriber:

    content:
```

```
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_monitor-subscriber'

    Required: true
  data_tailf-mobile-infra_logging_logger_logger-name_level_tracing:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_tracing'
    Required: true
  data_tailf-mobile-infra_logging_logger_logger-name_level_transaction:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_level_transaction'

    Required: true
  data_tailf-mobile-infra_logging_logger_logger-name_name:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_logger_logger-name_name'
    Required: true
  data_tailf-mobile-infra_logging_transaction:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_logging_transaction'
    Required: true
  data_tailf-mobile-infra_logging_transaction-post:
    content:
      application/yang-data+json:
        schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_logging_transaction-post'

    Required: true
  data_tailf-mobile-infra_logging_transaction_duplicate:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_transaction_duplicate'
    Required: true
  data_tailf-mobile-infra_logging_transaction_max-file-size:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_transaction_max-file-size'
    Required: true
```

```
    data_tailf-mobile-infra_logging_transaction_max-rotation:
      content:
        application/yang-data+json:
          schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_transaction_max-rotation'
      Required: true
    data_tailf-mobile-infra_logging_transaction_message:
      content:
        application/yang-data+json:
          schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_transaction_message'
      Required: true
    data_tailf-mobile-infra_logging_transaction_persist:
      content:
        application/yang-data+json:
          schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_logging_transaction_persist'
      Required: true
    data_tailf-mobile-infra_monitor:
      content:
        application/yang-data+json:
          schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_monitor'
      Required: true
    data_tailf-mobile-infra_monitor-post:
      content:
        application/yang-data+json:
          schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_monitor-post'
      Required: true
    data_tailf-mobile-infra_monitor_bfd:
      content:
        application/yang-data+json:
          schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_monitor_bfd'
      Required: true
    data_tailf-mobile-infra_monitor_bfd-post:
      content:
        application/yang-data+json:
          schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_monitor_bfd-post'
      Required: true
    data_tailf-mobile-infra_monitor_bfd_node-status:
      content:
        application/yang-data+json:
          schema:
           Reference: '#/components/schemas/data_tailf-mobile-infra_monitor_bfd_node-status'

      Required: true
    data_tailf-mobile-infra_monitor_protocol:
      content:
```

```
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_monitor_protocol'
    Required: true
  data_tailf-mobile-infra_monitor_protocol-post:
    content:
      application/yang-data+json:
        schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_monitor_protocol-post'

    Required: true
  data_tailf-mobile-infra_monitor_protocol_cpu-limit:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_monitor_protocol_cpu-limit'
    Required: true
  data_tailf-mobile-infra_nodemonitor:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_nodemonitor'
    Required: true
  data_tailf-mobile-infra_nodemonitor-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_nodemonitor-post'
    Required: true
  data_tailf-mobile-infra_nodemonitor_interval:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_nodemonitor_interval'

    Required: true
  data_tailf-mobile-infra_nodemonitor_mode:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_nodemonitor_mode'
    Required: true
  data_tailf-mobile-infra_peers:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_peers'
    Required: true
  data_tailf-mobile-infra_peers-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_peers-post'
```

```
      Required: true
    data_tailf-mobile-infra_resource:
      content:
        application/yang-data+json:
          schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_resource'
      Required: true
    data_tailf-mobile-infra_resource-post:
      content:
        application/yang-data+json:
          schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_resource-post'
      Required: true
    data_tailf-mobile-infra_resource_pod_pod-podtype:
      content:
        application/yang-data+json:
          schema:
           Reference: '#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype'

      Required: true
    data_tailf-mobile-infra_resource_pod_pod-podtype_cpu:
      content:
        application/yang-data+json:
          schema:
            Reference:
  '#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu'
      Required: true
    data_tailf-mobile-infra_resource_pod_pod-podtype_cpu-post:
      content:
        application/yang-data+json:
          schema:
            Reference:
  '#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu-post'
      Required: true
    data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_limit:
      content:
        application/yang-data+json:
          schema:
            Reference:
  '#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_limit'
      Required: true
    data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_request:
      content:
        application/yang-data+json:
          schema:
            Reference:
  '#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_cpu_request'
      Required: true
    data_tailf-mobile-infra_resource_pod_pod-podtype_gomaxproc:
      content:
        application/yang-data+json:
          schema:
            Reference:
  '#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_gomaxproc'
```

```
    Required: true
  data_tailf-mobile-infra_resource_pod_pod-podtype_labels:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels'
    Required: true
  data_tailf-mobile-infra_resource_pod_pod-podtype_labels-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels-post'
    Required: true
  data_tailf-mobile-infra_resource_pod_pod-podtype_labels_key:
    Description: Key for the label
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels_key'
    Required: true
  data_tailf-mobile-infra_resource_pod_pod-podtype_labels_value:
    Description: Value for the label
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_labels_value'
    Required: true
  data_tailf-mobile-infra_resource_pod_pod-podtype_memory:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory'
    Required: true
  data_tailf-mobile-infra_resource_pod_pod-podtype_memory-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory-post'
    Required: true
  data_tailf-mobile-infra_resource_pod_pod-podtype_memory_limit:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_limit'
    Required: true
  data_tailf-mobile-infra_resource_pod_pod-podtype_memory_request:
    content:
```

```
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_memory_request'
      Required: true
    data_tailf-mobile-infra_resource_pod_pod-podtype_podtype:
      content:
        application/yang-data+json:
          schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_resource_pod_pod-podtype_podtype'
      Required: true
    data_tailf-mobile-infra_resources:
      content:
        application/yang-data+json:
          schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_resources'
      Required: true
    data_tailf-mobile-infra_resources-post:
      content:
        application/yang-data+json:
          schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_resources-post'
      Required: true
    data_tailf-mobile-infra_router:
      content:
        application/yang-data+json:
          schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_router'
      Required: true
    data_tailf-mobile-infra_router-post:
      content:
        application/yang-data+json:
          schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_router-post'
      Required: true
    data_tailf-mobile-infra_router_bfd:
      content:
        application/yang-data+json:
          schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_router_bfd'
      Required: true
    data_tailf-mobile-infra_router_bfd-post:
      content:
        application/yang-data+json:
          schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_router_bfd-post'
      Required: true
    data_tailf-mobile-infra_router_bfd_instance:
      content:
        application/yang-data+json:
          schema:
            Reference: '#/components/schemas/data_tailf-mobile-infra_router_bfd_instance'
      Required: true
```

```
  data_tailf-mobile-infra_router_bfd_instance-post:
    content:
      application/yang-data+json:
        schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_router_bfd_instance-post'

    Required: true
  data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id'

    Required: true
  data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_id:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_id'

    Required: true

data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface'

    Required: true

data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_gateway-ip:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_gateway-ip'

    Required: true

data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_interface:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_interface'

    Required: true
  ?
data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor
```

```
  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor'

    Required: true
  ?
data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor_neighbor

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_neighbors_neighbors-neighbor_neighbor'

    Required: true

data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_vrf:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bfd_instance_instance-id_instance-id-id_interface-list_interface-list-interface_vrf'

    Required: true
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp'
    Required: true
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd'
    Required: true
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd-post'
    Required: true
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_dscp-marking:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_dscp-marking'
    Required: true
```

```
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_interval:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_interval'
    Required: true
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_min_rx:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_min_rx'
    Required: true
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_multiplier:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bfd_multiplier'
    Required: true
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bgp:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_bgp'
    Required: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface'

    Required: true
  ?
data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface'

    Required: true
  ?
data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface_bondingInterface

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_bondingInterfaces_bondingInterfaces-bondingInterface_bondingInterface'
```

```
    Required: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_interface:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_interface'

    Required: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor'

    Required: true
  ?
data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_fail-over

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_fail-over'

    Required: true
  ?
data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_neighbor

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_neighbor'

    Required: true
  ?
data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_remote-as

  : content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_neighbors_neighbors-neighbor_remote-as'

    Required: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_vrf:

    content:
      application/yang-data+json:
        schema:
```

```
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_interfaceList_interfaceList-interface_vrf'

    Required: true
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_learnDefaultRoute:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_learnDefaultRoute'

    Required: true
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackBFDPort:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackBFDPort'
    Required: true
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackPort:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_loopbackPort'
    Required: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name'

    Required: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_as-path-set:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_as-path-set'

    Required: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_gateWay:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_gateWay'

    Required: true
```

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_interface:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_interface'

Required: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_ip-prefix:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_ip-prefix'

Required: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_isStaticRoute:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_isStaticRoute'

Required: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_mask-range:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_mask-range'

Required: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_modifySourceIp:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_modifySourceIp'

Required: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_policy-name:

content:
application/yang-data+json:
schema:
Reference:

'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_policy-name'

    Required: true

data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_source-prefix:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_policies_policies-policy-name_source-prefix'

    Required: true
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend'
    Required: true
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend-post'
    Required: true
  data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend_as-path:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_bgplist_bgplist-bgp_prepend_as-path'
    Required: true
  data_tailf-mobile-infra_router_monitor-interface:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_router_monitor-interface'

    Required: true
  data_tailf-mobile-infra_router_monitor-interface-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_monitor-interface-post'
    Required: true

data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface'

```
    Required: true

data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface'

    Required: true

data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface-type:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_interface-type'

    Required: true

data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_linked-interface:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_router_monitor-interface_interface-list_interface-list-interface_linked-interface'

    Required: true
  data_tailf-mobile-infra_rpc:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_rpc'
    Required: true
  data_tailf-mobile-infra_rpc-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_rpc-post'
    Required: true
  data_tailf-mobile-infra_running-status:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_running-status'
    Required: true
  data_tailf-mobile-infra_running-status-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_running-status-post'
```

```
    Required: true
  data_tailf-mobile-infra_sessions:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_sessions'
    Required: true
  data_tailf-mobile-infra_sessions-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_sessions-post'
    Required: true
  data_tailf-mobile-infra_vrf:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_vrf'
    Required: true
  data_tailf-mobile-infra_vrf-info:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_vrf-info'
    Required: true
  data_tailf-mobile-infra_vrf-info-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_vrf-info-post'
    Required: true
  data_tailf-mobile-infra_vrf-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_tailf-mobile-infra_vrf-post'
    Required: true
  data_tailf-mobile-infra_vrf_vrflist_vrflist-name:
    content:
      application/yang-data+json:
        schema:
         Reference: '#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name'

    Required: true
  data_tailf-mobile-infra_vrf_vrflist_vrflist-name_device:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_device'
    Required: true
  data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gateway:
    content:
      application/yang-data+json:
```

```
        schema:
          Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gateway'
      Required: true
    data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gatewayIpv6:
      content:
        application/yang-data+json:
          schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_gatewayIpv6'
      Required: true
    data_tailf-mobile-infra_vrf_vrflist_vrflist-name_linkDevice:
      content:
        application/yang-data+json:
          schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_linkDevice'
      Required: true
    data_tailf-mobile-infra_vrf_vrflist_vrflist-name_name:
      content:
        application/yang-data+json:
          schema:
            Reference:
'#/components/schemas/data_tailf-mobile-infra_vrf_vrflist_vrflist-name_name'
      Required: true
  securitySchemes:
    basicAuth:
      Type: http
      scheme: basic
  x-original-swagger-version: '2.0'
```