etcd

- OpenAPI, on page 1
- Info, on page 1
- Servers, on page 1
- tags, on page 1
- Paths, on page 2
- Components, on page 454

OpenAPI

OpenAPI Version: 3.0.1

Info

```
Title: cisco-smi-etcd
Description: ''
Version: '2022-10-17'
```

Servers

```
  URL: /restconf
```

tags

```
- Name: root
  Description: root resources
- Name: operations
  Description: operations resources
- Name: data
  Description: data resources
```

```
- Name: get
  Description: get resources
- Name: head
  Description: head resources
- Name: post
  Description: post resources
- Name: patch
  Description: patch resources
- Name: put
  Description: put resources
- Name: options
  Description: options resources
- Name: delete
  Description: delete resources
```


Paths

/


```
get:

  Tags:
  - root
  - get
  Operation ID: root_get

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/root'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - root
  - head
  Operation ID: root_head

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/operations

```
get:

  Tags:
  - operations
  - get
  Operation ID: operations_get

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/operations'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
```

/yang-library-version

```
get:

  Tags:
  - yang-library-version
  - get
  Operation ID: yang_library_version_get

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/yang-library-version'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - yang-library-version
  - head
  Operation ID: yang_library_version_head

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data


```
get:

  Tags:
  - data
  - get
  Operation ID: data_get

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data-put-patch'
    Required/Optional: true

  Responses:
    '201':
      Description: Created
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: data
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data-post'
    Required/Optional: true

  Responses:
    '201':
      Description: Created
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: data
head:

  Tags:
  - data
  - head
  Operation ID: data_head

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data-put-patch'
    Required/Optional: true

  Responses:
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: data
```

/data/cisco-smi-etcd:etcd

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_cisco-smi-etcd_etcd'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd'
```

```
    Required/Optional: true

  Responses:
    '201':
      Description: container etcd created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: etcd
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_etcd_etcd_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container etcd created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: etcd
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd'
    Required/Optional: true

  Responses:
    '204':
      Description: container etcd updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: etcd
```

/data/cisco-smi-etcd:etcd/node-affinity

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_node_affinity_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_node-affinity'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_node_affinity_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_node-affinity'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf node-affinity created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: node-affinity
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_node_affinity_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_node_affinity_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_node_affinity_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_node_affinity_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_node-affinity'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf node-affinity updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: node-affinity
```

/data/cisco-smi-etcd:etcd/replicas

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_replicas_get

  Parameters:
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
    - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_replicas'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_replicas_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_replicas'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf replicas created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replicas
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_replicas_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_replicas_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_replicas_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_replicas_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_replicas'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf replicas updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replicas
```

/data/cisco-smi-etcd:etcd/go-max-procs

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_go_max_procs_get

  Parameters:
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_go-max-procs'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_go_max_procs_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_go-max-procs'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf go-max-procs created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: go-max-procs
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_go_max_procs_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_go_max_procs_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_go_max_procs_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_go_max_procs_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_go-max-procs'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf go-max-procs updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: go-max-procs
```

/data/cisco-smi-etcd:etcd/volume

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_volume_get

  Parameters:
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_volume'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_volume_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_volume'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf volume created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: volume
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_volume_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_volume_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_volume_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_volume_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_volume'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf volume updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: volume
```

/data/cisco-smi-etcd:etcd/backup

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_backup_get

  Parameters:
  - Name: content
    In: query
```

```
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
```

```
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_backup'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_backup_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_backup'
    Required/Optional: true

  Responses:
    '201':
      Description: container backup created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: backup
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_etcd_etcd_backup_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_backup-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container backup created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: backup
```

```
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_backup_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_backup_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_backup_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_backup_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
        Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_backup'
    Required/Optional: true

  Responses:
    '204':
      Description: container backup updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: backup
```

/data/cisco-smi-etcd:etcd/backup/disable

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_backup_disable_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_backup_disable'
  '204':
    Description: No Content
    Content: {}
  '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_backup_disable_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_backup_disable'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf disable created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: disable
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_backup_disable_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_backup_disable_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_backup_disable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_backup_disable_patch
    Request Body:
      Content:
```

```
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_backup_disable'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf disable updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: disable
```

/data/cisco-smi-etcd:etcd/backup/frequency

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_backup_frequency_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_backup_frequency'

  '204':
    Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_backup_frequency_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_backup_frequency'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf frequency created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: frequency
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_backup_frequency_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_backup_frequency_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_backup_frequency_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_backup_frequency_patch
```

```
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_backup_frequency'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf frequency updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: frequency
```

/data/cisco-smi-etcd:etcd/backup/restore

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore'
```

```
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore'
    Required/Optional: true

  Responses:
    '201':
      Description: container restore created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: restore
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore-post'

    Required/Optional: true

  Responses:
    '201':
      Description: container restore created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: restore
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_delete

  Responses:
```

```
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore'
    Required/Optional: true

  Responses:
    '204':
      Description: container restore updated
      Content: {}
    '400':
```

```
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
    Content: {}
  '409':
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: restore
```

/data/cisco-smi-etcd:etcd/backup/restore/use-local-snapshot

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_use_local_snapshot_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore_use-local-snapshot'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_use_local_snapshot_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore_use-local-snapshot'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf use-local-snapshot created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: use-local-snapshot
delete:

  Tags:
  - data
  - delete
```

```
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_use_local_snapshot_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_use_local_snapshot_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_use_local_snapshot_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_use_local_snapshot_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore_use-local-snapshot'
    Required/Optional: true

  Responses:
```

```
    '204':
      Description: leaf use-local-snapshot updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: use-local-snapshot
```

/data/cisco-smi-etcd:etcd/backup/restore/wait-time

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_wait_time_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore_wait-time'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_wait_time_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore_wait-time'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf wait-time created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: wait-time
```

```
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_wait_time_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_wait_time_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_wait_time_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_backup_restore_wait_time_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore_wait-time'
     Required/Optional: true

  Responses:
    '204':
      Description: leaf wait-time updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: wait-time
```

/data/cisco-smi-etcd:etcd/enable-daily-defragmentation

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_enable_daily_defragmentation_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_enable-daily-defragmentation'
      '204':
        Description: No Content
        Content: {}
```

```
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_enable_daily_defragmentation_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_enable-daily-defragmentation'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf enable-daily-defragmentation created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable-daily-defragmentation
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_enable_daily_defragmentation_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_enable_daily_defragmentation_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_enable_daily_defragmentation_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_enable_daily_defragmentation_patch
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_enable-daily-defragmentation'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf enable-daily-defragmentation updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable-daily-defragmentation
```

/data/cisco-smi-etcd:etcd/daily-defragmentation-start-time

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_etcd_etcd_daily_defragmentation_start_time_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
```

```
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_daily-defragmentation-start-time'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_daily_defragmentation_start_time_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_daily-defragmentation-start-time'
      Required/Optional: true

    Responses:
      '201':
        Description: leaf daily-defragmentation-start-time created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: daily-defragmentation-start-time
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_daily_defragmentation_start_time_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_daily_defragmentation_start_time_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_daily_defragmentation_start_time_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_daily_defragmentation_start_time_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_daily-defragmentation-start-time'
      Required/Optional: true

    Responses:
      '204':
        Description: leaf daily-defragmentation-start-time updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: daily-defragmentation-start-time
```

/data/cisco-smi-etcd:etcd/storage-label

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_etcd_etcd_storage_label_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_storage-label'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_storage_label_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_storage-label'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf storage-label created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: storage-label
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_storage_label_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_storage_label_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_storage_label_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_storage_label_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_storage-label'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf storage-label updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: storage-label
```

/data/cisco-smi-etcd:etcd/external-ip

```
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_external_ip_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-etcd:etcd/external-ip={external-ip-ip},{external-i p-port}

```
get:

  Tags:
  - data
  - get
 Operation ID: data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_get


  Parameters:
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
```

```
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
 Operation ID: data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_put


  Parameters:
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port'

      Required/Optional: true

    Responses:
      '201':
        Description: list external-ip created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: external-ip
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_delete

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_options

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
```

```
 - head
Operation ID: data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_head


 Parameters:
 - Name: external-ip-ip
   In: path
   Required/Optional: true
   Style: simple
   Explode: false
   Schema:
     Type: string
     Format: union
 - Name: external-ip-port
   In: path
   Required/Optional: true
   Style: simple
   Explode: false
   Schema:
     Type: integer
     Format: uint16
 - Name: content
   In: query
   Description: controlling descendant nodes in response
   Required/Optional: false
   Style: form
   Explode: true
   Schema:
     Type: string
     Format: enumeration
     Default: config
     enum:
     - config
     - nonconfig
     - all
 - Name: depth
   In: query
   Description: limit the depth of nodes in response
   Required/Optional: false
   Style: form
   Explode: true
   Schema:
     Type: integer
     Format: uint16
 - Name: fields
   In: query
   Description: optionally identify specific data nodes in response
   Required/Optional: false
   Style: form
   Explode: true
   Schema:
     Type: string
     Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_patch

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port'

      Required/Optional: true

    Responses:
      '204':
        Description: list external-ip updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: external-ip
```

/data/cisco-smi-etcd:etcd/external-ip={external-ip-ip},{external-i p-port}/ip

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_ip_get

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: union
- Name: external-ip-port
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_ip'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_ip_put

    Parameters:
    - Name: external-ip-ip
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_ip'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf ip created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ip
  delete:

    Tags:
```

```
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_ip_delete

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_ip_options

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
```

```
        Format: uint16

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_ip_head

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_ip_patch

    Parameters:
    - Name: external-ip-ip
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_ip'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf ip updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ip
```

/data/cisco-smi-etcd:etcd/external-ip={external-ip-ip},{external-ip-port}/port

```
  get:
```

```
    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_port_get

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_port'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_port_put

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_port'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf port created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
```

```
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_port_delete

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_port_options

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_port_head

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_port_patch

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_port'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf port updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: port
```

/data/cisco-smi-etcd:etcd/external-ip={external-ip-ip},{external-i-port}/label

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_label_get

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_label'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_label_put

  Parameters:
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_label'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf label created or replaced
      Content: {}
    '204':
      Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: label
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_label_delete

  Parameters:
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_label_options

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_label_head

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_label_patch

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_label'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf label updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
```

```
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: label
```

/data/cisco-smi-etcd:etcd/tls

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_tls_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_tls'
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_tls_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_tls'
    Required/Optional: true

  Responses:
    '201':
      Description: container tls created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tls
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_etcd_etcd_tls_post
  Request Body:
    Content:
```

```
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_tls-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container tls created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tls
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_tls_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_tls_options

  Responses:
    '200':
      Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_cisco_smi_etcd_etcd_tls_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_tls_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_tls'
    Required/Optional: true

  Responses:
    '204':
      Description: container tls updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: tls
```

/data/cisco-smi-etcd:etcd/tls/enable

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_tls_enable_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_tls_enable'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_tls_enable_put
```

```
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_tls_enable'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf enable created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_tls_enable_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_tls_enable_options

  Responses:
```

```
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_tls_enable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_tls_enable_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_tls_enable'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf enable updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
```

/data/cisco-smi-etcd:etcd/tls/certificate-config

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
```

```
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config'
      Required/Optional: true

    Responses:
      '201':
        Description: container certificate-config created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: certificate-config
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container certificate-config created
```

```
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: certificate-config
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_head
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config'
    Required/Optional: true

  Responses:
    '204':
      Description: container certificate-config updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: certificate-config
```

/data/cisco-smi-etcd:etcd/tls/certificate-config/server

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server'
     Required/Optional: true

   Responses:
     '201':
       Description: container server created or replaced
       Content: {}
     '204':
       Description: No Content
       Content: {}
     '400':
       Description: Bad Request
       Content: {}
     '401':
       Description: Unauthorized
       Content: {}
     '404':
       Description: Not Found
       Content: {}
     '405':
       Description: Method Not Allowed
       Content: {}
     '409':
       Description: Conflict
       Content: {}
   security:
   - basicAuth: []
   x-codegen-request-body-name: server
  Method: Post

   Tags:
   - data
   - post
   Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_post
   Request Body:
     Content:
       application/yang-data+json:
         Schema:
           Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server-post'
     Required/Optional: true

   Responses:
     '201':
       Description: container server created
       Content: {}
     '204':
       Description: No Content
       Content: {}
     '400':
       Description: Bad Request
       Content: {}
```

```
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: server
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server'
      Required/Optional: true

    Responses:
      '204':
        Description: container server updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: server
```

/data/cisco-smi-etcd:etcd/tls/certificate-config/server/ca-cert

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_get

    Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert'
      Required/Optional: true

    Responses:
      '201':
        Description: container ca-cert created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
```

```
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ca-cert
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container ca-cert created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ca-cert
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_options


  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
```

```
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert'
      Required/Optional: true

    Responses:
      '204':
        Description: container ca-cert updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ca-cert
```

/data/cisco-smi-etcd:etcd/tls/certificate-config/server/ca-cert/se cret-name

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_secret_name_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert_secret-name'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_secret_name_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert_secret-name'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf secret-name created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-name
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_secret_name_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_secret_name_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_secret_name_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_secret_name_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert_secret-name'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf secret-name updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-name
```

/data/cisco-smi-etcd:etcd/tls/certificate-config/server/key-pair

```
  get:

    Tags:
    - data
    - get
```

```
Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair'
      Required/Optional: true

    Responses:
      '201':
        Description: container key-pair created or replaced
        Content: {}
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key-pair
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container key-pair created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: key-pair
delete:

  Tags:
  - data
  - delete
 Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_delete


  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_options


  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair'
      Required/Optional: true

    Responses:
      '204':
        Description: container key-pair updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key-pair
```

/data/cisco-smi-etcd:etcd/tls/certificate-config/server/key-pair/secret-name

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_secret_name_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair_secret-name'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_secret_name_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair_secret-name'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf secret-name created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
```

```
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_secret_name_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_secret_name_options

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_secret_name_head

    Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_secret_name_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair_secret-name'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf secret-name updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-name
```

/data/cisco-smi-etcd:etcd/tls/certificate-config/peer

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer'
     Required/Optional: true

   Responses:
     '201':
       Description: container peer created or replaced
       Content: {}
     '204':
       Description: No Content
       Content: {}
     '400':
       Description: Bad Request
       Content: {}
     '401':
       Description: Unauthorized
       Content: {}
     '404':
       Description: Not Found
       Content: {}
     '405':
       Description: Method Not Allowed
       Content: {}
     '409':
       Description: Conflict
       Content: {}
   security:
   - basicAuth: []
   x-codegen-request-body-name: peer
  Method: Post

   Tags:
   - data
   - post
   Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_post
   Request Body:
     Content:
       application/yang-data+json:
         Schema:
           Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer-post'
     Required/Optional: true

   Responses:
     '201':
       Description: container peer created
       Content: {}
     '204':
       Description: No Content
       Content: {}
     '400':
       Description: Bad Request
       Content: {}
```

```
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: peer
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer'
      Required/Optional: true

    Responses:
      '204':
        Description: container peer updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: peer
```

/data/cisco-smi-etcd:etcd/tls/certificate-config/peer/ca-cert

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_get

    Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert'
      Required/Optional: true

    Responses:
      '201':
        Description: container ca-cert created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
```

```
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ca-cert
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container ca-cert created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ca-cert
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
```

```
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert'
      Required/Optional: true

    Responses:
      '204':
        Description: container ca-cert updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ca-cert
```

/data/cisco-smi-etcd:etcd/tls/certificate-config/peer/ca-cert/secr et-name

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_secret_name_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert_secret-name'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_secret_name_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert_secret-name'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf secret-name created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-name
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_secret_name_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_secret_name_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_secret_name_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_secret_name_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert_secret-name'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf secret-name updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-name
```

/data/cisco-smi-etcd:etcd/tls/certificate-config/peer/key-pair

```
  get:

    Tags:
    - data
    - get
```

```
Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair'
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair'
      Required/Optional: true

    Responses:
      '201':
        Description: container key-pair created or replaced
        Content: {}
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key-pair
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container key-pair created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: key-pair
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair'
      Required/Optional: true

    Responses:
      '204':
        Description: container key-pair updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key-pair
```

/data/cisco-smi-etcd:etcd/tls/certificate-config/peer/key-pair/sec ret-name

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_secret_name_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair_secret-name'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_secret_name_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair_secret-name'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf secret-name created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
```

```
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_secret_name_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_secret_name_options

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_secret_name_head

    Parameters:
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_secret_name_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair_secret-name'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf secret-name updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-name
```

/data/cisco-smi-etcd:etcd/repository

```
  get:

    Tags:
```

```
- data
- get
Operation ID: data_cisco_smi_etcd_etcd_repository_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_repository'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_repository_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_repository'
    Required/Optional: true

  Responses:
    '201':
      Description: leaf repository created or replaced
      Content: {}
```

```
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: repository
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_repository_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_repository_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_repository_head
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_repository_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_repository'
    Required/Optional: true

  Responses:
    '204':
      Description: leaf repository updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: repository
```

/data/cisco-smi-etcd:etcd/monitoring

```
get:
```

```
Tags:
- data
- get
Operation ID: data_cisco_smi_etcd_etcd_monitoring_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_monitoring'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_monitoring'
    Required/Optional: true

  Responses:
    '201':
      Description: container monitoring created or replaced
```

```
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitoring
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_monitoring-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container monitoring created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitoring
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
      - nonconfig
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:
```

```
  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_monitoring'
    Required/Optional: true

  Responses:
    '204':
      Description: container monitoring updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitoring
```

/data/cisco-smi-etcd:etcd/monitoring/enabled

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_enabled_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
      Content:
        application/yang-data+json:
          Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_enabled'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_enabled_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_enabled'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf enabled created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enabled
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_enabled_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_enabled_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_enabled_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
security:
```

```
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_enabled_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_enabled'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf enabled updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enabled
```

/data/cisco-smi-etcd:etcd/monitoring/alerts

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts'

    Required/Optional: true

  Responses:
    '201':
      Description: container alerts created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
```

```
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: alerts
  Method: Post

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts-post'
      Required/Optional: true

    Responses:
      '201':
        Description: container alerts created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
  x-codegen-request-body-name: alerts
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_patch
    Request Body:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts'

      Required/Optional: true

    Responses:
      '204':
        Description: container alerts updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: alerts
```

/data/cisco-smi-etcd:etcd/monitoring/alerts/dbsize

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize'
    '204':
      Description: No Content
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize'
    Required/Optional: true

  Responses:
    '201':
      Description: container dbsize created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dbsize
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize-post'
    Required/Optional: true

  Responses:
    '201':
      Description: container dbsize created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dbsize
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_delete

  Responses:
    '204':
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize'
      Required/Optional: true

    Responses:
      '204':
        Description: container dbsize updated
        Content: {}
      '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dbsize
```

/data/cisco-smi-etcd:etcd/monitoring/alerts/dbsize/major-alert-thr eshold

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_major_alert_threshold_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_major-alert-threshold'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
```

```
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_major_alert_threshold_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_major-alert-threshold'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf major-alert-threshold created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: major-alert-threshold
delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_major_alert_threshold_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_major_alert_threshold_options

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_major_alert_threshold_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_major_alert_threshold_patch
    Request Body:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_major-alert-threshold'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf major-alert-threshold updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: major-alert-threshold
```

/data/cisco-smi-etcd:etcd/monitoring/alerts/dbsize/critical-alert- threshold

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_critical_alert_threshold_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
      - nonconfig
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_critical-alert-threshold'
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_critical_alert_threshold_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_critical-alert-threshold'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf critical-alert-threshold created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
```

```
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: critical-alert-threshold
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_critical_alert_threshold_delete

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_critical_alert_threshold_options

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_critical_alert_threshold_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_critical_alert_threshold_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_critical-alert-threshold'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf critical-alert-threshold updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: critical-alert-threshold
```

/data/cisco-smi-etcd:etcd/network-policy

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_etcd_etcd_network_policy_get

    Parameters:
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_network-policy'
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_network-policy'
    Required/Optional: true

  Responses:
    '201':
      Description: container network-policy created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
```

```
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: network-policy
Method: Post

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_network-policy-post'

    Required/Optional: true

  Responses:
    '201':
      Description: container network-policy created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: network-policy
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_patch
  Request Body:
```

```
    Content:
      application/yang-data+json:
        Schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_network-policy'
    Required/Optional: true

  Responses:
    '204':
      Description: container network-policy updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: network-policy
```

/data/cisco-smi-etcd:etcd/network-policy/enable

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_enable_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
        - nonconfig
        - all
      - Name: depth
        In: query
        Description: limit the depth of nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: integer
          Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_network-policy_enable'
```

```
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_enable_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_network-policy_enable'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf enable created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_enable_delete

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_enable_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_enable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
```

```
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_enable_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_network-policy_enable'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf enable updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
```

/data/cisco-smi-etcd:etcd/additional-instances

```
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_additional_instances_options

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanœs-name}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_get

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_put

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name'

      Required/Optional: true

    Responses:
      '201':
        Description: list additional-instances created or replaced
        Content: {}
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: additional-instances
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_delete

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_options

    Parameters:
```

```
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: integer
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        '200':
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_patch

      Parameters:
      - Name: additional-instances-name
        In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name'

      Required/Optional: true

    Responses:
      '204':
        Description: list additional-instances updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: additional-instances
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/name

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_name_get

    Parameters:
    - Name: additional-instances-name
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_name'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_name_put

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_name'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf name created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_name_delete

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_name_options

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_name_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_name_patch

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_name'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf name updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: name
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/node-affinity

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_node_affinity_get

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_node-affinity'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_node_affinity_put

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_node-affinity'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf node-affinity created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
```

```
    security:
    - basicAuth: []
    x-codegen-request-body-name: node-affinity
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_node_affinity_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_node_affinity_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:
```

```
    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_node_affinity_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_node_affinity_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_node-affinity'

      Required/Optional: true

    Responses:
```

```
    '204':
      Description: leaf node-affinity updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: node-affinity
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/replicas

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_replicas_get

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_replicas'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_replicas_put

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_replicas'

      Required/Optional: true

    Responses:
      '201':
```

```
      Description: leaf replicas created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replicas
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_replicas_delete

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
```

```
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_replicas_options

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_replicas_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_replicas_patch

    Parameters:
```

```
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_replicas'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf replicas updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: replicas
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/go-max-procs

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_go_max_procs_get
```

```
Parameters:
- Name: additional-instances-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_go-max-procs'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_go_max_procs_put

    Parameters:
    - Name: additional-instances-name
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_go-max-procs'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf go-max-procs created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: go-max-procs
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_go_max_procs_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_go_max_procs_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_go_max_procs_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_go_max_procs_patch

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_go-max-procs'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf go-max-procs updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
```

```
      Description: Conflict
      Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: go-max-procs
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/volume

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_volume_get

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_volume'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
```

```
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_volume_put

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_volume'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf volume created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
```

```
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: volume
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_volume_delete

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_volume_options

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

```
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_volume_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_volume_patch

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_volume'

      Required/Optional: true

    Responses:
```

```
      '204':
        Description: leaf volume updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: volume
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/backup

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_get

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_put

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup'

      Required/Optional: true

    Responses:
      '201':
```

```
      Description: container backup created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: backup
Method: Post

  Tags:
  - data
  - post
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_post

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup-post'

    Required/Optional: true

  Responses:
    '201':
      Description: container backup created
      Content: {}
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: backup
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_delete

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_options

    Parameters:
```

```
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: integer
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        '200':
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_patch

      Parameters:
      - Name: additional-instances-name
        In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup'

      Required/Optional: true

    Responses:
      '204':
        Description: container backup updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: backup
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/backup/disable

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_disable_get

    Parameters:
    - Name: additional-instances-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_disable'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_disable_put

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_disable'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf disable created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: disable
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_disable_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_disable_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_disable_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_disable_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_disable'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf disable updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
```

```
      Description: Conflict
      Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: disable
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/backup/frequency

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_frequency_get


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_frequency'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_frequency_put


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_frequency'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf frequency created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: frequency
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_frequency_delete


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_frequency_options


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
```

```
      Description: OK
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_frequency_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_frequency_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_frequency'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf frequency updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: frequency
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/backup/restore

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_get

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_put

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore'
```

```
      Required/Optional: true

    Responses:
      '201':
        Description: container restore created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: restore
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_post


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore-post'
```

```
    Required/Optional: true

  Responses:
    '201':
      Description: container restore created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: restore
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_delete


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore'

      Required/Optional: true

    Responses:
      '204':
        Description: container restore updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: restore
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/backup/restore/use-local-snapshot

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_use_local_snapshot_get


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_use-local-snapshot'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_use_local_snapshot_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_use-local-snapshot'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf use-local-snapshot created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: use-local-snapshot
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_use_local_snapshot_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_use_local_snapshot_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:
```

```
  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_use_local_snapshot_head


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_use_local_snapshot_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_use-local-snapshot'

      Required/Optional: true

    Responses:
```

```
    '204':
      Description: leaf use-local-snapshot updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: use-local-snapshot
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/backup/restore/wait-time

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_wait_time_get


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_wait-time'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_wait_time_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_wait-time'

      Required/Optional: true

    Responses:
```

```
      '201':
        Description: leaf wait-time created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: wait-time
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_wait_time_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
```

```
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_wait_time_options

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_wait_time_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
```

```
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_wait_time_patch

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_wait-time'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf wait-time updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: wait-time
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/enable-daily-defragmentation

```
  get:

    Tags:
```

```
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_enable_daily_defragmentation_get


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_enable-daily-defragmentation'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_enable_daily_defragmentation_put

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_enable-daily-defragmentation'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf enable-daily-defragmentation created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable-daily-defragmentation
  delete:

    Tags:
    - data
    - delete
    Operation ID:
```

```
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_enable_daily_defragmentation_delete

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_enable_daily_defragmentation_options

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_enable_daily_defragmentation_head

    Parameters:
    - Name: additional-instances-name
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_enable_daily_defragmentation_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_enable-daily-defragmentation'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf enable-daily-defragmentation updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable-daily-defragmentation
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/daily-defragmentation-start-time

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_daily_defragmentation_start_time_get

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_daily-defragmentation-start-time'

    '204':
      Description: No Content
      Content: {}
```

```
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_daily_defragmentation_start_time_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_daily-defragmentation-start-time'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf daily-defragmentation-start-time created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
```

```
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: daily-defragmentation-start-time
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_daily_defragmentation_start_time_delete


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_daily_defragmentation_start_time_options


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_daily_defragmentation_start_time_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_daily_defragmentation_start_time_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_daily-defragmentation-start-time'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf daily-defragmentation-start-time updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: daily-defragmentation-start-time
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/storage-label

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_storage_label_get

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_storage-label'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_storage_label_put

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_storage-label'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf storage-label created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: storage-label
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_storage_label_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_storage_label_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_storage_label_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_storage_label_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_storage-label'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf storage-label updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: storage-label
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/external-ip

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_options


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/external-ip={external-ip-ip},{external-ip-port}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_get


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: external-ip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- Name: external-ip-port
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_put


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port'

      Required/Optional: true

    Responses:
      '201':
        Description: list external-ip created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: external-ip
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
```

```
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_head


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port'

      Required/Optional: true

    Responses:
      '204':
        Description: list external-ip updated
        Content: {}
```

```
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: external-ip
?
/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/external-ip={external-ip-ip},{external-ip-port}/ip
: get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_ip_get

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
```

```
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_ip'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_ip_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_ip'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf ip created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ip
  delete:

    Tags:
```

```
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_ip_delete

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_ip_options

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_ip_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_ip_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_ip'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf ip updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ip
?
/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/external-ip={external-ip-ip},{external-ip-port}/port
: get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_port_get


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: union
- Name: external-ip-port
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_port'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_port_put
```

```
Parameters:
- Name: additional-instances-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: external-ip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- Name: external-ip-port
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_port'

  Required/Optional: true

Responses:
  '201':
    Description: leaf port created or replaced
    Content: {}
  '204':
    Description: No Content
    Content: {}
  '400':
    Description: Bad Request
    Content: {}
  '401':
    Description: Unauthorized
    Content: {}
  '404':
    Description: Not Found
    Content: {}
  '405':
    Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: port
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_port_delete


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
```

```
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_port_options

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_port_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: external-ip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- Name: external-ip-port
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_port_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
```

```
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_port'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf port updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: port
?
/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/external-ip={external-ip-ip},{external-ip-port}/label
: get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_label_get


    Parameters:
    - Name: additional-instances-name
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_label'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_label_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_label'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf label created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
```

```
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: label
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_label_delete

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
```

```
  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_label_options


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_label_head
```

```
Parameters:
- Name: additional-instances-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: external-ip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- Name: external-ip-port
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_label_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: string
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_label'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf label updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: label
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/tls

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_get

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
```

```
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_put

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls'

      Required/Optional: true

    Responses:
      '201':
        Description: container tls created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: tls
```

```
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_post

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container tls created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: tls
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_delete

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_options

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_head

    Parameters:
```

```
- Name: additional-instances-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
 patch:

  Tags:
  - data
  - patch
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_patch

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls'

    Required/Optional: true

  Responses:
    '204':
      Description: container tls updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
```

```
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tls
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/tls/enable

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_enable_get

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_enable'

      '204':
        Description: No Content
        Content: {}
      '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_enable_put

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_enable'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf enable created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
```

```
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_enable_delete

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_enable_options

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_enable_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_enable_patch

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_enable'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf enable updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/tls/certificate-config

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_get


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
```

```
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config'

    Required/Optional: true

  Responses:
    '201':
      Description: container certificate-config created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: certificate-config
Method: Post

  Tags:
  - data
  - post
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_post


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container certificate-config created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: certificate-config
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_options


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_head


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config'

      Required/Optional: true

    Responses:
      '204':
        Description: container certificate-config updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: certificate-config
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/tls/certificate-config/server

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_get


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server'

      Required/Optional: true

    Responses:
      '201':
        Description: container server created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: server
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_post


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container server created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
    x-codegen-request-body-name: server
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
```

```
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server'

      Required/Optional: true

    Responses:
      '204':
        Description: container server updated
```

```
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: server
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/tls/certificate-config/server/ca-cert

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_get


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert'

      Required/Optional: true

    Responses:
      '201':
        Description: container ca-cert created or replaced
```

```
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ca-cert
Method: Post

  Tags:
  - data
  - post
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_post


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert-post'

    Required/Optional: true

  Responses:
    '201':
      Description: container ca-cert created
      Content: {}
```

```
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ca-cert
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_options
```

```
  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_head


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_patch


    Parameters:
```

```
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert'

      Required/Optional: true

    Responses:
      '204':
        Description: container ca-cert updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ca-cert
?
/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/tls/certificate-config/server/ca-cert/secret-name
: get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_secret_name_get


    Parameters:
    - Name: additional-instances-name
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert_secret-name'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_secret_name_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert_secret-name'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf secret-name created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_secret_name_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_secret_name_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_secret_name_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_secret_name_patch


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert_secret-name'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf secret-name updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-name
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/tls/certificate-config/server/key-pair

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_get


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
```

```
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_put


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair'

    Required/Optional: true

  Responses:
    '201':
      Description: container key-pair created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: key-pair
Method: Post

  Tags:
  - data
  - post
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_post


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair-post'

    Required/Optional: true

  Responses:
    '201':
      Description: container key-pair created
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
```

```
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: key-pair
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_delete


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_options


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair'

```
      Required/Optional: true

    Responses:
      '204':
        Description: container key-pair updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key-pair
?
/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/tls/certificate-config/server/key-pair/secret-name
: get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_secret_name_get


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair_secret-name'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_secret_name_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair_secret-name'

      Required/Optional: true

    Responses:
```

```
    '201':
      Description: leaf secret-name created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-name
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_secret_name_delete


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
```

```
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_secret_name_options

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_secret_name_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
```

```
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_secret_name_patch

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair_secret-name'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf secret-name updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-name
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/tls/certificate-config/peer

```
  get:

    Tags:
```

```
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_get


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_put

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer'

      Required/Optional: true

    Responses:
      '201':
        Description: container peer created or replaced
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: peer
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
```

data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_post

```
    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container peer created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: peer
  delete:

    Tags:
    - data
    - delete
    Operation ID:
```

data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_delete

```
    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '204':
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_head


    Parameters:
    - Name: additional-instances-name
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer'

      Required/Optional: true

    Responses:
      '204':
        Description: container peer updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
```

```
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: peer
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/tls/certificate-config/peer/ca-cert

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_get

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert'

    '204':
      Description: No Content
      Content: {}
    '400':
```

```
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_put


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert'

    Required/Optional: true

  Responses:
    '201':
      Description: container ca-cert created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
```

```
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ca-cert
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_post


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container ca-cert created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
```

```
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ca-cert
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_delete


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_options


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_patch


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert'

      Required/Optional: true

    Responses:
      '204':
        Description: container ca-cert updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ca-cert
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/tls/certificate-config/peer/ca-cert/secret-name

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_secret_name_get


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert_secret-name'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_secret_name_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert_secret-name'

    Required/Optional: true

  Responses:
    '201':
      Description: leaf secret-name created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-name
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_secret_name_delete

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_secret_name_options


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_secret_name_head


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    '200':
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_secret_name_patch


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert_secret-name'

    Required/Optional: true

  Responses:
    '204':
      Description: leaf secret-name updated
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-name
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instanc es-name}/tls/certificate-config/peer/key-pair

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_get

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    '200':
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair'

    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
```

```
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_put


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair'

    Required/Optional: true

  Responses:
    '201':
      Description: container key-pair created or replaced
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
```

```
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key-pair
  Method: Post

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_post


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair-post'

      Required/Optional: true

    Responses:
      '201':
        Description: container key-pair created
        Content: {}
      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: key-pair
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_delete


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_options


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '200':
      Description: OK
      Content: {}
  security:
```

```
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair'
```

```
      Required/Optional: true

    Responses:
      '204':
        Description: container key-pair updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key-pair
?
/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/tls/certificate-config/peer/key-pair/secret-name
: get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_secret_name_get


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  '200':
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair_secret-name'

      '204':
        Description: No Content
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_secret_name_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair_secret-name'

      Required/Optional: true

    Responses:
      '201':
        Description: leaf secret-name created or replaced
```

```
      Content: {}
    '204':
      Description: No Content
      Content: {}
    '400':
      Description: Bad Request
      Content: {}
    '401':
      Description: Unauthorized
      Content: {}
    '404':
      Description: Not Found
      Content: {}
    '405':
      Description: Method Not Allowed
      Content: {}
    '409':
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-name
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_secret_name_delete


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    '204':
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_secret_name_options
```

```
    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_secret_name_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      '200':
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_secret_name_patch
```

```
    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair_secret-name'

      Required/Optional: true

    Responses:
      '204':
        Description: leaf secret-name updated
        Content: {}
      '400':
        Description: Bad Request
        Content: {}
      '401':
        Description: Unauthorized
        Content: {}
      '404':
        Description: Not Found
        Content: {}
      '405':
        Description: Method Not Allowed
        Content: {}
      '409':
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-name
```

Components

```
schemas:
  data:
    Type: object
    Properties:
      ietf-restconf:data:
        Type: object
```

```
      Properties: {}
      Description: This resource represents the combined configuration and state
        data resources that can be accessed by a client and cannot be created
        or deleted by the client. See RESTCONF RFC 8040 for further information.
      x-yang:
        Type: datastore
data-post:
  Type: object
  Properties:
    cisco-smi-etcd:etcd:
      Reference: '#/components/schemas/datapost_ciscosmietcdetcd'
data-put-patch:
  Type: object
  Properties:
    ietf-restconf:data:
      Reference: '#/components/schemas/dataputpatch_ietfrestconfdata'
data_cisco-smi-etcd_etcd:
  Type: object
  Properties:
    cisco-smi-etcd:etcd:
      Reference: '#/components/schemas/datapost_ciscosmietcdetcd'
data_cisco-smi-etcd_etcd-post:
  Type: object
  Properties:
    cisco-smi-etcd:node-affinity:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    cisco-smi-etcd:replicas:
      Type: integer
      Description: (leaf)
      format: byte
      x-yang:
        Type: leaf
    cisco-smi-etcd:go-max-procs:
      Type: integer
      Description: (leaf)
      format: byte
      x-yang:
        Type: leaf
    cisco-smi-etcd:volume:
      Type: integer
      Description: (leaf)
      format: byte
      x-yang:
        Type: leaf
    cisco-smi-etcd:backup:
      Reference: '#/components/schemas/datapost_ciscosmietcdetcd_backup'
    cisco-smi-etcd:enable-daily-defragmentation:
      Type: string
```

```
      Description: (leaf)
      format: boolean
      x-yang:
        Type: leaf
    cisco-smi-etcd:daily-defragmentation-start-time:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    cisco-smi-etcd:storage-label:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    cisco-smi-etcd:external-ip:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_ciscosmietcdetcd_externalip'
      x-yang:
        Type: list
    cisco-smi-etcd:tls:
      Reference: '#/components/schemas/datapost_ciscosmietcdetcd_tls'
    cisco-smi-etcd:repository:
      Type: string
      Description: (leaf)
      format: leafref
      x-yang:
        Type: leaf
    cisco-smi-etcd:monitoring:
      Reference: '#/components/schemas/datapost_ciscosmietcdetcd_monitoring'
    cisco-smi-etcd:network-policy:
      Reference: '#/components/schemas/datapost_ciscosmietcdetcd_networkpolicy'
    cisco-smi-etcd:additional-instances:
      Type: array
      Description: (list)
      Items:
       Reference: '#/components/schemas/datapost_ciscosmietcdetcd_additionalinstances'

      x-yang:
        Type: list
data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name:

  Type: object
  Properties:
    cisco-smi-etcd:additional-instances:
      Type: array
      Description: (list)
      Items:
       Reference: '#/components/schemas/datapost_ciscosmietcdetcd_additionalinstances'
```

```
      x-yang:
        Type: list

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup:

    Type: object
    Properties:
      cisco-smi-etcd:backup:
        Reference: '#/components/schemas/datapost_ciscosmietcdetcd_backup'

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup-post:

    Type: object
    Properties:
      cisco-smi-etcd:disable:
        Type: string
        Description: (leaf)
        format: boolean
        x-yang:
          Type: leaf
      cisco-smi-etcd:frequency:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
      cisco-smi-etcd:restore:
        Reference: '#/components/schemas/datapost_ciscosmietcdetcd_backup_restore'

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_disable:

    Type: object
    Properties:
      cisco-smi-etcd:disable:
        Type: string
        Description: (leaf)
        format: boolean
        x-yang:
          Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_frequency:

    Type: object
    Properties:
      cisco-smi-etcd:frequency:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore:
```

```
    Type: object
    Properties:
      cisco-smi-etcd:restore:
        Reference: '#/components/schemas/datapost_ciscosmietcdetcd_backup_restore'

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore-post:

    Type: object
    Properties:
      cisco-smi-etcd:use-local-snapshot:
        Type: string
        Description: (leaf)
        format: boolean
        x-yang:
          Type: leaf
      cisco-smi-etcd:wait-time:
        Type: integer
        Description: (leaf)
        format: byte
        x-yang:
          Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_use-local-snapshot:

    Type: object
    Properties:
      cisco-smi-etcd:use-local-snapshot:
        Type: string
        Description: (leaf)
        format: boolean
        x-yang:
          Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_wait-time:

    Type: object
    Properties:
      cisco-smi-etcd:wait-time:
        Type: integer
        Description: (leaf)
        format: byte
        x-yang:
          Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_daily-defragmentation-start-time:

    Type: object
    Properties:
      cisco-smi-etcd:daily-defragmentation-start-time:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
```

```
        Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_enable-daily-defragmentation:

```
    Type: object
    Properties:
      cisco-smi-etcd:enable-daily-defragmentation:
        Type: string
        Description: (leaf)
        format: boolean
        x-yang:
          Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port:

```
    Type: object
    Properties:
      cisco-smi-etcd:external-ip:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_ciscosmietcdetcd_externalip'
        x-yang:
          Type: list
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_ip:

```
    Type: object
    Properties:
      cisco-smi-etcd:ip:
        Type: string
        Description: (leaf)
        format: union
        x-yang:
          Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_label:

```
    Type: object
    Properties:
      cisco-smi-etcd:label:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_port:

```
    Type: object
    Properties:
      cisco-smi-etcd:port:
        Type: integer
```

```
        Description: (leaf)
        format: uint16
        x-yang:
          Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_go-max-procs:

    Type: object
    Properties:
      cisco-smi-etcd:go-max-procs:
        Type: integer
        Description: (leaf)
        format: byte
        x-yang:
          Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_name:

    Type: object
    Properties:
      cisco-smi-etcd:name:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_node-affinity:

    Type: object
    Properties:
      cisco-smi-etcd:node-affinity:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_replicas:

    Type: object
    Properties:
      cisco-smi-etcd:replicas:
        Type: integer
        Description: (leaf)
        format: byte
        x-yang:
          Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_storage-label:

    Type: object
    Properties:
```

```
      cisco-smi-etcd:storage-label:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls:

    Type: object
    Properties:
      cisco-smi-etcd:tls:
        Reference: '#/components/schemas/datapost_ciscosmietcdetcd_tls'

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls-post:

    Type: object
    Properties:
      cisco-smi-etcd:enable:
        Type: string
        Description: (leaf)
        format: boolean
        x-yang:
          Type: leaf
      cisco-smi-etcd:certificate-config:
       Reference: '#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig'


data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config:

    Type: object
    Properties:
      cisco-smi-etcd:certificate-config:
       Reference: '#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig'


data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config-post:

    Type: object
    Properties:
      cisco-smi-etcd:server:
        Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server'
      cisco-smi-etcd:peer:
        Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server'

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer:

    Type: object
    Properties:
      cisco-smi-etcd:peer:
        Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server'
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer-post:

```
    Type: object
    Properties:
      cisco-smi-etcd:ca-cert:
        Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert'
      cisco-smi-etcd:key-pair:
        Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert'
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert:

```
    Type: object
    Properties:
      cisco-smi-etcd:ca-cert:
        Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert'
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert-post:

```
    Type: object
    Properties:
      cisco-smi-etcd:secret-name:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert_secret-name:

```
    Type: object
    Properties:
      cisco-smi-etcd:secret-name:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair:

```
    Type: object
    Properties:
      cisco-smi-etcd:key-pair:
        Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert'
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair-post:

```
    Type: object
    Properties:
      cisco-smi-etcd:secret-name:
```

```
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair_secret-name:

```
    Type: object
    Properties:
      cisco-smi-etcd:secret-name:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server:

```
    Type: object
    Properties:
      cisco-smi-etcd:server:
        Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server'
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server-post:

```
    Type: object
    Properties:
      cisco-smi-etcd:ca-cert:
        Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert'
      cisco-smi-etcd:key-pair:
        Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert'
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert:

```
    Type: object
    Properties:
      cisco-smi-etcd:ca-cert:
        Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert'
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert-post:

```
    Type: object
    Properties:
      cisco-smi-etcd:secret-name:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert_secret-name:

```
  Type: object
  Properties:
    cisco-smi-etcd:secret-name:
      Type: string
      Description: (leaf)
      format: leafref
      x-yang:
        Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair:

```
  Type: object
  Properties:
    cisco-smi-etcd:key-pair:
      Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert'
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair-post:

```
  Type: object
  Properties:
    cisco-smi-etcd:secret-name:
      Type: string
      Description: (leaf)
      format: leafref
      x-yang:
        Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair_secret-name:

```
  Type: object
  Properties:
    cisco-smi-etcd:secret-name:
      Type: string
      Description: (leaf)
      format: leafref
      x-yang:
        Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_enable:

```
  Type: object
  Properties:
    cisco-smi-etcd:enable:
      Type: string
      Description: (leaf)
      format: boolean
      x-yang:
        Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_volume:

```
  Type: object
  Properties:
    cisco-smi-etcd:volume:
      Type: integer
      Description: (leaf)
      format: byte
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_backup:
  Type: object
  Properties:
    cisco-smi-etcd:backup:
      Reference: '#/components/schemas/datapost_ciscosmietcdetcd_backup'
data_cisco-smi-etcd_etcd_backup-post:
  Type: object
  Properties:
    cisco-smi-etcd:disable:
      Type: string
      Description: (leaf)
      format: boolean
      x-yang:
        Type: leaf
    cisco-smi-etcd:frequency:
      Type: integer
      Description: (leaf)
      format: uint32
      x-yang:
        Type: leaf
    cisco-smi-etcd:restore:
      Reference: '#/components/schemas/datapost_ciscosmietcdetcd_backup_restore'
data_cisco-smi-etcd_etcd_backup_disable:
  Type: object
  Properties:
    cisco-smi-etcd:disable:
      Type: string
      Description: (leaf)
      format: boolean
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_backup_frequency:
  Type: object
  Properties:
    cisco-smi-etcd:frequency:
      Type: integer
      Description: (leaf)
      format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_backup_restore:
  Type: object
  Properties:
```

```
    cisco-smi-etcd:restore:
      Reference: '#/components/schemas/datapost_ciscosmietcdetcd_backup_restore'
data_cisco-smi-etcd_etcd_backup_restore-post:
  Type: object
  Properties:
    cisco-smi-etcd:use-local-snapshot:
      Type: string
      Description: (leaf)
      format: boolean
      x-yang:
        Type: leaf
    cisco-smi-etcd:wait-time:
      Type: integer
      Description: (leaf)
      format: byte
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_backup_restore_use-local-snapshot:
  Type: object
  Properties:
    cisco-smi-etcd:use-local-snapshot:
      Type: string
      Description: (leaf)
      format: boolean
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_backup_restore_wait-time:
  Type: object
  Properties:
    cisco-smi-etcd:wait-time:
      Type: integer
      Description: (leaf)
      format: byte
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_daily-defragmentation-start-time:
  Type: object
  Properties:
    cisco-smi-etcd:daily-defragmentation-start-time:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_enable-daily-defragmentation:
  Type: object
  Properties:
    cisco-smi-etcd:enable-daily-defragmentation:
      Type: string
      Description: (leaf)
      format: boolean
```

```
      x-yang:
        Type: leaf
  data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port:
    Type: object
    Properties:
      cisco-smi-etcd:external-ip:
        Type: array
        Description: (list)
        Items:
          Reference: '#/components/schemas/datapost_ciscosmietcdetcd_externalip'
        x-yang:
          Type: list
  data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_ip:

    Type: object
    Properties:
      cisco-smi-etcd:ip:
        Type: string
        Description: (leaf)
        format: union
        x-yang:
          Type: leaf

data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_label:

    Type: object
    Properties:
      cisco-smi-etcd:label:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_port:

    Type: object
    Properties:
      cisco-smi-etcd:port:
        Type: integer
        Description: (leaf)
        format: uint16
        x-yang:
          Type: leaf
  data_cisco-smi-etcd_etcd_go-max-procs:
    Type: object
    Properties:
      cisco-smi-etcd:go-max-procs:
        Type: integer
        Description: (leaf)
        format: byte
        x-yang:
          Type: leaf
```

```
    data_cisco-smi-etcd_etcd_monitoring:
      Type: object
      Properties:
        cisco-smi-etcd:monitoring:
          Reference: '#/components/schemas/datapost_ciscosmietcdetcd_monitoring'
    data_cisco-smi-etcd_etcd_monitoring-post:
      Type: object
      Properties:
        cisco-smi-etcd:enabled:
          Type: string
          Description: (leaf)
          format: boolean
          x-yang:
            Type: leaf
        cisco-smi-etcd:alerts:
          Reference: '#/components/schemas/datapost_ciscosmietcdetcd_monitoring_alerts'
    data_cisco-smi-etcd_etcd_monitoring_alerts:
      Type: object
      Properties:
        cisco-smi-etcd:alerts:
          Reference: '#/components/schemas/datapost_ciscosmietcdetcd_monitoring_alerts'
    data_cisco-smi-etcd_etcd_monitoring_alerts-post:
      Type: object
      Properties:
        cisco-smi-etcd:dbsize:
         Reference: '#/components/schemas/datapost_ciscosmietcdetcd_monitoring_alerts_dbsize'

    data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize:
      Type: object
      Properties:
        cisco-smi-etcd:dbsize:
         Reference: '#/components/schemas/datapost_ciscosmietcdetcd_monitoring_alerts_dbsize'

    data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize-post:
      Type: object
      Properties:
        cisco-smi-etcd:major-alert-threshold:
          Type: integer
          Description: (leaf)
          format: uint32
          x-yang:
            Type: leaf
        cisco-smi-etcd:critical-alert-threshold:
          Type: integer
          Description: (leaf)
          format: uint32
          x-yang:
            Type: leaf

  data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_critical-alert-threshold:

    Type: object
```

```
  Properties:
    cisco-smi-etcd:critical-alert-threshold:
      Type: integer
      Description: (leaf)
      format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_major-alert-threshold:
  Type: object
  Properties:
    cisco-smi-etcd:major-alert-threshold:
      Type: integer
      Description: (leaf)
      format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_monitoring_enabled:
  Type: object
  Properties:
    cisco-smi-etcd:enabled:
      Type: string
      Description: (leaf)
      format: boolean
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_network-policy:
  Type: object
  Properties:
    cisco-smi-etcd:network-policy:
      Reference: '#/components/schemas/datapost_ciscosmietcdetcd_networkpolicy'
data_cisco-smi-etcd_etcd_network-policy-post:
  Type: object
  Properties:
    cisco-smi-etcd:enable:
      Type: string
      Description: (leaf)
      format: boolean
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_network-policy_enable:
  Type: object
  Properties:
    cisco-smi-etcd:enable:
      Type: string
      Description: (leaf)
      format: boolean
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_node-affinity:
  Type: object
  Properties:
```

```
    cisco-smi-etcd:node-affinity:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_replicas:
  Type: object
  Properties:
    cisco-smi-etcd:replicas:
      Type: integer
      Description: (leaf)
      format: byte
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_repository:
  Type: object
  Properties:
    cisco-smi-etcd:repository:
      Type: string
      Description: (leaf)
      format: leafref
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_storage-label:
  Type: object
  Properties:
    cisco-smi-etcd:storage-label:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_tls:
  Type: object
  Properties:
    cisco-smi-etcd:tls:
      Reference: '#/components/schemas/datapost_ciscosmietcdetcd_tls'
data_cisco-smi-etcd_etcd_tls-post:
  Type: object
  Properties:
    cisco-smi-etcd:enable:
      Type: string
      Description: (leaf)
      format: boolean
      x-yang:
        Type: leaf
    cisco-smi-etcd:certificate-config:
     Reference: '#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig'

data_cisco-smi-etcd_etcd_tls_certificate-config:
  Type: object
```

```
    Properties:
      cisco-smi-etcd:certificate-config:
       Reference: '#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig'

  data_cisco-smi-etcd_etcd_tls_certificate-config-post:
    Type: object
    Properties:
      cisco-smi-etcd:server:
        Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server'
      cisco-smi-etcd:peer:
        Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server'
  data_cisco-smi-etcd_etcd_tls_certificate-config_peer:
    Type: object
    Properties:
      cisco-smi-etcd:peer:
        Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server'
  data_cisco-smi-etcd_etcd_tls_certificate-config_peer-post:
    Type: object
    Properties:
      cisco-smi-etcd:ca-cert:
        Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert'
      cisco-smi-etcd:key-pair:
        Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert'
  data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert:
    Type: object
    Properties:
      cisco-smi-etcd:ca-cert:
        Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert'
  data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert-post:
    Type: object
    Properties:
      cisco-smi-etcd:secret-name:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
 data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert_secret-name:

    Type: object
    Properties:
      cisco-smi-etcd:secret-name:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
```

```
    data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair:
      Type: object
      Properties:
        cisco-smi-etcd:key-pair:
          Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert'
    data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair-post:
      Type: object
      Properties:
        cisco-smi-etcd:secret-name:
          Type: string
          Description: (leaf)
          format: leafref
          x-yang:
            Type: leaf
    data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair_secret-name:
      Type: object
      Properties:
        cisco-smi-etcd:secret-name:
          Type: string
          Description: (leaf)
          format: leafref
          x-yang:
            Type: leaf
    data_cisco-smi-etcd_etcd_tls_certificate-config_server:
      Type: object
      Properties:
        cisco-smi-etcd:server:
          Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server'
    data_cisco-smi-etcd_etcd_tls_certificate-config_server-post:
      Type: object
      Properties:
        cisco-smi-etcd:ca-cert:
          Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert'
        cisco-smi-etcd:key-pair:
          Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert'
    data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert:
      Type: object
      Properties:
        cisco-smi-etcd:ca-cert:
          Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert'
    data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert-post:
      Type: object
      Properties:
        cisco-smi-etcd:secret-name:
          Type: string
          Description: (leaf)
          format: leafref
```

```
        x-yang:
          Type: leaf

data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert_secret-name:

    Type: object
    Properties:
      cisco-smi-etcd:secret-name:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
  data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair:
    Type: object
    Properties:
      cisco-smi-etcd:key-pair:
        Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert'
  data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair-post:
    Type: object
    Properties:
      cisco-smi-etcd:secret-name:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf

data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair_secret-name:

    Type: object
    Properties:
      cisco-smi-etcd:secret-name:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
  data_cisco-smi-etcd_etcd_tls_enable:
    Type: object
    Properties:
      cisco-smi-etcd:enable:
        Type: string
        Description: (leaf)
        format: boolean
        x-yang:
          Type: leaf
  data_cisco-smi-etcd_etcd_volume:
    Type: object
    Properties:
      cisco-smi-etcd:volume:
```

```
        Type: integer
        Description: (leaf)
        format: byte
        x-yang:
          Type: leaf
    operations:
      Type: object
      Properties:
        ietf-restconf:operations:
          Type: object
          Properties: {}
          Description: This resource is a container that provides access to the
data-model-specific
            RPC operations supported by the server. See RESTCONF RFC 8040 for further
            information.
          x-yang:
            Type: operations
    root:
      Type: object
      Properties:
        ietf-restconf:restconf:
          Reference: '#/components/schemas/root_ietfrestconfrestconf'
    yang-library-version:
      Type: object
      Properties:
        ietf-restconf:yang-library-version:
          Type: object
          Properties: {}
          Description: This leaf identifies the revision date of the 'ietf-yang-library'
            YANG module that is implemented by this server. See RESTCONF RFC 8040
            for further information.
          x-yang:
            Type: leaf
    datapost_ciscosmietcdetcd_backup_restore:
      Type: object
      Properties:
        use-local-snapshot:
          Type: string
          Description: (leaf)
          format: boolean
          x-yang:
            Type: leaf
        wait-time:
          Type: integer
          Description: (leaf)
          format: byte
          x-yang:
            Type: leaf
      Description: (non-presence)
    datapost_ciscosmietcdetcd_backup:
      Type: object
      Properties:
```

```
      disable:
        Type: string
        Description: (leaf)
        format: boolean
        x-yang:
          Type: leaf
      frequency:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
      restore:
        Reference: '#/components/schemas/datapost_ciscosmietcdetcd_backup_restore'
    Description: (non-presence)
  datapost_ciscosmietcdetcd_externalip:
    Type: object
    Properties:
      ip:
        Type: string
        Description: (leaf)
        format: union
        x-yang:
          Type: leaf
      port:
        Type: integer
        Description: (leaf)
        format: uint16
        x-yang:
          Type: leaf
      label:
        Type: string
        Description: (leaf)
        format: string
        x-yang:
          Type: leaf
  datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert:
    Type: object
    Properties:
      secret-name:
        Type: string
        Description: (leaf)
        format: leafref
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_ciscosmietcdetcd_tls_certificateconfig_server:
    Type: object
    Properties:
      ca-cert:
        Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert'
```

```
      key-pair:
        Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert'
    Description: (non-presence)
  datapost_ciscosmietcdetcd_tls_certificateconfig:
    Type: object
    Properties:
      server:
        Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server'
      peer:
        Reference:
'#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server'
    Description: (non-presence)
  datapost_ciscosmietcdetcd_tls:
    Type: object
    Properties:
      enable:
        Type: string
        Description: (leaf)
        format: boolean
        x-yang:
          Type: leaf
      certificate-config:
       Reference: '#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig'

    Description: (non-presence)
  datapost_ciscosmietcdetcd_monitoring_alerts_dbsize:
    Type: object
    Properties:
      major-alert-threshold:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
      critical-alert-threshold:
        Type: integer
        Description: (leaf)
        format: uint32
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_ciscosmietcdetcd_monitoring_alerts:
    Type: object
    Properties:
      dbsize:
       Reference: '#/components/schemas/datapost_ciscosmietcdetcd_monitoring_alerts_dbsize'

    Description: (non-presence)
  datapost_ciscosmietcdetcd_monitoring:
    Type: object
```

```
  Properties:
    enabled:
      Type: string
      Description: (leaf)
      format: boolean
      x-yang:
        Type: leaf
    alerts:
      Reference: '#/components/schemas/datapost_ciscosmietcdetcd_monitoring_alerts'
  Description: (non-presence)
datapost_ciscosmietcdetcd_networkpolicy:
  Type: object
  Properties:
    enable:
      Type: string
      Description: (leaf)
      format: boolean
      x-yang:
        Type: leaf
  Description: (presence)
datapost_ciscosmietcdetcd_additionalinstances:
  Type: object
  Properties:
    name:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    node-affinity:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    replicas:
      Type: integer
      Description: (leaf)
      format: byte
      x-yang:
        Type: leaf
    go-max-procs:
      Type: integer
      Description: (leaf)
      format: byte
      x-yang:
        Type: leaf
    volume:
      Type: integer
      Description: (leaf)
      format: byte
```

```
      x-yang:
        Type: leaf
    backup:
      Reference: '#/components/schemas/datapost_ciscosmietcdetcd_backup'
    enable-daily-defragmentation:
      Type: string
      Description: (leaf)
      format: boolean
      x-yang:
        Type: leaf
    daily-defragmentation-start-time:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    storage-label:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    external-ip:
      Type: array
      Description: (list)
      Items:
        Reference: '#/components/schemas/datapost_ciscosmietcdetcd_externalip'
      x-yang:
        Type: list
    tls:
      Reference: '#/components/schemas/datapost_ciscosmietcdetcd_tls'
datapost_ciscosmietcdetcd:
  Type: object
  Properties:
    node-affinity:
      Type: string
      Description: (leaf)
      format: string
      x-yang:
        Type: leaf
    replicas:
      Type: integer
      Description: (leaf)
      format: byte
      x-yang:
        Type: leaf
    go-max-procs:
      Type: integer
      Description: (leaf)
      format: byte
      x-yang:
```

```
    Type: leaf
volume:
  Type: integer
  Description: (leaf)
  format: byte
  x-yang:
    Type: leaf
backup:
  Reference: '#/components/schemas/datapost_ciscosmietcdetcd_backup'
enable-daily-defragmentation:
  Type: string
  Description: (leaf)
  format: boolean
  x-yang:
    Type: leaf
daily-defragmentation-start-time:
  Type: string
  Description: (leaf)
  format: string
  x-yang:
    Type: leaf
storage-label:
  Type: string
  Description: (leaf)
  format: string
  x-yang:
    Type: leaf
external-ip:
  Type: array
  Description: (list)
  Items:
    Reference: '#/components/schemas/datapost_ciscosmietcdetcd_externalip'
  x-yang:
    Type: list
tls:
  Reference: '#/components/schemas/datapost_ciscosmietcdetcd_tls'
repository:
  Type: string
  Description: (leaf)
  format: leafref
  x-yang:
    Type: leaf
monitoring:
  Reference: '#/components/schemas/datapost_ciscosmietcdetcd_monitoring'
network-policy:
  Reference: '#/components/schemas/datapost_ciscosmietcdetcd_networkpolicy'
additional-instances:
  Type: array
  Description: (list)
  Items:
   Reference: '#/components/schemas/datapost_ciscosmietcdetcd_additionalinstances'
```

```
        x-yang:
          Type: list
      Description: (non-presence)
    dataputpatch_ietfrestconfdata:
      Type: object
      Properties:
        cisco-smi-etcd:etcd:
          Reference: '#/components/schemas/datapost_ciscosmietcdetcd'
      Description: ''
    root_ietfrestconfrestconf:
      Type: object
      Properties:
        data:
          Type: object
          Properties: {}
        operations:
          Type: object
          Properties: {}
        yang-library-version:
          Type: string
      Description: This is the RESTCONF root resource for the RESTCONF datastore and
        operation resources. See RESTCONF RFC 8040 for further information.
  responses:
    '200':
      Description: OK
      content: {}
    '201':
      Description: Created
      content: {}
    '204':
      Description: No Content
      content: {}
    '400':
      Description: Bad Request
      content: {}
    '401':
      Description: Unauthorized
      content: {}
    '404':
      Description: Not Found
      content: {}
    '405':
      Description: Method Not Allowed
      content: {}
    '409':
      Description: Conflict
      content: {}
  parameters:
    content:
      name: content
      in: query
      Description: controlling descendant nodes in response
```

```
  Required: false
  style: form
  explode: true
  schema:
    Type: string
    format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
depth:
  name: depth
  in: query
  Description: limit the depth of nodes in response
  Required: false
  style: form
  explode: true
  schema:
    Type: integer
    format: uint16
fields:
  name: fields
  in: query
  Description: optionally identify specific data nodes in response
  Required: false
  style: form
  explode: true
  schema:
    Type: string
    format: string
filter:
  name: filter
  in: query
  Description: xpath expression to filter data nodes in response
  Required: false
  style: form
  explode: true
  schema:
    Type: string
    format: string
with-defaults:
  name: with-defaults
  in: query
  Description: controlling default values in response
  Required: false
  style: form
  explode: true
  schema:
    Type: string
    format: enumeration
    Default: report-all
```

```
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
insert:
  name: insert
  in: query
  Description: controlling the order when adding new list elements
  Required: false
  style: form
  explode: true
  schema:
    Type: string
    format: enumeration
    Default: first
    enum:
    - first
    - last
    - before
    - after
point:
  name: point
  in: query
  Description: used to specify the insertion point
  Required: false
  style: form
  explode: true
  schema:
    Type: string
    format: string
additional-instances-name:
  name: additional-instances-name
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: string
external-ip-ip:
  name: external-ip-ip
  in: path
  Required: true
  style: simple
  explode: false
  schema:
    Type: string
    format: union
external-ip-port:
  name: external-ip-port
  in: path
  Required: true
```

```
    style: simple
    explode: false
    schema:
      Type: integer
      format: uint16
requestBodies:
  data-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data-post'
    Required: true
  data-put-patch:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data-put-patch'
    Required: true
  data_cisco-smi-etcd_etcd:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd'
    Required: true
  data_cisco-smi-etcd_etcd-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd-post'
    Required: true
  data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name'
    Required: true
  data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup'
    Required: true
  data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup-post:
    content:
      application/yang-data+json:
        schema:
```

```
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup-post'

    Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_disable:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_disable'

    Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_frequency:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_frequency'

    Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore'

    Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore-post:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore-post'

    Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_use-local-snapshot:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_use-local-snapshot'

    Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_wait-time:
```

```
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_wait-time'

    Required: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_daily-defragmentation-start-time:

```
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_daily-defragmentation-start-time'

    Required: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_enable-daily-defragmentation:

```
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_enable-daily-defragmentation'

    Required: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port:

```
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port'

    Required: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_ip:

```
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_ip'

    Required: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_label:

```
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_label'

    Required: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_port:

  content:
    application/yang-data+json:
      schema:
        Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_port'

  Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_go-max-procs:

  content:
    application/yang-data+json:
      schema:
        Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_go-max-procs'

  Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_name:

  content:
    application/yang-data+json:
      schema:
        Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_name'

  Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_node-affinity:

  content:
    application/yang-data+json:
      schema:
        Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_node-affinity'

  Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_replicas:

  content:
    application/yang-data+json:
      schema:
        Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_replicas'

  Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_storage-label:

  content:
    application/yang-data+json:
      schema:
        Reference:

'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_storage-label'

Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls'

Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls-post:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls-post'

Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config'

Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config-post:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config-post'

Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer:

content:
application/yang-data+json:
schema:
Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer'

Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer-post:

content:

```
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer-post'

    Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert'

    Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert-post:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert-post'

    Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert_secret-name:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert_secret-name'

    Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair'

    Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair-post:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair-post'

    Required: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair_secret-name:

```
  content:
    application/yang-data+json:
      schema:
        Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair_secret-name'

  Required: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server:

```
  content:
    application/yang-data+json:
      schema:
        Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server'

  Required: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server-post:

```
  content:
    application/yang-data+json:
      schema:
        Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server-post'

  Required: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert:

```
  content:
    application/yang-data+json:
      schema:
        Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert'

  Required: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert-post:

```
  content:
    application/yang-data+json:
      schema:
        Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert-post'

  Required: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert_secret-name:

```
  content:
    application/yang-data+json:
      schema:
        Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert_secret-name'
```

```
    Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair'

    Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair-post:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair-post'

    Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair_secret-name:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair_secret-name'

    Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_enable:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_enable'

    Required: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_volume:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_volume'

    Required: true
  data_cisco-smi-etcd_etcd_backup:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_backup'
```

```
    Required: true
  data_cisco-smi-etcd_etcd_backup-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_backup-post'
    Required: true
  data_cisco-smi-etcd_etcd_backup_disable:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_backup_disable'
    Required: true
  data_cisco-smi-etcd_etcd_backup_frequency:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_backup_frequency'
    Required: true
  data_cisco-smi-etcd_etcd_backup_restore:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore'
    Required: true
  data_cisco-smi-etcd_etcd_backup_restore-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore-post'

    Required: true
  data_cisco-smi-etcd_etcd_backup_restore_use-local-snapshot:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore_use-local-snapshot'
    Required: true
  data_cisco-smi-etcd_etcd_backup_restore_wait-time:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore_wait-time'
    Required: true
  data_cisco-smi-etcd_etcd_daily-defragmentation-start-time:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_daily-defragmentation-start-time'
    Required: true
  data_cisco-smi-etcd_etcd_enable-daily-defragmentation:
```

```
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_enable-daily-defragmentation'
    Required: true
  data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port'

    Required: true
  data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_ip:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_ip'

    Required: true

data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_label:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_label'

    Required: true
  data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_port:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_port'

    Required: true
  data_cisco-smi-etcd_etcd_go-max-procs:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_go-max-procs'
    Required: true
  data_cisco-smi-etcd_etcd_monitoring:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_monitoring'
    Required: true
  data_cisco-smi-etcd_etcd_monitoring-post:
```

```
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_monitoring-post'
    Required: true
  data_cisco-smi-etcd_etcd_monitoring_alerts:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts'
    Required: true
  data_cisco-smi-etcd_etcd_monitoring_alerts-post:
    content:
      application/yang-data+json:
        schema:
         Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts-post'

    Required: true
  data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize'
    Required: true
  data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize-post'
    Required: true

data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_critical-alert-threshold:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_critical-alert-threshold'

    Required: true
  data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_major-alert-threshold:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_major-alert-threshold'

    Required: true
  data_cisco-smi-etcd_etcd_monitoring_enabled:
    content:
      application/yang-data+json:
        schema:
```

```
        Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_enabled'
    Required: true
  data_cisco-smi-etcd_etcd_network-policy:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_network-policy'
    Required: true
  data_cisco-smi-etcd_etcd_network-policy-post:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_network-policy-post'

    Required: true
  data_cisco-smi-etcd_etcd_network-policy_enable:
    content:
      application/yang-data+json:
        schema:
         Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_network-policy_enable'

    Required: true
  data_cisco-smi-etcd_etcd_node-affinity:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_node-affinity'
    Required: true
  data_cisco-smi-etcd_etcd_replicas:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_replicas'
    Required: true
  data_cisco-smi-etcd_etcd_repository:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_repository'
    Required: true
  data_cisco-smi-etcd_etcd_storage-label:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_storage-label'
    Required: true
  data_cisco-smi-etcd_etcd_tls:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_tls'
    Required: true
  data_cisco-smi-etcd_etcd_tls-post:
```

```
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_tls-post'
    Required: true
  data_cisco-smi-etcd_etcd_tls_certificate-config:
    content:
      application/yang-data+json:
        schema:
         Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config'

    Required: true
  data_cisco-smi-etcd_etcd_tls_certificate-config-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config-post'
    Required: true
  data_cisco-smi-etcd_etcd_tls_certificate-config_peer:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer'
    Required: true
  data_cisco-smi-etcd_etcd_tls_certificate-config_peer-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer-post'
    Required: true
  data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert'
    Required: true
  data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert-post'
    Required: true
  data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert_secret-name:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert_secret-name'
```

```
    Required: true
  data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair'
    Required: true
  data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair-post'
    Required: true
  data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair_secret-name:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair_secret-name'

    Required: true
  data_cisco-smi-etcd_etcd_tls_certificate-config_server:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server'
    Required: true
  data_cisco-smi-etcd_etcd_tls_certificate-config_server-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server-post'
    Required: true
  data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert'
    Required: true
  data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert-post'
    Required: true

data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert_secret-name:
```

```
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert_secret-name'

    Required: true
  data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair'
    Required: true
  data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair-post:
    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair-post'

    Required: true

data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair_secret-name:

    content:
      application/yang-data+json:
        schema:
          Reference:
'#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair_secret-name'

    Required: true
  data_cisco-smi-etcd_etcd_tls_enable:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_tls_enable'
    Required: true
  data_cisco-smi-etcd_etcd_volume:
    content:
      application/yang-data+json:
        schema:
          Reference: '#/components/schemas/data_cisco-smi-etcd_etcd_volume'
    Required: true
securitySchemes:
  basicAuth:
    Type: http
    scheme: basic
x-original-swagger-version: '2.0'
```