

cdl

- OpenAPI, on page 1
- Info, on page 1
- Servers, on page 1
- tags, on page 1
- Paths, on page 2
- Components, on page 2446

OpenAPI

OpenAPI Version: 3.0.1

Info

Title: cisco-smi-cdl
Description:
Version: 2026-05-11

Servers

- **URL**: /restconf

tags

- **Name**: root
  Description: root resources
- **Name**: operations
  Description: operations resources
- **Name**: data
  Description: data resources

```
- Name: get
  Description: get resources
- Name: head
  Description: head resources
- Name: post
  Description: post resources
- Name: patch
  Description: patch resources
- Name: put
  Description: put resources
- Name: options
  Description: options resources
- Name: delete
  Description: delete resources
```

Paths

/

```
get:

  Tags:
  - root
  - get
  Operation ID: root_get

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/root"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - root
  - head
  Operation ID: root_head

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/operations

```
get:

  Tags:
  - operations
  - get
  Operation ID: operations_get

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/operations"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
```

/yang-library-version

```
get:

  Tags:
  - yang-library-version
  - get
  Operation ID: yang_library_version_get

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/yang-library-version"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - yang-library-version
  - head
  Operation ID: yang_library_version_head

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data


```
get:

  Tags:
  - data
  - get
  Operation ID: data_get

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data-put-patch"
    Required/Optional: true

  Responses:
    "201":
      Description: Created
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: data
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data-post"
    Required/Optional: true

  Responses:
    "201":
      Description: Created
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: data
head:

  Tags:
  - data
  - head
  Operation ID: data_head

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data-put-patch"
    Required/Optional: true

  Responses:
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: data
```

/data/cisco-smi-cdl:feature-gates

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_feature_gates_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_feature-gates"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_feature_gates_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_feature-gates"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: container feature-gates created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: feature-gates
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_cdl_feature_gates_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_feature-gates-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container feature-gates created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: feature-gates
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_feature_gates_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_feature_gates_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_feature_gates_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_feature_gates_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_feature-gates"
    Required/Optional: true

  Responses:
    "204":
      Description: container feature-gates updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: feature-gates
```

/data/cisco-smi-cdl:feature-gates/alpha

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_feature_gates_alpha_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_feature-gates_alpha"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_feature_gates_alpha_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_feature-gates_alpha"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf alpha created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: alpha
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_feature_gates_alpha_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_feature_gates_alpha_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_feature_gates_alpha_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_feature_gates_alpha_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_feature-gates_alpha"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf alpha updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: alpha
```

/data/cisco-smi-cdl:feature-gates/test

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_feature_gates_test_get

  Parameters:
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_feature-gates_test"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_feature_gates_test_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_feature-gates_test"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf test created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: test
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_feature_gates_test_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_feature_gates_test_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_feature_gates_test_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_feature_gates_test_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_feature-gates_test"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf test updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: test
```

/data/cisco-smi-cdl:cdl

```
get:

  Tags:
  - data
  - get
  Summary: Configure cdl parameters for deployment. If cdl container is not configured,
 the cdl chart
     wont be deployed
  Description: Configure cdl parameters for deployment. If cdl container is not
configured, the cdl chart
```

```
  wont be deployed
Operation ID: data_cisco_smi_cdl_cdl_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: Configure cdl parameters for deployment. If cdl container is not
configured, the cdl chart
          wont be deployed
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_cisco-smi-cdl_cdl"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Summary: Configure cdl parameters for deployment. If cdl container is not configured,
 the cdl chart
      wont be deployed
    Description: Configure cdl parameters for deployment. If cdl container is not
configured, the cdl chart
      wont be deployed
    Operation ID: data_cisco_smi_cdl_cdl_put
    Request Body:
      Description: Configure cdl parameters for deployment. If cdl container is not
configured, the cdl chart
        wont be deployed
      Content:
```

```
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl"
      Required/Optional: true

    Responses:
      "201":
        Description: container cdl created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cdl
  Method: Post:

    Tags:
    - data
    - post
    Summary: Configure cdl parameters for deployment. If cdl container is not configured,
 the cdl chart
       wont be deployed
    Description: Configure cdl parameters for deployment. If cdl container is not
configured, the cdl chart
       wont be deployed
    Operation ID: data_cisco_smi_cdl_cdl_post
    Request Body:
      Description: Configure cdl parameters for deployment. If cdl container is not
configured, the cdl chart
         wont be deployed
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl-post"
      Required/Optional: true

    Responses:
      "201":
```

```
      Description: container cdl created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cdl
delete:

  Tags:
  - data
  - delete
  Summary: Configure cdl parameters for deployment. If cdl container is not configured,
 the cdl chart
    wont be deployed
  Description: Configure cdl parameters for deployment. If cdl container is not
configured, the cdl chart
    wont be deployed
  Operation ID: data_cisco_smi_cdl_cdl_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Summary: Configure cdl parameters for deployment. If cdl container is not configured,
 the cdl chart
    wont be deployed
  Description: Configure cdl parameters for deployment. If cdl container is not
configured, the cdl chart
    wont be deployed
  Operation ID: data_cisco_smi_cdl_cdl_options
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Summary: Configure cdl parameters for deployment. If cdl container is not configured,
  the cdl chart
      wont be deployed
    Description: Configure cdl parameters for deployment. If cdl container is not
configured, the cdl chart
      wont be deployed
    Operation ID: data_cisco_smi_cdl_cdl_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Summary: Configure cdl parameters for deployment. If cdl container is not configured,
 the cdl chart
      wont be deployed
    Description: Configure cdl parameters for deployment. If cdl container is not
configured, the cdl chart
      wont be deployed
    Operation ID: data_cisco_smi_cdl_cdl_patch
    Request Body:
      Description: Configure cdl parameters for deployment. If cdl container is not
configured, the cdl chart
        wont be deployed
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl"
      Required/Optional: true

    Responses:
      "204":
        Description: container cdl updated
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cdl
```

/data/cisco-smi-cdl:cdl/repository

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_repository_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_repository"
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_repository_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_repository"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf repository created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: repository
delete:

  Tags:
  - data
```

```
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_repository_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_repository_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_repository_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_repository_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_repository"
      Required/Optional: true

    Responses:
```

```
    "204":
      Description: leaf repository updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: repository
```

/data/cisco-smi-cdl:cdl/system-id

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_system_id_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_system-id"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_system_id_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_system-id"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf system-id created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: system-id
delete:
```

```
  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_system_id_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_system_id_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_system_id_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_system_id_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_system-id"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: leaf system-id updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: system-id
```

/data/cisco-smi-cdl:cdl/node-type

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_node_type_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_node-type"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_node_type_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_node-type"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf node-type created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  x-codegen-request-body-name: node-type
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_node_type_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_node_type_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_node_type_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_node_type_patch
    Request Body:
      Content:
        application/yang-data+json:
```

```
      Schema:
        Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_node-type"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf node-type updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: node-type
```

/data/cisco-smi-cdl:cdl/enable-geo-replication

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_enable_geo_replication_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_enable-geo-replication"
    "204":
      Description: No Content
      Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_enable_geo_replication_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_enable-geo-replication"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf enable-geo-replication created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable-geo-replication
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_enable_geo_replication_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_enable_geo_replication_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_enable_geo_replication_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_enable_geo_replication_patch
```

```
Request Body:
  Content:
    application/yang-data+json:
      Schema:
       Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_enable-geo-replication"

  Required/Optional: true

Responses:
  "204":
    Description: leaf enable-geo-replication updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: enable-geo-replication
```

/data/cisco-smi-cdl:cdl/use-rust-image

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_use_rust_image_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
```

```
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_use-rust-image"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_use_rust_image_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_use-rust-image"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf use-rust-image created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: use-rust-image
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_use_rust_image_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_use_rust_image_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_use_rust_image_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
```

```
- data
- patch
Operation ID: data_cisco_smi_cdl_cdl_use_rust_image_patch
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_use-rust-image"
  Required/Optional: true

Responses:
  "204":
    Description: leaf use-rust-image updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: use-rust-image
```

/data/cisco-smi-cdl:cdl/deployment-model

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_deployment_model_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_deployment-model"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_deployment_model_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_deployment-model"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf deployment-model created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: deployment-model
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_deployment_model_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_deployment_model_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_deployment_model_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_deployment_model_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_deployment-model"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf deployment-model updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: deployment-model
```

/data/cisco-smi-cdl:cdl/api

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_api_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_api_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api"
    Required/Optional: true

  Responses:
    "201":
      Description: container api created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: api
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_cdl_cdl_api_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container api created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: api
delete:

  Tags:
  - data
  - delete
```

```
  Operation ID: data_cisco_smi_cdl_cdl_api_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_api_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_api_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_api_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api"
    Required/Optional: true

  Responses:
    "204":
```

```
      Description: container api updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: api
```

/data/cisco-smi-cdl:cdl/api/deploy

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_api_deploy_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_deploy"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_api_deploy_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_deploy"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf deploy created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: deploy
delete:
```

```
  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_api_deploy_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_api_deploy_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_api_deploy_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_api_deploy_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_deploy"
    Required/Optional: true
```

```
  Responses:
    "204":
      Description: leaf deploy updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: deploy
```

/data/cisco-smi-cdl:cdl/api/external-ip

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_api_external_ip_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_external-ip"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_api_external_ip_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_external-ip"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf external-ip created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: external-ip
```

```
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_api_external_ip_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_api_external_ip_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_api_external_ip_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_api_external_ip_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_external-ip"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf external-ip updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: external-ip
```

/data/cisco-smi-cdl:cdl/api/storage

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_api_storage_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_storage"
  "204":
    Description: No Content
    Content: {}
  "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_api_storage_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_storage"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf storage created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: storage
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_api_storage_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_api_storage_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_api_storage_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_api_storage_patch
    Request Body:
      Content:
```

```
    application/yang-data+json:
      Schema:
        Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_storage"
  Required/Optional: true

Responses:
  "204":
    Description: leaf storage updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: storage
```

/data/cisco-smi-cdl:cdl/api/go-max-procs

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_api_go_max_procs_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_go-max-procs"
  "204":
    Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_api_go_max_procs_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_go-max-procs"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf go-max-procs created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: go-max-procs
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_api_go_max_procs_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_api_go_max_procs_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_api_go_max_procs_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_api_go_max_procs_patch
```

```
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_go-max-procs"
  Required/Optional: true

Responses:
  "204":
    Description: leaf go-max-procs updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: go-max-procs
```

/data/cisco-smi-cdl:cdl/api/cpu-limit

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_api_cpu_limit_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_cpu-limit"
```

```
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_api_cpu_limit_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_cpu-limit"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf cpu-limit created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cpu-limit
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_api_cpu_limit_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_api_cpu_limit_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_api_cpu_limit_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
```

```
- patch
Operation ID: data_cisco_smi_cdl_cdl_api_cpu_limit_patch
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_cpu-limit"
  Required/Optional: true

Responses:
  "204":
    Description: leaf cpu-limit updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: cpu-limit
```

/data/cisco-smi-cdl:cdl/api/memory-limit

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_api_memory_limit_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_memory-limit"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_api_memory_limit_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_memory-limit"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf memory-limit created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory-limit
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_api_memory_limit_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_api_memory_limit_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_api_memory_limit_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:
```

```
    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_api_memory_limit_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_memory-limit"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf memory-limit updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: memory-limit
```

/data/cisco-smi-cdl:cdl/advanced-config-profile

```
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_advanced_config_profile_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/advanced-config-profile={advanced-config-profile-name}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_get

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_put

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name"

      Required/Optional: true

    Responses:
      "201":
        Description: list advanced-config-profile created or replaced
        Content: {}
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: advanced-config-profile
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_delete

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_options

    Parameters:
```

```
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_head

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: integer
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_patch

      Parameters:
      - Name: advanced-config-profile-name
        In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name"

      Required/Optional: true

    Responses:
      "204":
        Description: list advanced-config-profile updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: advanced-config-profile
```

/data/cisco-smi-cdl:cdl/advanced-config-profile={advanced-config-profile-name}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_name_get

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_name_put

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_name"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_name_delete

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_name_options

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_name_head

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_name_patch

  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_name"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf name updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
```

/data/cisco-smi-cdl:cdl/advanced-config-profile={advanced-config-profile-name}/e

get:

Tags:
- data
- get

Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_get

Parameters:
- **Name**: advanced-config-profile-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_put

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint"

      Required/Optional: true

    Responses:
      "201":
        Description: container endpoint created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: endpoint
  Method: Post:
```

```
    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_post

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container endpoint created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: endpoint
  delete:

    Tags:
    - data
```

```
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_delete


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_options


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_head

    Parameters:
```

```
- Name: advanced-config-profile-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_patch

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint"

      Required/Optional: true

    Responses:
      "204":
        Description: container endpoint updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: endpoint
```

/data/cisco-smi-cdl:cdl/advanced-config-profile={advanced-config-profile-name}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_write_response_queue_size_get

  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_write-response-queue-size"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_write_response_queue_size_put


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_write-response-queue-size"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf write-response-queue-size created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: write-response-queue-size
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_write_response_queue_size_delete


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_write_response_queue_size_options


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_write_response_queue_size_head


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_write_response_queue_size_patch


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_write-response-queue-size"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf write-response-queue-size updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: write-response-queue-size
```

/data/cisco-smi-cdl:cdl/advanced-config-profile={advanced-config-profile-name}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_write_worker_count_get


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_write-worker-count"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_write_worker_count_put


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_write-worker-count"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf write-worker-count created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: write-worker-count
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_write_worker_count_delete


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_write_worker_count_options


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_write_worker_count_head


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_write_worker_count_patch


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_write-worker-count"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf write-worker-count updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: write-worker-count
```

/data/cisco-smi-cdl:cdl/advanced-config-profile={advanced-config-profile-name}/e

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_write_queue_size_get


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_write-queue-size"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_write_queue_size_put


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_write-queue-size"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf write-queue-size created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
    security:
    - basicAuth: []
    x-codegen-request-body-name: write-queue-size
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_write_queue_size_delete


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_write_queue_size_options


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:
```

```
    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_write_queue_size_head


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_write_queue_size_patch


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_write-queue-size"

      Required/Optional: true
```

```
  Responses:
    "204":
      Description: leaf write-queue-size updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: write-queue-size
```

/data/cisco-smi-cdl:cdl/advanced-config-profile={advanced-config-profile-name}/e

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_read_response_queue_size_get


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_read-response-queue-size"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_read_response_queue_size_put


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_read-response-queue-size"

      Required/Optional: true

    Responses:
      "201":
```

```
      Description: leaf read-response-queue-size created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: read-response-queue-size
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_read_response_queue_size_delete


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
```

```
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_read_response_queue_size_options

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_read_response_queue_size_head

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
```

data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_read_response_queue_size_patch

```
  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_read-response-queue-size"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf read-response-queue-size updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: read-response-queue-size
```

/data/cisco-smi-cdl:cdl/advanced-config-profile={advanced-config-profile-name}/e

```
get:

  Tags:
  - data
  - get
  Operation ID:
```

data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_read_worker_count_get

```
Parameters:
- Name: advanced-config-profile-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_read-worker-count"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_read_worker_count_put
```

```
    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_read-worker-count"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf read-worker-count created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: read-worker-count
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_read_worker_count_delete


    Parameters:
```

```
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_read_worker_count_options


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_read_worker_count_head


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_read_worker_count_patch


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_read-worker-count"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf read-worker-count updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: read-worker-count
```

/data/cisco-smi-cdl:cdl/advanced-config-profile={advanced-config-profile-name}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_read_queue_size_get


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_read-queue-size"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_read_queue_size_put


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_read-queue-size"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf read-queue-size created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: read-queue-size
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_read_queue_size_delete


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_read_queue_size_options


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_read_queue_size_head


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_read_queue_size_patch


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_read-queue-size"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf read-queue-size updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: read-queue-size
```

/data/cisco-smi-cdl:cdl/advanced-config-profile={advanced-config-profile-name}

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_max_concurrent_operations_get


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_max-concurrent-operations"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_max_concurrent_operations_put


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_max-concurrent-operations"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf max-concurrent-operations created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: max-concurrent-operations
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_max_concurrent_operations_delete


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
```

```
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_max_concurrent_operations_options


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_max_concurrent_operations_head


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_max_concurrent_operations_patch


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_max-concurrent-operations"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf max-concurrent-operations updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: max-concurrent-operations
```

/data/cisco-smi-cdl:cdl/advanced-config-profile={advanced-config-profile-name}/e

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_operation_timeout_get


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_operation-timeout"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_operation_timeout_put


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_operation-timeout"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf operation-timeout created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: operation-timeout
```

```
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_operation_timeout_delete


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_operation_timeout_options


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_operation_timeout_head

Parameters:
- **Name**: advanced-config-profile-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_operation_timeout_patch


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_operation-timeout"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf operation-timeout updated
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: operation-timeout
```

/data/cisco-smi-cdl:cdl/advanced-config-profile={advanced-config-profile-name}/e

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_index_timeout_get


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_index-timeout"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_index_timeout_put


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_index-timeout"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf index-timeout created or replaced
        Content: {}
      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: index-timeout
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_index_timeout_delete


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_index_timeout_options


  Parameters:
```

```
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_index_timeout_head


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_index_timeout_patch


    Parameters:
    - Name: advanced-config-profile-name
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_index-timeout"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf index-timeout updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: index-timeout
```


/data/cisco-smi-cdl:cdl/advanced-config-profile={advanced-config-profile-name}/e


```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_slot_timeout_get


    Parameters:
    - Name: advanced-config-profile-name
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_slot-timeout"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_slot_timeout_put


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_slot-timeout"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf slot-timeout created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: slot-timeout
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_slot_timeout_delete


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_slot_timeout_options


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_slot_timeout_head


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_slot_timeout_patch


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_slot-timeout"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf slot-timeout updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: slot-timeout
```

/data/cisco-smi-cdl:cdl/advanced-config-profile={advanced-config-profile-name}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_remote_ep_connection_count_get

  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_remote-ep-connection-count"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_remote_ep_connection_count_put


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_remote-ep-connection-count"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf remote-ep-connection-count created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: remote-ep-connection-count
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_remote_ep_connection_count_delete


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_remote_ep_connection_count_options


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_remote_ep_connection_count_head


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_endpoint_remote_ep_connection_count_patch


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_remote-ep-connection-count"

Required/Optional: true

Responses:
"204":
Description: leaf remote-ep-connection-count updated
Content: {}
"400":
Description: Bad Request
Content: {}
"401":
Description: Unauthorized
Content: {}
"404":
Description: Not Found
Content: {}
"405":
Description: Method Not Allowed
Content: {}
"409":
Description: Conflict
Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: remote-ep-connection-count

/data/cisco-smi-cdl:cdl/advanced-config-profile={advanced-config-profile-name}

get:

Tags:
- data
- get
Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_get

Parameters:
- Name: advanced-config-profile-name
In: path
Required/Optional: true
Style: simple
Explode: false
Schema:
Type: string
Format: string
- Name: content
In: query
Description: controlling descendant nodes in response
Required/Optional: false
Style: form
Explode: true

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_put

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index"

      Required/Optional: true
```

```
    Responses:
      "201":
        Description: container index created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: index
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_post

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index-post"

      Required/Optional: true

    Responses:
      "201":
```

```
      Description: container index created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: index
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_delete

  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
```

```
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_options

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_head

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_patch

    Parameters:
```

```
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index"

      Required/Optional: true

    Responses:
      "204":
        Description: container index updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: index
```

/data/cisco-smi-cdl:cdl/advanced-config-profile={advanced-config-profile-name}/in

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_init_record_count_get

    Parameters:
```

```
- Name: advanced-config-profile-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index_init-record-count"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_init_record_count_put


    Parameters:
    - Name: advanced-config-profile-name
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index_init-record-count"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf init-record-count created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: init-record-count
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_init_record_count_delete

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_init_record_count_options


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_init_record_count_head


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_init_record_count_patch


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index_init-record-count"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf init-record-count updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: init-record-count
```

/data/cisco-smi-cdl:cdl/advanced-config-profile={advanced-config-profile-name}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_audit_get


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index_audit"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_audit_put


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index_audit"

    Required/Optional: true

  Responses:
    "201":
      Description: container audit created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: audit
Method: Post:

  Tags:
  - data
  - post
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_audit_post


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index_audit-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container audit created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: audit
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_audit_delete


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_audit_options


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_audit_head


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_audit_patch


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index_audit"

Required/Optional: true

Responses:
"204":
Description: container audit updated
Content: {}
"400":
Description: Bad Request
Content: {}
"401":
Description: Unauthorized
Content: {}
"404":
Description: Not Found
Content: {}
"405":
Description: Method Not Allowed
Content: {}
"409":
Description: Conflict
Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: audit

/data/cisco-smi-cdl:cdl/advanced-config-profile={advanced-config-profile-name}/in

get:

Tags:
- data
- get
Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_audit_record_expiry_duration_get

Parameters:
- Name: advanced-config-profile-name
In: path
Required/Optional: true
Style: simple
Explode: false
Schema:
Type: string
Format: string
- Name: content
In: query
Description: controlling descendant nodes in response
Required/Optional: false
Style: form

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index_audit_record-expiry-duration"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_audit_record_expiry_duration_put


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index_audit_record-expiry-duration"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: leaf record-expiry-duration created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: record-expiry-duration
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_audit_record_expiry_duration_delete


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_audit_record_expiry_duration_options

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_audit_record_expiry_duration_head

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_index_audit_record_expiry_duration_patch


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index_audit_record-expiry-duration"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf record-expiry-duration updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: record-expiry-duration
```

/data/cisco-smi-cdl:cdl/advanced-config-profile={advanced-config-profile-name}/sl

```
  get:
```

```
    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_slot_get

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_slot"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_slot_put

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_slot"

      Required/Optional: true

    Responses:
      "201":
        Description: container slot created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: slot
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_slot_post
```

```
    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_slot-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container slot created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: slot
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_slot_delete

    Parameters:
```

```
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_slot_options

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_slot_head

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_slot_patch

    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_slot"

      Required/Optional: true

    Responses:
      "204":
        Description: container slot updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: slot
```

/data/cisco-smi-cdl:cdl/advanced-config-profile={advanced-config-profile-name}/sl

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_slot_init_record_count_get


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_slot_init-record-count"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_slot_init_record_count_put


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_slot_init-record-count"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf init-record-count created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: init-record-count
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_slot_init_record_count_delete


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_slot_init_record_count_options


  Parameters:
  - Name: advanced-config-profile-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
```

```
      Description: OK
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_slot_init_record_count_head


    Parameters:
    - Name: advanced-config-profile-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
        Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_cisco_smi_cdl_cdl_advanced_config_profile_advanced_config_profile_name_slot_init_record_count_patch


      Parameters:
      - Name: advanced-config-profile-name
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_slot_init-record-count"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf init-record-count updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: init-record-count
```

/data/cisco-smi-cdl:cdl/remote-site

```
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_remote_site_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/remote-site={remote-site-system-id}

```
get:

  Tags:
  - data
  - get
```

```
Operation ID: data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_get

Parameters:
- Name: remote-site-system-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_put

    Parameters:
    - Name: remote-site-system-id
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id"
    Required/Optional: true

  Responses:
    "201":
      Description: list remote-site created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: remote-site
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_delete

  Parameters:
  - Name: remote-site-system-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_options

  Parameters:
  - Name: remote-site-system-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_head

  Parameters:
  - Name: remote-site-system-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_patch

    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id"
      Required/Optional: true
```

```
Responses:
  "204":
    Description: list remote-site updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: remote-site
```

/data/cisco-smi-cdl:cdl/remote-site={remote-site-system-id}/system-id

```
get:

  Tags:
  - data
  - get
 Operation ID: data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_system_id_get


  Parameters:
  - Name: remote-site-system-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_system-id"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_system_id_put


    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_system-id"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf system-id created or replaced
        Content: {}
      "204":
```

```
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: system-id
  delete:

    Tags:
    - data
    - delete
   Operation ID: data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_system_id_delete


    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_system_id_options

    Parameters:
    - Name: remote-site-system-id
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_system_id_head


  Parameters:
  - Name: remote-site-system-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_system_id_patch


    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_system-id"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf system-id updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: system-id
```


/data/cisco-smi-cdl:cdl/remote-site={remote-site-system-id}/db-endpoint


```
  get:

    Tags:
    - data
    - get
   Operation ID: data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_db_endpoint_get


    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_db-endpoint"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_db_endpoint_put


    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
```

```
        Format: uint32
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_db-endpoint"

        Required/Optional: true

      Responses:
        "201":
          Description: container db-endpoint created or replaced
          Content: {}
        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
      x-codegen-request-body-name: db-endpoint
    Method: Post:

      Tags:
      - data
      - post
     Operation ID: data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_db_endpoint_post


      Parameters:
      - Name: remote-site-system-id
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: integer
          Format: uint32
      Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_db-endpoint-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container db-endpoint created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: db-endpoint
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_db_endpoint_delete

    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "204":
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
 options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_db_endpoint_options

  Parameters:
  - Name: remote-site-system-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
 Operation ID: data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_db_endpoint_head


  Parameters:
  - Name: remote-site-system-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_db_endpoint_patch

    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_db-endpoint"

      Required/Optional: true

    Responses:
      "204":
        Description: container db-endpoint updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: db-endpoint
```

/data/cisco-smi-cdl:cdl/remote-site={remote-site-system-id}/db-endpoint/host

get:

Tags:
- data
- get

Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_db_endpoint_host_get

Parameters:
- **Name**: remote-site-system-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_db-endpoint_host"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_db_endpoint_host_put

    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_db-endpoint_host"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf host created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: host
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_db_endpoint_host_delete

    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_db_endpoint_host_options

    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_db_endpoint_host_head

    Parameters:
```

```
- Name: remote-site-system-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_db_endpoint_host_patch

    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_db-endpoint_host"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf host updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: host
```

/data/cisco-smi-cdl:cdl/remote-site={remote-site-system-id}/db-endpoint/port

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_db_endpoint_port_get

  Parameters:
  - Name: remote-site-system-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_db-endpoint_port"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_db_endpoint_port_put

    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_db-endpoint_port"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf port created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_db_endpoint_port_delete

    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_db_endpoint_port_options

    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_db_endpoint_port_head

    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: string
        Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_db_endpoint_port_patch

      Parameters:
      - Name: remote-site-system-id
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: integer
          Format: uint32
      Request Body:
        Content:
          application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_db-endpoint_port"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf port updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: port
```

/data/cisco-smi-cdl:cdl/remote-site={remote-site-system-id}/kafka-server

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_options

    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "200":
        Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/remote-site={remote-site-system-id}/kafka-server={kafka-se

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_get


  Parameters:
  - Name: remote-site-system-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: kafka-server-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: kafka-server-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port"

"204":
Description: No Content
Content: {}
"400":
Description: Bad Request
Content: {}
"401":
Description: Unauthorized
Content: {}
"404":
Description: Not Found
Content: {}
"405":
Description: Method Not Allowed
Content: {}
"409":
Description: Conflict
Content: {}
security:
- basicAuth: []
put:

Tags:
- data
- put
Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_put

Parameters:
- Name: remote-site-system-id
In: path
Required/Optional: true
Style: simple
Explode: false
Schema:
Type: integer
Format: uint32
- Name: kafka-server-host
In: path
Required/Optional: true
Style: simple
Explode: false
Schema:
Type: string
Format: string
- Name: kafka-server-port
In: path
Required/Optional: true
Style: simple
Explode: false

```
      Schema:
        Type: integer
        Format: uint16
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port"

      Required/Optional: true

    Responses:
      "201":
        Description: list kafka-server created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: kafka-server
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_delete


  Parameters:
  - Name: remote-site-system-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: kafka-server-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: kafka-server-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
```

```
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_options

    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: kafka-server-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: kafka-server-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_head

    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
```

```
    Format: uint32
- Name: kafka-server-host
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: kafka-server-port
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_patch


    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: kafka-server-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    - Name: kafka-server-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port"

      Required/Optional: true

    Responses:
      "204":
        Description: list kafka-server updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: kafka-server
```


/data/cisco-smi-cdl:cdl/remote-site={remote-site-system-id}/kafka-server={kafka-se


```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_host_get


    Parameters:
```

```
- Name: remote-site-system-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: kafka-server-host
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: kafka-server-port
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port_host"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_host_put


    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: kafka-server-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: kafka-server-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port_host"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf host created or replaced
        Content: {}
      "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: host
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_host_delete


  Parameters:
  - Name: remote-site-system-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: kafka-server-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: kafka-server-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
```

```
      Format: uint16

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_host_options


  Parameters:
  - Name: remote-site-system-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: kafka-server-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: kafka-server-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
```

Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_host_head

Parameters:
- **Name**: remote-site-system-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- **Name**: kafka-server-host
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: kafka-server-port
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_host_patch


    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: integer
        Format: uint32
    - Name: kafka-server-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: kafka-server-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port_host"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf host updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: host
```

/data/cisco-smi-cdl:cdl/remote-site={remote-site-system-id}/kafka-server={kafka-


```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_port_get


  Parameters:
  - Name: remote-site-system-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: kafka-server-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: kafka-server-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port_port"

      "204":
        Description: No Content
        Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_port_put


    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: kafka-server-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: kafka-server-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port_port"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf port created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_port_delete


    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: kafka-server-host
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: kafka-server-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_port_options


    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: kafka-server-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: kafka-server-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
```

```
      Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_port_head


    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: kafka-server-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: kafka-server-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_port_patch


    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: kafka-server-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: kafka-server-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port_port"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf port updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: port
```

/data/cisco-smi-cdl:cdl/remote-site={remote-site-system-id}/kafka-server={kafka-

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_ssl_port_get

  Parameters:
  - Name: remote-site-system-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: kafka-server-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: kafka-server-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port_ssl-port"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_ssl_port_put


    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: kafka-server-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    - Name: kafka-server-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port_ssl-port"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf ssl-port created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ssl-port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_ssl_port_delete
```

```
    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: kafka-server-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: kafka-server-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_ssl_port_options


    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: kafka-server-host
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: kafka-server-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_ssl_port_head


    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: kafka-server-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: kafka-server-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_remote_site_remote_site_system_id_kafka_server_kafka_server_host_kafka_server_port_ssl_port_patch


    Parameters:
    - Name: remote-site-system-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: kafka-server-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: kafka-server-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port_ssl-port"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: leaf ssl-port updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ssl-port
```

/data/cisco-smi-cdl:cdl/label-config

```
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_label_config_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/label-config={label-config-name}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_get
```

```
Parameters:
- Name: label-config-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_put

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name"
      Required/Optional: true

    Responses:
      "201":
        Description: list label-config created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: label-config
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_delete

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_options

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
```

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_head

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_patch

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name"
      Required/Optional: true

    Responses:
      "204":
```

```
      Description: list label-config updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: label-config
```

/data/cisco-smi-cdl:cdl/label-config={label-config-name}/name

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_name_get

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
      - nonconfig
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_name"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_name_put

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_name"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_name_delete

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_name_options

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_name_head

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_name_patch

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_name"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
```

/data/cisco-smi-cdl:cdl/label-config={label-config-name}/endpoint

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_endpoint_get

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_endpoint"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_endpoint_put

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_endpoint"
      Required/Optional: true

    Responses:
```

```
      "201":
        Description: container endpoint created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: endpoint
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_endpoint_post

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_endpoint-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container endpoint created
        Content: {}
      "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: endpoint
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_endpoint_delete

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_endpoint_options


  Parameters:
  - Name: label-config-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_endpoint_head

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_endpoint_patch

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_endpoint"
      Required/Optional: true

    Responses:
      "204":
        Description: container endpoint updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: endpoint
```

/data/cisco-smi-cdl:cdl/label-config={label-config-name}/endpoint/key

```
  get:

    Tags:
    - data
    - get
   Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_endpoint_key_get


    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_endpoint_key"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_endpoint_key_put


    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_endpoint_key"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf key created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key
  delete:

    Tags:
    - data
    - delete
   Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_endpoint_key_delete


    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
```

```
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_endpoint_key_options

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_endpoint_key_head


    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
   Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_endpoint_key_patch


    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_endpoint_key"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf key updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key
```

/data/cisco-smi-cdl:cdl/label-config={label-config-name}/endpoint/value

```
  get:

    Tags:
```

```
- data
- get
Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_endpoint_value_get


Parameters:
- Name: label-config-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_endpoint_value"

        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    put:

      Tags:
      - data
      - put
     Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_endpoint_value_put
```

```
    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_endpoint_value"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf value created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: value
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_endpoint_value_delete

    Parameters:
```

```
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_endpoint_value_options

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_endpoint_value_head


    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_endpoint_value_patch

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_endpoint_value"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf value updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: value
```

/data/cisco-smi-cdl:cdl/label-config={label-config-name}/slot

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_get

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_slot"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_put

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_slot"
      Required/Optional: true

    Responses:
      "201":
        Description: container slot created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
    security:
    - basicAuth: []
    x-codegen-request-body-name: slot
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_post

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_slot-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container slot created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: slot
  delete:
```

```
  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_delete

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_options

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_head

  Parameters:
  - Name: label-config-name
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_patch

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_slot"
      Required/Optional: true

    Responses:
      "204":
        Description: container slot updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: slot
```

/data/cisco-smi-cdl:cdl/label-config={label-config-name}/slot/map

```
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_options


  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/label-config={label-config-name}/slot/map={map-map-id}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_get

  Parameters:
  - Name: label-config-name
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: map-map-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_put

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id"

      Required/Optional: true
```

```
    Responses:
      "201":
        Description: list map created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: map
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_delete

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "204":
```

```
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_options

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_head

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_patch

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id"

      Required/Optional: true

    Responses:
      "204":
```

```
      Description: list map updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: map
```

/data/cisco-smi-cdl:cdl/label-config={label-config-name}/slot/map={map-map-id}/

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_map_id_get

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: map-map-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id_map-id"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_map_id_put

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id_map-id"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf map-id created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: map-id
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_map_id_delete

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_map_id_options

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_map_id_head
```

```
Parameters:
- Name: label-config-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: map-map-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_map_id_patch

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
```

```
        Format: uint16
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id_map-id"

        Required/Optional: true

      Responses:
        "204":
          Description: leaf map-id updated
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
      x-codegen-request-body-name: map-id
```

/data/cisco-smi-cdl:cdl/label-config={label-config-name}/slot/map={map-map-id}/ke

```
    get:

      Tags:
      - data
      - get
      Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_key_get

      Parameters:
      - Name: label-config-name
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
```

```
- Name: map-map-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id_key"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_key_put

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id_key"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf key created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key
  delete:

    Tags:
    - data
    - delete
    Operation ID:
```

```
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_key_delete

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_key_options

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
```

```
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_key_head

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_key_patch

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id_key"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf key updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key
```

/data/cisco-smi-cdl:cdl/label-config={label-config-name}/slot/map={map-map-id}/

```
  get:

    Tags:
    - data
    - get
```

```
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_value_get

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id_value"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_value_put

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id_value"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf value created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: value
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_value_delete

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: map-map-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_value_options

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
        Type: string
        Format: string
      - Name: map-map-id
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: integer
          Format: uint16

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    head:

      Tags:
      - data
      - head
      Operation ID:
  data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_value_head

      Parameters:
      - Name: label-config-name
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
      - Name: map-map-id
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: integer
          Format: uint16
      - Name: content
        In: query
        Description: controlling descendant nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: config
          enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_slot_map_map_map_id_value_patch

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id_value"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf value updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: value
```

/data/cisco-smi-cdl:cdl/label-config={label-config-name}/index

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_index_get

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_index"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_index_put

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_index"
      Required/Optional: true

    Responses:
      "201":
        Description: container index created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: index
  Method: Post:
```

```
    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_index_post

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_index-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container index created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: index
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_index_delete
```

```
  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_index_options

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_index_head

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_index_patch

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_index"
    Required/Optional: true

  Responses:
    "204":
      Description: container index updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: index
```

/data/cisco-smi-cdl:cdl/label-config={label-config-name}/index/map

```
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_options


  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/label-config={label-config-name}/index/map={map-map-id}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_get

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: map-map-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_put

    Parameters:
    - Name: label-config-name
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id"

    Required/Optional: true

  Responses:
    "201":
      Description: list map created or replaced
      Content: {}
    "204":
      Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: map
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_delete

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: map-map-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_options

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_head

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_patch

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id"

      Required/Optional: true

    Responses:
      "204":
        Description: list map updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: map
```

/data/cisco-smi-cdl:cdl/label-config={label-config-name}/index/map={map-map-id}/

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_map_id_get

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: map-map-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id_map-id"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_map_id_put

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id_map-id"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf map-id created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: map-id
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_map_id_delete

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_map_id_options

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_map_id_head

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: map-map-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_map_id_patch

      Parameters:
      - Name: label-config-name
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
      - Name: map-map-id
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: integer
          Format: uint16
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id_map-id"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf map-id updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: map-id
```

/data/cisco-smi-cdl:cdl/label-config={label-config-name}/index/map={map-map-i

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_key_get

  Parameters:
  - Name: label-config-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: map-map-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id_key"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_key_put

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id_key"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf key created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_key_delete

    Parameters:
    - Name: label-config-name
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_key_options

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

```
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_key_head

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_key_patch

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id_key"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf key updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key
```

/data/cisco-smi-cdl:cdl/label-config={label-config-name}/index/map={map-map-id}/

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_value_get

    Parameters:
    - Name: label-config-name
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: map-map-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id_value"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_value_put

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id_value"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf value created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: value
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_value_delete

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_value_options

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_value_head

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
```

```
data_cisco_smi_cdl_cdl_label_config_label_config_name_index_map_map_map_id_value_patch

    Parameters:
    - Name: label-config-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: map-map-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id_value"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf value updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: value
```

/data/cisco-smi-cdl:cdl/external-secret-config

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config"

        Required/Optional: true

      Responses:
        "201":
          Description: container external-secret-config created or replaced
          Content: {}
        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
      x-codegen-request-body-name: external-secret-config
    Method: Post:

      Tags:
      - data
      - post
      Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_post
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config-post"
        Required/Optional: true

      Responses:
        "201":
          Description: container external-secret-config created
          Content: {}
        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: external-secret-config
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
```

```
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config"

    Required/Optional: true

  Responses:
    "204":
      Description: container external-secret-config updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: external-secret-config
```

/data/cisco-smi-cdl:cdl/external-secret-config/name

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_name_get

  Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_name"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_name_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_name"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_name_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_name_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_name_head

  Parameters:
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_name_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_name"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
```

/data/cisco-smi-cdl:cdl/external-secret-config/namespace

```
  get:

    Tags:
    - data
    - get
```

```
Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_namespace_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_namespace"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_namespace_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_namespace"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf namespace created or replaced
        Content: {}
```

```
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: namespace
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_namespace_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_namespace_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_namespace_head
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_namespace_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_namespace"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf namespace updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: namespace
```

/data/cisco-smi-cdl:cdl/external-secret-config/target-secret

```
  get:
```

```
Tags:
- data
- get
Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_target_secret_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_target-secret"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_target_secret_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_target-secret"
      Required/Optional: true

    Responses:
```

```
    "201":
      Description: leaf target-secret created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: target-secret
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_target_secret_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_target_secret_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
```

```
- data
- head
Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_target_secret_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_target_secret_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_target-secret"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf target-secret updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: target-secret
```

/data/cisco-smi-cdl:cdl/external-secret-config/remote-key-path

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_remote_key_path_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_remote-key-path"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_remote_key_path_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_remote-key-path"
     Required/Optional: true

  Responses:
    "201":
      Description: leaf remote-key-path created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: remote-key-path
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_remote_key_path_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_remote_key_path_options

  Responses:
    "200":
      Description: OK
      Content: {}
```

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_remote_key_path_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_remote_key_path_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_remote-key-path"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf remote-key-path updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: remote-key-path
```

/data/cisco-smi-cdl:cdl/external-secret-config/refresh-interval

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_refresh_interval_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_refresh-interval"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_refresh_interval_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_refresh-interval"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf refresh-interval created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: refresh-interval
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_refresh_interval_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
   Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_refresh_interval_options
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_refresh_interval_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_refresh_interval_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_refresh-interval"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf refresh-interval updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: refresh-interval
```

/data/cisco-smi-cdl:cdl/external-secret-config/secret-store

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_secret_store_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
        Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_secret-store"
        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_secret_store_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_secret-store"
      Required/Optional: true

    Responses:
      "201":
        Description: container secret-store created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-store
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_secret_store_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_secret-store-post"
      Required/Optional: true
```

```
  Responses:
    "201":
      Description: container secret-store created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-store
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_secret_store_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_secret_store_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:
```

```
Tags:
- data
- head
Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_secret_store_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_secret_store_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_secret-store"
      Required/Optional: true

    Responses:
      "204":
        Description: container secret-store updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-store
```

/data/cisco-smi-cdl:cdl/external-secret-config/secret-store/name

```
get:

  Tags:
  - data
  - get
  Summary: Overrides common secret store name
  Description: Overrides common secret store name
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_secret_store_name_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: Overrides common secret store name
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_secret-store_name"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Summary: Overrides common secret store name
    Description: Overrides common secret store name
    Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_secret_store_name_put
```

```
    Request Body:
      Description: Overrides common secret store name
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_secret-store_name"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
  delete:

    Tags:
    - data
    - delete
    Summary: Overrides common secret store name
    Description: Overrides common secret store name
   Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_secret_store_name_delete


    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
```

```
  - data
  - options
  Summary: Overrides common secret store name
  Description: Overrides common secret store name
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_secret_store_name_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Summary: Overrides common secret store name
  Description: Overrides common secret store name
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_secret_store_name_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
        Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Summary: Overrides common secret store name
      Description: Overrides common secret store name
      Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_secret_store_name_patch
      Request Body:
        Description: Overrides common secret store name
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_secret-store_name"
        Required/Optional: true

      Responses:
        "204":
          Description: leaf name updated
          Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
```

/data/cisco-smi-cdl:cdl/external-secret-config/secret-store/kind

```
get:

  Tags:
  - data
  - get
  Summary: Overrides common secret store kind
  Description: Overrides common secret store kind
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_secret_store_kind_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: Overrides common secret store kind
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_secret-store_kind"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Summary: Overrides common secret store kind
  Description: Overrides common secret store kind
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_secret_store_kind_put
  Request Body:
    Description: Overrides common secret store kind
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_secret-store_kind"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf kind created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: kind
delete:

  Tags:
  - data
  - delete
  Summary: Overrides common secret store kind
  Description: Overrides common secret store kind
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_secret_store_kind_delete


  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Summary: Overrides common secret store kind
  Description: Overrides common secret store kind
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_secret_store_kind_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Summary: Overrides common secret store kind
  Description: Overrides common secret store kind
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_secret_store_kind_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Summary: Overrides common secret store kind
    Description: Overrides common secret store kind
    Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_secret_store_kind_patch
    Request Body:
      Description: Overrides common secret store kind
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_secret-store_kind"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf kind updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: kind
```

/data/cisco-smi-cdl:cdl/external-secret-config/secret-store/namespace

```
  get:

    Tags:
    - data
    - get
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
   Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_secret_store_namespace_get
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: Overrides common secret store namespace
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_secret-store_namespace"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
   Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_secret_store_namespace_put

    Request Body:
      Description: Overrides common secret store namespace
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_secret-store_namespace"

      Required/Optional: true
```

```
    Responses:
      "201":
        Description: leaf namespace created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: namespace
  delete:

    Tags:
    - data
    - delete
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_secret_store_namespace_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_secret_store_namespace_options

    Responses:
      "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Summary: Overrides common secret store namespace
  Description: Overrides common secret store namespace
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_secret_store_namespace_head


  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_secret_store_namespace_patch
    Request Body:
      Description: Overrides common secret store namespace
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_secret-store_namespace"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf namespace updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: namespace
```

/data/cisco-smi-cdl:cdl/external-secret-config/data

```
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_data_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/external-secret-config/data={data-secret-key}

```
get:

  Tags:
  - data
  - get
 Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_get


  Parameters:
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_put


  Parameters:
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key"
      Required/Optional: true

    Responses:
      "201":
        Description: list data created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: data
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_delete

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_options

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_head

    Parameters:
```

```
- Name: data-secret-key
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_patch


  Parameters:
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key"
    Required/Optional: true

  Responses:
    "204":
      Description: list data updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: data
```

/data/cisco-smi-cdl:cdl/external-secret-config/data={data-secret-key}/secret-key

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_secret_key_get

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_secret-key"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_secret_key_put

  Parameters:
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_secret-key"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf secret-key created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-key
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_secret_key_delete

  Parameters:
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_secret_key_options

  Parameters:
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
```

```
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_secret_key_head

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
        Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_secret_key_patch

      Parameters:
      - Name: data-secret-key
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_secret-key"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf secret-key updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-key
```

/data/cisco-smi-cdl:cdl/external-secret-config/data={data-secret-key}/remote-ref

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_remote_ref_get

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_remote-ref"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_remote_ref_put

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_remote-ref"

      Required/Optional: true
```

```
    Responses:
      "201":
        Description: container remote-ref created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remote-ref
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_remote_ref_post

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_remote-ref-post"

      Required/Optional: true

    Responses:
```

```
      "201":
        Description: container remote-ref created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remote-ref
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_remote_ref_delete

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
```

```
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_remote_ref_options

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_remote_ref_head

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_remote_ref_patch
```

```
    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_remote-ref"

      Required/Optional: true

    Responses:
      "204":
        Description: container remote-ref updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remote-ref
```

/data/cisco-smi-cdl:cdl/external-secret-config/data={data-secret-key}/remote-ref/

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_remote_ref_key_get

    Parameters:
```

```
- Name: data-secret-key
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_remote-ref_key"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_remote_ref_key_put

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_remote-ref_key"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf key created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_remote_ref_key_delete

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_remote_ref_key_options

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_remote_ref_key_head

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_remote_ref_key_patch

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_remote-ref_key"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf key updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: key
```

/data/cisco-smi-cdl:cdl/external-secret-config/data={data-secret-key}/remote-ref/p

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_remote_ref_property_get

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_remote-ref_property"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_remote_ref_property_put

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_remote-ref_property"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf property created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
    x-codegen-request-body-name: property
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_remote_ref_property_delete


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_remote_ref_property_options


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
```

```
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_remote_ref_property_head

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_external_secret_config_data_data_secret_key_remote_ref_property_patch


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_remote-ref_property"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf property updated
```

```
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: property
```

/data/cisco-smi-cdl:cdl/ssl-config

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config"
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config"
    Required/Optional: true

  Responses:
    "201":
      Description: container ssl-config created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ssl-config
Method: Post:

  Tags:
  - data
```

```
  - post
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container ssl-config created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ssl-config
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_options
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config"
    Required/Optional: true

  Responses:
    "204":
      Description: container ssl-config updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: ssl-config
```

/data/cisco-smi-cdl:cdl/ssl-config/enable

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_enable_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_enable"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_enable_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_enable"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf enable created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_enable_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
```

```
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_enable_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_enable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_enable_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_enable"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf enable updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: enable
```

/data/cisco-smi-cdl:cdl/ssl-config/auto-generation

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_auto_generation_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_auto-generation"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_auto_generation_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_auto-generation"
      Required/Optional: true

    Responses:
      "201":
        Description: container auto-generation created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: auto-generation
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_auto_generation_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_auto-generation-post"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: container auto-generation created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: auto-generation
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_auto_generation_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_auto_generation_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

```
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_auto_generation_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_auto_generation_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_auto-generation"
      Required/Optional: true

    Responses:
      "204":
        Description: container auto-generation updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: auto-generation
```

/data/cisco-smi-cdl:cdl/ssl-config/auto-generation/enabled

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_auto_generation_enabled_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_auto-generation_enabled"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_auto_generation_enabled_put
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_auto-generation_enabled"
       Required/Optional: true

    Responses:
      "201":
        Description: leaf enabled created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enabled
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_auto_generation_enabled_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_auto_generation_enabled_options
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_auto_generation_enabled_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID: data_cisco_smi_cdl_cdl_ssl_config_auto_generation_enabled_patch
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_auto-generation_enabled"
        Required/Optional: true

      Responses:
        "204":
          Description: leaf enabled updated
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
```

```
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: enabled
```

/data/cisco-smi-cdl:cdl/ssl-config/tls-secret-name

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_tls_secret_name_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_tls-secret-name"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_tls_secret_name_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_tls-secret-name"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf tls-secret-name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: tls-secret-name
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_tls_secret_name_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:
```

```
  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_tls_secret_name_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_tls_secret_name_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_tls_secret_name_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_tls-secret-name"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf tls-secret-name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tls-secret-name
```

/data/cisco-smi-cdl:cdl/ssl-config/ca-secret-name

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_secret_name_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-secret-name"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_secret_name_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-secret-name"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf ca-secret-name created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ca-secret-name
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_secret_name_delete

  Responses:
    "204":
      Description: No Content
```

```
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_secret_name_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_secret_name_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_secret_name_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-secret-name"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf ca-secret-name updated
        Content: {}
      "400":
        Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ca-secret-name
```

/data/cisco-smi-cdl:cdl/ssl-config/ca-external-secret

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret"
      Required/Optional: true

    Responses:
      "201":
        Description: container ca-external-secret created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ca-external-secret
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_post
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret-post"
       Required/Optional: true

    Responses:
      "201":
        Description: container ca-external-secret created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ca-external-secret
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_options
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_patch
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret"
        Required/Optional: true

      Responses:
        "204":
          Description: container ca-external-secret updated
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
```

```
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: ca-external-secret
```

/data/cisco-smi-cdl:cdl/ssl-config/ca-external-secret/name

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_name_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_name"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_name_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_name"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_name_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:
```

```
  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_name_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_name_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_name_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_name"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
```

/data/cisco-smi-cdl:cdl/ssl-config/ca-external-secret/namespace

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_namespace_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_namespace"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_namespace_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_namespace"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf namespace created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: namespace
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_namespace_delete

  Responses:
    "204":
      Description: No Content
```

```
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_namespace_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_namespace_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_namespace_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_namespace"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf namespace updated
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: namespace
```

/data/cisco-smi-cdl:cdl/ssl-config/ca-external-secret/target-secret

```
get:

  Tags:
  - data
  - get
 Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_target_secret_get


  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_target-secret"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
 Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_target_secret_put

  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_target-secret"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf target-secret created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: target-secret
delete:

  Tags:
  - data
```

```
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_target_secret_delete


    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_target_secret_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_target_secret_head


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_target_secret_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_target-secret"
Required/Optional: true

Responses:
"204":
Description: leaf target-secret updated
Content: {}
"400":
Description: Bad Request
Content: {}
"401":
Description: Unauthorized
Content: {}
"404":
Description: Not Found
Content: {}
"405":
Description: Method Not Allowed
Content: {}
"409":
Description: Conflict
Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: target-secret

/data/cisco-smi-cdl:cdl/ssl-config/ca-external-secret/remote-key-path

get:

Tags:
- data
- get
Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_remote_key_path_get

Parameters:
- Name: content
In: query
Description: controlling descendant nodes in response
Required/Optional: false
Style: form
Explode: true
Schema:
Type: string
Format: enumeration
Default: config
enum:
- config
- nonconfig
- all
- Name: depth

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_remote-key-path"

    "204":
      Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
 Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_remote_key_path_put

  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_remote-key-path"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf remote-key-path created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remote-key-path
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_remote_key_path_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_remote_key_path_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_remote_key_path_head


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_remote_key_path_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_remote-key-path"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf remote-key-path updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remote-key-path
```

/data/cisco-smi-cdl:cdl/ssl-config/ca-external-secret/refresh-interval

```
  get:

    Tags:
    - data
    - get
   Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_refresh_interval_get


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_refresh-interval"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_refresh_interval_put

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_refresh-interval"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf refresh-interval created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: refresh-interval
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_refresh_interval_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_refresh_interval_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_refresh_interval_head

  Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_refresh_interval_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_refresh-interval"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf refresh-interval updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: refresh-interval
```

/data/cisco-smi-cdl:cdl/ssl-config/ca-external-secret/secret-store

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store"
     Required/Optional: true

   Responses:
     "201":
       Description: container secret-store created or replaced
       Content: {}
     "204":
       Description: No Content
       Content: {}
     "400":
       Description: Bad Request
       Content: {}
     "401":
       Description: Unauthorized
       Content: {}
     "404":
       Description: Not Found
       Content: {}
     "405":
       Description: Method Not Allowed
       Content: {}
     "409":
       Description: Conflict
       Content: {}
   security:
   - basicAuth: []
   x-codegen-request-body-name: secret-store
  Method: Post:

   Tags:
   - data
   - post
   Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_post

   Request Body:
     Content:
       application/yang-data+json:
         Schema:
           Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store-post"

     Required/Optional: true

   Responses:
     "201":
       Description: container secret-store created
       Content: {}
     "204":
       Description: No Content
       Content: {}
     "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-store
delete:

  Tags:
  - data
  - delete
 Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_delete


  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_head


  Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
   Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store"
      Required/Optional: true

    Responses:
      "204":
        Description: container secret-store updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-store
```

/data/cisco-smi-cdl:cdl/ssl-config/ca-external-secret/secret-store/name

```
  get:
```

```
    Tags:
    - data
    - get
    Summary: Overrides common secret store name
    Description: Overrides common secret store name
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_name_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: Overrides common secret store name
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store_name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Summary: Overrides common secret store name
    Description: Overrides common secret store name
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_name_put
    Request Body:
      Description: Overrides common secret store name
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store_name"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
  delete:

    Tags:
    - data
    - delete
    Summary: Overrides common secret store name
    Description: Overrides common secret store name
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_name_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
```

```
    Summary: Overrides common secret store name
    Description: Overrides common secret store name
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_name_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Summary: Overrides common secret store name
    Description: Overrides common secret store name
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_name_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
        Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Summary: Overrides common secret store name
      Description: Overrides common secret store name
      Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_name_patch
      Request Body:
        Description: Overrides common secret store name
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store_name"

        Required/Optional: true

      Responses:
        "204":
          Description: leaf name updated
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
```

/data/cisco-smi-cdl:cdl/ssl-config/ca-external-secret/secret-store/kind

```
get:

  Tags:
  - data
  - get
  Summary: Overrides common secret store kind
  Description: Overrides common secret store kind
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_kind_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: Overrides common secret store kind
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store_kind"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Summary: Overrides common secret store kind
    Description: Overrides common secret store kind
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_kind_put
    Request Body:
      Description: Overrides common secret store kind
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store_kind"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf kind created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: kind
  delete:

    Tags:
    - data
    - delete
    Summary: Overrides common secret store kind
    Description: Overrides common secret store kind
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_kind_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Summary: Overrides common secret store kind
    Description: Overrides common secret store kind
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_kind_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Summary: Overrides common secret store kind
    Description: Overrides common secret store kind
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_kind_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
```

```
      Description: OK
      Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Summary: Overrides common secret store kind
    Description: Overrides common secret store kind
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_kind_patch
    Request Body:
      Description: Overrides common secret store kind
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store_kind"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf kind updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: kind
```

/data/cisco-smi-cdl:cdl/ssl-config/ca-external-secret/secret-store/namespace

```
  get:

    Tags:
    - data
```

```
    - get
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_namespace_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: Overrides common secret store namespace
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store_namespace"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_namespace_put
    Request Body:
      Description: Overrides common secret store namespace
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store_namespace"

     Required/Optional: true

   Responses:
     "201":
       Description: leaf namespace created or replaced
       Content: {}
     "204":
       Description: No Content
       Content: {}
     "400":
       Description: Bad Request
       Content: {}
     "401":
       Description: Unauthorized
       Content: {}
     "404":
       Description: Not Found
       Content: {}
     "405":
       Description: Method Not Allowed
       Content: {}
     "409":
       Description: Conflict
       Content: {}
   security:
   - basicAuth: []
   x-codegen-request-body-name: namespace
 delete:

   Tags:
   - data
   - delete
   Summary: Overrides common secret store namespace
   Description: Overrides common secret store namespace
   Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_namespace_delete

   Responses:
     "204":
       Description: No Content
       Content: {}
   security:
   - basicAuth: []
 options:

   Tags:
   - data
   - options
   Summary: Overrides common secret store namespace
   Description: Overrides common secret store namespace
   Operation ID:
```

```
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_namespace_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_namespace_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_secret_store_namespace_patch
    Request Body:
      Description: Overrides common secret store namespace
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store_namespace"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf namespace updated
        Content: {}
      "400":
        Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: namespace
```

/data/cisco-smi-cdl:cdl/ssl-config/ca-external-secret/data

```
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/ssl-config/ca-external-secret/data={data-secret-key}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_get

  Parameters:
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_put

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
```

```
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key"

      Required/Optional: true

    Responses:
      "201":
        Description: list data created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: data
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_delete

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_options

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:
```

```
    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_head

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_patch

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key"

      Required/Optional: true

    Responses:
      "204":
        Description: list data updated
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: data
```

/data/cisco-smi-cdl:cdl/ssl-config/ca-external-secret/data={data-secret-key}/sec

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_secret_key_get

  Parameters:
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
      - nonconfig
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_secret-key"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_secret_key_put

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_secret-key"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf secret-key created or replaced
        Content: {}
      "204":
        Description: No Content
```

```
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-key
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_secret_key_delete


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_secret_key_options


    Parameters:
```

```
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_secret_key_head

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: integer
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_secret_key_patch

      Parameters:
      - Name: data-secret-key
        In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_secret-key"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf secret-key updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-key
```

/data/cisco-smi-cdl:cdl/ssl-config/ca-external-secret/data={data-secret-key}/rem

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_remote_ref_get

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_remote-ref"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_remote_ref_put

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_remote-ref"

      Required/Optional: true

    Responses:
      "201":
        Description: container remote-ref created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remote-ref
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_remote_ref_post

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_remote-ref-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container remote-ref created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remote-ref
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_remote_ref_delete


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_remote_ref_options


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_remote_ref_head

    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
 patch:

  Tags:
  - data
  - patch
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_remote_ref_patch

  Parameters:
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_remote-ref"

    Required/Optional: true

  Responses:
    "204":
      Description: container remote-ref updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: remote-ref
```

/data/cisco-smi-cdl:cdl/ssl-config/ca-external-secret/data={data-secret-key}/rem

get:

Tags:
- data
- get

Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_remote_ref_key_get

Parameters:
- **Name**: data-secret-key
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_remote-ref_key"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_remote_ref_key_put


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_remote-ref_key"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf key created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key
```

```
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_remote_ref_key_delete


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_remote_ref_key_options


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

```
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_remote_ref_key_head

  Parameters:
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_remote_ref_key_patch


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_remote-ref_key"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf key updated
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: key
```

/data/cisco-smi-cdl:cdl/ssl-config/ca-external-secret/data={data-secret-key}/rem

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_remote_ref_property_get


  Parameters:
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_remote-ref_property"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_remote_ref_property_put


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_remote-ref_property"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf property created or replaced
        Content: {}
      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: property
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_remote_ref_property_delete


  Parameters:
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_remote_ref_property_options


  Parameters:
```

```
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_remote_ref_property_head


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_ca_external_secret_data_data_secret_key_remote_ref_property_patch


    Parameters:
    - Name: data-secret-key
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_remote-ref_property"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf property updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: property
```

/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_get

    Parameters:
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth"
      Required/Optional: true

    Responses:
      "201":
        Description: container remote-ca-auth created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: remote-ca-auth
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container remote-ca-auth created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: remote-ca-auth
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_patch
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth"
      Required/Optional: true

    Responses:
      "204":
        Description: container remote-ca-auth updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remote-ca-auth
```

/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth/ca-secret-names

```
  options:

    Tags:
    - data
    - options
   Operation ID: data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_secret_names_options


    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth/ca-secret-names={ca-secret-n

```
  get:
```

```
    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_secret_names_ca_secret_names_site_id_get


    Parameters:
    - Name: ca-secret-names-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-secret-names_ca-secret-names-site-id"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
```

```
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_secret_names_ca_secret_names_site_id_put


    Parameters:
    - Name: ca-secret-names-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-secret-names_ca-secret-names-site-id"

      Required/Optional: true

    Responses:
      "201":
        Description: list ca-secret-names created or replaced
        Content: {}
      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ca-secret-names
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_secret_names_ca_secret_names_site_id_delete


  Parameters:
  - Name: ca-secret-names-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_secret_names_ca_secret_names_site_id_options


  Parameters:
```

```
  - Name: ca-secret-names-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_secret_names_ca_secret_names_site_id_head


  Parameters:
  - Name: ca-secret-names-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_secret_names_ca_secret_names_site_id_patch


    Parameters:
    - Name: ca-secret-names-site-id
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-secret-names_ca-secret-names-site-id"

      Required/Optional: true

    Responses:
      "204":
        Description: list ca-secret-names updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ca-secret-names
```


/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth/ca-secret-names={ca-secret-nam


```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_secret_names_ca_secret_names_site_id_site_id_get


    Parameters:
    - Name: ca-secret-names-site-id
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-secret-names_ca-secret-names-site-id_site-id"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_secret_names_ca_secret_names_site_id_site_id_put


    Parameters:
    - Name: ca-secret-names-site-id
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-secret-names_ca-secret-names-site-id_site-id"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf site-id created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: site-id
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_secret_names_ca_secret_names_site_id_site_id_delete


    Parameters:
    - Name: ca-secret-names-site-id
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_secret_names_ca_secret_names_site_id_site_id_options


    Parameters:
    - Name: ca-secret-names-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_secret_names_ca_secret_names_site_id_site_id_head


    Parameters:
    - Name: ca-secret-names-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_secret_names_ca_secret_names_site_id_site_id_patch


    Parameters:
    - Name: ca-secret-names-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-secret-names_ca-secret-names-site-id_site-id"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf site-id updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: site-id
```

/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth/ca-secret-names={ca-secret-n

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_secret_names_ca_secret_names_site_id_secret_name_get


  Parameters:
  - Name: ca-secret-names-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-secret-names_ca-secret-names-site-id_secret-name"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_secret_names_ca_secret_names_site_id_secret_name_put


    Parameters:
    - Name: ca-secret-names-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-secret-names_ca-secret-names-site-id_secret-name"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf secret-name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-name
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_secret_names_ca_secret_names_site_id_secret_name_delete


  Parameters:
  - Name: ca-secret-names-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_secret_names_ca_secret_names_site_id_secret_name_options


  Parameters:
  - Name: ca-secret-names-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "200":
      Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_secret_names_ca_secret_names_site_id_secret_name_head


    Parameters:
    - Name: ca-secret-names-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_secret_names_ca_secret_names_site_id_secret_name_patch


    Parameters:
    - Name: ca-secret-names-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-secret-names_ca-secret-names-site-id_secret-name"

Required/Optional: true

Responses:
"204":
Description: leaf secret-name updated
Content: {}
"400":
Description: Bad Request
Content: {}
"401":
Description: Unauthorized
Content: {}
"404":
Description: Not Found
Content: {}
"405":
Description: Method Not Allowed
Content: {}
"409":
Description: Conflict
Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: secret-name

/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth/ca-external-secrets

options:

Tags:
- data
- options
Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_options

Responses:
"200":
Description: OK
Content: {}
security:
- basicAuth: []

/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth/ca-external-secrets={ca-exter

get:

Tags:
- data
- get

Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_get

Parameters:
- **Name**: ca-external-secrets-site-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_put
```

```
Parameters:
- Name: ca-external-secrets-site-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: insert
  In: query
  Description: controlling the order when adding new list elements
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: first
    enum:
    - first
    - last
    - before
    - after
- Name: point
  In: query
  Description: used to specify the insertion point
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id"

  Required/Optional: true

Responses:
  "201":
    Description: list ca-external-secrets created or replaced
    Content: {}
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ca-external-secrets
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_delete


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_options


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_head


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_patch


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id"

      Required/Optional: true

    Responses:
      "204":
        Description: list ca-external-secrets updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ca-external-secrets
```


/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth/ca-external-secrets={ca-externa


```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_site_id_get


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: integer
    Format: uint32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_site-id"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_site_id_put


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
```

```
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_site-id"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf site-id created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: site-id
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_site_id_delete


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
```

```
    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_site_id_options


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_site_id_head


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_site_id_patch


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_site-id"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf site-id updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: site-id
```

/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth/ca-external-secrets={ca-exter

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_name_get


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_name_put


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_name"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf name created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_name_delete


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_name_options


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:
```

```
    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_name_head

    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_name_patch


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_name"

      Required/Optional: true
```

```
  Responses:
    "204":
      Description: leaf name updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
```

/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth/ca-external-secrets={ca-exter

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_namespace_get


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_namespace"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_namespace_put


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_namespace"

      Required/Optional: true

    Responses:
      "201":
```

```
      Description: leaf namespace created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: namespace
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_namespace_delete


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
```

```
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_namespace_options

    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_namespace_head

    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
```

data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_namespace_patch

```
  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_namespace"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf namespace updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: namespace
```

/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth/ca-external-secrets={ca-exter

```
get:

  Tags:
  - data
  - get
  Operation ID:
```

data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_target_secret_get

```
Parameters:
- Name: ca-external-secrets-site-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_target-secret"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_target_secret_put
```

```
    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_target-secret"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf target-secret created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: target-secret
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_target_secret_delete


    Parameters:
```

```
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_target_secret_options


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_target_secret_head


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_target_secret_patch


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_target-secret"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf target-secret updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: target-secret
```

/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth/ca-external-secrets={ca-externa

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_remote_key_path_get

  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_remote-key-path"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_remote_key_path_put


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_remote-key-path"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf remote-key-path created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: remote-key-path
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_remote_key_path_delete


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_remote_key_path_options


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_remote_key_path_head


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_remote_key_path_patch


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_remote-key-path"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf remote-key-path updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remote-key-path
```

/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth/ca-external-secrets={ca-externa

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_refresh_interval_get

    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_refresh-interval"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_refresh_interval_put


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_refresh-interval"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf refresh-interval created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: refresh-interval
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_refresh_interval_delete


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "204":
        Description: No Content
```

```
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_refresh_interval_options


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_refresh_interval_head


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_refresh_interval_patch


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_refresh-interval"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf refresh-interval updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: refresh-interval
```

/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth/ca-external-secrets={ca-exter

get:

Tags:
- data
- get

Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_get

Parameters:
- **Name**: ca-external-secrets-site-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string

```
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_put


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store"

      Required/Optional: true

    Responses:
      "201":
        Description: container secret-store created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-store
```

```
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_post


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container secret-store created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-store
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_delete


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_options


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
```

data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_head

```
Parameters:
- Name: ca-external-secrets-site-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_patch


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store"

      Required/Optional: true

    Responses:
      "204":
        Description: container secret-store updated
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-store
```

/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth/ca-external-secrets={ca-externa

```
get:

  Tags:
  - data
  - get
  Summary: Overrides common secret store name
  Description: Overrides common secret store name
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_name_get

  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: Overrides common secret store name
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store_name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Summary: Overrides common secret store name
    Description: Overrides common secret store name
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_name_put

    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Description: Overrides common secret store name
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store_name"

      Required/Optional: true

    Responses:
      "201":

```
      Description: leaf name created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
delete:

  Tags:
  - data
  - delete
  Summary: Overrides common secret store name
  Description: Overrides common secret store name
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_name_delete


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
```

```
    - data
    - options
    Summary: Overrides common secret store name
    Description: Overrides common secret store name
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_name_options


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Summary: Overrides common secret store name
    Description: Overrides common secret store name
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_name_head


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Summary: Overrides common secret store name
    Description: Overrides common secret store name
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_name_patch


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Description: Overrides common secret store name
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store_name"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
```

/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth/ca-external-secrets={ca-exter

```
get:

  Tags:
  - data
  - get
  Summary: Overrides common secret store kind
  Description: Overrides common secret store kind
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_kind_get


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: Overrides common secret store kind
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store_kind"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Summary: Overrides common secret store kind
    Description: Overrides common secret store kind
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_kind_put


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Description: Overrides common secret store kind
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store_kind"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf kind created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: kind
delete:

  Tags:
  - data
  - delete
  Summary: Overrides common secret store kind
  Description: Overrides common secret store kind
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_kind_delete


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Summary: Overrides common secret store kind
  Description: Overrides common secret store kind
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_kind_options


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
```

```
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Summary: Overrides common secret store kind
  Description: Overrides common secret store kind
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_kind_head

  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Summary: Overrides common secret store kind
  Description: Overrides common secret store kind
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_kind_patch


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
```

```
      Format: uint32
  Request Body:
    Description: Overrides common secret store kind
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store_kind"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf kind updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: kind
```


/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth/ca-external-secrets={ca-exter


```
get:

  Tags:
  - data
  - get
  Summary: Overrides common secret store namespace
  Description: Overrides common secret store namespace
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_namespace_get

  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: Overrides common secret store namespace
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store_namespace"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Summary: Overrides common secret store namespace
  Description: Overrides common secret store namespace
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_namespace_put


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
```

```
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Description: Overrides common secret store namespace
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store_namespace"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf namespace created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: namespace
  delete:

    Tags:
    - data
    - delete
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_namespace_delete


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_namespace_options


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_namespace_head


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Summary: Overrides common secret store namespace
  Description: Overrides common secret store namespace
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_secret_store_namespace_patch


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  Request Body:
    Description: Overrides common secret store namespace
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store_namespace"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf namespace updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: namespace
```

/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth/ca-external-secrets={ca-externa

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_options


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth/ca-external-secrets={ca-externa

```
get:

  Tags:
  - data
  - get
```

Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_get

Parameters:
- **Name**: ca-external-secrets-site-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- **Name**: data-secret-key
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string

```
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_put


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key"

      Required/Optional: true

    Responses:
      "201":
        Description: list data created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: data
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_delete


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: data-secret-key
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_options


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_head
```

```
Parameters:
- Name: ca-external-secrets-site-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: data-secret-key
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_patch


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key"

    Required/Optional: true

  Responses:
    "204":
      Description: list data updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: data
```

/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth/ca-external-secrets={ca-externa

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_secret_key_get


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
```

```
- Name: data-secret-key
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_secret-key"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_secret_key_put


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_secret-key"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf secret-key created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-key
  delete:

    Tags:
    - data
    - delete
```

```
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_secret_key_delete

    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_secret_key_options

    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_secret_key_head


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_secret_key_patch


    Parameters:
```

```
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
 Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_secret-key"

    Required/Optional: true

 Responses:
    "204":
      Description: leaf secret-key updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
 security:
 - basicAuth: []
 x-codegen-request-body-name: secret-key
```

/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth/ca-external-secrets={ca-exter

```
 get:
```

Tags:
- data
- get

Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_remote_ref_get

Parameters:
- **Name**: ca-external-secrets-site-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- **Name**: data-secret-key
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_remote-ref"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_remote_ref_put


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_remote-ref"

      Required/Optional: true

    Responses:
      "201":
        Description: container remote-ref created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remote-ref
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_remote_ref_post


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_remote-ref-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container remote-ref created
        Content: {}
      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: remote-ref
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_remote_ref_delete


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_remote_ref_options

    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_remote_ref_head

    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_remote_ref_patch


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_remote-ref"

    Required/Optional: true

  Responses:
    "204":
      Description: container remote-ref updated
      Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: remote-ref
```

/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth/ca-external-secrets={ca-externa

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_remote_ref_key_get

  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_remote-ref_key"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_remote_ref_key_put


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_remote-ref_key"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf key created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_remote_ref_key_delete


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
```

```
      Format: uint32
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_remote_ref_key_options


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
```

Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_remote_ref_key_head

Parameters:
- **Name**: ca-external-secrets-site-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- **Name**: data-secret-key
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_remote_ref_key_patch


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_remote-ref_key"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf key updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key
```

/data/cisco-smi-cdl:cdl/ssl-config/remote-ca-auth/ca-external-secrets={ca-exter

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_remote_ref_property_get


    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: integer
    Format: uint32
- Name: data-secret-key
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_remote-ref_property"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_remote_ref_property_put
```

```
    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_remote-ref_property"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf property created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: property
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_remote_ref_property_delete

    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_remote_ref_property_options

    Parameters:
    - Name: ca-external-secrets-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_remote_ref_property_head


  Parameters:
  - Name: ca-external-secrets-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
```

data_cisco_smi_cdl_cdl_ssl_config_remote_ca_auth_ca_external_secrets_ca_external_secrets_site_id_data_data_secret_key_remote_ref_property_patch

```
Parameters:
- Name: ca-external-secrets-site-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: data-secret-key
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_remote-ref_property"
  Required/Optional: true

Responses:
  "204":
    Description: leaf property updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: property
```

/data/cisco-smi-cdl:cdl/ssl-config/certs

```
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/ssl-config/certs={certs-host}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_get

  Parameters:
  - Name: certs-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_put

  Parameters:
  - Name: certs-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host"
      Required/Optional: true

    Responses:
      "201":
        Description: list certs created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: certs
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_delete

    Parameters:
    - Name: certs-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
```

```
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_options

  Parameters:
  - Name: certs-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_head

  Parameters:
  - Name: certs-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_patch

    Parameters:
    - Name: certs-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host"
      Required/Optional: true

    Responses:
      "204":
        Description: list certs updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: certs
```

/data/cisco-smi-cdl:cdl/ssl-config/certs={certs-host}/host

```
  get:
```

```
Tags:
- data
- get
Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_host_get

Parameters:
- Name: certs-host
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_host"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_host_put
```

```
    Parameters:
    - Name: certs-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_host"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf host created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: host
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_host_delete

    Parameters:
    - Name: certs-host
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_host_options

  Parameters:
  - Name: certs-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_host_head

  Parameters:
  - Name: certs-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_host_patch

    Parameters:
    - Name: certs-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_host"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf host updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: host
```

/data/cisco-smi-cdl:cdl/ssl-config/certs={certs-host}/ca-secret

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ca_secret_get

  Parameters:
  - Name: certs-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ca-secret"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ca_secret_put

    Parameters:
    - Name: certs-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ca-secret"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf ca-secret created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ca-secret
  delete:
```

```
  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ca_secret_delete

  Parameters:
  - Name: certs-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ca_secret_options

  Parameters:
  - Name: certs-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ca_secret_head

  Parameters:
  - Name: certs-host
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ca_secret_patch

    Parameters:
    - Name: certs-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ca-secret"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf ca-secret updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: ca-secret
```

/data/cisco-smi-cdl:cdl/ssl-config/certs={certs-host}/tls-secret

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_tls_secret_get

  Parameters:
  - Name: certs-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_tls-secret"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_tls_secret_put

    Parameters:
    - Name: certs-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_tls-secret"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf tls-secret created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tls-secret
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_tls_secret_delete

  Parameters:
  - Name: certs-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_tls_secret_options

  Parameters:
  - Name: certs-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:
```

```
Tags:
- data
- head
Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_tls_secret_head

Parameters:
- Name: certs-host
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_tls_secret_patch

      Parameters:
      - Name: certs-host
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_tls-secret"
        Required/Optional: true

      Responses:
        "204":
          Description: leaf tls-secret updated
          Content: {}
        "400":
          Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tls-secret
```

/data/cisco-smi-cdl:cdl/ssl-config/certs={certs-host}/ssl-key

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ssl_key_get

  Parameters:
  - Name: certs-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ssl-key"
      "204":
        Description: No Content
        Content: {}
      "400":
```

```
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ssl_key_put

    Parameters:
    - Name: certs-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ssl-key"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf ssl-key created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ssl-key
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ssl_key_delete

  Parameters:
  - Name: certs-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ssl_key_options

  Parameters:
  - Name: certs-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
```

```
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ssl_key_head

  Parameters:
  - Name: certs-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ssl_key_patch

    Parameters:
    - Name: certs-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ssl-key"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: leaf ssl-key updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ssl-key
```

/data/cisco-smi-cdl:cdl/ssl-config/certs={certs-host}/ssl-crt

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ssl_crt_get

  Parameters:
  - Name: certs-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ssl-crt"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ssl_crt_put

    Parameters:
    - Name: certs-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ssl-crt"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf ssl-crt created or replaced
        Content: {}
      "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ssl-crt
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ssl_crt_delete

  Parameters:
  - Name: certs-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ssl_crt_options

  Parameters:
  - Name: certs-host
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ssl_crt_head

  Parameters:
  - Name: certs-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ssl_crt_patch

    Parameters:
    - Name: certs-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ssl-crt"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf ssl-crt updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ssl-crt
```

/data/cisco-smi-cdl:cdl/ssl-config/certs={certs-host}/ssl-ca

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ssl_ca_get

    Parameters:
    - Name: certs-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ssl-ca"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ssl_ca_put

    Parameters:
    - Name: certs-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ssl-ca"
     Required/Optional: true

  Responses:
    "201":
      Description: leaf ssl-ca created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ssl-ca
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ssl_ca_delete

  Parameters:
  - Name: certs-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ssl_ca_options

  Parameters:
  - Name: certs-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ssl_ca_head

  Parameters:
  - Name: certs-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_ssl_config_certs_certs_host_ssl_ca_patch
```

```
    Parameters:
    - Name: certs-host
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ssl-ca"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf ssl-ca updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ssl-ca
```

/data/cisco-smi-cdl:cdl/logging

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_logging_get

    Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
      - report-all
      - trim
      - explicit
      - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_logging"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_logging_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_logging"
      Required/Optional: true

    Responses:
      "201":
        Description: container logging created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: logging
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_cdl_cdl_logging_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_logging-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container logging created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: logging
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_logging_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_logging_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_logging_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_logging_patch
    Request Body:
```

```
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_logging"
    Required/Optional: true

  Responses:
    "204":
      Description: container logging updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: logging
```

/data/cisco-smi-cdl:cdl/logging/default-log-level

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_logging_default_log_level_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_logging_default-log-level"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_logging_default_log_level_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_logging_default-log-level"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf default-log-level created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: default-log-level
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_logging_default_log_level_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_logging_default_log_level_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_logging_default_log_level_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
```

```
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_logging_default_log_level_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_logging_default-log-level"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf default-log-level updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: default-log-level
```

/data/cisco-smi-cdl:cdl/logging/json-logging

```
  get:

    Tags:
    - data
    - get
    Summary: Enable or disable logging in json format. Example value: true
    Description: Enable or disable logging in json format. Example value: true
    Operation ID: data_cisco_smi_cdl_cdl_logging_json_logging_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
```

```
      Description: Enable or disable logging in json format. Example value: true
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_logging_json-logging"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Summary: Enable or disable logging in json format. Example value: true
  Description: Enable or disable logging in json format. Example value: true
  Operation ID: data_cisco_smi_cdl_cdl_logging_json_logging_put
  Request Body:
    Description: Enable or disable logging in json format. Example value: true
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_logging_json-logging"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf json-logging created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: json-logging
delete:

  Tags:
  - data
  - delete
  Summary: Enable or disable logging in json format. Example value: true
  Description: Enable or disable logging in json format. Example value: true
  Operation ID: data_cisco_smi_cdl_cdl_logging_json_logging_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Summary: Enable or disable logging in json format. Example value: true
  Description: Enable or disable logging in json format. Example value: true
  Operation ID: data_cisco_smi_cdl_cdl_logging_json_logging_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Summary: Enable or disable logging in json format. Example value: true
  Description: Enable or disable logging in json format. Example value: true
  Operation ID: data_cisco_smi_cdl_cdl_logging_json_logging_head
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Summary: Enable or disable logging in json format. Example value: true
  Description: Enable or disable logging in json format. Example value: true
  Operation ID: data_cisco_smi_cdl_cdl_logging_json_logging_patch
  Request Body:
    Description: Enable or disable logging in json format. Example value: true
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_logging_json-logging"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf json-logging updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: json-logging
```

/data/cisco-smi-cdl:cdl/logging/logger

```
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_logging_logger_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/logging/logger={logger-name}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_logging_logger_logger_name_get

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_logging_logger_logger-name"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_logging_logger_logger_name_put

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_logging_logger_logger-name"
      Required/Optional: true

    Responses:
      "201":
        Description: list logger created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: logger
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_logging_logger_logger_name_delete

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
```

```
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_logging_logger_logger_name_options

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_logging_logger_logger_name_head

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_logging_logger_logger_name_patch

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_logging_logger_logger-name"
      Required/Optional: true

    Responses:
      "204":
        Description: list logger updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: logger
```

/data/cisco-smi-cdl:cdl/logging/logger={logger-name}/name

```
  get:
```

```
Tags:
- data
- get
Operation ID: data_cisco_smi_cdl_cdl_logging_logger_logger_name_name_get

Parameters:
- Name: logger-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_logging_logger_logger-name_name"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_logging_logger_logger_name_name_put
```

```
    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_logging_logger_logger-name_name"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_logging_logger_logger_name_name_delete

    Parameters:
    - Name: logger-name
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_logging_logger_logger_name_name_options

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_logging_logger_logger_name_name_head

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_logging_logger_logger_name_name_patch

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_logging_logger_logger-name_name"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
```

/data/cisco-smi-cdl:cdl/logging/logger={logger-name}/level

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_logging_logger_logger_name_level_get

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_logging_logger_logger-name_level"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_logging_logger_logger_name_level_put

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_logging_logger_logger-name_level"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf level created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: level
  delete:
```

```
  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_logging_logger_logger_name_level_delete

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_logging_logger_logger_name_level_options

  Parameters:
  - Name: logger-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_logging_logger_logger_name_level_head

  Parameters:
  - Name: logger-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_logging_logger_logger_name_level_patch

    Parameters:
    - Name: logger-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_logging_logger_logger-name_level"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf level updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: level
```

/data/cisco-smi-cdl:cdl/logging/sync-logging

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_logging_sync_logging_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_logging_sync-logging"

  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
```

```
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_logging_sync_logging_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_logging_sync-logging"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf sync-logging created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sync-logging
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_logging_sync_logging_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
```

```
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_logging_sync_logging_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_logging_sync_logging_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_logging_sync_logging_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_logging_sync-logging"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf sync-logging updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: sync-logging
```

/data/cisco-smi-cdl:cdl/logging/error-stack

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_logging_error_stack_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_logging_error-stack"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_logging_error_stack_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_logging_error-stack"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf error-stack created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: error-stack
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_logging_error_stack_delete

  Responses:
```

```
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_logging_error_stack_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_logging_error_stack_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_logging_error_stack_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_logging_error-stack"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf error-stack updated
      Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: error-stack
```

/data/cisco-smi-cdl:cdl/datastore

```
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
```

```
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name"
    Required/Optional: true

  Responses:
    "201":
      Description: list datastore created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: datastore
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_delete

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
```

```
Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_head

Parameters:
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name"
      Required/Optional: true

    Responses:
      "204":
        Description: list datastore updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: datastore
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/name

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_name_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_name"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_name_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_name"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_name_delete

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_name_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_name_head

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_name_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_name"
      Required/Optional: true

    Responses:
```

```
    "204":
      Description: leaf name updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/cluster-id

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_cluster_id_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

```
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_cluster-id"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_cluster_id_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_cluster-id"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf cluster-id created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cluster-id
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_cluster_id_delete

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_cluster_id_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_cluster_id_head

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_cluster_id_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_cluster-id"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf cluster-id updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cluster-id
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/label-config

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_label_config_get

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_label-config"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_label_config_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_label-config"
      Required/Optional: true
```

```
  Responses:
    "201":
      Description: leaf label-config created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: label-config
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_label_config_delete

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
```

```
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_label_config_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_label_config_head

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_label_config_patch

    Parameters:
    - Name: datastore-name
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_label-config"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf label-config updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: label-config
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/geo-remote-site

```
  options:

    Tags:
    - data
    - options
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_geo_remote_site_options

    Parameters:
    - Name: datastore-name
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/geo-remote-site={geo-remote-s

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_geo_remote_site_geo_remote_site_id_get

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: geo-remote-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
```

```
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_geo-remote-site_geo-remote-site-id"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_geo_remote_site_geo_remote_site_id_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: geo-remote-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_geo-remote-site_geo-remote-site-id"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf-list geo-remote-site created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: geo-remote-site
```

```
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_geo_remote_site_geo_remote_site_id_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: geo-remote-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_geo_remote_site_geo_remote_site_id_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: geo-remote-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_geo_remote_site_geo_remote_site_id_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: geo-remote-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_geo_remote_site_geo_remote_site_id_patch
```

```
    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: geo-remote-site-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_geo-remote-site_geo-remote-site-id"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf-list geo-remote-site updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: geo-remote-site
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/mode

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_mode_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_mode"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_mode_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_mode"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf mode created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: mode
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_mode_delete
```

```
  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_mode_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_mode_head

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_mode_patch

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_mode"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf mode updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: mode
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slice-names

```
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slice_names_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slice-names={slice-names-id}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slice_names_slice_names_id_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
- Name: slice-names-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slice-names_slice-names-id"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slice_names_slice_names_id_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: slice-names-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slice-names_slice-names-id"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf-list slice-names created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: slice-names
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slice_names_slice_names_id_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: slice-names-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
```

```
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slice_names_slice_names_id_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: slice-names-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slice_names_slice_names_id_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: slice-names-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slice_names_slice_names_id_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: slice-names-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slice-names_slice-names-id"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf-list slice-names updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: slice-names
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/advanced-config-profile

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_advanced_config_profile_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_advanced-config-profile"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_advanced_config_profile_put

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_advanced-config-profile"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf advanced-config-profile created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: advanced-config-profile
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_advanced_config_profile_delete

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_advanced_config_profile_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_advanced_config_profile_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_advanced_config_profile_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_advanced-config-profile"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf advanced-config-profile updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: advanced-config-profile
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/find-by-nuk-prefixes

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_find_by_nuk_prefixes_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/find-by-nuk-prefixes={find-by

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_find_by_nuk_prefixes_find_by_nuk_prefixes_id_get


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: find-by-nuk-prefixes-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_find-by-nuk-prefixes_find-by-nuk-prefixes-id"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_find_by_nuk_prefixes_find_by_nuk_prefixes_id_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: find-by-nuk-prefixes-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
```

```
        - before
        - after
      - Name: point
        In: query
        Description: used to specify the insertion point
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_find-by-nuk-prefixes_find-by-nuk-prefixes-id"

        Required/Optional: true

      Responses:
        "201":
          Description: leaf-list find-by-nuk-prefixes created or replaced
          Content: {}
        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
      x-codegen-request-body-name: find-by-nuk-prefixes
    delete:

      Tags:
      - data
      - delete
      Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_find_by_nuk_prefixes_find_by_nuk_prefixes_id_delete
```

```
    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: find-by-nuk-prefixes-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_find_by_nuk_prefixes_find_by_nuk_prefixes_id_options


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: find-by-nuk-prefixes-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
```

```
      Description: OK
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_find_by_nuk_prefixes_find_by_nuk_prefixes_id_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: find-by-nuk-prefixes-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_find_by_nuk_prefixes_find_by_nuk_prefixes_id_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: find-by-nuk-prefixes-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_find-by-nuk-prefixes_find-by-nuk-prefixes-id"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf-list find-by-nuk-prefixes updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: find-by-nuk-prefixes
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/metrics

```
  get:

    Tags:
    - data
    - get
```

```
Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_metrics_get

Parameters:
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_metrics"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_metrics_put

    Parameters:
    - Name: datastore-name
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_metrics"
      Required/Optional: true

    Responses:
      "201":
        Description: container metrics created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: metrics
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_metrics_post

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_metrics-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container metrics created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: metrics
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_metrics_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_metrics_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_metrics_head

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_metrics_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_metrics"
      Required/Optional: true

    Responses:
      "204":
        Description: container metrics updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: metrics
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/metrics/verbosity

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_metrics_verbosity_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_metrics_verbosity"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_metrics_verbosity_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_metrics_verbosity"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf verbosity created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: verbosity
  delete:

    Tags:
    - data
    - delete
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_metrics_verbosity_delete
```

```
  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_metrics_verbosity_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_metrics_verbosity_head


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_metrics_verbosity_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_metrics_verbosity"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf verbosity updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: verbosity
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_features_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_features_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features"
      Required/Optional: true

    Responses:
      "201":
        Description: container features created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: features
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_features_post

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container features created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
  x-codegen-request-body-name: features
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_features_delete

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_features_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_features_head
```

```
Parameters:
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_features_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features"
      Required/Optional: true

    Responses:
      "204":
        Description: container features updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: features
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/instance-aware-noti

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_put

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification"

    Required/Optional: true

  Responses:
    "201":
      Description: container instance-aware-notification created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: instance-aware-notification
Method: Post:

  Tags:
  - data
  - post
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_post

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container instance-aware-notification created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instance-aware-notification
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_delete


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_options


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
```

```
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
        Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_patch

      Parameters:
      - Name: datastore-name
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification"

      Required/Optional: true

    Responses:
      "204":
        Description: container instance-aware-notification updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: instance-aware-notification
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/instance-aware-notifi

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_enable_get


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_enable"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_enable_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_enable"
```

```
      Required/Optional: true

    Responses:
      "201":
        Description: leaf enable created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_enable_delete


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
```

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_enable_options


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_enable_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_enable_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_enable"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf enable updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable
```


/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/instance-aware-notifi


```
  options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_system_id_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/instance-aware-noti

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_system_id_system_id_id_get

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: system-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_system-id_system-id-id"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_system_id_system_id_id_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: system-id-id
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_system-id_system-id-id"

      Required/Optional: true

    Responses:
      "201":
        Description: list system-id created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: system-id
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_system_id_system_id_id_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: system-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_system_id_system_id_id_options


  Parameters:
```

```
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: system-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_system_id_system_id_id_head


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: system-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_system_id_system_id_id_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: system-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_system-id_system-id-id"

      Required/Optional: true

    Responses:
      "204":
        Description: list system-id updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: system-id
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/instance-aware-noti

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_system_id_system_id_id_id_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: system-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_system-id_system-id-id_id"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_system_id_system_id_id_id_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: system-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_system-id_system-id-id_id"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: leaf id created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: id
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_system_id_system_id_id_id_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: system-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
```

```
    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_system_id_system_id_id_id_options


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: system-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_system_id_system_id_id_id_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: system-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_system_id_system_id_id_id_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: system-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_system-id_system-id-id_id"

```
    Required/Optional: true

  Responses:
    "204":
      Description: leaf id updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: id
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/instance-aware-notifi

```
options:

  Tags:
  - data
  - options
  Operation ID:
```

data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_system_id_system_id_id_slice_names_options

```
  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: system-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: integer
        Format: uint32

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/instance-aware-noti

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_system_id_system_id_id_slice_names_slice_names_id_get


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: system-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: slice-names-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_system-id_system-id-id_slice-names_slice-names-id"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_system_id_system_id_id_slice_names_slice_names_id_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: system-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: integer
      Format: uint32
  - Name: slice-names-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_system-id_system-id-id_slice-names_slice-names-id"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf-list slice-names created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: slice-names
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_system_id_system_id_id_slice_names_slice_names_id_delete


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: system-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    - Name: slice-names-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
```

```
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_system_id_system_id_id_slice_names_slice_names_id_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: system-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: slice-names-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_system_id_system_id_id_slice_names_slice_names_id_head


  Parameters:
```

```
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: system-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
- Name: slice-names-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_instance_aware_notification_system_id_system_id_id_slice_names_slice_names_id_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: system-id-id
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint32
  - Name: slice-names-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_system-id_system-id-id_slice-names_slice-names-id"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf-list slice-names updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: slice-names
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/slot-stale-session-d

```
get:
```

```
    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_slot_stale_session_detection_get

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_slot-stale-session-detection"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_slot_stale_session_detection_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_slot-stale-session-detection"

      Required/Optional: true

    Responses:
      "201":
        Description: container slot-stale-session-detection created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: slot-stale-session-detection
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_slot_stale_session_detection_post
```

```
    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_slot-stale-session-detection-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container slot-stale-session-detection created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: slot-stale-session-detection
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_slot_stale_session_detection_delete
```

```
    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_slot_stale_session_detection_options


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_slot_stale_session_detection_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_slot_stale_session_detection_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_slot-stale-session-detection"

      Required/Optional: true

    Responses:
      "204":
        Description: container slot-stale-session-detection updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: slot-stale-session-detection
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/slot-stale-session-d

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_slot_stale_session_detection_disable_auto_deletion_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_slot-stale-session-detection_disable-auto-deletion"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_slot_stale_session_detection_disable_auto_deletion_put


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_slot-stale-session-detection_disable-auto-deletion"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf disable-auto-deletion created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: disable-auto-deletion
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_slot_stale_session_detection_disable_auto_deletion_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_slot_stale_session_detection_disable_auto_deletion_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_slot_stale_session_detection_disable_auto_deletion_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_slot_stale_session_detection_disable_auto_deletion_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_slot-stale-session-detection_disable-auto-deletion"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf disable-auto-deletion updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: disable-auto-deletion
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/slot-stale-session-d

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_slot_stale_session_detection_notification_retry_count_get


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_slot-stale-session-detection_notification-retry-count"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_slot_stale_session_detection_notification_retry_count_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_slot-stale-session-detection_notification-retry-count"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf notification-retry-count created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: notification-retry-count
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_slot_stale_session_detection_notification_retry_count_delete


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
```

```
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_slot_stale_session_detection_notification_retry_count_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_slot_stale_session_detection_notification_retry_count_head


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_slot_stale_session_detection_notification_retry_count_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_slot-stale-session-detection_notification-retry-count"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf notification-retry-count updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: notification-retry-count
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/overload-protection

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_get

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection"

      Required/Optional: true

    Responses:
      "201":
        Description: container overload-protection created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: overload-protection
  Method: Post:
```

```
    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_post

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container overload-protection created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: overload-protection
  delete:

    Tags:
    - data
```

```
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_head

    Parameters:
    - Name: datastore-name
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection"

      Required/Optional: true

    Responses:
      "204":
        Description: container overload-protection updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: overload-protection
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/overload-protection/

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_enable_get

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_enable"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_enable_put

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_enable"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf enable created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_enable_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_enable_options


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_enable_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: string
        Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_enable_patch

      Parameters:
      - Name: datastore-name
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
      Request Body:
        Content:
          application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_enable"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf enable updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/overload-protection/

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_index_max_record_count_get


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_index-max-record-count"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_index_max_record_count_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_index-max-record-count"

Required/Optional: true

Responses:
"201":
Description: leaf index-max-record-count created or replaced
Content: {}
"204":
Description: No Content
Content: {}
"400":
Description: Bad Request
Content: {}
"401":
Description: Unauthorized
Content: {}
"404":
Description: Not Found
Content: {}
"405":
Description: Method Not Allowed
Content: {}
"409":
Description: Conflict
Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: index-max-record-count
delete:

Tags:
- data
- delete
Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_index_max_record_count_delete

Parameters:
- Name: datastore-name
In: path
Required/Optional: true
Style: simple
Explode: false
Schema:
Type: string
Format: string

Responses:
"204":
Description: No Content
Content: {}
security:

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_index_max_record_count_options


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_index_max_record_count_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_index_max_record_count_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_index-max-record-count"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf index-max-record-count updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: index-max-record-count
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/overload-protection/sl

get:

Tags:
- data
- get

Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_slot_max_record_count_get

Parameters:
- **Name**: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string

```
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_slot-max-record-count"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_slot_max_record_count_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_slot-max-record-count"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf slot-max-record-count created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: slot-max-record-count
```

```
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_slot_max_record_count_delete


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_slot_max_record_count_options


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_slot_max_record_count_head

Parameters:
- **Name**: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_slot_max_record_count_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_slot-max-record-count"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf slot-max-record-count updated
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: slot-max-record-count
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/overload-protection/sl

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_slot_max_size_get


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_slot-max-size"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_slot_max_size_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_slot-max-size"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf slot-max-size created or replaced
        Content: {}
      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: slot-max-size
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_slot_max_size_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_slot_max_size_options


  Parameters:
```

```
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_slot_max_size_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_slot_max_size_patch


    Parameters:
    - Name: datastore-name
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_slot-max-size"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf slot-max-size updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: slot-max-size
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/overload-protection/ha

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_hard_limit_percentage_get

    Parameters:
    - Name: datastore-name
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_hard-limit-percentage"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_hard_limit_percentage_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_hard-limit-percentage"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf hard-limit-percentage created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: hard-limit-percentage
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_hard_limit_percentage_delete


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_hard_limit_percentage_options


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_hard_limit_percentage_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_hard_limit_percentage_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_hard-limit-percentage"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf hard-limit-percentage updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: hard-limit-percentage
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/overload-protection/

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_major_alert_threshold_get


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_major-alert-threshold"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_major_alert_threshold_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_major-alert-threshold"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf major-alert-threshold created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: major-alert-threshold
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_major_alert_threshold_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_major_alert_threshold_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_major_alert_threshold_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_major_alert_threshold_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_major-alert-threshold"

```
      Required/Optional: true

    Responses:
      "204":
        Description: leaf major-alert-threshold updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: major-alert-threshold
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/overload-protection/

```
  get:

    Tags:
    - data
    - get
    Operation ID:
```

data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_critical_alert_threshold_get

```
    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_critical-alert-threshold"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_critical_alert_threshold_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_critical-alert-threshold"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: leaf critical-alert-threshold created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: critical-alert-threshold
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_critical_alert_threshold_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_critical_alert_threshold_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_critical_alert_threshold_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_overload_protection_critical_alert_threshold_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_critical-alert-threshold"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf critical-alert-threshold updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: critical-alert-threshold
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/index-overwrite-det

```
  get:
```

```
    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_get

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection"

      Required/Optional: true

    Responses:
      "201":
        Description: container index-overwrite-detection created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: index-overwrite-detection
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_post
```

```
    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container index-overwrite-detection created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: index-overwrite-detection
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_delete

    Parameters:
```

```
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection"

      Required/Optional: true

    Responses:
      "204":
        Description: container index-overwrite-detection updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: index-overwrite-detection
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/index-overwrite-det

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_unique_keys_prefix_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/index-overwrite-det

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_unique_keys_prefix_unique_keys_prefix_key_prefix_get


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
```

```
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: unique-keys-prefix-key-prefix
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_unique-keys-prefix_unique-keys-prefix-key-prefix"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_unique_keys_prefix_unique_keys_prefix_key_prefix_put
```

```
Parameters:
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: unique-keys-prefix-key-prefix
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: insert
  In: query
  Description: controlling the order when adding new list elements
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: first
    enum:
    - first
    - last
    - before
    - after
- Name: point
  In: query
  Description: used to specify the insertion point
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_unique-keys-prefix_unique-keys-prefix-key-prefix"

  Required/Optional: true

Responses:
```

```
      "201":
        Description: list unique-keys-prefix created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: unique-keys-prefix
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_unique_keys_prefix_unique_keys_prefix_key_prefix_delete


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: unique-keys-prefix-key-prefix
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_unique_keys_prefix_unique_keys_prefix_key_prefix_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: unique-keys-prefix-key-prefix
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_unique_keys_prefix_unique_keys_prefix_key_prefix_head


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: unique-keys-prefix-key-prefix
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_unique_keys_prefix_unique_keys_prefix_key_prefix_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: unique-keys-prefix-key-prefix
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_unique-keys-prefix_unique-keys-prefix-key-prefix"

      Required/Optional: true
```

```
Responses:
  "204":
    Description: list unique-keys-prefix updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: unique-keys-prefix
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/index-overwrite-det

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_unique_keys_prefix_unique_keys_prefix_key_prefix_key_prefix_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: unique-keys-prefix-key-prefix
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_unique-keys-prefix_unique-keys-prefix-key-prefix_key-prefix"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_unique_keys_prefix_unique_keys_prefix_key_prefix_key_prefix_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: unique-keys-prefix-key-prefix
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_unique-keys-prefix_unique-keys-prefix-key-prefix_key-prefix"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf key-prefix created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key-prefix
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_unique_keys_prefix_unique_keys_prefix_key_prefix_key_prefix_delete


    Parameters:
    - Name: datastore-name
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: unique-keys-prefix-key-prefix
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_unique_keys_prefix_unique_keys_prefix_key_prefix_key_prefix_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: unique-keys-prefix-key-prefix
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
```

```
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_unique_keys_prefix_unique_keys_prefix_key_prefix_key_prefix_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: unique-keys-prefix-key-prefix
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_unique_keys_prefix_unique_keys_prefix_key_prefix_key_prefix_patch


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string
    - Name: unique-keys-prefix-key-prefix
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_unique-keys-prefix_unique-keys-prefix-key-prefix_key-prefix"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf key-prefix updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key-prefix
```


/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/index-overwrite-detec


```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_unique_keys_prefix_unique_keys_prefix_key_prefix_action_get
```

```
Parameters:
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: unique-keys-prefix-key-prefix
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_unique-keys-prefix_unique-keys-prefix-key-prefix_action"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_unique_keys_prefix_unique_keys_prefix_key_prefix_action_put

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: unique-keys-prefix-key-prefix
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_unique-keys-prefix_unique-keys-prefix-key-prefix_action"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf action created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: action
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_unique_keys_prefix_unique_keys_prefix_key_prefix_action_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: unique-keys-prefix-key-prefix
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_unique_keys_prefix_unique_keys_prefix_key_prefix_action_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: string
  - Name: unique-keys-prefix-key-prefix
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_unique_keys_prefix_unique_keys_prefix_key_prefix_action_head


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: unique-keys-prefix-key-prefix
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_unique_keys_prefix_unique_keys_prefix_key_prefix_action_patch


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: unique-keys-prefix-key-prefix
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_unique-keys-prefix_unique-keys-prefix-key-prefix_action"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf action updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: action
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/index-overwrite-detec

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_max_tps_get


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_max-tps"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_max_tps_put


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_max-tps"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf max-tps created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: max-tps
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_max_tps_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_max_tps_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
```

```
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_max_tps_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_max_tps_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_max-tps"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: leaf max-tps updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: max-tps
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/index-overwrite-detec

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_queue_size_get


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_queue-size"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_queue_size_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_queue-size"

      Required/Optional: true
```

```
  Responses:
    "201":
      Description: leaf queue-size created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: queue-size
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_queue_size_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
```

```
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_queue_size_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_queue_size_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
```

```
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
```

```
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_index_overwrite_detection_queue_size_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_queue-size"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf queue-size updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: queue-size
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/remote-site-connectio

```
  get:

    Tags:
    - data
```

```
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_get


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring"

        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    put:

      Tags:
      - data
      - put
      Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_put
```

```
    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring"

      Required/Optional: true

    Responses:
      "201":
        Description: container remote-site-connection-monitoring created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remote-site-connection-monitoring
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_post
```

```
    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container remote-site-connection-monitoring created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remote-site-connection-monitoring
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_delete


    Parameters:
```

```
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_options


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring"

      Required/Optional: true

    Responses:
      "204":
        Description: container remote-site-connection-monitoring updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: remote-site-connection-monitoring
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/remote-site-connectio

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_enable_get


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_enable"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_enable_put


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_enable"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf enable created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_enable_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_enable_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_enable_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_enable_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_enable"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf enable updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/remote-site-connectio

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_client_side_load_balancing_get


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_client-side-load-balancing"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_client_side_load_balancing_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_client-side-load-balancing"

      Required/Optional: true

    Responses:
      "201":
        Description: container client-side-load-balancing created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: client-side-load-balancing
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_client_side_load_balancing_post


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_client-side-load-balancing-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container client-side-load-balancing created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: client-side-load-balancing
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_client_side_load_balancing_delete


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
```

```
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_client_side_load_balancing_options


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_client_side_load_balancing_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_client_side_load_balancing_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_client-side-load-balancing"

      Required/Optional: true

    Responses:
      "204":
        Description: container client-side-load-balancing updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: client-side-load-balancing
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/remote-site-connectio

get:

Tags:
- data
- get

Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_client_side_load_balancing_enable_get

Parameters:
- **Name**: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string

```
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_client-side-load-balancing_enable"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_client_side_load_balancing_enable_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_client-side-load-balancing_enable"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf enable created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable
```

```
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_client_side_load_balancing_enable_delete


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_client_side_load_balancing_enable_options


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_client_side_load_balancing_enable_head

Parameters:
- **Name**: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_client_side_load_balancing_enable_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_client-side-load-balancing_enable"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf enable updated
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/features/remote-site-connectio

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_client_side_load_balancing_wait_seconds_before_load_balancing_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
    - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_client-side-load-balancing_wait-seconds-before-load-balancing"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_client_side_load_balancing_wait_seconds_before_load_balancing_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_client-side-load-balancing_wait-seconds-before-load-balancing"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf wait-seconds-before-load-balancing created or replaced
        Content: {}
      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: wait-seconds-before-load-balancing
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_client_side_load_balancing_wait_seconds_before_load_balancing_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_client_side_load_balancing_wait_seconds_before_load_balancing_options


  Parameters:
```

```
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_client_side_load_balancing_wait_seconds_before_load_balancing_head


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_features_remote_site_connection_monitoring_client_side_load_balancing_wait_seconds_before_load_balancing_patch

    Parameters:
    - Name: datastore-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_client-side-loadbalancing_wait-seconds-before-loadbalancing"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf wait-seconds-before-load-balancing updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: wait-seconds-before-load-balancing
```


/data/cisco-smi-cdl:cdl/datastore={datastore-name}/overload-protection


```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_overload_protection_get

  Parameters:
  - Name: datastore-name
    In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_overload-protection"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_overload_protection_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_overload-protection"
      Required/Optional: true

    Responses:
      "201":
        Description: container overload-protection created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: overload-protection
  Method: Post:

    Tags:
    - data
    - post
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_overload_protection_post


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_overload-protection-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container overload-protection created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: overload-protection
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_overload_protection_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
 options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_overload_protection_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_overload_protection_head


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_overload_protection_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_overload-protection"
      Required/Optional: true

    Responses:
      "204":
        Description: container overload-protection updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: overload-protection
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/overload-protection/disable

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_overload_protection_disable_get

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_overload-protection_disable"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_overload_protection_disable_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_overload-protection_disable"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf disable created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: disable
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_overload_protection_disable_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_overload_protection_disable_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_overload_protection_disable_head

    Parameters:
```

```
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_overload_protection_disable_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_overload-protection_disable"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf disable updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: disable
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/endpoint

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_put

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint"
    Required/Optional: true

  Responses:
    "201":
      Description: container endpoint created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: endpoint
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_post

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container endpoint created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: endpoint
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_delete

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
```

```
- data
- head
Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_head

Parameters:
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_patch

      Parameters:
      - Name: datastore-name
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint"
        Required/Optional: true

      Responses:
        "204":
          Description: container endpoint updated
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: endpoint
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/endpoint/patch-url

```
get:

  Tags:
  - data
  - get
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_patch_url_get


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_patch-url"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_patch_url_put


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_patch-url"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf patch-url created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: patch-url
  delete:

    Tags:
    - data
    - delete
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_patch_url_delete


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_patch_url_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_patch_url_head


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_patch_url_patch


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_patch-url"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf patch-url updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: patch-url
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/endpoint/go-debug

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_go_debug_get

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_go-debug"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_go_debug_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_go-debug"
      Required/Optional: true

    Responses:
      "201":
```

```
      Description: leaf go-debug created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: go-debug
delete:

  Tags:
  - data
  - delete
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_go_debug_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_go_debug_options
```

```
  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_go_debug_head


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_go_debug_patch


    Parameters:
```

```
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_go-debug"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf go-debug updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: go-debug
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/endpoint/go-max-procs

```
  get:

    Tags:
    - data
    - get
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_go_max_procs_get

    Parameters:
    - Name: datastore-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_go-max-procs"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_go_max_procs_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_go-max-procs"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf go-max-procs created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: go-max-procs
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_go_max_procs_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_go_max_procs_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_go_max_procs_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_go_max_procs_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_go-max-procs"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf go-max-procs updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: go-max-procs
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/endpoint/cpu-request

```
get:

  Tags:
  - data
  - get
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_cpu_request_get


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_cpu-request"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
```

```
        Content: {}
      security:
      - basicAuth: []
    put:

      Tags:
      - data
      - put
     Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_cpu_request_put


      Parameters:
      - Name: datastore-name
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_cpu-request"

        Required/Optional: true

      Responses:
        "201":
          Description: leaf cpu-request created or replaced
          Content: {}
        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
```

```
    x-codegen-request-body-name: cpu-request
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_cpu_request_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_cpu_request_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_cpu_request_head

Parameters:
- **Name**: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string

```
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_cpu_request_patch

      Parameters:
      - Name: datastore-name
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_cpu-request"

        Required/Optional: true

      Responses:
        "204":
          Description: leaf cpu-request updated
          Content: {}
        "400":
```

```
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: cpu-request
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/endpoint/cpu-limit

```
get:

  Tags:
  - data
  - get
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_cpu_limit_get


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_cpu-limit"
    "204":
      Description: No Content
      Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_cpu_limit_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_cpu-limit"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf cpu-limit created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cpu-limit
delete:

  Tags:
  - data
  - delete
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_cpu_limit_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_cpu_limit_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_cpu_limit_head


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_cpu_limit_patch


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_cpu-limit"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf cpu-limit updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu-limit
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/endpoint/memory-request

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_memory_request_get

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_memory-request"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_memory_request_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

```
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_memory-request"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf memory-request created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: memory-request
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_memory_request_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
```

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_memory_request_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_memory_request_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
```

```
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
```

```
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_memory_request_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_memory-request"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf memory-request updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: memory-request
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/endpoint/memory-limit

```
  get:

    Tags:
    - data
```

```
- get
Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_memory_limit_get

Parameters:
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_memory-limit"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_memory_limit_put
```

```
    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_memory-limit"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf memory-limit created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: memory-limit
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_memory_limit_delete

    Parameters:
    - Name: datastore-name
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_memory_limit_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_memory_limit_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_memory_limit_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_memory-limit"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf memory-limit updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory-limit
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/endpoint/replica

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_replica_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_replica"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_replica_put

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_replica"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf replica created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: replica
delete:

  Tags:
  - data
  - delete
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_replica_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_replica_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
```

```
- head
Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_replica_head

Parameters:
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_replica_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_replica"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf replica updated
        Content: {}
      "400":
        Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replica
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/endpoint/copies-per-node

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_copies_per_node_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_copies-per-node"

    "204":
      Description: No Content
      Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_copies_per_node_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_copies-per-node"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf copies-per-node created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: copies-per-node
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_copies_per_node_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_copies_per_node_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_copies_per_node_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_copies_per_node_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_copies-per-node"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf copies-per-node updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: copies-per-node
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/endpoint/settings

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_get

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

```
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings"
      Required/Optional: true

    Responses:
      "201":
        Description: container settings created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: settings
  Method: Post:

    Tags:
    - data
    - post
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_post


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings-post"

      Required/Optional: true
```

```
  Responses:
    "201":
      Description: container settings created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: settings
delete:

  Tags:
  - data
  - delete
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
```

```
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_options


 Parameters:
 - Name: datastore-name
   In: path
   Required/Optional: true
   Style: simple
   Explode: false
   Schema:
     Type: string
     Format: string

 Responses:
   "200":
     Description: OK
     Content: {}
 security:
 - basicAuth: []
head:

 Tags:
 - data
 - head
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_head


 Parameters:
 - Name: datastore-name
   In: path
   Required/Optional: true
   Style: simple
   Explode: false
   Schema:
     Type: string
     Format: string
 - Name: content
   In: query
   Description: controlling descendant nodes in response
   Required/Optional: false
   Style: form
   Explode: true
   Schema:
     Type: string
     Format: enumeration
     Default: config
     enum:
     - config
     - nonconfig
     - all
 - Name: depth
   In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_patch
```

```
    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings"
      Required/Optional: true

    Responses:
      "204":
        Description: container settings updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: settings
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/endpoint/settings/index-timeou

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_index_timeout_ms_get
```

```
Parameters:
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings_index-timeout-ms"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_index_timeout_ms_put

    Parameters:
    - Name: datastore-name
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings_index-timeout-ms"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf index-timeout-ms created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: index-timeout-ms
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_index_timeout_ms_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_index_timeout_ms_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_index_timeout_ms_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_index_timeout_ms_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings_index-timeout-ms"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf index-timeout-ms updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: index-timeout-ms
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/endpoint/settings/slot-timeou

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_slot_timeout_ms_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings_slot-timeout-ms"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_slot_timeout_ms_put

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings_slot-timeout-ms"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf slot-timeout-ms created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: slot-timeout-ms
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_slot_timeout_ms_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_slot_timeout_ms_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
```

```
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_slot_timeout_ms_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_slot_timeout_ms_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings_slot-timeout-ms"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf slot-timeout-ms updated
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: slot-timeout-ms
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/endpoint/settings/remote-ep-

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_remote_ep_connection_count_get


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings_remote-ep-connection-count"

    "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_remote_ep_connection_count_put


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings_remote-ep-connection-count"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf remote-ep-connection-count created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remote-ep-connection-count
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_remote_ep_connection_count_delete


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_remote_ep_connection_count_options


    Parameters:
    - Name: datastore-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_remote_ep_connection_count_head


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_settings_remote_ep_connection_count_patch


    Parameters:
    - Name: datastore-name
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings_remote-ep-connection-count"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf remote-ep-connection-count updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remote-ep-connection-count
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/endpoint/external-ip

```
  get:

    Tags:
    - data
    - get
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_external_ip_get


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_external-ip"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_external_ip_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_external-ip"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf external-ip created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: external-ip
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_external_ip_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_external_ip_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_external_ip_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_external_ip_patch

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_external-ip"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf external-ip updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: external-ip
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/endpoint/external-ipv6

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_external_ipv6_get

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_external-ipv6"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_external_ipv6_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_external-ipv6"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf external-ipv6 created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: external-ipv6
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_external_ipv6_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_external_ipv6_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_external_ipv6_head

    Parameters:
```

```
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_external_ipv6_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_external-ipv6"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf external-ipv6 updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: external-ipv6
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/endpoint/external-port

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_external_port_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_external-port"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_external_port_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_external-port"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf external-port created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: external-port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_external_port_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_external_port_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_external_port_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_endpoint_external_port_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_external-port"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf external-port updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: external-port
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/index

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_get

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index"
      Required/Optional: true

    Responses:
```

```
      "201":
        Description: container index created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: index
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_post

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container index created
        Content: {}
      "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: index
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_delete

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_options

  Parameters:
  - Name: datastore-name
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_head

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_patch

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index"
      Required/Optional: true

    Responses:
      "204":
        Description: container index updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: index
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/index/patch-url

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_patch_url_get

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_patch-url"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_patch_url_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_patch-url"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf patch-url created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: patch-url
  delete:

    Tags:
    - data
    - delete
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_patch_url_delete


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
```

```
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_patch_url_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_patch_url_head

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
```

```
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_patch_url_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_patch-url"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf patch-url updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: patch-url
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/index/go-debug

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_go_debug_get
```

```
Parameters:
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_go-debug"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_go_debug_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_go-debug"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf go-debug created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: go-debug
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_go_debug_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_go_debug_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_go_debug_head

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_go_debug_patch

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_go-debug"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf go-debug updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: go-debug
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/index/go-max-procs

```
get:

  Tags:
  - data
  - get
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_go_max_procs_get


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_go-max-procs"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
    Tags:
    - data
    - put
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_go_max_procs_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_go-max-procs"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf go-max-procs created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: go-max-procs
  delete:

    Tags:
    - data
```

```
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_go_max_procs_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_index_go_max_procs_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_go_max_procs_head

    Parameters:
    - Name: datastore-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_go_max_procs_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_go-max-procs"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf go-max-procs updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: go-max-procs
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/index/cpu-request

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_cpu_request_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: integer
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_cpu-request"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_cpu_request_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_cpu-request"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf cpu-request created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cpu-request
delete:

  Tags:
  - data
  - delete
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_cpu_request_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_cpu_request_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
```

```
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_cpu_request_head


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_cpu_request_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_cpu-request"
      Required/Optional: true

    Responses:
```

```
    "204":
      Description: leaf cpu-request updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cpu-request
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/index/cpu-limit

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_cpu_limit_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

```
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_cpu-limit"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_cpu_limit_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_cpu-limit"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf cpu-limit created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cpu-limit
delete:

  Tags:
  - data
  - delete
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_cpu_limit_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_cpu_limit_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_cpu_limit_head

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_cpu_limit_patch

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_cpu-limit"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf cpu-limit updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cpu-limit
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/index/memory-request

```
get:

  Tags:
  - data
  - get
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_memory_request_get


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_memory-request"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_memory_request_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_memory-request"

     Required/Optional: true

   Responses:
     "201":
       Description: leaf memory-request created or replaced
       Content: {}
     "204":
       Description: No Content
       Content: {}
     "400":
       Description: Bad Request
       Content: {}
     "401":
       Description: Unauthorized
       Content: {}
     "404":
       Description: Not Found
       Content: {}
     "405":
       Description: Method Not Allowed
       Content: {}
     "409":
       Description: Conflict
       Content: {}
   security:
   - basicAuth: []
   x-codegen-request-body-name: memory-request
 delete:

   Tags:
   - data
   - delete
   Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_index_memory_request_delete

   Parameters:
   - Name: datastore-name
     In: path
     Required/Optional: true
     Style: simple
     Explode: false
     Schema:
       Type: string
       Format: string

   Responses:
     "204":
       Description: No Content
       Content: {}
   security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_index_memory_request_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_memory_request_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_index_memory_request_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_memory-request"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf memory-request updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: memory-request
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/index/memory-limit

```
  get:

    Tags:
```

```
- data
- get
Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_memory_limit_get

Parameters:
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_memory-limit"
        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    put:

      Tags:
      - data
      - put
     Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_memory_limit_put
```

```
    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_memory-limit"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf memory-limit created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: memory-limit
  delete:

    Tags:
    - data
    - delete
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_memory_limit_delete


    Parameters:
    - Name: datastore-name
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_index_memory_limit_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_memory_limit_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
     Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_memory_limit_patch


      Parameters:
      - Name: datastore-name
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_memory-limit"
        Required/Optional: true

      Responses:
        "204":
          Description: leaf memory-limit updated
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
```

```
    Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory-limit
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/index/replica

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_replica_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_replica"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_replica_put

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_replica"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf replica created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replica
```

```
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_replica_delete

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_replica_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_replica_head

  Parameters:
```

```
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_replica_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_replica"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf replica updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: replica
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/index/prev-map-count

```
get:

 Tags:
 - data
 - get
Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_prev_map_count_get


 Parameters:
 - Name: datastore-name
   In: path
   Required/Optional: true
   Style: simple
   Explode: false
   Schema:
     Type: string
     Format: string
 - Name: content
   In: query
   Description: controlling descendant nodes in response
   Required/Optional: false
   Style: form
   Explode: true
   Schema:
     Type: string
     Format: enumeration
     Default: config
     enum:
     - config
     - nonconfig
     - all
 - Name: depth
   In: query
   Description: limit the depth of nodes in response
   Required/Optional: false
   Style: form
   Explode: true
   Schema:
```

```
        Type: integer
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_prev-map-count"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_prev_map_count_put


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_prev-map-count"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf prev-map-count created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: prev-map-count
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_index_prev_map_count_delete

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_index_prev_map_count_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_prev_map_count_head


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_index_prev_map_count_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_prev-map-count"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: leaf prev-map-count updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: prev-map-count
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/index/map

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_map_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_map"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_map_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_map"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf map created or replaced
        Content: {}
```

```
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: map
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_map_delete

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_map_options

  Parameters:
  - Name: datastore-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_map_head

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_map_patch

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_map"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf map updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: map
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/index/write-factor

```
  get:

    Tags:
    - data
    - get
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_write_factor_get


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_write-factor"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_write_factor_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_write-factor"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf write-factor created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: write-factor
  delete:

    Tags:
    - data
    - delete
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_write_factor_delete


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
```

```
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_index_write_factor_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_write_factor_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_index_write_factor_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
   Request Body:
     Content:
       application/yang-data+json:
         Schema:
           Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_write-factor"
     Required/Optional: true

   Responses:
     "204":
       Description: leaf write-factor updated
       Content: {}
     "400":
       Description: Bad Request
       Content: {}
     "401":
       Description: Unauthorized
       Content: {}
     "404":
       Description: Not Found
       Content: {}
     "405":
       Description: Method Not Allowed
       Content: {}
     "409":
       Description: Conflict
       Content: {}
   security:
   - basicAuth: []
   x-codegen-request-body-name: write-factor
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot

```
  get:

    Tags:
```

```
- data
- get
Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_get

Parameters:
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot"
        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    put:

      Tags:
      - data
      - put
      Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_put

      Parameters:
```

```
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot"
      Required/Optional: true

    Responses:
      "201":
        Description: container slot created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: slot
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_post

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container slot created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: slot
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_head

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
        Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_patch

      Parameters:
      - Name: datastore-name
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot"
        Required/Optional: true

      Responses:
        "204":
          Description: container slot updated
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
      x-codegen-request-body-name: slot
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/patch-url

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_patch_url_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_patch-url"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_patch_url_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_patch-url"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf patch-url created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: patch-url
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_patch_url_delete
```

```
  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_patch_url_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_patch_url_head

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_patch_url_patch

      Parameters:
      - Name: datastore-name
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_patch-url"
        Required/Optional: true

      Responses:
        "204":
          Description: leaf patch-url updated
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: patch-url
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/go-debug

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_go_debug_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_go-debug"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_go_debug_put

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_go-debug"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf go-debug created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: go-debug
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_go_debug_delete

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_go_debug_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_go_debug_head
```

```
Parameters:
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_go_debug_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_go-debug"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf go-debug updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: go-debug
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/go-max-procs

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_go_max_procs_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_go-max-procs"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_go_max_procs_put

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_go-max-procs"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf go-max-procs created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: go-max-procs
delete:

  Tags:
  - data
  - delete
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_go_max_procs_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_go_max_procs_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_go_max_procs_head


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_go_max_procs_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_go-max-procs"
      Required/Optional: true
```

```
  Responses:
    "204":
      Description: leaf go-max-procs updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: go-max-procs
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/cpu-request

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_cpu_request_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_cpu-request"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_cpu_request_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_cpu-request"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf cpu-request created or replaced
        Content: {}
      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cpu-request
delete:

  Tags:
  - data
  - delete
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_cpu_request_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_cpu_request_options


  Parameters:
  - Name: datastore-name
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_cpu_request_head

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_cpu_request_patch


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_cpu-request"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf cpu-request updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu-request
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/cpu-limit

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_cpu_limit_get

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_cpu-limit"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_cpu_limit_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_cpu-limit"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf cpu-limit created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cpu-limit
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_cpu_limit_delete

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
```

```
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_cpu_limit_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_cpu_limit_head

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
```

```
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_cpu_limit_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_cpu-limit"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf cpu-limit updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu-limit
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/memory-request

```
  get:

    Tags:
    - data
    - get
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_memory_request_get
```

```
Parameters:
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_memory-request"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_memory_request_put


    Parameters:
    - Name: datastore-name
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_memory-request"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf memory-request created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: memory-request
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_memory_request_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_memory_request_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_memory_request_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_memory_request_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_memory-request"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf memory-request updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: memory-request
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/memory-limit

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_memory_limit_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_memory-limit"
        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
```

```
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_memory_limit_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_memory-limit"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf memory-limit created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: memory-limit
  delete:
```

```
  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_memory_limit_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_memory_limit_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_memory_limit_head


  Parameters:
```

```
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_memory_limit_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_memory-limit"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf memory-limit updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory-limit
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/replica

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_replica_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_replica"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_replica_put

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_replica"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf replica created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replica
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_replica_delete

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_replica_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
```

```
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_replica_head

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_replica_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_replica"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf replica updated
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replica
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/map

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_map_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_map"
    "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_map_put

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_map"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf map created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: map
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_map_delete

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_map_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_map_head

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_map_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_map"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf map updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: map
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/write-factor

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_write_factor_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_write-factor"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_write_factor_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_write-factor"
      Required/Optional: true

    Responses:
      "201":
```

```
      Description: leaf write-factor created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: write-factor
delete:

  Tags:
  - data
  - delete
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_write_factor_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_write_factor_options
```

```
  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_write_factor_head


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_write_factor_patch


  Parameters:
```

```
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_write-factor"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf write-factor updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: write-factor
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/notification

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_get

    Parameters:
    - Name: datastore-name
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification"
      Required/Optional: true

    Responses:
      "201":
        Description: container notification created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: notification
  Method: Post:

    Tags:
    - data
    - post
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_post


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container notification created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: notification
  delete:

    Tags:
    - data
    - delete
   Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_delete


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_head


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification"
      Required/Optional: true

    Responses:
      "204":
        Description: container notification updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: notification
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/notification/connection-co

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_connection_count_get

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_connection-count"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_connection_count_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_connection-count"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf connection-count created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: connection-count
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_connection_count_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_connection_count_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_connection_count_head

    Parameters:
```

```
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_connection_count_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_connection-count"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf connection-count updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: connection-count
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/notification/dynamic-provi

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_dynamic_provisioning_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_dynamic-provisioning"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_dynamic_provisioning_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_dynamic-provisioning"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf dynamic-provisioning created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: dynamic-provisioning
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_dynamic_provisioning_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_dynamic_provisioning_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_dynamic_provisioning_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_dynamic_provisioning_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_dynamic-provisioning"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf dynamic-provisioning updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: dynamic-provisioning
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/notification/host

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_host_get

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_host"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_host_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_host"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf host created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: host
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_host_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_host_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_host_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_host_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_host"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf host updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: host
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/notification/port

```
  get:

    Tags:
```

```
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_port_get

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_port"

        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    put:

      Tags:
      - data
      - put
      Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_port_put
```

```
    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_port"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf port created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_port_delete

    Parameters:
```

```
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_port_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_port_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_port_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_port"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf port updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: port
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/notification/limit

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_limit_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_limit"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_limit_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_limit"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf limit created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: limit
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_limit_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_limit_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

```
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_limit_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_limit_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_limit"

      Required/Optional: true

    Responses:
```

```
    "204":
      Description: leaf limit updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: limit
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/notification/max-concurr

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_max_concurrent_bulk_notifications_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_max-concurrent-bulk-notifications"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_max_concurrent_bulk_notifications_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_max-concurrent-bulk-notifications"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf max-concurrent-bulk-notifications created or replaced
```

```
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: max-concurrent-bulk-notifications
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_max_concurrent_bulk_notifications_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_max_concurrent_bulk_notifications_options
```

```
    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_max_concurrent_bulk_notifications_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_max_concurrent_bulk_notifications_patch
```

```
    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_max-concurrent-bulk-notifications"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf max-concurrent-bulk-notifications updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: max-concurrent-bulk-notifications
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/notification/bulk-task-pr

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_bulk_task_progress_update_batch_size_get
```

```
Parameters:
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_bulk-task-progress-update-batch-size"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_bulk_task_progress_update_batch_size_put


    Parameters:
    - Name: datastore-name
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_bulk-task-progress-update-batch-size"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf bulk-task-progress-update-batch-size created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: bulk-task-progress-update-batch-size
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_bulk_task_progress_update_batch_size_delete


    Parameters:
    - Name: datastore-name
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_bulk_task_progress_update_batch_size_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_bulk_task_progress_update_batch_size_head


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_bulk_task_progress_update_batch_size_patch


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_bulk-task-progress-update-batch-size"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf bulk-task-progress-update-batch-size updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: bulk-task-progress-update-batch-size
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/notification/notification-re

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_notification_retry_seconds_get


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_notification-retry-seconds"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_notification_retry_seconds_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_notification-retry-seconds"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf notification-retry-seconds created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: notification-retry-seconds
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_notification_retry_seconds_delete


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_notification_retry_seconds_options


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
```

```
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_notification_retry_seconds_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_notification_retry_seconds_patch


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_notification-retry-seconds"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf notification-retry-seconds updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: notification-retry-seconds
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/notification/include-conflic

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_include_conflict_data_get


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_include-conflict-data"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_include_conflict_data_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_include-conflict-data"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf include-conflict-data created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: include-conflict-data
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_include_conflict_data_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_include_conflict_data_options


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_include_conflict_data_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_include_conflict_data_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_include-conflict-data"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf include-conflict-data updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: include-conflict-data
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/notification/remote-syste

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_remote_system_id_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/notification/remote-syste

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_remote_system_id_remote_system_id_id_get


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: remote-system-id-id
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_remote-system-id_remote-system-id-id"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_remote_system_id_remote_system_id_id_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: string
  - Name: remote-system-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_remote-system-id_remote-system-id-id"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf-list remote-system-id created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: remote-system-id
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_remote_system_id_remote_system_id_id_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: remote-system-id-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
```

```
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_remote_system_id_remote_system_id_id_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: remote-system-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_remote_system_id_remote_system_id_id_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: remote-system-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: leafref
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_remote_system_id_remote_system_id_id_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: remote-system-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_remote-system-id_remote-system-id-id"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf-list remote-system-id updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: remote-system-id
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/notification/use-stream

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_use_stream_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_use-stream"

      "204":
        Description: No Content
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_use_stream_put

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_use-stream"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf use-stream created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: use-stream
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_use_stream_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_use_stream_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_use_stream_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_use_stream_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_use-stream"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf use-stream updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: use-stream
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/notification/include-slic

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_include_slice_in_header_get


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_include-slice-in-header"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_include_slice_in_header_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_include-slice-in-header"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf include-slice-in-header created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: include-slice-in-header
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_include_slice_in_header_delete


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
```

```
      Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_include_slice_in_header_options


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_include_slice_in_header_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_include_slice_in_header_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_include-slice-in-header"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf include-slice-in-header updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: include-slice-in-header
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/notification/endpoints

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/notification/endpoints={en

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_get


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-slice-name
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: endpoints-app-instance-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_put
```

```
Parameters:
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: endpoints-slice-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: endpoints-app-instance-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: insert
  In: query
  Description: controlling the order when adding new list elements
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: first
    enum:
    - first
    - last
    - before
    - after
- Name: point
  In: query
  Description: used to specify the insertion point
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
Request Body:
  Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id"

      Required/Optional: true

    Responses:
      "201":
        Description: list endpoints created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: endpoints
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_delete


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-slice-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: endpoints-app-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_options


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-slice-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: endpoints-app-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
```

```
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-slice-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: endpoints-app-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-slice-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: endpoints-app-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id"

      Required/Optional: true

    Responses:
      "204":
        Description: list endpoints updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: endpoints
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/notification/endpoints={e

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_slice_name_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: endpoints-slice-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: endpoints-app-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_slice-name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_slice_name_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-slice-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: leafref
    - Name: endpoints-app-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_slice-name"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf slice-name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: slice-name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_slice_name_delete
```

```
  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: endpoints-slice-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: endpoints-app-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_slice_name_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: endpoints-slice-name
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: endpoints-app-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_slice_name_head


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: endpoints-slice-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: endpoints-app-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_slice_name_patch


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: endpoints-slice-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: endpoints-app-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_slice-name"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: leaf slice-name updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: slice-name
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/notification/endpoints={e

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_app_instance_id_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: endpoints-slice-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: leafref
  - Name: endpoints-app-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_app-instance-id"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_app_instance_id_put


    Parameters:
```

```
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: endpoints-slice-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: endpoints-app-instance-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_app-instance-id"

  Required/Optional: true

Responses:
  "201":
    Description: leaf app-instance-id created or replaced
    Content: {}
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: app-instance-id
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_app_instance_id_delete

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: endpoints-slice-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: endpoints-app-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_app_instance_id_options
```

```
    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-slice-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: endpoints-app-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_app_instance_id_head


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-slice-name
```

```
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: endpoints-app-instance-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_app_instance_id_patch


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: endpoints-slice-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: endpoints-app-instance-id
    In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_app-instance-id"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf app-instance-id updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: app-instance-id
```


/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/notification/endpoints={e


```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_host_get


    Parameters:
    - Name: datastore-name
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: endpoints-slice-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: endpoints-app-instance-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_host"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_host_put


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-slice-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: endpoints-app-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_host"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf host created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: host
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_host_delete


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-slice-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: endpoints-app-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
```

```
    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_host_options


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-slice-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: endpoints-app-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_host_head
```

```
Parameters:
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: endpoints-slice-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
- Name: endpoints-app-instance-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_host_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: string
  - Name: endpoints-slice-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: endpoints-app-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_host"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf host updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: host
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/notification/endpoints={en

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_port_get


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: endpoints-slice-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: endpoints-app-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_port"

    "204":
      Description: No Content
      Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_port_put


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: endpoints-slice-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: endpoints-app-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  Request Body:
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_port"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf port created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_port_delete


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-slice-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: endpoints-app-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_port_options


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-slice-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: endpoints-app-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
```

```
      Format: uint16

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_port_head


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: endpoints-slice-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  - Name: endpoints-app-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_notification_endpoints_endpoints_slice_name_endpoints_app_instance_id_port_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: endpoints-slice-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: leafref
    - Name: endpoints-app-instance-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_port"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf port updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: port
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/metrics

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_metrics_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: integer
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_metrics"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_metrics_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_metrics"
      Required/Optional: true

    Responses:
      "201":
        Description: container metrics created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: metrics
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_metrics_post

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_metrics-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container metrics created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: metrics
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_metrics_delete

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_metrics_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
```

```
Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_metrics_head

Parameters:
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_metrics_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_metrics"
      Required/Optional: true

    Responses:
      "204":
        Description: container metrics updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: metrics
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/slot/metrics/report-idle-sessi

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_metrics_report_idle_session_type_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_metrics_report-idle-session-type"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_metrics_report_idle_session_type_put

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_metrics_report-idle-session-type"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf report-idle-session-type created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: report-idle-session-type
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_metrics_report_idle_session_type_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_metrics_report_idle_session_type_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_metrics_report_idle_session_type_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_slot_metrics_report_idle_session_type_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_metrics_report-idle-session-type"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf report-idle-session-type updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: report-idle-session-type
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/test

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_get

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

```
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test"
      Required/Optional: true

    Responses:
      "201":
        Description: container test created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: test
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_post

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test-post"
      Required/Optional: true

    Responses:
```

```
    "201":
      Description: container test created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: test
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_delete

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_options
```

```
  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_head

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_patch

    Parameters:
    - Name: datastore-name
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test"
      Required/Optional: true

    Responses:
      "204":
        Description: container test updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: test
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/test/run

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_run_get

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_run"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_run_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_run"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf run created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: run
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_run_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
```

```
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_run_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_run_head

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_run_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_run"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf run updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: run
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/test/patch-url

```
  get:

    Tags:
    - data
```

```
- get
Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_patch_url_get

Parameters:
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_patch-url"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_patch_url_put

    Parameters:
```

```
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_patch-url"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf patch-url created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: patch-url
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_patch_url_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
```

```
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_patch_url_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_patch_url_head

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_patch_url_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_patch-url"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf patch-url updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: patch-url
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/test/loop

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_loop_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_loop"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_loop_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_loop"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf loop created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: loop
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_loop_delete
```

```
  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_loop_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_loop_head

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_loop_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_loop"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf loop updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: loop
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/test/txns

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_txns_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_txns"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_txns_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_txns"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf txns created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
  x-codegen-request-body-name: txns
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_txns_delete

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_txns_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_txns_head
```

```
Parameters:
- Name: datastore-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_txns_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_txns"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf txns updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: txns
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/test/txn-type

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_txn_type_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_txn-type"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_txn_type_put

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_txn-type"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf txn-type created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: txn-type
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_txn_type_delete

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_txn_type_options

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
```

```
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_txn_type_head

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_txn_type_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_txn-type"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf txn-type updated
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: txn-type
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/test/wait-time-ns

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_wait_time_ns_get

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_wait-time-ns"
    "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_wait_time_ns_put

  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_wait-time-ns"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf wait-time-ns created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: wait-time-ns
delete:

  Tags:
  - data
  - delete
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_wait_time_ns_delete


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_wait_time_ns_options


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
```

```
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_wait_time_ns_head


  Parameters:
  - Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_datastore_datastore_name_test_wait_time_ns_patch


    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_wait-time-ns"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf wait-time-ns updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: wait-time-ns
```

/data/cisco-smi-cdl:cdl/datastore={datastore-name}/test/max-non-unique-keys

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_test_max_non_unique_keys_get

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_max-non-unique-keys"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_test_max_non_unique_keys_put

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_max-non-unique-keys"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf max-non-unique-keys created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: max-non-unique-keys
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_test_max_non_unique_keys_delete

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_test_max_non_unique_keys_options

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_test_max_non_unique_keys_head

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
        - nonconfig
        - all
      - Name: depth
        In: query
        Description: limit the depth of nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: integer
          Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_datastore_datastore_name_test_max_non_unique_keys_patch

    Parameters:
    - Name: datastore-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_max-non-unique-keys"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf max-non-unique-keys updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: max-non-unique-keys
```

/data/cisco-smi-cdl:cdl/zookeeper

```
  get:

    Tags:
```

```
- data
- get
Operation ID: data_cisco_smi_cdl_cdl_zookeeper_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper"
    Required/Optional: true

  Responses:
    "201":
      Description: container zookeeper created or replaced
      Content: {}
```

```
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: zookeeper
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container zookeeper created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: zookeeper
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
```

```
- data
- patch
Operation ID: data_cisco_smi_cdl_cdl_zookeeper_patch
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper"
  Required/Optional: true

Responses:
  "204":
    Description: container zookeeper updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: zookeeper
```

/data/cisco-smi-cdl:cdl/zookeeper/data-storage-size

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_data_storage_size_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_data-storage-size"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_zookeeper_data_storage_size_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_data-storage-size"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf data-storage-size created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: data-storage-size
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_data_storage_size_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_data_storage_size_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_data_storage_size_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_zookeeper_data_storage_size_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_data-storage-size"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf data-storage-size updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: data-storage-size
```

/data/cisco-smi-cdl:cdl/zookeeper/log-storage-size

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_zookeeper_log_storage_size_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_log-storage-size"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_zookeeper_log_storage_size_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_log-storage-size"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf log-storage-size created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: log-storage-size
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_log_storage_size_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_log_storage_size_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_log_storage_size_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_zookeeper_log_storage_size_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_log-storage-size"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf log-storage-size updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: log-storage-size
```

/data/cisco-smi-cdl:cdl/zookeeper/log-level

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_zookeeper_log_level_get

    Parameters:
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_log-level"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_log_level_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_log-level"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf log-level created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: log-level
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_log_level_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_log_level_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_log_level_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_log_level_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_log-level"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf log-level updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: log-level
```

/data/cisco-smi-cdl:cdl/zookeeper/replica

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_replica_get
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_replica"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_replica_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_replica"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf replica created or replaced
      Content: {}
    "204":
      Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replica
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_replica_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_replica_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_replica_head

  Parameters:
  - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_replica_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_replica"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf replica updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replica
```

/data/cisco-smi-cdl:cdl/zookeeper/enable-JMX-metrics

```
get:

  Tags:
  - data
```

```
- get
Operation ID: data_cisco_smi_cdl_cdl_zookeeper_enable_JMX_metrics_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_enable-JMX-metrics"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_zookeeper_enable_JMX_metrics_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_enable-JMX-metrics"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf enable-JMX-metrics created or replaced
```

```
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable-JMX-metrics
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_enable_JMX_metrics_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_enable_JMX_metrics_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_enable_JMX_metrics_head
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_zookeeper_enable_JMX_metrics_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_enable-JMX-metrics"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf enable-JMX-metrics updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable-JMX-metrics
```

/data/cisco-smi-cdl:cdl/zookeeper/enable-persistence

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_enable_persistence_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_enable-persistence"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_zookeeper_enable_persistence_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_enable-persistence"
     Required/Optional: true

   Responses:
     "201":
       Description: leaf enable-persistence created or replaced
       Content: {}
     "204":
       Description: No Content
       Content: {}
     "400":
       Description: Bad Request
       Content: {}
     "401":
       Description: Unauthorized
       Content: {}
     "404":
       Description: Not Found
       Content: {}
     "405":
       Description: Method Not Allowed
       Content: {}
     "409":
       Description: Conflict
       Content: {}
   security:
   - basicAuth: []
   x-codegen-request-body-name: enable-persistence
 delete:

   Tags:
   - data
   - delete
   Operation ID: data_cisco_smi_cdl_cdl_zookeeper_enable_persistence_delete

   Responses:
     "204":
       Description: No Content
       Content: {}
   security:
   - basicAuth: []
 options:

   Tags:
   - data
   - options
   Operation ID: data_cisco_smi_cdl_cdl_zookeeper_enable_persistence_options

   Responses:
     "200":
       Description: OK
       Content: {}
```

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_enable_persistence_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_zookeeper_enable_persistence_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_enable-persistence"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf enable-persistence updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable-persistence
```

/data/cisco-smi-cdl:cdl/zookeeper/enable-parallel-pod-management

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_enable_parallel_pod_management_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_enable-parallel-pod-management"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID: data_cisco_smi_cdl_cdl_zookeeper_enable_parallel_pod_management_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_enable-parallel-pod-management"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf enable-parallel-pod-management created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable-parallel-pod-management
  delete:

    Tags:
    - data
    - delete
   Operation ID: data_cisco_smi_cdl_cdl_zookeeper_enable_parallel_pod_management_delete


    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
```

```
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_enable_parallel_pod_management_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_zookeeper_enable_parallel_pod_management_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_zookeeper_enable_parallel_pod_management_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_enable-parallel-pod-management"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf enable-parallel-pod-management updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: enable-parallel-pod-management
```

/data/cisco-smi-cdl:cdl/kafka

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_kafka_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka"
    Required/Optional: true

  Responses:
    "201":
      Description: container kafka created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: kafka
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_cdl_cdl_kafka_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka-post"
    Required/Optional: true
```

```
  Responses:
    "201":
      Description: container kafka created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: kafka
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:
```

```
Tags:
- data
- head
Operation ID: data_cisco_smi_cdl_cdl_kafka_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka"
      Required/Optional: true

    Responses:
      "204":
        Description: container kafka updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: kafka
```

/data/cisco-smi-cdl:cdl/kafka/replica

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_replica_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_replica"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_kafka_replica_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_replica"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: leaf replica created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replica
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_replica_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_replica_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

```
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_replica_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_kafka_replica_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_replica"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf replica updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replica
```

/data/cisco-smi-cdl:cdl/kafka/mode

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_mode_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_mode"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_kafka_mode_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_mode"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: leaf mode created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: mode
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_mode_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_mode_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

```
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_mode_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_kafka_mode_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_mode"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf mode updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: mode
```

/data/cisco-smi-cdl:cdl/kafka/kraft-migration

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_kraft_migration_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_kraft-migration"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_kraft_migration_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
        Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_kraft-migration"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf kraft-migration created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: kraft-migration
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_kraft_migration_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_kraft_migration_options

  Responses:
    "200":
      Description: OK
      Content: {}
```

```
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_kraft_migration_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
```

```
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_kafka_kraft_migration_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_kraft-migration"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf kraft-migration updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: kraft-migration
```

/data/cisco-smi-cdl:cdl/kafka/replication-factor

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_replication_factor_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_replication-factor"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID: data_cisco_smi_cdl_cdl_kafka_replication_factor_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_replication-factor"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf replication-factor created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: replication-factor
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_kafka_replication_factor_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_cisco_smi_cdl_cdl_kafka_replication_factor_options
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_replication_factor_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_replication_factor_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_replication-factor"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf replication-factor updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replication-factor
```

/data/cisco-smi-cdl:cdl/kafka/log-level

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_log_level_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_log-level"
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
```

```
put:
  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_kafka_log_level_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_log-level"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf log-level created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: log-level
delete:
  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_log_level_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_log_level_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_log_level_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_kafka_log_level_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_log-level"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf log-level updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: log-level
```

/data/cisco-smi-cdl:cdl/kafka/partition

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_partition_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_partition"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_kafka_partition_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_partition"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf partition created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: partition
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_partition_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
```

```
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_partition_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_partition_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_kafka_partition_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_partition"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf partition updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: partition
```

/data/cisco-smi-cdl:cdl/kafka/enable-JMX-metrics

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_enable_JMX_metrics_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_enable-JMX-metrics"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_enable_JMX_metrics_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_enable-JMX-metrics"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf enable-JMX-metrics created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable-JMX-metrics
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_kafka_enable_JMX_metrics_delete

    Responses:
      "204":
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_enable_JMX_metrics_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_enable_JMX_metrics_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_enable_JMX_metrics_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_enable-JMX-metrics"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf enable-JMX-metrics updated
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable-JMX-metrics
```

/data/cisco-smi-cdl:cdl/kafka/resource

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_resource"
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_resource"
    Required/Optional: true

  Responses:
    "201":
      Description: container resource created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: resource
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_post
```

```
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_resource-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container resource created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: resource
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_options
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_resource"
    Required/Optional: true

  Responses:
    "204":
      Description: container resource updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: resource
```

/data/cisco-smi-cdl:cdl/kafka/resource/cpu-request

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_cpu_request_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_resource_cpu-request"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_cpu_request_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_resource_cpu-request"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf cpu-request created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu-request
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_cpu_request_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
```

```
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_cpu_request_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_cpu_request_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_cpu_request_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_resource_cpu-request"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf cpu-request updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: cpu-request
```

/data/cisco-smi-cdl:cdl/kafka/resource/cpu-limit

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_cpu_limit_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_resource_cpu-limit"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_cpu_limit_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_resource_cpu-limit"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf cpu-limit created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu-limit
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_cpu_limit_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
```

```
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_cpu_limit_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_cpu_limit_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_cpu_limit_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_resource_cpu-limit"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf cpu-limit updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cpu-limit
```

/data/cisco-smi-cdl:cdl/kafka/resource/memory-request

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_memory_request_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_resource_memory-request"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_memory_request_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_resource_memory-request"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf memory-request created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory-request
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_memory_request_delete
```

```
  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_memory_request_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_memory_request_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_memory_request_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_resource_memory-request"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf memory-request updated
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory-request
```

/data/cisco-smi-cdl:cdl/kafka/resource/memory-limit

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_memory_limit_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: integer
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_resource_memory-limit"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_memory_limit_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_resource_memory-limit"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf memory-limit created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: memory-limit
  delete:

    Tags:
```

```
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_memory_limit_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_memory_limit_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_memory_limit_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_resource_memory_limit_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_resource_memory-limit"
      Required/Optional: true
```

```
  Responses:
    "204":
      Description: leaf memory-limit updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory-limit
```

/data/cisco-smi-cdl:cdl/kafka/external-ip

```
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_external_ip_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/kafka/external-ip={external-ip-ip},{external-ip-port}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_get

  Parameters:
```

```
- Name: external-ip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: external-ip-port
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
```

```
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_put

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port"
```

```
      Required/Optional: true

    Responses:
      "201":
        Description: list external-ip created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: external-ip
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_delete

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
```

```
    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_options

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_head

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: external-ip-port
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_patch

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port"

      Required/Optional: true
```

```
  Responses:
    "204":
      Description: list external-ip updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: external-ip
```

/data/cisco-smi-cdl:cdl/kafka/external-ip={external-ip-ip},{external-ip-port}/ip

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_ip_get

  Parameters:
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port_ip"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_ip_put

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port_ip"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf ip created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ip
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_ip_delete

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: string
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_ip_options

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
```

```
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_ip_head

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_ip_patch

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port_ip"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf ip updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ip
```

/data/cisco-smi-cdl:cdl/kafka/external-ip={external-ip-ip},{external-ip-port}/port

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_port_get

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: string
- Name: external-ip-port
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port_port"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_port_put

    Parameters:
    - Name: external-ip-ip
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port_port"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf port created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: port
  delete:

    Tags:
```

```
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_port_delete

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_port_options

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
```

```
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_port_head

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_port_patch

    Parameters:
    - Name: external-ip-ip
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port_port"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf port updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: port
```

/data/cisco-smi-cdl:cdl/kafka/external-ip={external-ip-ip},{external-ip-port}/ssl-port

```
  get:
```

```
    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_ssl_port_get

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port_ssl-port"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_ssl_port_put

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port_ssl-port"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf ssl-port created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ssl-port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_ssl_port_delete

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_ssl_port_options

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_ssl_port_head

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ip_external_ip_ip_external_ip_port_ssl_port_patch

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port_ssl-port"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf ssl-port updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ssl-port
```

/data/cisco-smi-cdl:cdl/kafka/external-ipv6

```
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_external_ipv6_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/kafka/external-ipv6={external-ipv6-ip},{external-ipv6-port}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_get

  Parameters:
  - Name: external-ipv6-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: external-ipv6-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_put

    Parameters:
    - Name: external-ipv6-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ipv6-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port"

      Required/Optional: true

    Responses:
      "201":
        Description: list external-ipv6 created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: external-ipv6
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_delete

  Parameters:
  - Name: external-ipv6-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: external-ipv6-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_options

  Parameters:
  - Name: external-ipv6-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
      Schema:
        Type: string
        Format: string
    - Name: external-ipv6-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_head

    Parameters:
    - Name: external-ipv6-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ipv6-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_patch

    Parameters:
    - Name: external-ipv6-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ipv6-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port"

      Required/Optional: true

    Responses:
      "204":
        Description: list external-ipv6 updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: external-ipv6
```

/data/cisco-smi-cdl:cdl/kafka/external-ipv6={external-ipv6-ip},{external-ipv6-port}/i

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_ip_get

  Parameters:
  - Name: external-ipv6-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: external-ipv6-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port_ip"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_ip_put

  Parameters:
  - Name: external-ipv6-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: external-ipv6-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port_ip"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf ip created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ip
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_ip_delete

    Parameters:
    - Name: external-ipv6-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ipv6-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
```

```
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_ip_options

    Parameters:
    - Name: external-ipv6-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ipv6-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_ip_head

    Parameters:
    - Name: external-ipv6-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ipv6-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
```

```
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_ip_patch

    Parameters:
    - Name: external-ipv6-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ipv6-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port_ip"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf ip updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ip
```

/data/cisco-smi-cdl:cdl/kafka/external-ipv6={external-ipv6-ip},{external-ipv6-port

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_port_get

  Parameters:
  - Name: external-ipv6-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: external-ipv6-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port_port"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_port_put

    Parameters:
    - Name: external-ipv6-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ipv6-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port_port"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf port created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_port_delete

    Parameters:
    - Name: external-ipv6-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ipv6-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: integer
        Format: uint16

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_port_options


    Parameters:
    - Name: external-ipv6-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ipv6-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_port_head

    Parameters:
    - Name: external-ipv6-ip
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: external-ipv6-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_port_patch

    Parameters:
    - Name: external-ipv6-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ipv6-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port_port"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf port updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: port
```

/data/cisco-smi-cdl:cdl/kafka/external-ipv6={external-ipv6-ip},{external-ipv6-port}/s

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_ssl_port_get


    Parameters:
    - Name: external-ipv6-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ipv6-port
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port_ssl-port"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_ssl_port_put


    Parameters:
    - Name: external-ipv6-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: string
    - Name: external-ipv6-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port_ssl-port"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf ssl-port created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ssl-port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_ssl_port_delete
```

```
    Parameters:
    - Name: external-ipv6-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ipv6-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_ssl_port_options


    Parameters:
    - Name: external-ipv6-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ipv6-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_ssl_port_head


  Parameters:
  - Name: external-ipv6-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: external-ipv6-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_external_ipv6_external_ipv6_ip_external_ipv6_port_ssl_port_patch


    Parameters:
    - Name: external-ipv6-ip
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ipv6-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port_ssl-port"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf ssl-port updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ssl-port
```

/data/cisco-smi-cdl:cdl/kafka/enable-persistence

```
  get:

    Tags:
    - data
    - get
```

```
Operation ID: data_cisco_smi_cdl_cdl_kafka_enable_persistence_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_enable-persistence"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_enable_persistence_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_enable-persistence"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf enable-persistence created or replaced
        Content: {}
```

```
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable-persistence
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_enable_persistence_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_enable_persistence_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_enable_persistence_head
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_enable_persistence_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_enable-persistence"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf enable-persistence updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable-persistence
```

/data/cisco-smi-cdl:cdl/kafka/storage

```
  get:
```

```
Tags:
- data
- get
Operation ID: data_cisco_smi_cdl_cdl_kafka_storage_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_storage"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_storage_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_storage"
      Required/Optional: true

    Responses:
      "201":
```

```
      Description: leaf storage created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: storage
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_storage_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_storage_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
```

```
Operation ID: data_cisco_smi_cdl_cdl_kafka_storage_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_kafka_storage_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_storage"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf storage updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: storage
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
```

```
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings"
      Required/Optional: true

    Responses:
      "201":
        Description: container ssl-settings created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ssl-settings
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container ssl-settings created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ssl-settings
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings"
    Required/Optional: true

  Responses:
    "204":
      Description: container ssl-settings updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ssl-settings
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings/enable-ssl

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_enable_ssl_get

  Parameters:
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_enable-ssl"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_enable_ssl_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_enable-ssl"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf enable-ssl created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable-ssl
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_enable_ssl_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_enable_ssl_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_enable_ssl_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_enable_ssl_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_enable-ssl"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf enable-ssl updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable-ssl
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings/disable-host-name-verification

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_disable_host_name_verification_get
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_disable-host-name-verification"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_disable_host_name_verification_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_disable-host-name-verification"

      Required/Optional: true

    Responses:
      "201":
```

```
      Description: leaf disable-host-name-verification created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: disable-host-name-verification
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_disable_host_name_verification_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_disable_host_name_verification_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
```

```
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_disable_host_name_verification_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_disable_host_name_verification_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_disable-host-name-verification"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf disable-host-name-verification updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: disable-host-name-verification
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings/auto-generation

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_auto_generation_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_auto-generation"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_auto_generation_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_auto-generation"
     Required/Optional: true

   Responses:
     "201":
       Description: container auto-generation created or replaced
       Content: {}
     "204":
       Description: No Content
       Content: {}
     "400":
       Description: Bad Request
       Content: {}
     "401":
       Description: Unauthorized
       Content: {}
     "404":
       Description: Not Found
       Content: {}
     "405":
       Description: Method Not Allowed
       Content: {}
     "409":
       Description: Conflict
       Content: {}
   security:
   - basicAuth: []
   x-codegen-request-body-name: auto-generation
 Method: Post:

   Tags:
   - data
   - post
   Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_auto_generation_post
   Request Body:
     Content:
       application/yang-data+json:
         Schema:
           Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_auto-generation-post"
     Required/Optional: true

   Responses:
     "201":
       Description: container auto-generation created
       Content: {}
     "204":
       Description: No Content
       Content: {}
     "400":
       Description: Bad Request
       Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: auto-generation
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_auto_generation_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_auto_generation_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_auto_generation_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_auto_generation_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_auto-generation"
      Required/Optional: true

    Responses:
      "204":
        Description: container auto-generation updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: auto-generation
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings/auto-generation/enabled

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_auto_generation_enabled_get

    Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_auto-generation_enabled"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_auto_generation_enabled_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_auto-generation_enabled"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf enabled created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enabled
delete:

  Tags:
  - data
  - delete
 Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_auto_generation_enabled_delete


  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_auto_generation_enabled_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_auto_generation_enabled_head
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_auto_generation_enabled_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_auto-generation_enabled"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf enabled updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enabled
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings/broker-tls-secret-name

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_tls_secret_name_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-tls-secret-name"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_tls_secret_name_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-tls-secret-name"
     Required/Optional: true

   Responses:
     "201":
       Description: leaf broker-tls-secret-name created or replaced
       Content: {}
     "204":
       Description: No Content
       Content: {}
     "400":
       Description: Bad Request
       Content: {}
     "401":
       Description: Unauthorized
       Content: {}
     "404":
       Description: Not Found
       Content: {}
     "405":
       Description: Method Not Allowed
       Content: {}
     "409":
       Description: Conflict
       Content: {}
   security:
   - basicAuth: []
   x-codegen-request-body-name: broker-tls-secret-name
 delete:

   Tags:
   - data
   - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_tls_secret_name_delete


   Responses:
     "204":
       Description: No Content
       Content: {}
   security:
   - basicAuth: []
 options:

   Tags:
   - data
   - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_tls_secret_name_options


   Responses:
     "200":
       Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_tls_secret_name_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
   Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_tls_secret_name_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-tls-secret-name"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf broker-tls-secret-name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: broker-tls-secret-name
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings/broker-ca-secret-name

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_secret_name_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-secret-name"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
```

```
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_secret_name_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-secret-name"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf broker-ca-secret-name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: broker-ca-secret-name
  delete:

    Tags:
    - data
    - delete
   Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_secret_name_delete


    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
```

```
  Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_secret_name_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_secret_name_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_secret_name_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-secret-name"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf broker-ca-secret-name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: broker-ca-secret-name
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings/broker-ca-external-secret

```
get:

  Tags:
  - data
  - get
 Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_get


  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_put

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret"
      Required/Optional: true

    Responses:
      "201":
        Description: container broker-ca-external-secret created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: broker-ca-external-secret
  Method: Post:

    Tags:
    - data
    - post
   Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_post

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container broker-ca-external-secret created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: broker-ca-external-secret
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_options

    Responses:
      "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_head


  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
     Operation ID: data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_patch

      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret"
        Required/Optional: true

      Responses:
        "204":
          Description: container broker-ca-external-secret updated
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: broker-ca-external-secret
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings/broker-ca-external-secret/name

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_name_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_name_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_name"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_name_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
```

```
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_name_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_name_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_name_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_name"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf name updated
        Content: {}
      "400":
        Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings/broker-ca-external-secret/namespace

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_namespace_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_namespace"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_namespace_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_namespace"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf namespace created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: namespace
delete:

  Tags:
```

```
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_namespace_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_namespace_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_namespace_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: integer
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_namespace_patch
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_namespace"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf namespace updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: namespace
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings/broker-ca-external-secret/target-secre

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_target_secret_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_target-secret"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_target_secret_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_target-secret"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf target-secret created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
```

```
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: target-secret
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_target_secret_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_target_secret_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_target_secret_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_target_secret_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_target-secret"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf target-secret updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: target-secret
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings/broker-ca-external-secret/remote-key-pa

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_remote_key_path_get

    Parameters:
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_remote-key-path"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_remote_key_path_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_remote-key-path"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf remote-key-path created or replaced
        Content: {}
      "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: remote-key-path
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_remote_key_path_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_remote_key_path_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
```

```
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_remote_key_path_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_remote_key_path_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_remote-key-path"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf remote-key-path updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remote-key-path
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings/broker-ca-external-secret/refresh-interva

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_refresh_interval_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_refresh-interval"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_refresh_interval_put
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_refresh-interval"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf refresh-interval created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: refresh-interval
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_refresh_interval_delete


    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_refresh_interval_options
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_refresh_interval_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_refresh_interval_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_refresh-interval"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf refresh-interval updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: refresh-interval
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings/broker-ca-external-secret/secret-store

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store"

    Required/Optional: true

  Responses:
    "201":
      Description: container secret-store created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-store
Method: Post:

  Tags:
  - data
  - post
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_post
  Request Body:
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container secret-store created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-store
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_options
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store"

      Required/Optional: true

    Responses:
      "204":
        Description: container secret-store updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-store
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings/broker-ca-external-secret/secret-store

```
  get:

    Tags:
    - data
    - get
    Summary: Overrides common secret store name
    Description: Overrides common secret store name
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_name_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: Overrides common secret store name
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store_name"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Summary: Overrides common secret store name
  Description: Overrides common secret store name
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_name_put
  Request Body:
    Description: Overrides common secret store name
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store_name"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf name created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
delete:

  Tags:
  - data
  - delete
```

```
    Summary: Overrides common secret store name
    Description: Overrides common secret store name
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_name_delete


    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Summary: Overrides common secret store name
    Description: Overrides common secret store name
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_name_options


    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Summary: Overrides common secret store name
    Description: Overrides common secret store name
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_name_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
```

```
    Summary: Overrides common secret store name
    Description: Overrides common secret store name
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_name_patch

    Request Body:
      Description: Overrides common secret store name
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store_name"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings/broker-ca-external-secret/secret-store/k

```
  get:

    Tags:
    - data
    - get
    Summary: Overrides common secret store kind
    Description: Overrides common secret store kind
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_kind_get

    Parameters:
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: Overrides common secret store kind
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store_kind"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Summary: Overrides common secret store kind
    Description: Overrides common secret store kind
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_kind_put
    Request Body:
      Description: Overrides common secret store kind
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store_kind"

      Required/Optional: true

    Responses:
      "201":
```

```
      Description: leaf kind created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: kind
delete:

  Tags:
  - data
  - delete
  Summary: Overrides common secret store kind
  Description: Overrides common secret store kind
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_kind_delete


  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Summary: Overrides common secret store kind
  Description: Overrides common secret store kind
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_kind_options


  Responses:
    "200":
      Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Summary: Overrides common secret store kind
    Description: Overrides common secret store kind
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_kind_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Summary: Overrides common secret store kind
    Description: Overrides common secret store kind
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_kind_patch

    Request Body:
      Description: Overrides common secret store kind
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store_kind"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf kind updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: kind
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings/broker-ca-external-secret/secret-store/n

```
get:

  Tags:
  - data
  - get
  Summary: Overrides common secret store namespace
  Description: Overrides common secret store namespace
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_namespace_get


  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: Overrides common secret store namespace
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store_namespace"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_namespace_put

    Request Body:
      Description: Overrides common secret store namespace
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store_namespace"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf namespace created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: namespace
```

```
  delete:

    Tags:
    - data
    - delete
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_namespace_delete


    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_namespace_options


    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_namespace_head


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
```

```
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_secret_store_namespace_patch

    Request Body:
      Description: Overrides common secret store namespace
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store_namespace"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf namespace updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: namespace
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings/broker-ca-external-secret/data

```
  options:

    Tags:
    - data
    - options
    Operation ID:
```

```
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings/broker-ca-external-secret/data={data-se

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_get


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
```

```
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_put


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key"

      Required/Optional: true

    Responses:
      "201":
        Description: list data created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: data
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_delete


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
```

```
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_options


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_head


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
 patch:

  Tags:
  - data
  - patch
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_patch


  Parameters:
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key"

    Required/Optional: true

  Responses:
    "204":
      Description: list data updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: data
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings/broker-ca-external-secret/data={data-s

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_secret_key_get


  Parameters:
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_secret-key"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_secret_key_put


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_secret-key"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf secret-key created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-key
```

```
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_secret_key_delete


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_secret_key_options


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_secret_key_head

Parameters:
- **Name**: data-secret-key
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_secret_key_patch


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_secret-key"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf secret-key updated
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-key
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings/broker-ca-external-secret/data={data-s

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_remote_ref_get


  Parameters:
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_remote-ref"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_remote_ref_put


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_remote-ref"

      Required/Optional: true

    Responses:
      "201":
        Description: container remote-ref created or replaced
        Content: {}
      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: remote-ref
Method: Post:

  Tags:
  - data
  - post
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_remote_ref_post


  Parameters:
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_remote-ref-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container remote-ref created
      Content: {}
    "204":
      Description: No Content
      Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remote-ref
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_remote_ref_delete


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_remote_ref_options


    Parameters:
    - Name: data-secret-key
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_remote_ref_head


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: integer
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_remote_ref_patch


      Parameters:
      - Name: data-secret-key
        In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_remote-ref"

      Required/Optional: true

    Responses:
      "204":
        Description: container remote-ref updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remote-ref
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings/broker-ca-external-secret/data={data-se

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_remote_ref_key_get


    Parameters:
    - Name: data-secret-key
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_remote-ref_key"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_remote_ref_key_put


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_remote-ref_key"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf key created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_remote_ref_key_delete


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_remote_ref_key_options


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_remote_ref_key_head


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_remote_ref_key_patch


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_remote-ref_key"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf key updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: key
```

/data/cisco-smi-cdl:cdl/kafka/ssl-settings/broker-ca-external-secret/data={data-s

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_remote_ref_property_get

  Parameters:
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_remote-ref_property"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_remote_ref_property_put


  Parameters:
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_remote-ref_property"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf property created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: property
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_remote_ref_property_delete


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_remote_ref_property_options


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
```

```
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_remote_ref_property_head


  Parameters:
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_ssl_settings_broker_ca_external_secret_data_data_secret_key_remote_ref_property_patch


    Parameters:
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_remote-ref_property"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: leaf property updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: property
```

/data/cisco-smi-cdl:cdl/kafka/retention-time

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_retention_time_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_retention-time"

  "204":
    Description: No Content
    Content: {}
  "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_kafka_retention_time_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_retention-time"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf retention-time created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: retention-time
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_retention_time_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_retention_time_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_retention_time_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_kafka_retention_time_patch
  Request Body:
```

```
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_retention-time"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf retention-time updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: retention-time
```

/data/cisco-smi-cdl:cdl/kafka/retention-size

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_retention_size_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_retention-size"
```

```
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_kafka_retention_size_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_retention-size"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf retention-size created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: retention-size
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_retention_size_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_retention_size_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_retention_size_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
```

```
- data
- patch
Operation ID: data_cisco_smi_cdl_cdl_kafka_retention_size_patch
Request Body:
  Content:
    application/yang-data+json:
      Schema:
       Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_retention-size"

  Required/Optional: true

Responses:
  "204":
    Description: leaf retention-size updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: retention-size
```

/data/cisco-smi-cdl:cdl/kafka/log-compaction

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_log_compaction_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_log-compaction"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_kafka_log_compaction_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_log-compaction"

    Required/Optional: true

  Responses:
    "201":
      Description: container log-compaction created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: log-compaction
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_cdl_cdl_kafka_log_compaction_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_log-compaction-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container log-compaction created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: log-compaction
delete:

  Tags:
  - data
```

```
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_log_compaction_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_log_compaction_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_log_compaction_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_log_compaction_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_log-compaction"

      Required/Optional: true
```

```
Responses:
  "204":
    Description: container log-compaction updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: log-compaction
```

/data/cisco-smi-cdl:cdl/kafka/log-compaction/disable

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_log_compaction_disable_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_log-compaction_disable"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_log_compaction_disable_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_log-compaction_disable"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf disable created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
  x-codegen-request-body-name: disable
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_log_compaction_disable_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_log_compaction_disable_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_log_compaction_disable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_kafka_log_compaction_disable_patch
  Request Body:
    Content:
      application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_log-compaction_disable"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf disable updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: disable
```

/data/cisco-smi-cdl:cdl/kafka/log-compaction/delete-retention-ms

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_log_compaction_delete_retention_ms_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_log-compaction_delete-retention-ms"
    "204":
      Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_kafka_log_compaction_delete_retention_ms_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_log-compaction_delete-retention-ms"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf delete-retention-ms created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: delete-retention-ms
delete:

  Tags:
  - data
  - delete
 Operation ID: data_cisco_smi_cdl_cdl_kafka_log_compaction_delete_retention_ms_delete


  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_kafka_log_compaction_delete_retention_ms_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_log_compaction_delete_retention_ms_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
```

```
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_log_compaction_delete_retention_ms_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_log-compaction_delete-retention-ms"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf delete-retention-ms updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: delete-retention-ms
```

/data/cisco-smi-cdl:cdl/kafka/disable-unclean-leader-election

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_kafka_disable_unclean_leader_election_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_disable-unclean-leader-election"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_disable_unclean_leader_election_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_disable-unclean-leader-election"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf disable-unclean-leader-election created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: disable-unclean-leader-election
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_disable_unclean_leader_election_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_disable_unclean_leader_election_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_disable_unclean_leader_election_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_disable_unclean_leader_election_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_disable-unclean-leader-election"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf disable-unclean-leader-election updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: disable-unclean-leader-election
```

/data/cisco-smi-cdl:cdl/kafka/label-config

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_kafka_label_config_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_label-config"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_kafka_label_config_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_label-config"
    Required/Optional: true

  Responses:
    "201":
      Description: container label-config created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: label-config
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_cdl_cdl_kafka_label_config_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_label-config-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container label-config created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: label-config
```

```
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_label_config_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_label_config_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_label_config_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_label_config_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_label-config"
      Required/Optional: true

    Responses:
      "204":
        Description: container label-config updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: label-config
```

/data/cisco-smi-cdl:cdl/kafka/label-config/key

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_label_config_key_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_label-config_key"
    "204":
      Description: No Content
      Content: {}
    "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_kafka_label_config_key_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_label-config_key"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf key created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: key
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_label_config_key_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_label_config_key_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_label_config_key_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_label_config_key_patch
    Request Body:
```

```
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_label-config_key"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf key updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: key
```

/data/cisco-smi-cdl:cdl/kafka/label-config/value

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_label_config_value_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

```
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_label-config_value"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_label_config_value_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_label-config_value"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf value created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: value
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_label_config_value_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_label_config_value_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_label_config_value_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
```

```
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_label_config_value_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_label-config_value"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf value updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: value
```

/data/cisco-smi-cdl:cdl/kafka/controller

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller"
      Required/Optional: true

    Responses:
      "201":
        Description: container controller created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: controller
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container controller created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: controller
delete:

  Tags:
  - data
  - delete
```

```
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller"
      Required/Optional: true

    Responses:
      "204":
```

```
      Description: container controller updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: controller
```

/data/cisco-smi-cdl:cdl/kafka/controller/replica

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_replica_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_replica"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_replica_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_replica"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf replica created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replica
delete:
```

```
  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_replica_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_replica_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_replica_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_replica_patch
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_replica"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: leaf replica updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replica
```

/data/cisco-smi-cdl:cdl/kafka/controller/log-level

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_log_level_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_log-level"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_log_level_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_log-level"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf log-level created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: log-level
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_log_level_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_log_level_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_log_level_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_log_level_patch
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_log-level"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf log-level updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: log-level
```

/data/cisco-smi-cdl:cdl/kafka/controller/heap-options

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_heap_options_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
```

```
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_heap-options"
    "204":
```

```
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_heap_options_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_heap-options"
      Required/Optional: true

    Responses:
      "201":
        Description: container heap-options created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: heap-options
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_heap_options_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_heap-options-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container heap-options created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: heap-options
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_heap_options_delete

    Responses:
```

```
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_heap_options_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_heap_options_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_heap_options_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_heap-options"
      Required/Optional: true

    Responses:
      "204":
        Description: container heap-options updated
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: heap-options
```

/data/cisco-smi-cdl:cdl/kafka/controller/heap-options/min-heap-size-mb

```
get:

  Tags:
  - data
  - get
 Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_heap_options_min_heap_size_mb_get


  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_heap-options_min-heap-size-mb"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_heap_options_min_heap_size_mb_put

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_heap-options_min-heap-size-mb"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf min-heap-size-mb created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: min-heap-size-mb
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_controller_heap_options_min_heap_size_mb_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_controller_heap_options_min_heap_size_mb_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_controller_heap_options_min_heap_size_mb_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_controller_heap_options_min_heap_size_mb_patch
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_heap-options_min-heap-size-mb"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf min-heap-size-mb updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: min-heap-size-mb
```

/data/cisco-smi-cdl:cdl/kafka/controller/heap-options/max-heap-size-mb

```
  get:

    Tags:
    - data
    - get
   Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_heap_options_max_heap_size_mb_get


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

```
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_heap-options_max-heap-size-mb"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_heap_options_max_heap_size_mb_put

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_heap-options_max-heap-size-mb"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf max-heap-size-mb created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: max-heap-size-mb
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_controller_heap_options_max_heap_size_mb_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_controller_heap_options_max_heap_size_mb_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_kafka_controller_heap_options_max_heap_size_mb_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_kafka_controller_heap_options_max_heap_size_mb_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_heap-options_max-heap-size-mb"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf max-heap-size-mb updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: max-heap-size-mb
```

/data/cisco-smi-cdl:cdl/kafka/controller/resource

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_get

    Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_resource"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_resource"
      Required/Optional: true

    Responses:
      "201":
        Description: container resource created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: resource
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_resource-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container resource created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: resource
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
```

```
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_resource"
      Required/Optional: true

    Responses:
      "204":
        Description: container resource updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: resource
```

/data/cisco-smi-cdl:cdl/kafka/controller/resource/cpu-request

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_cpu_request_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_resource_cpu-request"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_cpu_request_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_resource_cpu-request"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf cpu-request created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cpu-request
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_cpu_request_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_cpu_request_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_cpu_request_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_cpu_request_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_resource_cpu-request"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf cpu-request updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu-request
```

/data/cisco-smi-cdl:cdl/kafka/controller/resource/cpu-limit

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_cpu_limit_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_resource_cpu-limit"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_cpu_limit_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_resource_cpu-limit"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf cpu-limit created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cpu-limit
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_cpu_limit_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_cpu_limit_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_cpu_limit_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_cpu_limit_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_resource_cpu-limit"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf cpu-limit updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu-limit
```

/data/cisco-smi-cdl:cdl/kafka/controller/resource/memory-request

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_memory_request_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_resource_memory-request"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_memory_request_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_resource_memory-request"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf memory-request created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory-request
delete:

  Tags:
  - data
  - delete
 Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_memory_request_delete


  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_memory_request_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_memory_request_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_memory_request_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_resource_memory-request"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf memory-request updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: memory-request
```

/data/cisco-smi-cdl:cdl/kafka/controller/resource/memory-limit

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_memory_limit_get
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_resource_memory-limit"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_memory_limit_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_resource_memory-limit"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf memory-limit created or replaced
        Content: {}
      "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory-limit
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_memory_limit_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_memory_limit_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_memory_limit_head

  Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID: data_cisco_smi_cdl_cdl_kafka_controller_resource_memory_limit_patch
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_resource_memory-limit"
        Required/Optional: true

      Responses:
        "204":
          Description: leaf memory-limit updated
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
      x-codegen-request-body-name: memory-limit
```

/data/cisco-smi-cdl:cdl/kafka/enable-parallel-pod-management

```
    get:
```

```
Tags:
- data
- get
Operation ID: data_cisco_smi_cdl_cdl_kafka_enable_parallel_pod_management_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_enable-parallel-pod-management"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_enable_parallel_pod_management_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_enable-parallel-pod-management"
      Required/Optional: true

    Responses:
      "201":
```

```
      Description: leaf enable-parallel-pod-management created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable-parallel-pod-management
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_enable_parallel_pod_management_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_enable_parallel_pod_management_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
```

Operation ID: data_cisco_smi_cdl_cdl_kafka_enable_parallel_pod_management_head

Parameters:
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_enable_parallel_pod_management_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_enable-parallel-pod-management"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf enable-parallel-pod-management updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable-parallel-pod-management
```

/data/cisco-smi-cdl:cdl/kafka/heap-options

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_heap_options_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_heap-options"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_kafka_heap_options_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
```

```
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_heap-options"
      Required/Optional: true

    Responses:
      "201":
        Description: container heap-options created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: heap-options
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_cdl_cdl_kafka_heap_options_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_heap-options-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container heap-options created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: heap-options
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_heap_options_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_heap_options_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_heap_options_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_kafka_heap_options_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_heap-options"
    Required/Optional: true

  Responses:
    "204":
      Description: container heap-options updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: heap-options
```

/data/cisco-smi-cdl:cdl/kafka/heap-options/min-heap-size-mb

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_heap_options_min_heap_size_mb_get

  Parameters:
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_heap-options_min-heap-size-mb"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_heap_options_min_heap_size_mb_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_heap-options_min-heap-size-mb"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf min-heap-size-mb created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: min-heap-size-mb
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_heap_options_min_heap_size_mb_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_heap_options_min_heap_size_mb_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_heap_options_min_heap_size_mb_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_heap_options_min_heap_size_mb_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_heap-options_min-heap-size-mb"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf min-heap-size-mb updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: min-heap-size-mb
```

/data/cisco-smi-cdl:cdl/kafka/heap-options/max-heap-size-mb

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_kafka_heap_options_max_heap_size_mb_get
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_heap-options_max-heap-size-mb"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_heap_options_max_heap_size_mb_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_heap-options_max-heap-size-mb"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf max-heap-size-mb created or replaced
        Content: {}
      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: max-heap-size-mb
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_heap_options_max_heap_size_mb_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_heap_options_max_heap_size_mb_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_heap_options_max_heap_size_mb_head

  Parameters:
  - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_heap_options_max_heap_size_mb_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_heap-options_max-heap-size-mb"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf max-heap-size-mb updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: max-heap-size-mb
```

/data/cisco-smi-cdl:cdl/kafka/describe

```
  get:

    Tags:
```

```
- data
- get
Operation ID: data_cisco_smi_cdl_cdl_kafka_describe_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_describe"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_kafka_describe_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_describe"
    Required/Optional: true

  Responses:
    "201":
      Description: container describe created or replaced
      Content: {}
```

```
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: describe
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_cdl_cdl_kafka_describe_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_describe-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container describe created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: describe
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_kafka_describe_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_describe_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_describe_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
      - nonconfig
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:
```

```
  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_kafka_describe_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_describe"
    Required/Optional: true

  Responses:
    "204":
      Description: container describe updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: describe
```

/data/cisco-smi-cdl:cdl/kafka/list

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_list_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_list"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_kafka_list_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_list"
    Required/Optional: true

  Responses:
    "201":
      Description: container list created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: list
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_cdl_cdl_kafka_list_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_list-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container list created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: list
delete:

  Tags:
  - data
  - delete
```

```
  Operation ID: data_cisco_smi_cdl_cdl_kafka_list_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_list_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_list_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_kafka_list_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_list"
    Required/Optional: true

  Responses:
    "204":
```

```
    Description: container list updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: list
```

/data/cisco-smi-cdl:cdl/kafka/reset-offsets

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_reset_offsets_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_reset-offsets"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_kafka_reset_offsets_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_reset-offsets"

    Required/Optional: true

  Responses:
    "201":
      Description: container reset-offsets created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: reset-offsets
Method: Post:
```

```
    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_cdl_cdl_kafka_reset_offsets_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_reset-offsets-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container reset-offsets created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: reset-offsets
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_kafka_reset_offsets_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
```

```
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_kafka_reset_offsets_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_reset_offsets_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_kafka_reset_offsets_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_reset-offsets"

    Required/Optional: true

  Responses:
    "204":
      Description: container reset-offsets updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: reset-offsets
```

/data/cisco-smi-cdl:cdl/kafka/reset-offsets-dry-run

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_kafka_reset_offsets_dry_run_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_reset-offsets-dry-run"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_kafka_reset_offsets_dry_run_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_reset-offsets-dry-run"
      Required/Optional: true

    Responses:
      "201":
        Description: container reset-offsets-dry-run created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: reset-offsets-dry-run
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_cdl_cdl_kafka_reset_offsets_dry_run_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

```
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_reset-offsets-dry-run-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container reset-offsets-dry-run created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: reset-offsets-dry-run
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_kafka_reset_offsets_dry_run_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_cisco_smi_cdl_cdl_kafka_reset_offsets_dry_run_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
```

```
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_kafka_reset_offsets_dry_run_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_kafka_reset_offsets_dry_run_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_reset-offsets-dry-run"
      Required/Optional: true

    Responses:
      "204":
        Description: container reset-offsets-dry-run updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: reset-offsets-dry-run
```

/data/cisco-smi-cdl:cdl/mirror-maker

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_put
    Request Body:
```

```
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker"
    Required/Optional: true

  Responses:
    "201":
      Description: container mirror-maker created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: mirror-maker
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container mirror-maker created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: mirror-maker
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker"
    Required/Optional: true

  Responses:
    "204":
      Description: container mirror-maker updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: mirror-maker
```

/data/cisco-smi-cdl:cdl/mirror-maker/log-level

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_log_level_get
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_log-level"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_log_level_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_log-level"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf log-level created or replaced
        Content: {}
      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: log-level
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_log_level_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_log_level_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_log_level_head

  Parameters:
  - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_log_level_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_log-level"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf log-level updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: log-level
```

/data/cisco-smi-cdl:cdl/mirror-maker/enable-JMX-metrics

```
get:

  Tags:
```

```
- data
- get
Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_enable_JMX_metrics_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_enable-JMX-metrics"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_enable_JMX_metrics_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_enable-JMX-metrics"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf enable-JMX-metrics created or replaced
```

```
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable-JMX-metrics
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_enable_JMX_metrics_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_enable_JMX_metrics_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_enable_JMX_metrics_head
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_enable_JMX_metrics_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_enable-JMX-metrics"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf enable-JMX-metrics updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable-JMX-metrics
```

/data/cisco-smi-cdl:cdl/mirror-maker/ssl

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_ssl_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_ssl_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: container ssl created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ssl
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_ssl_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container ssl created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ssl
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_ssl_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_ssl_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_ssl_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_ssl_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl"
    Required/Optional: true

  Responses:
    "204":
      Description: container ssl updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ssl
```

/data/cisco-smi-cdl:cdl/mirror-maker/ssl/broker-ca-secret-names

```
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_secret_names_options


  Responses:
    "200":
      Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/mirror-maker/ssl/broker-ca-secret-names={broker-ca-sec

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_secret_names_broker_ca_secret_names_id_get


  Parameters:
  - Name: broker-ca-secret-names-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-secret-names_broker-ca-secret-names-id"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_secret_names_broker_ca_secret_names_id_put


    Parameters:
    - Name: broker-ca-secret-names-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-secret-names_broker-ca-secret-names-id"
```

```
      Required/Optional: true

    Responses:
      "201":
        Description: leaf-list broker-ca-secret-names created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: broker-ca-secret-names
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_secret_names_broker_ca_secret_names_id_delete


    Parameters:
    - Name: broker-ca-secret-names-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_secret_names_broker_ca_secret_names_id_options


    Parameters:
    - Name: broker-ca-secret-names-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_secret_names_broker_ca_secret_names_id_head


    Parameters:
    - Name: broker-ca-secret-names-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
      - nonconfig
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_secret_names_broker_ca_secret_names_id_patch


    Parameters:
    - Name: broker-ca-secret-names-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-secret-names_broker-ca-secret-names-id"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf-list broker-ca-secret-names updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: broker-ca-secret-names
```

/data/cisco-smi-cdl:cdl/mirror-maker/ssl/broker-ca-external-secrets

```
  options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/cisco-smi-cdl:cdl/mirror-maker/ssl/broker-ca-external-secrets={broker-ca-ex

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_get


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_put


  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name"

      Required/Optional: true

    Responses:
      "201":
        Description: list broker-ca-external-secrets created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: broker-ca-external-secrets
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_delete


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_options


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_head


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_patch


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name"

      Required/Optional: true

    Responses:
      "204":
        Description: list broker-ca-external-secrets updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: broker-ca-external-secrets
```

/data/cisco-smi-cdl:cdl/mirror-maker/ssl/broker-ca-external-secrets={broker-ca-

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_name_get

  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_name"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_name_put


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_name"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_name_delete


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_name_options


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

```
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_name_head


  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_name_patch


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_name"

      Required/Optional: true
```

```
  Responses:
    "204":
      Description: leaf name updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
```

/data/cisco-smi-cdl:cdl/mirror-maker/ssl/broker-ca-external-secrets={broker-ca-

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_namespace_get

  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_namespace"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_namespace_put


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_namespace"

      Required/Optional: true

    Responses:
```

```
      "201":
        Description: leaf namespace created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: namespace
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_namespace_delete


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
```

```
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_namespace_options

    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_namespace_head

    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
```

```
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_namespace_patch

    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_namespace"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf namespace updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: namespace
```

/data/cisco-smi-cdl:cdl/mirror-maker/ssl/broker-ca-external-secrets={broker-ca-

```
  get:

    Tags:
    - data
    - get
```

Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_target_secret_get

Parameters:
- **Name**: broker-ca-external-secrets-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_target-secret"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_target_secret_put
```

```
    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_target-secret"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf target-secret created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: target-secret
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_target_secret_delete
```

```
    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_target_secret_options


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_target_secret_head


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_target_secret_patch


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_target-secret"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf target-secret updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: target-secret
```

/data/cisco-smi-cdl:cdl/mirror-maker/ssl/broker-ca-external-secrets={broker-ca-ex

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_remote_key_path_get

  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_remote-key-path"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_remote_key_path_put


  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_remote-key-path"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf remote-key-path created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: remote-key-path
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_remote_key_path_delete


  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_remote_key_path_options


  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
 head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_remote_key_path_head


  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_remote_key_path_patch


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_remote-key-path"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf remote-key-path updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: remote-key-path
```

/data/cisco-smi-cdl:cdl/mirror-maker/ssl/broker-ca-external-secrets={broker-ca-ex

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_refresh_interval_get


  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_refresh-interval"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_refresh_interval_put


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_refresh-interval"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf refresh-interval created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: refresh-interval
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_refresh_interval_delete


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_refresh_interval_options


  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_refresh_interval_head


  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_refresh_interval_patch


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_refresh-interval"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf refresh-interval updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: refresh-interval
```

/data/cisco-smi-cdl:cdl/mirror-maker/ssl/broker-ca-external-secrets={broker-ca-

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_get


  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store"

  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_put


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store"

      Required/Optional: true

    Responses:
      "201":
        Description: container secret-store created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-store
```

```
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_post


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container secret-store created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-store
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_delete

    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_options

    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
```

data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_head

```
Parameters:
- Name: broker-ca-external-secrets-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_patch


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store"

      Required/Optional: true

    Responses:
      "204":
        Description: container secret-store updated
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-store
```

/data/cisco-smi-cdl:cdl/mirror-maker/ssl/broker-ca-external-secrets={broker-ca-ex

```
get:

  Tags:
  - data
  - get
  Summary: Overrides common secret store name
  Description: Overrides common secret store name
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_name_get

  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: Overrides common secret store name
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store_name"

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Summary: Overrides common secret store name
    Description: Overrides common secret store name
    Operation ID:
```

data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_name_put

```
    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Description: Overrides common secret store name
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store_name"

```
      Required/Optional: true

    Responses:
      "201":
```

```
      Description: leaf name created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: name
delete:

  Tags:
  - data
  - delete
  Summary: Overrides common secret store name
  Description: Overrides common secret store name
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_name_delete


  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
```

```
    - data
    - options
    Summary: Overrides common secret store name
    Description: Overrides common secret store name
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_name_options

    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Summary: Overrides common secret store name
    Description: Overrides common secret store name
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_name_head

    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Summary: Overrides common secret store name
    Description: Overrides common secret store name
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_name_patch


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Description: Overrides common secret store name
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store_name"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
```

/data/cisco-smi-cdl:cdl/mirror-maker/ssl/broker-ca-external-secrets={broker-ca-

```
get:

  Tags:
  - data
  - get
  Summary: Overrides common secret store kind
  Description: Overrides common secret store kind
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_kind_get


  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: Overrides common secret store kind
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store_kind"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Summary: Overrides common secret store kind
    Description: Overrides common secret store kind
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_kind_put


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Description: Overrides common secret store kind
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store_kind"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf kind created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: kind
delete:

  Tags:
  - data
  - delete
  Summary: Overrides common secret store kind
  Description: Overrides common secret store kind
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_kind_delete


  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Summary: Overrides common secret store kind
  Description: Overrides common secret store kind
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_kind_options


  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
```

```
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Summary: Overrides common secret store kind
  Description: Overrides common secret store kind
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_kind_head

  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Summary: Overrides common secret store kind
  Description: Overrides common secret store kind
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_kind_patch


  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string
    Request Body:
      Description: Overrides common secret store kind
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store_kind"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf kind updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: kind
```

/data/cisco-smi-cdl:cdl/mirror-maker/ssl/broker-ca-external-secrets={broker-ca-

```
  get:

    Tags:
    - data
    - get
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_namespace_get

    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: Overrides common secret store namespace
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store_namespace"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_namespace_put


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Description: Overrides common secret store namespace
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store_namespace"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf namespace created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: namespace
  delete:

    Tags:
    - data
    - delete
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_namespace_delete


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_namespace_options


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_namespace_head


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Summary: Overrides common secret store namespace
    Description: Overrides common secret store namespace
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_secret_store_namespace_patch


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Description: Overrides common secret store namespace
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store_namespace"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf namespace updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: namespace
```

/data/cisco-smi-cdl:cdl/mirror-maker/ssl/broker-ca-external-secrets={broker-ca-ex

```
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_options


  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/mirror-maker/ssl/broker-ca-external-secrets={broker-ca-ex

```
get:

  Tags:
  - data
  - get
```

Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_get

Parameters:
- **Name**: broker-ca-external-secrets-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: data-secret-key
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string

```
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key"

  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_put


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key"

      Required/Optional: true

    Responses:
      "201":
        Description: list data created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: data
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_delete


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: data-secret-key
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_options


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_head
```

```
Parameters:
- Name: broker-ca-external-secrets-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: data-secret-key
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_patch


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key"

    Required/Optional: true

  Responses:
    "204":
      Description: list data updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: data
```

/data/cisco-smi-cdl:cdl/mirror-maker/ssl/broker-ca-external-secrets={broker-ca-ex

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_secret_key_get

  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
- Name: data-secret-key
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_secret-key"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_secret_key_put


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_secret-key"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf secret-key created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-key
  delete:

    Tags:
    - data
    - delete
```

```
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_secret_key_delete

    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_secret_key_options

    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_secret_key_head


  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_secret_key_patch


    Parameters:
```

```
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_secret-key"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf secret-key updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-key
```

/data/cisco-smi-cdl:cdl/mirror-maker/ssl/broker-ca-external-secrets={broker-ca-

```
  get:
```

Tags:
- data
- get

Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_remote_ref_get

Parameters:
- **Name**: broker-ca-external-secrets-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: data-secret-key
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form

```
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_remote-ref"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_remote_ref_put


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_remote-ref"

      Required/Optional: true

    Responses:
      "201":
        Description: container remote-ref created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: remote-ref
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_remote_ref_post


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_remote-ref-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container remote-ref created
        Content: {}
      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: remote-ref
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_remote_ref_delete


  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_remote_ref_options


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_remote_ref_head


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_remote_ref_patch


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_remote-ref"

      Required/Optional: true

    Responses:
      "204":
        Description: container remote-ref updated
        Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: remote-ref
```

/data/cisco-smi-cdl:cdl/mirror-maker/ssl/broker-ca-external-secrets={broker-ca-ex

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_remote_ref_key_get

  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_remote-ref_key"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_remote_ref_key_put


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_remote-ref_key"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf key created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: key
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_remote_ref_key_delete

  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
      Format: string
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_remote_ref_key_options


  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
```

Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_remote_ref_key_head

Parameters:
- **Name**: broker-ca-external-secrets-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: data-secret-key
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_remote_ref_key_patch


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_remote-ref_key"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf key updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key
```

/data/cisco-smi-cdl:cdl/mirror-maker/ssl/broker-ca-external-secrets={broker-ca-

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_remote_ref_property_get


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: data-secret-key
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_remote-ref_property"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_remote_ref_property_put
```

```
    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_remote-ref_property"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf property created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: property
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_remote_ref_property_delete

    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_remote_ref_property_options

    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_remote_ref_property_head


    Parameters:
    - Name: broker-ca-external-secrets-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: data-secret-key
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
```

data_cisco_smi_cdl_cdl_mirror_maker_ssl_broker_ca_external_secrets_broker_ca_external_secrets_name_data_data_secret_key_remote_ref_property_patch

```
  Parameters:
  - Name: broker-ca-external-secrets-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: data-secret-key
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_remote-ref_property"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf property updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: property
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot"
      Required/Optional: true

    Responses:
      "201":
        Description: container slot created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: slot
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container slot created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: slot
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot"
    Required/Optional: true

  Responses:
    "204":
      Description: container slot updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: slot
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot/replicas

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_replicas_get

  Parameters:
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_replicas"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_replicas_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_replicas"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf replicas created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replicas
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_replicas_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_replicas_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_replicas_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_replicas_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_replicas"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf replicas updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: replicas
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot/replication-factor

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_replication_factor_get
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_replication-factor"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_replication_factor_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_replication-factor"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf replication-factor created or replaced
        Content: {}
      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replication-factor
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_replication_factor_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_replication_factor_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_replication_factor_head

  Parameters:
  - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_replication_factor_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_replication-factor"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf replication-factor updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: replication-factor
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot/settings

```
  get:

    Tags:
```

```
- data
- get
Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings"
      Required/Optional: true

    Responses:
      "201":
        Description: container settings created or replaced
```

```
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: settings
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container settings created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: settings
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings"
      Required/Optional: true

    Responses:
      "204":
        Description: container settings updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: settings
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot/settings/tasks-max

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_tasks_max_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_tasks-max"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_tasks_max_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_tasks-max"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf tasks-max created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tasks-max
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_tasks_max_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_tasks_max_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_tasks_max_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_tasks_max_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_tasks-max"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf tasks-max updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: tasks-max
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot/settings/producer-properties

```
  get:

    Tags:
    - data
    - get
   Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_get


    Parameters:
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
   Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_put

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties"

      Required/Optional: true

    Responses:
      "201":
        Description: container producer-properties created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: producer-properties
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container producer-properties created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: producer-properties
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
      - nonconfig
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties"

      Required/Optional: true

    Responses:
      "204":
        Description: container producer-properties updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: producer-properties
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot/settings/producer-properties/batch-size

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_batch_size_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_batch-size"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_batch_size_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_batch-size"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf batch-size created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: batch-size
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_batch_size_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_batch_size_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_batch_size_head

  Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_batch_size_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_batch-size"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf batch-size updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: batch-size
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot/settings/producer-properties/linger-ms

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_linger_ms_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_linger-ms"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_linger_ms_put
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_linger-ms"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf linger-ms created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: linger-ms
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_linger_ms_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_linger_ms_options
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_linger_ms_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_linger_ms_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_linger-ms"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf linger-ms updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: linger-ms
```


/data/cisco-smi-cdl:cdl/mirror-maker/slot/settings/producer-properties/receive-buff


```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_receive_buffer_bytes_get


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_receive-buffer-bytes"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_receive_buffer_bytes_put

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_receive-buffer-bytes"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf receive-buffer-bytes created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: receive-buffer-bytes
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_receive_buffer_bytes_delete
```

```
    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_receive_buffer_bytes_options


    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_receive_buffer_bytes_head


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_receive_buffer_bytes_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_receive-buffer-bytes"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: leaf receive-buffer-bytes updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: receive-buffer-bytes
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot/settings/producer-properties/send-buff

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_send_buffer_bytes_get


  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_send-buffer-bytes"

      "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_send_buffer_bytes_put

  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_send-buffer-bytes"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf send-buffer-bytes created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: send-buffer-bytes
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_send_buffer_bytes_delete


  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_send_buffer_bytes_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_send_buffer_bytes_head


  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_send_buffer_bytes_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_send-buffer-bytes"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf send-buffer-bytes updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: send-buffer-bytes
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot/settings/producer-properties/max-reques

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_max_request_size_get
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_max-request-size"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_max_request_size_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_max-request-size"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf max-request-size created or replaced
```

```
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: max-request-size
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_max_request_size_delete


  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_max_request_size_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:
```

```
    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_max_request_size_head


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_producer_properties_max_request_size_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_max-request-size"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf max-request-size updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: max-request-size
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot/settings/consumer-properties

```
get:

  Tags:
  - data
  - get
 Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_get


  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
```

```
    - put
   Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_put

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties"

      Required/Optional: true

    Responses:
      "201":
        Description: container consumer-properties created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: consumer-properties
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties-post"

      Required/Optional: true

    Responses:
```

```
      "201":
        Description: container consumer-properties created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: consumer-properties
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:
```

```
    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties"

      Required/Optional: true

    Responses:
      "204":
        Description: container consumer-properties updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: consumer-properties
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot/settings/consumer-properties/receive-buf

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_receive_buffer_bytes_get


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_receive-buffer-bytes"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
```

```
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_receive_buffer_bytes_put

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_receive-buffer-bytes"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf receive-buffer-bytes created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: receive-buffer-bytes
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_receive_buffer_bytes_delete


    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_receive_buffer_bytes_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_receive_buffer_bytes_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: string
        Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_receive_buffer_bytes_patch

      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_receive-buffer-bytes"

        Required/Optional: true

      Responses:
        "204":
          Description: leaf receive-buffer-bytes updated
          Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: receive-buffer-bytes
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot/settings/consumer-properties/send-buf

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_send_buffer_bytes_get


  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_send-buffer-bytes"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_send_buffer_bytes_put

  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_send-buffer-bytes"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf send-buffer-bytes created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
    x-codegen-request-body-name: send-buffer-bytes
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_send_buffer_bytes_delete


    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_send_buffer_bytes_options


    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_send_buffer_bytes_head


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
```

```
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_send_buffer_bytes_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_send-buffer-bytes"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf send-buffer-bytes updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: send-buffer-bytes
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot/settings/consumer-properties/max-poll-re

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_max_poll_records_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_max-poll-records"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_max_poll_records_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_max-poll-records"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf max-poll-records created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: max-poll-records
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_max_poll_records_delete


    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_max_poll_records_options


    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_max_poll_records_head


    Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_max_poll_records_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_max-poll-records"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf max-poll-records updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: max-poll-records
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot/settings/consumer-properties/max-partiti

get:

Tags:
- data
- get

Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_max_partition_fetch_bytes_get

Parameters:
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_max-partition-fetch-bytes"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_max_partition_fetch_bytes_put
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_max-partition-fetch-bytes"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf max-partition-fetch-bytes created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: max-partition-fetch-bytes
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_max_partition_fetch_bytes_delete


    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
```

```
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_max_partition_fetch_bytes_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_max_partition_fetch_bytes_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_settings_consumer_properties_max_partition_fetch_bytes_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_max-partition-fetch-bytes"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf max-partition-fetch-bytes updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: max-partition-fetch-bytes
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot/resource

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_resource"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_resource"
    Required/Optional: true

  Responses:
    "201":
      Description: container resource created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: resource
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_post
  Request Body:
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_resource-post"
       Required/Optional: true

    Responses:
      "201":
        Description: container resource created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: resource
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_options

    Responses:
      "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_resource"
      Required/Optional: true

    Responses:
      "204":
        Description: container resource updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: resource
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot/resource/cpu-request

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_cpu_request_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_cpu-request"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
```

```
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_cpu_request_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_cpu-request"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf cpu-request created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu-request
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_cpu_request_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
```

```
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_cpu_request_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_cpu_request_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_cpu_request_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_cpu-request"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf cpu-request updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cpu-request
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot/resource/cpu-limit

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_cpu_limit_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_cpu-limit"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_cpu_limit_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_cpu-limit"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf cpu-limit created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu-limit
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_cpu_limit_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
```

```
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_cpu_limit_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_cpu_limit_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_cpu_limit_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_cpu-limit"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf cpu-limit updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: cpu-limit
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot/resource/memory-request

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_memory_request_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_memory-request"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_memory_request_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_memory-request"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf memory-request created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: memory-request
  delete:

    Tags:
    - data
    - delete
   Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_memory_request_delete


    Responses:
```

```
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_memory_request_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_memory_request_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_memory_request_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_memory-request"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf memory-request updated
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory-request
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot/resource/memory-limit

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_memory_limit_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: integer
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_memory-limit"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_memory_limit_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_memory-limit"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf memory-limit created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: memory-limit
  delete:

    Tags:
```

```
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_memory_limit_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_memory_limit_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_memory_limit_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_resource_memory_limit_patch
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_memory-limit"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: leaf memory-limit updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory-limit
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot/heap-options

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_heap_options_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_heap-options"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_heap_options_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_heap-options"
    Required/Optional: true

  Responses:
    "201":
      Description: container heap-options created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: heap-options
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_heap_options_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_heap-options-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container heap-options created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: heap-options
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_heap_options_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
```

```
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_heap_options_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_heap_options_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_slot_heap_options_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_heap-options"
      Required/Optional: true

    Responses:
      "204":
        Description: container heap-options updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: heap-options
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot/heap-options/min-heap-size-mb

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_heap_options_min_heap_size_mb_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_heap-options_min-heap-size-mb"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_heap_options_min_heap_size_mb_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_heap-options_min-heap-size-mb"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf min-heap-size-mb created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: min-heap-size-mb
delete:

  Tags:
  - data
  - delete
```

```
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_heap_options_min_heap_size_mb_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_heap_options_min_heap_size_mb_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_heap_options_min_heap_size_mb_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
```

```
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_heap_options_min_heap_size_mb_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

```
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_heap-options_min-heap-size-mb"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf min-heap-size-mb updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: min-heap-size-mb
```

/data/cisco-smi-cdl:cdl/mirror-maker/slot/heap-options/max-heap-size-mb

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_heap_options_max_heap_size_mb_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_heap-options_max-heap-size-mb"

    "204":
```

```
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_heap_options_max_heap_size_mb_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_heap-options_max-heap-size-mb"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf max-heap-size-mb created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: max-heap-size-mb
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_heap_options_max_heap_size_mb_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_heap_options_max_heap_size_mb_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_heap_options_max_heap_size_mb_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_slot_heap_options_max_heap_size_mb_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_heap-options_max-heap-size-mb"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf max-heap-size-mb updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: max-heap-size-mb
```

/data/cisco-smi-cdl:cdl/mirror-maker/index

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index"
    Required/Optional: true

  Responses:
    "201":
      Description: container index created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: index
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container index created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  x-codegen-request-body-name: index
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_patch
    Request Body:
      Content:
        application/yang-data+json:
```

```
      Schema:
        Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index"
    Required/Optional: true

  Responses:
    "204":
      Description: container index updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: index
```

/data/cisco-smi-cdl:cdl/mirror-maker/index/replicas

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_replicas_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_replicas"
      "204":
        Description: No Content
        Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_replicas_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_replicas"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf replicas created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
```

```
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replicas
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_replicas_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_replicas_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_replicas_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_replicas_patch
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_replicas"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf replicas updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: replicas
```

/data/cisco-smi-cdl:cdl/mirror-maker/index/replication-factor

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_replication_factor_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
```

```
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_replication-factor"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_replication_factor_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_replication-factor"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf replication-factor created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replication-factor
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_replication_factor_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_replication_factor_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_replication_factor_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_replication_factor_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_replication-factor"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf replication-factor updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: replication-factor
```

/data/cisco-smi-cdl:cdl/mirror-maker/index/settings

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_settings_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_settings_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings"
      Required/Optional: true

    Responses:
      "201":
        Description: container settings created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: settings
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_settings_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container settings created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: settings
delete:

  Tags:
```

```
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_settings_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_settings_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_settings_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_settings_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings"
      Required/Optional: true
```

```
  Responses:
    "204":
      Description: container settings updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: settings
```

/data/cisco-smi-cdl:cdl/mirror-maker/index/settings/tasks-max

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_settings_tasks_max_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_tasks-max"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_settings_tasks_max_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_tasks-max"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf tasks-max created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
  x-codegen-request-body-name: tasks-max
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_settings_tasks_max_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_settings_tasks_max_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_settings_tasks_max_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_settings_tasks_max_patch
  Request Body:
    Content:
      application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_tasks-max"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf tasks-max updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: tasks-max
```

/data/cisco-smi-cdl:cdl/mirror-maker/index/settings/producer-properties

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties"

      Required/Optional: true

    Responses:
      "201":
        Description: container producer-properties created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: producer-properties
Method: Post:

  Tags:
  - data
  - post
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container producer-properties created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: producer-properties
delete:

  Tags:
  - data
```

```
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
```

```
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_patch
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
```

```
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties"

      Required/Optional: true

    Responses:
      "204":
        Description: container producer-properties updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: producer-properties
```


/data/cisco-smi-cdl:cdl/mirror-maker/index/settings/producer-properties/batch-size


```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_batch_size_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_batch-size"

    "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_batch_size_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_batch-size"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf batch-size created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: batch-size
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_batch_size_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_batch_size_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_batch_size_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_batch_size_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_batch-size"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf batch-size updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: batch-size
```

/data/cisco-smi-cdl:cdl/mirror-maker/index/settings/producer-properties/linger-m

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_linger_ms_get

    Parameters:
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_linger-ms"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_linger_ms_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_linger-ms"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf linger-ms created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: linger-ms
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_linger_ms_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_linger_ms_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_linger_ms_head
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_linger_ms_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_linger-ms"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf linger-ms updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: linger-ms
```

/data/cisco-smi-cdl:cdl/mirror-maker/index/settings/producer-properties/receive-

get:

Tags:
- data
- get

Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_receive_buffer_bytes_get

Parameters:
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_receive-buffer-bytes"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_receive_buffer_bytes_put
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_receive-buffer-bytes"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf receive-buffer-bytes created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: receive-buffer-bytes
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_receive_buffer_bytes_delete


    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
```

```
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_receive_buffer_bytes_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_receive_buffer_bytes_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_receive_buffer_bytes_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_receive-buffer-bytes"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf receive-buffer-bytes updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: receive-buffer-bytes
```

/data/cisco-smi-cdl:cdl/mirror-maker/index/settings/producer-properties/send-buffe

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_send_buffer_bytes_get


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
```

```
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_send-buffer-bytes"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_send_buffer_bytes_put

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_send-buffer-bytes"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf send-buffer-bytes created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: send-buffer-bytes
  delete:

    Tags:
```

```
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_send_buffer_bytes_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_send_buffer_bytes_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_send_buffer_bytes_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_send_buffer_bytes_patch
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_send-buffer-bytes"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf send-buffer-bytes updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: send-buffer-bytes
```

/data/cisco-smi-cdl:cdl/mirror-maker/index/settings/producer-properties/max-req

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_max_request_size_get


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_max-request-size"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_max_request_size_put

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_max-request-size"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf max-request-size created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: max-request-size
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_max_request_size_delete


  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_max_request_size_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_max_request_size_head


  Parameters:
  - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_producer_properties_max_request_size_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_max-request-size"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf max-request-size updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: max-request-size
```

/data/cisco-smi-cdl:cdl/mirror-maker/index/settings/consumer-properties

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_put
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties"

      Required/Optional: true

    Responses:
      "201":
        Description: container consumer-properties created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: consumer-properties
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container consumer-properties created
        Content: {}
      "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: consumer-properties
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
```

```
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties"

      Required/Optional: true

    Responses:
      "204":
        Description: container consumer-properties updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: consumer-properties
```

/data/cisco-smi-cdl:cdl/mirror-maker/index/settings/consumer-properties/receive

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_receive_buffer_bytes_get


  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_receive-buffer-bytes"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_receive_buffer_bytes_put
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_receive-buffer-bytes"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf receive-buffer-bytes created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: receive-buffer-bytes
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_receive_buffer_bytes_delete


    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
```

```
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_receive_buffer_bytes_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_receive_buffer_bytes_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_receive_buffer_bytes_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_receive-buffer-bytes"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf receive-buffer-bytes updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: receive-buffer-bytes
```

/data/cisco-smi-cdl:cdl/mirror-maker/index/settings/consumer-properties/send-buff

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_send_buffer_bytes_get


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
```

```
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_send-buffer-bytes"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_send_buffer_bytes_put

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_send-buffer-bytes"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf send-buffer-bytes created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: send-buffer-bytes
  delete:

    Tags:
```

```
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_send_buffer_bytes_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_send_buffer_bytes_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_send_buffer_bytes_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_send_buffer_bytes_patch
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_send-buffer-bytes"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf send-buffer-bytes updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: send-buffer-bytes
```

/data/cisco-smi-cdl:cdl/mirror-maker/index/settings/consumer-properties/max-po

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_max_poll_records_get


    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_max-poll-records"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_max_poll_records_put

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_max-poll-records"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf max-poll-records created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: max-poll-records
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_max_poll_records_delete


    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_max_poll_records_options


    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_max_poll_records_head


    Parameters:
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_max_poll_records_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_max-poll-records"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf max-poll-records updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: max-poll-records
```

/data/cisco-smi-cdl:cdl/mirror-maker/index/settings/consumer-properties/max-pa

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_max_partition_fetch_bytes_get


  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_max-partition-fetch-bytes"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_max_partition_fetch_bytes_put
```

```
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_max-partition-fetch-bytes"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf max-partition-fetch-bytes created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: max-partition-fetch-bytes
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_max_partition_fetch_bytes_delete


    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
```

```
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_max_partition_fetch_bytes_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_max_partition_fetch_bytes_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
```

```
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_settings_consumer_properties_max_partition_fetch_bytes_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_max-partition-fetch-bytes"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf max-partition-fetch-bytes updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: max-partition-fetch-bytes
```

/data/cisco-smi-cdl:cdl/mirror-maker/index/resource

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_resource"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_resource"
    Required/Optional: true

  Responses:
    "201":
      Description: container resource created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: resource
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_post
  Request Body:
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_resource-post"
       Required/Optional: true

    Responses:
      "201":
        Description: container resource created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: resource
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_options

    Responses:
      "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_resource"
      Required/Optional: true

    Responses:
      "204":
        Description: container resource updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: resource
```

/data/cisco-smi-cdl:cdl/mirror-maker/index/resource/cpu-request

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_cpu_request_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_resource_cpu-request"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
```

```
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_cpu_request_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_resource_cpu-request"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf cpu-request created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu-request
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_cpu_request_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
```

```
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_cpu_request_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_cpu_request_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_cpu_request_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_resource_cpu-request"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf cpu-request updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: cpu-request
```

/data/cisco-smi-cdl:cdl/mirror-maker/index/resource/cpu-limit

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_cpu_limit_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: string
        Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_resource_cpu-limit"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_cpu_limit_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_resource_cpu-limit"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf cpu-limit created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: cpu-limit
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_cpu_limit_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
```

```
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_cpu_limit_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_cpu_limit_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_cpu_limit_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_resource_cpu-limit"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf cpu-limit updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: cpu-limit
```

/data/cisco-smi-cdl:cdl/mirror-maker/index/resource/memory-request

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_memory_request_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_resource_memory-request"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
 put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_memory_request_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_resource_memory-request"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf memory-request created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory-request
 delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_memory_request_delete
```

```
  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_memory_request_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
 Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_memory_request_head


  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_memory_request_patch

    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_resource_memory-request"
      Required/Optional: true

    Responses:
```

```
    "204":
      Description: leaf memory-request updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory-request
```

/data/cisco-smi-cdl:cdl/mirror-maker/index/resource/memory-limit

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_memory_limit_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_resource_memory-limit"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_memory_limit_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_resource_memory-limit"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf memory-limit created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory-limit
```

```
delete:

  Tags:
  - data
  - delete
 Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_memory_limit_delete


  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_memory_limit_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_memory_limit_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_resource_memory_limit_patch
  Request Body:
    Content:
      application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_resource_memory-limit"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf memory-limit updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: memory-limit
```

/data/cisco-smi-cdl:cdl/mirror-maker/index/heap-options

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_heap_options_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_heap-options"
    "204":
      Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_heap_options_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_heap-options"
    Required/Optional: true

  Responses:
    "201":
      Description: container heap-options created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: heap-options
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_heap_options_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_heap-options-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container heap-options created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: heap-options
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_heap_options_delete

  Responses:
    "204":
```

```
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_heap_options_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_heap_options_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_cdl_cdl_mirror_maker_index_heap_options_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_heap-options"
      Required/Optional: true

    Responses:
      "204":
        Description: container heap-options updated
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: heap-options
```

/data/cisco-smi-cdl:cdl/mirror-maker/index/heap-options/min-heap-size-mb

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_heap_options_min_heap_size_mb_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
```

```
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_heap-options_min-heap-size-mb"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_heap_options_min_heap_size_mb_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_heap-options_min-heap-size-mb"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf min-heap-size-mb created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: min-heap-size-mb
delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_heap_options_min_heap_size_mb_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_heap_options_min_heap_size_mb_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_heap_options_min_heap_size_mb_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_heap_options_min_heap_size_mb_patch
    Request Body:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_heap-options_min-heap-size-mb"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf min-heap-size-mb updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: min-heap-size-mb
```

/data/cisco-smi-cdl:cdl/mirror-maker/index/heap-options/max-heap-size-mb

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_heap_options_max_heap_size_mb_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
```

```
      - nonconfig
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_heap-options_max-heap-size-mb"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_heap_options_max_heap_size_mb_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_heap-options_max-heap-size-mb"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf max-heap-size-mb created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: max-heap-size-mb
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_heap_options_max_heap_size_mb_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_heap_options_max_heap_size_mb_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_heap_options_max_heap_size_mb_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_cdl_cdl_mirror_maker_index_heap_options_max_heap_size_mb_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_heap-options_max-heap-size-mb"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf max-heap-size-mb updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: max-heap-size-mb
```

/data/cisco-smi-cdl:cdl/show

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_show_get

    Parameters:
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_show"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_show_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/cisco-smi-cdl:cdl/show/sessions

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_show_sessions_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_show_sessions"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_show_sessions_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/show/sessions/count

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_show_sessions_count_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_show_sessions_count"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:
```

```
Tags:
- data
- head
Operation ID: data_cisco_smi_cdl_cdl_show_sessions_count_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/cisco-smi-cdl:cdl/clear

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_clear_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
```

```
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_clear"
  "204":
    Description: No Content
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_clear_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/cisco-smi-cdl:cdl/actions

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_actions_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_actions"
    "204":
      Description: No Content
      Content: {}
    "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_actions_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/cisco-smi-cdl:cdl/actions/remote-index-sync

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_actions_remote_index_sync_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_actions_remote-index-sync"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID: data_cisco_smi_cdl_cdl_actions_remote_index_sync_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/cisco-smi-cdl:cdl/actions/backup

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_cdl_cdl_actions_backup_get
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
```

```
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_actions_backup"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_actions_backup_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

/data/cisco-smi-cdl:cdl/actions/restore

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_actions_restore_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_actions_restore"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_actions_restore_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-cdl:cdl/network-policy

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_network_policy_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
```

```
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_network-policy"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
```

```
  - data
  - put
  Operation ID: data_cisco_smi_cdl_cdl_network_policy_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_network-policy"
    Required/Optional: true

  Responses:
    "201":
      Description: container network-policy created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: network-policy
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_cdl_cdl_network_policy_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_network-policy-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container network-policy created
      Content: {}
```

```
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: network-policy
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_network_policy_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_network_policy_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_network_policy_head
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_network_policy_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_network-policy"
    Required/Optional: true

  Responses:
    "204":
      Description: container network-policy updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: network-policy
```

/data/cisco-smi-cdl:cdl/network-policy/enable

```
get:
```

```
Tags:
- data
- get
Operation ID: data_cisco_smi_cdl_cdl_network_policy_enable_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_network-policy_enable"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_cdl_cdl_network_policy_enable_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_network-policy_enable"

      Required/Optional: true

    Responses:
      "201":
```

```
      Description: leaf enable created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_cdl_cdl_network_policy_enable_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_cdl_cdl_network_policy_enable_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
```

```
Operation ID: data_cisco_smi_cdl_cdl_network_policy_enable_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_cdl_cdl_network_policy_enable_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_network-policy_enable"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf enable updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
```

/data/cisco-smi-cdl:cdl/rebalance-index

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_cdl_cdl_rebalance_index_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_rebalance-index"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_cdl_cdl_rebalance_index_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```


Components


```
 schemas:
   data:
     Type: object
     Properties:
       ietf-restconf:data:
         Type: object
         Properties: {}
        Description: This resource represents the combined configuration and state data
resources that can be
          accessed by a client and cannot be created or deleted by the client. See RESTCONF
RFC 8040
           for further information.
         x-yang:
           Type: datastore
   data-post:
     Type: object
     Properties:
       cisco-smi-cdl:feature-gates:
         Reference: "#/components/schemas/datapost_ciscosmicdlfeaturegates"
       cisco-smi-cdl:cdl:
         Reference: "#/components/schemas/datapost_ciscosmicdlcdl"
   data-put-patch:
     Type: object
     Properties:
       ietf-restconf:data:
         Reference: "#/components/schemas/dataputpatch_ietfrestconfdata"
   data_cisco-smi-cdl_cdl:
     Type: object
     Properties:
       cisco-smi-cdl:cdl:
         Reference: "#/components/schemas/datapost_ciscosmicdlcdl"
   data_cisco-smi-cdl_cdl-post:
     Type: object
     Properties:
       cisco-smi-cdl:repository:
         Type: string
         Description: (leaf)
         Format: leafref
         x-yang:
```

```
    Type: leaf
cisco-smi-cdl:system-id:
  Type: integer
  Description: (leaf)
  Format: uint32
  x-yang:
    Type: leaf
cisco-smi-cdl:node-type:
  Type: string
  Description: (leaf)
  Format: string
  x-yang:
    Type: leaf
cisco-smi-cdl:enable-geo-replication:
  Type: boolean
  Description: (leaf)
  x-yang:
    Type: leaf
cisco-smi-cdl:use-rust-image:
  Type: boolean
  Description: (leaf)
  x-yang:
    Type: leaf
cisco-smi-cdl:deployment-model:
  Type: string
  Description: (leaf)
  Format: enumeration
  Default: large
  enum:
  - large
  - small
  x-yang:
    Type: leaf
cisco-smi-cdl:api:
  Reference: "#/components/schemas/datapost_ciscosmicdlcdl_api"
cisco-smi-cdl:advanced-config-profile:
  Type: array
  Description: (list)
  Items:
   Reference: "#/components/schemas/datapost_ciscosmicdlcdl_advancedconfigprofile"

  x-yang:
    Type: list
cisco-smi-cdl:remote-site:
  Type: array
  Description: (list)
  Items:
    Reference: "#/components/schemas/datapost_ciscosmicdlcdl_remotesite"
  x-yang:
    Type: list
cisco-smi-cdl:label-config:
  Type: array
```

```
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_ciscosmicdlcdl_labelconfig"
      x-yang:
        Type: list
    cisco-smi-cdl:external-secret-config:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig"

    cisco-smi-cdl:ssl-config:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_sslconfig"
    cisco-smi-cdl:logging:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_logging"
    cisco-smi-cdl:datastore:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_ciscosmicdlcdl_datastore"
      x-yang:
        Type: list
    cisco-smi-cdl:zookeeper:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_zookeeper"
    cisco-smi-cdl:kafka:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka"
    cisco-smi-cdl:mirror-maker:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker"
    cisco-smi-cdl:show:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_show"
    cisco-smi-cdl:clear:
      Type: object
      Properties: {}
      Description: (non-presence)
      x-yang:
        Type: container
        is_presence: false
    cisco-smi-cdl:actions:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_actions"
    cisco-smi-cdl:network-policy:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_networkpolicy"
    cisco-smi-cdl:rebalance-index:
      Type: object
      Properties: {}
      Description: (non-presence)
      x-yang:
        Type: container
        is_presence: false
data_cisco-smi-cdl_cdl_actions:
  Type: object
  Properties:
    cisco-smi-cdl:actions:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_actions"
data_cisco-smi-cdl_cdl_actions_backup:
  Type: object
```

```
      Properties:
        cisco-smi-cdl:backup:
          Type: object
          Properties: {}
          Description: (non-presence)
          x-yang:
            Type: container
            is_presence: false
    data_cisco-smi-cdl_cdl_actions_remote-index-sync:
      Type: object
      Properties:
        cisco-smi-cdl:remote-index-sync:
          Type: object
          Properties: {}
          Description: (non-presence)
          x-yang:
            Type: container
            is_presence: false
    data_cisco-smi-cdl_cdl_actions_restore:
      Type: object
      Properties:
        cisco-smi-cdl:restore:
          Type: object
          Properties: {}
          Description: (non-presence)
          x-yang:
            Type: container
            is_presence: false

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name:

      Type: object
      Properties:
        cisco-smi-cdl:advanced-config-profile:
          Type: array
          Description: (list)
          Items:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_advancedconfigprofile"

          x-yang:
            Type: list

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint:

      Type: object
      Properties:
        cisco-smi-cdl:endpoint:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_endpoint"

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint-post:

      Type: object
      Properties:
```

```
cisco-smi-cdl:write-response-queue-size:
  Type: integer
  Description: (leaf)
  Format: uint32
  x-yang:
    Type: leaf
cisco-smi-cdl:write-worker-count:
  Type: integer
  Description: (leaf)
  Format: uint32
  x-yang:
    Type: leaf
cisco-smi-cdl:write-queue-size:
  Type: integer
  Description: (leaf)
  Format: uint32
  x-yang:
    Type: leaf
cisco-smi-cdl:read-response-queue-size:
  Type: integer
  Description: (leaf)
  Format: uint32
  x-yang:
    Type: leaf
cisco-smi-cdl:read-worker-count:
  Type: integer
  Description: (leaf)
  Format: uint32
  x-yang:
    Type: leaf
cisco-smi-cdl:read-queue-size:
  Type: integer
  Description: (leaf)
  Format: uint32
  x-yang:
    Type: leaf
cisco-smi-cdl:max-concurrent-operations:
  Type: integer
  Description: (leaf)
  Format: uint16
  x-yang:
    Type: leaf
cisco-smi-cdl:operation-timeout:
  Type: integer
  Description: (leaf)
  Format: uint32
  x-yang:
    Type: leaf
cisco-smi-cdl:index-timeout:
  Type: integer
  Description: (leaf)
```

```
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:slot-timeout:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:remote-ep-connection-count:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
```

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_index-timeout:

```
Type: object
Properties:
  cisco-smi-cdl:index-timeout:
    Type: integer
    Description: (leaf)
    Format: uint32
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_max-concurrent-operations:

```
Type: object
Properties:
  cisco-smi-cdl:max-concurrent-operations:
    Type: integer
    Description: (leaf)
    Format: uint16
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_operation-timeout:

```
Type: object
Properties:
  cisco-smi-cdl:operation-timeout:
    Type: integer
    Description: (leaf)
    Format: uint32
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_read-queue-size:

```
Type: object
Properties:
```

```
      cisco-smi-cdl:read-queue-size:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
```

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_read-response-queue-size:

```
    Type: object
    Properties:
      cisco-smi-cdl:read-response-queue-size:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
```

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_read-worker-count:

```
    Type: object
    Properties:
      cisco-smi-cdl:read-worker-count:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
```

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_remote-ep-connection-count:

```
    Type: object
    Properties:
      cisco-smi-cdl:remote-ep-connection-count:
        Type: integer
        Description: (leaf)
        Format: byte
        x-yang:
          Type: leaf
```

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_slot-timeout:

```
    Type: object
    Properties:
      cisco-smi-cdl:slot-timeout:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
```

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_write-queue-size:

```
      Type: object
      Properties:
        cisco-smi-cdl:write-queue-size:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_write-response-queue-size:

```
      Type: object
      Properties:
        cisco-smi-cdl:write-response-queue-size:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_write-worker-count:

```
      Type: object
      Properties:
        cisco-smi-cdl:write-worker-count:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index:

```
      Type: object
      Properties:
        cisco-smi-cdl:index:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_index"
```

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index-post:

```
      Type: object
      Properties:
        cisco-smi-cdl:init-record-count:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
        cisco-smi-cdl:audit:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_index_audit"
```

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index_audit:

```
      Type: object
      Properties:
        cisco-smi-cdl:audit:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_index_audit"

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index_audit-post:

      Type: object
      Properties:
        cisco-smi-cdl:record-expiry-duration:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index_audit_record-expiry-duration:

      Type: object
      Properties:
        cisco-smi-cdl:record-expiry-duration:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index_init-record-count:

      Type: object
      Properties:
        cisco-smi-cdl:init-record-count:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_name:

      Type: object
      Properties:
        cisco-smi-cdl:name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_slot:

      Type: object
      Properties:
```

```
        cisco-smi-cdl:slot:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_slot"

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_slot-post:

      Type: object
      Properties:
        cisco-smi-cdl:init-record-count:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_slot_init-record-count:

      Type: object
      Properties:
        cisco-smi-cdl:init-record-count:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_api:
      Type: object
      Properties:
        cisco-smi-cdl:api:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_api"
    data_cisco-smi-cdl_cdl_api-post:
      Type: object
      Properties:
        cisco-smi-cdl:deploy:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
        cisco-smi-cdl:external-ip:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        cisco-smi-cdl:storage:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
        cisco-smi-cdl:go-max-procs:
          Type: integer
          Description: (leaf)
```

```
      Format: byte
      x-yang:
        Type: leaf
    cisco-smi-cdl:cpu-limit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:memory-limit:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_api_cpu-limit:
  Type: object
  Properties:
    cisco-smi-cdl:cpu-limit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_api_deploy:
  Type: object
  Properties:
    cisco-smi-cdl:deploy:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_api_external-ip:
  Type: object
  Properties:
    cisco-smi-cdl:external-ip:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_api_go-max-procs:
  Type: object
  Properties:
    cisco-smi-cdl:go-max-procs:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_api_memory-limit:
```

```
    Type: object
    Properties:
      cisco-smi-cdl:memory-limit:
        Type: integer
        Description: (leaf)
        Format: byte
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_api_storage:
    Type: object
    Properties:
      cisco-smi-cdl:storage:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_clear:
    Type: object
    Properties:
      cisco-smi-cdl:clear:
        Type: object
        Properties: {}
        Description: (non-presence)
        x-yang:
          Type: container
          is_presence: false
  data_cisco-smi-cdl_cdl_datastore_datastore-name:
    Type: object
    Properties:
      cisco-smi-cdl:datastore:
        Type: array
        Description: (list)
        Items:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_datastore"
        x-yang:
          Type: list
  data_cisco-smi-cdl_cdl_datastore_datastore-name_advanced-config-profile:
    Type: object
    Properties:
      cisco-smi-cdl:advanced-config-profile:
        Type: string
        Description: (leaf)
        Format: leafref
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_datastore_datastore-name_cluster-id:
    Type: object
    Properties:
      cisco-smi-cdl:cluster-id:
        Type: integer
```

```
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint:
  Type: object
  Properties:
    cisco-smi-cdl:endpoint:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_endpoint_2"
data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint-post:
  Type: object
  Properties:
    cisco-smi-cdl:patch-url:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    cisco-smi-cdl:go-debug:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    cisco-smi-cdl:go-max-procs:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    cisco-smi-cdl:cpu-request:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:cpu-limit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:memory-request:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:memory-limit:
      Type: integer
      Description: (leaf)
```

```
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:replica:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    cisco-smi-cdl:copies-per-node:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    cisco-smi-cdl:settings:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_endpoint_2_settings"
    cisco-smi-cdl:external-ip:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    cisco-smi-cdl:external-ipv6:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    cisco-smi-cdl:external-port:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf

data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_copies-per-node:

  Type: object
  Properties:
    cisco-smi-cdl:copies-per-node:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_cpu-limit:
  Type: object
  Properties:
    cisco-smi-cdl:cpu-limit:
      Type: integer
      Description: (leaf)
```

```
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_cpu-request:
  Type: object
  Properties:
    cisco-smi-cdl:cpu-request:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_external-ip:
  Type: object
  Properties:
    cisco-smi-cdl:external-ip:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_external-ipv6:
  Type: object
  Properties:
    cisco-smi-cdl:external-ipv6:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_external-port:
  Type: object
  Properties:
    cisco-smi-cdl:external-port:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_go-debug:
  Type: object
  Properties:
    cisco-smi-cdl:go-debug:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_go-max-procs:
```

```
    Type: object
    Properties:
      cisco-smi-cdl:go-max-procs:
        Type: integer
        Description: (leaf)
        Format: byte
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_memory-limit:
    Type: object
    Properties:
      cisco-smi-cdl:memory-limit:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_memory-request:
    Type: object
    Properties:
      cisco-smi-cdl:memory-request:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_patch-url:
    Type: object
    Properties:
      cisco-smi-cdl:patch-url:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_replica:
    Type: object
    Properties:
      cisco-smi-cdl:replica:
        Type: integer
        Description: (leaf)
        Format: byte
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings:
    Type: object
    Properties:
      cisco-smi-cdl:settings:
        Reference: "#/components/schemas/datapost_ciscosmicdlcdl_endpoint_2_settings"
  data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings-post:
```

```
      Type: object
      Properties:
        cisco-smi-cdl:index-timeout-ms:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
        cisco-smi-cdl:slot-timeout-ms:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
        cisco-smi-cdl:remote-ep-connection-count:
          Type: integer
          Description: (leaf)
          Format: byte
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings_index-timeout-ms:

      Type: object
      Properties:
        cisco-smi-cdl:index-timeout-ms:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings_remote-ep-connection-count:

      Type: object
      Properties:
        cisco-smi-cdl:remote-ep-connection-count:
          Type: integer
          Description: (leaf)
          Format: byte
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings_slot-timeout-ms:

      Type: object
      Properties:
        cisco-smi-cdl:slot-timeout-ms:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
```

```
          Type: leaf
    data_cisco-smi-cdl_cdl_datastore_datastore-name_features:
      Type: object
      Properties:
        cisco-smi-cdl:features:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_features"
    data_cisco-smi-cdl_cdl_datastore_datastore-name_features-post:
      Type: object
      Properties:
        cisco-smi-cdl:instance-aware-notification:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_instanceawarenotification"
        cisco-smi-cdl:slot-stale-session-detection:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_slotstalesessiondetection"
        cisco-smi-cdl:overload-protection:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_overloadprotection"
        cisco-smi-cdl:index-overwrite-detection:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_indexoverwritedetection"
        cisco-smi-cdl:remote-site-connection-monitoring:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_remotesiteconnectionmonitoring"

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection:

      Type: object
      Properties:
        cisco-smi-cdl:index-overwrite-detection:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_indexoverwritedetection"

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection-post:

      Type: object
      Properties:
        cisco-smi-cdl:unique-keys-prefix:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_indexoverwritedetection_uniquekeysprefix"

          x-yang:
            Type: list
        cisco-smi-cdl:max-tps:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf
        cisco-smi-cdl:queue-size:
          Type: integer
```

```
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_max-tps:

      Type: object
      Properties:
        cisco-smi-cdl:max-tps:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_queue-size:

      Type: object
      Properties:
        cisco-smi-cdl:queue-size:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_unique-keys-prefix_unique-keys-prefix-key-prefix:

      Type: object
      Properties:
        cisco-smi-cdl:unique-keys-prefix:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_indexoverwritedetection_uniquekeysprefix"

          x-yang:
            Type: list

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_unique-keys-prefix_unique-keys-prefix-key-prefix_action:

      Type: object
      Properties:
        cisco-smi-cdl:action:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: notify-record
          enum:
          - notify-record
          - log-record
          - delete-record
```

```
        x-yang:
          Type: leaf

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_unique-keys-prefix_unique-keys-prefix-key-prefix_key-prefix:

      Type: object
      Properties:
        cisco-smi-cdl:key-prefix:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification:

      Type: object
      Properties:
        cisco-smi-cdl:instance-aware-notification:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_instanceawarenotification"

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification-post:

      Type: object
      Properties:
        cisco-smi-cdl:enable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
        cisco-smi-cdl:system-id:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_instanceawarenotification_systemid"
          x-yang:
            Type: list

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_enable:

      Type: object
      Properties:
        cisco-smi-cdl:enable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_system-id_system-id-id:

      Type: object
      Properties:
```

```
        cisco-smi-cdl:system-id:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_instanceawarenotification_systemid"
          x-yang:
            Type: list
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_system-id_system-id-id_id:

```
      Type: object
      Properties:
        cisco-smi-cdl:id:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_system-id_system-id-id_slice-names_slice-names-id:

```
      Type: object
      Properties:
        cisco-smi-cdl:slice-names:
          Type: array
          Items:
            Type: string
            Description: (leaf-list)
            Format: leafref
          x-yang:
            Type: leaf-list
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection:

```
      Type: object
      Properties:
        cisco-smi-cdl:overload-protection:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_overloadprotection"
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection-post:

```
      Type: object
      Properties:
        cisco-smi-cdl:enable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
        cisco-smi-cdl:index-max-record-count:
          Type: integer
          Description: (leaf)
```

```
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:slot-max-record-count:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:slot-max-size:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:hard-limit-percentage:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    cisco-smi-cdl:major-alert-threshold:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    cisco-smi-cdl:critical-alert-threshold:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_critical-alert-threshold:

```
  Type: object
  Properties:
    cisco-smi-cdl:critical-alert-threshold:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_enable:

```
  Type: object
  Properties:
    cisco-smi-cdl:enable:
      Type: boolean
      Description: (leaf)
```

```
      x-yang:
        Type: leaf

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_hard-limit-percentage:

    Type: object
    Properties:
      cisco-smi-cdl:hard-limit-percentage:
        Type: integer
        Description: (leaf)
        Format: byte
        x-yang:
          Type: leaf

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_index-max-record-count:

    Type: object
    Properties:
      cisco-smi-cdl:index-max-record-count:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_major-alert-threshold:

    Type: object
    Properties:
      cisco-smi-cdl:major-alert-threshold:
        Type: integer
        Description: (leaf)
        Format: byte
        x-yang:
          Type: leaf

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_slot-max-record-count:

    Type: object
    Properties:
      cisco-smi-cdl:slot-max-record-count:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_slot-max-size:

    Type: object
    Properties:
      cisco-smi-cdl:slot-max-size:
        Type: integer
```

```
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring:

```
    Type: object
    Properties:
      cisco-smi-cdl:remote-site-connection-monitoring:
        Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_remotesiteconnectionmonitoring"
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring-post:

```
    Type: object
    Properties:
      cisco-smi-cdl:enable:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
      cisco-smi-cdl:client-side-load-balancing:
        Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_remotesiteconnectionmonitoring_clientsideloadbalancing"
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_client-side-load-balancing:

```
    Type: object
    Properties:
      cisco-smi-cdl:client-side-load-balancing:
        Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_remotesiteconnectionmonitoring_clientsideloadbalancing"
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_client-side-load-balancing-post:

```
    Type: object
    Properties:
      cisco-smi-cdl:enable:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
      cisco-smi-cdl:wait-seconds-before-load-balancing:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_client-side-load-balancing_enable:

```
      Type: object
      Properties:
        cisco-smi-cdl:enable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_client-side-load-balancing_wait-seconds-before-load-balancing:

```
      Type: object
      Properties:
        cisco-smi-cdl:wait-seconds-before-load-balancing:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_enable:

```
      Type: object
      Properties:
        cisco-smi-cdl:enable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_slot-stale-session-detection:

```
      Type: object
      Properties:
        cisco-smi-cdl:slot-stale-session-detection:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_slotstalesessiondetection"
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_slot-stale-session-detection-post:

```
      Type: object
      Properties:
        cisco-smi-cdl:disable-auto-deletion:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
        cisco-smi-cdl:notification-retry-count:
          Type: integer
          Description: (leaf)
          Format: byte
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_slot-stale-session-detection_disable-auto-deletion:

```
Type: object
Properties:
  cisco-smi-cdl:disable-auto-deletion:
    Type: boolean
    Description: (leaf)
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_slot-stale-session-detection_notification-retry-count:

```
Type: object
Properties:
  cisco-smi-cdl:notification-retry-count:
    Type: integer
    Description: (leaf)
    Format: byte
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_find-by-nuk-prefixes_find-by-nuk-prefixes-id:

```
Type: object
Properties:
  cisco-smi-cdl:find-by-nuk-prefixes:
    Type: array
    Items:
      Type: string
      Description: (leaf-list)
      Format: string
    x-yang:
      Type: leaf-list
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_geo-remote-site_geo-remote-site-id:

```
Type: object
Properties:
  cisco-smi-cdl:geo-remote-site:
    Type: array
    Items:
      Type: string
      Description: (leaf-list)
      Format: leafref
    x-yang:
      Type: leaf-list
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_index:

```
Type: object
Properties:
  cisco-smi-cdl:index:
    Reference: "#/components/schemas/datapost_ciscosmicdlcdl_index_1"
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_index-post:

```
Type: object
```

```
Properties:
  cisco-smi-cdl:patch-url:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
  cisco-smi-cdl:go-debug:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
  cisco-smi-cdl:go-max-procs:
    Type: integer
    Description: (leaf)
    Format: byte
    x-yang:
      Type: leaf
  cisco-smi-cdl:cpu-request:
    Type: integer
    Description: (leaf)
    Format: uint32
    x-yang:
      Type: leaf
  cisco-smi-cdl:cpu-limit:
    Type: integer
    Description: (leaf)
    Format: uint32
    x-yang:
      Type: leaf
  cisco-smi-cdl:memory-request:
    Type: integer
    Description: (leaf)
    Format: uint32
    x-yang:
      Type: leaf
  cisco-smi-cdl:memory-limit:
    Type: integer
    Description: (leaf)
    Format: uint32
    x-yang:
      Type: leaf
  cisco-smi-cdl:replica:
    Type: integer
    Description: (leaf)
    Format: byte
    x-yang:
      Type: leaf
  cisco-smi-cdl:prev-map-count:
    Type: integer
```

```
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
    cisco-smi-cdl:map:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
    cisco-smi-cdl:write-factor:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_index_cpu-limit:
  Type: object
  Properties:
    cisco-smi-cdl:cpu-limit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_index_cpu-request:
  Type: object
  Properties:
    cisco-smi-cdl:cpu-request:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_index_go-debug:
  Type: object
  Properties:
    cisco-smi-cdl:go-debug:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_index_go-max-procs:
  Type: object
  Properties:
    cisco-smi-cdl:go-max-procs:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
```

```
      Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_index_map:
  Type: object
  Properties:
    cisco-smi-cdl:map:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_index_memory-limit:
  Type: object
  Properties:
    cisco-smi-cdl:memory-limit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_index_memory-request:
  Type: object
  Properties:
    cisco-smi-cdl:memory-request:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_index_patch-url:
  Type: object
  Properties:
    cisco-smi-cdl:patch-url:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_index_prev-map-count:
  Type: object
  Properties:
    cisco-smi-cdl:prev-map-count:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_index_replica:
  Type: object
  Properties:
    cisco-smi-cdl:replica:
      Type: integer
```

```
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_index_write-factor:
  Type: object
  Properties:
    cisco-smi-cdl:write-factor:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_label-config:
  Type: object
  Properties:
    cisco-smi-cdl:label-config:
      Type: string
      Description: (leaf)
      Format: leafref
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_metrics:
  Type: object
  Properties:
    cisco-smi-cdl:metrics:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_metrics"
data_cisco-smi-cdl_cdl_datastore_datastore-name_metrics-post:
  Type: object
  Properties:
    cisco-smi-cdl:verbosity:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: production
      enum:
      - production
      - debug
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_metrics_verbosity:
  Type: object
  Properties:
    cisco-smi-cdl:verbosity:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: production
      enum:
      - production
      - debug
      x-yang:
```

```
          Type: leaf
    data_cisco-smi-cdl_cdl_datastore_datastore-name_mode:
      Type: object
      Properties:
        cisco-smi-cdl:mode:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: regular
          enum:
          - regular
          - scale-up
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_datastore_datastore-name_name:
      Type: object
      Properties:
        cisco-smi-cdl:name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_datastore_datastore-name_overload-protection:
      Type: object
      Properties:
        cisco-smi-cdl:overload-protection:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_overloadprotection"

data_cisco-smi-cdl_cdl_datastore_datastore-name_overload-protection-post:

      Type: object
      Properties:
        cisco-smi-cdl:disable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_datastore_datastore-name_overload-protection_disable:

      Type: object
      Properties:
        cisco-smi-cdl:disable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_datastore_datastore-name_slice-names_slice-names-id:

      Type: object
      Properties:
```

```
    cisco-smi-cdl:slice-names:
      Type: array
      Items:
        Type: string
        Description: (leaf-list)
        Format: string
      x-yang:
        Type: leaf-list
data_cisco-smi-cdl_cdl_datastore_datastore-name_slot:
  Type: object
  Properties:
    cisco-smi-cdl:slot:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_slot_2"
data_cisco-smi-cdl_cdl_datastore_datastore-name_slot-post:
  Type: object
  Properties:
    cisco-smi-cdl:patch-url:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    cisco-smi-cdl:go-debug:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    cisco-smi-cdl:go-max-procs:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    cisco-smi-cdl:cpu-request:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:cpu-limit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:memory-request:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
```

```
        Type: leaf
      cisco-smi-cdl:memory-limit:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      cisco-smi-cdl:replica:
        Type: integer
        Description: (leaf)
        Format: byte
        x-yang:
          Type: leaf
      cisco-smi-cdl:map:
        Type: integer
        Description: (leaf)
        Format: uint16
        x-yang:
          Type: leaf
      cisco-smi-cdl:write-factor:
        Type: integer
        Description: (leaf)
        Format: byte
        x-yang:
          Type: leaf
      cisco-smi-cdl:notification:
        Reference: "#/components/schemas/datapost_ciscosmicdlcdl_slot_2_notification"
      cisco-smi-cdl:metrics:
        Reference: "#/components/schemas/datapost_ciscosmicdlcdl_slot_2_metrics"
  data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_cpu-limit:
    Type: object
    Properties:
      cisco-smi-cdl:cpu-limit:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_cpu-request:
    Type: object
    Properties:
      cisco-smi-cdl:cpu-request:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_go-debug:
    Type: object
    Properties:
      cisco-smi-cdl:go-debug:
```

```
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_go-max-procs:
  Type: object
  Properties:
    cisco-smi-cdl:go-max-procs:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_map:
  Type: object
  Properties:
    cisco-smi-cdl:map:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_memory-limit:
  Type: object
  Properties:
    cisco-smi-cdl:memory-limit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_memory-request:
  Type: object
  Properties:
    cisco-smi-cdl:memory-request:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_metrics:
  Type: object
  Properties:
    cisco-smi-cdl:metrics:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_slot_2_metrics"
data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_metrics-post:
  Type: object
  Properties:
    cisco-smi-cdl:report-idle-session-type:
      Type: boolean
```

```
        Description: (leaf)
        x-yang:
          Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_metrics_report-idle-session-type:
    Type: object
    Properties:
      cisco-smi-cdl:report-idle-session-type:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
 data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification:
    Type: object
    Properties:
      cisco-smi-cdl:notification:
        Reference: "#/components/schemas/datapost_ciscosmicdlcdl_slot_2_notification"
data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification-post:
    Type: object
    Properties:
      cisco-smi-cdl:connection-count:
        Type: integer
        Description: (leaf)
        Format: byte
        x-yang:
          Type: leaf
      cisco-smi-cdl:dynamic-provisioning:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
      cisco-smi-cdl:host:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
      cisco-smi-cdl:port:
        Type: integer
        Description: (leaf)
        Format: uint16
        x-yang:
          Type: leaf
      cisco-smi-cdl:limit:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      cisco-smi-cdl:max-concurrent-bulk-notifications:
```

```
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    cisco-smi-cdl:bulk-task-progress-update-batch-size:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:notification-retry-seconds:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    cisco-smi-cdl:include-conflict-data:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    cisco-smi-cdl:remote-system-id:
      Type: array
      Items:
        Type: string
        Description: (leaf-list)
        Format: leafref
      x-yang:
        Type: leaf-list
    cisco-smi-cdl:use-stream:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    cisco-smi-cdl:include-slice-in-header:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    cisco-smi-cdl:endpoints:
      Type: array
      Description: (list)
      Items:
        Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_slot_2_notification_endpoints"
      x-yang:
        Type: list
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_bulk-task-progress-update-batch-size:

```
  Type: object
```

```
      Properties:
        cisco-smi-cdl:bulk-task-progress-update-batch-size:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_connection-count:

      Type: object
      Properties:
        cisco-smi-cdl:connection-count:
          Type: integer
          Description: (leaf)
          Format: byte
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_dynamic-provisioning:

      Type: object
      Properties:
        cisco-smi-cdl:dynamic-provisioning:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id:

      Type: object
      Properties:
        cisco-smi-cdl:endpoints:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_slot_2_notification_endpoints"
          x-yang:
            Type: list

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_app-instance-id:

      Type: object
      Properties:
        cisco-smi-cdl:app-instance-id:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_host:

```
Type: object
Properties:
  cisco-smi-cdl:host:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_port:

```
Type: object
Properties:
  cisco-smi-cdl:port:
    Type: integer
    Description: (leaf)
    Format: uint16
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_slice-name:

```
Type: object
Properties:
  cisco-smi-cdl:slice-name:
    Type: string
    Description: (leaf)
    Format: leafref
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_host:

```
Type: object
Properties:
  cisco-smi-cdl:host:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_include-conflict-data:

```
Type: object
Properties:
  cisco-smi-cdl:include-conflict-data:
    Type: boolean
    Description: (leaf)
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_include-slice-in-header:

```
Type: object
Properties:
  cisco-smi-cdl:include-slice-in-header:
    Type: boolean
    Description: (leaf)
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_limit:

```
Type: object
Properties:
  cisco-smi-cdl:limit:
    Type: integer
    Description: (leaf)
    Format: uint32
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_max-concurrent-bulk-notifications:

```
Type: object
Properties:
  cisco-smi-cdl:max-concurrent-bulk-notifications:
    Type: integer
    Description: (leaf)
    Format: byte
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_notification-retry-seconds:

```
Type: object
Properties:
  cisco-smi-cdl:notification-retry-seconds:
    Type: integer
    Description: (leaf)
    Format: byte
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_port:

```
Type: object
Properties:
  cisco-smi-cdl:port:
    Type: integer
    Description: (leaf)
    Format: uint16
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_remote-system-id_remote-system-id-id:

```
      Type: object
      Properties:
        cisco-smi-cdl:remote-system-id:
          Type: array
          Items:
            Type: string
            Description: (leaf-list)
            Format: leafref
          x-yang:
            Type: leaf-list

  data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_use-stream:
      Type: object
      Properties:
        cisco-smi-cdl:use-stream:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_patch-url:
      Type: object
      Properties:
        cisco-smi-cdl:patch-url:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_replica:
      Type: object
      Properties:
        cisco-smi-cdl:replica:
          Type: integer
          Description: (leaf)
          Format: byte
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_write-factor:
      Type: object
      Properties:
        cisco-smi-cdl:write-factor:
          Type: integer
          Description: (leaf)
          Format: byte
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_datastore_datastore-name_test:
      Type: object
      Properties:
        cisco-smi-cdl:test:
```

```
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_test"
data_cisco-smi-cdl_cdl_datastore_datastore-name_test-post:
  Type: object
  Properties:
    cisco-smi-cdl:run:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    cisco-smi-cdl:patch-url:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    cisco-smi-cdl:loop:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:txns:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:txn-type:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
    cisco-smi-cdl:wait-time-ns:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:max-non-unique-keys:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_test_loop:
  Type: object
  Properties:
    cisco-smi-cdl:loop:
      Type: integer
      Description: (leaf)
```

```
          Format: uint32
          x-yang:
            Type: leaf
data_cisco-smi-cdl_cdl_datastore_datastore-name_test_max-non-unique-keys:
      Type: object
      Properties:
        cisco-smi-cdl:max-non-unique-keys:
          Type: integer
          Description: (leaf)
          Format: byte
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_datastore_datastore-name_test_patch-url:
      Type: object
      Properties:
        cisco-smi-cdl:patch-url:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_datastore_datastore-name_test_run:
      Type: object
      Properties:
        cisco-smi-cdl:run:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_datastore_datastore-name_test_txn-type:
      Type: object
      Properties:
        cisco-smi-cdl:txn-type:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_datastore_datastore-name_test_txns:
      Type: object
      Properties:
        cisco-smi-cdl:txns:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_datastore_datastore-name_test_wait-time-ns:
      Type: object
      Properties:
```

```
    cisco-smi-cdl:wait-time-ns:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_deployment-model:
  Type: object
  Properties:
    cisco-smi-cdl:deployment-model:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: large
      enum:
      - large
      - small
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_enable-geo-replication:
  Type: object
  Properties:
    cisco-smi-cdl:enable-geo-replication:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_external-secret-config:
  Type: object
  Properties:
    cisco-smi-cdl:external-secret-config:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig"

data_cisco-smi-cdl_cdl_external-secret-config-post:
  Type: object
  Properties:
    cisco-smi-cdl:name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    cisco-smi-cdl:namespace:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    cisco-smi-cdl:target-secret:
      Type: string
      Description: (leaf)
      Format: string
```

```
        x-yang:
          Type: leaf
      cisco-smi-cdl:remote-key-path:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
      cisco-smi-cdl:refresh-interval:
        Type: integer
        Description: (leaf)
        Format: uint16
        x-yang:
          Type: leaf
      cisco-smi-cdl:secret-store:
        Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_secretstore"
      cisco-smi-cdl:data:
        Type: array
        Description: (list)
        Items:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_data"
        x-yang:
          Type: list
  data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key:
    Type: object
    Properties:
      cisco-smi-cdl:data:
        Type: array
        Description: (list)
        Items:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_data"
        x-yang:
          Type: list

data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_remote-ref:

    Type: object
    Properties:
      cisco-smi-cdl:remote-ref:
        Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_remoteref"

data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_remote-ref-post:

    Type: object
    Properties:
      cisco-smi-cdl:key:
        Type: string
        Description: (leaf)
        Format: string
```

```
          x-yang:
            Type: leaf
        cisco-smi-cdl:property:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_remote-ref_key:

    Type: object
    Properties:
      cisco-smi-cdl:key:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf

data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_remote-ref_property:

    Type: object
    Properties:
      cisco-smi-cdl:property:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf

data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_secret-key:

    Type: object
    Properties:
      cisco-smi-cdl:secret-key:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_external-secret-config_name:
    Type: object
    Properties:
      cisco-smi-cdl:name:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_external-secret-config_namespace:
    Type: object
    Properties:
```

```
      cisco-smi-cdl:namespace:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
    data_cisco-smi-cdl_cdl_external-secret-config_refresh-interval:
      Type: object
      Properties:
        cisco-smi-cdl:refresh-interval:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_external-secret-config_remote-key-path:
      Type: object
      Properties:
        cisco-smi-cdl:remote-key-path:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_external-secret-config_secret-store:
      Type: object
      Properties:
        cisco-smi-cdl:secret-store:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_secretstore"
    data_cisco-smi-cdl_cdl_external-secret-config_secret-store-post:
      Type: object
      Properties:
        cisco-smi-cdl:name:
          Type: string
          Description: Overrides common secret store name (leaf)
          Format: string
          x-yang:
            Type: leaf
        cisco-smi-cdl:kind:
          Type: string
          Description: Overrides common secret store kind (leaf)
          Format: enumeration
          Default: SecretStore
          enum:
          - SecretStore
          - ClusterSecretStore
          x-yang:
            Type: leaf
        cisco-smi-cdl:namespace:
          Type: string
          Description: Overrides common secret store namespace (leaf)
```

```
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_external-secret-config_secret-store_kind:
  Type: object
  Properties:
    cisco-smi-cdl:kind:
      Type: string
      Description: Overrides common secret store kind (leaf)
      Format: enumeration
      Default: SecretStore
      enum:
      - SecretStore
      - ClusterSecretStore
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_external-secret-config_secret-store_name:
  Type: object
  Properties:
    cisco-smi-cdl:name:
      Type: string
      Description: Overrides common secret store name (leaf)
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_external-secret-config_secret-store_namespace:
  Type: object
  Properties:
    cisco-smi-cdl:namespace:
      Type: string
      Description: Overrides common secret store namespace (leaf)
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_external-secret-config_target-secret:
  Type: object
  Properties:
    cisco-smi-cdl:target-secret:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka:
  Type: object
  Properties:
    cisco-smi-cdl:kafka:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka"
data_cisco-smi-cdl_cdl_kafka-post:
  Type: object
  Properties:
    cisco-smi-cdl:replica:
```

```
  Type: integer
  Description: (leaf)
  Format: byte
  x-yang:
    Type: leaf
cisco-smi-cdl:mode:
  Type: string
  Description: (leaf)
  Format: enumeration
  Default: zookeeper
  enum:
  - zookeeper
  - kraft
  x-yang:
    Type: leaf
cisco-smi-cdl:kraft-migration:
  Type: string
  Description: (leaf)
  Format: enumeration
  Default: disabled
  enum:
  - disabled
  - enabled
  - finalized
  x-yang:
    Type: leaf
cisco-smi-cdl:replication-factor:
  Type: integer
  Description: (leaf)
  Format: byte
  x-yang:
    Type: leaf
cisco-smi-cdl:log-level:
  Type: string
  Description: (leaf)
  Format: enumeration
  Default: fatal
  enum:
  - fatal
  - error
  - warn
  - info
  - debug
  - trace
  x-yang:
    Type: leaf
cisco-smi-cdl:partition:
  Type: integer
  Description: (leaf)
  Format: uint16
  x-yang:
    Type: leaf
cisco-smi-cdl:enable-JMX-metrics:
  Type: boolean
```

```
      Description: (leaf)
      x-yang:
        Type: leaf
    cisco-smi-cdl:resource:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_resource"
    cisco-smi-cdl:external-ip:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_externalip"
      x-yang:
        Type: list
    cisco-smi-cdl:external-ipv6:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_externalip"
      x-yang:
        Type: list
    cisco-smi-cdl:enable-persistence:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    cisco-smi-cdl:storage:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
    cisco-smi-cdl:ssl-settings:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_sslsettings"
    cisco-smi-cdl:retention-time:
      Type: integer
      Description: (leaf)
      Format: int16
      x-yang:
        Type: leaf
    cisco-smi-cdl:retention-size:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    cisco-smi-cdl:log-compaction:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_logcompaction"
    cisco-smi-cdl:disable-unclean-leader-election:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
```

```
        cisco-smi-cdl:label-config:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_endpoint_1"
        cisco-smi-cdl:controller:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_controller"
        cisco-smi-cdl:enable-parallel-pod-management:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
        cisco-smi-cdl:heap-options:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_kafka_controller_heapoptions"
        cisco-smi-cdl:describe:
          Type: object
          Properties: {}
          Description: (non-presence)
          x-yang:
            Type: container
            is_presence: false
        cisco-smi-cdl:list:
          Type: object
          Properties: {}
          Description: (non-presence)
          x-yang:
            Type: container
            is_presence: false
        cisco-smi-cdl:reset-offsets:
          Type: object
          Properties: {}
          Description: (non-presence)
          x-yang:
            Type: container
            is_presence: false
        cisco-smi-cdl:reset-offsets-dry-run:
          Type: object
          Properties: {}
          Description: (non-presence)
          x-yang:
            Type: container
            is_presence: false
    data_cisco-smi-cdl_cdl_kafka_controller:
      Type: object
      Properties:
        cisco-smi-cdl:controller:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_controller"
    data_cisco-smi-cdl_cdl_kafka_controller-post:
      Type: object
      Properties:
        cisco-smi-cdl:replica:
          Type: integer
          Description: (leaf)
          Format: byte
```

```
          x-yang:
            Type: leaf
        cisco-smi-cdl:log-level:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: fatal
          enum:
          - fatal
          - error
          - warn
          - info
          - debug
          - trace
          x-yang:
            Type: leaf
        cisco-smi-cdl:heap-options:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_kafka_controller_heapoptions"
        cisco-smi-cdl:resource:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_resource"
    data_cisco-smi-cdl_cdl_kafka_controller_heap-options:
      Type: object
      Properties:
        cisco-smi-cdl:heap-options:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_kafka_controller_heapoptions"
    data_cisco-smi-cdl_cdl_kafka_controller_heap-options-post:
      Type: object
      Properties:
        cisco-smi-cdl:min-heap-size-mb:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
        cisco-smi-cdl:max-heap-size-mb:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
  data_cisco-smi-cdl_cdl_kafka_controller_heap-options_max-heap-size-mb:

      Type: object
      Properties:
        cisco-smi-cdl:max-heap-size-mb:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
  data_cisco-smi-cdl_cdl_kafka_controller_heap-options_min-heap-size-mb:
```

```
    Type: object
    Properties:
      cisco-smi-cdl:min-heap-size-mb:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_kafka_controller_log-level:
    Type: object
    Properties:
      cisco-smi-cdl:log-level:
        Type: string
        Description: (leaf)
        Format: enumeration
        Default: fatal
        enum:
        - fatal
        - error
        - warn
        - info
        - debug
        - trace
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_kafka_controller_replica:
    Type: object
    Properties:
      cisco-smi-cdl:replica:
        Type: integer
        Description: (leaf)
        Format: byte
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_kafka_controller_resource:
    Type: object
    Properties:
      cisco-smi-cdl:resource:
        Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_resource"
  data_cisco-smi-cdl_cdl_kafka_controller_resource-post:
    Type: object
    Properties:
      cisco-smi-cdl:cpu-request:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      cisco-smi-cdl:cpu-limit:
        Type: integer
        Description: (leaf)
        Format: uint32
```

```
      x-yang:
        Type: leaf
    cisco-smi-cdl:memory-request:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:memory-limit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_controller_resource_cpu-limit:
  Type: object
  Properties:
    cisco-smi-cdl:cpu-limit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_controller_resource_cpu-request:
  Type: object
  Properties:
    cisco-smi-cdl:cpu-request:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_controller_resource_memory-limit:
  Type: object
  Properties:
    cisco-smi-cdl:memory-limit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_controller_resource_memory-request:
  Type: object
  Properties:
    cisco-smi-cdl:memory-request:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_describe:
```

```
      Type: object
      Properties:
        cisco-smi-cdl:describe:
          Type: object
          Properties: {}
          Description: (non-presence)
          x-yang:
            Type: container
            is_presence: false
    data_cisco-smi-cdl_cdl_kafka_describe-post:
      Type: object
    data_cisco-smi-cdl_cdl_kafka_disable-unclean-leader-election:
      Type: object
      Properties:
        cisco-smi-cdl:disable-unclean-leader-election:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_kafka_enable-JMX-metrics:
      Type: object
      Properties:
        cisco-smi-cdl:enable-JMX-metrics:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_kafka_enable-parallel-pod-management:
      Type: object
      Properties:
        cisco-smi-cdl:enable-parallel-pod-management:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_kafka_enable-persistence:
      Type: object
      Properties:
        cisco-smi-cdl:enable-persistence:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf

  data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port:

      Type: object
      Properties:
        cisco-smi-cdl:external-ip:
          Type: array
          Description: (list)
          Items:
```

```
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_externalip"
        x-yang:
          Type: list

data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port_ip:

    Type: object
    Properties:
      cisco-smi-cdl:ip:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf

data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port_port:

    Type: object
    Properties:
      cisco-smi-cdl:port:
        Type: integer
        Description: (leaf)
        Format: uint16
        x-yang:
          Type: leaf

data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port_ssl-port:

    Type: object
    Properties:
      cisco-smi-cdl:ssl-port:
        Type: integer
        Description: (leaf)
        Format: uint16
        x-yang:
          Type: leaf

data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port:

    Type: object
    Properties:
      cisco-smi-cdl:external-ipv6:
        Type: array
        Description: (list)
        Items:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_externalip"
        x-yang:
          Type: list

data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port_ip:

    Type: object
    Properties:
```

```
        cisco-smi-cdl:ip:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port_port:

      Type: object
      Properties:
        cisco-smi-cdl:port:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port_ssl-port:

      Type: object
      Properties:
        cisco-smi-cdl:ssl-port:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_kafka_heap-options:
      Type: object
      Properties:
        cisco-smi-cdl:heap-options:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_kafka_controller_heapoptions"
    data_cisco-smi-cdl_cdl_kafka_heap-options-post:
      Type: object
      Properties:
        cisco-smi-cdl:min-heap-size-mb:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
        cisco-smi-cdl:max-heap-size-mb:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_kafka_heap-options_max-heap-size-mb:
      Type: object
      Properties:
```

```
    cisco-smi-cdl:max-heap-size-mb:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_heap-options_min-heap-size-mb:
  Type: object
  Properties:
    cisco-smi-cdl:min-heap-size-mb:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_kraft-migration:
  Type: object
  Properties:
    cisco-smi-cdl:kraft-migration:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: disabled
      enum:
      - disabled
      - enabled
      - finalized
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_label-config:
  Type: object
  Properties:
    cisco-smi-cdl:label-config:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_endpoint_1"
data_cisco-smi-cdl_cdl_kafka_label-config-post:
  Type: object
  Properties:
    cisco-smi-cdl:key:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    cisco-smi-cdl:value:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_label-config_key:
  Type: object
  Properties:
```

```
    cisco-smi-cdl:key:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_label-config_value:
  Type: object
  Properties:
    cisco-smi-cdl:value:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_list:
  Type: object
  Properties:
    cisco-smi-cdl:list:
      Type: object
      Properties: {}
      Description: (non-presence)
      x-yang:
        Type: container
        is_presence: false
data_cisco-smi-cdl_cdl_kafka_list-post:
  Type: object
data_cisco-smi-cdl_cdl_kafka_log-compaction:
  Type: object
  Properties:
    cisco-smi-cdl:log-compaction:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_logcompaction"
data_cisco-smi-cdl_cdl_kafka_log-compaction-post:
  Type: object
  Properties:
    cisco-smi-cdl:disable:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    cisco-smi-cdl:delete-retention-ms:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_log-compaction_delete-retention-ms:
  Type: object
  Properties:
    cisco-smi-cdl:delete-retention-ms:
      Type: integer
```

```
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_log-compaction_disable:
  Type: object
  Properties:
    cisco-smi-cdl:disable:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_log-level:
  Type: object
  Properties:
    cisco-smi-cdl:log-level:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: fatal
      enum:
      - fatal
      - error
      - warn
      - info
      - debug
      - trace
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_mode:
  Type: object
  Properties:
    cisco-smi-cdl:mode:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: zookeeper
      enum:
      - zookeeper
      - kraft
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_partition:
  Type: object
  Properties:
    cisco-smi-cdl:partition:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_replica:
  Type: object
```

```
  Properties:
    cisco-smi-cdl:replica:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_replication-factor:
  Type: object
  Properties:
    cisco-smi-cdl:replication-factor:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_reset-offsets:
  Type: object
  Properties:
    cisco-smi-cdl:reset-offsets:
      Type: object
      Properties: {}
      Description: (non-presence)
      x-yang:
        Type: container
        is_presence: false
data_cisco-smi-cdl_cdl_kafka_reset-offsets-dry-run:
  Type: object
  Properties:
    cisco-smi-cdl:reset-offsets-dry-run:
      Type: object
      Properties: {}
      Description: (non-presence)
      x-yang:
        Type: container
        is_presence: false
data_cisco-smi-cdl_cdl_kafka_reset-offsets-dry-run-post:
  Type: object
data_cisco-smi-cdl_cdl_kafka_reset-offsets-post:
  Type: object
data_cisco-smi-cdl_cdl_kafka_resource:
  Type: object
  Properties:
    cisco-smi-cdl:resource:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_resource"
data_cisco-smi-cdl_cdl_kafka_resource-post:
  Type: object
  Properties:
    cisco-smi-cdl:cpu-request:
      Type: integer
      Description: (leaf)
```

```
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:cpu-limit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:memory-request:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:memory-limit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_resource_cpu-limit:
  Type: object
  Properties:
    cisco-smi-cdl:cpu-limit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_resource_cpu-request:
  Type: object
  Properties:
    cisco-smi-cdl:cpu-request:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_resource_memory-limit:
  Type: object
  Properties:
    cisco-smi-cdl:memory-limit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_resource_memory-request:
  Type: object
  Properties:
```

```
    cisco-smi-cdl:memory-request:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_retention-size:
  Type: object
  Properties:
    cisco-smi-cdl:retention-size:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_retention-time:
  Type: object
  Properties:
    cisco-smi-cdl:retention-time:
      Type: integer
      Description: (leaf)
      Format: int16
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_kafka_ssl-settings:
  Type: object
  Properties:
    cisco-smi-cdl:ssl-settings:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_sslsettings"
data_cisco-smi-cdl_cdl_kafka_ssl-settings-post:
  Type: object
  Properties:
    cisco-smi-cdl:enable-ssl:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    cisco-smi-cdl:disable-host-name-verification:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    cisco-smi-cdl:auto-generation:
     Reference: "#/components/schemas/datapost_ciscosmicdlcdl_sslconfig_autogeneration"

    cisco-smi-cdl:broker-tls-secret-name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    cisco-smi-cdl:broker-ca-secret-name:
```

```
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    cisco-smi-cdl:broker-ca-external-secret:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig"

  data_cisco-smi-cdl_cdl_kafka_ssl-settings_auto-generation:
    Type: object
    Properties:
      cisco-smi-cdl:auto-generation:
       Reference: "#/components/schemas/datapost_ciscosmicdlcdl_sslconfig_autogeneration"

  data_cisco-smi-cdl_cdl_kafka_ssl-settings_auto-generation-post:
    Type: object
    Properties:
      cisco-smi-cdl:enabled:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_kafka_ssl-settings_auto-generation_enabled:
    Type: object
    Properties:
      cisco-smi-cdl:enabled:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret:
    Type: object
    Properties:
      cisco-smi-cdl:broker-ca-external-secret:
        Reference: "#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig"


data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret-post:

    Type: object
    Properties:
      cisco-smi-cdl:name:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
      cisco-smi-cdl:namespace:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
```

```
          Type: leaf
        cisco-smi-cdl:target-secret:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        cisco-smi-cdl:remote-key-path:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        cisco-smi-cdl:refresh-interval:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf
        cisco-smi-cdl:secret-store:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_secretstore"
        cisco-smi-cdl:data:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_data"
          x-yang:
            Type: list

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key:

      Type: object
      Properties:
        cisco-smi-cdl:data:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_data"
          x-yang:
            Type: list

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_remote-ref:

      Type: object
      Properties:
        cisco-smi-cdl:remote-ref:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_remoteref"

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_remote-ref-post:
```

```
      Type: object
      Properties:
        cisco-smi-cdl:key:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        cisco-smi-cdl:property:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_remote-ref_key:

```
      Type: object
      Properties:
        cisco-smi-cdl:key:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_remote-ref_property:

```
      Type: object
      Properties:
        cisco-smi-cdl:property:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_secret-key:

```
      Type: object
      Properties:
        cisco-smi-cdl:secret-key:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_name:

```
      Type: object
      Properties:
```

```
      cisco-smi-cdl:name:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_namespace:

    Type: object
    Properties:
      cisco-smi-cdl:namespace:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_refresh-interval:

    Type: object
    Properties:
      cisco-smi-cdl:refresh-interval:
        Type: integer
        Description: (leaf)
        Format: uint16
        x-yang:
          Type: leaf

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_remote-key-path:

    Type: object
    Properties:
      cisco-smi-cdl:remote-key-path:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store:

    Type: object
    Properties:
      cisco-smi-cdl:secret-store:
        Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_secretstore"

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store-post:

    Type: object
    Properties:
      cisco-smi-cdl:name:
        Type: string
```

```
      Description: Overrides common secret store name (leaf)
      Format: string
      x-yang:
        Type: leaf
    cisco-smi-cdl:kind:
      Type: string
      Description: Overrides common secret store kind (leaf)
      Format: enumeration
      Default: SecretStore
      enum:
      - SecretStore
      - ClusterSecretStore
      x-yang:
        Type: leaf
    cisco-smi-cdl:namespace:
      Type: string
      Description: Overrides common secret store namespace (leaf)
      Format: string
      x-yang:
        Type: leaf
```

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store_kind:

```
Type: object
Properties:
  cisco-smi-cdl:kind:
    Type: string
    Description: Overrides common secret store kind (leaf)
    Format: enumeration
    Default: SecretStore
    enum:
    - SecretStore
    - ClusterSecretStore
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store_name:

```
Type: object
Properties:
  cisco-smi-cdl:name:
    Type: string
    Description: Overrides common secret store name (leaf)
    Format: string
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store_namespace:

```
Type: object
Properties:
  cisco-smi-cdl:namespace:
    Type: string
```

```
        Description: Overrides common secret store namespace (leaf)
        Format: string
        x-yang:
          Type: leaf

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_target-secret:

    Type: object
    Properties:
      cisco-smi-cdl:target-secret:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-secret-name:
    Type: object
    Properties:
      cisco-smi-cdl:broker-ca-secret-name:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-tls-secret-name:
    Type: object
    Properties:
      cisco-smi-cdl:broker-tls-secret-name:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf

data_cisco-smi-cdl_cdl_kafka_ssl-settings_disable-host-name-verification:

    Type: object
    Properties:
      cisco-smi-cdl:disable-host-name-verification:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_kafka_ssl-settings_enable-ssl:
    Type: object
    Properties:
      cisco-smi-cdl:enable-ssl:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_kafka_storage:
```

```
    Type: object
    Properties:
      cisco-smi-cdl:storage:
        Type: integer
        Description: (leaf)
        Format: uint16
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_label-config_label-config-name:
    Type: object
    Properties:
      cisco-smi-cdl:label-config:
        Type: array
        Description: (list)
        Items:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_labelconfig"
        x-yang:
          Type: list
  data_cisco-smi-cdl_cdl_label-config_label-config-name_endpoint:
    Type: object
    Properties:
      cisco-smi-cdl:endpoint:
        Reference: "#/components/schemas/datapost_ciscosmicdlcdl_endpoint_1"
  data_cisco-smi-cdl_cdl_label-config_label-config-name_endpoint-post:
    Type: object
    Properties:
      cisco-smi-cdl:key:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
      cisco-smi-cdl:value:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_label-config_label-config-name_endpoint_key:
    Type: object
    Properties:
      cisco-smi-cdl:key:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_label-config_label-config-name_endpoint_value:
    Type: object
    Properties:
      cisco-smi-cdl:value:
```

```
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
    data_cisco-smi-cdl_cdl_label-config_label-config-name_index:
      Type: object
      Properties:
        cisco-smi-cdl:index:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_slot_1"
    data_cisco-smi-cdl_cdl_label-config_label-config-name_index-post:
      Type: object
      Properties:
        cisco-smi-cdl:map:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_ciscosmicdlcdl_slot_1_map"
          x-yang:
            Type: list

data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id:

      Type: object
      Properties:
        cisco-smi-cdl:map:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_ciscosmicdlcdl_slot_1_map"
          x-yang:
            Type: list

data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id_key:

      Type: object
      Properties:
        cisco-smi-cdl:key:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id_map-id:

      Type: object
      Properties:
        cisco-smi-cdl:map-id:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
```

```
          Type: leaf

data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id_value:

      Type: object
      Properties:
        cisco-smi-cdl:value:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_label-config_label-config-name_name:
      Type: object
      Properties:
        cisco-smi-cdl:name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_label-config_label-config-name_slot:
      Type: object
      Properties:
        cisco-smi-cdl:slot:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_slot_1"
    data_cisco-smi-cdl_cdl_label-config_label-config-name_slot-post:
      Type: object
      Properties:
        cisco-smi-cdl:map:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_ciscosmicdlcdl_slot_1_map"
          x-yang:
            Type: list

data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id:

      Type: object
      Properties:
        cisco-smi-cdl:map:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_ciscosmicdlcdl_slot_1_map"
          x-yang:
            Type: list

data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id_key:

      Type: object
      Properties:
```

```
        cisco-smi-cdl:key:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id_map-id:

      Type: object
      Properties:
        cisco-smi-cdl:map-id:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id_value:

      Type: object
      Properties:
        cisco-smi-cdl:value:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_logging:
      Type: object
      Properties:
        cisco-smi-cdl:logging:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_logging"
    data_cisco-smi-cdl_cdl_logging-post:
      Type: object
      Properties:
        cisco-smi-cdl:default-log-level:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: off
          enum:
          - off
          - error
          - warn
          - info
          - debug
          - trace
          x-yang:
            Type: leaf
        cisco-smi-cdl:json-logging:
          Type: boolean
          Description: Enable or disable logging in json format. Example value: true
(leaf)
```

```
          x-yang:
            Type: leaf
        cisco-smi-cdl:logger:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_ciscosmicdlcdl_logging_logger"
          x-yang:
            Type: list
        cisco-smi-cdl:sync-logging:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
        cisco-smi-cdl:error-stack:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_logging_default-log-level:
      Type: object
      Properties:
        cisco-smi-cdl:default-log-level:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: off
          enum:
          - off
          - error
          - warn
          - info
          - debug
          - trace
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_logging_error-stack:
      Type: object
      Properties:
        cisco-smi-cdl:error-stack:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_logging_json-logging:
      Type: object
      Properties:
        cisco-smi-cdl:json-logging:
          Type: boolean
          Description: Enable or disable logging in json format. Example value: true
(leaf)
          x-yang:
            Type: leaf
```

```
data_cisco-smi-cdl_cdl_logging_logger_logger-name:
  Type: object
  Properties:
    cisco-smi-cdl:logger:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_ciscosmicdlcdl_logging_logger"
      x-yang:
        Type: list
data_cisco-smi-cdl_cdl_logging_logger_logger-name_level:
  Type: object
  Properties:
    cisco-smi-cdl:level:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: off
      enum:
      - off
      - error
      - warn
      - info
      - debug
      - trace
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_logging_logger_logger-name_name:
  Type: object
  Properties:
    cisco-smi-cdl:name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_logging_sync-logging:
  Type: object
  Properties:
    cisco-smi-cdl:sync-logging:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_mirror-maker:
  Type: object
  Properties:
    cisco-smi-cdl:mirror-maker:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker"
data_cisco-smi-cdl_cdl_mirror-maker-post:
  Type: object
  Properties:
    cisco-smi-cdl:log-level:
```

```
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: fatal
      enum:
      - fatal
      - error
      - warn
      - info
      - debug
      - trace
      x-yang:
        Type: leaf
    cisco-smi-cdl:enable-JMX-metrics:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    cisco-smi-cdl:ssl:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_ssl"
    cisco-smi-cdl:slot:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_slot"
    cisco-smi-cdl:index:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_slot"
data_cisco-smi-cdl_cdl_mirror-maker_enable-JMX-metrics:
  Type: object
  Properties:
    cisco-smi-cdl:enable-JMX-metrics:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_mirror-maker_index:
  Type: object
  Properties:
    cisco-smi-cdl:index:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_slot"
data_cisco-smi-cdl_cdl_mirror-maker_index-post:
  Type: object
  Properties:
    cisco-smi-cdl:replicas:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    cisco-smi-cdl:replication-factor:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    cisco-smi-cdl:settings:
```

```
        Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_slot_settings"
      cisco-smi-cdl:resource:
        Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_resource"
      cisco-smi-cdl:heap-options:
        Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_kafka_controller_heapoptions"
  data_cisco-smi-cdl_cdl_mirror-maker_index_heap-options:
    Type: object
    Properties:
      cisco-smi-cdl:heap-options:
        Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_kafka_controller_heapoptions"
  data_cisco-smi-cdl_cdl_mirror-maker_index_heap-options-post:
    Type: object
    Properties:
      cisco-smi-cdl:min-heap-size-mb:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      cisco-smi-cdl:max-heap-size-mb:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_mirror-maker_index_heap-options_max-heap-size-mb:

    Type: object
    Properties:
      cisco-smi-cdl:max-heap-size-mb:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_mirror-maker_index_heap-options_min-heap-size-mb:

    Type: object
    Properties:
      cisco-smi-cdl:min-heap-size-mb:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_mirror-maker_index_replicas:
    Type: object
    Properties:
      cisco-smi-cdl:replicas:
```

```
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_mirror-maker_index_replication-factor:
  Type: object
  Properties:
    cisco-smi-cdl:replication-factor:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_mirror-maker_index_resource:
  Type: object
  Properties:
    cisco-smi-cdl:resource:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_resource"
data_cisco-smi-cdl_cdl_mirror-maker_index_resource-post:
  Type: object
  Properties:
    cisco-smi-cdl:cpu-request:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:cpu-limit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:memory-request:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:memory-limit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_mirror-maker_index_resource_cpu-limit:
  Type: object
  Properties:
    cisco-smi-cdl:cpu-limit:
      Type: integer
```

```
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
      data_cisco-smi-cdl_cdl_mirror-maker_index_resource_cpu-request:
        Type: object
        Properties:
          cisco-smi-cdl:cpu-request:
            Type: integer
            Description: (leaf)
            Format: uint32
            x-yang:
              Type: leaf
      data_cisco-smi-cdl_cdl_mirror-maker_index_resource_memory-limit:
        Type: object
        Properties:
          cisco-smi-cdl:memory-limit:
            Type: integer
            Description: (leaf)
            Format: uint32
            x-yang:
              Type: leaf
      data_cisco-smi-cdl_cdl_mirror-maker_index_resource_memory-request:
        Type: object
        Properties:
          cisco-smi-cdl:memory-request:
            Type: integer
            Description: (leaf)
            Format: uint32
            x-yang:
              Type: leaf
      data_cisco-smi-cdl_cdl_mirror-maker_index_settings:
        Type: object
        Properties:
          cisco-smi-cdl:settings:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_slot_settings"
      data_cisco-smi-cdl_cdl_mirror-maker_index_settings-post:
        Type: object
        Properties:
          cisco-smi-cdl:tasks-max:
            Type: integer
            Description: (leaf)
            Format: int32
            x-yang:
              Type: leaf
          cisco-smi-cdl:producer-properties:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_slot_settings_producerproperties"

          cisco-smi-cdl:consumer-properties:
            Reference:
```

```
"#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_slot_settings_consumerproperties"

   data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties:

      Type: object
      Properties:
        cisco-smi-cdl:consumer-properties:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_slot_settings_consumerproperties"


data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties-post:

      Type: object
      Properties:
        cisco-smi-cdl:receive-buffer-bytes:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf
        cisco-smi-cdl:send-buffer-bytes:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf
        cisco-smi-cdl:max-poll-records:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf
        cisco-smi-cdl:max-partition-fetch-bytes:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_max-partition-fetch-bytes:

      Type: object
      Properties:
        cisco-smi-cdl:max-partition-fetch-bytes:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_max-poll-records:

      Type: object
```

```
      Properties:
        cisco-smi-cdl:max-poll-records:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_receive-buffer-bytes:

      Type: object
      Properties:
        cisco-smi-cdl:receive-buffer-bytes:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_send-buffer-bytes:

      Type: object
      Properties:
        cisco-smi-cdl:send-buffer-bytes:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf
   data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties:

      Type: object
      Properties:
        cisco-smi-cdl:producer-properties:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_slot_settings_producerproperties"

data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties-post:

      Type: object
      Properties:
        cisco-smi-cdl:batch-size:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf
        cisco-smi-cdl:linger-ms:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
```

```
        Type: leaf
      cisco-smi-cdl:receive-buffer-bytes:
        Type: integer
        Description: (leaf)
        Format: int64
        x-yang:
          Type: leaf
      cisco-smi-cdl:send-buffer-bytes:
        Type: integer
        Description: (leaf)
        Format: int64
        x-yang:
          Type: leaf
      cisco-smi-cdl:max-request-size:
        Type: integer
        Description: (leaf)
        Format: int64
        x-yang:
          Type: leaf
```

data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_batch-size:

```
Type: object
Properties:
  cisco-smi-cdl:batch-size:
    Type: integer
    Description: (leaf)
    Format: int64
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_linger-ms:

```
Type: object
Properties:
  cisco-smi-cdl:linger-ms:
    Type: integer
    Description: (leaf)
    Format: int64
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_max-request-size:

```
Type: object
Properties:
  cisco-smi-cdl:max-request-size:
    Type: integer
    Description: (leaf)
    Format: int64
    x-yang:
      Type: leaf
```

```
data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_receive-buffer-bytes:
      Type: object
      Properties:
        cisco-smi-cdl:receive-buffer-bytes:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf
data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_send-buffer-bytes:
      Type: object
      Properties:
        cisco-smi-cdl:send-buffer-bytes:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_mirror-maker_index_settings_tasks-max:
      Type: object
      Properties:
        cisco-smi-cdl:tasks-max:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_mirror-maker_log-level:
      Type: object
      Properties:
        cisco-smi-cdl:log-level:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: fatal
          enum:
          - fatal
          - error
          - warn
          - info
          - debug
          - trace
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_mirror-maker_slot:
      Type: object
      Properties:
        cisco-smi-cdl:slot:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_slot"
    data_cisco-smi-cdl_cdl_mirror-maker_slot-post:
```

```
      Type: object
      Properties:
        cisco-smi-cdl:replicas:
          Type: integer
          Description: (leaf)
          Format: byte
          x-yang:
            Type: leaf
        cisco-smi-cdl:replication-factor:
          Type: integer
          Description: (leaf)
          Format: byte
          x-yang:
            Type: leaf
        cisco-smi-cdl:settings:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_slot_settings"
        cisco-smi-cdl:resource:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_resource"
        cisco-smi-cdl:heap-options:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_kafka_controller_heapoptions"
    data_cisco-smi-cdl_cdl_mirror-maker_slot_heap-options:
      Type: object
      Properties:
        cisco-smi-cdl:heap-options:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_kafka_controller_heapoptions"
    data_cisco-smi-cdl_cdl_mirror-maker_slot_heap-options-post:
      Type: object
      Properties:
        cisco-smi-cdl:min-heap-size-mb:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
        cisco-smi-cdl:max-heap-size-mb:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
  data_cisco-smi-cdl_cdl_mirror-maker_slot_heap-options_max-heap-size-mb:

      Type: object
      Properties:
        cisco-smi-cdl:max-heap-size-mb:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
```

```
        Type: leaf
data_cisco-smi-cdl_cdl_mirror-maker_slot_heap-options_min-heap-size-mb:
  Type: object
  Properties:
    cisco-smi-cdl:min-heap-size-mb:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_mirror-maker_slot_replicas:
  Type: object
  Properties:
    cisco-smi-cdl:replicas:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_mirror-maker_slot_replication-factor:
  Type: object
  Properties:
    cisco-smi-cdl:replication-factor:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_mirror-maker_slot_resource:
  Type: object
  Properties:
    cisco-smi-cdl:resource:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_resource"
data_cisco-smi-cdl_cdl_mirror-maker_slot_resource-post:
  Type: object
  Properties:
    cisco-smi-cdl:cpu-request:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:cpu-limit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    cisco-smi-cdl:memory-request:
      Type: integer
      Description: (leaf)
```

```
        Format: uint32
        x-yang:
          Type: leaf
      cisco-smi-cdl:memory-limit:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
    data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_cpu-limit:
      Type: object
      Properties:
        cisco-smi-cdl:cpu-limit:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_cpu-request:
      Type: object
      Properties:
        cisco-smi-cdl:cpu-request:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_memory-limit:
      Type: object
      Properties:
        cisco-smi-cdl:memory-limit:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_memory-request:
      Type: object
      Properties:
        cisco-smi-cdl:memory-request:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_mirror-maker_slot_settings:
      Type: object
      Properties:
        cisco-smi-cdl:settings:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_slot_settings"
    data_cisco-smi-cdl_cdl_mirror-maker_slot_settings-post:
```

```
      Type: object
      Properties:
        cisco-smi-cdl:tasks-max:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
        cisco-smi-cdl:producer-properties:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_slot_settings_producerproperties"

        cisco-smi-cdl:consumer-properties:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_slot_settings_consumerproperties"
```

data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties:

```
      Type: object
      Properties:
        cisco-smi-cdl:consumer-properties:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_slot_settings_consumerproperties"
```

data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties-post:

```
      Type: object
      Properties:
        cisco-smi-cdl:receive-buffer-bytes:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf
        cisco-smi-cdl:send-buffer-bytes:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf
        cisco-smi-cdl:max-poll-records:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf
        cisco-smi-cdl:max-partition-fetch-bytes:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf
```

```
data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_max-partition-fetch-bytes:

      Type: object
      Properties:
        cisco-smi-cdl:max-partition-fetch-bytes:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_max-poll-records:

      Type: object
      Properties:
        cisco-smi-cdl:max-poll-records:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_receive-buffer-bytes:

      Type: object
      Properties:
        cisco-smi-cdl:receive-buffer-bytes:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_send-buffer-bytes:

      Type: object
      Properties:
        cisco-smi-cdl:send-buffer-bytes:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf
   data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties:

      Type: object
      Properties:
        cisco-smi-cdl:producer-properties:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_slot_settings_producerproperties"


data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties-post:
```

```
      Type: object
      Properties:
        cisco-smi-cdl:batch-size:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf
        cisco-smi-cdl:linger-ms:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf
        cisco-smi-cdl:receive-buffer-bytes:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf
        cisco-smi-cdl:send-buffer-bytes:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf
        cisco-smi-cdl:max-request-size:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_batch-size:

```
      Type: object
      Properties:
        cisco-smi-cdl:batch-size:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_linger-ms:

```
      Type: object
      Properties:
        cisco-smi-cdl:linger-ms:
          Type: integer
          Description: (leaf)
```

```
          Format: int64
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_max-request-size:

      Type: object
      Properties:
        cisco-smi-cdl:max-request-size:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_receive-buffer-bytes:

      Type: object
      Properties:
        cisco-smi-cdl:receive-buffer-bytes:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_send-buffer-bytes:

      Type: object
      Properties:
        cisco-smi-cdl:send-buffer-bytes:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_tasks-max:
      Type: object
      Properties:
        cisco-smi-cdl:tasks-max:
          Type: integer
          Description: (leaf)
          Format: int32
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_mirror-maker_ssl:
      Type: object
      Properties:
        cisco-smi-cdl:ssl:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_ssl"
    data_cisco-smi-cdl_cdl_mirror-maker_ssl-post:
      Type: object
      Properties:
```

```
        cisco-smi-cdl:broker-ca-secret-names:
          Type: array
          Items:
            Type: string
            Description: (leaf-list)
            Format: string
          x-yang:
            Type: leaf-list
        cisco-smi-cdl:broker-ca-external-secrets:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_ssl_brokercaexternalsecrets"
          x-yang:
            Type: list
```

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name:

```
      Type: object
      Properties:
        cisco-smi-cdl:broker-ca-external-secrets:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_ssl_brokercaexternalsecrets"
          x-yang:
            Type: list
```

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key:

```
      Type: object
      Properties:
        cisco-smi-cdl:data:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_data"
          x-yang:
            Type: list
```

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_remote-ref:

```
      Type: object
      Properties:
        cisco-smi-cdl:remote-ref:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_remoteref"
```

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_remote-ref-post:

```
      Type: object
```

```
      Properties:
        cisco-smi-cdl:key:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        cisco-smi-cdl:property:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_remote-ref_key:

```
      Type: object
      Properties:
        cisco-smi-cdl:key:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_remote-ref_property:

```
      Type: object
      Properties:
        cisco-smi-cdl:property:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_secret-key:

```
      Type: object
      Properties:
        cisco-smi-cdl:secret-key:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_name:

```
      Type: object
      Properties:
        cisco-smi-cdl:name:
          Type: string
```

```
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
```

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_namespace:

```
    Type: object
    Properties:
      cisco-smi-cdl:namespace:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
```

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_refresh-interval:

```
    Type: object
    Properties:
      cisco-smi-cdl:refresh-interval:
        Type: integer
        Description: (leaf)
        Format: uint16
        x-yang:
          Type: leaf
```

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_remote-key-path:

```
    Type: object
    Properties:
      cisco-smi-cdl:remote-key-path:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
```

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store:

```
    Type: object
    Properties:
      cisco-smi-cdl:secret-store:
        Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_secretstore"
```

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store-post:

```
    Type: object
    Properties:
      cisco-smi-cdl:name:
        Type: string
        Description: Overrides common secret store name (leaf)
        Format: string
```

```
      x-yang:
        Type: leaf
    cisco-smi-cdl:kind:
      Type: string
      Description: Overrides common secret store kind (leaf)
      Format: enumeration
      Default: SecretStore
      enum:
      - SecretStore
      - ClusterSecretStore
      x-yang:
        Type: leaf
    cisco-smi-cdl:namespace:
      Type: string
      Description: Overrides common secret store namespace (leaf)
      Format: string
      x-yang:
        Type: leaf
```

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store_kind:

```
Type: object
Properties:
  cisco-smi-cdl:kind:
    Type: string
    Description: Overrides common secret store kind (leaf)
    Format: enumeration
    Default: SecretStore
    enum:
    - SecretStore
    - ClusterSecretStore
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store_name:

```
Type: object
Properties:
  cisco-smi-cdl:name:
    Type: string
    Description: Overrides common secret store name (leaf)
    Format: string
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store_namespace:

```
Type: object
Properties:
  cisco-smi-cdl:namespace:
    Type: string
    Description: Overrides common secret store namespace (leaf)
    Format: string
```

```
        x-yang:
          Type: leaf

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_target-secret:

    Type: object
    Properties:
      cisco-smi-cdl:target-secret:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-secret-names_broker-ca-secret-names-id:

    Type: object
    Properties:
      cisco-smi-cdl:broker-ca-secret-names:
        Type: array
        Items:
          Type: string
          Description: (leaf-list)
          Format: string
        x-yang:
          Type: leaf-list
  data_cisco-smi-cdl_cdl_network-policy:
    Type: object
    Properties:
      cisco-smi-cdl:network-policy:
        Reference: "#/components/schemas/datapost_ciscosmicdlcdl_networkpolicy"
  data_cisco-smi-cdl_cdl_network-policy-post:
    Type: object
    Properties:
      cisco-smi-cdl:enable:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_network-policy_enable:
    Type: object
    Properties:
      cisco-smi-cdl:enable:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
  data_cisco-smi-cdl_cdl_node-type:
    Type: object
    Properties:
      cisco-smi-cdl:node-type:
        Type: string
```

```
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
    data_cisco-smi-cdl_cdl_rebalance-index:
      Type: object
      Properties:
        cisco-smi-cdl:rebalance-index:
          Type: object
          Properties: {}
          Description: (non-presence)
          x-yang:
            Type: container
            is_presence: false
    data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id:
      Type: object
      Properties:
        cisco-smi-cdl:remote-site:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_ciscosmicdlcdl_remotesite"
          x-yang:
            Type: list
    data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_db-endpoint:
      Type: object
      Properties:
        cisco-smi-cdl:db-endpoint:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_dbendpoint"

data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_db-endpoint-post:

      Type: object
      Properties:
        cisco-smi-cdl:host:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        cisco-smi-cdl:port:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_db-endpoint_host:

      Type: object
      Properties:
        cisco-smi-cdl:host:
```

```
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_db-endpoint_port:

      Type: object
      Properties:
        cisco-smi-cdl:port:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port:

      Type: object
      Properties:
        cisco-smi-cdl:kafka-server:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafkaserver"
          x-yang:
            Type: list

data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port_host:

      Type: object
      Properties:
        cisco-smi-cdl:host:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port_port:

      Type: object
      Properties:
        cisco-smi-cdl:port:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf

data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port_ssl-port:
```

```
  Type: object
  Properties:
    cisco-smi-cdl:ssl-port:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_system-id:
  Type: object
  Properties:
    cisco-smi-cdl:system-id:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_repository:
  Type: object
  Properties:
    cisco-smi-cdl:repository:
      Type: string
      Description: (leaf)
      Format: leafref
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_show:
  Type: object
  Properties:
    cisco-smi-cdl:show:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_show"
data_cisco-smi-cdl_cdl_show_sessions:
  Type: object
  Properties:
    cisco-smi-cdl:sessions:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_show_sessions"
data_cisco-smi-cdl_cdl_show_sessions_count:
  Type: object
  Properties:
    cisco-smi-cdl:count:
      Type: object
      Properties: {}
      Description: (non-presence)
      x-yang:
        Type: container
        is_presence: false
data_cisco-smi-cdl_cdl_ssl-config:
  Type: object
  Properties:
    cisco-smi-cdl:ssl-config:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_sslconfig"
```

```
data_cisco-smi-cdl_cdl_ssl-config-post:
  Type: object
  Properties:
    cisco-smi-cdl:enable:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    cisco-smi-cdl:auto-generation:
     Reference: "#/components/schemas/datapost_ciscosmicdlcdl_sslconfig_autogeneration"

    cisco-smi-cdl:tls-secret-name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    cisco-smi-cdl:ca-secret-name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    cisco-smi-cdl:ca-external-secret:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig"

    cisco-smi-cdl:remote-ca-auth:
     Reference: "#/components/schemas/datapost_ciscosmicdlcdl_sslconfig_remotecaauth"

    cisco-smi-cdl:certs:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_ciscosmicdlcdl_sslconfig_certs"
      x-yang:
        Type: list
data_cisco-smi-cdl_cdl_ssl-config_auto-generation:
  Type: object
  Properties:
    cisco-smi-cdl:auto-generation:
     Reference: "#/components/schemas/datapost_ciscosmicdlcdl_sslconfig_autogeneration"

data_cisco-smi-cdl_cdl_ssl-config_auto-generation-post:
  Type: object
  Properties:
    cisco-smi-cdl:enabled:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_ssl-config_auto-generation_enabled:
  Type: object
```

```
      Properties:
        cisco-smi-cdl:enabled:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret:
      Type: object
      Properties:
        cisco-smi-cdl:ca-external-secret:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig"

    data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret-post:
      Type: object
      Properties:
        cisco-smi-cdl:name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        cisco-smi-cdl:namespace:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        cisco-smi-cdl:target-secret:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        cisco-smi-cdl:remote-key-path:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        cisco-smi-cdl:refresh-interval:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf
        cisco-smi-cdl:secret-store:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_secretstore"
        cisco-smi-cdl:data:
          Type: array
          Description: (list)
          Items:
```

```
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_data"
        x-yang:
          Type: list

data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key:

    Type: object
    Properties:
      cisco-smi-cdl:data:
        Type: array
        Description: (list)
        Items:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_data"
        x-yang:
          Type: list

data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_remote-ref:

    Type: object
    Properties:
      cisco-smi-cdl:remote-ref:
        Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_remoteref"

data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_remote-ref-post:

    Type: object
    Properties:
      cisco-smi-cdl:key:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
      cisco-smi-cdl:property:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf

data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_remote-ref_key:

    Type: object
    Properties:
      cisco-smi-cdl:key:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
```

```
data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_remote-ref_property:
      Type: object
      Properties:
        cisco-smi-cdl:property:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_secret-key:
      Type: object
      Properties:
        cisco-smi-cdl:secret-key:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_name:
      Type: object
      Properties:
        cisco-smi-cdl:name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_namespace:
      Type: object
      Properties:
        cisco-smi-cdl:namespace:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
   data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_refresh-interval:
      Type: object
      Properties:
        cisco-smi-cdl:refresh-interval:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_remote-key-path:
      Type: object
      Properties:
```

```
        cisco-smi-cdl:remote-key-path:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store:
      Type: object
      Properties:
        cisco-smi-cdl:secret-store:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_secretstore"
  data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store-post:

      Type: object
      Properties:
        cisco-smi-cdl:name:
          Type: string
          Description: Overrides common secret store name (leaf)
          Format: string
          x-yang:
            Type: leaf
        cisco-smi-cdl:kind:
          Type: string
          Description: Overrides common secret store kind (leaf)
          Format: enumeration
          Default: SecretStore
          enum:
          - SecretStore
          - ClusterSecretStore
          x-yang:
            Type: leaf
        cisco-smi-cdl:namespace:
          Type: string
          Description: Overrides common secret store namespace (leaf)
          Format: string
          x-yang:
            Type: leaf
  data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store_kind:

      Type: object
      Properties:
        cisco-smi-cdl:kind:
          Type: string
          Description: Overrides common secret store kind (leaf)
          Format: enumeration
          Default: SecretStore
          enum:
          - SecretStore
          - ClusterSecretStore
          x-yang:
            Type: leaf
  data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store_name:
```

```
      Type: object
      Properties:
        cisco-smi-cdl:name:
          Type: string
          Description: Overrides common secret store name (leaf)
          Format: string
          x-yang:
            Type: leaf

  data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store_namespace:

      Type: object
      Properties:
        cisco-smi-cdl:namespace:
          Type: string
          Description: Overrides common secret store namespace (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_target-secret:
      Type: object
      Properties:
        cisco-smi-cdl:target-secret:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_ssl-config_ca-secret-name:
      Type: object
      Properties:
        cisco-smi-cdl:ca-secret-name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host:
      Type: object
      Properties:
        cisco-smi-cdl:certs:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_ciscosmicdlcdl_sslconfig_certs"
          x-yang:
            Type: list
    data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ca-secret:
      Type: object
      Properties:
        cisco-smi-cdl:ca-secret:
```

```
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_host:
  Type: object
  Properties:
    cisco-smi-cdl:host:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ssl-ca:
  Type: object
  Properties:
    cisco-smi-cdl:ssl-ca:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ssl-crt:
  Type: object
  Properties:
    cisco-smi-cdl:ssl-crt:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ssl-key:
  Type: object
  Properties:
    cisco-smi-cdl:ssl-key:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_tls-secret:
  Type: object
  Properties:
    cisco-smi-cdl:tls-secret:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_ssl-config_enable:
```

```
      Type: object
      Properties:
        cisco-smi-cdl:enable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
    data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth:
      Type: object
      Properties:
        cisco-smi-cdl:remote-ca-auth:
         Reference: "#/components/schemas/datapost_ciscosmicdlcdl_sslconfig_remotecaauth"

    data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth-post:
      Type: object
      Properties:
        cisco-smi-cdl:ca-secret-names:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_sslconfig_remotecaauth_casecretnames"
          x-yang:
            Type: list
        cisco-smi-cdl:ca-external-secrets:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_sslconfig_remotecaauth_caexternalsecrets"
          x-yang:
            Type: list

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id:

      Type: object
      Properties:
        cisco-smi-cdl:ca-external-secrets:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_sslconfig_remotecaauth_caexternalsecrets"
          x-yang:
            Type: list

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key:

      Type: object
      Properties:
        cisco-smi-cdl:data:
          Type: array
          Description: (list)
```

```
        Items:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_data"
        x-yang:
          Type: list
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_remote-ref:

```
      Type: object
      Properties:
        cisco-smi-cdl:remote-ref:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_remoteref"
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_remote-ref-post:

```
      Type: object
      Properties:
        cisco-smi-cdl:key:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        cisco-smi-cdl:property:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_remote-ref_key:

```
      Type: object
      Properties:
        cisco-smi-cdl:key:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_remote-ref_property:

```
      Type: object
      Properties:
        cisco-smi-cdl:property:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_secret-key:

```
      Type: object
      Properties:
        cisco-smi-cdl:secret-key:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_name:

```
      Type: object
      Properties:
        cisco-smi-cdl:name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_namespace:

```
      Type: object
      Properties:
        cisco-smi-cdl:namespace:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_refresh-interval:

```
      Type: object
      Properties:
        cisco-smi-cdl:refresh-interval:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_remote-key-path:

```
      Type: object
      Properties:
        cisco-smi-cdl:remote-key-path:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store:

```
Type: object
Properties:
  cisco-smi-cdl:secret-store:
    Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_secretstore"
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store-post:

```
Type: object
Properties:
  cisco-smi-cdl:name:
    Type: string
    Description: Overrides common secret store name (leaf)
    Format: string
    x-yang:
      Type: leaf
  cisco-smi-cdl:kind:
    Type: string
    Description: Overrides common secret store kind (leaf)
    Format: enumeration
    Default: SecretStore
    enum:
    - SecretStore
    - ClusterSecretStore
    x-yang:
      Type: leaf
  cisco-smi-cdl:namespace:
    Type: string
    Description: Overrides common secret store namespace (leaf)
    Format: string
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store_kind:

```
Type: object
Properties:
  cisco-smi-cdl:kind:
    Type: string
    Description: Overrides common secret store kind (leaf)
    Format: enumeration
    Default: SecretStore
    enum:
    - SecretStore
    - ClusterSecretStore
    x-yang:
      Type: leaf
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store_name:

```
Type: object
```

```
      Properties:
        cisco-smi-cdl:name:
          Type: string
          Description: Overrides common secret store name (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store_namespace:

```
      Type: object
      Properties:
        cisco-smi-cdl:namespace:
          Type: string
          Description: Overrides common secret store namespace (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_site-id:

```
      Type: object
      Properties:
        cisco-smi-cdl:site-id:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_target-secret:

```
      Type: object
      Properties:
        cisco-smi-cdl:target-secret:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-secret-names_ca-secret-names-site-id:

```
      Type: object
      Properties:
        cisco-smi-cdl:ca-secret-names:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_sslconfig_remotecaauth_casecretnames"
          x-yang:
            Type: list
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-secret-names_ca-secret-names-site-id_secret-name:

```
  Type: object
  Properties:
    cisco-smi-cdl:secret-name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-secret-names_ca-secret-names-site-id_site-id:

```
  Type: object
  Properties:
    cisco-smi-cdl:site-id:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_ssl-config_tls-secret-name:
  Type: object
  Properties:
    cisco-smi-cdl:tls-secret-name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_system-id:
  Type: object
  Properties:
    cisco-smi-cdl:system-id:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_use-rust-image:
  Type: object
  Properties:
    cisco-smi-cdl:use-rust-image:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_zookeeper:
  Type: object
  Properties:
    cisco-smi-cdl:zookeeper:
```

```
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_zookeeper"
data_cisco-smi-cdl_cdl_zookeeper-post:
  Type: object
  Properties:
    cisco-smi-cdl:data-storage-size:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    cisco-smi-cdl:log-storage-size:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    cisco-smi-cdl:log-level:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: fatal
      enum:
      - fatal
      - error
      - warn
      - info
      - debug
      - trace
      x-yang:
        Type: leaf
    cisco-smi-cdl:replica:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    cisco-smi-cdl:enable-JMX-metrics:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    cisco-smi-cdl:enable-persistence:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    cisco-smi-cdl:enable-parallel-pod-management:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_zookeeper_data-storage-size:
  Type: object
```

```
  Properties:
    cisco-smi-cdl:data-storage-size:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_zookeeper_enable-JMX-metrics:
  Type: object
  Properties:
    cisco-smi-cdl:enable-JMX-metrics:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_zookeeper_enable-parallel-pod-management:
  Type: object
  Properties:
    cisco-smi-cdl:enable-parallel-pod-management:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_zookeeper_enable-persistence:
  Type: object
  Properties:
    cisco-smi-cdl:enable-persistence:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_zookeeper_log-level:
  Type: object
  Properties:
    cisco-smi-cdl:log-level:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: fatal
      enum:
      - fatal
      - error
      - warn
      - info
      - debug
      - trace
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_zookeeper_log-storage-size:
  Type: object
  Properties:
    cisco-smi-cdl:log-storage-size:
      Type: integer
```

```
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
data_cisco-smi-cdl_cdl_zookeeper_replica:
  Type: object
  Properties:
    cisco-smi-cdl:replica:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
data_cisco-smi-cdl_feature-gates:
  Type: object
  Properties:
    cisco-smi-cdl:feature-gates:
      Reference: "#/components/schemas/datapost_ciscosmicdlfeaturegates"
data_cisco-smi-cdl_feature-gates-post:
  Type: object
  Properties:
    cisco-smi-cdl:alpha:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    cisco-smi-cdl:test:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
data_cisco-smi-cdl_feature-gates_alpha:
  Type: object
  Properties:
    cisco-smi-cdl:alpha:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
data_cisco-smi-cdl_feature-gates_test:
  Type: object
  Properties:
    cisco-smi-cdl:test:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
operations:
  Type: object
  Properties:
    ietf-restconf:operations:
```

```
        Type: object
        Properties: {}
        Description: This resource is a container that provides access to the
data-model-specific RPC
         operations supported by the server. See RESTCONF RFC 8040 for further information.

        x-yang:
          Type: operations
    root:
      Type: object
      Properties:
        ietf-restconf:restconf:
          Reference: "#/components/schemas/root_ietfrestconfrestconf"
    yang-library-version:
      Type: object
      Properties:
        ietf-restconf:yang-library-version:
          Type: object
          Properties: {}
         Description: This leaf identifies the revision date of the 'ietf-yang-library'
 YANG module that is
           implemented by this server. See RESTCONF RFC 8040 for further information.
          x-yang:
            Type: leaf
    datapost_ciscosmicdlfeaturegates:
      Type: object
      Properties:
        alpha:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
        test:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
      Description: (non-presence)
    datapost_ciscosmicdlcdl_api:
      Type: object
      Properties:
        deploy:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
        external-ip:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

```
      storage:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      go-max-procs:
        Type: integer
        Description: (leaf)
        Format: byte
        x-yang:
          Type: leaf
      cpu-limit:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      memory-limit:
        Type: integer
        Description: (leaf)
        Format: byte
        x-yang:
          Type: leaf
    Description: (presence)
  datapost_ciscosmicdlcdl_endpoint:
    Type: object
    Properties:
      write-response-queue-size:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      write-worker-count:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      write-queue-size:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      read-response-queue-size:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
```

```
        Type: leaf
      read-worker-count:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      read-queue-size:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      max-concurrent-operations:
        Type: integer
        Description: (leaf)
        Format: uint16
        x-yang:
          Type: leaf
      operation-timeout:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      index-timeout:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      slot-timeout:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      remote-ep-connection-count:
        Type: integer
        Description: (leaf)
        Format: byte
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_ciscosmicdlcdl_index_audit:
    Type: object
    Properties:
      record-expiry-duration:
        Type: integer
        Description: (leaf)
        Format: uint16
```

```
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_ciscosmicdlcdl_index:
  Type: object
  Properties:
    init-record-count:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    audit:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_index_audit"
  Description: (non-presence)
datapost_ciscosmicdlcdl_slot:
  Type: object
  Properties:
    init-record-count:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_ciscosmicdlcdl_advancedconfigprofile:
  Type: object
  Properties:
    Name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    endpoint:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_endpoint"
    index:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_index"
    slot:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_slot"
datapost_ciscosmicdlcdl_dbendpoint:
  Type: object
  Properties:
    host:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    port:
      Type: integer
```

```
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_ciscosmicdlcdl_kafkaserver:
  Type: object
  Properties:
    host:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    port:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
    ssl-port:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
datapost_ciscosmicdlcdl_remotesite:
  Type: object
  Properties:
    system-id:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    db-endpoint:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_dbendpoint"
    kafka-server:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafkaserver"
      x-yang:
        Type: list
datapost_ciscosmicdlcdl_endpoint_1:
  Type: object
  Properties:
    key:
      Type: string
      Description: (leaf)
      Format: string
```

```
      x-yang:
        Type: leaf
    value:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
  Description: (presence)
datapost_ciscosmicdlcdl_slot_1_map:
  Type: object
  Properties:
    map-id:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
    key:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    value:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
datapost_ciscosmicdlcdl_slot_1:
  Type: object
  Properties:
    map:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_ciscosmicdlcdl_slot_1_map"
      x-yang:
        Type: list
  Description: (presence)
datapost_ciscosmicdlcdl_labelconfig:
  Type: object
  Properties:
    Name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    endpoint:
```

```
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_endpoint_1"
    slot:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_slot_1"
    index:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_slot_1"
datapost_ciscosmicdlcdl_externalsecretconfig_secretstore:
  Type: object
  Properties:
    Name:
      Type: string
      Description: Overrides common secret store name (leaf)
      Format: string
      x-yang:
        Type: leaf
    kind:
      Type: string
      Description: Overrides common secret store kind (leaf)
      Format: enumeration
      Default: SecretStore
      enum:
      - SecretStore
      - ClusterSecretStore
      x-yang:
        Type: leaf
    namespace:
      Type: string
      Description: Overrides common secret store namespace (leaf)
      Format: string
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_ciscosmicdlcdl_externalsecretconfig_remoteref:
  Type: object
  Properties:
    key:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    property:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_ciscosmicdlcdl_externalsecretconfig_data:
  Type: object
  Properties:
    secret-key:
      Type: string
```

```
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        remote-ref:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_remoteref"
    datapost_ciscosmicdlcdl_externalsecretconfig:
      Type: object
      Properties:
        Name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        namespace:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        target-secret:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        remote-key-path:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        refresh-interval:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf
        secret-store:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_secretstore"
        data:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_data"
          x-yang:
            Type: list
      Description: (non-presence)
```

```
datapost_ciscosmicdlcdl_sslconfig_autogeneration:
  Type: object
  Properties:
    enabled:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_ciscosmicdlcdl_sslconfig_remotecaauth_casecretnames:
  Type: object
  Properties:
    site-id:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    secret-name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
datapost_ciscosmicdlcdl_sslconfig_remotecaauth_caexternalsecrets:
  Type: object
  Properties:
    site-id:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    Name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    namespace:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    target-secret:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
```

```
        remote-key-path:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        refresh-interval:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf
        secret-store:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_secretstore"
        data:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_data"
          x-yang:
            Type: list
    datapost_ciscosmicdlcdl_sslconfig_remotecaauth:
      Type: object
      Properties:
        ca-secret-names:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_sslconfig_remotecaauth_casecretnames"
          x-yang:
            Type: list
        ca-external-secrets:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_sslconfig_remotecaauth_caexternalsecrets"
          x-yang:
            Type: list
      Description: (non-presence)
    datapost_ciscosmicdlcdl_sslconfig_certs:
      Type: object
      Properties:
        host:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

```
    ca-secret:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    tls-secret:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    ssl-key:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    ssl-crt:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    ssl-ca:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
datapost_ciscosmicdlcdl_sslconfig:
  Type: object
  Properties:
    enable:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    auto-generation:
     Reference: "#/components/schemas/datapost_ciscosmicdlcdl_sslconfig_autogeneration"
    tls-secret-name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    ca-secret-name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
```

```
        Type: leaf
      ca-external-secret:
       Reference: "#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig"

      remote-ca-auth:
       Reference: "#/components/schemas/datapost_ciscosmicdlcdl_sslconfig_remotecaauth"

      certs:
        Type: array
        Description: (list)
        Items:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_sslconfig_certs"
        x-yang:
          Type: list
    Description: (non-presence)
datapost_ciscosmicdlcdl_logging_logger:
  Type: object
  Properties:
    Name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    level:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: off
      enum:
      - off
      - error
      - warn
      - info
      - debug
      - trace
      x-yang:
        Type: leaf
datapost_ciscosmicdlcdl_logging:
  Type: object
  Properties:
    default-log-level:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: off
      enum:
      - off
      - error
      - warn
      - info
      - debug
      - trace
      x-yang:
```

```
            Type: leaf
          json-logging:
            Type: boolean
            Description: Enable or disable logging in json format. Example value: true
(leaf)
            x-yang:
              Type: leaf
          logger:
            Type: array
            Description: (list)
            Items:
              Reference: "#/components/schemas/datapost_ciscosmicdlcdl_logging_logger"
            x-yang:
              Type: list
          sync-logging:
            Type: boolean
            Description: (leaf)
            x-yang:
              Type: leaf
          error-stack:
            Type: boolean
            Description: (leaf)
            x-yang:
              Type: leaf
        Description: (non-presence)
      datapost_ciscosmicdlcdl_metrics:
        Type: object
        Properties:
          verbosity:
            Type: string
            Description: (leaf)
            Format: enumeration
            Default: production
            enum:
            - production
            - debug
            x-yang:
              Type: leaf
        Description: (non-presence)
      datapost_ciscosmicdlcdl_features_instanceawarenotification_systemid:
        Type: object
        Properties:
          id:
            Type: integer
            Description: (leaf)
            Format: uint32
            x-yang:
              Type: leaf
          slice-names:
            Type: array
            Items:
              Type: string
```

```
          Description: (leaf-list)
          Format: leafref
        x-yang:
          Type: leaf-list
    datapost_ciscosmicdlcdl_features_instanceawarenotification:
      Type: object
      Properties:
        enable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
        system-id:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_instanceawarenotification_systemid"
          x-yang:
            Type: list
      Description: (non-presence)
    datapost_ciscosmicdlcdl_features_slotstalesessiondetection:
      Type: object
      Properties:
        disable-auto-deletion:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
        notification-retry-count:
          Type: integer
          Description: (leaf)
          Format: byte
          x-yang:
            Type: leaf
      Description: (non-presence)
    datapost_ciscosmicdlcdl_features_overloadprotection:
      Type: object
      Properties:
        enable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
        index-max-record-count:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
        slot-max-record-count:
          Type: integer
```

```
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    slot-max-size:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    hard-limit-percentage:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    major-alert-threshold:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    critical-alert-threshold:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
  Description: (non-presence)

datapost_ciscosmicdlcdl_features_indexoverwritedetection_uniquekeysprefix:

  Type: object
  Properties:
    key-prefix:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    action:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: notify-record
      enum:
      - notify-record
      - log-record
      - delete-record
      x-yang:
        Type: leaf
datapost_ciscosmicdlcdl_features_indexoverwritedetection:
```

```
      Type: object
      Properties:
        unique-keys-prefix:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_indexoverwritedetection_uniquekeysprefix"

          x-yang:
            Type: list
        max-tps:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf
        queue-size:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf
      Description: (non-presence)

datapost_ciscosmicdlcdl_features_remotesiteconnectionmonitoring_clientsideloadbalancing:

      Type: object
      Properties:
        enable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
        wait-seconds-before-load-balancing:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
      Description: (non-presence)
    datapost_ciscosmicdlcdl_features_remotesiteconnectionmonitoring:
      Type: object
      Properties:
        enable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
        client-side-load-balancing:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_remotesiteconnectionmonitoring_clientsideloadbalancing"
```

```
      Description: (non-presence)
    datapost_ciscosmicdlcdl_features:
      Type: object
      Properties:
        instance-aware-notification:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_instanceawarenotification"
        slot-stale-session-detection:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_slotstalesessiondetection"
        overload-protection:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_overloadprotection"
        index-overwrite-detection:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_indexoverwritedetection"
        remote-site-connection-monitoring:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_features_remotesiteconnectionmonitoring"
      Description: (non-presence)
    datapost_ciscosmicdlcdl_overloadprotection:
      Type: object
      Properties:
        disable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
      Description: (non-presence)
    datapost_ciscosmicdlcdl_endpoint_2_settings:
      Type: object
      Properties:
        index-timeout-ms:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
        slot-timeout-ms:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
        remote-ep-connection-count:
          Type: integer
          Description: (leaf)
          Format: byte
          x-yang:
            Type: leaf
      Description: (non-presence)
    datapost_ciscosmicdlcdl_endpoint_2:
```

```
Type: object
Properties:
  patch-url:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
  go-debug:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
  go-max-procs:
    Type: integer
    Description: (leaf)
    Format: byte
    x-yang:
      Type: leaf
  cpu-request:
    Type: integer
    Description: (leaf)
    Format: uint32
    x-yang:
      Type: leaf
  cpu-limit:
    Type: integer
    Description: (leaf)
    Format: uint32
    x-yang:
      Type: leaf
  memory-request:
    Type: integer
    Description: (leaf)
    Format: uint32
    x-yang:
      Type: leaf
  memory-limit:
    Type: integer
    Description: (leaf)
    Format: uint32
    x-yang:
      Type: leaf
  replica:
    Type: integer
    Description: (leaf)
    Format: byte
    x-yang:
      Type: leaf
  copies-per-node:
```

```
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    settings:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_endpoint_2_settings"
    external-ip:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    external-ipv6:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    external-port:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_ciscosmicdlcdl_index_1:
  Type: object
  Properties:
    patch-url:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    go-debug:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    go-max-procs:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    cpu-request:
      Type: integer
      Description: (leaf)
      Format: uint32
```

```
      x-yang:
        Type: leaf
    cpu-limit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    memory-request:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    memory-limit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    replica:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    prev-map-count:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
    map:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
    write-factor:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_ciscosmicdlcdl_slot_2_notification_endpoints:
  Type: object
  Properties:
    slice-name:
      Type: string
      Description: (leaf)
```

```
      Format: leafref
      x-yang:
        Type: leaf
    app-instance-id:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
    host:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    port:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
datapost_ciscosmicdlcdl_slot_2_notification:
  Type: object
  Properties:
    connection-count:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    dynamic-provisioning:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    host:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    port:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
    limit:
      Type: integer
      Description: (leaf)
      Format: uint32
```

```
      x-yang:
        Type: leaf
    max-concurrent-bulk-notifications:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    bulk-task-progress-update-batch-size:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    notification-retry-seconds:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    include-conflict-data:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    remote-system-id:
      Type: array
      Items:
        Type: string
        Description: (leaf-list)
        Format: leafref
      x-yang:
        Type: leaf-list
    use-stream:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    include-slice-in-header:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    endpoints:
      Type: array
      Description: (list)
      Items:
        Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_slot_2_notification_endpoints"
      x-yang:
        Type: list
  Description: (non-presence)
```

```
datapost_ciscosmicdlcdl_slot_2_metrics:
  Type: object
  Properties:
    report-idle-session-type:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_ciscosmicdlcdl_slot_2:
  Type: object
  Properties:
    patch-url:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    go-debug:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    go-max-procs:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    cpu-request:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    cpu-limit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    memory-request:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    memory-limit:
      Type: integer
      Description: (leaf)
```

```
      Format: uint32
      x-yang:
        Type: leaf
    replica:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    map:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
    write-factor:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    notification:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_slot_2_notification"
    metrics:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_slot_2_metrics"
  Description: (non-presence)
datapost_ciscosmicdlcdl_test:
  Type: object
  Properties:
    run:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    patch-url:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    loop:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    txns:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
```

```
        Type: leaf
      txn-type:
        Type: integer
        Description: (leaf)
        Format: uint16
        x-yang:
          Type: leaf
      wait-time-ns:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      max-non-unique-keys:
        Type: integer
        Description: (leaf)
        Format: byte
        x-yang:
          Type: leaf
    Description: (non-presence)
datapost_ciscosmicdlcdl_datastore:
    Type: object
    Properties:
      Name:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
      cluster-id:
        Type: integer
        Description: (leaf)
        Format: byte
        x-yang:
          Type: leaf
      label-config:
        Type: string
        Description: (leaf)
        Format: leafref
        x-yang:
          Type: leaf
      geo-remote-site:
        Type: array
        Items:
          Type: string
          Description: (leaf-list)
          Format: leafref
        x-yang:
          Type: leaf-list
      mode:
        Type: string
```

```
      Description: (leaf)
      Format: enumeration
      Default: regular
      enum:
      - regular
      - scale-up
      x-yang:
        Type: leaf
    slice-names:
      Type: array
      Items:
        Type: string
        Description: (leaf-list)
        Format: string
      x-yang:
        Type: leaf-list
    advanced-config-profile:
      Type: string
      Description: (leaf)
      Format: leafref
      x-yang:
        Type: leaf
    find-by-nuk-prefixes:
      Type: array
      Items:
        Type: string
        Description: (leaf-list)
        Format: string
      x-yang:
        Type: leaf-list
    metrics:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_metrics"
    features:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_features"
    overload-protection:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_overloadprotection"
    endpoint:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_endpoint_2"
    index:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_index_1"
    slot:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_slot_2"
    test:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_test"
datapost_ciscosmicdlcdl_zookeeper:
  Type: object
  Properties:
    data-storage-size:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
```

```
        Type: leaf
      log-storage-size:
        Type: integer
        Description: (leaf)
        Format: byte
        x-yang:
          Type: leaf
      log-level:
        Type: string
        Description: (leaf)
        Format: enumeration
        Default: fatal
        enum:
        - fatal
        - error
        - warn
        - info
        - debug
        - trace
        x-yang:
          Type: leaf
      replica:
        Type: integer
        Description: (leaf)
        Format: byte
        x-yang:
          Type: leaf
      enable-JMX-metrics:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
      enable-persistence:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
      enable-parallel-pod-management:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_ciscosmicdlcdl_kafka_resource:
    Type: object
    Properties:
      cpu-request:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      cpu-limit:
```

```
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    memory-request:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    memory-limit:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_ciscosmicdlcdl_kafka_externalip:
  Type: object
  Properties:
    ip:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    port:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
    ssl-port:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
datapost_ciscosmicdlcdl_kafka_sslsettings:
  Type: object
  Properties:
    enable-ssl:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    disable-host-name-verification:
      Type: boolean
      Description: (leaf)
      x-yang:
```

```
        Type: leaf
      auto-generation:
       Reference: "#/components/schemas/datapost_ciscosmicdlcdl_sslconfig_autogeneration"

      broker-tls-secret-name:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
      broker-ca-secret-name:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
      broker-ca-external-secret:
        Reference: "#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig"

    Description: (non-presence)
  datapost_ciscosmicdlcdl_kafka_logcompaction:
    Type: object
    Properties:
      disable:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
      delete-retention-ms:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_ciscosmicdlcdl_kafka_controller_heapoptions:
    Type: object
    Properties:
      min-heap-size-mb:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      max-heap-size-mb:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
    Description: (non-presence)
  datapost_ciscosmicdlcdl_kafka_controller:
```

```
      Type: object
      Properties:
        replica:
          Type: integer
          Description: (leaf)
          Format: byte
          x-yang:
            Type: leaf
        log-level:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: fatal
          enum:
          - fatal
          - error
          - warn
          - info
          - debug
          - trace
          x-yang:
            Type: leaf
        heap-options:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_kafka_controller_heapoptions"
        resource:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_resource"
      Description: (non-presence)
    datapost_ciscosmicdlcdl_kafka:
      Type: object
      Properties:
        replica:
          Type: integer
          Description: (leaf)
          Format: byte
          x-yang:
            Type: leaf
        mode:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: zookeeper
          enum:
          - zookeeper
          - kraft
          x-yang:
            Type: leaf
        kraft-migration:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: disabled
          enum:
```

```
  - disabled
  - enabled
  - finalized
  x-yang:
    Type: leaf
replication-factor:
  Type: integer
  Description: (leaf)
  Format: byte
  x-yang:
    Type: leaf
log-level:
  Type: string
  Description: (leaf)
  Format: enumeration
  Default: fatal
  enum:
  - fatal
  - error
  - warn
  - info
  - debug
  - trace
  x-yang:
    Type: leaf
partition:
  Type: integer
  Description: (leaf)
  Format: uint16
  x-yang:
    Type: leaf
enable-JMX-metrics:
  Type: boolean
  Description: (leaf)
  x-yang:
    Type: leaf
resource:
  Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_resource"
external-ip:
  Type: array
  Description: (list)
  Items:
    Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_externalip"
  x-yang:
    Type: list
external-ipv6:
  Type: array
  Description: (list)
  Items:
    Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_externalip"
  x-yang:
    Type: list
enable-persistence:
```

```
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    storage:
      Type: integer
      Description: (leaf)
      Format: uint16
      x-yang:
        Type: leaf
    ssl-settings:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_sslsettings"
    retention-time:
      Type: integer
      Description: (leaf)
      Format: int16
      x-yang:
        Type: leaf
    retention-size:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
        Type: leaf
    log-compaction:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_logcompaction"
    disable-unclean-leader-election:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    label-config:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_endpoint_1"
    controller:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_controller"
    enable-parallel-pod-management:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    heap-options:
      Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_kafka_controller_heapoptions"
    describe:
      Type: object
      Properties: {}
      Description: (non-presence)
      x-yang:
        Type: container
        is_presence: false
    list:
      Type: object
```

```
      Properties: {}
      Description: (non-presence)
      x-yang:
        Type: container
        is_presence: false
    reset-offsets:
      Type: object
      Properties: {}
      Description: (non-presence)
      x-yang:
        Type: container
        is_presence: false
    reset-offsets-dry-run:
      Type: object
      Properties: {}
      Description: (non-presence)
      x-yang:
        Type: container
        is_presence: false
  Description: (non-presence)
datapost_ciscosmicdlcdl_mirrormaker_ssl_brokercaexternalsecrets:
  Type: object
  Properties:
    Name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    namespace:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    target-secret:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    remote-key-path:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    refresh-interval:
      Type: integer
      Description: (leaf)
      Format: uint16
```

```
          x-yang:
            Type: leaf
        secret-store:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_secretstore"
        data:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig_data"
          x-yang:
            Type: list
    datapost_ciscosmicdlcdl_mirrormaker_ssl:
      Type: object
      Properties:
        broker-ca-secret-names:
          Type: array
          Items:
            Type: string
            Description: (leaf-list)
            Format: string
          x-yang:
            Type: leaf-list
        broker-ca-external-secrets:
          Type: array
          Description: (list)
          Items:
            Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_ssl_brokercaexternalsecrets"
          x-yang:
            Type: list
      Description: (non-presence)
    datapost_ciscosmicdlcdl_mirrormaker_slot_settings_producerproperties:
      Type: object
      Properties:
        batch-size:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf
        linger-ms:
          Type: integer
          Description: (leaf)
          Format: int64
          x-yang:
            Type: leaf
        receive-buffer-bytes:
          Type: integer
          Description: (leaf)
          Format: int64
```

```
      x-yang:
        Type: leaf
    send-buffer-bytes:
      Type: integer
      Description: (leaf)
      Format: int64
      x-yang:
        Type: leaf
    max-request-size:
      Type: integer
      Description: (leaf)
      Format: int64
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_ciscosmicdlcdl_mirrormaker_slot_settings_consumerproperties:
  Type: object
  Properties:
    receive-buffer-bytes:
      Type: integer
      Description: (leaf)
      Format: int64
      x-yang:
        Type: leaf
    send-buffer-bytes:
      Type: integer
      Description: (leaf)
      Format: int64
      x-yang:
        Type: leaf
    max-poll-records:
      Type: integer
      Description: (leaf)
      Format: int64
      x-yang:
        Type: leaf
    max-partition-fetch-bytes:
      Type: integer
      Description: (leaf)
      Format: int64
      x-yang:
        Type: leaf
  Description: (non-presence)
datapost_ciscosmicdlcdl_mirrormaker_slot_settings:
  Type: object
  Properties:
    tasks-max:
      Type: integer
      Description: (leaf)
      Format: int32
      x-yang:
```

```
          Type: leaf
        producer-properties:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_slot_settings_producerproperties"

        consumer-properties:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_slot_settings_consumerproperties"

      Description: (non-presence)
    datapost_ciscosmicdlcdl_mirrormaker_slot:
      Type: object
      Properties:
        replicas:
          Type: integer
          Description: (leaf)
          Format: byte
          x-yang:
            Type: leaf
        replication-factor:
          Type: integer
          Description: (leaf)
          Format: byte
          x-yang:
            Type: leaf
        settings:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_slot_settings"
        resource:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka_resource"
        heap-options:
          Reference:
"#/components/schemas/datapost_ciscosmicdlcdl_kafka_controller_heapoptions"
      Description: (non-presence)
    datapost_ciscosmicdlcdl_mirrormaker:
      Type: object
      Properties:
        log-level:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: fatal
          enum:
          - fatal
          - error
          - warn
          - info
          - debug
          - trace
          x-yang:
            Type: leaf
        enable-JMX-metrics:
          Type: boolean
          Description: (leaf)
```

```
      x-yang:
        Type: leaf
    ssl:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_ssl"
    slot:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_slot"
    index:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker_slot"
  Description: (non-presence)
datapost_ciscosmicdlcdl_show_sessions:
  Type: object
  Properties:
    count:
      Type: object
      Properties: {}
      Description: (non-presence)
      x-yang:
        Type: container
        is_presence: false
  Description: (non-presence)
datapost_ciscosmicdlcdl_show:
  Type: object
  Properties:
    sessions:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_show_sessions"
  Description: (non-presence)
datapost_ciscosmicdlcdl_actions:
  Type: object
  Properties:
    remote-index-sync:
      Type: object
      Properties: {}
      Description: (non-presence)
      x-yang:
        Type: container
        is_presence: false
    backup:
      Type: object
      Properties: {}
      Description: (non-presence)
      x-yang:
        Type: container
        is_presence: false
    restore:
      Type: object
      Properties: {}
      Description: (non-presence)
      x-yang:
        Type: container
        is_presence: false
  Description: (non-presence)
```

```
datapost_ciscosmicdlcdl_networkpolicy:
  Type: object
  Properties:
    enable:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
  Description: (presence)
datapost_ciscosmicdlcdl:
  Type: object
  Properties:
    repository:
      Type: string
      Description: (leaf)
      Format: leafref
      x-yang:
        Type: leaf
    system-id:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
    node-type:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    enable-geo-replication:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    use-rust-image:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    deployment-model:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: large
      enum:
      - large
      - small
      x-yang:
        Type: leaf
    api:
      Reference: "#/components/schemas/datapost_ciscosmicdlcdl_api"
```

```
advanced-config-profile:
  Type: array
  Description: (list)
  Items:
  Reference: "#/components/schemas/datapost_ciscosmicdlcdl_advancedconfigprofile"

  x-yang:
    Type: list
remote-site:
  Type: array
  Description: (list)
  Items:
    Reference: "#/components/schemas/datapost_ciscosmicdlcdl_remotesite"
  x-yang:
    Type: list
label-config:
  Type: array
  Description: (list)
  Items:
    Reference: "#/components/schemas/datapost_ciscosmicdlcdl_labelconfig"
  x-yang:
    Type: list
external-secret-config:
  Reference: "#/components/schemas/datapost_ciscosmicdlcdl_externalsecretconfig"

ssl-config:
  Reference: "#/components/schemas/datapost_ciscosmicdlcdl_sslconfig"
logging:
  Reference: "#/components/schemas/datapost_ciscosmicdlcdl_logging"
datastore:
  Type: array
  Description: (list)
  Items:
    Reference: "#/components/schemas/datapost_ciscosmicdlcdl_datastore"
  x-yang:
    Type: list
zookeeper:
  Reference: "#/components/schemas/datapost_ciscosmicdlcdl_zookeeper"
kafka:
  Reference: "#/components/schemas/datapost_ciscosmicdlcdl_kafka"
mirror-maker:
  Reference: "#/components/schemas/datapost_ciscosmicdlcdl_mirrormaker"
show:
  Reference: "#/components/schemas/datapost_ciscosmicdlcdl_show"
clear:
  Type: object
  Properties: {}
  Description: (non-presence)
  x-yang:
    Type: container
    is_presence: false
actions:
```

```
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_actions"
        network-policy:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl_networkpolicy"
        rebalance-index:
          Type: object
          Properties: {}
          Description: (non-presence)
          x-yang:
            Type: container
            is_presence: false
      Description: Configure cdl parameters for deployment. If cdl container is not
configured, the cdl chart
        wont be deployed (presence)
    dataputpatch_ietfrestconfdata:
      Type: object
      Properties:
        cisco-smi-cdl:feature-gates:
          Reference: "#/components/schemas/datapost_ciscosmicdlfeaturegates"
        cisco-smi-cdl:cdl:
          Reference: "#/components/schemas/datapost_ciscosmicdlcdl"
      Description:
    root_ietfrestconfrestconf:
      Type: object
      Properties:
        data:
          Type: object
          Properties: {}
        operations:
          Type: object
          Properties: {}
        yang-library-version:
          Type: string
      Description: This is the RESTCONF root resource for the RESTCONF datastore and
operation resources. See
        RESTCONF RFC 8040 for further information.
  Responses:
    "200":
      Description: OK
      Content: {}
    "201":
      Description: Created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  Parameters:
    Content:
      Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    depth:
      Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    fields:
      Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    filter:
      Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: string
    Format: string
with-defaults:
  Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
insert:
  Name: insert
  In: query
  Description: controlling the order when adding new list elements
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: first
    enum:
    - first
    - last
    - before
    - after
point:
  Name: point
  In: query
  Description: used to specify the insertion point
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
advanced-config-profile-name:
  Name: advanced-config-profile-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
```

```
broker-ca-external-secrets-name:
  Name: broker-ca-external-secrets-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
broker-ca-secret-names-id:
  Name: broker-ca-secret-names-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
ca-external-secrets-site-id:
  Name: ca-external-secrets-site-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
ca-secret-names-site-id:
  Name: ca-secret-names-site-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
certs-host:
  Name: certs-host
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
data-secret-key:
  Name: data-secret-key
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
```

```
    Schema:
      Type: string
      Format: string
  datastore-name:
    Name: datastore-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  endpoints-app-instance-id:
    Name: endpoints-app-instance-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  endpoints-slice-name:
    Name: endpoints-slice-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  external-ip-ip:
    Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  external-ip-port:
    Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  external-ipv6-ip:
    Name: external-ipv6-ip
    In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  external-ipv6-port:
    Name: external-ipv6-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  find-by-nuk-prefixes-id:
    Name: find-by-nuk-prefixes-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  geo-remote-site-id:
    Name: geo-remote-site-id
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: leafref
  kafka-server-host:
    Name: kafka-server-host
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  kafka-server-port:
    Name: kafka-server-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
```

```
label-config-name:
  Name: label-config-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
logger-name:
  Name: logger-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
map-map-id:
  Name: map-map-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
remote-site-system-id:
  Name: remote-site-system-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint32
remote-system-id-id:
  Name: remote-system-id-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: leafref
slice-names-id:
  Name: slice-names-id
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
```

```
      Schema:
        Type: string
        Format: string
    system-id-id:
      Name: system-id-id
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint32
    unique-keys-prefix-key-prefix:
      Name: unique-keys-prefix-key-prefix
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
  requestBodies:
    data-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data-post"
      Required/Optional: true
    data-put-patch:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data-put-patch"
      Required/Optional: true
    data_cisco-smi-cdl_cdl:
      Description: Configure cdl parameters for deployment. If cdl container is not
configured, the cdl chart
        wont be deployed
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl"
      Required/Optional: true
    data_cisco-smi-cdl_cdl-post:
      Description: Configure cdl parameters for deployment. If cdl container is not
configured, the cdl chart
        wont be deployed
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl-post"
      Required/Optional: true
```

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name"

Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint"

Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint-post:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint-post"

Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_index-timeout:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_index-timeout"

Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_max-concurrent-operations:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_max-concurrent-operations"

Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_operation-timeout:

Content:
application/yang-data+json:
Schema:

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_operation-timeout"

      Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_read-queue-size:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_read-queue-size"

      Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_read-response-queue-size:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_read-response-queue-size"

      Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_read-worker-count:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_read-worker-count"

      Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_remote-ep-connection-count:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_remote-ep-connection-count"

      Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_slot-timeout:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_slot-timeout"

      Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_write-queue-size:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_write-queue-size"

      Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_write-response-queue-size:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_write-response-queue-size"

      Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_write-worker-count:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_endpoint_write-worker-count"

      Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index"

      Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index-post"

      Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index_audit:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index_audit"
```

```
      Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index_audit-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index_audit-post"

      Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index_audit_record-expiry-duration:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index_audit_record-expiry-duration"

      Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index_init-record-count:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_index_init-record-count"

      Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_name:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_name"

      Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_slot:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_slot"

      Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_slot-post:

      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_slot-post"

      Required/Optional: true

data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_slot_init-record-count:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_advanced-config-profile_advanced-config-profile-name_slot_init-record-count"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_api:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_api-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api-post"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_api_cpu-limit:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_cpu-limit"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_api_deploy:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_deploy"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_api_external-ip:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_external-ip"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_api_go-max-procs:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_go-max-procs"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_api_memory-limit:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_memory-limit"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_api_storage:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_api_storage"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name"
      Required/Optional: true
   data_cisco-smi-cdl_cdl_datastore_datastore-name_advanced-config-profile:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_advanced-config-profile"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_cluster-id:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_cluster-id"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint-post"
      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_copies-per-node:

      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_copies-per-node"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_cpu-limit:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_cpu-limit"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_cpu-request:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_cpu-request"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_external-ip:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_external-ip"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_external-ipv6:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_external-ipv6"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_external-port:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_external-port"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_go-debug:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_go-debug"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_go-max-procs:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_go-max-procs"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_memory-limit:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_memory-limit"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_memory-request:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_memory-request"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_patch-url:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_patch-url"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_replica:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_replica"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings-post"
```

```
      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings_index-timeout-ms:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings_index-timeout-ms"

      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings_remote-ep-connection-count:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings_remote-ep-connection-count"

      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings_slot-timeout-ms:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_endpoint_settings_slot-timeout-ms"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_features:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_features-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features-post"
      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection"
```

Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection-post:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection-post"

Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_max-tps:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_max-tps"

Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_queue-size:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_queue-size"

Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_unique-keys-prefix_unique-keys-prefix-key-prefix:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_unique-keys-prefix_unique-keys-prefix-key-prefix"

Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_unique-keys-prefix_unique-keys-prefix-key-prefix_action:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_unique-keys-prefix_unique-keys-prefix-key-prefix_action"

Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_unique-keys-prefix_unique-keys-prefix-key-prefix_key-prefix:

Content:
application/yang-data+json:

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_index-overwrite-detection_unique-keys-prefix_unique-keys-prefix-key-prefix_key-prefix"

      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification"

      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification-post"

      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_enable:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_enable"

      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_system-id_system-id-id:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_system-id_system-id-id"

      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_system-id_system-id-id_id:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_system-id_system-id-id_id"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_system-id_system-id-id_slice-names_slice-names-id:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_instance-aware-notification_system-id_system-id-id_slice-names_slice-names-id"

Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection"

Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection-post:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection-post"

Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_critical-alert-threshold:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_critical-alert-threshold"

Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_enable:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_enable"

Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_hard-limit-percentage:

Content:
application/yang-data+json:
Schema:
Reference:

"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_hard-limit-percentage"

Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_index-max-record-count:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_index-max-record-count"

Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_major-alert-threshold:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_major-alert-threshold"

Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_slot-max-record-count:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_slot-max-record-count"

Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_slot-max-size:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_overload-protection_slot-max-size"

Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring"

Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring-post:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring-post"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_client-side-load-balancing:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_client-side-load-balancing"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_client-side-load-balancing-post:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_client-side-load-balancing-post"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_client-side-load-balancing_enable:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_client-side-load-balancing_enable"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_client-side-load-balancing_wait-seconds-before-load-balancing:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_client-side-load-balancing_wait-seconds-before-load-balancing"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_enable:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_remote-site-connection-monitoring_enable"
```

```
      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_slot-stale-session-detection:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_slot-stale-session-detection"

      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_slot-stale-session-detection-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_slot-stale-session-detection-post"

      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_slot-stale-session-detection_disable-auto-deletion:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_slot-stale-session-detection_disable-auto-deletion"

      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_features_slot-stale-session-detection_notification-retry-count:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_features_slot-stale-session-detection_notification-retry-count"

      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_find-by-nuk-prefixes_find-by-nuk-prefixes-id:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_find-by-nuk-prefixes_find-by-nuk-prefixes-id"

      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_geo-remote-site_geo-remote-site-id:

      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_geo-remote-site_geo-remote-site-id"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_index:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_index-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index-post"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_index_cpu-limit:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_cpu-limit"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_index_cpu-request:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_cpu-request"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_index_go-debug:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_go-debug"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_index_go-max-procs:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_go-max-procs"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_index_map:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_map"
```

```
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_index_memory-limit:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_memory-limit"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_index_memory-request:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_memory-request"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_index_patch-url:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_patch-url"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_index_prev-map-count:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_prev-map-count"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_index_replica:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_replica"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_index_write-factor:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_index_write-factor"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_label-config:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_label-config"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_metrics:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_metrics"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_metrics-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_metrics-post"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_metrics_verbosity:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_metrics_verbosity"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_mode:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_mode"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_name:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_name"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_overload-protection:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_overload-protection"
      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_overload-protection-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_overload-protection-post"

      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_overload-protection_disable:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_overload-protection_disable"

      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_slice-names_slice-names-id:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slice-names_slice-names-id"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_slot:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_slot-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot-post"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_cpu-limit:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_cpu-limit"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_cpu-request:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_cpu-request"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_go-debug:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_go-debug"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_go-max-procs:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_go-max-procs"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_map:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_map"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_memory-limit:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_memory-limit"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_memory-request:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_memory-request"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_metrics:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_metrics"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_metrics-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_metrics-post"
      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_metrics_report-idle-session-type:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_metrics_report-idle-session-type"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification"
      Required/Optional: true
   data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification-post"

      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_bulk-task-progress-update-batch-size:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_bulk-task-progress-update-batch-size"

      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_connection-count:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_connection-count"

      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_dynamic-provisioning:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_dynamic-provisioning"

      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id"

      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_app-instance-id:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_app-instance-id"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_host:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_host"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_port:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_port"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_slice-name:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_endpoints_endpoints-slice-name_endpoints-app-instance-id_slice-name"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_host:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_host"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_include-conflict-data:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_include-conflict-data"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_include-slice-in-header:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_include-slice-in-header"

Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_limit:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_limit"

Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_max-concurrent-bulk-notifications:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_max-concurrent-bulk-notifications"

Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_notification-retry-seconds:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_notification-retry-seconds"

Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_port:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_port"

Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_remote-system-id_remote-system-id-id:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_remote-system-id_remote-system-id-id"

```
      Required/Optional: true

data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_use-stream:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_notification_use-stream"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_patch-url:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_patch-url"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_replica:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_replica"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_write-factor:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_slot_write-factor"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_test:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_test-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test-post"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_test_loop:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_loop"
      Required/Optional: true
```

```
data_cisco-smi-cdl_cdl_datastore_datastore-name_test_max-non-unique-keys:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_max-non-unique-keys"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_test_patch-url:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_patch-url"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_test_run:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_run"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_test_txn-type:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_txn-type"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_test_txns:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_txns"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_datastore_datastore-name_test_wait-time-ns:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_datastore_datastore-name_test_wait-time-ns"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_deployment-model:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_deployment-model"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_enable-geo-replication:
      Content:
```

```
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_enable-geo-replication"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_external-secret-config:
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_external-secret-config-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config-post"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key"
      Required/Optional: true

data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_remote-ref:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_remote-ref"

      Required/Optional: true

data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_remote-ref-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_remote-ref-post"

      Required/Optional: true

data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_remote-ref_key:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_remote-ref_key"
```

```
      Required/Optional: true

data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_remote-ref_property:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_remote-ref_property"

      Required/Optional: true

data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_secret-key:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_data_data-secret-key_secret-key"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_external-secret-config_name:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_name"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_external-secret-config_namespace:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_namespace"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_external-secret-config_refresh-interval:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_refresh-interval"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_external-secret-config_remote-key-path:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_remote-key-path"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_external-secret-config_secret-store:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

```
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_secret-store"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_external-secret-config_secret-store-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_secret-store-post"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_external-secret-config_secret-store_kind:
      Description: Overrides common secret store kind
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_secret-store_kind"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_external-secret-config_secret-store_name:
      Description: Overrides common secret store name
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_secret-store_name"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_external-secret-config_secret-store_namespace:
      Description: Overrides common secret store namespace
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_secret-store_namespace"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_external-secret-config_target-secret:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_external-secret-config_target-secret"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka-post"
      Required/Optional: true
```

```
    data_cisco-smi-cdl_cdl_kafka_controller:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_controller-post:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller-post"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_controller_heap-options:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_heap-options"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_controller_heap-options-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_heap-options-post"
      Required/Optional: true
   data_cisco-smi-cdl_cdl_kafka_controller_heap-options_max-heap-size-mb:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_heap-options_max-heap-size-mb"

      Required/Optional: true
   data_cisco-smi-cdl_cdl_kafka_controller_heap-options_min-heap-size-mb:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_heap-options_min-heap-size-mb"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_controller_log-level:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_log-level"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_controller_replica:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_replica"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_controller_resource:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_resource"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_controller_resource-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_resource-post"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_controller_resource_cpu-limit:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_resource_cpu-limit"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_controller_resource_cpu-request:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_resource_cpu-request"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_controller_resource_memory-limit:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_resource_memory-limit"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_controller_resource_memory-request:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_controller_resource_memory-request"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_describe:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_describe"
```

```
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_describe-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_describe-post"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_disable-unclean-leader-election:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_disable-unclean-leader-election"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_enable-JMX-metrics:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_enable-JMX-metrics"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_enable-parallel-pod-management:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_enable-parallel-pod-management"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_enable-persistence:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_enable-persistence"
      Required/Optional: true

data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port"

      Required/Optional: true

data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port_ip:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port_ip"
```

```
      Required/Optional: true

data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port_port:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port_port"

      Required/Optional: true

data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port_ssl-port:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ip_external-ip-ip_external-ip-port_ssl-port"

      Required/Optional: true

data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port"

      Required/Optional: true

data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port_ip:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port_ip"

      Required/Optional: true

data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port_port:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port_port"

      Required/Optional: true

data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port_ssl-port:

      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_external-ipv6_external-ipv6-ip_external-ipv6-port_ssl-port"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_heap-options:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_heap-options"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_heap-options-post:
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_heap-options-post"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_heap-options_max-heap-size-mb:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_heap-options_max-heap-size-mb"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_heap-options_min-heap-size-mb:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_heap-options_min-heap-size-mb"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_kraft-migration:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_kraft-migration"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_label-config:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_label-config"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_label-config-post:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_label-config-post"

      Required/Optional: true
```

```
    data_cisco-smi-cdl_cdl_kafka_label-config_key:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_label-config_key"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_label-config_value:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_label-config_value"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_list:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_list"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_list-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_list-post"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_log-compaction:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_log-compaction"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_log-compaction-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_log-compaction-post"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_log-compaction_delete-retention-ms:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_log-compaction_delete-retention-ms"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_log-compaction_disable:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_log-compaction_disable"
```

```
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_log-level:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_log-level"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_mode:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_mode"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_partition:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_partition"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_replica:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_replica"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_replication-factor:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_replication-factor"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_reset-offsets:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_reset-offsets"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_reset-offsets-dry-run:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_reset-offsets-dry-run"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_reset-offsets-dry-run-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_reset-offsets-dry-run-post"
```

```
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_reset-offsets-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_reset-offsets-post"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_resource:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_resource"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_resource-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_resource-post"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_resource_cpu-limit:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_resource_cpu-limit"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_resource_cpu-request:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_resource_cpu-request"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_resource_memory-limit:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_resource_memory-limit"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_resource_memory-request:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_resource_memory-request"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_retention-size:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_retention-size"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_retention-time:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_retention-time"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_ssl-settings:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_ssl-settings-post:
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings-post"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_ssl-settings_auto-generation:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_auto-generation"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_ssl-settings_auto-generation-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_auto-generation-post"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_ssl-settings_auto-generation_enabled:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_auto-generation_enabled"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret"
      Required/Optional: true

    data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret-post:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret-post"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_remote-ref:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_remote-ref"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_remote-ref-post:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_remote-ref-post"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_remote-ref_key:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_remote-ref_key"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_remote-ref_property:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_remote-ref_property"
```

```
      Required/Optional: true

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_secret-key:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_data_data-secret-key_secret-key"

      Required/Optional: true

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_name:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_name"

      Required/Optional: true

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_namespace:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_namespace"

      Required/Optional: true

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_refresh-interval:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_refresh-interval"

      Required/Optional: true

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_remote-key-path:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_remote-key-path"

      Required/Optional: true

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store:

      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store"

      Required/Optional: true

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store-post"

      Required/Optional: true

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store_kind:

      Description: Overrides common secret store kind
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store_kind"

      Required/Optional: true

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store_name:

      Description: Overrides common secret store name
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store_name"

      Required/Optional: true

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store_namespace:

      Description: Overrides common secret store namespace
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_secret-store_namespace"

      Required/Optional: true

data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_target-secret:

      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-external-secret_target-secret"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-secret-name:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-ca-secret-name"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-tls-secret-name:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_broker-tls-secret-name"
      Required/Optional: true

data_cisco-smi-cdl_cdl_kafka_ssl-settings_disable-host-name-verification:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_disable-host-name-verification"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_ssl-settings_enable-ssl:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_kafka_ssl-settings_enable-ssl"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_kafka_storage:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_kafka_storage"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_label-config_label-config-name:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_label-config_label-config-name_endpoint:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_endpoint"
```

```
      Required/Optional: true
    data_cisco-smi-cdl_cdl_label-config_label-config-name_endpoint-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_endpoint-post"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_label-config_label-config-name_endpoint_key:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_endpoint_key"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_label-config_label-config-name_endpoint_value:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_endpoint_value"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_label-config_label-config-name_index:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_index"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_label-config_label-config-name_index-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_index-post"
      Required/Optional: true

data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id"

      Required/Optional: true

data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id_key:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id_key"

Required/Optional: true

data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id_map-id:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id_map-id"

Required/Optional: true

data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id_value:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_index_map_map-map-id_value"

Required/Optional: true
data_cisco-smi-cdl_cdl_label-config_label-config-name_name:
Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_name"
Required/Optional: true
data_cisco-smi-cdl_cdl_label-config_label-config-name_slot:
Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_slot"
Required/Optional: true
data_cisco-smi-cdl_cdl_label-config_label-config-name_slot-post:
Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_slot-post"
Required/Optional: true

data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id"

Required/Optional: true

```
data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id_key:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id_key"
      Required/Optional: true
data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id_map-id:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id_map-id"
      Required/Optional: true
data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id_value:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_label-config_label-config-name_slot_map_map-map-id_value"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_logging:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_logging"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_logging-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_logging-post"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_logging_default-log-level:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_logging_default-log-level"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_logging_error-stack:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_logging_error-stack"
```

```
      Required/Optional: true
    data_cisco-smi-cdl_cdl_logging_json-logging:
      Description: Enable or disable logging in json format. Example value: true
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_logging_json-logging"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_logging_logger_logger-name:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_logging_logger_logger-name"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_logging_logger_logger-name_level:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_logging_logger_logger-name_level"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_logging_logger_logger-name_name:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_logging_logger_logger-name_name"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_logging_sync-logging:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_logging_sync-logging"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker-post"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_enable-JMX-metrics:
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_enable-JMX-metrics"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_index:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_index-post:
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index-post"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_index_heap-options:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_heap-options"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_index_heap-options-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_heap-options-post"
      Required/Optional: true
   data_cisco-smi-cdl_cdl_mirror-maker_index_heap-options_max-heap-size-mb:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_heap-options_max-heap-size-mb"

      Required/Optional: true
   data_cisco-smi-cdl_cdl_mirror-maker_index_heap-options_min-heap-size-mb:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_heap-options_min-heap-size-mb"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_index_replicas:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_replicas"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_index_replication-factor:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_replication-factor"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_index_resource:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_resource"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_index_resource-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_resource-post"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_index_resource_cpu-limit:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_resource_cpu-limit"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_index_resource_cpu-request:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_resource_cpu-request"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_index_resource_memory-limit:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_resource_memory-limit"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_index_resource_memory-request:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_resource_memory-request"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_index_settings:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_index_settings-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings-post"
      Required/Optional: true
   data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties-post"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_max-partition-fetch-bytes:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_max-partition-fetch-bytes"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_max-poll-records:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_max-poll-records"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_receive-buffer-bytes:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_receive-buffer-bytes"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_send-buffer-bytes:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_consumer-properties_send-buffer-bytes"

      Required/Optional: true
   data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties-post"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_batch-size:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_batch-size"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_linger-ms:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_linger-ms"

      Required/Optional: true
```

```
data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_max-request-size:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_max-request-size"
      Required/Optional: true
data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_receive-buffer-bytes:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_receive-buffer-bytes"
      Required/Optional: true
data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_send-buffer-bytes:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_producer-properties_send-buffer-bytes"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_index_settings_tasks-max:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_index_settings_tasks-max"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_log-level:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_log-level"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_slot:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_slot-post:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot-post"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_slot_heap-options:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_heap-options"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_slot_heap-options-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_heap-options-post"
      Required/Optional: true
   data_cisco-smi-cdl_cdl_mirror-maker_slot_heap-options_max-heap-size-mb:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_heap-options_max-heap-size-mb"

      Required/Optional: true
   data_cisco-smi-cdl_cdl_mirror-maker_slot_heap-options_min-heap-size-mb:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_heap-options_min-heap-size-mb"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_slot_replicas:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_replicas"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_slot_replication-factor:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_replication-factor"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_slot_resource:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

```
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_resource"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_slot_resource-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_resource-post"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_cpu-limit:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_cpu-limit"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_cpu-request:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_cpu-request"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_memory-limit:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_memory-limit"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_memory-request:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_resource_memory-request"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_slot_settings:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_slot_settings-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings-post"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties-post"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_max-partition-fetch-bytes:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_max-partition-fetch-bytes"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_max-poll-records:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_max-poll-records"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_receive-buffer-bytes:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_receive-buffer-bytes"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_send-buffer-bytes:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_consumer-properties_send-buffer-bytes"
```

```
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties-post"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_batch-size:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_batch-size"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_linger-ms:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_linger-ms"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_max-request-size:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_max-request-size"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_receive-buffer-bytes:

      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_receive-buffer-bytes"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_send-buffer-bytes:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_producer-properties_send-buffer-bytes"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_tasks-max:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_slot_settings_tasks-max"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_ssl:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_mirror-maker_ssl-post:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl-post"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_remote-ref:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_remote-ref"

Required/Optional: true
```

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_remote-ref-post:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_remote-ref-post"

Required/Optional: true
```

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_remote-ref_key:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_remote-ref_key"

Required/Optional: true
```

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_remote-ref_property:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_remote-ref_property"

Required/Optional: true
```

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_secret-key:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_data_data-secret-key_secret-key"

Required/Optional: true
```

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_name:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
```

"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_name"

Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_namespace:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_namespace"

Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_refresh-interval:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_refresh-interval"

Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_remote-key-path:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_remote-key-path"

Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store"

Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store-post:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store-post"

Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store_kind:

```
      Description: Overrides common secret store kind
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store_kind"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store_name:

      Description: Overrides common secret store name
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store_name"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store_namespace:

      Description: Overrides common secret store namespace
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_secret-store_namespace"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_target-secret:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-external-secrets_broker-ca-external-secrets-name_target-secret"

      Required/Optional: true

data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-secret-names_broker-ca-secret-names-id:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_mirror-maker_ssl_broker-ca-secret-names_broker-ca-secret-names-id"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_network-policy:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_network-policy"
```

```
      Required/Optional: true
    data_cisco-smi-cdl_cdl_network-policy-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_network-policy-post"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_network-policy_enable:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_network-policy_enable"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_node-type:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_node-type"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_db-endpoint:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_db-endpoint"

      Required/Optional: true

data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_db-endpoint-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_db-endpoint-post"

      Required/Optional: true

data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_db-endpoint_host:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_db-endpoint_host"
```

```
      Required/Optional: true

data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_db-endpoint_port:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_db-endpoint_port"

      Required/Optional: true

data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port"

      Required/Optional: true

data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port_host:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port_host"

      Required/Optional: true

data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port_port:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port_port"

      Required/Optional: true

data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port_ssl-port:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_kafka-server_kafka-server-host_kafka-server-port_ssl-port"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_system-id:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_remote-site_remote-site-system-id_system-id"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_repository:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_repository"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config-post"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_auto-generation:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_auto-generation"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_auto-generation-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_auto-generation-post"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_auto-generation_enabled:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_auto-generation_enabled"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret-post:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret-post"
      Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key"

      Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_remote-ref:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_remote-ref"

      Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_remote-ref-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_remote-ref-post"

      Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_remote-ref_key:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_remote-ref_key"

      Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_remote-ref_property:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_remote-ref_property"

      Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_secret-key:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_data_data-secret-key_secret-key"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_name:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_name"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_namespace:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_namespace"
      Required/Optional: true
   data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_refresh-interval:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_refresh-interval"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_remote-key-path:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_remote-key-path"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store"
      Required/Optional: true
   data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store-post"
```

```
      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store_kind:

      Description: Overrides common secret store kind
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store_kind"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store_name:

      Description: Overrides common secret store name
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store_name"

      Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store_namespace:

      Description: Overrides common secret store namespace
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_secret-store_namespace"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_target-secret:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-external-secret_target-secret"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_ca-secret-name:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_ca-secret-name"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ca-secret:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ca-secret"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_host:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_host"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ssl-ca:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ssl-ca"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ssl-crt:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ssl-crt"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ssl-key:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_ssl-key"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_tls-secret:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_certs_certs-host_tls-secret"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_enable:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_enable"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth"
```

```
      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth-post"
      Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id"

      Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key"

      Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_remote-ref:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_remote-ref"

      Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_remote-ref-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_remote-ref-post"

      Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_remote-ref_key:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_remote-ref_key"

Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_remote-ref_property:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_remote-ref_property"

Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_secret-key:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_data_data-secret-key_secret-key"

Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_name:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_name"

Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_namespace:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_namespace"

Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_refresh-interval:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_refresh-interval"

Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_remote-key-path:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_remote-key-path"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store-post:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store-post"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store_kind:

```
      Description: Overrides common secret store kind
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store_kind"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store_name:

```
      Description: Overrides common secret store name
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store_name"

      Required/Optional: true
```

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store_namespace:

```
      Description: Overrides common secret store namespace
      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_secret-store_namespace"

      Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_site-id:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_site-id"

      Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_target-secret:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-external-secrets_ca-external-secrets-site-id_target-secret"

      Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-secret-names_ca-secret-names-site-id:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-secret-names_ca-secret-names-site-id"

      Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-secret-names_ca-secret-names-site-id_secret-name:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-secret-names_ca-secret-names-site-id_secret-name"

      Required/Optional: true

data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-secret-names_ca-secret-names-site-id_site-id:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_remote-ca-auth_ca-secret-names_ca-secret-names-site-id_site-id"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_ssl-config_tls-secret-name:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_ssl-config_tls-secret-name"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_system-id:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_system-id"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_use-rust-image:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_use-rust-image"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_zookeeper:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_zookeeper-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper-post"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_zookeeper_data-storage-size:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_data-storage-size"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_zookeeper_enable-JMX-metrics:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_enable-JMX-metrics"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_zookeeper_enable-parallel-pod-management:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_enable-parallel-pod-management"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_zookeeper_enable-persistence:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_enable-persistence"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_zookeeper_log-level:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_log-level"

      Required/Optional: true
    data_cisco-smi-cdl_cdl_zookeeper_log-storage-size:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_log-storage-size"
      Required/Optional: true
    data_cisco-smi-cdl_cdl_zookeeper_replica:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_cdl_zookeeper_replica"
      Required/Optional: true
    data_cisco-smi-cdl_feature-gates:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_feature-gates"
      Required/Optional: true
    data_cisco-smi-cdl_feature-gates-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_feature-gates-post"
      Required/Optional: true
    data_cisco-smi-cdl_feature-gates_alpha:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_feature-gates_alpha"
      Required/Optional: true
    data_cisco-smi-cdl_feature-gates_test:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-cdl_feature-gates_test"
      Required/Optional: true
  securitySchemes:
    basicAuth:
```

Type: http
scheme: basic