

etcd

- OpenAPI, on page 1
- Info, on page 1
- Servers, on page 1
- tags, on page 1
- Paths, on page 2
- Components, on page 512

OpenAPI

OpenAPI Version: 3.0.1

Info

```
Title: cisco-smi-etcd
Description:
Version: 2025-10-30
```

Servers

```
- URL: /restconf
```

tags

```
- Name: root
  Description: root resources
- Name: operations
  Description: operations resources
- Name: data
  Description: data resources
```

```
- Name: get
  Description: get resources
- Name: head
  Description: head resources
- Name: post
  Description: post resources
- Name: patch
  Description: patch resources
- Name: put
  Description: put resources
- Name: options
  Description: options resources
- Name: delete
  Description: delete resources
```

Paths

/

```
get:

  Tags:
  - root
  - get
  Operation ID: root_get

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/root"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - root
  - head
  Operation ID: root_head

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/operations

```
get:

  Tags:
  - operations
  - get
  Operation ID: operations_get

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/operations"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
```

/yang-library-version

```
get:

  Tags:
  - yang-library-version
  - get
  Operation ID: yang_library_version_get

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/yang-library-version"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - yang-library-version
  - head
  Operation ID: yang_library_version_head

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data


```
get:

  Tags:
  - data
  - get
  Operation ID: data_get

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data-put-patch"
    Required/Optional: true

  Responses:
    "201":
      Description: Created
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: data
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data-post"
    Required/Optional: true

  Responses:
    "201":
      Description: Created
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
  - basicAuth: []
  x-codegen-request-body-name: data
head:

  Tags:
  - data
  - head
  Operation ID: data_head

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data-put-patch"
    Required/Optional: true

  Responses:
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: data
```

/data/cisco-smi-etcd:etcd

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: container etcd created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: etcd
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_etcd_etcd_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container etcd created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: etcd
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd"
    Required/Optional: true

  Responses:
    "204":
      Description: container etcd updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: etcd
```

/data/cisco-smi-etcd:etcd/node-affinity

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_node_affinity_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_node-affinity"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_node_affinity_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_node-affinity"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf node-affinity created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: node-affinity
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_node_affinity_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_node_affinity_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_node_affinity_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_node_affinity_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_node-affinity"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf node-affinity updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: node-affinity
```

/data/cisco-smi-etcd:etcd/replicas

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_replicas_get

  Parameters:
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_replicas"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_replicas_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_replicas"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf replicas created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replicas
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_replicas_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_replicas_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_replicas_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_replicas_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_replicas"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf replicas updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replicas
```

/data/cisco-smi-etcd:etcd/go-max-procs

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_go_max_procs_get

  Parameters:
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_go-max-procs"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_go_max_procs_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_go-max-procs"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf go-max-procs created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: go-max-procs
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_go_max_procs_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_go_max_procs_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_go_max_procs_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_go_max_procs_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_go-max-procs"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf go-max-procs updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: go-max-procs
```

/data/cisco-smi-etcd:etcd/volume

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_volume_get

  Parameters:
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
    - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_volume"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_volume_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_volume"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf volume created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: volume
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_volume_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_volume_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_volume_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_volume_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_volume"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf volume updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: volume
```

/data/cisco-smi-etcd:etcd/pv-anti-affinity-mode

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_pv_anti_affinity_mode_get

  Parameters:
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_pv-anti-affinity-mode"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_pv_anti_affinity_mode_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_pv-anti-affinity-mode"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf pv-anti-affinity-mode created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
```

```
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pv-anti-affinity-mode
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_pv_anti_affinity_mode_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_pv_anti_affinity_mode_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_pv_anti_affinity_mode_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_pv_anti_affinity_mode_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_pv-anti-affinity-mode"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf pv-anti-affinity-mode updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pv-anti-affinity-mode
```

/data/cisco-smi-etcd:etcd/pv-reclaim-policy

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_pv_reclaim_policy_get
```

```
Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_pv-reclaim-policy"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_pv_reclaim_policy_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_pv-reclaim-policy"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf pv-reclaim-policy created or replaced
      Content: {}
    "204":
      Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pv-reclaim-policy
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_pv_reclaim_policy_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_pv_reclaim_policy_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_pv_reclaim_policy_head

  Parameters:
  - Name: content
```

```
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
```

```
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_pv_reclaim_policy_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco_smi-etcd_etcd_pv-reclaim-policy"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf pv-reclaim-policy updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pv-reclaim-policy
```

/data/cisco-smi-etcd:etcd/backup

```
get:

  Tags:
```

```
- data
- get
Operation ID: data_cisco_smi_etcd_etcd_backup_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_backup"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_backup_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_backup"
    Required/Optional: true

  Responses:
    "201":
      Description: container backup created or replaced
      Content: {}
```

```
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: backup
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_etcd_etcd_backup_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_backup-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container backup created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: backup
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_backup_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_backup_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_backup_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
```

```
- data
- patch
Operation ID: data_cisco_smi_etcd_etcd_backup_patch
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_backup"
  Required/Optional: true

Responses:
  "204":
    Description: container backup updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: backup
```

/data/cisco-smi-etcd:etcd/backup/disable

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_backup_disable_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_backup_disable"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_backup_disable_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_backup_disable"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf disable created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: disable
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_backup_disable_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_backup_disable_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_backup_disable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
Tags:
- data
- patch
Operation ID: data_cisco_smi_etcd_etcd_backup_disable_patch
Request Body:
  Content:
    application/yang-data+json:
      Schema:
        Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_backup_disable"
  Required/Optional: true

Responses:
  "204":
    Description: leaf disable updated
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: disable
```

/data/cisco-smi-etcd:etcd/backup/frequency

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_backup_frequency_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_backup_frequency"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_backup_frequency_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_backup_frequency"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf frequency created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: frequency
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_backup_frequency_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_backup_frequency_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_backup_frequency_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
```

```
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_backup_frequency_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_backup_frequency"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf frequency updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: frequency
```

/data/cisco-smi-etcd:etcd/backup/restore

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore"
    Required/Optional: true

  Responses:
    "201":
      Description: container restore created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: restore
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container restore created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: restore
delete:
```

```
  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_backup_restore_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore"
      Required/Optional: true
```

```
  Responses:
    "204":
      Description: container restore updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: restore
```

/data/cisco-smi-etcd:etcd/backup/restore/use-local-snapshot

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_use_local_snapshot_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore_use-local-snapshot"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_backup_restore_use_local_snapshot_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore_use-local-snapshot"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf use-local-snapshot created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
  x-codegen-request-body-name: use-local-snapshot
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_use_local_snapshot_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_use_local_snapshot_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_use_local_snapshot_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_backup_restore_use_local_snapshot_patch
    Request Body:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore_use-local-snapshot"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf use-local-snapshot updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: use-local-snapshot
```

/data/cisco-smi-etcd:etcd/backup/restore/wait-time

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_wait_time_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore_wait-time"
    "204":
      Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_wait_time_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore_wait-time"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf wait-time created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: wait-time
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_wait_time_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_wait_time_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_backup_restore_wait_time_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
```

```
    Operation ID: data_cisco_smi_etcd_etcd_backup_restore_wait_time_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore_wait-time"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf wait-time updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: wait-time
```

/data/cisco-smi-etcd:etcd/enable-daily-defragmentation

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_etcd_etcd_enable_daily_defragmentation_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_enable-daily-defragmentation"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_enable_daily_defragmentation_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_enable-daily-defragmentation"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf enable-daily-defragmentation created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable-daily-defragmentation
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_enable_daily_defragmentation_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_enable_daily_defragmentation_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_enable_daily_defragmentation_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_enable_daily_defragmentation_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_enable-daily-defragmentation"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf enable-daily-defragmentation updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable-daily-defragmentation
```

/data/cisco-smi-etcd:etcd/daily-defragmentation-start-time

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_etcd_etcd_daily_defragmentation_start_time_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_daily-defragmentation-start-time"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_daily_defragmentation_start_time_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_daily-defragmentation-start-time"
      Required/Optional: true

    Responses:
      "201":
        Description: leaf daily-defragmentation-start-time created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: daily-defragmentation-start-time
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_daily_defragmentation_start_time_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_daily_defragmentation_start_time_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_daily_defragmentation_start_time_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
```

```
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_daily_defragmentation_start_time_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_daily-defragmentation-start-time"
      Required/Optional: true

    Responses:
      "204":
        Description: leaf daily-defragmentation-start-time updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: daily-defragmentation-start-time
```

/data/cisco-smi-etcd:etcd/storage-label

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_etcd_etcd_storage_label_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_storage-label"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_storage_label_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_storage-label"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf storage-label created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: storage-label
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_storage_label_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_storage_label_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_storage_label_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_storage_label_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_storage-label"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf storage-label updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: storage-label
```

/data/cisco-smi-etcd:etcd/external-ip

```
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_external_ip_options

  Responses:
    "200":
      Description: OK
```

```
    Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-etcd:etcd/external-ip={external-ip-ip},{external-ip-port}

```
get:

  Tags:
  - data
  - get
 Operation ID: data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_get


  Parameters:
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
 Operation ID: data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_put


  Parameters:
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
```

```
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port"

      Required/Optional: true

    Responses:
      "201":
        Description: list external-ip created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: external-ip
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_delete

    Parameters:
    - Name: external-ip-ip
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_options

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

```
head:

  Tags:
  - data
  - head
 Operation ID: data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_head


  Parameters:
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_patch

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port"

      Required/Optional: true

    Responses:
      "204":
        Description: list external-ip updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: external-ip
```


/data/cisco-smi-etcd:etcd/external-ip={external-ip-ip},{external-ip-port}/ip


```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_ip_get

    Parameters:
    - Name: external-ip-ip
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- Name: external-ip-port
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_ip"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
```

```
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_ip_put

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_ip"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf ip created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: ip
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_ip_delete

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_ip_options

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_ip_head

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
```

```
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_ip_patch

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_ip"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf ip updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ip
```

/data/cisco-smi-etcd:etcd/external-ip={external-ip-ip},{external-ip-port}/port

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_port_get

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
```

```
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_port"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_port_put

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_port"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf port created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: port
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_port_delete

  Parameters:
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_port_options
```

```
    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_port_head

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_port_patch

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_port"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf port updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: port
```

/data/cisco-smi-etcd:etcd/external-ip={external-ip-ip},{external-ip-port}/label

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_label_get

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_label"

      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_label_put

  Parameters:
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_label"

    Required/Optional: true

  Responses:
```

```
      "201":
        Description: leaf label created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: label
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_label_delete

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "204":
        Description: No Content
```

```
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_label_options

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_label_head

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_external_ip_external_ip_ip_external_ip_port_label_patch

    Parameters:
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_label"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf label updated
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: label
```

/data/cisco-smi-etcd:etcd/tls

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_tls_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_tls"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
```

```
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_tls_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_tls"
    Required/Optional: true

  Responses:
    "201":
      Description: container tls created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tls
Method: Post:

  Tags:
  - data
```

```
  - post
  Operation ID: data_cisco_smi_etcd_etcd_tls_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_tls-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container tls created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: tls
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_tls_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_tls_options
```

```
  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_tls_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_tls_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_tls"
    Required/Optional: true

  Responses:
    "204":
      Description: container tls updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: tls
```

/data/cisco-smi-etcd:etcd/tls/enable

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_tls_enable_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
```

```
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_tls_enable"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:
```

```
  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_tls_enable_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_tls_enable"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf enable created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_tls_enable_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
```

```
  - options
  Operation ID: data_cisco_smi_etcd_etcd_tls_enable_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_tls_enable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_tls_enable_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_tls_enable"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf enable updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
```

```
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
```

/data/cisco-smi-etcd:etcd/tls/certificate-config

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config"
      Required/Optional: true

    Responses:
      "201":
        Description: container certificate-config created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: certificate-config
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config-post"
      Required/Optional: true
```

```
  Responses:
    "201":
      Description: container certificate-config created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: certificate-config
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:
```

```
Tags:
- data
- head
Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_head

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config"
      Required/Optional: true

    Responses:
      "204":
        Description: container certificate-config updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: certificate-config
```

/data/cisco-smi-etcd:etcd/tls/certificate-config/server

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server"
     Required/Optional: true

   Responses:
     "201":
       Description: container server created or replaced
       Content: {}
     "204":
       Description: No Content
       Content: {}
     "400":
       Description: Bad Request
       Content: {}
     "401":
       Description: Unauthorized
       Content: {}
     "404":
       Description: Not Found
       Content: {}
     "405":
       Description: Method Not Allowed
       Content: {}
     "409":
       Description: Conflict
       Content: {}
   security:
   - basicAuth: []
   x-codegen-request-body-name: server
 Method: Post:

   Tags:
   - data
   - post
   Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_post
   Request Body:
     Content:
       application/yang-data+json:
         Schema:
           Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server-post"
     Required/Optional: true

   Responses:
     "201":
       Description: container server created
       Content: {}
     "204":
       Description: No Content
       Content: {}
     "400":
       Description: Bad Request
       Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: server
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server"
      Required/Optional: true

    Responses:
      "204":
        Description: container server updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: server
```

/data/cisco-smi-etcd:etcd/tls/certificate-config/server/ca-cert

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_get

    Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert"
      Required/Optional: true

    Responses:
      "201":
        Description: container ca-cert created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ca-cert
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container ca-cert created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ca-cert
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
```

```
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert"
      Required/Optional: true

    Responses:
      "204":
        Description: container ca-cert updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ca-cert
```

/data/cisco-smi-etcd:etcd/tls/certificate-config/server/ca-cert/secret-name

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_secret_name_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert_secret-name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_secret_name_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert_secret-name"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf secret-name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-name
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_secret_name_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_secret_name_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_secret_name_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_ca_cert_secret_name_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert_secret-name"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf secret-name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-name
```

/data/cisco-smi-etcd:etcd/tls/certificate-config/server/key-pair

```
  get:

    Tags:
    - data
    - get
```

```
Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair"
      Required/Optional: true

    Responses:
      "201":
        Description: container key-pair created or replaced
        Content: {}
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key-pair
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container key-pair created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: key-pair
delete:

  Tags:
  - data
  - delete
 Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_delete


  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
 Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_options


  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair"
      Required/Optional: true

    Responses:
      "204":
        Description: container key-pair updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key-pair
```

/data/cisco-smi-etcd:etcd/tls/certificate-config/server/key-pair/secret-name

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_secret_name_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair_secret-name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_secret_name_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair_secret-name"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf secret-name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-name
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_secret_name_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_secret_name_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_secret_name_head

  Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_server_key_pair_secret_name_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair_secret-name"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf secret-name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-name
```

/data/cisco-smi-etcd:etcd/tls/certificate-config/peer

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer"
     Required/Optional: true

   Responses:
     "201":
       Description: container peer created or replaced
       Content: {}
     "204":
       Description: No Content
       Content: {}
     "400":
       Description: Bad Request
       Content: {}
     "401":
       Description: Unauthorized
       Content: {}
     "404":
       Description: Not Found
       Content: {}
     "405":
       Description: Method Not Allowed
       Content: {}
     "409":
       Description: Conflict
       Content: {}
   security:
   - basicAuth: []
   x-codegen-request-body-name: peer
 Method: Post:

   Tags:
   - data
   - post
   Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_post
   Request Body:
     Content:
       application/yang-data+json:
         Schema:
           Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer-post"
     Required/Optional: true

   Responses:
     "201":
       Description: container peer created
       Content: {}
     "204":
       Description: No Content
       Content: {}
     "400":
       Description: Bad Request
       Content: {}
```

```
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: peer
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer"
      Required/Optional: true

    Responses:
      "204":
        Description: container peer updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: peer
```

/data/cisco-smi-etcd:etcd/tls/certificate-config/peer/ca-cert

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_get

    Parameters:
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert"
      Required/Optional: true

    Responses:
      "201":
        Description: container ca-cert created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ca-cert
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container ca-cert created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ca-cert
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
```

```
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
```

```
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert"
      Required/Optional: true

    Responses:
      "204":
        Description: container ca-cert updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ca-cert
```

/data/cisco-smi-etcd:etcd/tls/certificate-config/peer/ca-cert/secret-name

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_secret_name_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert_secret-name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_secret_name_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert_secret-name"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf secret-name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-name
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_secret_name_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_secret_name_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_secret_name_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_ca_cert_secret_name_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert_secret-name"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf secret-name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-name
```

/data/cisco-smi-etcd:etcd/tls/certificate-config/peer/key-pair

```
  get:

    Tags:
    - data
    - get
```

```
Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair"
      Required/Optional: true

    Responses:
      "201":
        Description: container key-pair created or replaced
        Content: {}
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key-pair
  Method: Post:

    Tags:
    - data
    - post
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container key-pair created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: key-pair
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
      - nonconfig
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:
```

```
    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair"
      Required/Optional: true

    Responses:
      "204":
        Description: container key-pair updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key-pair
```

/data/cisco-smi-etcd:etcd/tls/certificate-config/peer/key-pair/secret-name

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_secret_name_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair_secret-name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_secret_name_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair_secret-name"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf secret-name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
```

```
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_secret_name_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_secret_name_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_secret_name_head

    Parameters:
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_tls_certificate_config_peer_key_pair_secret_name_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair_secret-name"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf secret-name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-name
```

/data/cisco-smi-etcd:etcd/label-config

```
  get:

    Tags:
```

```
- data
- get
Operation ID: data_cisco_smi_etcd_etcd_label_config_get

Parameters:
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_label-config"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_label_config_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_label-config"
    Required/Optional: true

  Responses:
    "201":
      Description: container label-config created or replaced
      Content: {}
```

```
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: label-config
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_etcd_etcd_label_config_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_label-config-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container label-config created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: label-config
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_label_config_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_label_config_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_label_config_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
```

```
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:
```

```
    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_label_config_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_label-config"
      Required/Optional: true

    Responses:
      "204":
        Description: container label-config updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: label-config
```

/data/cisco-smi-etcd:etcd/label-config/key

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_etcd_etcd_label_config_key_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_label-config_key"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_label_config_key_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_label-config_key"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf key created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: key
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_label_config_key_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_label_config_key_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_label_config_key_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
```

```
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
```

```
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_label_config_key_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_label-config_key"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf key updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: key
```

/data/cisco-smi-etcd:etcd/label-config/value

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_label_config_value_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
```

```
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
```

```
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_label-config_value"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_label_config_value_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_label-config_value"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf value created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: value
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_label_config_value_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_label_config_value_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_label_config_value_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_label_config_value_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_label-config_value"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf value updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: value
```

/data/cisco-smi-etcd:etcd/repository

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_etcd_etcd_repository_get

    Parameters:
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_repository"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_repository_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_repository"
    Required/Optional: true

  Responses:
    "201":
      Description: leaf repository created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: repository
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_repository_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_repository_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_repository_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
```

```
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_repository_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_repository"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf repository updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: repository
```

/data/cisco-smi-etcd:etcd/monitoring

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_get

  Parameters:
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_monitoring"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_monitoring"
    Required/Optional: true

  Responses:
    "201":
      Description: container monitoring created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
```

```
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitoring
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_monitoring-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container monitoring created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitoring
```

```
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_monitoring_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
        Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_monitoring"
    Required/Optional: true

  Responses:
    "204":
      Description: container monitoring updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: monitoring
```


/data/cisco-smi-etcd:etcd/monitoring/enabled


```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_enabled_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_enabled"

  "204":
    Description: No Content
    Content: {}
  "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_enabled_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_enabled"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf enabled created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: enabled
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_enabled_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_enabled_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_enabled_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_monitoring_enabled_patch
    Request Body:
```

```
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_enabled"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf enabled updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enabled
```

/data/cisco-smi-etcd:etcd/monitoring/alerts

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts"
```

```
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts"

    Required/Optional: true

  Responses:
    "201":
      Description: container alerts created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: alerts
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts-post"
    Required/Optional: true

  Responses:
    "201":
      Description: container alerts created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: alerts
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_delete
```

```
  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts"

      Required/Optional: true

    Responses:
      "204":
        Description: container alerts updated
```

```
    Content: {}
  "400":
    Description: Bad Request
    Content: {}
  "401":
    Description: Unauthorized
    Content: {}
  "404":
    Description: Not Found
    Content: {}
  "405":
    Description: Method Not Allowed
    Content: {}
  "409":
    Description: Conflict
    Content: {}
security:
- basicAuth: []
x-codegen-request-body-name: alerts
```

/data/cisco-smi-etcd:etcd/monitoring/alerts/dbsize

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize"
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize"
      Required/Optional: true

    Responses:
      "201":
        Description: container dbsize created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: dbsize
  Method: Post:

    Tags:
```

```
    - data
    - post
    Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_post
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize-post"
      Required/Optional: true

    Responses:
      "201":
        Description: container dbsize created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: dbsize
  delete:

    Tags:
    - data
    - delete
    Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
```

```
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID: data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize"
      Required/Optional: true

    Responses:
      "204":
        Description: container dbsize updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: dbsize
```


/data/cisco-smi-etcd:etcd/monitoring/alerts/dbsize/major-alert-threshold


```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_major_alert_threshold_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
      Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_major-alert-threshold"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_major_alert_threshold_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_major-alert-threshold"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf major-alert-threshold created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: major-alert-threshold
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_major_alert_threshold_delete

    Responses:
      "204":
        Description: No Content
```

```
      Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_major_alert_threshold_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_major_alert_threshold_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_major_alert_threshold_patch
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_major-alert-threshold"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf major-alert-threshold updated
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: major-alert-threshold
```

/data/cisco-smi-etcd:etcd/monitoring/alerts/dbsize/critical-alert-threshold

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_critical_alert_threshold_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
        Type: integer
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_critical-alert-threshold"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_critical_alert_threshold_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_critical-alert-threshold"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf critical-alert-threshold created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: critical-alert-threshold
```

```
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_critical_alert_threshold_delete

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_critical_alert_threshold_options

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_critical_alert_threshold_head

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_monitoring_alerts_dbsize_critical_alert_threshold_patch
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_critical-alert-threshold"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf critical-alert-threshold updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: critical-alert-threshold
```

/data/cisco-smi-etcd:etcd/network-policy

```
  get:

    Tags:
    - data
    - get
    Operation ID: data_cisco_smi_etcd_etcd_network_policy_get

    Parameters:
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
```

```
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_network-policy"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID: data_cisco_smi_etcd_etcd_network_policy_put
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_network-policy"
      Required/Optional: true

    Responses:
      "201":
        Description: container network-policy created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: network-policy
Method: Post:

  Tags:
  - data
  - post
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_post
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
         Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_network-policy-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container network-policy created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: network-policy
delete:

  Tags:
  - data
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_delete
```

```
  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_network-policy"
    Required/Optional: true

  Responses:
    "204":
      Description: container network-policy updated
      Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: network-policy
```

/data/cisco-smi-etcd:etcd/network-policy/enable

```
get:

  Tags:
  - data
  - get
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_enable_get

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
```

```
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_network-policy_enable"
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_enable_put
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_network-policy_enable"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf enable created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
delete:

  Tags:
  - data
```

```
  - delete
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_enable_delete

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_enable_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_enable_head

  Parameters:
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID: data_cisco_smi_etcd_etcd_network_policy_enable_patch
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
        Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_network-policy_enable"

    Required/Optional: true
```

```
  Responses:
    "204":
      Description: leaf enable updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
```

/data/cisco-smi-etcd:etcd/additional-instances

```
options:

  Tags:
  - data
  - options
  Operation ID: data_cisco_smi_etcd_etcd_additional_instances_options

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_get

  Parameters:
```

```
- Name: additional-instances-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_put

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: insert
      In: query
      Description: controlling the order when adding new list elements
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: first
        enum:
        - first
        - last
        - before
        - after
    - Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name"

    Required/Optional: true

  Responses:
    "201":
      Description: list additional-instances created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: additional-instances
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_delete

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_options

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
```

```
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_patch

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name"
```

```
    Required/Optional: true

  Responses:
    "204":
      Description: list additional-instances updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: additional-instances
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/name

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_name_get

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

Responses:
  "200":
```

```
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_name_put

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_name"

      Required/Optional: true
```

```
    Responses:
      "201":
        Description: leaf name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_name_delete

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
```

```
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_name_options

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_name_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_name_patch
```

```
    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_name"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: name
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/node-a

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_node_affinity_get
```

```
Parameters:
- Name: additional-instances-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
```

```
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_node-affinity"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_node_affinity_put

    Parameters:
    - Name: additional-instances-name
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_node-affinity"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf node-affinity created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: node-affinity
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_node_affinity_delete

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_node_affinity_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_node_affinity_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
```

```
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_node_affinity_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_node-affinity"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf node-affinity updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: node-affinity
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/repl

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_replicas_get

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_replicas"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_replicas_put

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_replicas"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf replicas created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
```

```
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: replicas
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_replicas_delete

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_replicas_options

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:
```

```
    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_replicas_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_replicas_patch

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_replicas"

      Required/Optional: true

    Responses:
      "204":
```

```
      Description: leaf replicas updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: replicas
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/go-m

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_go_max_procs_get

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
```

```
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
      application/yang-data+json:
        Schema:
          Reference:
```

"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_go-max-procs"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_go_max_procs_put

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_go-max-procs"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf go-max-procs created or replaced
        Content: {}
      "204":

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: go-max-procs
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_go_max_procs_delete


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_go_max_procs_options
```

```
    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_go_max_procs_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_go_max_procs_patch

    Parameters:
    - Name: additional-instances-name
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_go-max-procs"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf go-max-procs updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: go-max-procs
```


/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/volu


```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_volume_get

    Parameters:
    - Name: additional-instances-name
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_volume"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_volume_put

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_volume"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf volume created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: volume
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_volume_delete

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_volume_options

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_volume_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
```

```
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
```

```
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_volume_patch

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_volume"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf volume updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: volume
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/pv-ant

get:

Tags:
- data
- get

Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_pv_anti_affinity_mode_get

Parameters:
- **Name**: additional-instances-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_pv-anti-affinity-mode"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_pv_anti_affinity_mode_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_pv-anti-affinity-mode"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf pv-anti-affinity-mode created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pv-anti-affinity-mode
```

```
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_pv_anti_affinity_mode_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_pv_anti_affinity_mode_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
```

Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_pv_anti_affinity_mode_head

Parameters:
- **Name**: additional-instances-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- **Name**: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- **Name**: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- **Name**: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- **Name**: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string

```
      Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_pv_anti_affinity_mode_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_pv-anti-affinity-mode"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf pv-anti-affinity-mode updated
        Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pv-anti-affinity-mode
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/pv-rec

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_pv_reclaim_policy_get


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_pv-reclaim-policy"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_pv_reclaim_policy_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_pv-reclaim-policy"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf pv-reclaim-policy created or replaced
        Content: {}
      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: pv-reclaim-policy
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_pv_reclaim_policy_delete


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_pv_reclaim_policy_options


  Parameters:
```

```
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_pv_reclaim_policy_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_pv_reclaim_policy_patch


    Parameters:
    - Name: additional-instances-name
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_pv-reclaim-policy"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf pv-reclaim-policy updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: pv-reclaim-policy
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/backu

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_get

    Parameters:
    - Name: additional-instances-name
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_put

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup"

      Required/Optional: true

    Responses:
      "201":
        Description: container backup created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: backup
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_post

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container backup created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: backup
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_delete

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_options

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_patch

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup"

      Required/Optional: true

    Responses:
      "204":
        Description: container backup updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: backup
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/backu

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_disable_get

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
```

```
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_disable"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
```

```
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_disable_put

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_disable"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf disable created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: disable
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_disable_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_disable_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_disable_head
```

```
Parameters:
- Name: additional-instances-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_disable_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_disable"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf disable updated
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: disable
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/backu

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_frequency_get


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_frequency"

    "204":
```

```
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_frequency_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_frequency"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf frequency created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: frequency
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_frequency_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_frequency_options


    Parameters:
    - Name: additional-instances-name
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_frequency_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: integer
        Format: uint16
      - Name: fields
        In: query
        Description: optionally identify specific data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: filter
        In: query
        Description: xpath expression to filter data nodes in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_frequency_patch


      Parameters:
      - Name: additional-instances-name
        In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_frequency"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf frequency updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: frequency
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/backu

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_get

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_put

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore"

      Required/Optional: true

    Responses:
      "201":
        Description: container restore created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: restore
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_post


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container restore created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: restore
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
```

```
    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
```

```
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore"

      Required/Optional: true

    Responses:
      "204":
        Description: container restore updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
```

```
    - basicAuth: []
    x-codegen-request-body-name: restore
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/backu

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_use_local_snapshot_get


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_use-local-snapshot"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
```

```
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_use_local_snapshot_put


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_use-local-snapshot"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf use-local-snapshot created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
    security:
    - basicAuth: []
    x-codegen-request-body-name: use-local-snapshot
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_use_local_snapshot_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_use_local_snapshot_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:
```

```
    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_use_local_snapshot_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_use_local_snapshot_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_use-local-snapshot"

      Required/Optional: true
```

```
  Responses:
    "204":
      Description: leaf use-local-snapshot updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: use-local-snapshot
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/backu

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_wait_time_get


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_wait-time"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_wait_time_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_wait-time"

      Required/Optional: true

    Responses:
      "201":
```

```
      Description: leaf wait-time created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: wait-time
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_wait_time_delete


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
```

```
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_wait_time_options

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_wait_time_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
```

data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_backup_restore_wait_time_patch

```
  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_wait-time"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf wait-time updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: wait-time
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/enable

```
get:

  Tags:
  - data
  - get
  Operation ID:
```

```
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_enable_daily_defragmentation_get

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_enable-daily-defragmentation"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_enable_daily_defragmentation_put
```

```
    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_enable-daily-defragmentation"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf enable-daily-defragmentation created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable-daily-defragmentation
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_enable_daily_defragmentation_delete


    Parameters:
```

```
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_enable_daily_defragmentation_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_enable_daily_defragmentation_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
```

```
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_enable_daily_defragmentation_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_enable-daily-defragmentation"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf enable-daily-defragmentation updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable-daily-defragmentation
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/dail

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_daily_defragmentation_start_time_get


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_daily-defragmentation-start-time"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_daily_defragmentation_start_time_put


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_daily-defragmentation-start-time"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf daily-defragmentation-start-time created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
```

```
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: daily-defragmentation-start-time
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_daily_defragmentation_start_time_delete


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_daily_defragmentation_start_time_options


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_daily_defragmentation_start_time_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_daily_defragmentation_start_time_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_daily-defragmentation-start-time"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf daily-defragmentation-start-time updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: daily-defragmentation-start-time
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/stora

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_storage_label_get

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_storage-label"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_storage_label_put

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_storage-label"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf storage-label created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: storage-label
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_storage_label_delete

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_storage_label_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_storage_label_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
```

```
      - config
      - nonconfig
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:
```

```
    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_storage_label_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_storage-label"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf storage-label updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: storage-label
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/exte

```
  options:
```

```
    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/extern

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_get


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
```

```
- Name: external-ip-port
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_put


    Parameters:
    - Name: additional-instances-name
      In: path
```

```
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: insert
    In: query
    Description: controlling the order when adding new list elements
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: first
      enum:
      - first
      - last
      - before
      - after
  - Name: point
    In: query
    Description: used to specify the insertion point
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port"
```

```
    Required/Optional: true

  Responses:
    "201":
      Description: list external-ip created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: external-ip
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_delete


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
```

```
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_options


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16

  Responses:
    "200":
      Description: OK
```

```
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
```

data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_patch

```
  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port"

    Required/Optional: true

  Responses:
    "204":
      Description: list external-ip updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: external-ip
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/exte

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_ip_get

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_ip"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_ip_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_ip"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf ip created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ip
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_ip_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_ip_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
      Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_ip_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    - Name: content
      In: query
      Description: controlling descendant nodes in response
```

```
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_ip_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_ip"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf ip updated
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ip
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/exte

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_port_get


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: external-ip-port
    In: path
    Required/Optional: true
```

```
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
```

```
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_port"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_port_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_port"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf port created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
```

```
    x-codegen-request-body-name: port
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_port_delete

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_port_options

    Parameters:
    - Name: additional-instances-name
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_port_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
    Type: string
    Format: union
- Name: external-ip-port
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
```

```
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_port_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
```

```
      Format: uint16
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_port"

    Required/Optional: true

  Responses:
    "204":
      Description: leaf port updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: port
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/exte

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_label_get

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
```

```
    Format: string
- Name: external-ip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- Name: external-ip-port
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_label"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:
```

```
    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_label_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_label"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf label created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
```

```
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: label
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_label_delete


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: external-ip-ip
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: union
  - Name: external-ip-port
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: integer
      Format: uint16

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_label_options

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_label_head

    Parameters:
    - Name: additional-instances-name
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: external-ip-ip
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: union
- Name: external-ip-port
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: integer
    Format: uint16
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
```

```
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_external_ip_external_ip_ip_external_ip_port_label_patch


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: external-ip-ip
    In: path
    Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    - Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_label"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf label updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: label
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/tls

```
  get:

    Tags:
    - data
```

```
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_get

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content:
            application/yang-data+json:
              Schema:
                Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls"

        "204":
          Description: No Content
          Content: {}
        "400":
          Description: Bad Request
          Content: {}
        "401":
          Description: Unauthorized
          Content: {}
        "404":
          Description: Not Found
          Content: {}
        "405":
          Description: Method Not Allowed
          Content: {}
        "409":
          Description: Conflict
          Content: {}
      security:
      - basicAuth: []
    put:

      Tags:
      - data
      - put
      Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_put
```

```
    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls"

      Required/Optional: true

    Responses:
      "201":
        Description: container tls created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: tls
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_post

    Parameters:
    - Name: additional-instances-name
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container tls created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: tls
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_delete

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_options

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
```

```
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
```

```
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_patch

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls"

      Required/Optional: true

    Responses:
      "204":
        Description: container tls updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: tls
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/tls/e

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_enable_get

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_enable"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_enable_put

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_enable"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf enable created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
    security:
    - basicAuth: []
    x-codegen-request-body-name: enable
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_enable_delete

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_enable_options

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
```

```
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_enable_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: string
        Format: string
      - Name: with-defaults
        In: query
        Description: controlling default values in response
        Required/Optional: false
        Style: form
        Explode: true
        Schema:
          Type: string
          Format: enumeration
          Default: report-all
          enum:
          - report-all
          - trim
          - explicit
          - report-all-tagged

      Responses:
        "200":
          Description: OK
          Content: {}
      security:
      - basicAuth: []
    patch:

      Tags:
      - data
      - patch
      Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_enable_patch

      Parameters:
      - Name: additional-instances-name
        In: path
        Required/Optional: true
        Style: simple
        Explode: false
        Schema:
          Type: string
          Format: string
      Request Body:
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_enable"

        Required/Optional: true

      Responses:
        "204":
          Description: leaf enable updated
          Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: enable
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/tls/c

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_get

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
```

```
      - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config"
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config"

      Required/Optional: true

    Responses:
      "201":
        Description: container certificate-config created or replaced
        Content: {}
      "204":
        Description: No Content
```

```
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: certificate-config
 Method: Post:

  Tags:
  - data
  - post
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_post


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container certificate-config created
      Content: {}
    "204":
      Description: No Content
      Content: {}
```

```
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: certificate-config
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_options


    Parameters:
    - Name: additional-instances-name
```

```
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_patch


    Parameters:
    - Name: additional-instances-name
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config"

      Required/Optional: true

    Responses:
      "204":
        Description: container certificate-config updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: certificate-config
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/tls/cer

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_get


    Parameters:
    - Name: additional-instances-name
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server"

      Required/Optional: true

    Responses:
      "201":
        Description: container server created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: server
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_post


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container server created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: server
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_options


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_head


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_patch


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server"

    Required/Optional: true

  Responses:
    "204":
      Description: container server updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: server
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/tls/cer

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_get


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert"

      Required/Optional: true

    Responses:
      "201":
        Description: container ca-cert created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ca-cert
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_post


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container ca-cert created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
```

```
    security:
    - basicAuth: []
    x-codegen-request-body-name: ca-cert
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:
```

```
  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_head

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
```

```
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert"

      Required/Optional: true
```

```
  Responses:
    "204":
      Description: container ca-cert updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ca-cert
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/tls/c

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_secret_name_get


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert_secret-name"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_secret_name_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert_secret-name"

      Required/Optional: true

    Responses:
      "201":
```

```
      Description: leaf secret-name created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-name
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_secret_name_delete


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
```

```
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_secret_name_options

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_secret_name_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
```

```
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
```

data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_ca_cert_secret_name_patch

```
  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert_secret-name"
    Required/Optional: true

  Responses:
    "204":
      Description: leaf secret-name updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-name
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/tls/c

```
get:

  Tags:
  - data
  - get
  Operation ID:
```

data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_get

```
Parameters:
- Name: additional-instances-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_put
```

```
    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair"

      Required/Optional: true

    Responses:
      "201":
        Description: container key-pair created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key-pair
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_post


    Parameters:
```

```
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container key-pair created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key-pair
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_delete


    Parameters:
    - Name: additional-instances-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_options


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_head


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
```

```
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
```

```
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair"

      Required/Optional: true

    Responses:
      "204":
        Description: container key-pair updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
```

```
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key-pair
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/tls/c

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_secret_name_get


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
```

```
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair_secret-name"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
```

```
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_secret_name_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair_secret-name"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf secret-name created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-name
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_secret_name_delete


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_secret_name_options


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
```

```
    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_secret_name_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
```

```
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_server_key_pair_secret_name_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
```

```
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair_secret-name"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf secret-name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-name
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/tls/c

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_get


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_put


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
```

```
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer"

      Required/Optional: true

    Responses:
      "201":
        Description: container peer created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: peer
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_post


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
```

"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer-post"

```
      Required/Optional: true

    Responses:
      "201":
        Description: container peer created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: peer
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
```

```
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
```

```
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content: {}
security:
- basicAuth: []
```

```
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer"

      Required/Optional: true

    Responses:
      "204":
        Description: container peer updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: peer
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/tls/c

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_get


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
```

```
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
```

```
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert"

      Required/Optional: true

    Responses:
      "201":
        Description: container ca-cert created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ca-cert
```

```
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_post


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container ca-cert created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: ca-cert
  delete:
```

```
    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_delete

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_options

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
```

data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_head

```
Parameters:
- Name: additional-instances-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
```

```
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert"

      Required/Optional: true

    Responses:
      "204":
        Description: container ca-cert updated
        Content: {}
      "400":
```

```
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: ca-cert
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/tls/cer

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_secret_name_get


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
```

```
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: with-defaults
    In: query
    Description: controlling default values in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: report-all
      enum:
      - report-all
      - trim
      - explicit
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert_secret-name"

    "204":
```

```
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_secret_name_put


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert_secret-name"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf secret-name created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
```

```
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-name
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_secret_name_delete


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_secret_name_options


  Parameters:
  - Name: additional-instances-name
```

```
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_secret_name_head


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
```

```
      Type: integer
      Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_ca_cert_secret_name_patch


    Parameters:
    - Name: additional-instances-name
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert_secret-name"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf secret-name updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-name
```


/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/tls/cer


```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_get


    Parameters:
    - Name: additional-instances-name
      In: path
```

```
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_put


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
```

```
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair"

      Required/Optional: true

    Responses:
      "201":
        Description: container key-pair created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key-pair
  Method: Post:

    Tags:
    - data
    - post
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_post


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
```

```
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair-post"

      Required/Optional: true

    Responses:
      "201":
        Description: container key-pair created
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key-pair
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
```

```
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_options


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_head


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
```

```
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
```

```
      - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content: {}
  security:
  - basicAuth: []
patch:

  Tags:
  - data
  - patch
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_patch


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair"

    Required/Optional: true

  Responses:
    "204":
      Description: container key-pair updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
```

```
  security:
  - basicAuth: []
  x-codegen-request-body-name: key-pair
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/tls/cer

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_secret_name_get

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
```

```
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair_secret-name"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
```

```
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_secret_name_put


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair_secret-name"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf secret-name created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
```

```
      Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: secret-name
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_secret_name_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_secret_name_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
```

```
head:

  Tags:
  - data
  - head
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_secret_name_head


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
    In: query
    Description: optionally identify specific data nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: string
  - Name: filter
    In: query
    Description: xpath expression to filter data nodes in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_tls_certificate_config_peer_key_pair_secret_name_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair_secret-name"

      Required/Optional: true
```

```
  Responses:
    "204":
      Description: leaf secret-name updated
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: secret-name
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/label-c

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_label_config_get

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged

Responses:
  "200":
    Description: OK
    Content:
```

```
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_label-config"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_label_config_put

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_label-config"

      Required/Optional: true

    Responses:
      "201":
```

```
      Description: container label-config created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: label-config
Method: Post:

  Tags:
  - data
  - post
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_label_config_post

  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_label-config-post"

    Required/Optional: true

  Responses:
    "201":
      Description: container label-config created
      Content: {}
```

```
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: label-config
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_label_config_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_label_config_options
```

```
    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_label_config_head

    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
```

```
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_label_config_patch

    Parameters:
```

```
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_label-config"

      Required/Optional: true

    Responses:
      "204":
        Description: container label-config updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: label-config
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/labe

```
  get:

    Tags:
    - data
    - get
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_label_config_key_get


    Parameters:
```

```
- Name: additional-instances-name
  In: path
  Required/Optional: true
  Style: simple
  Explode: false
  Schema:
    Type: string
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
```

```
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content:
          application/yang-data+json:
            Schema:
              Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_label-config_key"

      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
  put:

    Tags:
    - data
    - put
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_label_config_key_put


    Parameters:
    - Name: additional-instances-name
      In: path
```

```
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_label-config_key"

      Required/Optional: true

    Responses:
      "201":
        Description: leaf key created or replaced
        Content: {}
      "204":
        Description: No Content
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: key
  delete:

    Tags:
    - data
    - delete
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_label_config_key_delete


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
```

```
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "204":
        Description: No Content
        Content: {}
    security:
    - basicAuth: []
  options:

    Tags:
    - data
    - options
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_label_config_key_options


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_label_config_key_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
```

```
    Format: string
- Name: content
  In: query
  Description: controlling descendant nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: config
    enum:
    - config
    - nonconfig
    - all
- Name: depth
  In: query
  Description: limit the depth of nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: integer
    Format: uint16
- Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
- Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
```

```
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_label_config_key_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_label-config_key"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf key updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
```

```
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: key
```

/data/cisco-smi-etcd:etcd/additional-instances={additional-instances-name}/label-

```
get:

  Tags:
  - data
  - get
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_label_config_value_get


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  - Name: content
    In: query
    Description: controlling descendant nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: string
      Format: enumeration
      Default: config
      enum:
      - config
      - nonconfig
      - all
  - Name: depth
    In: query
    Description: limit the depth of nodes in response
    Required/Optional: false
    Style: form
    Explode: true
    Schema:
      Type: integer
      Format: uint16
  - Name: fields
```

```
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

  Responses:
    "200":
      Description: OK
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_label-config_value"

    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
```

```
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
put:

  Tags:
  - data
  - put
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_label_config_value_put


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string
  Request Body:
    Content:
      application/yang-data+json:
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_label-config_value"

    Required/Optional: true

  Responses:
    "201":
      Description: leaf value created or replaced
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
```

```
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  security:
  - basicAuth: []
  x-codegen-request-body-name: value
delete:

  Tags:
  - data
  - delete
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_label_config_value_delete


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "204":
      Description: No Content
      Content: {}
  security:
  - basicAuth: []
options:

  Tags:
  - data
  - options
  Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_label_config_value_options


  Parameters:
  - Name: additional-instances-name
    In: path
    Required/Optional: true
    Style: simple
    Explode: false
    Schema:
      Type: string
      Format: string

  Responses:
    "200":
```

```
      Description: OK
      Content: {}
    security:
    - basicAuth: []
  head:

    Tags:
    - data
    - head
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_label_config_value_head


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    - Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    - Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: integer
        Format: uint16
    - Name: fields
      In: query
      Description: optionally identify specific data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
```

```
        Format: string
    - Name: filter
      In: query
      Description: xpath expression to filter data nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    - Name: with-defaults
      In: query
      Description: controlling default values in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: report-all
        enum:
        - report-all
        - trim
        - explicit
        - report-all-tagged

    Responses:
      "200":
        Description: OK
        Content: {}
    security:
    - basicAuth: []
  patch:

    Tags:
    - data
    - patch
    Operation ID:
data_cisco_smi_etcd_etcd_additional_instances_additional_instances_name_label_config_value_patch


    Parameters:
    - Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    Request Body:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_label-config_value"

      Required/Optional: true

    Responses:
      "204":
        Description: leaf value updated
        Content: {}
      "400":
        Description: Bad Request
        Content: {}
      "401":
        Description: Unauthorized
        Content: {}
      "404":
        Description: Not Found
        Content: {}
      "405":
        Description: Method Not Allowed
        Content: {}
      "409":
        Description: Conflict
        Content: {}
    security:
    - basicAuth: []
    x-codegen-request-body-name: value
```

Components

```
 schemas:
   data:
     Type: object
     Properties:
       ietf-restconf:data:
         Type: object
         Properties: {}
        Description: This resource represents the combined configuration and state data
resources that can be
          accessed by a client and cannot be created or deleted by the client. See RESTCONF
RFC 8040
           for further information.
         x-yang:
           Type: datastore
   data-post:
     Type: object
     Properties:
       cisco-smi-etcd:etcd:
         Reference: "#/components/schemas/datapost_ciscosmietcdetcd"
   data-put-patch:
```

```
  Type: object
  Properties:
    ietf-restconf:data:
      Reference: "#/components/schemas/dataputpatch_ietfrestconfdata"
data_cisco-smi-etcd_etcd:
  Type: object
  Properties:
    cisco-smi-etcd:etcd:
      Reference: "#/components/schemas/datapost_ciscosmietcdetcd"
data_cisco-smi-etcd_etcd-post:
  Type: object
  Properties:
    cisco-smi-etcd:node-affinity:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    cisco-smi-etcd:replicas:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    cisco-smi-etcd:go-max-procs:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    cisco-smi-etcd:volume:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    cisco-smi-etcd:pv-anti-affinity-mode:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: soft
      enum:
      - soft
      - hard
      x-yang:
        Type: leaf
    cisco-smi-etcd:pv-reclaim-policy:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: Retain
      enum:
```

```
    - Retain
    - Delete
    - Recycle
    x-yang:
      Type: leaf
  cisco-smi-etcd:backup:
    Reference: "#/components/schemas/datapost_ciscosmietcdetcd_backup"
  cisco-smi-etcd:enable-daily-defragmentation:
    Type: boolean
    Description: (leaf)
    x-yang:
      Type: leaf
  cisco-smi-etcd:daily-defragmentation-start-time:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
  cisco-smi-etcd:storage-label:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
  cisco-smi-etcd:external-ip:
    Type: array
    Description: (list)
    Items:
      Reference: "#/components/schemas/datapost_ciscosmietcdetcd_externalip"
    x-yang:
      Type: list
  cisco-smi-etcd:tls:
    Reference: "#/components/schemas/datapost_ciscosmietcdetcd_tls"
  cisco-smi-etcd:label-config:
    Reference: "#/components/schemas/datapost_ciscosmietcdetcd_labelconfig"
  cisco-smi-etcd:repository:
    Type: string
    Description: (leaf)
    Format: leafref
    x-yang:
      Type: leaf
  cisco-smi-etcd:monitoring:
    Reference: "#/components/schemas/datapost_ciscosmietcdetcd_monitoring"
  cisco-smi-etcd:network-policy:
    Reference: "#/components/schemas/datapost_ciscosmietcdetcd_networkpolicy"
  cisco-smi-etcd:additional-instances:
    Type: array
    Description: (list)
    Items:
     Reference: "#/components/schemas/datapost_ciscosmietcdetcd_additionalinstances"

    x-yang:
```

```
        Type: list
  data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name:

    Type: object
    Properties:
      cisco-smi-etcd:additional-instances:
        Type: array
        Description: (list)
        Items:
        Reference: "#/components/schemas/datapost_ciscosmietcdetcd_additionalinstances"

        x-yang:
          Type: list

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup:

    Type: object
    Properties:
      cisco-smi-etcd:backup:
        Reference: "#/components/schemas/datapost_ciscosmietcdetcd_backup"

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup-post:

    Type: object
    Properties:
      cisco-smi-etcd:disable:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
      cisco-smi-etcd:frequency:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
      cisco-smi-etcd:restore:
        Reference: "#/components/schemas/datapost_ciscosmietcdetcd_backup_restore"

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_disable:

    Type: object
    Properties:
      cisco-smi-etcd:disable:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_frequency:

    Type: object
    Properties:
```

```
        cisco-smi-etcd:frequency:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore:

      Type: object
      Properties:
        cisco-smi-etcd:restore:
          Reference: "#/components/schemas/datapost_ciscosmietcdetcd_backup_restore"

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore-post:

      Type: object
      Properties:
        cisco-smi-etcd:use-local-snapshot:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
        cisco-smi-etcd:wait-time:
          Type: integer
          Description: (leaf)
          Format: byte
          x-yang:
            Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_use-local-snapshot:

      Type: object
      Properties:
        cisco-smi-etcd:use-local-snapshot:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_wait-time:

      Type: object
      Properties:
        cisco-smi-etcd:wait-time:
          Type: integer
          Description: (leaf)
          Format: byte
          x-yang:
            Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_daily-defragmentation-start-time:
```

```
      Type: object
      Properties:
        cisco-smi-etcd:daily-defragmentation-start-time:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_enable-daily-defragmentation:

```
      Type: object
      Properties:
        cisco-smi-etcd:enable-daily-defragmentation:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port:

```
      Type: object
      Properties:
        cisco-smi-etcd:external-ip:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_ciscosmietcdetcd_externalip"
          x-yang:
            Type: list
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_ip:

```
      Type: object
      Properties:
        cisco-smi-etcd:ip:
          Type: string
          Description: (leaf)
          Format: union
          x-yang:
            Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_label:

```
      Type: object
      Properties:
        cisco-smi-etcd:label:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_port:

```
Type: object
Properties:
  cisco-smi-etcd:port:
    Type: integer
    Description: (leaf)
    Format: uint16
    x-yang:
      Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_go-max-procs:

```
Type: object
Properties:
  cisco-smi-etcd:go-max-procs:
    Type: integer
    Description: (leaf)
    Format: byte
    x-yang:
      Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_label-config:

```
Type: object
Properties:
  cisco-smi-etcd:label-config:
    Reference: "#/components/schemas/datapost_ciscosmietcdetcd_labelconfig"
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_label-config-post:

```
Type: object
Properties:
  cisco-smi-etcd:key:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
  cisco-smi-etcd:value:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_label-config_key:

```
Type: object
Properties:
  cisco-smi-etcd:key:
    Type: string
    Description: (leaf)
```

```
          Format: string
          x-yang:
            Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_label-config_value:

      Type: object
      Properties:
        cisco-smi-etcd:value:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_name:

      Type: object
      Properties:
        cisco-smi-etcd:name:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_node-affinity:

      Type: object
      Properties:
        cisco-smi-etcd:node-affinity:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_pv-anti-affinity-mode:

      Type: object
      Properties:
        cisco-smi-etcd:pv-anti-affinity-mode:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: soft
          enum:
          - soft
          - hard
          x-yang:
            Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_pv-reclaim-policy:
```

```
      Type: object
      Properties:
        cisco-smi-etcd:pv-reclaim-policy:
          Type: string
          Description: (leaf)
          Format: enumeration
          Default: Retain
          enum:
          - Retain
          - Delete
          - Recycle
          x-yang:
            Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_replicas:

      Type: object
      Properties:
        cisco-smi-etcd:replicas:
          Type: integer
          Description: (leaf)
          Format: byte
          x-yang:
            Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_storage-label:

      Type: object
      Properties:
        cisco-smi-etcd:storage-label:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls:

      Type: object
      Properties:
        cisco-smi-etcd:tls:
          Reference: "#/components/schemas/datapost_ciscosmietcdetcd_tls"

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls-post:

      Type: object
      Properties:
        cisco-smi-etcd:enable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
        cisco-smi-etcd:certificate-config:
         Reference: "#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig"
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config:

```
Type: object
Properties:
  cisco-smi-etcd:certificate-config:
   Reference: "#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig"
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config-post:

```
Type: object
Properties:
  cisco-smi-etcd:server:
    Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server"
   cisco-smi-etcd:peer:
    Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server"
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer:

```
Type: object
Properties:
  cisco-smi-etcd:peer:
    Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server"
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer-post:

```
Type: object
Properties:
  cisco-smi-etcd:ca-cert:
    Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert"
   cisco-smi-etcd:key-pair:
    Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert"
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert:

```
Type: object
Properties:
  cisco-smi-etcd:ca-cert:
    Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert"
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert-post:

```
Type: object
Properties:
  cisco-smi-etcd:secret-name:
    Type: string
    Description: (leaf)
```

```
          Format: leafref
          x-yang:
            Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert_secret-name:

```
      Type: object
      Properties:
        cisco-smi-etcd:secret-name:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair:

```
      Type: object
      Properties:
        cisco-smi-etcd:key-pair:
          Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert"
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair-post:

```
      Type: object
      Properties:
        cisco-smi-etcd:secret-name:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair_secret-name:

```
      Type: object
      Properties:
        cisco-smi-etcd:secret-name:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server:

```
      Type: object
      Properties:
        cisco-smi-etcd:server:
          Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server"
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server-post:

```
      Type: object
      Properties:
        cisco-smi-etcd:ca-cert:
          Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert"
        cisco-smi-etcd:key-pair:
          Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert"
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert:

```
      Type: object
      Properties:
        cisco-smi-etcd:ca-cert:
          Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert"
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert-post:

```
      Type: object
      Properties:
        cisco-smi-etcd:secret-name:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert_secret-name:

```
      Type: object
      Properties:
        cisco-smi-etcd:secret-name:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair:

```
      Type: object
      Properties:
        cisco-smi-etcd:key-pair:
          Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert"
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair-post:

```
      Type: object
      Properties:
        cisco-smi-etcd:secret-name:
          Type: string
```

```
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair_secret-name:

```
      Type: object
      Properties:
        cisco-smi-etcd:secret-name:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_enable:

```
      Type: object
      Properties:
        cisco-smi-etcd:enable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_volume:

```
      Type: object
      Properties:
        cisco-smi-etcd:volume:
          Type: integer
          Description: (leaf)
          Format: byte
          x-yang:
            Type: leaf
    data_cisco-smi-etcd_etcd_backup:
      Type: object
      Properties:
        cisco-smi-etcd:backup:
          Reference: "#/components/schemas/datapost_ciscosmietcdetcd_backup"
    data_cisco-smi-etcd_etcd_backup-post:
      Type: object
      Properties:
        cisco-smi-etcd:disable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
        cisco-smi-etcd:frequency:
          Type: integer
          Description: (leaf)
          Format: uint32
```

```
      x-yang:
        Type: leaf
    cisco-smi-etcd:restore:
      Reference: "#/components/schemas/datapost_ciscosmietcdetcd_backup_restore"
data_cisco-smi-etcd_etcd_backup_disable:
  Type: object
  Properties:
    cisco-smi-etcd:disable:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_backup_frequency:
  Type: object
  Properties:
    cisco-smi-etcd:frequency:
      Type: integer
      Description: (leaf)
      Format: uint32
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_backup_restore:
  Type: object
  Properties:
    cisco-smi-etcd:restore:
      Reference: "#/components/schemas/datapost_ciscosmietcdetcd_backup_restore"
data_cisco-smi-etcd_etcd_backup_restore-post:
  Type: object
  Properties:
    cisco-smi-etcd:use-local-snapshot:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
    cisco-smi-etcd:wait-time:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_backup_restore_use-local-snapshot:
  Type: object
  Properties:
    cisco-smi-etcd:use-local-snapshot:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_backup_restore_wait-time:
  Type: object
  Properties:
```

```
      cisco-smi-etcd:wait-time:
        Type: integer
        Description: (leaf)
        Format: byte
        x-yang:
          Type: leaf
    data_cisco-smi-etcd_etcd_daily-defragmentation-start-time:
      Type: object
      Properties:
        cisco-smi-etcd:daily-defragmentation-start-time:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_cisco-smi-etcd_etcd_enable-daily-defragmentation:
      Type: object
      Properties:
        cisco-smi-etcd:enable-daily-defragmentation:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
    data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port:
      Type: object
      Properties:
        cisco-smi-etcd:external-ip:
          Type: array
          Description: (list)
          Items:
            Reference: "#/components/schemas/datapost_ciscosmietcdetcd_externalip"
          x-yang:
            Type: list
  data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_ip:

      Type: object
      Properties:
        cisco-smi-etcd:ip:
          Type: string
          Description: (leaf)
          Format: union
          x-yang:
            Type: leaf

data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_label:

      Type: object
      Properties:
        cisco-smi-etcd:label:
          Type: string
          Description: (leaf)
          Format: string
```

```
          x-yang:
            Type: leaf
data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_port:
      Type: object
      Properties:
        cisco-smi-etcd:port:
          Type: integer
          Description: (leaf)
          Format: uint16
          x-yang:
            Type: leaf
    data_cisco-smi-etcd_etcd_go-max-procs:
      Type: object
      Properties:
        cisco-smi-etcd:go-max-procs:
          Type: integer
          Description: (leaf)
          Format: byte
          x-yang:
            Type: leaf
    data_cisco-smi-etcd_etcd_label-config:
      Type: object
      Properties:
        cisco-smi-etcd:label-config:
          Reference: "#/components/schemas/datapost_ciscosmietcdetcd_labelconfig"
    data_cisco-smi-etcd_etcd_label-config-post:
      Type: object
      Properties:
        cisco-smi-etcd:key:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        cisco-smi-etcd:value:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_cisco-smi-etcd_etcd_label-config_key:
      Type: object
      Properties:
        cisco-smi-etcd:key:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_cisco-smi-etcd_etcd_label-config_value:
```

```
      Type: object
      Properties:
        cisco-smi-etcd:value:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_cisco-smi-etcd_etcd_monitoring:
      Type: object
      Properties:
        cisco-smi-etcd:monitoring:
          Reference: "#/components/schemas/datapost_ciscosmietcdetcd_monitoring"
    data_cisco-smi-etcd_etcd_monitoring-post:
      Type: object
      Properties:
        cisco-smi-etcd:enabled:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
        cisco-smi-etcd:alerts:
          Reference: "#/components/schemas/datapost_ciscosmietcdetcd_monitoring_alerts"
    data_cisco-smi-etcd_etcd_monitoring_alerts:
      Type: object
      Properties:
        cisco-smi-etcd:alerts:
          Reference: "#/components/schemas/datapost_ciscosmietcdetcd_monitoring_alerts"
    data_cisco-smi-etcd_etcd_monitoring_alerts-post:
      Type: object
      Properties:
        cisco-smi-etcd:dbsize:
          Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_monitoring_alerts_dbsize"
    data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize:
      Type: object
      Properties:
        cisco-smi-etcd:dbsize:
          Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_monitoring_alerts_dbsize"
    data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize-post:
      Type: object
      Properties:
        cisco-smi-etcd:major-alert-threshold:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
        cisco-smi-etcd:critical-alert-threshold:
          Type: integer
          Description: (leaf)
```

```
        Format: uint32
        x-yang:
          Type: leaf
data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_critical-alert-threshold:
    Type: object
    Properties:
      cisco-smi-etcd:critical-alert-threshold:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
  data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_major-alert-threshold:
    Type: object
    Properties:
      cisco-smi-etcd:major-alert-threshold:
        Type: integer
        Description: (leaf)
        Format: uint32
        x-yang:
          Type: leaf
 data_cisco-smi-etcd_etcd_monitoring_enabled:
    Type: object
    Properties:
      cisco-smi-etcd:enabled:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
 data_cisco-smi-etcd_etcd_network-policy:
    Type: object
    Properties:
      cisco-smi-etcd:network-policy:
        Reference: "#/components/schemas/datapost_ciscosmietcdetcd_networkpolicy"
 data_cisco-smi-etcd_etcd_network-policy-post:
    Type: object
    Properties:
      cisco-smi-etcd:enable:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
  data_cisco-smi-etcd_etcd_network-policy_enable:
    Type: object
    Properties:
      cisco-smi-etcd:enable:
        Type: boolean
        Description: (leaf)
        x-yang:
```

```
      Type: leaf
data_cisco-smi-etcd_etcd_node-affinity:
  Type: object
  Properties:
    cisco-smi-etcd:node-affinity:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_pv-anti-affinity-mode:
  Type: object
  Properties:
    cisco-smi-etcd:pv-anti-affinity-mode:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: soft
      enum:
      - soft
      - hard
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_pv-reclaim-policy:
  Type: object
  Properties:
    cisco-smi-etcd:pv-reclaim-policy:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: Retain
      enum:
      - Retain
      - Delete
      - Recycle
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_replicas:
  Type: object
  Properties:
    cisco-smi-etcd:replicas:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
data_cisco-smi-etcd_etcd_repository:
  Type: object
  Properties:
    cisco-smi-etcd:repository:
      Type: string
      Description: (leaf)
```

```
        Format: leafref
        x-yang:
          Type: leaf
    data_cisco-smi-etcd_etcd_storage-label:
      Type: object
      Properties:
        cisco-smi-etcd:storage-label:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
    data_cisco-smi-etcd_etcd_tls:
      Type: object
      Properties:
        cisco-smi-etcd:tls:
          Reference: "#/components/schemas/datapost_ciscosmietcdetcd_tls"
    data_cisco-smi-etcd_etcd_tls-post:
      Type: object
      Properties:
        cisco-smi-etcd:enable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
        cisco-smi-etcd:certificate-config:
         Reference: "#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig"

    data_cisco-smi-etcd_etcd_tls_certificate-config:
      Type: object
      Properties:
        cisco-smi-etcd:certificate-config:
         Reference: "#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig"

    data_cisco-smi-etcd_etcd_tls_certificate-config-post:
      Type: object
      Properties:
        cisco-smi-etcd:server:
          Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server"
        cisco-smi-etcd:peer:
          Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server"
    data_cisco-smi-etcd_etcd_tls_certificate-config_peer:
      Type: object
      Properties:
        cisco-smi-etcd:peer:
          Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server"
    data_cisco-smi-etcd_etcd_tls_certificate-config_peer-post:
      Type: object
      Properties:
```

```
        cisco-smi-etcd:ca-cert:
          Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert"
        cisco-smi-etcd:key-pair:
          Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert"
    data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert:
      Type: object
      Properties:
        cisco-smi-etcd:ca-cert:
          Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert"
    data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert-post:
      Type: object
      Properties:
        cisco-smi-etcd:secret-name:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf

data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert_secret-name:

      Type: object
      Properties:
        cisco-smi-etcd:secret-name:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
    data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair:
      Type: object
      Properties:
        cisco-smi-etcd:key-pair:
          Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert"
    data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair-post:
      Type: object
      Properties:
        cisco-smi-etcd:secret-name:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf

data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair_secret-name:

      Type: object
      Properties:
        cisco-smi-etcd:secret-name:
```

```
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
    data_cisco-smi-etcd_etcd_tls_certificate-config_server:
      Type: object
      Properties:
        cisco-smi-etcd:server:
          Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server"
    data_cisco-smi-etcd_etcd_tls_certificate-config_server-post:
      Type: object
      Properties:
        cisco-smi-etcd:ca-cert:
          Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert"
        cisco-smi-etcd:key-pair:
          Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert"
    data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert:
      Type: object
      Properties:
        cisco-smi-etcd:ca-cert:
          Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert"
    data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert-post:
      Type: object
      Properties:
        cisco-smi-etcd:secret-name:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf

data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert_secret-name:

      Type: object
      Properties:
        cisco-smi-etcd:secret-name:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
    data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair:
      Type: object
      Properties:
        cisco-smi-etcd:key-pair:
          Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert"
    data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair-post:
```

```
      Type: object
      Properties:
        cisco-smi-etcd:secret-name:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf

data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair_secret-name:

      Type: object
      Properties:
        cisco-smi-etcd:secret-name:
          Type: string
          Description: (leaf)
          Format: leafref
          x-yang:
            Type: leaf
    data_cisco-smi-etcd_etcd_tls_enable:
      Type: object
      Properties:
        cisco-smi-etcd:enable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
    data_cisco-smi-etcd_etcd_volume:
      Type: object
      Properties:
        cisco-smi-etcd:volume:
          Type: integer
          Description: (leaf)
          Format: byte
          x-yang:
            Type: leaf
    operations:
      Type: object
      Properties:
        ietf-restconf:operations:
          Type: object
          Properties: {}
          Description: This resource is a container that provides access to the
data-model-specific RPC
           operations supported by the server. See RESTCONF RFC 8040 for further information.

          x-yang:
            Type: operations
    root:
      Type: object
      Properties:
        ietf-restconf:restconf:
```

```
        Reference: "#/components/schemas/root_ietfrestconfrestconf"
    yang-library-version:
      Type: object
      Properties:
        ietf-restconf:yang-library-version:
          Type: object
          Properties: {}
         Description: This leaf identifies the revision date of the 'ietf-yang-library'
YANG module that is
          implemented by this server. See RESTCONF RFC 8040 for further information.
          x-yang:
            Type: leaf
    datapost_ciscosmietcdetcd_backup_restore:
      Type: object
      Properties:
        use-local-snapshot:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
        wait-time:
          Type: integer
          Description: (leaf)
          Format: byte
          x-yang:
            Type: leaf
      Description: (non-presence)
    datapost_ciscosmietcdetcd_backup:
      Type: object
      Properties:
        disable:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
        frequency:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
        restore:
          Reference: "#/components/schemas/datapost_ciscosmietcdetcd_backup_restore"
      Description: (non-presence)
    datapost_ciscosmietcdetcd_externalip:
      Type: object
      Properties:
        ip:
          Type: string
          Description: (leaf)
          Format: union
          x-yang:
```

```
            Type: leaf
          port:
            Type: integer
            Description: (leaf)
            Format: uint16
            x-yang:
              Type: leaf
          label:
            Type: string
            Description: (leaf)
            Format: string
            x-yang:
              Type: leaf
      datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert:
        Type: object
        Properties:
          secret-name:
            Type: string
            Description: (leaf)
            Format: leafref
            x-yang:
              Type: leaf
        Description: (non-presence)
      datapost_ciscosmietcdetcd_tls_certificateconfig_server:
        Type: object
        Properties:
          ca-cert:
            Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert"
          key-pair:
            Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server_cacert"
        Description: (non-presence)
      datapost_ciscosmietcdetcd_tls_certificateconfig:
        Type: object
        Properties:
          server:
            Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server"
          peer:
            Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig_server"
        Description: (non-presence)
      datapost_ciscosmietcdetcd_tls:
        Type: object
        Properties:
          enable:
            Type: boolean
            Description: (leaf)
            x-yang:
              Type: leaf
          certificate-config:
```

```
          Reference: "#/components/schemas/datapost_ciscosmietcdetcd_tls_certificateconfig"

      Description: (non-presence)
    datapost_ciscosmietcdetcd_labelconfig:
      Type: object
      Properties:
        key:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
        value:
          Type: string
          Description: (leaf)
          Format: string
          x-yang:
            Type: leaf
      Description: (presence)
    datapost_ciscosmietcdetcd_monitoring_alerts_dbsize:
      Type: object
      Properties:
        major-alert-threshold:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
        critical-alert-threshold:
          Type: integer
          Description: (leaf)
          Format: uint32
          x-yang:
            Type: leaf
      Description: (non-presence)
    datapost_ciscosmietcdetcd_monitoring_alerts:
      Type: object
      Properties:
        dbsize:
          Reference:
"#/components/schemas/datapost_ciscosmietcdetcd_monitoring_alerts_dbsize"
      Description: (non-presence)
    datapost_ciscosmietcdetcd_monitoring:
      Type: object
      Properties:
        enabled:
          Type: boolean
          Description: (leaf)
          x-yang:
            Type: leaf
        alerts:
          Reference: "#/components/schemas/datapost_ciscosmietcdetcd_monitoring_alerts"
```

```
  Description: (non-presence)
datapost_ciscosmietcdetcd_networkpolicy:
  Type: object
  Properties:
    enable:
      Type: boolean
      Description: (leaf)
      x-yang:
        Type: leaf
  Description: (presence)
datapost_ciscosmietcdetcd_additionalinstances:
  Type: object
  Properties:
    Name:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    node-affinity:
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    replicas:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    go-max-procs:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    volume:
      Type: integer
      Description: (leaf)
      Format: byte
      x-yang:
        Type: leaf
    pv-anti-affinity-mode:
      Type: string
      Description: (leaf)
      Format: enumeration
      Default: soft
      enum:
      - soft
      - hard
      x-yang:
```

```
        Type: leaf
      pv-reclaim-policy:
        Type: string
        Description: (leaf)
        Format: enumeration
        Default: Retain
        enum:
        - Retain
        - Delete
        - Recycle
        x-yang:
          Type: leaf
      backup:
        Reference: "#/components/schemas/datapost_ciscosmietcdetcd_backup"
      enable-daily-defragmentation:
        Type: boolean
        Description: (leaf)
        x-yang:
          Type: leaf
      daily-defragmentation-start-time:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
      storage-label:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
      external-ip:
        Type: array
        Description: (list)
        Items:
          Reference: "#/components/schemas/datapost_ciscosmietcdetcd_externalip"
        x-yang:
          Type: list
      tls:
        Reference: "#/components/schemas/datapost_ciscosmietcdetcd_tls"
      label-config:
        Reference: "#/components/schemas/datapost_ciscosmietcdetcd_labelconfig"
  datapost_ciscosmietcdetcd:
    Type: object
    Properties:
      node-affinity:
        Type: string
        Description: (leaf)
        Format: string
        x-yang:
          Type: leaf
      replicas:
```

```
    Type: integer
    Description: (leaf)
    Format: byte
    x-yang:
      Type: leaf
  go-max-procs:
    Type: integer
    Description: (leaf)
    Format: byte
    x-yang:
      Type: leaf
  volume:
    Type: integer
    Description: (leaf)
    Format: byte
    x-yang:
      Type: leaf
  pv-anti-affinity-mode:
    Type: string
    Description: (leaf)
    Format: enumeration
    Default: soft
    enum:
    - soft
    - hard
    x-yang:
      Type: leaf
  pv-reclaim-policy:
    Type: string
    Description: (leaf)
    Format: enumeration
    Default: Retain
    enum:
    - Retain
    - Delete
    - Recycle
    x-yang:
      Type: leaf
  backup:
    Reference: "#/components/schemas/datapost_ciscosmietcdetcd_backup"
  enable-daily-defragmentation:
    Type: boolean
    Description: (leaf)
    x-yang:
      Type: leaf
  daily-defragmentation-start-time:
    Type: string
    Description: (leaf)
    Format: string
    x-yang:
      Type: leaf
  storage-label:
```

```
      Type: string
      Description: (leaf)
      Format: string
      x-yang:
        Type: leaf
    external-ip:
      Type: array
      Description: (list)
      Items:
        Reference: "#/components/schemas/datapost_ciscosmietcdetcd_externalip"
      x-yang:
        Type: list
    tls:
      Reference: "#/components/schemas/datapost_ciscosmietcdetcd_tls"
    label-config:
      Reference: "#/components/schemas/datapost_ciscosmietcdetcd_labelconfig"
    repository:
      Type: string
      Description: (leaf)
      Format: leafref
      x-yang:
        Type: leaf
    monitoring:
      Reference: "#/components/schemas/datapost_ciscosmietcdetcd_monitoring"
    network-policy:
      Reference: "#/components/schemas/datapost_ciscosmietcdetcd_networkpolicy"
    additional-instances:
      Type: array
      Description: (list)
      Items:
       Reference: "#/components/schemas/datapost_ciscosmietcdetcd_additionalinstances"

      x-yang:
        Type: list
  Description: (non-presence)
dataputpatch_ietfrestconfdata:
  Type: object
  Properties:
    cisco-smi-etcd:etcd:
      Reference: "#/components/schemas/datapost_ciscosmietcdetcd"
  Description:
root_ietfrestconfrestconf:
  Type: object
  Properties:
    data:
      Type: object
      Properties: {}
    operations:
      Type: object
      Properties: {}
    yang-library-version:
      Type: string
```

```
      Description: This is the RESTCONF root resource for the RESTCONF datastore and
operation resources. See
        RESTCONF RFC 8040 for further information.
  Responses:
    "200":
      Description: OK
      Content: {}
    "201":
      Description: Created
      Content: {}
    "204":
      Description: No Content
      Content: {}
    "400":
      Description: Bad Request
      Content: {}
    "401":
      Description: Unauthorized
      Content: {}
    "404":
      Description: Not Found
      Content: {}
    "405":
      Description: Method Not Allowed
      Content: {}
    "409":
      Description: Conflict
      Content: {}
  Parameters:
    Content:
      Name: content
      In: query
      Description: controlling descendant nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: enumeration
        Default: config
        enum:
        - config
        - nonconfig
        - all
    depth:
      Name: depth
      In: query
      Description: limit the depth of nodes in response
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
```

```
    Type: integer
    Format: uint16
fields:
  Name: fields
  In: query
  Description: optionally identify specific data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
filter:
  Name: filter
  In: query
  Description: xpath expression to filter data nodes in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: string
with-defaults:
  Name: with-defaults
  In: query
  Description: controlling default values in response
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: report-all
    enum:
    - report-all
    - trim
    - explicit
    - report-all-tagged
insert:
  Name: insert
  In: query
  Description: controlling the order when adding new list elements
  Required/Optional: false
  Style: form
  Explode: true
  Schema:
    Type: string
    Format: enumeration
    Default: first
    enum:
    - first
    - last
    - before
```

```
      - after
    point:
      Name: point
      In: query
      Description: used to specify the insertion point
      Required/Optional: false
      Style: form
      Explode: true
      Schema:
        Type: string
        Format: string
    additional-instances-name:
      Name: additional-instances-name
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: string
    external-ip-ip:
      Name: external-ip-ip
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: string
        Format: union
    external-ip-port:
      Name: external-ip-port
      In: path
      Required/Optional: true
      Style: simple
      Explode: false
      Schema:
        Type: integer
        Format: uint16
  requestBodies:
    data-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data-post"
      Required/Optional: true
    data-put-patch:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data-put-patch"
      Required/Optional: true
    data_cisco-smi-etcd_etcd:
```

```
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd"
      Required/Optional: true
    data_cisco-smi-etcd_etcd-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd-post"
      Required/Optional: true
   data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name"

      Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup"

      Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup-post"

      Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_disable:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_disable"

      Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_frequency:

      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_frequency"

      Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore"

      Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore-post"

      Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_use-local-snapshot:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_use-local-snapshot"

      Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_wait-time:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_backup_restore_wait-time"

      Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_daily-defragmentation-start-time:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_daily-defragmentation-start-time"

      Required/Optional: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_enable-daily-defragmentation:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_enable-daily-defragmentation"

Required/Optional: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port"

Required/Optional: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_ip:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_ip"

Required/Optional: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_label:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_label"

Required/Optional: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_port:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_external-ip_external-ip-ip_external-ip-port_port"

Required/Optional: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_go-max-procs:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
```

"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_go-max-procs"

Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_label-config:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_label-config"

Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_label-config-post:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_label-config-post"

Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_label-config_key:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_label-config_key"

Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_label-config_value:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_label-config_value"

Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_name:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_name"

Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_node-affinity:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_node-affinity"

      Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_pv-anti-affinity-mode:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_pv-anti-affinity-mode"

      Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_pv-reclaim-policy:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_pv-reclaim-policy"

      Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_replicas:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_replicas"

      Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_storage-label:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_storage-label"

      Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls"
```

```
      Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls-post"

      Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config"

      Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config-post"

      Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer"

      Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer-post:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer-post"

      Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert:

      Content:
        application/yang-data+json:
```

```
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert"

      Required/Optional: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert-post:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert-post"

      Required/Optional: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert_secret-name:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_ca-cert_secret-name"

      Required/Optional: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair"

      Required/Optional: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair-post:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair-post"

      Required/Optional: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair_secret-name:

```
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_peer_key-pair_secret-name"

      Required/Optional: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server"

Required/Optional: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server-post:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server-post"

Required/Optional: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert"

Required/Optional: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert-post:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert-post"

Required/Optional: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert_secret-name:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_ca-cert_secret-name"

Required/Optional: true
```

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair:

```
Content:
  application/yang-data+json:
    Schema:
      Reference:
```

"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair"

Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair-post:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair-post"

Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair_secret-name:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_certificate-config_server_key-pair_secret-name"

Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_enable:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_tls_enable"

Required/Optional: true

data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_volume:

Content:
application/yang-data+json:
Schema:
Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_additional-instances_additional-instances-name_volume"

Required/Optional: true
data_cisco-smi-etcd_etcd_backup:
Content:
application/yang-data+json:
Schema:
Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_backup"
Required/Optional: true
data_cisco-smi-etcd_etcd_backup-post:
Content:
application/yang-data+json:
Schema:
Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_backup-post"
Required/Optional: true

```
    data_cisco-smi-etcd_etcd_backup_disable:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_backup_disable"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_backup_frequency:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_backup_frequency"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_backup_restore:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_backup_restore-post:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore-post"

      Required/Optional: true
    data_cisco-smi-etcd_etcd_backup_restore_use-local-snapshot:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore_use-local-snapshot"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_backup_restore_wait-time:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_backup_restore_wait-time"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_daily-defragmentation-start-time:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_daily-defragmentation-start-time"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_enable-daily-defragmentation:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_enable-daily-defragmentation"
```

```
      Required/Optional: true
    data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port"

      Required/Optional: true
   data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_ip:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_ip"

      Required/Optional: true

data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_label:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_label"

      Required/Optional: true

data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_port:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_external-ip_external-ip-ip_external-ip-port_port"

      Required/Optional: true
    data_cisco-smi-etcd_etcd_go-max-procs:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_go-max-procs"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_label-config:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_label-config"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_label-config-post:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_label-config-post"

      Required/Optional: true
    data_cisco-smi-etcd_etcd_label-config_key:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_label-config_key"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_label-config_value:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_label-config_value"

      Required/Optional: true
    data_cisco-smi-etcd_etcd_monitoring:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_monitoring"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_monitoring-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_monitoring-post"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_monitoring_alerts:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts"

      Required/Optional: true
    data_cisco-smi-etcd_etcd_monitoring_alerts-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts-post"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize-post:
      Content:
        application/yang-data+json:
```

```
        Schema:
          Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize-post"
      Required/Optional: true

data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_critical-alert-threshold:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_critical-alert-threshold"

      Required/Optional: true
    data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_major-alert-threshold:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_alerts_dbsize_major-alert-threshold"

      Required/Optional: true
    data_cisco-smi-etcd_etcd_monitoring_enabled:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_monitoring_enabled"

      Required/Optional: true
    data_cisco-smi-etcd_etcd_network-policy:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_network-policy"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_network-policy-post:
      Content:
        application/yang-data+json:
          Schema:
           Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_network-policy-post"

      Required/Optional: true
    data_cisco-smi-etcd_etcd_network-policy_enable:
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_network-policy_enable"

      Required/Optional: true
    data_cisco-smi-etcd_etcd_node-affinity:
      Content:
        application/yang-data+json:
          Schema:
```

```
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_node-affinity"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_pv-anti-affinity-mode:
      Content:
        application/yang-data+json:
          Schema:
          Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_pv-anti-affinity-mode"

      Required/Optional: true
    data_cisco-smi-etcd_etcd_pv-reclaim-policy:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_pv-reclaim-policy"

      Required/Optional: true
    data_cisco-smi-etcd_etcd_replicas:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_replicas"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_repository:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_repository"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_storage-label:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_storage-label"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_tls:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_tls"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_tls-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_tls-post"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_tls_certificate-config:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config"
```

```
      Required/Optional: true
    data_cisco-smi-etcd_etcd_tls_certificate-config-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config-post"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_tls_certificate-config_peer:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_tls_certificate-config_peer-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer-post"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert-post"
      Required/Optional: true

data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert_secret-name:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_ca-cert_secret-name"

      Required/Optional: true
    data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair"
      Required/Optional: true
```

```
    data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair-post"
      Required/Optional: true

data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair_secret-name:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_peer_key-pair_secret-name"

      Required/Optional: true
    data_cisco-smi-etcd_etcd_tls_certificate-config_server:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_tls_certificate-config_server-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server-post"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert-post"
      Required/Optional: true

data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert_secret-name:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_ca-cert_secret-name"
```

```
      Required/Optional: true
    data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair-post:
      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair-post"

      Required/Optional: true

data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair_secret-name:

      Content:
        application/yang-data+json:
          Schema:
            Reference:
"#/components/schemas/data_cisco-smi-etcd_etcd_tls_certificate-config_server_key-pair_secret-name"

      Required/Optional: true
    data_cisco-smi-etcd_etcd_tls_enable:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_tls_enable"
      Required/Optional: true
    data_cisco-smi-etcd_etcd_volume:
      Content:
        application/yang-data+json:
          Schema:
            Reference: "#/components/schemas/data_cisco-smi-etcd_etcd_volume"
      Required/Optional: true
  securitySchemes:
    basicAuth:
      Type: http
      scheme: basic
```